


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : H01M 10/50	A1	(11) International Publication Number: WO 94/14206 (43) International Publication Date: 23 June 1994 (23.06.94)
(21) International Application Number: PCT/US93/11707 (22) International Filing Date: 8 December 1993 (08.12.93) (30) Priority Data: 988,670 10 December 1992 (10.12.92) US (71) Applicant: COMSAT CORPORATION [US/US]; 6560 Rock Spring Drive, Bethesda, MD 20817 (US). (72) Inventors: EARL, Martin, W.; 14001 Burning Bush Lane, Silver Spring, MD 21701 (US). KELLY, William, H.; 13 Honey Brook Circle, Gaithersburg, MD 20878 (US). JIANG, Wein-Shen; 13517 Teakwood Lane, Germantown, MD 20874 (US). KESSLER, Ronald, R.; 2691 Walston Road, Mt. Airy, MD 21771 (US). BRANTNER, Fred, W.; 5647 Singletree Drive, Frederick, MD 21701 (US). (74) Agents: SEAS, Robert, J. et al.; Sughrue, Mion, Zinn, MacPeak & Seas, 2100 Pennsylvania Avenue, N.W., Washington, DC 20037-3202 (US).		(81) Designated States: CA, JP, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>
(54) Title: NI-H ₂ BATTERY HAVING IMPROVED THERMAL PROPERTIES 		

(57) Abstract

A common pressure vessel type nickel-hydrogen storage battery having an outer pressure vessel (5) contains a stack of compartments. Each compartment includes at least one battery cell (80), a heat transfer member (21) and a cell spacer (22) for maintaining a relatively constant distance between adjacent compartments. Each heat transfer member includes a fin portion (21a), which is thermal contact with a battery cell, and a flange portion (21b) which extends longitudinally from the fin portion and is in tight thermal contact with the inner wall of the pressure vessel. The heat transfer member serves to transfer heat generated by the cell radially outward to the pressure vessel, which is capable of dissipating the heat into the surrounding atmosphere.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

NI-H₂ BATTERY HAVING IMPROVED THERMAL PROPERTIESBACKGROUND OF THE INVENTION

The present invention relates to a common pressure vessel type Ni-H₂ storage battery, which may be used, for example, in powering satellites. More particularly, the invention relates to a common pressure vessel type Ni-H₂ storage battery having improved heat transfer properties between individual battery cells of the cell stack and the walls of the pressure vessel of the battery.

The earliest Ni-H₂ batteries for satellite application employed individual pressure vessels for each cell in the battery. However, to gain improvements in specific energy and energy density and to reduce the total weight and volume of the battery, the recent trend has been to incorporate multiple cells in a stack arrangement within a single pressure vessel. This type of Ni-H₂ battery is termed in the art a common pressure vessel type battery. Examples of common pressure vessel type Ni-H₂ batteries are described in the following publications: M. Earl et al., "Design and Development of an Aerospace CPV Ni/H₂ Battery", 24th Intersociety Energy Conversion Engineering Conference, Washington, D.C., August 1989, Proc., Vol. 3, pp. 1395-1400; J. Dunlop et al., "Making Space Nickel/Hydrogen Batteries Light and Less Expensive", AIAA/DARPA Meeting on Lightweight Satellite Systems, Monterey, California, August 1987, NTIS No. N88-13530; G. Holleck, "Common Pressure Vessel Nickel-Hydrogen Battery Design", 15th Intersociety Energy Conversion Engineering Conference, Seattle, Washington, August 1980, Proc.,

Vol. 3, pp. 1908-1911; and E. Adler et al. "Design Considerations Related to Nickel Hydrogen Common Pressure Vessel Battery Modules", 21st Intersociety Energy conversion Engineering Conference, San Diego, California, August 1986, Proc., Vol. 3, pp. 1554-1559.

In Ni-H₂ batteries, considerable waste heat is generated during both charge and discharge portion of cycles. In the conventional common pressure vessel type Ni-H₂ battery, the individual cells were generally disposed inside of an insulating carrier. The thermal path between the heat generating portions of the cells and the wall of the pressure vessel was lengthwise through the battery cell stack components and then through the hydrogen gas of the battery to the adjacent wall of the pressure vessel. As a result, the thermal resistance between the individual cells and the pressure vessel was high, resulting in undesirable large temperature increases within the battery.

SUMMARY OF THE INVENTION

It is therefore an object of the invention to provide a common pressure vessel type Ni-H₂ battery in which the thermal resistance between the individual cells and the pressure vessel of the battery is greatly reduced, thereby effecting rapid heat transfer between the cells and the pressure vessel and thus allowing the specific capacity of the battery to be increased.

In accordance with the above and other objects, the invention provides a battery including a pressure vessel, and a plurality of compartments disposed in side-by-side relation, each of the plurality of compartments including a heat transfer member

having a fin portion and a flange portion extending longitudinally from the fin portion, the flange being in thermal contact with an inner wall of the pressure vessel, and a plurality of battery cells, at least one battery cell being
5 disposed in each of the compartments and in thermal contact with adjacent fin portions of the heat transfer members.

In further accordance with the above and other objects, the present invention provides a metal oxide hydrogen battery including an outer pressure vessel, a plurality of cell modules
10 disposed in side-by-side relation in the vessel, a heat transfer member disposed between adjacent cells modules, each heat transfer member including a generally flat fin disposed between adjacent cell modules and a peripheral flange extending from the periphery of the fin and disposed in engagement with the inner
15 surface of the pressure vessel, the width of the cell modules being greater than the longitudinal length of the flanges whereby the outer end of each flange is disposed out of contact with adjacent heat transfer members, and connecting means for connecting the cell modules and heat transfer members in side-by-
20 side relations as a stack.

Even further, the present invention provides a metal oxide-hydrogen battery composed of an outer pressure vessel including a generally cylindrical metal shell, a plurality of heat transfer members each including a generally flat fin disposed between each
25 pair of adjacent cell modules and having a peripheral flange disposed in engagement with the metal shell, the width of the cell modules being greater than the length of the flanges of the heat transfer members whereby each flange is disposed out of

contact with the adjacent heat transfer member, clamping means for clamping the cell modules and the heat transfer members together in side-by-side relations as a stack, and means for permitting the flange to follow radial expansion of the pressure vessel.

Still, even further, the present invention provides a metal oxide-hydrogen battery including an outer pressure vessel, a group of cell modules disposed in side-by-side relations in the pressure vessel, a plurality of heat transfer members, each heat transfer member including a generally flat fin disposed between adjacent cell modules and each heat transfer member including a peripheral flange extending generally longitudinally from the peripheral edge of each fin and disposed in engagement with the inner surface of the pressure vessel, each flange being provided with a plurality of longitudinally extending circumferentially spaced slits, the width of each cell modules being greater than the length of each flange whereby the outer end of each flange is disposed out of contact with the adjacent heat transfer member, and clamping means for clamping the cell modules and heat transfer member in side-by-side relation as a stack.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is partially cut-away cross-sectional view of a common pressure vessel type Ni-H₂ battery constructed in accordance with a preferred embodiment of the present invention;

5 Fig. 2 illustrates a heat transfer member according to a first embodiment of the invention;

Fig. 3 illustrates the heat transfer member of Fig. 2 making contact with the pressure vessel of Fig. 1;

10 Fig. 4 illustrates a stack of compartments with an internal cell spacer;

Fig. 5 illustrates a stack of compartments with an outer end cell spacer;

Fig. 6 illustrates two battery cells disposed within a heat transfer member of Fig. 2;

15 Fig. 7 shows an enlarged fragmentary longitudinal section of the battery of Fig. 1 showing a group of compartments including a heat transfer member, battery cell, cell spacer, and end cell spacer;

20 Fig. 8 is an enlarged cross-sectional view showing the relationship between the vessel wall, heat transfer member, individual battery cells, cell spacer, and spacer;

Fig. 9 illustrates a cross-sectional view illustrating the mode of interconnecting adjacent battery cells;

25 Fig. 10 illustrates a heat transfer member according to a second embodiment of the present invention; and

Fig. 11 illustrates a heat transfer member according to a third embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Preferred embodiments of the invention will now be described with reference to the attached drawings.

Referring to Fig. 1, a pressure vessel 5 of a preferred
5 embodiment of a Ni-H₂ battery 1 of the invention is composed of
a central cylindrical portion 4 capped at respective ends by end
portions 2 and 3. Within the pressure vessel 5, there is a stack
6 of individual cylindrical compartments 20 disposed in side-by-
side relation. The outer wall of the stack 6 of the cylindrical
10 compartments 6 conforms to the shape of the central cylindrical
portion 4 such that the outer wall of the stack is in thermal
contact throughout its surface with the inner wall or surface of
the central cylindrical portion 4 of the pressure vessel 5. As
will be described below in more detail, each compartment 20 is
15 composed of at least one battery cell 80, a heat transfer member
21, and a cell spacer 22 or an end plate 24 as shown in Fig. 5,
for example.

Figs. 2 and 3 illustrate the heat transfer member 21, which
serves to transfer heat radially outward from the center of the
20 battery to the inner wall of the pressure vessel 5 and thence
into the surrounding atmosphere. The heat transfer member 21 is
made of an aluminum or any other material having a high
coefficient of thermal conductivity. According to a first
embodiment of the invention, the heat transfer member 21 includes
25 a circular-shaped fin or body 21a having a cut-out 21d and a
plurality of integral flanges 21b, which are separated from one
another by a plurality of slits 21c. The flanges 21b extend
longitudinally from the body 21a so as to form an "L-shape" from
a cross-sectional view of the heat transfer member 21. The

flange 21b also forms the outside wall of the compartments 20, which is in thermal contact with the inner wall of the vessel 5.

As illustrated in Fig. 3, the flange 21b forms an obtuse angle θ with the fin or body 21a of the heat transfer member 21 so as to insure a firm thermal contact between the flange and the inner wall of the vessel when inserted into the pressure vessel 5. When the heat transfer members 21 are inserted into the vessel, the flanges 21b are deflected or bent inward and due to the flexibility of the flanges a radial force or biasing action will be exerted so as to maintain the segments in tight engagement with the inner wall of the vessel. This further ensures that as heat is extracted from within the vessel, the heat is sufficiently transferred to the vessel and subsequently to the surrounding atmosphere.

Referring to Figs. 8 and 9 and as described in commonly assigned patent application serial no. 07/711,602, which is herein incorporated by reference, each battery cell 80 is of generally semi-cylindrical or cylindrical shape and contains a repeating pattern of a gas diffusion screen 82, negative electrode 83, separator 84, and positive electrode 85. The arrangement and selection of the materials for these components is conventional and well within the skill of those familiar with this art. Each cell 80 is encased, for example, by a plastic bag 81, which electrically insulates the above-mentioned components from the fins 21 and spacers 22. The outer sides of the bag 81, however, are in intimate thermal contact with the fins 21a of the heat transfer member 21 on both sides of the cell so as to

provide good thermal conduction between the cell 80, over its entire surface, and the heat transfer member 21.

Fig. 6 illustrates the manner in which two generally semi-cylindrical battery cells 80 are situated within a heat transfer member 21, while Figs. 7 and 8 illustrate the encasing 81 of a battery cells 80 being in intimate thermal contact with adjacent fins 21a of adjacent heat transfer members 21. Figs. 7 and 8 also illustrate that the length of the flange 21b can vary relative to the width of a battery cell 80 and compartment 20. That is, the maximum length of a flange 21b will allow the end of the flange to come in contact with the adjacent heat transfer member 21. Preferably though, the length of the flange is less than the width of a compartment 20 or battery cell 80 so that the distance between adjacent heat transfer members 21 is determined by the spacers 22 as described in more detail below. However, the length of the flange must be of a certain length to provide a sufficient amount of surface contact between the flange and the inner wall of the vessel 5 so that a sufficient amount of heat can be withdrawn.

Again referring to Figs. 7 and 8, the heat transfer member 21 of a first compartment is spaced from the heat transfer member 21 of an adjacent compartment by the cell spacer 22, which is generally of a ring-shape, as illustrated best in Fig. 4. First and second sides of the spacer come into contact with the fin or body 21a of adjacent heat transfer members 21. The cell spacers 22 are made of a rigid material (e.g., aluminum) such that the heat transfer members 21 are held stationary and at a relatively constant distance from one another. The spacers 22 also provide

for the compartments 20 to remain at a relatively constant compression. As shown in Figs. 5 and 8, the outer compartment 20 is spaced by an end cell spacer 24, which is composed of a ring-shaped portion 24a, similar to a cell spacer 22, and an
5 integral circular body portion 24b with a cut-out 24c.

Referring now to Fig. 9, each cell 80 has positive electrode terminals 86 and negative electrode terminals 87 which are respectively connected to the positive and negative electrodes 85 and 83 of the cell 80. The battery cells 80 of a compartment
10 20 can be connected to the battery cells of an adjacent compartment in series or in parallel to obtain the desired voltage output. The connection of adjacent terminals can be through the use of insulated interconnecting rods 36 and 46 which pass through center holes of the terminals 86 and 87,
15 respectively, and through the cut-outs 21d of each of the heat transfer members and the cut-out 24c of the end cell spacer 24. The connection between battery cells and from the battery cells to external positive and negative electrodes 9, 10 can be similar to that which is described in the aforementioned patent
20 application.

Referring back to Fig. 1, first and second weld rings 7 secure the outer end portions 2 and 3, to the center cylindrical portion 4 and also hold the stack of compartments in place so as to prevent any shifting of the stack 6 of the compartments 20 in
25 the axial direction. A wave spring 8 is disposed between the end cell spacer 24 of the stack and the weld ring 7. The wave spring 8 provides a preloading force on the stack of compartments in the

axial direction thereof as well as absorbing any vibration or shock.

Figs. 4 and 5 illustrate exploded views of a stack 6. Specifically, Fig. 4 illustrates two battery cells 80 placed within a heat transfer member 21. A cell spacer 22 abuts the fin portion 21a of the heat transfer member and around the outer periphery of the two battery cells 80. Fig. 5 illustrates the outer end compartment in which the ring-shaped portion 24b of the end cell spacer 24 is placed against the fin 21a of the heat transfer member 21 and around the outer periphery of the two battery cells 80. The circular body 24a of the end cell spacer 24 rests in contact with the bag 81 of the cell 80. The cut-out 24c allows the rods 36, 46 to pass therethrough.

With the above-discussed battery structure, heat generated within each battery cell 80 is rapidly transferred through the heat transfer members 21 from the fin body 21a to the flanges 21b, and thence, due to the tight contact between the inner wall of the pressure vessel and the flange, to the pressure vessel 5. As a result, the thermal conductivity between the battery cells 80 and the pressure vessel 5 is greatly improved compared with a conventional common pressure vessel type Ni-H₂ battery.

Several alternatives and variations of the above-described battery are possible. For example, as shown in Fig. 10, the heat transfer members 21 can be semi-circular in shape as well as the spacers. In this case, two stacks of compartments, each compartment being generally semi-cylindrical in shape, are assembled together to form a cylindrical shape. That is, each of the stack of compartments has an outer wall having the shape

of a cylinder sliced lengthwise along a plane slightly offset from the longitudinal axis of the cylinder so that a small gap is provided between the two cell stacks. The two stacks of compartments once assembled are inserted into the vessel 5.

5 Provisions for maintaining the gap between the two stacks are well known in the art, and a suitable example is illustrated and described in the aforementioned patent application.

Other embodiments include a heat transfer member of a "T-shape" such as that shown in Fig. 11. Here, the heat transfer
10 member includes a fin body 21a and a plurality of flanges 21b, 21b' extending longitudinally from both sides of the fin 21a. The flanges 21b, 21b' are separated by a plurality of slits 21c, 21c'.

There has thus been shown and described a novel Ni-H₂
15 battery having improved thermal properties which fulfills all the objects and advantages sought therefor. Many changes, modifications, variations and other uses and applications of the subject invention will, however, become apparent to those skilled in the art after considering the specification and the
20 accompanying drawings which disclose preferred embodiments thereof. All such changes, modifications, variations and other uses and applications which do not depart from the spirit and scope of the invention are deemed to be covered by the invention which is limited only by the claims which follow.

CLAIMS

What is claimed is:

1. A battery comprising:

a pressure vessel; and

a plurality of compartments disposed in side-by-side relation, each of said compartments comprising:

5 a heat transfer member having a fin portion and a flange portion extending longitudinally from said fin portion, said flange being in thermal contact with an inner wall of said pressure vessel; and

10 a plurality of battery cells, at least one battery cell being disposed in each of said compartments and in thermal contact with adjacent fin portions of said heat transfer members.

2. A battery as defined in Claim 1, wherein each of said compartments further comprises a cell spacer for maintaining adjacent heat transfer members of adjacent compartments a predetermined distance from one another.

3. A battery as defined in Claim 2, wherein said cell spacer is ring-shaped.

4. A battery as defined in Claim 2, further comprising first and second weld rings and a wave spring, and wherein a first outer one of said compartments comprises an end cell spacer, said first weld ring being in contact with a heat transfer member of a second outer compartment, and said wave spring being in contact with said end cell spacer and said first

5

weld ring so as to provide a preloading force on said stack of compartments.

5. A battery as defined in Claim 1, wherein the length of said flange portion of said heat transfer member is less than the width of said battery cell.

6. A battery as defined in Claim 1, wherein the length of said flange portion of said heat transfer member is the same as the width of said battery cell.

7. A battery as defined in Claim 1, wherein said flange portion forms an obtuse angle with said fin portion.

8. In a metal oxide hydrogen battery, an outer pressure vessel, a plurality of cell modules disposed in side-by-side relation in said vessel, a heat transfer member disposed between adjacent cells modules, each heat transfer member including a
5 generally flat fin disposed between adjacent cell modules and a peripheral flange extending from the periphery of said fin and disposed in engagement with the inner surface of said pressure vessel, the width of said cell modules being greater than the longitudinal length of said flanges whereby the outer end of each
10 flange is disposed out of contact with adjacent heat transfer members, and connecting means for connecting the cell modules and heat transfer members in side-by-side relation as a stack.

9. The battery of Claim 8, wherein said pressure vessel includes a generally cylindrical metal liner, said flanges being disposed in contact with said metal liner.

10. The battery of Claim 9, wherein said heat transfer members are composed of a material having a high coefficient of thermal conductivity.

11. The battery of Claim 8, wherein each cell modules is semi-cylindrical in configuration and said fins are generally semi-circular in configuration.

12. The battery of Claim 8, wherein each cell modules in generally cylindrical in configuration and each fin is generally circular in configuration.

13. The battery of Claim 8, wherein each flange is provided with a plurality of generally longitudinal circumferentially spaced Slits.

14. The battery of Claim 8, wherein each flange is flexible and in the unrestrained state before assembly of the stack with said pressure vessel extends at an obtuse angle with respect to the corresponding fin.

15. The battery of Claim 8, wherein each flange is constructed and arranged to exert an outward radial force against said pressure vessel.

16. In a metal oxide-hydrogen battery, an outer pressure vessel including a generally cylindrical metal shell, a plurality of heat transfer members each including a generally flat fin disposed between each pair of adjacent cell modules and having a peripheral flange disposed in engagement with said metal shell, the width of said cell modules being greater than the length of the flanges of said heat transfer members whereby each flange is disposed out of contact with the adjacent heat transfer member, clamping means for clamping the cell modules and said heat transfer members together in side-by-side relations as a stack, and means for permitting said flange to follow radial expansion of said pressure vessel.



17. The battery of Claim 16, wherein each cell module is generally semi-cylindrical in shape and each fin is semi-circular in shape.

18. The battery of Claim 16, wherein each cell module is generally cylindrical in shape and each fin is circular in shape.

19. In a metal oxide-hydrogen battery, an outer pressure vessel, a group of cell modules disposed in side-by-side relations in said pressure vessel, a plurality of heat transfer members, each heat transfer member including a generally flat fin disposed between adjacent cell modules and each heat transfer member including a peripheral flange extending generally longitudinally from the peripheral edge of each fin and disposed in engagement with the inner surface of said pressure vessel,

each flange being provided with a plurality of longitudinally
10 extending circumferentially spaced slits, the width of each cell
modules being greater than the length of each flange whereby the
outer end of each flange is disposed out of contact with the
adjacent heat transfer member, and clamping means for clamping
the cell modules and heat transfer member in side-by-side
15 relation as a stack.

20. The battery of Claim 19, wherein each flange in the
unrestrained state prior to assembly of said stack with said
pressure vessel extends at an obtuse angle with respect to the
corresponding fin, said flange exerting an outward radial force
5 against pressure vessel after assembly of said stack with said
vessel.








FIG. 5





FIG. 7






FIG.8




FIG. 10




FIG. 11




FIG. 9

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US93/11707

A. CLASSIFICATION OF SUBJECT MATTER

IPC(5) :H01M 10/50

US CL :429/120

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 429/120, 101, 59, 164, 176

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US, A, 5,071,652 (Jones et al.) 10 December 1991, figures 1-5, col. 2, lines 13-29, column 3, line 66 through column 5, line 3.	1, 5-20
A	US, A, 5,168,017 (Jones et al.) 01 December 1992, col. 3, lines 54-68, fig. 3.	1-20
A	US, A, 4,909,807 (Klink et al.) 20 March 1990, col. 3, lines 48-67.	1-20
A	US, A, 4,327,158 (Holleck) 27 April 1982, col. 2, lines 13-29.	1-20

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	*T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
*A document defining the general state of the art which is not considered to be part of particular relevance	*X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
*E earlier document published on or after the international filing date	*Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
*L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*& document member of the same patent family
*O document referring to an oral disclosure, use, exhibition or other means	
*P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search
18 January 1994

Date of mailing of the international search report
17 FEB 1994

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Authorized officer

Stephen J. Kalafut

Facsimile No. NOT APPLICABLE

Telephone No. (703) 308-0433