

US012257871B2

(12) **United States Patent**
Ericksen et al.

(10) **Patent No.:** **US 12,257,871 B2**
(45) **Date of Patent:** ***Mar. 25, 2025**

(54) **METHOD AND APPARATUS FOR AN ADJUSTABLE DAMPER**

(58) **Field of Classification Search**
CPC .. B60G 17/016; B60G 17/015; B60G 17/018; B60G 17/08; B60G 2202/24;
(Continued)

(71) Applicant: **Fox Factory, Inc.**, Duluth, GA (US)

(72) Inventors: **Everet Owen Ericksen**, Santa Cruz, CA (US); **Christopher Paul Cox**, Capitola, CA (US); **Philip Tsiaras**, Dacula, GA (US); **Mark Larson**, Santa Cruz, CA (US); **Mario Galasso**, Sandy Hook, CT (US); **Matt McLellan**, Fremont, CA (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

435,995 A 9/1890 Dunlop
1,078,060 A 11/1913 Newman
(Continued)

(73) Assignee: **Fox Factory, Inc.**, Duluth, GA (US)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

CN 101468587 A 7/2009
DE 1555311 A1 8/1970
(Continued)

This patent is subject to a terminal disclaimer.

OTHER PUBLICATIONS

European Search Report for European Application No. 19193903.2, 6 pages, Oct. 19, 2021 (Oct. 19, 2021).

(21) Appl. No.: **17/083,837**

(Continued)

(22) Filed: **Oct. 29, 2020**

Primary Examiner — Yuen Wong

(65) **Prior Publication Data**

US 2021/0039468 A1 Feb. 11, 2021

(57) **ABSTRACT**

Related U.S. Application Data


(60) Continuation of application No. 16/051,302, filed on Jul. 31, 2018, now Pat. No. 10,821,795, which is a (Continued)

A method for controlling vehicle motion is described. The method includes accessing a set of control signals including a measured vehicle speed value associated with a movement of a vehicle. A control signal associated with user-induced input is also accessed. The method compares the measured vehicle speed value with a predetermined vehicle speed threshold value to achieve a speed value threshold approach status, and then compares the set of values to achieve a user-induced input threshold value approach status. The method monitors a state of a valve within the vehicle suspension damper, and determines a control mode for the vehicle suspension damper. The method also regulates damping forces within the vehicle suspension damper.

(51) **Int. Cl.**
B60G 17/016 (2006.01)
B60G 17/015 (2006.01)
(Continued)

7 Claims, 41 Drawing Sheets

(52) **U.S. Cl.**
CPC **B60G 17/016** (2013.01); **B60G 17/015** (2013.01); **B60G 17/018** (2013.01);
(Continued)



Related U.S. Application Data

division of application No. 15/275,078, filed on Sep. 23, 2016, now Pat. No. 10,040,329, which is a division of application No. 14/466,831, filed on Aug. 22, 2014, now Pat. No. 9,452,654, which is a continuation-in-part of application No. 14/251,446, filed on Apr. 11, 2014, now Pat. No. 10,047,817, which is a continuation-in-part of application No. 13/934,067, filed on Jul. 2, 2013, now Pat. No. 10,060,499, which is a continuation-in-part of application No. 13/843,704, filed on Mar. 15, 2013, now Pat. No. 9,033,122, said application No. 14/251,446 is a continuation-in-part of application No. 13/485,401, filed on May 31, 2012, now abandoned, and a continuation-in-part of application No. 12/684,072, filed on Jan. 7, 2010, now abandoned, and a continuation-in-part of application No. 13/189,216, filed on Jul. 22, 2011, now Pat. No. 9,239,090, which is a continuation-in-part of application No. 13/010,697, filed on Jan. 20, 2011, now Pat. No. 8,857,580, and a continuation-in-part of application No. 13/175,244, filed on Jul. 1, 2011, now Pat. No. 8,627,932.

(60) Provisional application No. 61/709,041, filed on Oct. 2, 2012, provisional application No. 61/667,327, filed on Jul. 2, 2012, provisional application No. 61/645,465, filed on May 10, 2012, provisional application No. 61/491,858, filed on May 31, 2011, provisional application No. 61/361,127, filed on Jul. 2, 2010, provisional application No. 61/296,826, filed on Jan. 20, 2010, provisional application No. 61/143,152, filed on Jan. 7, 2009.

(51) **Int. Cl.**
B60G 17/018 (2006.01)
B60G 17/08 (2006.01)
F16F 9/512 (2006.01)

(52) **U.S. Cl.**
 CPC **B60G 17/08** (2013.01); **F16F 9/512** (2013.01); **F16F 9/5126** (2013.01); **B60G 2202/24** (2013.01); **B60G 2206/41** (2013.01); **B60G 2400/104** (2013.01); **B60G 2400/202** (2013.01); **B60G 2400/204** (2013.01); **B60G 2400/208** (2013.01); **B60G 2400/252** (2013.01); **B60G 2400/33** (2013.01); **B60G 2400/34** (2013.01); **B60G 2400/39** (2013.01); **B60G 2400/41** (2013.01); **B60G 2400/44** (2013.01); **B60G 2400/5182** (2013.01); **B60G 2400/62** (2013.01); **B60G 2400/63** (2013.01); **B60G 2500/10** (2013.01); **B60G 2500/102** (2013.01); **B60G 2500/11** (2013.01); **B60G 2600/02** (2013.01); **B60G 2600/187** (2013.01); **B60G 2600/20** (2013.01); **B60G 2600/26** (2013.01); **B60G 2600/70** (2013.01); **B60G 2800/012** (2013.01); **B60G 2800/014** (2013.01); **B60G 2800/91** (2013.01)

(58) **Field of Classification Search**
 CPC B60G 2206/41; B60G 2400/104; B60G 2400/202; B60G 2400/204; B60G 2400/208; B60G 2400/252; B60G 2400/33; B60G 2400/34; B60G 2400/39; B60G 2400/41; B60G 2400/44; B60G 2400/5182; B60G 2400/62; B60G 2400/63; B60G 2500/10; B60G 2500/102; B60G 2500/11; B60G 2600/02; B60G

2600/187; B60G 2600/20; B60G 2600/26; B60G 2600/70; B60G 2800/012; B60G 2800/014; B60G 2800/91; F16F 9/512; F16F 9/5126; F16F 15/002; F16F 3/04; F16F 9/061; F16F 9/065; F16F 9/182; F16F 9/185; F16F 9/19; F16F 9/464; F16F 9/466; F16F 2230/08

See application file for complete search history.

(56)

References Cited

U.S. PATENT DOCUMENTS

1,307,502	A	6/1919	Martin
1,313,763	A	8/1919	Thomas
1,409,849	A	3/1922	Haerberlein
1,468,652	A	9/1923	Storey et al.
1,492,731	A	5/1924	Kerr
1,560,477	A	11/1925	Kessler
1,571,788	A	2/1926	Bramlette, Jr.
1,575,973	A	3/1926	Coleman
1,655,786	A	1/1928	Guerritore et al.
1,923,011	A	8/1933	Moulton
1,948,600	A	2/1934	Templeton
1,970,239	A	8/1934	Klaas
2,018,312	A	10/1935	Moulton
2,098,119	A	11/1937	White
2,115,072	A	4/1938	Hunt et al.
2,122,407	A	7/1938	Chisholm
2,186,266	A	1/1940	Henry
2,259,437	A	10/1941	Dean
2,354,340	A	7/1944	Utter
2,363,867	A	11/1944	Isely
2,492,331	A	12/1949	Spring
2,518,553	A	8/1950	Kieber
2,540,525	A	2/1951	Howarth et al.
2,559,633	A	7/1951	Maurice et al.
2,588,520	A	3/1952	Halgren et al.
2,697,600	A	12/1954	Gregoire
2,705,119	A	3/1955	Ingwer
2,725,076	A	11/1955	Hansen et al.
2,729,308	A	1/1956	Koski et al.
2,778,378	A	1/1957	Presnell
2,784,962	A	3/1957	Sherburne
2,809,722	A	10/1957	Smith
2,838,140	A	6/1958	Rasmusson et al.
2,846,028	A	8/1958	Gunther
2,853,974	A	9/1958	Hewitt
2,879,971	A	3/1959	Demay
2,883,181	A	4/1959	Hogan et al.
2,897,613	A	8/1959	Davidson et al.
2,924,304	A	2/1960	Patriquin
2,941,629	A	6/1960	Etienne et al.
2,967,065	A	1/1961	Schwendner
2,973,744	A	3/1961	Hennells
2,991,804	A	7/1961	Merkle
3,003,595	A	10/1961	Patriquin et al.
3,056,598	A	10/1962	Ransom et al.
3,071,394	A	1/1963	Miller
3,073,586	A	1/1963	Hartel et al.
3,074,709	A	1/1963	Ellis et al.
3,085,530	A	4/1963	Williamson
3,087,583	A	4/1963	Bruns
3,107,753	A	10/1963	Georgette et al.
3,127,958	A	4/1964	Szostak
3,175,645	A	3/1965	Schafer et al.
3,202,413	A	8/1965	Colmerauer
3,206,153	A	9/1965	Burke
3,207,270	A	9/1965	Ellis
3,216,535	A	11/1965	Schultze
3,238,850	A	3/1966	Desmarchelier
3,284,076	A	11/1966	Gibson
3,286,797	A	11/1966	Leibfritz et al.
3,405,625	A	10/1968	Carlson et al.
3,419,849	A	12/1968	Anderson et al.
3,420,493	A	1/1969	Kraft et al.
3,447,644	A	6/1969	Duckett
3,494,606	A	2/1970	Hanchen

(56)

References Cited

U.S. PATENT DOCUMENTS

3,528,700	A	9/1970	Janu et al.	4,655,440	A	4/1987	Eckert
3,537,722	A	11/1970	Moulton	4,657,280	A	4/1987	Ohmori et al.
3,556,137	A	1/1971	Billeter et al.	4,659,104	A	4/1987	Tanaka et al.
3,559,027	A	1/1971	Arsem	4,660,689	A	4/1987	Hayashi et al.
3,560,033	A	2/1971	Barkus	4,662,616	A	5/1987	Hennells
3,575,442	A	4/1971	Elliott et al.	4,673,194	A	6/1987	Sugasawa
3,584,331	A	6/1971	D'Hooge	4,696,489	A	9/1987	Fujishiro et al.
3,603,575	A	9/1971	Arlasky et al.	4,709,779	A	12/1987	Takehara
3,605,960	A	9/1971	Singer	4,723,753	A	2/1988	Torimoto et al.
3,618,972	A	11/1971	Buhl	4,729,459	A	3/1988	Inagaki et al.
3,621,950	A	11/1971	Lutz	4,732,244	A	3/1988	Verkuylen
3,650,033	A	3/1972	Behne et al.	4,743,000	A	5/1988	Karnopp
3,701,544	A	10/1972	Stankovich	4,744,444	A	5/1988	Gillingham
3,714,953	A	2/1973	Solvang	4,750,735	A	6/1988	Furgerson et al.
3,750,856	A	8/1973	Kenworthy et al.	4,765,648	A	8/1988	Mander et al.
3,784,228	A	1/1974	Hoffmann et al.	4,773,671	A	9/1988	Inagaki
3,791,408	A	2/1974	Saitou et al.	4,786,034	A	11/1988	Heess et al.
3,792,644	A	2/1974	Ferguson et al.	4,802,561	A	2/1989	Knecht et al.
3,795,291	A	3/1974	Naito et al.	4,806,082	A	2/1989	Schenk
3,830,482	A	8/1974	Norris	4,815,575	A	3/1989	Murty et al.
3,842,753	A	10/1974	Ross et al.	4,821,852	A	4/1989	Yokoya
3,861,487	A	1/1975	Gill	4,826,207	A	5/1989	Yoshioka et al.
3,903,613	A	9/1975	Bisberg	4,830,395	A	5/1989	Foley
3,941,402	A	3/1976	Yankowski et al.	4,836,578	A	6/1989	Soltis
3,981,204	A	9/1976	Starbard et al.	4,838,306	A	6/1989	Horn et al.
3,981,479	A	9/1976	Foster et al.	4,838,394	A	6/1989	Lemme et al.
3,986,118	A	10/1976	Madigan	4,838,527	A	6/1989	Holley
3,995,883	A	12/1976	Glaze	4,846,317	A	7/1989	Hudgens
4,022,113	A	5/1977	Blatt et al.	4,858,733	A	8/1989	Noguchi et al.
4,032,829	A	6/1977	Schenavar et al.	4,919,166	A	4/1990	Sims et al.
4,036,335	A	7/1977	Thompson et al.	4,936,423	A	6/1990	Karnopp
4,045,008	A	8/1977	Bauer	4,936,424	A	6/1990	Costa
4,072,087	A	2/1978	Mueller et al.	4,938,228	A	7/1990	Righter
4,103,881	A	8/1978	Simich	4,949,262	A	8/1990	Buma et al.
4,106,522	A	8/1978	Manesse	4,949,989	A	8/1990	Kakizaki et al.
4,114,735	A	9/1978	Kato	4,958,706	A	9/1990	Richardson et al.
4,121,610	A	10/1978	Harms et al.	4,972,928	A	11/1990	Sirven
4,131,657	A	12/1978	Ball et al.	4,975,849	A	12/1990	Ema et al.
4,139,186	A	2/1979	Postema et al.	4,984,819	A	1/1991	Kakizaki et al.
4,153,237	A	5/1979	Supalla	4,986,393	A	1/1991	Preukschat et al.
4,159,106	A	6/1979	Nyman et al.	5,027,303	A	6/1991	Witte
4,166,612	A	9/1979	Freitag et al.	5,031,455	A	7/1991	Cline
4,174,098	A	11/1979	Baker et al.	5,036,934	A	8/1991	Nishina et al.
4,183,509	A	1/1980	Nishikawa et al.	5,040,381	A	8/1991	Hazen
4,236,613	A	12/1980	Van Der Lely	5,044,614	A	9/1991	Rau
4,287,812	A	9/1981	Izumi	5,060,910	A	10/1991	Iwata et al.
4,291,850	A	9/1981	Sharples	5,060,959	A	10/1991	Davis et al.
4,305,566	A	12/1981	Grawunde	5,072,812	A	12/1991	Imaizumi
4,311,302	A	1/1982	Heyer et al.	5,074,624	A	12/1991	Stauble et al.
4,333,668	A	6/1982	Hendrickson et al.	5,076,404	A	12/1991	Gustafsson
4,334,711	A	6/1982	Mazur et al.	5,080,392	A	1/1992	Bazergui
4,337,850	A	7/1982	Shimokura et al.	5,094,325	A	3/1992	Smith
4,348,016	A	9/1982	Milly	5,105,918	A	4/1992	Hagiwara et al.
4,351,515	A	9/1982	Yoshida	5,113,980	A	5/1992	Furrer et al.
4,366,969	A	1/1983	Benya et al.	5,127,634	A	7/1992	Le Gourvellec
4,387,781	A	6/1983	Ezell et al.	5,152,547	A	10/1992	Davis
4,437,548	A	3/1984	Ashiba et al.	5,161,653	A	11/1992	Hare
4,465,299	A	8/1984	Stone et al.	5,161,817	A	11/1992	Daum et al.
4,474,363	A	10/1984	Numazawa et al.	5,163,742	A	11/1992	Topfer et al.
4,491,207	A	1/1985	Boonchanta et al.	5,178,242	A	1/1993	Nakamura et al.
4,500,827	A	2/1985	Merritt et al.	5,186,481	A	2/1993	Turner
4,502,673	A	3/1985	Clark et al.	5,203,584	A	4/1993	Butsuen et al.
4,529,180	A	7/1985	Hill	5,207,774	A	5/1993	Wolfe et al.
4,546,959	A	10/1985	Tanno	5,230,364	A	7/1993	Leng et al.
4,548,233	A	10/1985	Wolfges	5,231,583	A	7/1993	Lizell
4,550,899	A	11/1985	Holley	5,236,169	A	8/1993	Johnsen et al.
4,570,851	A	2/1986	Cirillo et al.	5,246,247	A	9/1993	Runkel
4,572,317	A	2/1986	Isono et al.	5,248,014	A	9/1993	Ashiba
4,588,053	A	5/1986	Foster	5,259,487	A	11/1993	Petek et al.
4,616,810	A	10/1986	Richardson et al.	5,263,559	A	11/1993	Mettner
4,620,619	A	11/1986	Emura et al.	5,265,902	A	11/1993	Lewis
4,624,346	A	11/1986	Katz et al.	5,275,086	A	1/1994	Stallings, Jr.
4,630,818	A	12/1986	Saarinen	5,277,283	A	1/1994	Yamaoka et al.
4,634,142	A	1/1987	Woods et al.	5,283,733	A	2/1994	Colley
4,647,068	A	3/1987	Asami et al.	5,284,330	A	2/1994	Carlson et al.
				5,293,971	A	3/1994	Kanari
				5,295,074	A	3/1994	Williams
				5,295,563	A	3/1994	Bennett
				5,297,045	A	3/1994	Williams et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

5,301,776	A	4/1994	Beck	5,996,745	A	12/1999	Jones et al.
5,307,907	A	5/1994	Nakamura et al.	5,996,746	A	12/1999	Turner et al.
5,310,203	A	5/1994	Chen	5,999,868	A	12/1999	Beno et al.
5,311,709	A	5/1994	Kobori et al.	6,000,702	A	12/1999	Streiter
5,318,066	A	6/1994	Burgorf et al.	6,013,007	A	1/2000	Root et al.
5,328,004	A	7/1994	Fannin et al.	6,017,047	A	1/2000	Hoose
5,346,242	A	9/1994	Karnopp	6,029,958	A	2/2000	Larsson et al.
5,347,186	A	9/1994	Konotchick et al.	6,035,979	A	3/2000	Forster
5,348,112	A	9/1994	Vaillancourt	6,050,583	A	4/2000	Bohn
5,372,223	A	12/1994	DeKock et al.	6,058,340	A	5/2000	Uchiyama et al.
5,372,224	A	12/1994	Samonil et al.	6,067,490	A	5/2000	Ichimaru et al.
5,381,952	A	1/1995	Duprez	6,073,536	A	6/2000	Campbell
5,390,949	A	2/1995	Naganathan et al.	6,073,700	A	6/2000	Tsuji et al.
5,392,885	A	2/1995	Patzenhauer et al.	6,073,736	A	6/2000	Franklin
5,392,886	A	2/1995	Drummond	6,079,526	A	6/2000	Nezu et al.
5,396,973	A	3/1995	Schwemmer et al.	6,092,011	A	7/2000	Hiramoto et al.
5,398,787	A	3/1995	Woessner et al.	6,092,816	A	7/2000	Sekine et al.
5,413,196	A	5/1995	Forster	6,105,988	A	8/2000	Turner et al.
5,445,366	A	8/1995	Shih et al.	6,112,868	A	9/2000	Graham et al.
5,467,280	A	11/1995	Kimura	6,120,049	A	9/2000	Gonzalez et al.
5,475,593	A	12/1995	Townend	6,131,709	A	10/2000	Jolly et al.
5,480,011	A	1/1996	Nagai et al.	6,135,434	A	10/2000	Marking
5,485,417	A	1/1996	Wolf et al.	6,141,969	A	11/2000	Launchbury et al.
5,487,006	A	1/1996	Kakizaki et al.	6,151,930	A	11/2000	Carlson
5,503,258	A	4/1996	Clarke et al.	6,152,856	A	11/2000	Studor et al.
5,517,898	A	5/1996	Kim et al.	6,157,103	A	12/2000	Ohta et al.
5,542,150	A	8/1996	Tu	6,179,098	B1	1/2001	Hayakawa et al.
5,551,674	A	9/1996	Johnsen	6,182,687	B1	2/2001	Förster et al.
5,553,836	A	9/1996	Ericson	6,196,555	B1	3/2001	Gaibler
5,558,190	A	9/1996	Chang	6,199,669	B1	3/2001	Huang et al.
5,566,794	A	10/1996	Wiard	6,203,026	B1	3/2001	Jones
5,578,877	A	11/1996	Tiemann	6,213,263	B1	4/2001	De Frenne
5,586,637	A	12/1996	Aidlin et al.	6,215,217	B1	4/2001	Kurosawa et al.
5,588,510	A	12/1996	Wilke	6,217,049	B1	4/2001	Becker
5,592,401	A	1/1997	Kramer	6,219,045	B1	4/2001	Leahy et al.
5,597,180	A	1/1997	Ganzel et al.	6,244,398	B1	6/2001	Girvin et al.
5,598,337	A	1/1997	Butsuen et al.	6,254,067	B1	7/2001	Yih
5,601,164	A	2/1997	Ohsaki et al.	6,279,702	B1	8/2001	Koh
5,611,413	A	3/1997	Feigel	6,290,034	B1	9/2001	Ichimaru
5,634,563	A	6/1997	Peng	6,293,530	B1	9/2001	Delorenzis et al.
5,651,433	A	7/1997	Wirth et al.	6,296,092	B1	10/2001	Marking et al.
5,657,840	A	8/1997	Lizell	6,311,962	B1	11/2001	Marking
5,687,575	A	11/1997	Keville et al.	6,318,525	B1	11/2001	Vignocchi et al.
5,697,477	A	12/1997	Hiramoto et al.	6,321,888	B1	11/2001	Reybrouck et al.
5,699,885	A	12/1997	Forster	6,322,468	B1	11/2001	Wing et al.
5,722,645	A	3/1998	Reitter	6,336,648	B1	1/2002	Bohn
5,735,372	A	4/1998	Hamilton et al.	6,343,807	B1	2/2002	Rathbun
5,803,443	A	9/1998	Chang	6,352,144	B1	3/2002	Brooks et al.
5,806,159	A	9/1998	Ohnishi et al.	6,359,837	B1	3/2002	Tsukamoto et al.
5,810,128	A	9/1998	Eriksson et al.	6,360,857	B1	3/2002	Fox et al.
5,810,384	A	9/1998	Iwasaki et al.	6,371,262	B1	4/2002	Katou et al.
5,813,456	A	9/1998	Milner et al.	6,371,267	B1	4/2002	Kao et al.
5,813,731	A	9/1998	Newman et al.	6,378,816	B1	4/2002	Pfister
5,816,281	A	10/1998	Mixon	6,378,885	B1	4/2002	Ellsworth et al.
5,818,132	A	10/1998	Konotchick et al.	6,382,370	B1	5/2002	Girvin
5,826,935	A	10/1998	DeFreitas et al.	6,389,341	B1	5/2002	Davis
5,828,843	A	10/1998	Samuel et al.	6,390,747	B1	5/2002	Commins
5,829,733	A	11/1998	Becker	6,394,238	B1	5/2002	Rogala
5,833,036	A	11/1998	Gillespie	6,401,883	B1	6/2002	Nyce et al.
5,850,352	A	12/1998	Moezzi et al.	6,412,788	B1	7/2002	Ichimaru
5,850,896	A	12/1998	Tanaka	6,415,895	B2	7/2002	Marking et al.
5,853,071	A	12/1998	Robinson	6,418,360	B1	7/2002	Spivey et al.
5,872,418	A	2/1999	Wischnewskiy	6,427,812	B2	8/2002	Crawley et al.
5,884,921	A	3/1999	Katsuda et al.	6,434,460	B1	8/2002	Uchino et al.
5,937,975	A	8/1999	Forster	6,446,771	B1	9/2002	Sintorn et al.
5,947,238	A	9/1999	Jolly et al.	6,458,060	B1	10/2002	Watterson et al.
5,952,823	A	9/1999	Sprecher et al.	6,460,567	B1	10/2002	Hansen et al.
5,954,318	A	9/1999	Kluhsman	6,467,593	B1	10/2002	Corradini et al.
5,956,951	A	9/1999	O'Callaghan	6,474,454	B2	11/2002	Matsumoto et al.
5,957,252	A	9/1999	Berthold	6,474,753	B1	11/2002	Rieth et al.
5,971,116	A	10/1999	Franklin	6,501,554	B1	12/2002	Hackney et al.
5,987,368	A	11/1999	Kamimae et al.	6,502,837	B1	1/2003	Hamilton et al.
5,988,330	A	11/1999	Morris	6,510,929	B1	1/2003	Gordaninejad et al.
5,988,655	A	11/1999	Sakai et al.	6,520,297	B1	2/2003	Lumpkin et al.
5,992,450	A	11/1999	Parker et al.	6,527,093	B2	3/2003	Oliver et al.
				6,592,136	B2	7/2003	Becker et al.
				6,604,751	B2	8/2003	Fox
				6,609,686	B2	8/2003	Malizia
				6,619,615	B1	9/2003	Mayr et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,623,389	B1	9/2003	Campagnolo	7,558,574	B2	7/2009	Feher et al.
6,648,109	B2	11/2003	Farr et al.	7,566,290	B2	7/2009	Lee et al.
6,651,788	B1	11/2003	Wohlfarth	7,569,952	B1	8/2009	Bono et al.
6,659,240	B2	12/2003	Dernebo	7,581,743	B2	9/2009	Graney et al.
6,659,241	B2	12/2003	Sendrea	7,591,352	B2	9/2009	Hanawa
6,672,687	B2	1/2004	Nishio	7,600,616	B2	10/2009	Anderfaas et al.
6,701,234	B1	3/2004	Vogelsang et al.	7,628,259	B2	12/2009	Norgaard et al.
6,722,678	B2	4/2004	McAndrews	7,628,414	B2	12/2009	Dobson et al.
6,732,033	B2	5/2004	LaPlante et al.	7,631,882	B2	12/2009	Hirao et al.
6,755,113	B2	6/2004	Shih	7,654,369	B2	2/2010	Murray et al.
6,782,980	B2	8/2004	Nakadate	7,673,936	B2	3/2010	Hsu et al.
6,817,454	B2	11/2004	Nezu et al.	7,684,911	B2	3/2010	Seifert et al.
6,837,827	B1	1/2005	Lee et al.	7,694,785	B2	4/2010	Nakadate
6,840,257	B2	1/2005	Dario et al.	7,694,987	B2	4/2010	McAndrews
6,853,955	B1	2/2005	Burrell et al.	7,699,753	B2	4/2010	Daikeler et al.
6,857,625	B2	2/2005	Löser et al.	7,703,585	B2	4/2010	Fox
6,863,291	B2	3/2005	Miyoshi	7,722,056	B2	5/2010	Inoue et al.
6,883,650	B2	4/2005	Van Wonderen et al.	7,722,069	B2	5/2010	Shirai
6,902,513	B1	6/2005	McClure et al.	7,726,042	B2	6/2010	Meschan
6,905,203	B2	6/2005	Kremers et al.	7,730,906	B2	6/2010	Kleinert et al.
6,920,951	B2	7/2005	Song et al.	7,736,272	B2	6/2010	Martens
6,921,351	B1	7/2005	Hickman et al.	7,744,097	B2	6/2010	Noguchi
6,923,853	B2	8/2005	Kremers et al.	7,764,990	B2	7/2010	Martikka et al.
6,935,157	B2	8/2005	Miller	7,766,794	B2	8/2010	Oliver et al.
6,952,060	B2	10/2005	Goldner et al.	7,770,701	B1	8/2010	Davis
6,959,906	B2	11/2005	Hoenig et al.	7,775,128	B2	8/2010	Roessingh et al.
6,959,921	B2	11/2005	Rose	7,779,974	B2	8/2010	Timoney et al.
6,966,412	B2	11/2005	Braswell et al.	7,795,711	B2	9/2010	Sauciuc et al.
6,978,871	B2	12/2005	Holiviers	7,828,125	B2	11/2010	Sekiya et al.
6,978,872	B2	12/2005	Turner	7,828,126	B2	11/2010	Lun
6,991,076	B2	1/2006	McAndrews	7,837,213	B2	11/2010	Colegrove et al.
7,025,367	B2	4/2006	McKinnon et al.	7,840,346	B2	11/2010	Huhtala et al.
7,076,351	B2	7/2006	Hamilton et al.	7,841,258	B2	11/2010	Komatsu et al.
7,128,192	B2	10/2006	Fox	7,845,602	B1	12/2010	Young et al.
7,128,693	B2	10/2006	Brown et al.	7,857,325	B2	12/2010	Copsey et al.
7,135,794	B2	11/2006	Kühnel	7,872,764	B2	1/2011	Higgins-Luthman et al.
7,147,207	B2	12/2006	Jordan et al.	7,874,567	B2	1/2011	Ichida et al.
7,163,222	B2	1/2007	Becker et al.	7,901,292	B1	3/2011	Uhlir et al.
7,166,062	B1	1/2007	Watterson et al.	7,909,348	B2	3/2011	Klieber et al.
7,166,064	B2	1/2007	Ashby et al.	7,927,253	B2	4/2011	DiBenedetto et al.
7,204,466	B2	4/2007	Hsieh	7,931,132	B2	4/2011	Braun
7,208,845	B2	4/2007	Schaefer et al.	7,931,563	B2	4/2011	Shaw et al.
7,217,224	B2	5/2007	Thomas	7,946,163	B2	5/2011	Gartner
7,234,574	B2	6/2007	Matsunaga et al.	7,975,814	B2	7/2011	Soederdahl
7,234,575	B2	6/2007	Anderfaas et al.	8,016,349	B2	9/2011	Mouri et al.
7,234,680	B2	6/2007	Hull et al.	8,021,270	B2	9/2011	D'Eredita
7,243,763	B2	7/2007	Carlson	8,042,427	B2	10/2011	Kawakami et al.
7,255,210	B2	8/2007	Larsson et al.	8,056,392	B2	11/2011	Ryan et al.
7,270,221	B2	9/2007	McAndrews	8,069,964	B2	12/2011	Deferme et al.
7,270,222	B1	9/2007	Aymar et al.	8,087,676	B2	1/2012	McIntyre
7,287,760	B1	10/2007	Quick et al.	8,091,910	B2	1/2012	Hara et al.
7,289,138	B2	10/2007	Footo et al.	8,104,591	B2	1/2012	Barefoot et al.
7,292,867	B2	11/2007	Werner et al.	8,121,757	B2	2/2012	Extance et al.
7,293,764	B2	11/2007	Fang	8,121,785	B2	2/2012	Swisher et al.
7,299,112	B2	11/2007	LaPlante et al.	8,127,900	B2	3/2012	Inoue
7,302,961	B2	12/2007	Martin et al.	8,136,877	B2	3/2012	Walsh et al.
7,306,206	B2	12/2007	Turner	8,141,438	B2	3/2012	Roessingh et al.
7,316,406	B2	1/2008	Kimura et al.	8,151,952	B2	4/2012	Lenz et al.
7,320,387	B2	1/2008	Sendrea	8,191,964	B2	6/2012	Hsu et al.
7,325,660	B2	2/2008	Norgaard et al.	8,201,476	B2	6/2012	Tsumiyama
7,363,129	B1	4/2008	Barnicle et al.	8,210,106	B2	7/2012	Tai et al.
7,374,028	B2	5/2008	Fox	8,210,330	B2	7/2012	Vandewal
7,397,355	B2	7/2008	Tracy	8,246,065	B1	8/2012	Kodama et al.
7,413,062	B2	8/2008	Vandewal	8,256,587	B2	9/2012	Bakke et al.
7,413,063	B1	8/2008	Davis	8,256,732	B1	9/2012	Young et al.
7,415,336	B1	8/2008	Burch et al.	8,262,058	B2	9/2012	Kot
7,422,092	B2	9/2008	Hitchcock et al.	8,262,062	B2	9/2012	Kamo et al.
7,441,638	B2	10/2008	Hanawa	8,262,100	B2	9/2012	Thomas
7,469,910	B2	12/2008	Münster et al.	8,265,825	B2	9/2012	Kajino et al.
7,484,603	B2	2/2009	Fox	8,285,447	B2	10/2012	Bennett et al.
7,490,705	B2	2/2009	Fox	8,286,982	B2	10/2012	Plantet et al.
7,512,520	B2	3/2009	Sack et al.	8,291,889	B2	10/2012	Shafer et al.
7,513,490	B2	4/2009	Robertson	8,292,274	B2	10/2012	Adoline et al.
7,523,617	B2	4/2009	Colpitts et al.	8,307,965	B2	11/2012	Föster et al.
7,558,313	B2	7/2009	Feher	8,308,124	B2	11/2012	Hsu
				8,317,261	B2	11/2012	Walsh et al.
				8,321,177	B2	11/2012	Sack et al.
				8,322,497	B2	12/2012	Marjoram et al.
				8,328,454	B2	12/2012	McAndrews et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,336,683 B2	12/2012	McAndrews et al.	9,765,842 B2	9/2017	Noguchi	
8,364,389 B2	1/2013	Dorogusker et al.	9,784,333 B2	10/2017	Marking	
8,393,446 B2	3/2013	Haugen	9,810,282 B2	11/2017	Roessle et al.	
8,413,773 B2	4/2013	Anderfaas et al.	9,975,598 B2	5/2018	Bender et al.	
8,423,244 B2	4/2013	Proemm et al.	10,012,282 B2	7/2018	Kimura et al.	
8,430,770 B2	4/2013	Dugan et al.	10,029,172 B2	7/2018	Galasso et al.	
8,458,080 B2	6/2013	Shirai	10,036,443 B2	7/2018	Galasso et al.	
8,480,064 B2	7/2013	Talavasek	10,040,328 B2	8/2018	Marking	
8,495,947 B2	7/2013	Hata	10,040,329 B2	8/2018	Erickson et al.	
8,550,223 B2	10/2013	Cox et al.	10,047,817 B2	8/2018	Erickson et al.	
8,550,551 B2	10/2013	Shirai	10,054,185 B2	8/2018	Cox	
8,556,048 B2	10/2013	Maeda et al.	10,072,724 B2	9/2018	Haugen et al.	
8,556,049 B2	10/2013	Jee	10,086,670 B2	10/2018	Galasso et al.	
8,596,663 B2	12/2013	Shirai et al.	10,089,868 B1	10/2018	Hayward	
8,616,351 B2	12/2013	Roessle et al.	10,094,443 B2	10/2018	Marking	
8,622,180 B2	1/2014	Wootten et al.	10,145,435 B2	12/2018	Galasso et al.	
8,627,930 B2	1/2014	Smith et al.	10,160,511 B2	12/2018	Erickson et al.	
8,627,932 B2	1/2014	Marking	10,180,171 B2	1/2019	Laird et al.	
8,641,073 B2	2/2014	Lee et al.	10,330,171 B2	6/2019	Cox et al.	
8,651,251 B2	2/2014	Preukschat et al.	10,336,148 B2	7/2019	Erickson et al.	
8,655,548 B2	2/2014	Ichida et al.	10,336,149 B2	7/2019	Erickson et al.	
8,684,367 B2	4/2014	Haugen	10,400,847 B2	9/2019	Marking	
8,727,947 B2	5/2014	Tagliabue	10,406,883 B2	9/2019	Marking	
8,744,699 B2	6/2014	Yamaguchi et al.	10,415,662 B2	9/2019	Marking	
8,752,682 B2	6/2014	Park et al.	10,443,671 B2	10/2019	Marking	
8,763,770 B2	7/2014	Marking	10,473,179 B2	11/2019	Ripa	
8,770,357 B2	7/2014	Sims et al.	10,550,909 B2	2/2020	Haugen	
8,781,680 B2	7/2014	Ichida et al.	10,670,106 B2	6/2020	Erickson et al.	
8,781,690 B2	7/2014	Hara et al.	10,677,309 B2	6/2020	Erickson et al.	
8,814,109 B2	8/2014	Calendrille et al.	10,697,514 B2	6/2020	Marking	
8,833,786 B2	9/2014	Camp et al.	10,718,397 B2	7/2020	Marking	
8,838,335 B2	9/2014	Bass et al.	10,723,409 B2	7/2020	Erickson et al.	
8,845,496 B2	9/2014	Arrasvuori et al.	10,737,546 B2	8/2020	Tong	
8,857,580 B2	10/2014	Marking	11,162,555 B2	11/2021	Haugen	
8,868,253 B2	10/2014	Hashimoto et al.	11,279,198 B2	3/2022	Marking	
8,888,115 B2	11/2014	Chubbuck et al.	11,299,233 B2	4/2022	Erickson et al.	
8,935,036 B1	1/2015	Christensen et al.	11,472,252 B2	10/2022	Tong	
8,936,139 B2	1/2015	Galasso et al.	11,519,477 B2	12/2022	Marking	
8,950,771 B2	2/2015	Felsl et al.	11,549,565 B2	1/2023	Erickson et al.	
8,955,653 B2	2/2015	Marking	11,708,878 B2	7/2023	Marking	
8,967,343 B2	3/2015	Battlogg et al.	11,866,120 B2	1/2024	Erickson et al.	
8,985,594 B2	3/2015	Yabumoto	11,920,655 B2	3/2024	Galasso et al.	
8,991,571 B2	3/2015	Murakami	2001/0017334 A1	8/2001	Vincent	
9,033,122 B2	5/2015	Erickson et al.	2001/0022621 A1	9/2001	Squibbs	
9,038,791 B2	5/2015	Marking	2001/0030408 A1	10/2001	Miyoshi et al.	
9,047,778 B1	6/2015	Cazanas et al.	2001/0042663 A1	11/2001	Marking et al.	
9,057,416 B2	6/2015	Talavasek	2001/0055373 A1	12/2001	Yamashita	
9,073,592 B2	7/2015	Hsl	2002/0000352 A1	1/2002	Matsumoto et al.	
9,103,400 B2	8/2015	Becker	2002/0032508 A1	3/2002	Uchino et al.	
9,108,098 B2	8/2015	Galasso et al.	2002/0045987 A1	4/2002	Ohata et al.	
9,120,362 B2	9/2015	Marking	2002/0050112 A1	5/2002	Koch et al.	
9,126,647 B2	9/2015	Kuo	2002/0050518 A1	5/2002	Roustaei	
9,140,325 B2	9/2015	Cox et al.	2002/0053493 A1	5/2002	Sintorn et al.	
9,157,523 B2	10/2015	Miki et al.	2002/0055422 A1	5/2002	Airmet et al.	
9,186,949 B2	11/2015	Galasso et al.	2002/0063469 A1	5/2002	Nishio	
9,194,456 B2	11/2015	Laird et al.	2002/0089107 A1	7/2002	Koh	
9,199,690 B2	12/2015	Watarai	2002/0095979 A1	7/2002	Shirato et al.	
9,229,712 B2	1/2016	Takamoto et al.	2002/0113347 A1	8/2002	Robbins et al.	
9,239,090 B2	1/2016	Marking et al.	2002/0121416 A1	9/2002	Katayama et al.	
9,278,598 B2	3/2016	Galasso et al.	2002/0130000 A1	9/2002	Lisenker et al.	
9,303,712 B2	4/2016	Cox	2002/0130003 A1	9/2002	Lisenker et al.	
9,353,818 B2	5/2016	Marking	2002/0185581 A1	12/2002	Trask et al.	
9,366,307 B2	6/2016	Marking	2002/0187867 A1	12/2002	Ichida et al.	
9,415,659 B2	8/2016	Kikuchi et al.	2003/0001346 A1*	1/2003	Hamilton	F16F 9/466 280/5.515
9,422,018 B2	8/2016	Pelot et al.	2003/0001358 A1	1/2003	Becker et al.	
9,422,025 B2	8/2016	Pezzi et al.	2003/0034697 A1	2/2003	Goldner et al.	
9,452,654 B2	9/2016	Erickson et al.	2003/0040348 A1	2/2003	Martens et al.	
9,523,406 B2	12/2016	Galasso et al.	2003/0051954 A1	3/2003	Sendra	
9,528,565 B2	12/2016	Marking	2003/0054327 A1	3/2003	Evensen et al.	
9,550,405 B2	1/2017	Marking et al.	2003/0065430 A1	4/2003	Lu et al.	
9,556,925 B2	1/2017	Marking	2003/0075403 A1	4/2003	Dernebo	
9,616,728 B2	4/2017	Marking	2003/0103651 A1	6/2003	Novak	
9,650,094 B2	5/2017	Laird et al.	2003/0128275 A1	7/2003	Maguire	
9,663,181 B2	5/2017	Erickson et al.	2003/0160369 A1*	8/2003	LaPlante	B60G 17/08 188/380
9,682,604 B2	6/2017	Cox et al.	2003/0191567 A1	10/2003	Gentilcore	
			2003/0216845 A1	11/2003	Williston	
			2004/0004659 A1	1/2004	Foote et al.	

(56)

References Cited

U.S. PATENT DOCUMENTS

2004/0017455	A1	1/2004	Kremers et al.	2008/0006494	A1	1/2008	Vandewal
2004/0021754	A1	2/2004	Kremers et al.	2008/0009992	A1	1/2008	Izawa et al.
2004/0075350	A1	4/2004	Kuhnel	2008/0015089	A1	1/2008	Hurwitz et al.
2004/0091111	A1	5/2004	Levy et al.	2008/0018065	A1	1/2008	Hirao et al.
2004/0099312	A1	5/2004	Boyer et al.	2008/0029730	A1	2/2008	Kamo et al.
2004/0103146	A1	5/2004	Park	2008/0041677	A1	2/2008	Namuduri
2004/0172178	A1	9/2004	Takeda et al.	2008/0059025	A1	3/2008	Furuichi et al.
2004/0208687	A1	10/2004	Sicz et al.	2008/0067019	A1	3/2008	Jensen et al.
2004/0220708	A1	11/2004	Owen et al.	2008/0093820	A1	4/2008	McAndrews
2004/0220712	A1	11/2004	Takeda et al.	2008/0096726	A1	4/2008	Riley et al.
2004/0222056	A1	11/2004	Fox	2008/0099968	A1	5/2008	Schroeder
2004/0256778	A1	12/2004	Verriet	2008/0109158	A1	5/2008	Huhtala et al.
2005/0055156	A1	3/2005	Maltagliati et al.	2008/0114239	A1	5/2008	Randall et al.
2005/0056507	A1	3/2005	De Molina et al.	2008/0116622	A1	5/2008	Fox
2005/0077131	A1	4/2005	Russell	2008/0119330	A1	5/2008	Chiang et al.
2005/0098401	A1	5/2005	Hamilton et al.	2008/0162009	A1	7/2008	Miki et al.
2005/0104320	A1	5/2005	Wesling et al.	2008/0163718	A1	7/2008	Chiang
2005/0107216	A1	5/2005	Lee et al.	2008/0185244	A1	8/2008	Maeda et al.
2005/0110229	A1	5/2005	Kimura et al.	2008/0200310	A1	8/2008	Tagliabue
2005/0121269	A1	6/2005	Namuduri	2008/0250844	A1	10/2008	Gartner
2005/0173849	A1	8/2005	Vandewal	2008/0254944	A1	10/2008	Muri et al.
2005/0195094	A1	9/2005	White	2008/0303320	A1	12/2008	Schranz et al.
2005/0199455	A1	9/2005	Browne et al.	2008/0312799	A1	12/2008	Miglioranza
2005/0216186	A1	9/2005	Dorfman et al.	2008/0314706	A1	12/2008	Lun et al.
2005/0227798	A1	10/2005	Ichida et al.	2009/0000885	A1	1/2009	McAndrews
2005/0239601	A1	10/2005	Thomas	2009/0001684	A1	1/2009	McAndrews et al.
2005/0288154	A1	12/2005	Lee et al.	2009/0020382	A1	1/2009	Van Weelden et al.
2006/0040793	A1	2/2006	Martens et al.	2009/0038897	A1	2/2009	Murakami
2006/0064223	A1	3/2006	Voss	2009/0048070	A1	2/2009	Vincent et al.
2006/0065496	A1	3/2006	Fox	2009/0069972	A1	3/2009	Templeton et al.
2006/0066074	A1	3/2006	Turner et al.	2009/0070037	A1	3/2009	Templeton et al.
2006/0076757	A1	4/2006	Bromley	2009/0071772	A1	3/2009	Cho et al.
2006/0081431	A1	4/2006	Breese et al.	2009/0071773	A1	3/2009	Lun
2006/0096817	A1	5/2006	Norgaard et al.	2009/0098981	A1	4/2009	Del et al.
2006/0113834	A1	6/2006	Hanawa	2009/0118100	A1	5/2009	Oliver et al.
2006/0120080	A1*	6/2006	Sipinski	2009/0121398	A1	5/2009	Inoue
				2009/0131224	A1	5/2009	Yuen
				2009/0138157	A1	5/2009	Hagglund et al.
				2009/0140501	A1	6/2009	Taylor et al.
				2009/0171532	A1	7/2009	Ryan et al.
				2009/0192673	A1	7/2009	Song et al.
				2009/0200126	A1	8/2009	Kondo et al.
				2009/0236807	A1	9/2009	Wootten et al.
				2009/0258710	A1	10/2009	Quatrochi et al.
				2009/0261542	A1	10/2009	McIntyre
				2009/0277736	A1	11/2009	McAndrews et al.
				2009/0288924	A1	11/2009	Murray et al.
				2009/0294231	A1	12/2009	Carlson et al.
				2009/0302558	A1	12/2009	Shirai
				2009/0314592	A1	12/2009	Nygren
				2009/0324327	A1	12/2009	McAndrews et al.
				2010/0004097	A1	1/2010	D'Eredita
				2010/0010709	A1	1/2010	Song
				2010/0025946	A1	2/2010	Inoue et al.
				2010/0032254	A1	2/2010	Anderfaas et al.
				2010/0044975	A1	2/2010	Yablon et al.
				2010/0059964	A1	3/2010	Morris
				2010/0066051	A1	3/2010	Haugen
				2010/0109277	A1	5/2010	Furrer
				2010/0133764	A1	6/2010	Greaves
				2010/0139442	A1	6/2010	Tsumiyama
				2010/0147640	A1	6/2010	Jones et al.
				2010/0160014	A1	6/2010	Galasso et al.
				2010/0170760	A1	7/2010	Marking
				2010/0186836	A1	7/2010	Yoshihiro et al.
				2010/0198453	A1	8/2010	Dorogusker et al.
				2010/0207351	A1	8/2010	Klieber et al.
				2010/0224454	A1	9/2010	Chen et al.
				2010/0244340	A1	9/2010	Wootten et al.
				2010/0252972	A1	10/2010	Cox et al.
				2010/0276238	A1	11/2010	Crasset
				2010/0276906	A1	11/2010	Galasso et al.
				2010/0308628	A1	12/2010	Hsu et al.
				2010/0314917	A1	12/2010	Hsieh et al.
				2010/0324781	A1	12/2010	Gagliano
				2010/0326780	A1	12/2010	Murakami
				2010/0327542	A1	12/2010	Hara et al.
				2011/0022266	A1	1/2011	Ippolito et al.
				2011/0035105	A1	2/2011	Jolly

F21S 10/04
362/253

(56)

References Cited

FOREIGN PATENT DOCUMENTS

EP	2103512	A2	9/2009
EP	2116739	A2	11/2009
EP	2189191	A2	5/2010
EP	2248691	A1	11/2010
EP	2357098	A2	8/2011
EP	2410203	A2	1/2012
EP	2479095	A2	7/2012
EP	2495472	A2	9/2012
EP	2357098	B1	10/2014
EP	2848582	A1	3/2015
EP	3786049	A1	3/2021
EP	4257469	A3	8/2024
FR	1343760	A	11/1963
FR	2432424	A1	2/1980
FR	2449236	A1	9/1980
FR	2529002	A2	12/1983
FR	2617928	A1	1/1989
FR	2952031	A1	5/2011
GB	806307	A	12/1958
GB	1185074	A	3/1970
GB	2104183	A	3/1983
GB	2159234	A	11/1985
GB	2159604	A	12/1985
GB	2180320	A	3/1987
GB	2190461	A	11/1987
GB	2282864	A	4/1995
GB	2289111	A	11/1995
JP	57173632	A	10/1982
JP	57173632	U	11/1982
JP	57182506	A	11/1982
JP	S58172142	A	10/1983
JP	01106721	A	4/1989
JP	H0193637	A	4/1989
JP	H02168038	A	6/1990
JP	H03113139	A	5/1991
JP	04203540	A	7/1992
JP	05149364	A	6/1993
JP	H05319054	A	12/1993
JP	06101735	A	4/1994
JP	06185562	A	7/1994
JP	H1084818	A	1/1996
JP	H1073141	A	3/1998
JP	2005119548	A	5/2005
JP	2005119549	A	5/2005
JP	2007302211	A	11/2007
JP	2008238921	A	10/2008
KR	19980043226	U	9/1998
KR	20070076226	A	7/2007
KR	20100041679	A	4/2010
RU	2469224	C1	12/2012
WO	9840231	A2	9/1998
WO	99/06231		2/1999
WO	0027658	A1	5/2000
WO	03070546	A1	8/2003
WO	2007017739	A2	2/2007
WO	2007117884	A2	10/2007
WO	2008086605	A1	7/2008
WO	2008114445	A1	9/2008
WO	2013066159	A1	5/2013

OTHER PUBLICATIONS

European Search Report for European Application No. 19206334.5, 6 pages, May 12, 2020 (May 12, 2020).
 European Search Report for European Application No. 19212356.0, 8 pages, May 7, 2020 (May 7, 2020).
 Machine translation DE3613386; Oct. 1986.
 Machine translation EP 0403803; Dec. 1990.
 Machine translation KR20100041679; Apr. 2010.
 European Search Report for European Application No. 19157767, Oct. 16, 2019, 9 Pages.
 EP Search Report for European Application No. 21173940.4, Nov. 12, 2021, 9 Pages.

European Search Report for European Application No. 20187747, Nov. 18, 2020, 11 Pages.
 Fachkunde Fahrradtechnik 4 Auflage, Gressmann_Inhaltv und S, 2011, 206-207.
 Statement of Grounds of Appeal, EP App. No. 11153607.4, May 28, 2018, 88 Pages.
 Grounds of Appeal, EP App. No. 11153607.4, Jun. 1, 2018, 28 Pages.
 "17 Years of Innovation and Still Evolving", <https://www.powertap.com/post/blog-15-17-years-of-innovation-and-still-evolving>, Nov. 28, 2018, 8 Pages.
 "ANT Message Protocol and Usage", Dynastream Innovations, Inc., Jul. 2, 2007, 68 Pages.
 "Basis For Claims Filed Jan. 23, 2015", European Patent Application No. 14189773.6, 2 Pages.
 "Communication Re Oral Proceedings for European Application No. 10161906, dated Feb. 15, 2013 (Feb. 15, 2013)".
 "European Search Report for European Application No. 09159949 , 2 pages, Sep. 11, 2017 (Sep. 11, 2017)".
 "European Search Report for European Application No. 10161906 , 3 pages, Sep. 15, 2010 (Sep. 15, 2010)".
 "European Search Report for European Application No. 11172612 , 2 pages, Oct. 6, 2011 (Oct. 6, 2011)".
 "European Search Report for European Application No. 11275170 , 2 pages, Jan. 10, 2018 (Jan. 10, 2018)".
 "European Search Report for European Application No. 13158034 , 4 pages, Jun. 28, 2013 (Jun. 28, 2013)".
 "European Search Report for European Application No. 15167426 , 4 pages, Sep. 18, 2015 (Sep. 18, 2015)".
 "European Search Report for European Application No. 16167306 , 2 pages, Mar. 23, 2017 (Mar. 23, 2017)".
 "European Search Report for European Application No. 17188022 , 9 pages, Feb. 1, 2018 (Feb. 1, 2018)".
 "European Search Report for EP Application No. 18154672, 3 pages, Mailed Aug. 28, 2018 (Aug. 28, 2018)".
 "Notice of Intent to Grant EP Application 09159949.8 mailed Nov. 14, 2019, pp. 48".
 "Office Action for European Application No. 13158034.2, 5 pages, Mailed May 22, 2014".
 "The Lee Company Technical Hydraulic Handbook", 1996, 1-696.
 Healey, "The Tyre as Part of the Suspension System", The Institution of Automobile Engineers, Nov. 1924, 26-128.
 Kasprzak, "Understanding Your Dampers: A guide from Jim Kasprzak", <http://www.kaztechnologies.com/downloads/kaz-tech-tips/> Accessed: Oct. 24, 2018, 25 pages.
 Litchfield, "Pneumatic Tires", Transactions (Society of Automobile Engineers), vol. 8, Part II, 1913, 208-223.
 Puhn, "How To Make Your Car Handle", HPBooks, 1981, 7 Pages.
 Thum, Notice of Opposition to a European Patent, EP App. No. 14189773.6, Dec. 13, 2018, 49 Pages.
 Thum, "Opposition Letter Against EP2357098", Oct. 16, 2018, 39.
 Thum, "Opposition Letter Against EP2357098", Dec. 17, 2019, 25 Pages.
 Waechter, et al., "A Multibody Model for the Simulation of Bicycle Suspension Systems", Vehicle System Dynamics, vol. 37, No. 1, 2002, 3-28.
 Haller, E, EPO machine translation of CN 101468587 (A) Device with a suspension system and method for setting a suspension system, published on Jul. 1, 2009.
 Electronic Translation of DE3709447A1.
 English language abstract for EP 0207409 (no date).
 European Search Report for European Application No. 19155995 , 11 pages, Aug. 28, 2019.
 European Search Report, European Patent Application No. 14189773.6, May 4, 2015, 4 Pages.
 EP Search Report for European Application No. 15163428.4, Jul. 3, 2017, 7 Pages.
 "European Patent Office Final Decision dated Mar. 21, 2013", European Patent Application No. 10161906.2.
 "European Search Report for European Application No. 09177128, 4 pages, Aug. 25, 2010 (Aug. 25, 2010)".
 "European Search Report for European Application No. 10187320, 12 pages, Sep. 25, 2017 (Sep. 25, 2017)".

(56)

References Cited

OTHER PUBLICATIONS

“European Search Report for European Application No. 11153607, 3 pages, Aug. 10, 2012 (Aug. 10, 2012)”.

“European Search Report for European Application No. 11172553, 2 pages, Sep. 25, 2017 (Sep. 25, 2017)”.

“European Search Report for European Application No. 11175126, 2 pages, Sep. 25, 2017 (Sep. 25, 2017)”.

“European Search Report for European Application No. 12170370, 2 pages, Nov. 15, 2017 (Nov. 15, 2017)”.

“European Search Report for European Application No. 12184150, 10 pages, Dec. 12, 2017 (Dec. 12, 2017)”.

“European Search Report for European Application No. 13174817, 0, 13 pages, Jan. 8, 2018 (Jan. 8, 2018)”.

“European Search Report for European Application No. 13189574, 2 pages, Feb. 19, 2014 (Feb. 19, 2014)”.

“European Search Report for European Application No. 17154191, 2 pages, Jun. 28, 2017 (Jun. 28, 2017)”.

“European Search Report and Written Opinion, European Patent Application No. 13165362.8”, Sep. 24, 2014, 6 Pages.

Nilsson, “Opposition Letter Against EP-2357098”, Oct. 13, 2017, 7.

Shiozaki, et al., “SP-861-Vehicle Dynamics and Electronic Controlled Suspensions SAE Technical Paper Series No. 910661”, International Congress and Exposition, Detroit, Mich., Feb. 25-Mar. 1, 1991.

Smith, ““The Bump Stop” in Engineer to win—Chapter 13: Springs and Shock Absorbers”, MBI Publishing Company and Motorbooks, USA XP055430818, ISBN: 978-0-87938-186-8, Dec. 31, 1984, 207.

European Extended Search Report for European Application No. 23166846.8, 24 Pages, Mailed Jul. 25, 2024.

Weickert, Response to the Communication of the Board of Appeal, Opposition Against European Patent, EP App. No. 14189773.6, 13 Pages, Dated Aug. 29, 2024.

Kensuke, Suspension Control Device, machine translation of JPH05319054 (A), Dec. 3, 1993 (Year: 1993).

* cited by examiner




FIG. 1




FIG. 2A




FIG. 2B




FIG. 2C





FIG. 3






FIG. 4B




FIG. 4C




FIG. 4D





FIG. 5

**FIG. 6**




FIG. 7




FIG. 8




FIG. 9





FIG. 10A

**FIG. 10B**





FIG. 11A

**FIG. 11B**





FIG. 12A

**FIG. 12B**





FIG. 13A

**FIG. 13B**





FIG. 14A

**FIG. 14B**





FIG. 15A

**FIG. 15B**





FIG. 16A

**FIG. 16B**




FIG. 17A




FIG. 17B




FIG. 17C




FIG. 18A




FIG. 18B




FIG. 18E




FIG. 18C




FIG. 18D




FIG. 18F




FIG. 18G




FIG. 18H




FIG. 18I





FIG. 18J






FIG. 18L




FIG. 18K




FIG. 18N




FIG. 18M




FIG. 18P





FIG. 180






FIG. 18R2

**METHOD AND APPARATUS FOR AN
ADJUSTABLE DAMPER**

CROSS-REFERENCE TO RELATED
APPLICATIONS

This application is a continuation application of and claims the benefit of U.S. patent application Ser. No. 16/051,302, filed on Jul. 31, 2018, entitled "METHOD AND APPARATUS FOR AN ADJUSTABLE DAMPER" by Ericksen et al., assigned to the assignee of the present application, and is hereby incorporated by reference in its entirety herein.

The application with Ser. No. 16/051,346 is a divisional application of and claims the benefit of U.S. patent application Ser. No. 15/275,078, filed on Sep. 23, 2016, now Issued U.S. Pat. No. 10,040,329, entitled "METHOD AND APPARATUS FOR AN ADJUSTABLE DAMPER" by Ericksen et al., assigned to the assignee of the present application, and is hereby incorporated by reference in its entirety herein.

The application with Ser. No. 15/275,078 is a divisional application of and claims the benefit of U.S. patent application Ser. No. 14/466,831, now Issued U.S. Pat. No. 9,452,654, filed on Aug. 22, 2014, entitled "METHOD AND APPARATUS FOR AN ADJUSTABLE DAMPER" by Ericksen et al., assigned to the assignee of the present application, and is hereby incorporated by reference in its entirety herein.

The application with Ser. No. 14/466,831 is a continuation-in-part application of and claims the benefit of U.S. patent application Ser. No. 14/251,446, filed on Apr. 11, 2014, now Issued U.S. Pat. No. 10,047,817, entitled "METHOD AND APPARATUS FOR ADJUSTABLE DAMPER" by Ericksen et al., assigned to the assignee of the present application, and is hereby incorporated by reference in its entirety herein.

The U.S. patent application Ser. No. 14/251,446 is a continuation-in-part application of and claims the benefit of U.S. patent application Ser. No. 13/934,067, filed on Jul. 2, 2013, now Issued U.S. Pat. No. 10,060,499, entitled "METHOD AND APPARATUS FOR ADJUSTABLE DAMPER" by Ericksen et al., assigned to the assignee of the present application, and is hereby incorporated by reference in its entirety herein.

The application with Ser. No. 13/934,067 is a continuation-in-part application of and claims the benefit of U.S. patent application Ser. No. 13/843,704, now Issued U.S. Pat. No. 9,033,122, filed on Mar. 15, 2013, entitled "METHOD AND APPARATUS FOR ADJUSTABLE DAMPER" by Ericksen et al., assigned to the assignee of the present application, and is hereby incorporated by reference in its entirety herein.

The application with Ser. No. 13/843,704, claims the benefit of and claims priority of U.S. provisional patent application Ser. No. 61/709,041, filed on Oct. 2, 2012, entitled "METHOD AND APPARATUS FOR AN ADJUSTABLE DAMPER" by Ericksen et al., assigned to the assignee of the present application, and is hereby incorporated by reference in its entirety herein.

The application with Ser. No. 13/843,704, claims priority of U.S. provisional patent application Ser. No. 61/667,327, filed on Jul. 2, 2012, entitled "METHOD AND APPARATUS FOR AN ADJUSTABLE DAMPER" by Ericksen et al., assigned to the assignee of the present application, and is hereby incorporated by reference in its entirety herein.

The application with Ser. No. 14/251,446 is a continuation-in-part application of and claims the benefit of U.S. patent application Ser. No. 13/485,401, filed on May 31, 2012, entitled "METHODS AND APPARATUS FOR POSITION SENSITIVE SUSPENSION DAMPING" by Ericksen et al., assigned to the assignee of the present application, and is hereby incorporated by reference in its entirety herein.

The application with Ser. No. 13/485,401 claims the benefit of and claims priority of U.S. provisional patent application Ser. No. 61/491,858, filed on May 31, 2011, entitled "METHODS AND APPARATUS FOR POSITION SENSITIVE SUSPENSION DAMPENING" by Ericksen et al., assigned to the assignee of the present application, and is hereby incorporated by reference in its entirety herein.

The application with Ser. No. 13/485,401 claims the benefit of and claims priority of U.S. provisional patent application Ser. No. 61/645,465, filed on May 10, 2012, entitled "METHOD AND APPARATUS FOR AN ADJUSTABLE DAMPER" by Cox et al., assigned to the assignee of the present application, and is hereby incorporated by reference in its entirety herein.

The application with Ser. No. 14/251,446 is a continuation-in-part application of and claims the benefit of U.S. patent application Ser. No. 12/684,072, filed on Jan. 7, 2010, entitled "REMOTELY OPERATED BYPASS FOR A SUSPENSION DAMPER" by John Marking, assigned to the assignee of the present application, and is hereby incorporated by reference in its entirety herein.

The application with Ser. No. 12/684,072 claims the benefit of and claims priority of U.S. provisional patent application Ser. No. 61/143,152, filed on Jan. 7, 2009, entitled "REMOTE BYPASS LOCK-OUT" by John Marking, assigned to the assignee of the present application, and is hereby incorporated by reference in its entirety herein.

The application with Ser. No. 14/251,446 is a continuation-in-part application of and claims the benefit of U.S. patent application Ser. No. 13/189,216, now Issued U.S. Pat. No. 9,239,090, filed on Jul. 22, 2011, entitled "SUSPENSION DAMPER WITH REMOTELY-OPERABLE VALVE" by John Marking, assigned to the assignee of the present application, and is hereby incorporated by reference in its entirety herein.

The application with Ser. No. 13/189,216 is a continuation-in-part application of and claims the benefit of U.S. patent application Ser. No. 13/010,697, now Issued U.S. Pat. No. 8,857,580, filed on Jan. 20, 2011, entitled "REMOTELY OPERATED BYPASS FOR A SUSPENSION DAMPER" by John Marking, assigned to the assignee of the present application, and is hereby incorporated by reference in its entirety herein.

The application with Ser. No. 13/010,697 claims the benefit of and claims priority of U.S. provisional patent application Ser. No. 61/296,826, filed on Jan. 20, 2010, entitled "BYPASS LOCK-OUT VALVE FOR A SUSPENSION DAMPER" by John Marking, assigned to the assignee of the present application, and is hereby incorporated by reference in its entirety herein.

The application with Ser. No. 13/189,216 is a continuation-in-part application of and claims the benefit of U.S. patent application Ser. No. 13/175,244, now Issued U.S. Pat. No. 8,627,932, filed on Jul. 1, 2011, entitled "BYPASS FOR A SUSPENSION DAMPER" by John Marking, assigned to the assignee of the present application, and is hereby incorporated by reference in its entirety herein.

The application with Ser. No. 13/175,244 claims the benefit of and claims priority of U.S. provisional patent application Ser. No. 61/361,127, filed on Jul. 2, 2010,

entitled "BYPASS LOCK-OUT VALVE FOR A SUSPENSION DAMPER" by John Marking, assigned to the assignee of the present application, and is hereby incorporated by reference in its entirety herein.

BACKGROUND

Field of the Invention

Embodiments generally relate to a damper assembly for a vehicle. More specifically, the invention relates to an adjustable damper for use with a vehicle suspension.

Description of the Related Art

Vehicle suspension systems typically include a spring component or components and a dampening component or components. Typically, mechanical springs, like helical springs are used with some type of viscous fluid-based dampening mechanism and the two are mounted functionally in parallel. In some instances, a spring may comprise pressurized gas and features of the damper or spring are user-adjustable, such as by adjusting the air pressure in a gas spring. A damper may be constructed by placing a damping piston in a fluid-filled cylinder (e.g., liquid such as oil). As the damping piston is moved in the cylinder, fluid is compressed and passes from one side of the piston to the other side. Often, the piston includes vents there through which may be covered by shim stacks to provide for different operational characteristics in compression or extension.

Conventional damping components provide a constant damping rate during compression or extension through the entire length of the stroke. Other conventional damping components provide mechanisms for varying the damping rate. Further, in the world of bicycles, damping components are most prevalently mechanical. As various types of recreational and sporting vehicles continue to become more technologically advanced, what is needed in the art are improved techniques for varying the damping rate.

BRIEF DESCRIPTION OF THE DRAWINGS

Aspects of the present invention are illustrated by way of example, and not by way of limitation, in the accompanying drawings, wherein:

FIG. 1 depicts an example electronic valve of a vehicle suspension damper, in accordance with an embodiment.

FIGS. 2A-2C depict an electronic valve, in accordance with an embodiment.

FIG. 3 is a block diagram of an example computer system with which or upon which various embodiments of the present invention may be implemented.

FIG. 4A is a block diagram of a system 400 for controlling vehicle motion, in accordance with an embodiment.

FIG. 4B is a block diagram of an electronic valve 460 which may be integrated into the system 400, in accordance with an embodiment.

FIG. 4C is a block diagram of the control system 404 of FIG. 4A, in accordance with an embodiment.

FIG. 4D is a block diagram of the database 416 of FIG. 4A, in accordance with an embodiment.

FIG. 5 is a flow diagram of a method 500 for controlling vehicle motion, in accordance with an embodiment.

FIG. 6, followed by FIG. 7, is a flow diagram of a method 600 for controlling vehicle motion, in accordance with embodiments.

FIG. 8 shows a method for controlling vehicle motion, in accordance with an embodiment.

FIG. 9 depicts a side cross-sectional view of a shock absorber 900 upon which embodiments may be implemented.

FIGS. 10A-16B depict methods for controlling vehicle motion, in accordance with various embodiments.

FIGS. 17A-17C show interactive touch screens, in accordance with various embodiments.

FIG. 18A is a side cross-sectional view of a monotube piggyback arrangement with the electronic valve located at the main piston, in accordance with an embodiment.

FIG. 18B is an enlarged view of Detail A of FIG. 18A, in accordance with an embodiment.

FIG. 18C is an enlarged cross-sectional view of Detail of FIG. 18A, in accordance with an embodiment.

FIG. 18D is an enlarged cross-sectional view of Detail of FIG. 18A, in accordance with an embodiment.

FIG. 18E is a side cross-sectional view of a solenoid and surrounding components, in accordance with an embodiment.

FIG. 18F is an enlarged cross-sectional side view of Detail A of FIG. 18A, in accordance with an embodiment.

FIG. 18G is an enlarged cross-sectional side view of Detail A of FIG. 18A, in accordance with an embodiment.

FIG. 18H is an enlarged cross-sectional side view of Detail A of FIG. 18A, in accordance with an embodiment.

FIG. 18I is an enlarged cross-sectional side view of Detail A of FIG. 18A, in accordance with an embodiment.

FIG. 18J is a side cross-sectional view of the electronic valve acting as the base valve assembly, in accordance with an embodiment.

FIG. 18K is an electronic valve 460 integrated into a monotube design of a shock absorber, with a piggy back chamber, in accordance with an embodiment.

FIG. 18L is an enlarged cross-sectional view of the base valve electronic valve of Detail A of FIG. 18K, in accordance with an embodiment.

FIG. 18M is the monotube design of FIG. 18K in a rebound position, in accordance with an embodiment.

FIG. 18N is an enlarged view of the electronic valve 460 shown in Detail A of FIG. 18M, in accordance with an embodiment.

FIG. 18O is the electronic valve 460 integrated into an internal bypass monotube design 1863 for a shock absorber, in accordance with an embodiment.

FIG. 18P is an enlarged view of the electronic valve 460 of Detail A shown in FIG. 18O, in accordance with an embodiment.

FIG. 18Q is a side section view of a twin tube 1878 in a compression state, in accordance with an embodiment.

FIG. 18R is a block description of the relationship between the components shown in FIGS. 18R1 and 18R2, in accordance with an embodiment.

FIG. 18R1 is a side section view of the twin tube 1878 in a compression state, in accordance with an embodiment.

FIG. 18R2 is a section view of the two electronic valves of FIG. 18R1 positioned in parallel with each other, in accordance with an embodiment.

The drawings referred to in this description should be understood as not being drawn to scale except if specifically noted.

DESCRIPTION OF EMBODIMENTS

The detailed description set forth below in connection with the appended drawings is intended as a description of

various embodiments of the present invention and is not intended to represent the only embodiments in which the present invention may be practiced. Each embodiment described in this disclosure is provided merely as an example or illustration of the present invention, and should not necessarily be construed as preferred or advantageous over other embodiments. In some instances, well known methods, procedures, objects, and circuits have not been described in detail as not to unnecessarily obscure aspects of the present disclosure.

Notation and Nomenclature

Unless specifically stated otherwise as apparent from the following discussions, it is appreciated that throughout the present Description of Embodiments, discussions utilizing terms such as “accessing”, “comparing”, “monitoring”, “determining”, “regulating”, “calculating”, or the like, often refer to the actions and processes of a computer system or similar electronic computing device (or portion thereof) such as, but not limited to, a control system. (See FIGS. 3, 4A, 4C and 4D.) The electronic computing device manipulates and transforms data represented as physical (electronic) quantities within the electronic computing device’s processors, registers, and/or memories into other data similarly represented as physical quantities within the electronic computing device’s memories, registers and/or other such information storage, processing, transmission, and/or display components of the electronic computing device or other electronic computing device(s). Under the direction of computer-readable instructions, the electronic computing device may carry out operations of one or more of the methods described herein.

Overview of Discussion

As is generally known, shock absorbers, such as those described in US Patent Application No. 114/231,446, “Method and Apparatus for an Adjustable Damper”, may be applied to a multi-wheeled vehicle. These shock absorbers may include an electronic valve that has an orifice block, a primary valve and a pilot valve assembly. Sensors may be attached to the vehicle and provide information, to a control system attached to the electronic valve, on acceleration (with respect to a bicycle) and on acceleration, tilt, velocity and position (with respect to vehicles with more than two wheels). The control system accesses the sensor signals and actuates the electronic valve to provide variable damping.

Example conventional and novel techniques, systems, and methods for controlling vehicle motion are described herein. Herein, with reference to FIGS. 1 and 2A-2C, various conventional systems, methods and techniques that utilize a conventional control system and a conventional electronic valve for controlling vehicle motion in vehicles with three or more wheels are described. Then, with reference to FIGS. 4A-4D, a novel electronic valve and its functioning is described. This novel electronic valve is not only utilized to perform the conventional methods for controlling a vehicle’s motion described with respect to FIGS. 1, 2A-2C and 5-8, but also novel methods for controlling a vehicle’s motion by enabling even more selective damping to occur, discussed with reference to FIGS. 10A-16B.

In regards to FIGS. 1 and 2A-2C, the conventional features described therein, and as will be described herein, not only deduce the vertical acceleration values, but also deduce, from a received set of control signals (that include acceleration values associated with various vehicle compo-

ments), the roll and pitch of a vehicle with more than two wheels. These measured acceleration values relate to the tilt (e.g., roll, pitch) of the vehicle and are compared to a database having thereon preprogrammed acceleration threshold values associated with vehicle components as it relates to tilt. Further, the conventional control system receives measured velocity values associated with user-induced events (e.g., turning a steering wheel, pressing/releasing a brake pedal, pressing/releasing the gas pedal, thereby causing a throttle to open/close). The control system compares these measured velocity values relating to user-induced events to a database having preprogrammed thereon velocity threshold values associated with vehicle components. Based on the comparison performed with regard to the measured acceleration values with the predetermined acceleration threshold values and the measured velocity values with the predetermined velocity threshold values, as well as the determined state of valves within various vehicle suspension dampers attached to vehicle components, the control system sends an activation signal to power sources of the vehicle suspension dampers. The activation signal activates the power source to deliver a current to valve assemblies within the vehicle suspension dampers. Once delivered, the valve assemblies adjust to a desired state. The desired state is configured to adjust the damping force to reduce or eliminate the tilt of the vehicle’s frame. In other words, the orientation of the vehicle frame is placed as close to level as possible.

As will be described herein, these conventional systems and methods also provide various system modes within which the vehicle suspension dampers may operate, along with control modes for affecting roll and pitch dynamics of the vehicle. Further, these conventional methods and systems for implementing delays and rebound settle time, for de-conflicting multiple control modes and for cycling between different system modes are described.

Thus, described first herein are conventional, though newer, systems and methods for controlling a vehicle’s motion by increasing and/or decreasing damping forces within a vehicle suspension damper in quick response to sensed movement of vehicle components (e.g., vehicle wheel base). These systems and methods may be used in various types of multi-wheeled vehicles, such as, but not limited to, side-by-sides (four-wheel drive off-road vehicle), snow mobiles, etc. These conventional devices may be positioned in both the front fork and the rear shock. While, in general, vehicle suspension dampers cannot respond quickly enough to a sensed movement of a vehicle’s front wheel traversing an obstacle such that the rider avoids feeling the effect via the vehicle’s frame, the conventional, though newer, systems and methods described herein are able to quickly and selectively apply damping forces through the vehicle suspension dampers (that are coupled with both the vehicle’s forks and the vehicle’s frame). Such damping enables the vehicle’s frame, and thus the vehicle’s rider, to experience less acceleration than that being experienced by the wheel base(s).

The conventional systems and methods described herein for controlling vehicle motion provide a control system that enables the use of sensors and an electronic valve to read the terrain and make changes to the vehicle suspension damper (s) in real time. The conventional control system described herein enables at least the following functions: the execution of algorithms that enable a quicker response and adjustment to the vehicle suspension damper(s) than other conventional vehicle suspension dampers; a quiet operation since there are no audible electronic valve actuation sounds; a power

efficient model that is designed for low power consumption; an easily tunable model that may use conventional means in combination with the control system described herein, such as, but not limited to, valve shims; a fail-safe shock absorber, as the electronic valve also functions as a conventional shock if power is lost; a small model that can be packaged in bicycle forks and shocks; and a versatile model that may function in conventional shocks, twin tube shocks and bypass shocks.

In contrast to the conventional system and method for controlling a vehicle's motion described herein, embodiments utilize a variable pressure valve as part of an electronic valve (instead of a pilot valve assembly), as will be discussed herein with reference to FIGS. 4A-4D and 10A-16B. A variable pressure valve is, in comparison to the pilot valve, more robust for use in vehicles with three or more wheels, such as side-by-sides. Further, embodiments of the present technology provide for methods for controlling vehicle motion that consider a wider range of variables (e.g., temperature, humidity, date, pressure applied against vehicle seats and storage compartments, and vehicle component acceleration, velocity, speed and position, etc.) (as compared with the conventional methods described herein), which enables the vehicle suspension damper to even more selectively tune damping effects (as compared with conventional methods). The robust variable pressure valve is capable of implementing such tuned damping within the shock absorber. The methods described herein enable a firm control mode, a medium control mode, a soft control mode, and control modes there between.

Thus, the novel systems and methods discussed herein for controlling vehicle motion, according to embodiments, not only provide the same aforementioned benefits also provided by conventional electronic valves and conventional control system, but also provide a more robust alternative device/system for effecting changes within the shock absorbers (i.e., more or less damping), while providing methods for customized damping as it specifically applies to the vehicle's environment.

A conventional, though newer, electronic valve and control system and its operation will be explained first. Next, a novel electronic valve and control system and its operation will be explained. Following, novel methods for controlling a vehicle's movement will be described.

Conventional Electronic Valve with Pilot Valve Assembly and Operation Thereof

FIG. 1 shows the electronic valve 100 of a vehicle suspension damper. The electronic valve 100 includes at least a primary valve 112, a first pressure reducing means which, in FIG. 1, is an orifice block 122, and a second pressure reducing means which, in FIG. 1, is a pilot valve assembly 132, all of which components cooperatively control the flow of fluid throughout the electronic valve 100 and manipulate the fluid pressure within the pilot pressure chamber 126.

In basic operation, the permanent magnet 136 of the solenoid assembly 120 conducts through the component 134 to attract the pilot spool 128. This is the latched position as shown. The spool spring 130 resists this condition. When the coil is turned on with positive polarity, it cancels the effect of the permanent magnet 136 and the spool spring 130 moves the pilot spool 128 to the left or closed position. With negative polarity applied to the coil, the electromagnet is added to the permanent magnet 136 and the pilot spool 128 is drawn to the right or open position.

The main oil flow path, or first fluid flow path, is through the center of the base valve and radially outwardly into

piston port 104 area. Assuming there is enough pressure in the piston ports, it then blows off the valve shims 108 and oil flows into the reservoir 102. A small amount of oil also flows in parallel through a second fluid flow path in the electronic valve 100 (also called an inertia valve), and in particular through the control orifice 124 and through the solenoid assembly 120. This generates a pilot pressure inside the area of the primary valve 112.

The valve member 114 acts to resist the valve shims 108 from opening. This resistive force is dependent on pressure inside the area of the primary valve 112 which is controlled by the pressure drop across the solenoid. Basically, when the solenoid is closed, there is high pressure inside the area of the primary valve 112 (resulting in locked-out fork or firm damping, depending on the damping characteristics determined for the electronic valve 100, as described in greater detail below). When the solenoid is in an open position, there is low pressure inside the area of the primary valve 112 and the valve member 114 pushes against valve shims 108 with less force, allowing the valve shims 108 to open under lower fluid pressure. This open position of the solenoid provides a normally-operating fork, by which is meant the damping characteristic of the inertia valve is determined predominantly by the tuning of the valve shims 108 (although there is some damping effect provided by the control orifice 124).

A more particular description follows. A control signal (a.k.a., activation signal sent by activation signal sender 450 of FIG. 4A) instructs the vehicle suspension damper to increase or decrease its damping force therein. The vehicle suspension damper is configured to respond to the control signal instruction. More particularly, the electronic valve 100 of the vehicle suspension damper, in response to the control signal instruction, quickly manipulates the pressure in the pilot pressure chamber of the electronic valve 100 by moving/adjusting the pilot valve assembly 132 to at least partially close or open the flow ports 118. The pressure in the pilot pressure chamber 126 increases or decreases in proportion to the amount of closure or opening that the flow ports 118 experience, respectively.

In general, fluid in the electronic valve 100 flows along a first fluid flow path from the damping cylinder interior 35 and through the shims 108 (unless the shims 108 are held closed under pressure from the valve member 114, as will be described herein) via the piston port 104 area. Additionally, fluid also flows along a second fluid flow path from the damping cylinder interior 35 and through the control orifice 124 of the orifice block 122. After having flowed through the control orifice 124, the fluid moves into the pilot pressure chamber 126. From the pilot pressure chamber 126, the fluid moves out of the pilot spool valve 116 (wherein the pilot spool valve 116 is in at least a partially open position) through a set of flow ports 118 and into the reservoir 102. Additionally, from the pilot pressure chamber 126, the fluid also moves into the area of the primary valve 112. When the fluid presents a predetermined pressure against surface 110 of the valve member 114, a force proportional to the pressure is exerted on the valve member 114 which urges it against the shims 108. The valve member 114 pushes against the shims 108, thereby biasing the shims 108 toward a closed position, even though fluid is moving through the shims 108 from the piston port 104 area and into the reservoir 102. If the force of the valve member 114 against the shims 108 is greater than the force of the fluid moving from the piston port 104 area against the shims 108, then the shims 108 will become biased toward closing. Likewise, if the force of the fluid moving from the piston port 104 area against the shims

108 is greater than the force of the valve member **114** against the shims **108**, then the shims **108** will be biased toward an open position, in which the fluid may remain flowing through the shims **108**.

During compression of the shock absorber, in order to change the fluid pressure within the pilot pressure chamber in quick response to changes in the vehicle's position and speed (and components thereof), for example, embodiments use a control system to receive control signals from a set of sensors positioned on a vehicle. In accordance with the control signals received from the set of sensors, the control system activates a power source that is attached to the electronic valve. The power source delivers a current to the electronic valve. The electronic valve responds to the delivered current by causing the pilot valve assembly **132** to move and block or open at least a portion of the flow ports **118** through which fluid may flow there through from the pilot pressure chamber **126** and into the reservoir **102**, thereby at least partially closing or opening the flow parts **118**.

In general, upon compression of the shock absorber, a damper piston moves into a damper cylinder interior. More particularly, when the flow ports **118** are at least partially closed, the fluid pressure within the pilot pressure chamber **126** increases such that the fluid pressure in the area of the primary valve **112** also increases. This increase in the fluid pressure in the area of the primary valve **112** causes the valve member **114** to move toward the shims **108** that are open and to push against the shims **108**, thereby causing the shims **108** to at least partially or fully close. When these shims **108** are at least partially or fully closed, the amount of fluid flowing there through decreases or stops. The movement of the damper piston into the damper cylinder interior causes fluid to flow through the piston port **104** area and hence out through open shims **108** and into the reservoir **102**. The fluid also flows through the control orifice **124** into the pilot pressure chamber **126**. If the shims **108** are closed due to movement of the pilot valve assembly **132** to block the flow ports **118**, then fluid may not flow out through the shims **108** or out through the flow ports **118** into the reservoir **102**. Consequently, the ability of the damper piston to move within the damper cylinder interior to cause fluid to flow through the piston port **104** area as well as through the flow ports **118** is reduced or eliminated. The effect of the at least partial closure of the shims **108** is to cause a damping function to occur. Thus, the movement of the pilot valve assembly **132** to at least partially block the flow ports **118** causes the damping (or slowing of movement) of the damper piston into the damper cylinder interior.

The control orifice **124** operates cooperatively with the pilot valve assembly **132** to meter the flow of fluid to the primary valve **112**. The control orifice **124** is a pathway within the orifice block **122** and is positioned between the damper cylinder interior **35** and the pilot pressure chamber **126**. The size of the control orifice **124** is tunable according to the application; the size may be variously changed. The control orifice **124** is a key component in enabling the quick and accurate response to sensed changes in a vehicle's motion. As will be explained herein, without the presence of the control orifice **124**, the vehicle would not experience damping during periods of low compression speed, or experience too much damping during periods of high compression speeds. The pilot valve assembly **132** would act like a bypass. In other words, without the control orifice, at low compression speed there would almost be no damping and the control orifice **124** and pilot valve assembly **132** would act like a bypass; but at higher compression speeds, pressure

drop across the pilot valve assembly **132** would cause a high pressure in the pilot pressure chamber **126** and therefore too much clamping force on the shims **108**. The control orifice **124**, thus, allows damping to occur even during periods of low compression speed, and slows the damping rate during periods of high compression speed.

In this particular application, it was discovered that (without the control orifice **124**) if the area of the primary valve is approximately 60% or more of the piston port **104** area, the valve member **114** is hydraulically locked (at all speeds) onto the shims **108**. This led to undesirable high damping force at high compression speeds. Although in this particular application the hydraulic lock occurred at about 60% area ratio and higher, this may not be true in all cases: there may be arrangements where a lock occurs at a higher or lower ratio than 60%, or where no lock occurs at all at any ratio. It is expected that the particular ratio will be dependent on design parameters such as the valve shim arrangement and main piston design.

The solution is to cause a pressure drop of damping fluid before it enters the pilot pressure chamber **126**. This is achieved with the control orifice **124**. The control orifice **124** provides some damping effect at low compression speeds (by enabling damping fluid to 'bleed' through the control orifice), but at high compression speeds provides a significant pressure drop to ensure that the pressure inside the pilot pressure chamber does not get too high, thereby preventing the valve member **114** from locking onto the shims **108**.

In its present form, the control orifice **124** is between 0.5 mm and 2 mm in diameter, but these sizes are dependent on the specific application and the desired damping curve. Pressure drop is directly proportional to the length of the control orifice **124**, but inversely proportional to its diameter. Either one or both of these parameters can be changed at the design stage to affect the performance of the control orifice **124**.

The essential function of the control orifice **124** is to create a pressure drop. Therefore, anything that will do this could be used in place of the specific arrangement shown. Some possible examples include, but are not limited to: a diffuser; a labyrinth between parallel plates; and leakage past a screw thread.

A further key feature is the combination of the area of the surface **110** inside the valve member **114**, the control orifice **124**, the pilot valve assembly **132**, and the way this combination enables a variable force to be applied to the shims **108** to control the damping force at any point in time.

In particular, the ratio of the surface area **106** of the shims **108** (The surface area **106** is next to the piston port **104** area; the pressure is acting on the surface area **106** of the shims **108** as well as the surface area **110** of the inside of the valve member **114**, within the primary valve **112** area) to the surface area **110** inside the valve member **114** controls the overall damping characteristic of the electronic valve **100**, i.e., what overall range of force can be applied to the shims **108**. By selecting this ratio appropriately, the valve member **114** can be set up to move between full lockout and a completely soft state, or between a firm damping state and a soft state, for example.

Within that overall range of force, a particular force at any point in time is set by the position of the pilot valve assembly **132**, which, as explained above, controls the pressure drop across the flow ports **118**. By adjusting the pressure drop across flow ports **118**, the pressure of fluid in the pilot pressure chamber **126** is also adjusted. Since the pressure inside the pilot pressure chamber **126** acts against surface **110** of the valve member **114**, the force applied by the valve

member **114** to the shims is controllable by adjustment of the position of the pilot valve assembly **132**.

It should be noted that the overall resistance to fluid flow along the first fluid flow path (i.e. through piston port **104** area and past shims **108**) is given by the sum of the force provided by the shims **108** and the force applied to the shims **108** by the valve member **114**.

A significant feature is that a force is generated on the valve member **114** by a control of pressure inside the area of the primary valve **112** (in contrast to other valve bodies where force comes from pressure acting on the outside of the valve member **114**, usually from the damper reservoir). The ultimate source of pressure in the pilot pressure chamber **126** is the pressure of the damping fluid in the main damping cylinder **35** during compression (but regulated by the control orifice **124** and the pilot valve assembly **132** to give a lower pressure in the pilot pressure chamber **126**).

There are significant advantages to the combination of the ratio of the area of the surface **110** to the area of the piston port **104**, control orifice **124**, and the pilot valve assembly **132**. Some of them are as follows: 1) the damping force generated by electronic valve **100** is not temperature sensitive; 2) the damping force generated by electronic valve **100** is not position sensitive; 3) when using an electro-mechanical inertia device to control the pilot valve assembly **132**, the damping force can be turned on and off very quickly (recent experiments achieved 4 ms between full firm and full soft to the best of the applicant's knowledge and belief the fastest time for turning on and off of damping force in other devices is 20 ms. The reason such fast speeds are achieved is because, when the pressure in the pilot pressure chamber **126** is released, it is the pressure in the main damper (which is the same as the fluid pressure in the piston port **104** area) that pushes on the shims **108** and moves the primary valve **112** back (which can happen very quickly). This is in contrast to other arrangements that rely on an electric motor to move a valve body, for example, which takes more time; 4) using a latching solenoid pilot valve enables a full firm state to be maintained with no power; 5) the pilot valve assembly **132** enables very large damping forces to be controlled because: (a) the pilot pressure is 'magnified' according to the ratio of the area of the primary valve **112** to the area of the piston port **104**; and (b) because the pilot valve assembly **132** is not required to move any element against the high pressure damping fluid; and 5) the pilot valve assembly **132** allows the damper to utilize conventional shims, but with some level of controllability over the damping force applied by the shims. This allows the shims to be tuned in a conventional manner. Furthermore, if power to the pilot valve assembly **132** fails, the shock absorber will continue to operate (in contrast to other electronically controlled shocks where power loss causes the shock to stop working completely).

Thus, the electronic valve **100**, including the primary valve **112**, the pilot valve assembly **132**, and the orifice block **122**, not only enables a variable force to be applied to shims **108**, but also enables the control of the damping force within the vehicle at any point in time. The pilot valve assembly **132** meters a flow of fluid to the primary valve **112** and enables the generation of relatively large damping forces by a relatively small solenoid (or other motive source), while using relatively low amounts of power.

Furthermore, since the incompressible fluid inside of the primary valve **112** of the shock absorber assembly causes damping to occur as the primary valve **112** opens and the valve member **114** collapses, a controllable preload on the shims **108** and a controllable damping rate are enabled. In

four-wheeled vehicles, the solenoid continuously powers the inertia valve and does not have a latching mechanism. A monitor will continuously monitor a power source and its operation in order to make sure that the wires leading to the power source do not get cut, thereby providing a dangerous situation for the rider and other vehicles.

In regards to the area of the primary valve **112**, although it is shown as an internal base valve, it is not limited to this position or application. For example, it can be mounted externally of the vehicle suspension damper (for example in a 'piggy-back' reservoir). Further, it could be made part of the main damper piston (either in compression or rebound directions).

In considering the design of the control orifice **124**, it must have at least the following two functions: a provision of low speed bleed; and a provision of a sufficient pressure drop at high speed to prevent hydraulic lock of the valve member **114** onto the shims **108**. The general methodology for determining the diameter and/or length of the control orifice **124** during design is as follows: (1) identify the desired damping curve that the damper should have; (2) determine from step (1) the target low speed damping force; (3) determine from step (1) the target high speed damping force; (4) make informed guess at control orifice diameter and/or length to achieve steps (2) and (3); (5) test the output damping forces produced by shock at different speeds within low to high speed range; (6) compare the measured damping curve against the desired damping curve; (7) if there is too much high speed damping force, then reduce the diameter of the control orifice (to lower the pressure inside the pilot pressure chamber **126**); (8) if there is too much low speed damping force, then decrease the area ratio (between the area of the primary valve **112** and the piston port **104** area), and increase the diameter of the control orifice **124**; and (9) repeat steps (5)-(8) until a good approximate to a desired damping curve is obtained. It is to be noted that in steps (7) and (8) the length of the control orifice can also be adjusted, either separately or in addition to the diameter, to achieve a similar effect.

It was found that the pilot valve assembly **132** would "auto-close" at a certain oil high flow rate. A diffuser pin inserted into the vehicle suspension damper downstream of the control orifice **124** is used to eliminate this auto-closing issue. FIG. 2A shows an electronic valve **200A** with a diffuser pin **204** positioned through one set of the cross holes **202** going to the primary valve **112** area. Another set of holes remains (normal to the page) to feed oil to the valve member **114**. The diffuser pin **204** functions to disrupt the jet flow coming out of the control orifice **124**. FIG. 2B shows an electronic valve **200B** with a diffuser plug **206** pressed into, at least one of and at least partially, the orifice block **122** and the pilot pressure chamber **126**. The diffuser plug **206** also functions to disrupt the jet flow coming out of the control orifice **124**. FIG. 2C shows an electronic valve **2000** with a diffuser pin **204**. The spool retainer **208** (see FIG. 2C) is replaced with the diffuser pin **210**. The diffuser pin **210** and its position within the vehicle suspension damper **2000** functions to disrupt the jet flow coming out of the control orifice **124** and to minimize the contact of the pilot valve assembly **132** in the firm setting.

The solenoid includes a "latching" mechanism to open and close the pressure-balanced pilot spool. Due to the latching configuration of the solenoid, power is only required to open or close the pilot valve assembly **132**. Power is not required to hold the pilot valve assembly **132**

13

open or closed in either setting. Consequently, reduced power consumption is enabled compared to the traditional shock absorber.

Further, an externally-adjustable means of tuning the open state of the damper is described. An adjuster turns in or out to vary the effective orifice size of the flow ports **116** when in the open position. This allows the rider to adjust the soft setting of the damper to his preference.

With respect to the shock absorber described above in conjunction with FIGS. **1** and **2A-2C**, it is to be noted that, whilst preferred, the use of a valve shims **108** is optional. Instead, it would be possible for the valve member **114** to act directly on the fluid flow ports **145**. In fact, valve shims are optional in any shock absorber described herein at the point where it would be possible for the valve member **114** (or any other similar valve member described herein) to act directly on the fluid flow ports that control the main flow through the valve assembly.

With reference again to FIGS. **1**, **2A-2C** and **4A**, it should be again noted that the set of sensors **440** may be positioned in various locations on various types of vehicles. For example, in one embodiment, the set of sensors **440** is positioned on the seat post of a bicycle. In another embodiment, a first set of sensors is positioned near the front wheel, while a second set of sensors is positioned near the rear wheel.

The set of sensors may include at least one accelerometer, but generally includes three accelerometers. The three accelerometers define a plane of the vehicle's body, such that the acceleration, and in other embodiments, the acceleration and the tilt (i.e., pitch and roll), of the vehicle body may be measured. When the set of sensors senses vehicle motion, the set of sensors sends a control signal to the control system attached to the vehicle suspension damper. The control system determines if the sensed vehicle motion meet and/or exceeds a predetermined threshold. The predetermined threshold may be a constant in one embodiment. However, in another embodiment, the predetermined threshold may be a variable based on other situations sensed at the vehicle. Once a control signal is received by the power source, the power source that is attached to the vehicle suspension damper becomes activated. Upon activation, the power source sends a current to the vehicle suspension damper, thereby causing the pilot valve assembly to move, as is described herein. Various methods of sensing via accelerometers and other forms of motion via sensors are known in the art.

As described herein, the vehicle to which a set of sensors and the vehicle suspension damper described thus far herein are attached may be attached to a multi-wheeled vehicle, such as, but not limited to, a bicycle, a side-by-side, a snowmobile, a car, a truck, etc. In one embodiment, more than one set of sensors may be used on the non-limiting example of a side-by-side vehicle (e.g., recreational off-highway vehicle [ROV]). For example, each wheel base (e.g., four) may include the shock absorber that has thus far been described herein. More specifically, each wheel base has attached thereto a different set of sensors, such as a set of accelerometers, each set being attached to a separate vehicle suspension damper. One set of sensors (e.g., set of accelerometers) is attached to the ROV, as well as being attached to one or more vehicle suspension dampers.

If the ROV is traveling along a path that does not have any bumps or uneven terrain, then the vehicle suspension dampers may each be programmed to operate in a fully open mode (i.e., soft mode), in which the pilot spool valve **116** of the pilot valve assembly **132** is open to the flow ports **118**,

14

thereby allowing fluid to flow from the damper cylinder interior **35** and into the reservoir **102** either through the first fluid flow path, with resistance provided by the shims **108** (and no additional force provided by the valve member **114**), and/or through the control orifice **124** that permits low speed bleed of damping fluid via the second fluid flow path. Thus, for example, when the right front tire of an ROV hits a large rock, the right front tire and a portion of the suspension attached to the tire (or attached wheel base) may rise upwards to move over the rock. The set of sensors attached to the ROV's right front side will sense the tire's upward movement, and will sense the tire reaching its peak upward movement (the peak of the rock), and will sense the tire beginning to move downwards. The set of sensors on the ROV's right front side would send control signals to the vehicle suspension damper attached to the ROV's right front side throughout the tire's movement upward and downward. The control system attached to the vehicle suspension damper receives the control signals and causes the power source also attached to the vehicle suspension damper to deliver a current to the vehicle suspension damper in accordance with the control signals. The delivered current functions to cause the pilot valve assembly **132** to move to cause the flow ports **118** to be at least partially blocked. As described herein, the pressure within the pilot pressure chamber **126** increases due to the at least partially blocked flowports **118**, thereby causing the pressure within the area of the primary valve **112** to increase. The valve member **114**, in response to increased pressure in the area of the primary valve **112**, is urged against the shims **108**, thereby changing the damping characteristics of the shims **108**. Thus, the fluid flowing along the first fluid flow path from the damper cylinder interior **35** and through the piston port **104** area is reduced, resulting in placing the vehicle suspension damper in a firm damping setting.

Significant advantages over other conventional shock absorber systems are as follows. In conventional mechanical inertia valves, an inertia valve senses a pressure wave (occurring at the speed of sound) after a vehicle's tire hits a bump. The inertia valve opens in response to receiving the pressure wave. However, the vehicle rider still experiences some form of response to the terrain before the inertia valve has a chance to open into a "soft" mode. In contrast, in the shock absorbers thus far described herein, using an electronic valve attached to accelerometers, the electronic valve opens into a "soft" mode before a motion significant enough for a vehicle rider to experience the motion has begun. For example, when a wheel motion occurs, such as an ROV wheel base beginning to move upward while running over a large rock, the wheel base experiences an upward acceleration. This acceleration is measured by embodiments. Before the wheels' velocity and/or displacement can be or is measured, a control signal is sent from a set of accelerometers that communicate the acceleration values of the wheel to a control system that is connected (wire or wirelessly) to the electronic valve. The set of accelerometers are positioned to measure the acceleration experienced by the wheel base. These acceleration signals are sent at the beginning of the wheel's ascent over the rock. The electronic valve is opened into a soft mode in response to receiving the signals from the set of accelerometers. The soft mode is initiated before the wheel experiences such a large acceleration upwards that the vehicle rider feels a reaction to the wheel's motion through the vehicle's frame. Unlike other conventional damping systems, in the instant conventional damping system, a quick response to a sensed acceleration of a vehicle wheel is enabled such that an acceleration of a

vehicle frame due to the movement of the vehicle wheel may be reduced or prevented. It should be appreciated that one or more set of sensors may be attached to each ROV wheel base, and independently control the vehicle suspension damper to account for and respond to various rolls and other types of vehicle motion.

One or more motion sensors are provided on a forward or front part of a vehicle, and a signal or signals from the one or more motion sensors is used to control a vehicle suspension damper mounted on a rear part of the vehicle. In use, motion information learned from the movement of the front part of the vehicle can be used to anticipate movement of the rear part of the vehicle, and adjustments may be made to control the damper on the rear part accordingly.

Thus, the control of both compression and the rebound state of the vehicle suspension damper is enabled, such that an acceleration at the vehicle frame is maintained as close to zero as possible throughout off-road riding and over varied terrain, regardless of the acceleration being experienced at the vehicle's wheel.

As noted herein, more than one type of sensor may be used. For example and not limited to such example, an accelerometer and a gyrometer may be used. Further, the set of control signals sent to the control system may include, but are not limited to the following values: acceleration values; tilt (e.g., pitch, roll) values; and velocity values. It should also be noted that numerous methods for determining orientation in a plane in space using a sensor attached to an object are well known in the art. Thus, the adjustment of the vehicle compression dampers to a desired state, based on a comparison of the measured signal values with a database of threshold values, enables the reduction of the tilt of a vehicle's frame.

Novel Electronic Valve Having Variable Pressure Valve and Novel Control System and Operation Thereof

As will be described herein, embodiments provide a novel and robust electronic valve that may be integrated within shock absorbers for use on vehicles having more than two wheels. Further, described herein are novel systems and methods for controlling vehicle motion, in which sensors are attached to the vehicle (with more than two wheels) and provide information on, for example, the following variables: acceleration, tilt, velocity, position, lateral acceleration, speed, temperature, pressure applied to vehicle seats and cargo bay, and humidity. A novel control system accesses the sensor signals and performs calculations to a control mode setting to be actuated depending on a particular predetermined relationship between the variables. According to an embodiment, the control system causes the electronic valve to become actuated, thereby providing variable damping that is more narrowly tailored to the vehicle's environment and to the vehicle rider.

The novel electronic valve includes an orifice block, a primary valve and a variable pressure valve is described herein with respect to FIGS. 4A-4D and 18A-18I, wherein the electronic valve is shown installed in a monotube piggyback arrangement (the electronic valve is located at the main piston), a monotube internal bypass arrangement and a twin-tube arrangement.

FIG. 18A is a side cross-sectional view of a monotube piggyback arrangement 1800 with the electronic valve 460 located at the main piston 1804, in accordance with an embodiment. The monotube piggyback arrangement 1800 is shown in a rebound configuration.

FIG. 18B is an enlarged view of Detail A of FIG. 18A, in a compression method position, in accordance with an embodiment. The electronic valve 460 includes the primary valve 1810, the variable pressure valve 1814, the orifice 1818 and reservoir 1920. In one embodiment, the valve member 1808 is a model TS08-20B-0-V-12ER valve, commercially available from HydraForce, Inc. of Lincolnshire, IL, USA. Also shown in FIG. 18B is the piston 1804, the shims 1806, the valve member 1808, the flow ports 1812 and the pilot spool 1816. Upon compression, if the power source that is attached to the electronic valve 460 is not actuated, then the flow ports 1812 are and will remain closed, and the fluid that moves from the reservoir 1820 and into the orifice 1818 will then flow into the primary valve 1810. Once in the primary valve 1810, the fluid exerts force against the outer walls of the valve member 1808, which causes the valve member to move closer to the shims 1806. Upon moving closer to the shims 1806, the shims 1806 begin to close against the components on the other side of the shims 1806. Due to limited flow ports through which the fluid, during compression may travel, a large damping effect is created. Of note, both positions (rebound and compression positions) of FIGS. 18A and 18B, respectively, may use a similar cartage fashion control valve as is shown in FIGS. 18C and 18D.

FIG. 18C is an enlarged cross-sectional view of Detail A of FIG. 18A. FIG. 18A shows the orifice 1818, the reservoir 1820, the piston 1804, the shims 1806, the valve member 1808, the primary valve 1810, and a second valve 1822. It should be appreciated that the port within FIG. 18C showing the second valve 1822 may use any applicable metering device such as a pilot operated and non-pilot operated spool-type valve, poppet type valves and pressure relief valves. Further, the second valve 1822 may be the variable pressure valve mentioned above, or another type of fluid metering device. The robustness of the design of the electronic valve 460 is due in part to the placement of the primary valve 1810 below the valve member 1808, which itself is placed directly against the shims 1806. The second valve 1822 will provide an additional form of damping, in one embodiment.

FIG. 18D is an enlarged cross-sectional view of Detail A of FIG. 18A. FIG. 18D shows a type of metering device 1824 placed into the area at which the second valve 1822 was shown (see FIG. 18C). Known in the art is a proportionally controlled pilot operated spool valve placed in the "modular valve port location", also known as a location for the second valve 1822. These valves that occupy the location for the second valve 1822 may be actuated through electronic means such as a solenoid, stepper motor or servo motor, according to an embodiment.

FIG. 18E is a side cross-sectional view of a solenoid and surrounding components, in accordance with an embodiment. FIG. 18E shows a novel method of applying a solenoid to increase the ease of vehicle packaging. In this method, the shaft is used for the solenoid housing and will conduct the magnetic field to the solenoid plunger 1830 so as to produce movement of the metering control device 1824, in accordance with an embodiment. Embodiments also allow for the moving parts to be wet or under pressure so as not to have seal friction of a pressure differential requiring a higher output of force for actuation. The solenoid plunger 1830 is sealed into the shaft using a press fit plug 1828. The coil 1826 surrounds the shaft, similar to other known methods regarding solenoids. According to embodiments, the coil must have enough stiffness to support the load of the main vehicle spring that surrounds the shock

17

absorber. Another method is to use a snap ring fitting onto the shaft in order to separate the spring forces from the coil **1826**. This snap ring design may be used as a separate nonintegrated device that is 90 degrees oriented out of the eyelet of the shock absorber.

FIG. **18F** shows an enlarged cross-sectional side view of Detail A of FIG. **18A**, during compression, in accordance with an embodiment. As seen, the electronic valve **460** is in soft position, such that the flow ports **1812** are open and fluid may flow there through. Thus, during compression, the fluid flow **1836** moves through the orifice **1818** and into the area of the second valve **1822**, and then through the flow ports **1812**. The fluid flow moves into the reservoir **1832** and then provides a force against the valve member **1808**, which itself presses further against the shims **1806**.

FIG. **18G** shows an enlarged cross-sectional side view of Detail A of FIG. **18A**, during compression, in accordance with an embodiment. As seen, the electronic valve **460** is in firm position, in which the flow ports **1812** are blocked. Thus, the fluid flow **1838** moves through the orifice **1818** and into the primary valve **1810**, thereby pushing the valve member **1808** further against the shims **1806**, in one embodiment. It should be noted that the shims **1806**, in one embodiment, are reed valves.

FIG. **18H** shows an enlarged cross-sectional side view of Detail A of FIG. **18A**, during rebound, in accordance with an embodiment. As seen, the valve member **1808** is positioned on the compression side of the piston **1804**. The fluid flow **1842** shows the flow of fluid moving through the flow ports **1812**, into the orifice **1828**, and out into the reservoir **1820**.

FIG. **18I** shows an enlarged cross-sectional side view of Detail A of FIG. **18A**, during rebound, in accordance with an embodiment. As seen, the valve member **1808** is positioned on the compression side of the piston **1804**. The fluid flow arrow **1844** shows the flow of fluid moving from the reservoir **1832**, into and through the piston **1804**, and into the primary valve **1810**. Once the fluid is in the primary valve **1810**, then the fluid presses against the valve member **1808**, which in turn presses against the shims **1806**.

FIG. **18J** is a side cross-sectional view of the electronic valve **460** acting as the base valve assembly. In various embodiments, the design of the electronic valve to be located next to the piston of the monotube by-pass shock absorber is the same design as that electronic valve to be located as the base valve design. Of note, the electronic valve of FIG. **18J** also includes check valves **1848** and compression valves **1850**.

As noted and as will be described below, embodiments of the new technology may be implemented at least in the following design types: 1) a monotube design; 102) a monotube internal bypass design; and 3) a twin-tube design.

1) Monotube Shock Absorber Design with Integrated Variable Pressure Valve: A brief description of a monotube shock absorber design is as follows. A monotube shock absorber has a single cylinder that is divided by a floating piston and seal into a fluid area section and a high pressure gas chamber section. The piston and the shaft move in the fluid portion. It uses a single fluid valve assembly in the piston. There is no need for an air or gas in the fluid area. This provides an expansion area for the excess fluid movement during the compression stroke. On more aggressive movement, the floating piston is pushed further into the gas chamber with increases gas pressure quickly and provides additional damping.

FIG. **18K** shows an electronic valve **460** integrated into a monotube design of a shock absorber, with a piggy back chamber, in accordance with an embodiment. The electronic

18

valve **460** operates as the base valve. (Of note, the monotube design may operate without a base valve.) FIG. **18L** shows an enlarged cross-sectional view of the base valve electronic valve **460** of Detail A of FIG. **18K**, in accordance with an embodiment. A general description of the monotube design in operation is as follows. The electronic valve **460** is utilized as the base valve, in this embodiment. The shaft **1853** is displaced into the chamber **1856** for shaft displacement (fluid chamber). This monotube design includes an internal floating piston (IFP) **1859** that moves backwards and forwards depending on the shaft's **1853** displacement and/or thermal expansion of the fluid. In this case, the IFP **1859** moves toward the side opposite that of the shaft **1853**, making room for that fluid that is being displaced as a result of the shaft displacement. The fluid is displaced into the external shaft displacement reservoir **1858**, shown to be on one side of the IFP **1859**. Within this design, there are two pistons: the main damping piston **1855** affixed to the piston rod **1854**; and the IFP **1859** which separates the gas charge (the spring) and the oil (fluid).

More particularly, during compression, the shaft **1853** along with the piston rod **1854** enters the chamber **1856**, thereby also pushing the damping piston **1855** further into the chamber **1856**. The damping piston **1855** takes up volume within the chamber **1856**, and creates a fluid flow **1857** toward the electronic valve **460**, acting as the base valve. As can be seen in the enlarged view of the electronic valve **460**, the fluid flows into the passageway leading to the electronic valve **460**. The check valve **1861** is found to be closed. Also shown in FIG. **18L** is the primary valve **1814** that is pressed against the reed shims **1806**. When the check valve **1861** is closed, the fluid flows through the reed shims **1806**, which open upon receiving the force of the fluid flow (of note, this may be any sort of compression valve appropriate to regulate fluid flow there through), and into the external shaft displacement reservoir **1858**. The fluid also flows, to some small degree, through the orifice **1818** and then through the pressure variable valve **1814** and into the external shaft displacement reservoir **1858**. When enough fluid enters the external shaft displacement reservoir **1858**, that fluid takes up its volume and then pushes against the IFP **1859**. The IFP **1859**, upon being pushed during compression of the shock absorber, further enters the gas chamber **1860**, which acts as a spring, and hence another source of damping, in accordance with embodiments.

FIG. **18M** shows the monotube design **1852** in a rebound position, in accordance with an embodiment.

FIG. **18N** shows an enlarged view of the electronic valve **460** shown in Detail A of FIG. **18M**, in accordance with an embodiment. During rebound of the shock absorber, the shaft **1853** and the piston rod **1854** move out of the chamber **1856**, thereby also pulling the damping piston **1855** further toward the end of the chamber **1856** that is opposite the end with the electronic valve **460** coupled therewith. A vacuum of fluid flow **1863** is created, wherein the fluid flow **1863** is directed toward the damping piston **1855** that is moving in the same directions as the shaft **1853**, in one embodiment. During rebound, the check valve **1861** is open. The fluid flow **1863** from the external shaft displacement reservoir **1858**, through the channel connecting the chamber **1856** and the external shaft displacement reservoir **1858**, and into the chamber **1856** is unimpeded. For example, the check valve **1861** is open during rebound. Fluid flow generally takes the path of least resistance. Thus, the fluid, during rebound, and in response to the vacuum of fluid that is created by the shaft **1853** being pulled out of the chamber **1856**, does not flow back through the electronic valve **460** (such as through the

pressure variable valve **1814** and then through the reed shims **1806**). Instead, the path of least resistance is the gap left by the check valve **1861** while it is open during rebound movement. Thus, the fluid flows from the external shaft displacement reservoir **1858**, through the check valve **1861**, and into the chamber **1856**, according to one embodiment. Additionally, the gas spring and/or the coil spring within the gas chamber **1860** facilitates the movement of the fluid flow from the external shaft displacement reservoir **1858** and into the chamber **1856** by pushing the IFP **1859** further into the external shaft displacement reservoir **1858**, in accordance with embodiments.

102) Internal Bypass Monotube Shock Absorber Design with Integrated Variable Pressure Valve: FIG. **18O** shows the electronic valve **460** integrated into an internal bypass monotube design **1863** for a shock absorber, in accordance with an embodiment. FIG. **18P** shows an enlarged view of the electronic valve **460** of Detail A shown in FIG. **18O**. With exception to the bypass holes **1864** located along the wall of the chamber **1856**, during compression and rebound, the components of the internal bypass monotube design **1863** function in the same manner as those components described with respect to FIG. **18K**, in accordance with an embodiment. The bypass holes **1864** function as follows. As the shaft **1853** moves more deeply into the chamber **1856**, the damping piston **1855** creates a fluid flow **1857** toward the electronic valve **460**. In so doing, the fluid flows past the bypass holes **1864**. Some of the fluid enters the bypass holes **1864** and travels through an annular chamber **1865** and back to the rebound reservoir chamber **1866**, in accordance with embodiments. Once the damping piston **1855** travels past the location of the bypass holes **1864**, no more fluid from the compression side of the damping piston **1855** moves through the bypass holes **1864**. During rebound, compression process is reversed and the check valve **1861**, as was described with respect to the monotube design **1852** of FIG. **18K**, is open. On note, the base valve circuitry is the same as the monotube design **1858** and the internal bypass monotube design **1863**.

3) Twin Tube Shock Absorber Design with Integrated Variable Pressure Valve: A brief description of a twin tube shock absorber design is as follows. A twin tube shock absorber has an inner and outer cylinder. The inner cylinder is a working cylinder, in which a piston and shaft move up and down. The outer cylinder serves as a reservoir for a hydraulic fluid. There are fluid valves in the piston and in the stationary base valve. The base valve controls the fluid flow between both cylinders and provides some of the damping force. The valves in the piston control most of the damping.

FIG. **18Q** is a side section view of a twin tube design **1878** in a compression state, in accordance with an embodiment. Of note, the damping piston **1868** does not have any valves there through, such that the movement of the shaft **1869**, which pushes the damping piston **1868** into the reservoir **1875**, causes the fluid flow **1870** toward the left valve **1872**, in accordance with an embodiment. The check valve **1871** is closed. The fluid then moves through the left electronic valve **1872**, turns a corner, flows around the right electronic valve **1873**, and then flows through the open check valve **1872**, and down into the outer part **1874** of the tube. From the outer part **1874** of the tube, the fluid flows into the backside **1876** of the damping piston **1868**. When the twin tube experiences a rebound positioning, the aforementioned fluid flow process is reversed. Of note, only the amount of fluid reflows that actually fits within the backside **1876** of the damping piston **1868**.

Additionally, in between the two electronic valves **1872** and **1873** that are positioned in parallel with each other, is a cavity that connects to the IFP cavity **1877**, in one embodiment. In this embodiment, one of the electronic valves works for compression and the other electronic valve works for rebound, while the damping piston is being used as a pump.

FIG. **18R** is a side section view of the twin tube design **1878** in a compression state, including a section view from the two electronic valves positioned in parallel with each other, in accordance with an embodiment. Of note, the fluid flow **1870** shown in FIG. **18R** is the same as that described with respect to FIG. **18Q**.

Example Computer System Environment

With reference now to FIG. **3**, all or portions of some embodiments described herein are composed of computer-readable and computer-executable instructions that reside, for example, in computer-usable/computer-readable storage media of a computer system. That is, FIG. **3** illustrates one example of a type of computer (computer system **300**) that can be used in accordance with or to implement various embodiments which are discussed herein. It is appreciated that computer system **300** of FIG. **3** is only an example and that embodiments as described herein can operate on or within a number of different computer systems including, but not limited to, general purpose networked computer systems, embedded computer systems, routers, switches, server devices, client devices, various intermediate devices/nodes, stand alone computer systems, distributed computer systems, media centers, handheld computer systems, multimedia devices, and the like. Computer system **300** of FIG. **3** is well adapted to having peripheral non-transitory computer-readable storage media **302** such as, for example, a floppy disk, a compact disc, digital versatile disc, other disc based storage, universal serial bus “thumb” drive, removable memory card, and the like coupled thereto.

System **300** of FIG. **3** includes an address/data bus **304** for communicating information, and a processor **306A** coupled with bus **304** for processing information and instructions. As depicted in FIG. **3**, system **300** is also well suited to a multi-processor environment in which a plurality of processors **306A**, **306B**, and **306C** are present. Conversely, system **300** is also well suited to having a single processor such as, for example, processor **306A**. Processors **306A**, **306B**, and **306C** may be any of various types of microprocessors. System **300** also includes data storage features such as a computer usable volatile memory **308**, e.g., random access memory (RAM), coupled with bus **304** for storing information and instructions for processors **306A**, **306B**, and **306C**.

System **300** also includes computer usable non-volatile memory **310**, e.g., read only memory (ROM), coupled with bus **304** for storing static information and instructions for processors **306A**, **306B**, and **306C**. Also present in system **300** is a data storage unit **312** (e.g., a magnetic or optical disk and disk drive) coupled with bus **304** for storing information and instructions. System **300** also includes an optional alphanumeric input device **314** including alphanumeric and function keys coupled with bus **304** for communicating information and command selections to processor **306A** or processors **306A**, **306B**, and **306C**. System **300** also includes an optional cursor control device **316** coupled with bus **304** for communicating user input information and command selections to processor **306A** or processors **306A**, **306B**, and

306C. In one embodiment, system 300 also includes an optional display device 318 coupled with bus 304 for displaying information.

Referring still to FIG. 3, optional display device 318 of FIG. 3 may be a liquid crystal device, cathode ray tube, plasma display device or other display device suitable for creating graphic images and alphanumeric characters recognizable to a user. Optional cursor control device 316 allows the computer user to dynamically signal the movement of a visible symbol (cursor) on a display screen of display device 318 and indicate user selections of selectable items displayed on display device 318. Many implementations of cursor control device 316 are known in the art including a trackball, mouse, touch pad, joystick or special keys on alphanumeric input device 314 capable of signaling movement of a given direction or manner of displacement. Alternatively, it will be appreciated that a cursor can be directed and/or activated via input from alphanumeric input device 314 using special keys and key sequence commands. System 300 is also well suited to having a cursor directed by other means such as, for example, voice commands. System 300 also includes an I/O device 320 for coupling system 300 with external entities. For example, in one embodiment, I/O device 320 is a modem for enabling wired or wireless communications between system 300 and an external network such as, but not limited to, the Internet.

Referring still to FIG. 3, various other components are depicted for system 300. Specifically, when present, an operating system 322, applications 324, modules 326, and data 328 are shown as typically residing in one or some combination of computer usable volatile memory 308 (e.g., RAM), computer usable non-volatile memory 310 (e.g., ROM), and data storage unit 312. In some embodiments, all or portions of various embodiments described herein are stored, for example, as an application 324 and/or module 326 in memory locations within RAM 308, computer-readable storage media within data storage unit 312, peripheral computer-readable storage media 302, and/or other tangible computer-readable storage media.

Example System for Controlling Vehicle Motion of a Vehicle with More than Two Wheels (e.g., Truck, Car, Side-by-Side)

The system 400 (of FIG. 4A) for controlling vehicle motion is described in relation to controlling the operation of a multi-wheeled vehicle that has more than two wheels, such as, but not limited to, trucks, cars, and more specialized vehicles such as, but not limited to side-by-sides and snowmobiles, in accordance with embodiments. It should be appreciated that while the following discussion focuses on vehicles with four wheels, it should be appreciated that embodiments are not limited to controlling the operation upon vehicles with four wheels. For example, embodiments may be used with vehicles with three wheels, five wheels, six wheels, etc. Four-wheeled vehicles may have four vehicle suspension dampers attached therewith, one vehicle suspension damper attached to each wheel and to the vehicle's frame. In one embodiment, the system 400 includes an electronic valve 460, as shown in FIG. 4A. The electronic valve, in one embodiment, includes the orifice block 122, the primary valve 132 and a valve 490. The valve 490, in one embodiment, is the pilot valve assembly 112. In another embodiment, the valve 490 is a variable pressure valve 462.

The system 400 and method, as will be described, detects rolls, pitches, and heaves of four-wheeled vehicles. For example and with regard to detecting rolls, if a car turns a

corner sharply left and begins to roll to the right, embodiments sense the velocity of the steering wheel as it is being turned, as well as the translational acceleration associated with the roll experienced by the vehicle. The translational acceleration (distance/time²) associated with the roll measures side accelerations. In response to this sensing and in order to control the roll, a control system causes the outer right front and back vehicle suspension dampers to firm up, in some embodiments. Of note, in some embodiments, the vehicle's pitch is measured by sensing the velocity of the throttle pedal as it is being pressed and/or released. In other embodiments, the vehicle's pitch may also be measured by sensing the velocity and/or the position of the throttle pedal as it is being pressed and/or released. In yet other embodiments, the vehicle's pitch is measured by sensing the acceleration of the vehicle. Of further note, the control system does not utilize throttle pedal information to measure roll.

As noted, FIG. 4A is a block diagram of a system 400 for controlling vehicle motion, in accordance with an embodiment. In one embodiment, the system 400 includes the electronic valve 460 (that includes the same component as the electronic valve 100 shown in FIG. 1 or includes the same components as the electronic valve 460 shown in FIGS. 4A & 4B) and the control system 404. It should be appreciated that the orifice block 122 (including the orifice 124) and the primary valve 132 of the electronic valve 460 operate in a similar manner as is described herein in regard to the electronic valve 100 of FIG. 1, in accordance with embodiments.

In one embodiment, the control system 404 includes the following components: a control signal accessor 456; a first comparator 406; a second comparator 410; a valve monitor 452; a control mode determiner 454; and an activation signal sender 450. Of note, the control signal accessor 456, the first comparator 406, and the valve monitor 452 have similar features and functions as the control signal accessor 1730, the comparator 172, the valve monitor 1745, and the activation signal sender 1750, respectively. The second comparator 410 compares the accessed user-induced inputs to predetermined user-induced inputs threshold values 448 found at, in one embodiment, the database 416 (in another embodiment, a database residing external to the control system 404. Further, in various embodiments, the control system 404 optionally includes any of the following: a database 416, a hold-off timer 426; a tracker 430; a hold logic delayer 432; a rebound settle timer 428; a weightings applicator 434; and a signal filter 436. The database 416, according to various embodiments, optionally includes predetermined acceleration threshold values 418 and predetermined user-induced inputs threshold values 448. In various embodiments, the predetermined user-induced inputs threshold values 448 include predetermined velocity threshold values 420. In other embodiments, the predetermined user-induced inputs threshold values include any of the following values: steering velocity threshold value; shock absorber velocity threshold value; brake velocity threshold value; steering position threshold value; throttle position threshold value; shock absorber position threshold value; and brake threshold value.

In one embodiment, the control system 404 may be part of the vehicle suspension damper 402 (that is, for example, on a side-by-side), or it may be wire/wirelessly connected to the control system 404. As will be discussed below, the control system 404 of system 400 is further configured for comparing a set of values associated with at least one user-induced input (such as a user turning a steering wheel

and the velocity resulting therefrom) with at least one user-induced input threshold value.

In brief, and with reference to FIGS. 1, 4A and 4B, embodiments provide for a control system 404 that accesses a set of control signals 442 (control signal 442A, control signal 442B and control signal 442C; it should be appreciated that there may be any number of control signals, depending on the number of sensors coupled with vehicle components) that includes both acceleration values and a set of values associated with user-induced inputs (such as velocity values [of a steering wheel being turned and/or a throttle pedal being pressed upon and/or released] measured by a set of gyrometers). It should be appreciated that the set of sensors 440A, 440B and 440C (hereinafter, set of sensors 440, unless specifically noted otherwise) attached to the vehicle component 438A, 438B and 438C (hereinafter, vehicle component 438, unless specifically noted otherwise), respectively, may include one or more sensors, such as, but not limited to, accelerometers and gyrometers. In some embodiments, the acceleration values with respect to the four-wheeled vehicles are lateral (side-to-side motion) and longitudinal g's (forward and backwards motion). In other embodiments, the acceleration values with respect to four-wheeled vehicles are lateral g's, longitudinal g's and vertical g's (up and down motion). User-induced inputs, according to embodiments, are those inputs by a user that cause a movement to a vehicle component of the vehicle. For example, user-induced inputs may include, but are not limited to any of the following: turning a steering wheel; pressing a brake pedal (the ON/OFF resultant position of the brake pedal being pressed is measured); and pressing a throttle pedal (a velocity and/or position of the throttle pedal is measured). Thus, a set of values associated with the user-induced inputs may be, but are not limited to being, any of the following user-induced inputs: a measured velocity value of the turning of a steering wheel; a brake's on/off status; velocities associated with pressing down on the brake and/or the throttle pedal; and the difference in the positions of the throttle pedal before and after being pressed (or the absolute throttle position). Of note, the user-induced inputs that are measured are inputs received before acceleration is measured, yet relevant in quickly determining corrective damping forces required to control the roll, pitch and heave once experienced. Thus, the user-induced inputs are precursors to the sensed accelerations of various vehicle components (e.g., vehicle wheels).

Once these values (measured acceleration value and the set of values associated with the user-induced inputs) are accessed by the control signal accessor 456, the first comparer 406 and the second comparer 410 compare these values to threshold values, such as those found in the database 416 (a store of information). Further, according to embodiments, the activation signal sender 450 sends an activation signal to the power source 458 to deliver a current to the electronic valve 460, and more particularly, a valve (e.g., of the variable pressure valve 464), based upon the following: 1) the comparison made between the measured acceleration value and the predetermined acceleration threshold value 418 discussed herein; 2) the comparison made between the measured velocity of the steering wheel as it is being turned (the set of values associated with user-induced inputs) and the predetermined velocity threshold value 420 of the predetermined user-induced inputs threshold values 448; and 3) the monitoring of the state of the electronic valve 460.

It should be appreciated that embodiments may include, but are not limited to, other configurations having a control

system in wire/wireless communication with the vehicle suspension damper to which it is controlling, such as: 1) a vehicle with only one control system that is wire and/or wirelessly connected to all vehicle suspension dampers attached thereto; 2) a vehicle with one control system attached to one vehicle suspension damper, wherein the one control system controls the other control systems attached to other vehicle suspension dampers (that are attached to different wheels) of the vehicle; and 3) a vehicle with one control system that is not attached to a vehicle suspension damper, wherein the one control system controls other control systems that are attached to vehicle suspension dampers on the vehicle.

In embodiments, the system has at least four user selectable modes: a soft mode; a firm mode; an auto mode; and a remote mode. Further, embodiments enable modes there between the at least four user selectable modes.

According to embodiments, in the soft mode, all the vehicle suspension dampers are soft for compression and rebound.

According to embodiments, in the firm mode, all rebound and/or compression are firm. The firmness of the rebound and/or compression is adjustable through system settings. In one embodiment, the adjustable system settings are factory set and are finite in number. In another embodiment, an infinite number of adjustable system settings are provided. In yet another embodiment, the user may customize and re-configure a finite number of system settings.

According to embodiments, in the auto mode, all vehicle suspension dampers are placed in the soft setting with the control system transiently setting various vehicle suspension dampers to be firm.

In the remote mode, a wireless browser interface enables the soft, firm and auto mode to be selected. In one embodiment, the control system 404 monitors the position setting of a mechanical switch positioned on the vehicle, wherein the position setting may be set at one of the following modes: soft; firm; auto; and remote (i.e., at least partially wireless). Compression and rebounds are used to reduce the tilt of the vehicle frame. Particular advantages associated with using rebound adjustments are at least the following: a vehicle suspension damper in a hard rebound mode lowers the vehicle's center gravity; and the suspension is allowed to compress and absorb bumps while performing a controlled turn, thereby reducing the feeling of a harsh ride.

When the vehicle suspension damper is in the auto mode, the control system 404 causes the damping force within the vehicle suspension dampers to be adjusted when the trigger logic described below is found to be accurate for the roll and pitch positive and negative modes. The desired state of the vehicle suspension damper that is achieved from this adjustment is considered to be a control mode. "Trigger Logic" is logic implemented by the control system 404 that determines whether or not the vehicle suspension damper is allowed to pass into one of the control modes when the vehicle suspension damper is in an auto mode. Operational examples of trigger logic implemented by the control system 404 are described below. "Hold Logic" is logic that is implemented by the control system 404 that holds the system in a given control mode even after the possibly transient trigger logic has become false (becomes inaccurate). Operational examples of hold logic implemented by the control system will be described below.

Embodiments also provide various damper control settings available to be implemented for each control mode. A damper control setting is one in which the damping force

within the vehicle suspension damper is adjusted for one or more of the vehicle suspension dampers attached to the vehicle.

In embodiments, the vehicle's roll and pitch are ultimately determined from measuring the vehicle's acceleration and measuring the vehicle component movement caused by user-induced inputs. In measuring the vehicle's roll and pitch, both have defined positive and negative directions. For example, the vehicle axis is defined as having an x-axis, a z-axis, and a y-axis. The x-axis is defined as being out the front of the vehicle. The z-axis is defined as being up. The y-axis is defined as following the right hand rule, which means the y-axis is out the left side of the vehicle.

Thus, a roll positive mode is defined as a positive rotation about the x-axis of the vehicle associated with a left turn. A roll negative mode is defined as a negative rotation about the x-axis of the vehicle associated with a right turn.

A pitch positive mode, occurring during a dive, is defined as a positive rotation about the y-axis of the vehicle associated with braking. A pitch negative mode, occurring during a squat, is defined as a negative rotation about the y-axis of the vehicle associated with throttling.

Below is a description of the control modes: 1) roll positive and roll negative control modes; 2) pitch positive control mode—dive; and 3) pitch negative control mode—squat. Further, the trigger and hold logic associated with each control mode and the damper control setting options available for each control mode, is also described in accordance with various embodiments:

It should be appreciated that information associated with the control modes, the trigger and hold logic associated with each control mode and the damper control setting options available for each control mode are stored, in one embodiment, in the database 416. The information is accessible by the first comparer 406, the second comparer 410 and the control mode determiner 454.

1) Roll Positive and Roll Negative Control Modes—Trigger Logic, Hold Logic, and Damper Control Settings Available

Upon exceeding a threshold (defined by the trigger logic below) while the vehicle experiences a roll positive or a roll negative, the control system 404 causes the variable pressure valve 464 to adjust to achieve a control state in which the roll positive and the roll negative are reduced or eliminated. Implementation options also available to achieve such a control state are listed below. With regard to the roll positive and roll negative controls that define circumstances when the roll positive and roll negative control modes are triggered or the control modes are held in place, the following definitions apply:

“ThreshSteerVelTrigger”—This is the threshold required for steering wheel velocity to trigger a roll control, subject to the side acceleration being above at least “threshSideAccelRollAllow”. The main advantage of triggering a damping force change on steering wheel velocity over side acceleration is that the side acceleration signal lags that of the signal for the velocity value corresponding to the turning of the steering wheel. This threshold is adjustable and may be tuned for trigger and hold logic (tuned by the end user or hard coded).

“ThreshSideAccelRollAllow”—This is the threshold required for side acceleration to allow threshSteerVelTrigger to trigger roll control. The threshSideAccelRollAllow is nominally set less than zero given that it is used to ensure the

steering wheel velocity signal is not inconsistent with the side acceleration signal which, for example, would be the case in a counter steer maneuver. Setting this threshold too high adversely affects the system response time by forcing it to wait for the side acceleration signal to build up. This threshold is adjustable and may be tuned for trigger and hold logic (tuned by the end user or hard coded).

“ThreshSideAccelRollTrigger”—This is the threshold required for side acceleration to trigger roll control, without the need for any other trigger. This allows the system to initiate roll control even if the steering wheel velocity signal does not. This is nominally set high on the order of 0.7 g or greater, values that are normally only reached in a sustained turn. This condition could be reached, for example, when coming out of a corner steer maneuver, or if the terrain were to help turn the vehicle sideways. This threshold is adjustable and may be tuned for trigger and hold logic (tuned by the end user or hard coded).

“ThreshSideAccelRollHold”—This threshold is required for side acceleration to keep the system in roll control after it's already triggered. The level of side acceleration required to stay in roll control should be lower than the value required to trigger it. This adds hysteresis to the system and reduces the tendency to bounce in and out of the control mode when the signals are near their thresholds. Nominally, this value is set between may be 0.2-0.5 g's. This threshold is adjustable and may be tuned for trigger and hold logic (tuned by the end user or hard coded).

“ThreshSteerPosHold”—This threshold is required for the steering wheel angle to keep the system in roll control. This threshold is adjustable and may be tuned for trigger and hold logic (tuned by the end user or hard coded).

1) Roll Positive and Roll Negative Control Logic
A. Roll Positive Control and Roll Negative Control Trigger Logic

- i. Roll Positive Control Trigger Logic:
 - a. ((steer velocity>threshSteerVelTrigger) AND (side acceleration>threshSideAccelRollAllow)); OR
 - b. (side acceleration>threshSideAccelRollTrigger).
- ii. Roll Negative Control Trigger Logic:
 - a. ((steer velocity<threshSteerVelTrigger) AND (side acceleration<threshSideAccelRollAllow)); OR
 - b. (side acceleration<threshSideAccelRollTrigger).

B. Roll Positive Control and Roll Negative Control Hold Logic

- i. Roll Positive Control Hold Logic:
 - a. (side acceleration>threshSideAccelRollHold); OR
 - b. (steer position>threshSteerPosHold).
- ii. Roll Negative Control Hold Logic:
 - a. (side acceleration<threshSideAccelRollHold); OR
 - b. (steer position<threshSteerPosHold).

C. Roll Positive Control and Roll Negative Damper Control Settings Available

- Option 1: Firm inside rebound front and back.
Option 2: Firm outside compression front and back.
Option 3: (1) Firm inside rebound front and back; and (2) Firm outside compression front and back.
Option 104: (1) Firm inside rebound front and back; (2) Firm outside compression front and back; and (3) Firm outside rebound front and back.

In discussion of embodiments comparing the measured values to the threshold values, the following example is given with regard to trigger logic. A driver of a vehicle turns a steering wheel to the left. The vehicle then turns left. As a result of these actions, the steering wheel has a velocity value associated with it, and the vehicle has a side acceleration associated with it.

A control signal accessor **456** of the vehicle accesses a set of control signals **442** that includes the measured side acceleration value and the measured steering wheel velocity value. The first comparer **406** compares the measured side acceleration value to the predetermined acceleration threshold values **418** (stored at the database **416**). The first comparer **406** determines if the measured acceleration value is more or less than the predetermined acceleration threshold value. The first comparer **406** accesses the database **416** to find trigger logic that matches the statement in which the comparison between the measured acceleration value and the predetermined acceleration threshold value holds true.

The trigger logic is linked to a particular control mode that is pre-assigned to that particular trigger logic. If the trigger logic describes the comparison between the measured values and the predetermined threshold values accurately, then the trigger logic is determined to be true. The control system **404** will then actuate the valve within the electronic valve **100** according to the control mode assigned to the trigger logic statement.

Continuing with the example above, the first comparer **406** finds that the measured side acceleration value was greater than the predetermined side acceleration threshold value. The second comparer **410** finds that the measured steering wheel velocity value is greater than the predetermined user-induced input threshold value.

As described herein, one set of trigger logic that is linked to the roll positive control, is as follows:

- a. ((steer velocity>threshSteerVelTrigger) AND (side acceleration>threshSideAccelRollAllow)); OR
- b. (side acceleration>threshSideAccelRollTrigger).

Accordingly, if either of the statements “a” or “b” above is found to be accurate, then the control mode determiner **454** determines which control mode is linked to these logic statements. Once the control mode is determined, the control system **404** actuates a valve (e.g., pilot valve assembly **132**) within the electronic valve **100** to adjust the vehicle suspension damper. In this example, the first comparer **406** found that the following statement is accurate: (side acceleration>threshSideAccelRollTrigger). The control mode determiner **454** determines that the accurate statement is linked to the roll positive control. Knowing under what control mode the vehicle suspension damper should operate (e.g., roll positive control, roll negative control), the control system **404** actuates the electronic valve **100**, and more particularly, the pilot valve assembly **132** therein. Thus, in this embodiment, the control system **404** is enabled to implement the roll positive control mode, according to at least the options discussed herein with regard to the roll positive control mode.

Further, in this situation, the second comparer **410** finds that the steer velocity value is greater than the predetermined steer velocity threshold value (of the predetermined velocity threshold values **420**). Thus, the second comparer **410** finds the following first portion of a statement to be accurate: ((steer velocity>threshSteerVelTrigger). The second portion of the statement, (side acceleration>threshSideAccelRollTrigger), has already been compared and determined to be accurate.

Thus, in one embodiment, the control mode determiner **454** may determine a control mode for a vehicle suspension damper in which trigger logic that includes only acceleration comparisons are used. However, in another embodiment, the control mode determiner **454** may determine a control mode for a vehicle suspension damper in which trigger logic includes both acceleration comparisons and user-induced inputs comparisons.

The control mode determiner **454** operates in a similar manner in interpreting the trigger logic and hold logic linked to other control modes. Thus, in one embodiment, should the trigger logic (a.k.a. control logic) be determined to be accurate, the control mode determiner **454** follows the link from the trigger logic to find the control mode setting.

In discussion of embodiments comparing the measured values to the threshold values, the following examples are given with regard to hold logic. There are at least several situations that occur in which the system is held in a given control mode even after the trigger logic has become false. Below, examples are given of a few of these cases. For the three example scenarios described below, the following threshold values are set in the control system: the steering velocity threshold (“threshSteerVelTrigger”) value is 10 rad./sec.; the acceleration trigger threshold (“threshSideAccelRollTrigger”) value is 0.7 g’s; the acceleration hold threshold (“threshSideAccelRollHold”) value is 0.2 g’s; and the acceleration allow threshold (“threshSideAccelRollAllow”) value is -0.1 g’s.

With reference to FIG. **4A**, a first example scenario involves the triggering of an adjustment of the vehicle suspension dampers upon receiving a steering wheel velocity measurement, but the holding of the control mode as to the vehicle suspension damper upon receiving a particular side acceleration value. For example, a vehicle rider turns a steering wheel while the vehicle is directed into a turn. The set of sensors **440** (could be set of sensors **440A**, **440B** and/or **440C**; it should be appreciated that there could be more or less sets of sensors, depending on the quantity of vehicle components to which the sets of sensors may be attached) send a velocity signal to the control signal accessor **456**. The second comparer **410** compares the measured velocity value of 15 rad/sec. to the predetermined velocity threshold values **420** and to the trigger logic also stored at the database **416** and determines that the measured velocity value of 15 rad/sec. is higher than the predetermined velocity threshold value of 10 rad/sec. The set of sensors **440** also sends to the control signal accessor **456** a side acceleration value of 0.4 g’s. The first comparer **406** compares the measured side acceleration value of 0.4 g’s to the predetermined acceleration trigger threshold value of the predetermined acceleration threshold values **418** and to the trigger logic also stored at the database **416** and determines that the measured side acceleration value of 0.4 g’s is lower than the predetermined acceleration trigger threshold value for side acceleration of 0.7 g’s. Since at least one of the trigger logics, namely, the steering wheel velocity, is true, then the control system **404** is triggered to cause the power source **458** to be actuated such that the electronic valve **100** receives a current. The current causes the electronic valve to close into the firm mode.

However, after a small amount of time (e.g., a fraction of a second) during the turn, since the steering wheel is no longer being moved into a sharper or less sharp turning position, the steering wheel velocity value lessens to a value close to zero. Thus, the trigger logic has become false, even though, the vehicle is still experiencing g’s and is still turning. Without “hold logic” (“threshSideAccelRollHold” of 0.2 g’s), the control system **404** would be triggered to cause the vehicle suspension damper to return to the soft mode (by causing the electronic valve **100** to open). In this example, the logic requires the side acceleration value to fall below 0.7 g’s before the control system **404** is possibly triggered to adjust the damping of the vehicle suspension damper. However, the side acceleration g’s that the vehicle is experiencing remains close to 0.4 g’s throughout the turn,

which is greater than 0.2 g's (the acceleration hold threshold value), the control system 404 does not cause the vehicle suspension damper to be adjusted throughout the turn. When the vehicle then begins moving in a straight path, the side acceleration values fall below 0.2 g's and thus below the "threshSideAccelRollHold" value, and the control system 404 is triggered to cause the vehicle suspension damper to adjust to the soft mode.

With continued reference to FIGS. 4A and 4B, a second example scenario involves the triggering of an adjustment of the vehicle suspension dampers upon receiving a first side acceleration value, and the holding of the control mode as to the vehicle suspension damper upon receiving a second side acceleration value. For example, if a vehicle is traveling down a straight path that has various obstacles causing the vehicle to jump and dip, then the vehicle is caused to rattle back and forth (i.e., from side-to-side). If the side acceleration trigger threshold value was set at 0.2 g's and there was no hold logic, then due to the measured side acceleration from the side-to-side movement, the control system would be constantly triggered to cause the vehicle suspension damper to switch in and out of the hard mode, as if the vehicle were in fact repeatedly turning. Additionally, if "hold logic" was not available to be programmed, then one would either have to program the trigger logic to have low acceleration trigger threshold values of about 0.2 g's and suffer the system constantly falsely triggering on bumps (due to the side-to-side rocking movement) that it perceives as turns, or set the trigger logic to have high acceleration trigger threshold values of about 0.7 g's and suffer the system not staying in the hard mode through an entire turn.

However, since the side acceleration trigger threshold value is set at 0.7 g's, it is not until the vehicle actually moves into a turn that the vehicle experiences g's above 0.7 g's. If the vehicle's side acceleration value is measured at 0.8 g's, then the control system causes the vehicle suspension to adjust to be in the hard mode. The hold logic ensures that the vehicle suspension damper will remain in the hard mode until the side acceleration g's are measured below the acceleration hold threshold value of 0.2 g's.

With continued reference to FIGS. 4A and 4B, a third example scenario involves counter steering. For instance, suppose that a driver turns a steering wheel to the left as he heads into a turn. The steering wheel velocity is measured at 25 rad/sec. and the side acceleration g's are measured at 0.6 g's. Since the steering wheel velocity measured at 25 rad/sec. and the side acceleration g's measured at 0.6 g's are above the steering wheel threshold velocity ("threshSteerVelTrigger") of 10 rad/sec. and the side allow acceleration threshold ("threshSideAccelRollAllow") value of -0.1 g's, respectively, the control system causes the vehicle suspension damper to adjust to the firm mode. Next, while the vehicle is still turning to the left and the vehicle is still experiencing a side acceleration of 0.6 g's, the vehicle driver turns the steering wheel to the right with a velocity of 20 rad./sec. in the right direction. However, even though the steering wheel is being turned to the right at the velocity of 20 rad./sec. and above the steering wheel velocity threshold value of 10 rad./sec., the vehicle is still turning to the left and still experiencing side acceleration g's consistent with turning to the left, namely, positive 0.6 g's. This type of steering wheel action is termed "counter steering". In this example, counter steering is counter to that which is expected, such as when a driver turns a steering wheel to the right, it is expected that the resulting side acceleration g's will be directed to the right (negative Y-axis). However, in counter steering, such as in the foregoing example, the resulting side

acceleration g's are directed to the left (positive). In this example scenario, since the side acceleration allow threshold value is at -0.1 g's; the measured side acceleration for a right turn must be below -(0.1) g's (which is equal to +0.1 g's) (according to the "Roll Negative Control Trigger Logic" described above) for the acceleration allow threshold to be accurate. However, since 0.6 is greater than +0.1 g's, the measured side acceleration as compared to the side acceleration allow threshold value denotes that the trigger allow logic is inaccurate. Therefore, even though the steering velocity value of 20 rad./sec. is measured to be above the steering velocity threshold value of 10 rad./sec., based on the determination of inaccurate trigger acceleration allow logic, the control system will cause the vehicle suspension damper to remain in its current firm mode (will not cause the vehicle suspension dampers to adjust to a soft mode). Of note, following is an example which further explains the relationship between the vehicle, the vehicle's driver, the turning of the vehicle and the experienced acceleration during such a vehicle turn. When a vehicle's driver turns the vehicle to the right, the driver feels as if he is being pushed out the left of the vehicle. However, the vehicle is really being pushed to the right and is pushing the driver to the right also; the driver's inertia is resisting this acceleration. Similarly, when a vehicle's driver applies the brakes to the vehicle, the driver feels as if he is being pushed forward.

Pitch Positive Control Mode

Upon exceeding a threshold (defined by the trigger logic below) while the vehicle is experiencing a pitch positive (e.g., dive), the control system 404 causes the variable pressure valve 464 to adjust to achieve a control state in which the pitch positive is reduced or eliminated. Implementation options also available to achieve such a control state are listed below. With regard to the pitch positive controls that define circumstances when the pitch positive control modes are triggered or the control modes are held in place, the following definitions apply:

"ThreshForwardAccelBrakeAllow"—The forward acceleration is required to be below this threshold in order that the brake-on-signal is allowed to trigger the pitch positive control mode. Note that the forward acceleration is negative during braking. Therefore, this control signal is nominally set greater than zero; given that it is used to ensure that the brake signal is not inconsistent with the forward acceleration. This can be used to detect a driver just touching the brake, or possibly driving with the left foot is pressing on the brake while the right foot is pressing on the throttle pedal. This threshold is adjustable and may be tuned for trigger and hold logic (tuned by the end user or hard coded).

"ThreshForwardAccelBrakeTrigger"—The forward acceleration is required to be below this threshold in order that the pitch positive control may be triggered, even without the brake being engaged. This allows the control system 404 to initiate a pitch positive control mode even if the brake is not detected. This threshold is nominally set below 1 g, effectively negating it. This threshold is adjustable and may be tuned for trigger and hold logic (tuned by the end user or hard coded).

2) Pitch Positive Control Mode—Trigger Logic and Hold Logic

A. Pitch Positive Control—Dive—Trigger Logic

- i. ((brake on) AND (forward acceleration < threshForwardAccelBrakeAllow)); OR
- ii. (forward acceleration < threshForwardAccelBrakeTrigger)

- B. Pitch Positive Control—Dive—Hold Logic
 - i. Forward acceleration<threshForwardAccelBrakeHold.
- C. Pitch Positive Control Damper Control Settings Available
 - Option 1: (1) Firm rear rebound left and right.
 - Option 2: (1) Firm front compression left and right.
 - Option 3: (1) Firm rear rebound left and right; and (2) Firm front compression left and right.
 - Option 4: (1) Firm rear rebound left and right; (2) Soft front rebound left and right; and (3) Soft front compression left and right.

Pitch Negative Control Mode

Upon exceeding a threshold (defined by the trigger logic below) while the vehicle is experiencing a pitch negative (e.g., squat), the control system 404 causes the variable pressure valve 464 to adjust to achieve a control state in which the pitch negative is reduced or eliminated. Implementation options also available to achieve such a control state are listed below. With regard to the pitch negative controls defining circumstances when the pitch negative control modes are triggered or the control modes are held in place, the following definitions apply:

“ThreshThrottle”—This is the threshold required for the derivative of the throttle position to be above in order to trigger the pitch negative control mode, subject to the forward acceleration being above threshForwardAccelThrottleAllow. Pressing down on the throttle and giving the engine more gas is defined as positive throttle. The main advantage of triggering on the time derivative of the throttle position as opposed to simply the forward acceleration is that the acceleration signal lags that of the throttle. The derivative of the throttle is used because, in general, the steady state position of the throttle is related to velocity and not to the acceleration of the vehicle. This threshold is adjustable and may be tuned for trigger and hold logic (tuned by the end user or hard coded).

“ThreshForwardAccelThrottleAllow”—This is the threshold required for forward acceleration to be above in order to allow the derivative of the throttle position signal to trigger pitch negative control. This is used to ensure that the derivative of the throttle position is not inconsistent with the forward acceleration. This can be used to detect when one is driving with the left foot on the brake and the right foot is on the throttle. This threshold value is nominally set below 0 g. This threshold is adjustable and may be tuned for trigger and hold logic (tuned by the end user or hard coded).

“ThreshForwardAccelThrottleTrigger”—This is the threshold required for forward acceleration to be above in order to trigger negative pitch control, even without the changes in the throttle position. This allows the system to initiate negative pitch control even if the throttle is not being pressed. This threshold value is nominally set above 1 g, effectively negating it. This threshold is adjustable and may be tuned for trigger and hold logic (tuned by the end user or hard coded).

“ThreshForwardAccelThrottleHold”—Forward acceleration is required to be above this threshold value in order for the negative pitch control mode to remain in place after its trigger logic has already been triggered. This is necessary given that the derivative of the throttle is used, and there can be relatively long delays in engine response and this signal. This threshold is adjustable and may be tuned for trigger and hold logic (tuned by the end user or hard coded).

- 3) Pitch Negative Control Mode—Trigger Logic and Hold Logic
 - A. Pitch Negative Control—Squat—Trigger Logic
 - i. ((throttle pedal velocity>threshThrottle) AND (forward acceleration>threshForwardAccelThrottleAllow)); OR
 - ii. (forward acceleration>threshForwardAccelThrottleTrigger)
 - B. Pitch Negative Control—Squat—Hold Logic
 - i. Forward acceleration>threshForwardAccelThrottleHold
 - C. Pitch Negative Control Damper—Squat—Control Settings Available
 - Option 1: (1) Firm front rebound left and right.
 - Option 2: (1) Firm rear compression left and right.
 - Option 3: (1) Firm front rebound left and right; and (2) Firm rear compression left and right.
 - Option 104: (1) Firm front rebound left and right; (2) Soft rear rebound left and right; and (3) Soft rear compression left and right.
- 4) Zero Gravity Control Mode

In one embodiment, a zero gravity control mode is attained, at which vehicle suspension dampers that were operating in a “soft” mode, upon a detection of a zero gravity situation, are made to operate in the “firm” mode. For example, a vehicle that is operating in a “soft” mode is traveling in a straight line along a path that initially contains small bumps, but graduates into large rollers. The vehicle initially is placed in the “soft” mode in order to mitigate and/or nullify the effect (upon the vehicle rider) of the vehicle traveling over small bumps along the pathway. At a particular velocity, when the vehicle then moves up one side and over the top of the large roller, on the way down to the bottom of the other side of the roller, the vehicle experiences a free fall.

The vehicle is considered to be in freefall when the resultant magnitude of the X, Y, and Z accelerations is less than a predetermined threshold. The end of the freefall condition will be when the resultant acceleration has exceeded the threshold for a pre-determined amount of time. For example, suppose the pre-determined freefall acceleration threshold is 0.4 g, the calculated resultant acceleration has a magnitude of 0.3 g, and the end-of-freefall timer is 1 second. Since the resultant acceleration is less than the threshold, this is a freefall condition, and the vehicle dampers will be set to the “firm” state. The vehicle will revert to the “soft” state 1 second after the resultant acceleration exceeds 0.4 g.

In explanation of the above described zero gravity control mode example, the following description is proffered. The resultant acceleration is taken by squaring the acceleration at each axis, adding them together, and then taking the square root (the equation is: $\sqrt{(x^2+y^2+z^2)}$). The resultant acceleration is always positive. This equation gives just the magnitude of the resultant acceleration, and does not give information regarding the direction of the resultant acceleration.

- 1) Take the following example scenarios to illustrate the above concept: Vehicle sitting flat on level ground: X,Y,Z accelerations are 0 g, 0 g, 1.0 g. Resultant acceleration is 1.0 g.
- 2) Vehicle sitting upside down on flat level ground: X,Y,Z accelerations are 0 g, 0 g, -1.0 g. Resultant acceleration is 1.0 g.
- 3) Vehicle sitting on flat ground, but on a slope of ‘n’ degrees: X,Y,Z accelerations are 0 g sin(n)g, cos(n)g. Resultant acceleration is 1 g due to trig identity: $\sin^2(x)+\cos^2(x)=1.0$

- 4) Vehicle on flat ground, accelerating forward at 0.5 g; X,Y,Z accelerations are 0 g, 0.5 g, 1.0 g. Resultant acceleration is 1.12 g
- 5) Vehicle on flat ground, driving at constant velocity, but turning so lateral acceleration of 0.5 g; X,Y,Z are seen, and accelerations are 0.5 g, 0 g, 1 g. Resultant acceleration is 1.12 g.

In the first three examples above, the vehicle is in completely different orientations, but the resultant is the same. Likewise, in the last two examples, the components are different, but the resultant is the same. Thus, only the magnitude is calculated (the direction of the resultant acceleration does not matter for the purposes of detecting a freefall condition).

Additionally, as long as the vehicle is touching the ground, the accelerometer will always measure the 1 g acceleration due to gravity. This could be measured all in one axis, or distributed across all three axis. But when the vehicle is not moving, the resultant will always be 1 g as long as the vehicle is on the ground. When the vehicle comes off the ground (like when going off a jump), the 1 g acceleration due to gravity goes away, and the resultant acceleration is 0 g. The only way to have a resultant acceleration of less than 1 g is to go into a freefall.

The freefall mode isn't triggered either when the resultant equals 0 g, or when the resultant is less than 1.0 g. This is due to at least the following four circumstances that occur when measuring actual motion, rather than doing paper calculations:

- 1) The vehicle's engine causes high-frequency vibrations of a fairly high magnitude. Measurements may be as high as 2.0 g and as low as 0 g (so noise of +/-1.0 g of the actual value). Since the vibrations of the engine are generally going to be fairly high (at least 30 Hz with the engine at 2000 RPM) and the actual motion of the vehicle fairly low (usually 1-2 Hz), a low-pass filter may be used to ignore the vibrations from the engine such that only the acceleration of the vehicle is seen. Since filtering the acceleration takes some time, if the threshold is set at 0 g, a freefall scenario may not be noticed in time for a proper response, or the freefall scenario may be completely missed.

- 2) An accelerometer chip is built, there will always be some internal stresses that make it output a non-zero value even when it should. This means that the minimum acceleration the accelerometer might output is 0.05 g. This could be calibrated out, but to avoid a complicated calibration routine, a non-zero threshold is selected for implementation.

- 3) Due to the same stresses mentioned in number "2" above, the output when sitting on the ground might be 0.95 g rather than 1.0 g. So, to be effective, a threshold between 0 g and 1.0 g is needed.

- 4) Since an accelerometer cannot easily be placed at the vehicle's center of mass, the acceleration is measured when the vehicle rotates in the air. Thus, a truly 0 g situation is never seen.

As stated herein, FIG. 4A is a block diagram that includes the control system 404, in accordance with an embodiment. Embodiments of the control system 404 of FIG. 4A further include: a hold-off timer 426; a tracker 430; a hold logic delayer 432; a rebound settle timer 428; a weighting applicator 434; and a signal filter 436.

The hold-off timer 426 may be used when the vehicle suspension damper 402 is in any of the roll and pitch positive and negative control modes. The hold-off timer 426 enables a time to be set between the time that a first trigger logic is passed and the time that a second trigger logic is allowed to be passed. The implementation of the hold-off

timer 426 limits the amount of cycling the vehicle suspension damper 402 will experience between passive damper settings. ("Cycling" refers to the vehicle suspension damper rapidly cycling between the soft and damper firm settings of the dampers. This may or may not be a significant problem for the rider of vehicle performance. Cycling is more wearing on the solenoids and power circuitry of the vehicle suspension damper. If the transients are much faster than the time constants of the vehicle dynamics, then the rider should not directly notice the effects of cycling.) To this end, the control system 404 further optionally includes, in one embodiment, a tracker 430 for tracking the times at which a trigger logic is passed. For example, the tracker 430 tracks the time at which the trigger logic is passed and the hold-off timer 426 is configured to disallow another pass until a minimum hold-off time is reached. If the trigger logic goes false before the hold-off time is reached, the trigger will not pass, and the hold-off timer 426 is not reset. There is only a hold-off timer 426 for going into the damper firm setting, and not coming out of it. This still limits cycling, without increasing the system minimum reaction response time to short stimulus.

In one embodiment, the hold logic delayer 432 is programmed to provide a delay that gives time for the hold logic to become true after the trigger logic goes true. However, this has the disadvantage of increasing the minimum reaction response time of the vehicle suspension damper to even short stimulus (e.g., cycling). An example of where this delay may be useful is if the steering wheel is turned so fast that the side acceleration signals do not build up before the steering velocity signal drops back off again. Theoretically, the side accelerations values should present themselves to the control system as the wheels turn, but this is not necessarily true. For example, there are situations in which the front tires are not getting great traction at an exact moment. Another example in which this delay may be useful is when the gas pedal is slammed down faster than the engine has time to respond.

In one embodiment, the rebound settle timer 428 establishes a period of time for the vehicle suspension to settle down before the compression is set firm. This is a method for controlling the height of the vehicle's center of gravity in firm mode. This method can be reversed through user settings so that the vehicle has increased clearance.

In one embodiment, the weightings applicator 434 resolves the situation in which different system control modes make conflicting requests to the same vehicle suspension damper. The weightings applicator 434 provides weightings associated with each control mode for each of the vehicle suspension dampers that system control mode can affect. Then the weightings applicator 434 implements the request with the highest weighting.

In one embodiment, the signal filter 436 filters the control signals that are accessed by the control system 404. In one embodiment, the control system 404 includes the signal filter 436. In another embodiment, the signal filter 436 is external to the control system 404. The signal filter 436 reduces signal noise levels and helps filter extremely transient signals or glitches. The signal filter 436, in one embodiment, also adds signal latency, which can have various effects on the control system 404 and hence the vehicle suspension damper 402, including reducing the need for system delays and dampers.

With reference now to FIG. 4C, in various embodiments, in addition to that which the control system 404 is described to include, the control system 404 further optionally includes any of the following (each of which will be

described below): a location comparer **466**; an environmental information comparer **468**; a vehicle component speed comparer **470**; a vehicle component position comparer **472**; a vehicle component velocity comparer **474**; a vehicle component pressure comparer **476**; a date tracker **478**; and a center of gravity (CG) calculator **480**. Further, the CG calculator **480** includes the following: a pressure value accessor **482**; a pressure value comparer **484**; and a CG determiner **486**.

With reference to FIG. 4D, in various embodiments, in addition to that which the database **416** is described to include, the database **416** further optionally includes any of the following (each of which will be described below): predetermined global location information **493**; predetermined environmental threshold values **487** which include predetermined environmental temperature threshold values **488** and predetermined humidity threshold values **489**; predetermined vehicle component speed threshold values **494** which include predetermined vehicle speed threshold values **495** and predetermined wheel speed threshold values **496**; predetermined shock absorber position threshold values **490**; predetermined shock absorber velocity threshold values **491**; and predetermined vehicle component base-level pressure values **492**.

With reference to FIGS. 4A-4D, the following components are described. The location comparer **466**, in one embodiment, is configured to compare a vehicle global position (that was determined by a GPS sensor attached to a vehicle) with predetermined global location information **493**.

The environmental information comparer **468**, in one embodiment, is configured to compare environment information (that was determined by temperature sensors and humidity sensors) with predetermined environmental threshold values **487** (and more particularly, in one embodiment, predetermined temperature threshold values **488** and predetermined humidity threshold values **489**).

The vehicle component speed comparer **470**, in one embodiment, is configured to compare the speed of a component of a vehicle (that a vehicle speed sensor measured) with the predetermined vehicle component speed threshold values **494** (and more particularly, in one embodiment, the predetermined vehicle [the entire vehicle being a component onto itself] speed threshold values **495** and the wheel speed threshold values **496**).

The vehicle component position comparer **472**, in one embodiment, is configured to compare the position of a component of a vehicle (that a vehicle position sensor measured) with the predetermined shock absorber position threshold values **490**.

The vehicle component velocity comparer **474**, in one embodiment, is configured to compare the velocity of a component of a vehicle (that a vehicle velocity sensor measured) with the predetermined shock absorber velocity threshold values **490**.

The vehicle component velocity comparer **474**, in one embodiment, is configured to compare the pressure applied to a component of a vehicle (that a pressure sensor measured) with the predetermined vehicle component base level pressure values **492**.

Example Methods for Controlling Vehicle Motion in Vehicles (e.g., Side-by-Side) with More than Two Wheels Utilizing a Variable Pressure Valve of an Electronic Valve and Novel Control System

With reference to FIGS. 4A-4D, 10A-16B and 18A-18R, the flow diagrams thereof illustrate example methods **500**,

600, 800, 1000, 1050, 1000, 1050, 1200, 1250, 1300, 1350, 1400, 1450, 1500, 1550, 1600 and 1650 used by various embodiments. The flow diagrams include methods **500, 600, 800, 1000, 1050, 1000, 1050, 1200, 1250, 1300, 1350, 1400, 1450, 1500, 1550, 1600 and 1650** and operations thereof that, in various embodiments, are carried out by one or more processors (e.g., processor(s) **306A-306C** of FIG. 3) under the control of computer-readable and computer-executable instructions. It is appreciated that in some embodiments, the one or more processors may be in physically separate locations or electronic devices/computing systems. The computer-readable and computer-executable instructions reside, for example, in tangible data storage features such as volatile memory, non-volatile memory, and/or a data storage unit (see e.g., **308, 310, 312** of FIG. 3). The computer-readable and computer-executable instructions can also reside on any tangible computer-readable media such as a hard disk drive, floppy disk, magnetic tape, Compact Disc, Digital versatile Disc, and the like. In some embodiments, the computer-readable storage media is non-transitory. The computer-readable and computer-executable instructions, which may reside on computer-readable storage media, are used to control or operate in conjunction with, for example, one or more components of a control system **404**, a user's electronic computing device or user interface thereof, and/or one or more of processors **306**. When executed by one or more computer systems or portion(s) thereof, such as a processor, the computer-readable instructions cause the computer system(s) to perform operations described by the methods **500, 600, 800, 1000, 1050, 1000, 1050, 1200, 1250, 1300, 1350, 1400, 1450, 1500, 1550, 1600 and 1650** of the flow diagrams.

Although specific operations are disclosed in methods **500, 600, 800, 1000, 1050, 1000, 1050, 1200, 1250, 1300, 1350, 1400, 1450, 1500, 1550, 1600 and 1650** of the flow diagrams, such operations are examples. That is, embodiments are well suited to performing various other operations or variations of the operations recited in the processes of flow diagrams. Likewise, in some embodiments, the operations of the methods **500, 600, 800, 1000, 1050, 1000, 1050, 1200, 1250, 1300, 1350, 1400, 1450, 1500, 1550, 1600 and 1650** in the flow diagrams may be performed in an order different than presented, not all of the operations described in one or more of these flow diagrams may be performed, and/or more additional operations may be added. It is further appreciated that steps described in the **500, 600, 800, 1000, 1050, 1000, 1050, 1200, 1250, 1300, 1350, 1400, 1450, 1500, 1550, 1600 and 1650** may be implemented in hardware, or a combination of hardware with firmware and/or software.

The following is a discussion of FIGS. 5-8, 10A-16B, flow diagrams for methods **500, 600, 800, 1000, 1050, 1000, 1050, 1200, 1250, 1300, 1350, 1400, 1450, 1500, 1550, 1600 and 1650** for controlling vehicle motion, in accordance with embodiments, and relating to side-by-side roll and/or pitch control. FIG. 5 describes a method **500** of an operation of control system **404** detecting and responding to a detection of roll and/or pitch of a vehicle component. FIGS. 6 and 7 follow with a description of a method **600** of controlling vehicle motion, wherein both translational acceleration (roll/pitch) and user-induced inputs are taken into consideration when determining a response to sensed acceleration.

Reference will be made to elements of FIGS. 1A-2C and 4A-4D to facilitate the explanation of the operations of the methods of flow diagrams **500, 600, 800, 1000, 1050, 1000, 1050, 1200, 1250, 1300, 1350, 1400, 1450, 1500, 1550, 1600 and 1650**. In some embodiments, the methods **500**,

600, 800, 1000, 1050, 1000, 1050, 1200, 1250, 1300, 1350, 1400, 1450, 1500, 1550, 1600 and 1650 of the flow diagrams describe a use of or instructions for operation of control system 404. With regard to FIGS. 5-8, it should be appreciated that the method described herein may be performed by the electronic valve 460 that includes the variable pressure valve 462, instead of the pilot valve assembly 132 shown in FIGS. 1 and 2A-2C.

With reference now FIG. 5, the method 500 starts at operation 502. The method 500 moves to operation 504.

At operation 504, in one embodiment, the control system 404 determines under which system mode the vehicle suspension damper is operating, the soft mode, the firm mode or the auto mode. It should be appreciated that the system mode, in one embodiment, is selected by a user of the vehicle suspension damper. In another embodiment, the system mode is preprogrammed to default to a particular mode, unless overridden by a user.

If the control system 404 determines that the vehicle suspension damper is operating under the soft mode, then the method 500 moves to operation 506. At operation 506, in one embodiment, the control system 404 determines if all the vehicle suspension dampers on the vehicle are in the soft mode. If the control system 404 determines that all of the vehicle suspension dampers are in the soft mode, then the method 500 returns to start 502. If the control system 404 determines that all of the vehicle suspension dampers are not in the soft mode, then the method 500 moves to operation 508.

At operation 508, in one embodiment, the control system 404 causes any vehicle suspension damper that is not in the soft mode to adjust to become in the soft mode. After all vehicle suspension dampers are found to be in the soft mode according to the system setting, then the method 500 returns to start 502.

At operation 504, in one embodiment, if the control system 404 determines that the vehicle suspension damper is operating in the firm mode, then the method 500 moves to operation 510. At operation 510, in one embodiment, the control system 404 determines if the rebound is firm and the compression is soft. If the control system 404 determines that the rebound of the vehicle suspension damper is firm and the compression of the vehicle suspension dampers is soft, then the method 500 moves to operation 514.

At operation 514, in one embodiment, if the control system 404 determines that the rebound of the vehicle suspension dampers is not firm OR the compression of the vehicle suspension dampers is not soft, then the method 500 moves to operation 512. At operation 512, in one embodiment, the control system 404 causes all rebound of the vehicle suspension dampers to become firm and all compression of the vehicle suspension dampers to become soft. The method 500 then moves to operation 514.

At operation 514, in one embodiment, the control system 404 determines if there is a rebound settle time remaining and if the compression of the vehicle suspension dampers is still soft. If the control system 404 determines that there is rebound settle time remaining and the compression of the vehicle dampers is soft, then the method 500 moves to operation 516. At operation 516, in one embodiment, the control system 404 causes all of the compression in the vehicle suspension dampers to be firm. The method 500 then returns to the start 502.

At operation 514, in one embodiment, if the control system 404 determines that there is no rebound settle time remaining and the compression of the vehicle suspension dampers is soft, then the method 500 moves to start 502.

At operation 504, in one embodiment, if the control system 404 determines that the vehicle suspension damper 402 is operating in the auto mode, then the method 500 moves to operation 518. At operation 518, in one embodiment, the control system 404 determines if the control mode state is active. If the control system 404 determines that the control mode state is not active, then the method 500 moves to operation 520. At operation 520, in one embodiment, the control system 404 determines whether a trigger logic is passed AND if a time applied by a hold-off timer 426 is in place. If the control system 404 determines both conditions have occurred, then the method 500 moves to operation 522. At operation 522, the control system 404 resets the hold-off time and sets the control mode state to active.

At operation 520, in one embodiment, if the control system 404 determines that either a trigger logic has not passed OR a time has not been applied by the hold-off timer 426, then the method 500 moves to operation 530. At operation 530, in one embodiment, the control system 404 sets the control mode state to inactive. The method 500 then moves to operation 532.

At operation 518, in one embodiment, if the control system 404 determines that the control mode state is active, then the method 500 moves to operation 528. At operation 528, in one embodiment, the control system 404 determines if the hold logic has passed OR if the trigger logic is passed OR if the delay for hold has passed.

At operation 528, in one embodiment, if the control system 404 determines that either a hold logic has passed OR a trigger logic has passed OR a delay for hold has passed, then the method 500 moves to operation 524. At operation 524, in one embodiment, the control system 404 determines under what damping control setting the vehicle suspension damper 402 is operating.

At operation 524, in one embodiment, if the control system 404 determines that the vehicle suspension damper 402 is operating under a particular damper control setting, then the method 500 returns to the start 502. At operation 524, in one embodiment, if the control system 404 determines that the vehicle suspension damper 402 is operating under a different damper control setting than desired, the control system 404 adjusts the vehicle suspension damper 402 so that it operates under the desired damper control setting. The method 500 then returns to start 502.

At operation 528, in one embodiment, if the control system 404 determines that either a hold logic has not passed OR a trigger logic has not passed OR a delay for hold has not passed, then the method 500 moves to operation 530. At operation 530, in one embodiment, the control system 404 sets the control mode state to inactive. Then, the method 500 moves to operation 532. At operation 532, in one embodiment, the control system 404 determines if the vehicle suspension dampers are soft.

At operation 532, in one embodiment, if the control system 404 determines that the vehicle suspension dampers are soft, then the method 500 returns to the start 502. At operation 532, in one embodiment, if the control system 404 determines that the vehicle suspension dampers are not soft, then the method 500 moves to operation 534.

At operation 534, in one embodiment, the control system 404 functions, as described herein, to cause the vehicle suspension dampers to become soft. The method 500 then returns to the start 502.

Of note, the checks for whether or not a vehicle suspension damper is already set according to the method 500 need to be done individually for each vehicle suspension damper.

FIGS. 6 and 7 is a flow diagram of a method 600 for controlling vehicle motion, in accordance with embodiments. The method 600, in embodiments, may be performed using the pilot valve assembly 132 or the novel electronic valve 460 that includes the variable pressure valve 462.

With reference to FIGS. 4A-4D, 6 and 7, at operation 602 of method 600, in one embodiment, a set of control signals are accessed, wherein at least a first control signal of the set of control signals includes a measured acceleration value associated with a movement of a vehicle component of a vehicle, and at least a second control signal of the set of control signals comprises a set of values associated with user-induced inputs, wherein the vehicle component is coupled with a frame of the vehicle via at least one vehicle suspension damper.

At operation 604 of method 600, in one embodiment and as described herein, the measured acceleration value is compared with a predetermined acceleration threshold value that corresponds to the vehicle component to achieve an acceleration value threshold approach status. In various embodiments, the predetermined acceleration threshold values are located at the database 416 and include the trigger logic, the hold logic, and the damper control setting options described herein. The control system 404 compares the measured acceleration values with the acceleration threshold values expressed in the trigger logic and hold logic. The comparing, at operation 604, includes determining if the measured acceleration values do or do not exceed the predetermined acceleration threshold values corresponding to the relevant vehicle component. Further, the control system 404 will pass into the appropriate control mode based on the comparisons made at operation 604 and 606.

For example, and with reference to the trigger logic #1(A)(i) above relating to the "Roll Positive Control". If it is found that ((steer velocity>threshSteerVelTrigger) AND (side acceleration>threshSideAccelRollAllow)) is a true statement, OR (side acceleration>threshSideAccelRollTrigger) is a true statement, then the vehicle suspension damper, and the control system 404 operating thereon, switches/passes into the roll positive control mode. Upon passing into the roll positive control mode, the control system 404 selects which option to implement on the vehicle suspension dampers (e.g., setting individual dampers to firm or soft, etc.) of the options available and described herein for the Roll Positive Control Mode. It should be appreciated that the control system 404 is preprogrammed to select a particular control mode implementation option. These implementation decisions may be factory settings or individually customized by the rider/user. Additionally, it should also be appreciated that in one embodiment, the rider may override the control system 404's selection.

At operation 606 of method 600, in one embodiment and as described herein, the set of values associated with the user-induced inputs (already described herein) are compared to predetermined user-induced inputs threshold values to achieve a user-induced input threshold value approach status. In various embodiments, the predetermined user-induced inputs threshold values are located at the database 416. Further, in various embodiments, the database 416 includes at least one of, optionally the following which is described herein: the trigger logic; the hold logic; and the damper control setting options. The comparing, at operation 606 includes determining if the measured user-induced inputs (represented as values) does or does not exceed the user-induced inputs threshold values corresponding to the relevant vehicle component. Further, the control system 404

will pass into the appropriate control mode based on the comparisons made at operation 604 and 606.

At operation 608 of method 600, in one embodiment and as described herein, a state of at least one valve within at least one vehicle suspension damper of the vehicle is monitored, wherein the state controls a damping force within the at least one vehicle suspension damper.

At operation 610 of method 600, in one embodiment and as described herein, based on the acceleration value threshold approach status and the user-induced input threshold value approach status, determining a control mode for the vehicle suspension damper.

At operation 612 of method 600, in one embodiment and as described herein, according to the control mode and based on the monitoring, damping forces are regulated within the at least one vehicle suspension damper by actuating the at least one valve to adjust to a desired state, such that a tilt of the vehicle's frame is reduced.

At operation 614 of method 600, in one embodiment and as described herein, before the regulating at operation 610, a mode switch setting for the at least one vehicle suspension damper is determined.

At operation 616 of method 600, in one embodiment and as described herein, a period of time to hold the at least one vehicle suspension damper in the desired state is set, such that the period of time begins when a first threshold value is determined to have been exceeded and ends when a second threshold value is determined to have been exceeded.

At operation 618 of method 600, in one embodiment and as described herein, a period of time for the at least one vehicle suspension damper to settle down before a compression mode of the at least one vehicle suspension damper is set to firm is established.

At operation 620 of method 600, in one embodiment and as described herein, a set of times when threshold values are determined to have been exceeded is tracked.

Of note with regard to method 600, the acceleration values that are measured may include lateral acceleration of the vehicle as is described with respect to method 800 of FIG. 8. Further, the user-induced inputs that are measured may include the velocity with which a steering wheel is being turned and the absolute value of the difference between the steering wheel's initial position before it was turned and its final position after it was turned, as is described with respect to method 800 of FIG. 8.

FIG. 8 is a flow diagram of a method 800 for controlling vehicle motion, in accordance with an embodiment. The method 800 starts at operation 802. The method 800 moves from operation 802 to operation 804.

At operation 804, in one embodiment, the control system 404 receives signals from at least one sensor of the set of sensors 440 that gives information regarding a particular vehicle component. For example, a steering wheel sensor and an accelerometer send signals 442 to the control system 404 regarding the velocity and position of the steering wheel having been turned, and the acceleration that the vehicle is experiencing. The control signal accessor 456 of the control system 404 accessing these signals 442. The first comparer 406 compares the measured acceleration of the vehicle with the predetermined acceleration threshold value 418. The second comparer 410 compares the measured steering wheel velocity and position to the predetermined user-induced inputs threshold values 448. The control mode determiner 454 determines if any of the following scenarios at step 806 are met: 1) at 808, the measured lateral acceleration of the vehicle is greater than the predetermined acceleration threshold value; 2) at 810, the measured steering position is greater

than the predetermined user-induced input threshold value for that steering wheel position AND the measured lateral acceleration of the vehicle is greater than the predetermined acceleration release threshold value; and 3) at **812**, the measured steering velocity is greater than the predetermined user-induced input threshold value for that steering wheel velocity AND the measured lateral acceleration of the vehicle is greater than the predetermined acceleration release threshold value.

If any of the foregoing three conditions are found to be met, then the control system **404** allows a control mode to be activated. The control mode to be activated is determined by the control mode determiner **454**. In this situation, the control mode includes: the inside compression to be “soft”; the outside compression to be “firm”; the inside rebound to be “firm”; and the outside rebound to be “soft”.

However, if all of the foregoing conditions are not met, then the control mode determiner **454**, at operation **816**, determines if both of the following conditions are met: 1) the measured steering wheel position is less than the predetermined velocity user-induced input threshold value for the steering wheel position; AND 2) the measured lateral acceleration is less than the predetermined acceleration threshold value for release. If both of the foregoing two conditions are found to be met, then the control system **404** allows a control mode to be activated. The control mode to be activated is determined by the control mode determiner **454**. In this situation, the control mode includes, at operation **818**: the inside compression to be “medium” (at some point in between “soft” and “hard”); the outside compression to be “medium”; the inside rebound to be “medium”; and the outside rebound to be “medium”.

However, if the foregoing two conditions are not met, then a control mode adjustment is not allowed, and the process moves back to start at operation **802**.

Of note, the method **800** may be implemented with a single direction semi-active shock (in which the shock is only semi-active in rebound or compression) on any combination of shock absorbers (i.e., the front shock has semi-active rebound and compression, whereas the rear shocks has semi-active only for compression). The steering wheel sensor may be an absolute or incremental encoder, a potentiometer, a gyro, a hall effect sensor, etc. Additionally, for vehicles with a pair of inline wheels/skis/tracks in the rear, the following logic is used: (a) Front wheel/ski/track: Treat as inside for purposes of assigning firm/soft control mode; and (b) Rear wheel/ski/track: Treat as outside for purposes of assigning firm/soft control mode.

Additionally, method **800** may be implemented in shock absorbers using springs. For example, method **800** may be implemented in a shock absorber having an air spring with a concentric cylinder bypass damper therein, shown in FIG. **9**.

FIG. **9** depicts a side cross-sectional view of a shock absorber **900** upon which embodiments may be implemented. More specifically, the shock absorber **900** includes an air spring integrated with a concentric cylinder bypass damper.

The shock absorber **900** includes the air spring **902** with a concentric cylinder bypass damper **912** slidably engaged therein. As shown, the air spring **902** includes the air spring chamber **906** and the shaft **908**. A fitting **904** is disposed at the top of the air spring **902**. The fitting **904** is enables an entry of air into the air spring chamber **906**.

The air spring chamber **906** has only air within, in one embodiment. As compression of the shock absorber **900** occurs, the concentric cylinder bypass damper **912** moves

further into the air spring chamber **906** of the air spring **902**. As the concentric cylinder bypass damper **912** moves further into the air spring chamber **906**, the shaft **908** moves further into the damping fluid chamber **914** of the concentric cylinder bypass damper **912**.

Upon the movement of the concentric cylinder bypass damper **912** into the air spring chamber **906**, a damping effect occurs. The strength of the damping effect is determined by the amount of air pressure that is within the air spring chamber **906**. As the concentric cylinder bypass damper **912** enters the air spring chamber **906** the volume of the air spring chamber **906** is increased. The air within the air spring chamber **906** provides resistance to the movement of the concentric cylinder bypass damper **912** therein.

Additionally, in one embodiment, the electronic valve **460** is integrated within the concentric cylinder bypass damper **912**. In one embodiment, for example, the electronic valve **460** is integrated with the main piston attached to the shaft **944**. However, it should be noted that the electronic valve **460** may be implemented elsewhere in or on the shock absorber **918**, as described herein with regard to other types of shock absorber structures. See FIGS. **18A-18R** for a description of the integration of the electronic valve **460** onto various shock absorber designs.

FIG. **10A** is a flow diagram of a method **1000** for controlling vehicle motion, in accordance with an embodiment. The method **1000** starts at operation **1002**. The method **1000** moves from operation **1002** to operation **1004**.

At operation **1004**, in one embodiment, the set of sensors **440** of the vehicle components **438** sense the vehicle speed, the wheel speed, the shock absorber position and the shock absorber velocity. At operation **1006**, after the control system **404** received the control signals from the set of sensors **440** including the information regarding the vehicle speed, the wheel speed, the shock absorber position and the shock absorber velocity, the control system **404** calculates the “soft” (some position less than “medium”), “medium” (some position between “soft” and “firm”), and “firm” (some position more than “medium”) damping settings.

The following is a key for the equations detailed below:

SR: soft rebound damping setting;
 SC: soft compression damping setting;
 NR: medium rebound damping setting;
 NC: medium compression damping setting;
 FR: firm rebound damping setting;
 FC: firm compression damping setting;
 S_v : speed of the vehicle;
 S_w : speed of the individual wheels;
 P_s : position shock;
 V_s : velocity shock;
 T : temperature of shock;
 T_n : nominal temperature of shock;
 b_{xx} : nominal damping setting;
 m_{xx} : how damping setting changes based on vehicle speed, could be any relationship;
 n_{xx} : how the damping setting changes based on difference in vehicle speed and individual wheel speed, this could be any relationship;
 c_{xx} : how the damping setting changes based on shock position, this could be any relationship;
 d_{xx} : how the damping setting changes based on shock velocity, this could be any relationship; and
 g_{xx} : how damping setting changes based on temperature, could be any relationship.

Regarding the “soft” setting control mode, the control system 404, in one embodiment, calculates the soft rebound and the soft compression control mode setting using the following equations:

Soft Rebound Control Mode Setting:

$$SR(S_{Yr}, S_{Yp}, P_S, V_S, T) = b_{sr} + m_{sr} s_v + n_{sr} (S_{Yr} - S_Y) + c_{sr} P_S + d_{sr} V_S + g_{sr} (T - T_n)$$

Soft Compression Control Mode Setting:

$$SC(S_{Yr}, S_{Yp}, P_S, V_S, T) = b_{sc} + m_{sc} s_v + n_{sc} (S_{Yr} - S_Y) + c_{sc} P_S + d_{sc} V_S + g_{sc} (T - T_n)$$

Regarding the “medium” setting control mode, the control system 404, in one embodiment, calculates the medium rebound and the medium compression control mode setting using the following equations:

Medium Rebound Control Mode Setting:

$$MR(S_{Yr}, S_{Yp}, P_S, V_S, T) = b_{mc} + m_{mc} s_v + n_{mc} (S_{Yr} - S_Y) + c_{mc} P_S + d_{mc} V_S + g_{mc} (T - T_n)$$

Medium Compression Control Mode Setting:

$$MC(S_{Yr}, S_{Yp}, P_S, V_S, T) = b_{mc} + m_{mc} s_v + n_{mc} (S_{Yr} - S_Y) + c_{mc} P_S + d_{mc} V_S + g_{mc} (T - T_n)$$

Regarding the “firm” setting control mode, the control system 404, in one embodiment, calculates the firm rebound and the firm compression control mode setting using the following equations:

Firm Rebound Control Mode Setting:

$$FR(S_{Yr}, S_{Yp}, P_S, V_S, T) = b_{fr} + m_{fr} s_v + n_{fr} (S_{Yr} - S_Y) + c_{fr} P_S + d_{fr} V_S + g_{fr} (T - T_n)$$

Firm Compression Control Mode Setting:

$$FC(S_{Yr}, S_{Yp}, P_S, V_S, T) = b_{fc} + m_{fc} s_v + n_{fc} (S_{Yr} - S_Y) + c_{fc} P_S + d_{fc} V_S + g_{fc} (T - T_n)$$

At operation 1008, in one embodiment, based on the calculated “soft”, “medium” and “firm” damping settings, the control system 404 sends an actuation signal to the power source 458, causing each of the shock absorbers to adjust according to the calculated damping setting at operation 1006; the rebound and/or compression damping control modes are actuated.

Of note, according to various embodiments, the vehicle speed sensor may be a GPS, a wheel speed sensor, an inertial sensor, etc., or any combination thereof. The wheel speed sensor may be a rotary/absolute encoder, a gear tooth sensor, etc.

According to various embodiments, the shock position sensor may be a LVDT, a string pot, a double integral of an accelerometer or any appropriate sensor.

According to various embodiments, the shock velocity sensor may be a derivative of a position sensor, an integral of an accelerometer or any appropriate sensor.

According to various embodiments, the shock heat sensor may be a thermocouple, a thermistor or any appropriate technology. The shock heat sensor may be internal or external to the shock body.

According to various embodiments, the decision between the firm and the soft damping setting may be manual (e.g., the rider’s choice) or automatic based on a desired roll control determination, a desired anti-squat control determination, driving history, etc.

According to various embodiments, the different firm and soft damping settings may be calculated for each wheel/track/etc. on the vehicle (i.e., this method is performed independently on each wheel/track/etc.).

FIG. 10B is a flow diagram of a method 1050 for controlling vehicle motion, in accordance with an embodiment. With reference to FIGS. 4A-4C and 10B, the method 1050 is described.

At operation 1055, in one embodiment, the set of control signals 442 are accessed, wherein a first control signal of the set of control signals 442 includes a measured vehicle speed value associated with a movement of a vehicle, a second control signal of the set of control signals 442 includes a measured wheel speed value associated with a movement of a wheel of the vehicle, a third control signal of the set of control signals 442 includes a measured vehicle suspension damper position value of a movement of a vehicle suspension damper of the vehicle and a fourth control signal of the set of control signals 442 includes a measured vehicle suspension damper velocity value associated with the movement of the vehicle suspension damper, wherein the vehicle suspension damper is coupled with a frame of the vehicle.

At operation 1060, in one embodiment, the measured vehicle speed value, the wheel speed value, the vehicle suspension damper position value and the vehicle suspension damper velocity value with corresponding predetermined vehicle speed threshold values 495, predetermined wheel speed threshold values 496, vehicle suspension damper position threshold values 490 and predetermined vehicle suspension damper velocity threshold values 491, respectively, to achieve a threshold approach status.

At operation 1065, in one embodiment, a state of at least one valve within the at least one vehicle suspension damper is monitored, wherein the state controls a damping force within the at least one vehicle suspension damper.

At operation 1070, in one embodiment, based on the threshold approach statuses, a control mode for the at least one vehicle suspension damper is determined.

At operation 1075, in one embodiment, according to the control mode determined at operation 1070 and based on the monitoring performed at operation 1075, damping forces are regulated within the at least one vehicle suspension damper by actuating the at least one valve to adjust to a desired state, such that a tilt of the frame is reduced.

FIG. 11A is a flow diagram of a method 1100 for controlling vehicle motion, in accordance with an embodiment. The method 1100 starts at operation 1102. The method 1100, in one embodiment, moves from operation 1102 to operation 1104.

At operation 1104, in one embodiment, at least one set of sensors of the set of sensors 440 senses the vehicle speed.

After receiving the vehicle speed measurements having been sensed by the set of sensors 440, the control system 404 performs at least one of three operations 1106, 1110 and 1114.

At operation 1106, in one embodiment, the roll control thresholds, such as the steering position threshold and the steering velocity threshold, are calculated. The steering position threshold, in one embodiment, is calculated using the following equation:

$$SPT(s) = b_{sp} + m_{sp} s$$

The steering velocity threshold is calculated using the following equation:

$$SVT(s) = b_{sv} + m_{sv} s$$

At operation 1108, in one embodiment, the calculations performed at operation 1106 are used to perform the roll control method 800 shown in FIG. 8.

45

At operation **1110**, in one embodiment, the anti-dive thresholds, such as the brake position trigger threshold and the brake velocity trigger threshold, are calculated.

The brake position trigger threshold, in one embodiment, is calculated using the following equation:

$$\text{BPT}(s)=b_{bp}+m_{bp}s$$

The brake velocity trigger threshold, in one embodiment, is calculated using the following equation:

$$\text{BVT}(s)=b_{bv}+m_{bv}s$$

At operation **1112**, in one embodiment, the calculations performed at operation **1110** are used to perform the anti-dive method that will be explained with respect to method **1200** of FIG. **12A**.

At operation **1114**, in one embodiment, the anti-squat thresholds, such as the throttle position trigger threshold and the throttle velocity trigger threshold, are calculated.

The throttle position trigger threshold, in one embodiment, is calculated using the following equation:

$$\text{TPT}(s)=b_{tp}+m_{tp}s$$

The throttle velocity trigger threshold, in one embodiment, is calculated using the following equation:

$$\text{TVT}(s)=b_{tv}+m_{tv}s$$

At operation **1116**, in one embodiment, the calculations performed at operation **1114** are used to perform the anti-squat method that will be explained with respect to method **1300** of FIG. **13**.

At operation **1118**, in one embodiment, once the roll control method at **1108**, the anti-dive method at **1112** and/or the anti-squat method at **1116** are calculated, the control system **404** sends an actuation signal to the power source **458** to activate the electronic valve **100** or **460** to achieve the control modes determined based on the methods performed at operation **1108**, **1112** and/or **1116**.

After the operation **1118** is complete, in one embodiment, the method **1100** moves to the start at operation **1102**.

Of note, in one embodiment, the vehicle speed sensor may be a GPS, a wheel speed sensor, an inertial sensor, etc., or any combination thereof. The operations performed at **1106**, **1110** and **1115**, in one embodiment, may be enabled/disabled independently of each other.

FIG. **11B** is a flow diagram of a method **1150** for controlling vehicle motion, in accordance with an embodiment. With reference to FIGS. **4A-4C** and FIGS. **11A** and **11B**, the method **1150** is described.

At operation **1155**, in one embodiment, a set of control signals **442**, wherein a first control signal of said set of control signals **442** includes a measured vehicle speed value associated with a movement of a vehicle, and wherein a second control signal of the set of control signals **442** includes a set of values associated with at least one user-induced input, wherein a vehicle suspension damper is coupled with a frame of the vehicle.

At operation **1160**, in one embodiment, the measured vehicle speed value is compared with a predetermined vehicle speed threshold value **495** that corresponds to the vehicle, to achieve a speed value threshold approach status.

At operation **1165**, in one embodiment, the set of values associated with the at least one user-induced input is compared with a predetermined user-induced input threshold value **448**, to achieve a user-induced input threshold value approach status.

46

At operation **1170**, in one embodiment, a state of a valve within the vehicle suspension damper is monitored, wherein the state controls a damping force within the vehicle suspension damper.

At operation **1175**, in one embodiment, based on at least one of the vehicle speed value threshold approach status and the user-induced input threshold value approach status, a control mode for the at least one vehicle suspension damper is determined.

At operation **1180**, in one embodiment, according to the control mode and based on the monitoring, damping forces within the at least one vehicle suspension damper are regulated by actuating the at least one valve to adjust to a desired state, such that a tilt of the frame is reduced.

FIG. **12A** is a flow diagram of a method **1200** for controlling vehicle motion, in accordance with an embodiment. The method **1200** provides for “anti-diving” control mode determinations. The method **1200** starts at operation **1202**. The method **1200** moves from operation **1202** to operation **1204**.

At operation **1204**, in one embodiment, the set of sensors **440** sense the brake pedal information, such as the position of the brake pedal and the velocity at which the brake pedal moves in response to being pressed.

At operation **1206**, in one embodiment, the control system **404** accesses (retrieves from the set of sensors **440** or receives from the set of sensors **440**) the sensed information from the set of sensors **440**, such as the brake position and the brake velocity. The control system **404**, in one embodiment, compares the measured brake position and the measured brake velocity to the predetermined user-induced inputs threshold values. More specifically, the measured brake position is compared to the predetermined brake position trigger threshold value and the measured brake velocity is compared to the predetermined brake velocity trigger threshold value. In one embodiment, if the control mode determiner **454** determines whether or not the following conditions are met: the measured brake position is found to be greater than the predetermined brake position trigger threshold; OR the measured brake velocity is found to be greater than the predetermined brake velocity trigger threshold. If the foregoing conditions of operation **1206** are met, then the method **1200** moves to operation **1208**.

At operation **1208**, in one embodiment, the control mode determiner **454** determines the following control modes: the control mode for the front compression is to be “firm”; the control mode for the rear compression is to be “soft”; the control mode for the front rebound is to be “soft”; and the control mode for the rear rebound is to be “firm”. The control system **404** sends an actuation signal to the power source **458** to cause the electronic valve **100** to adjust to achieve these control modes.

However, in one embodiment, if the foregoing conditions of operation **1206** are not met, then the method **1200** moves from operation **1206** to operation **1210**. At operation **1210**, in one embodiment, the control mode determiner **454** determines if the following conditions are met: the measured brake position is less than the predetermined brake position release threshold; AND the measured brake velocity is less than the predetermined brake velocity release threshold.

If it is determined that the foregoing conditions of operation **1210** are met, in one embodiment, then the control mode determiner **454** determines, at operation **1212**, the following control modes: the control mode for the front compression is to be “medium”; the control mode for the rear compression is to be “medium”; the control mode for the front rebound is to be “medium”; and the control mode for the rear

rebound is to be “medium”. The control system **404** sends an actuation signal to the power source **458** to cause the electronic valve **100** to adjust to achieve these control modes.

However, in one embodiment, if the foregoing conditions of operation **1210** are not met, then the method **1200** moves from operation **1210** to the start at operation **1202**.

Of note, the method **1200**, in one embodiment, may be implemented with a single direction semi-active shock (only semi-active in rebound or compression) on any combination of shock absorbers (i.e., the front shock absorbers have semi-active rebound and compression, while the rear shock absorbers have semi-active only for compression). Of further note, the thresholds for the soft/medium/firm damping settings are configured according to the methods **1000** and **1100**. Additionally, the brake sensor of the set of sensors **440** may be a hardware sensor (e.g., potentiometer, LVDT, encoder, etc.) or a parameter read from the vehicle’s computer.

FIG. **12B** is a flow diagram of a method **1250** for controlling vehicle motion, in accordance with an embodiment. With reference to FIGS. **4A-4C**, **12A** and **12B**, the method **1250** is described.

At operation **1255**, in one embodiment, a set of control signals **442** are accessed, wherein at least a first control signal of the set of control signals **442** includes a set of values associated with at least one user-induced input, wherein at least one vehicle suspension damper is coupled to a frame of the vehicle.

At operation **1260**, in one embodiment, a set of release thresholds associated with a brake position and a brake velocity of the at least one user-induced input is accessed.

At operation **1265**, in one embodiment, the set of values associated with the at least one user-induced input is compared with the predetermined user-induced input threshold values **448**, to achieve a user-induced input threshold value approach status.

At operation **1270**, in one embodiment, a state of at least one valve within the at least one vehicle suspension damper is monitored, wherein the state controls a damping force within the at least one vehicle suspension damper.

At operation **1275**, in one embodiment, based on the user-induced input threshold value approach status and the set of release thresholds, a control mode for the at least one vehicle suspension damper is determined.

At operation **1280**, in one embodiment, according to the control mode and based on the monitoring, damping forces within the at least one vehicle suspension damper are regulated by actuating the at least one valve to adjust to a desired state, such that a tilt of the frame is reduced.

FIG. **13A** is a flow diagram of a method **1300** for controlling vehicle motion, in accordance with an embodiment. The method **1300** provides for “anti-squatting” control mode determinations. The method **1300** starts at operation **1302**. The method **1300** moves from operation **1302** to operation **1304**.

At operation **1304**, in one embodiment, the set of sensors **440** sense the throttle information, such as the position of the throttle and the velocity at which the throttle moves in response to being pressed.

At operation **1306**, in one embodiment, the control system **404** accesses (retrieves from the set of sensors **440** or receives from the set of sensors **440**) the sensed information from the set of sensors **440**, such as the throttle position and the throttle velocity. The control system **404**, in one embodiment, compares the measured throttle position and the measured throttle velocity to the predetermined user-in-

duced inputs threshold values. More specifically, the measured throttle position is compared to the predetermined throttle position trigger threshold value and the measured throttle velocity is compared to the predetermined throttle velocity trigger threshold value. In one embodiment, if the control mode determiner **454** determines whether or not the following conditions are met: the measured throttle position is found to be greater than the predetermined throttle position trigger threshold; OR the measured throttle velocity is found to be greater than the predetermined throttle velocity trigger threshold. If the foregoing conditions of operation **1306** are met, then the method **1300** moves to operation **1308**.

At operation **1308**, in one embodiment, the control mode determiner **454** determines the following control modes: the control mode for the front compression is to be “soft”; the control mode for the rear compression is to be “firm”; the control mode for the front rebound is to be “firm”; and the control mode for the rear rebound is to be “soft”. The control system **404** sends an actuation signal to the power source **458** to cause the electronic valve **460** to adjust to achieve these control modes.

However, in one embodiment, if the foregoing conditions of operation **1306** are not met, then the method **1300** moves from operation **1306** to operation **1310**. At operation **1310**, in one embodiment, the control mode determiner **454** determines if the following conditions are met: the measured throttle position is less than the predetermined throttle position release threshold; AND the measured throttle velocity is less than the predetermined throttle velocity release threshold.

If it is determined that the foregoing conditions of operation **1310** are met, in one embodiment, then the control mode determiner **454** determines, at operation **1312**, the following control modes: the control mode for the front compression is to be “soft”; the control mode for the rear compression is to be “soft”; the control mode for the front rebound is to be “soft”; and the control mode for the rear rebound is to be “soft”. The control system **404** sends an actuation signal to the power source **458** to cause the electronic valve **460** to adjust to achieve these control modes.

However, in one embodiment, if the foregoing conditions of operation **1310** are not met, then the method **1300** moves from operation **1310** to the start at operation **1302**.

Of note, the method **1300**, in one embodiment, may be implemented with a single direction semi-active shock (only semi-active in rebound or compression) on any combination of shock absorbers (i.e., the front shock absorbers have semi-active rebound and compression, while the rear shock absorbers have semi-active only for compression). Of further note, the thresholds for the soft/medium/firm damping settings are configured according to the methods **1000** and **1100**. Additionally, the throttle sensor of the set of sensors **440** may be a hardware sensor (e.g., potentiometer, LVDT, encoder, etc.) or a parameter read from the vehicle’s computer.

FIG. **13B** is a flow diagram of a method **1350** for controlling vehicle motion, in accordance with an embodiment. With reference to FIGS. **4A-4C**, **34A** and **34B**, the method **1350** is described.

At operation **1355**, in one embodiment, a set of control signals **442** are accessed, wherein at least a first control signal of the set of control signals **442** includes a set of values associated with at least one user-induced input, wherein at least one vehicle suspension damper is coupled to a frame of the vehicle.

At operation **1360**, in one embodiment, a set of release thresholds associated with a throttle position and a throttle velocity of the at least one user-induced input is accessed.

At operation **1365**, in one embodiment, the set of values associated with the at least one user-induced input is compared with the predetermined user-induced input threshold values **448**, to achieve a user-induced input threshold value approach status.

At operation **1370**, in one embodiment, a state of at least one valve within the at least one vehicle suspension damper is monitored, wherein the state controls a damping force within the at least one vehicle suspension damper.

At operation **1375**, in one embodiment, based on the user-induced input threshold value approach status and the set of release thresholds, a control mode for the at least one vehicle suspension damper is determined.

At operation **1380**, in one embodiment, according to the control mode and based on the monitoring, damping forces within the at least one vehicle suspension damper are regulated by actuating the at least one valve to adjust to a desired state, such that a tilt of the frame is reduced.

FIG. **14A** is a flow diagram of a method **1400** for controlling vehicle motion, in accordance with an embodiment. The method **1400** provides for center of gravity restoration control mode determinations. The method **1400** starts at operation **1402**. The method **1400** moves from operation **1402** to operation **1404**.

At operation **1404**, in one embodiment, the set of sensors **440** sense the center of gravity information, such as the pressure applied to the vehicle seats and the pressure applied to the vehicle's cargo bay (due to transporting items [e.g., luggage, fuel, etc.]).

At operation **1406**, in one embodiment, the control system **404** accesses (retrieves from the set of sensors **440** or receives from the set of sensors **440**) the sensed information from the set of sensors **440**, such as the sensed pressure applied to the vehicle's seats and the sensed pressure applied to the vehicle's cargo bay. The control system **404**, in one embodiment, at operation **1406**, calculates the approximate center of gravity of the vehicle and the passengers/cargo based on the pressures measured at operation **1404**.

At operation **1408**, in one embodiment, the damping is adjusted at each corner of the vehicle, via the shock absorbers, to compensate for the shift, if any, in the vehicle's center of gravity.

Of note, the method **1400**, in one embodiment, may be implemented with a single direction semi-active shock (only semi-active in rebound or compression) on any combination of shock absorbers (i.e., the front shock absorbers have semi-active rebound and compression, while the rear shock absorbers have semi-active only for compression).

FIG. **14B** is a flow diagram of a method **1450** for controlling vehicle motion, in accordance with an embodiment. With reference to FIGS. **4A-4C**, **14A** and **14B**, the method **1450** is described.

At operation **1455**, in one embodiment, a set of control signals **442** are accessed, wherein at least a first control signal of the set of control signals includes a set of values associated a pressure applied to a vehicle component of a vehicle, wherein at least one vehicle suspension damper is coupled to a frame of the vehicle.

At operation **1460**, in one embodiment, a set of predetermined vehicle component base-level pressure values associated with the vehicle component is accessed.

At operation **1465**, in one embodiment, the set of values associated with a pressure applied to the vehicle component

are compared with the set of predetermined vehicle component base-level pressure values.

At operation **1470**, in one embodiment, based on the comparing, an approximate shift in a center of gravity of the vehicle is calculated.

At operation **1475**, in one embodiment, a state of at least one valve within the at least one vehicle suspension damper is monitored, wherein the state controls a damping force within the at least one vehicle suspension damper.

At operation **1480**, in one embodiment, based on the calculating and the monitoring, a control mode for the at least one vehicle suspension damper is determined, that, if actuated, would compensate the vehicle for the shift in the center of gravity.

At operation **1485**, in one embodiment, according to the control mode, damping forces are regulated within the at least one vehicle suspension damper by actuating the at least one valve to adjust to a desired state, such that the base-level center of gravity is approximately restored.

FIG. **15A** is a flow diagram of a method **1500** for controlling vehicle motion, in accordance with an embodiment. The method **1500** provides for freefall control mode determinations. The method **500** starts at operation **1502**. The method **1500** moves from operation **1502** to operation **1504**.

At operation **1504**, in one embodiment, the set of sensors **440** sense acceleration information, such as the acceleration information associated with a vehicle component.

At operation **1506**, in one embodiment, the control system **404** accesses (retrieves from the set of sensors **440** or receives from the set of sensors **440**) the sensed information from the set of sensors **440**, such as the acceleration information. The control system **404**, in one embodiment, compares the measured vehicle component acceleration with a freefall acceleration threshold. If the measured vehicle component acceleration is found to be less than the freefall acceleration threshold, then at operation **1508**, in one embodiment, a freefall timer is set.

At operation **1510**, in one embodiment, subsequent to the freefall timer being set, the front compression control mode is set to "firm", the rear compression control mode is set to "firm", the front rebound control mode is set to "soft" and the rear rebound control mode is set to "soft".

However, if at operation **1506**, the measured vehicle body acceleration is more than the freefall acceleration threshold, then at operation **1512**, in one embodiment, a freefall timer is decremented.

At operation **1514**, in one embodiment, after the freefall timer is decremented at operation **1512**, it is determined whether or not the freefall time has expired.

If the freefall timer is found to have expired, then at operation **1516**, in one embodiment, the front compression control mode is set to "soft", the rear compression control mode is set to "soft", the front rebound control mode is set to "soft" and the rear rebound control mode is set to "soft".

However, in one embodiment, if at operation **1514**, it is found that the freefall timer has not expired, then the method **1500** moves to the start at operation **1502**.

Of note, the above method **1500** may be implemented with a single direction semi-active shock (only semi-active in rebound or compression) on any combination of shock absorbers (i.e., the front shock absorber has semi-active rebound and compression, whereas the rear shock absorber has semi-active only for compression). The thresholds and the soft/firm damping settings are configured in methods described herein. The intent of the freefall timer is to keep

the compression firm for a short time after freefall ends (approximately 1 s in testing, but configurable in software).

FIG. 15B is a flow diagram of a method 1550 for controlling vehicle motion, in accordance with an embodiment. With reference to FIG. 15B and FIGS. 4A-4C, the method 1550 is described.

At operation 1555, in one embodiment, a set of control signals are accessed, wherein at least a first control signal of the set of control signals includes a measured acceleration value associated with a movement of a vehicle component of a vehicle, wherein the vehicle component is coupled with a frame of the vehicle via at least one vehicle suspension damper.

At operation 1560, in one embodiment, a set of freefall acceleration threshold values is accessed.

At operation 1565, in one embodiment, the measured acceleration value is compared with the set of freefall acceleration threshold values.

At operation 1570, in one embodiment, a state of at least one valve within the at least one vehicle suspension damper is monitored, wherein the state controls a damping force within the at least one vehicle suspension damper.

At operation 1575, in one embodiment, based on the comparing, a control mode is determined for the at least one vehicle suspension damper.

At operation 1580, in one embodiment, according to the control mode and based on the monitoring, damping forces are regulated within the at least one vehicle suspension damper by actuating the at least one valve to adjust to a desired state, such that a tilt of the frame is reduced.

FIG. 16A is a flow diagram of a method 1600 for controlling vehicle motion, in accordance with an embodiment. The method 1600 provides for control mode determinations based on a vehicle's global position, the time of day, the calendar date, the environmental temperature, and the humidity. The method 1600 starts at operation 1602. The method 1602 moves from operation 2602 to operation 1604.

At operation 1604, in one embodiment, the set of sensors 440 sense the vehicles global position, the environmental temperature and the humidity.

At operation 1606, in one embodiment, a date tracker 478 determines the time of day and the calendar date.

At operation 1608, in one embodiment, the control system 404 accesses (retrieves from the set of sensors 440 or receives from the set of sensors 440) the sensed information from the set of sensors 440 (such as the vehicle global position information, the environmental temperature information and the humidity information) and the date information from the date tracker 478 (such as the time of day and the calendar date). The control system 404, in one embodiment, compares the determined vehicle global position with a database of information regarding global positioning, compares the measured environmental temperature values with predetermined environmental temperature threshold values, and compares the measured humidity values with predetermined humidity threshold values 489. The control system 404 then determines, based on the comparisons made and the date information, control mode settings for each of the vehicle shock absorbers.

At operation 1610, in one embodiment, the control system 404 causes the control modes to be applied to the shock absorbers by setting the rebound and/or compression damping control modes.

FIG. 16B is a flow diagram of a method 1650 for controlling vehicle motion, in accordance with an embodiment. With reference to FIG. 16B and FIGS. 4A-4C, the method 1650 is described.

At operation 1655, in one embodiment, a set of control signals 442 is accessed, wherein at least a first control signal of the set of control signals 442 includes a measured location information associated with a location of a vehicle, wherein a vehicle suspension damper is coupled with a frame of the vehicle, wherein at least a second control signal of the set of control signals includes measured environmental information.

At operation 1660, in one embodiment, a set of date values is accessed.

At operation 1665, in one embodiment, the measured environmental information is compared with predetermined environmental threshold values 487.

At operation 1670, in one embodiment, a state of at least one valve within the at least one vehicle suspension damper is monitored, wherein the state controls a damping force within the at least one vehicle suspension damper.

At operation 1675, in one embodiment, based on the measured location information, the set of date values and the comparing, a control mode for the at least one vehicle suspension damper is determined.

At operation 1680, in one embodiment, according to the control mode and based on the monitoring, damping forces are regulated within the at least one vehicle suspension damper by actuating the at least one valve to adjust to a desired state, such that a tilt of the frame is reduced.

At FIGS. 17A-17C, user interfaces of the auto mode screen 1700, the manual mode screen 1720 and the shock setup screen 1740 are shown, in accordance with various embodiments. These user interfaces may appear on a touchscreen mounted in a vehicle or on a small phone/tablet that may be accessed remotely, in various embodiments.

The auto mode screen 1700 at FIG. 17A appears on an interactive touch screen, which includes any of the following options for automatic performance: a roll control option 1702; a load detect option 1704; an anti-squat option 1706; an anti-dive option 1708; and a freefall option 1710. Any of these options may be enabled or disabled. Additionally, a vehicle 1712 is shown at the auto mode screen 1700. A visual indicator (e.g., a color, a pattern, etc.) at each wheel shows if the rebound or compression of the shock absorber located at that wheel base is firm or soft.

The manual mode screen 1720 at FIG. 17B appears on an interactive touch screen, which includes various selectable options that, once selected, support a certain terrain, style, location, driving style, etc. related to the selection. For example, selectable options may include any of the following: a woods option 1722; a desert option 1724; a Barstow option 1726; a firm setting option 1728; a soft setting option 1730; a towing option 1732; and a rookie (slow driving) option 1734. Basically, parameters may be chosen based on a location of the vehicle or type of terrain anticipated to be traveling upon, for example. Additionally, parameters may be controlled through a remote phone that is communicatively coupled with a wireless transmitter located at the vehicle. Further, the manual mode screen 1720 may also include a visual of a vehicle 1736. A visual indicator (e.g., a color, a pattern, etc.) at each wheel represents what control mode under which each wheel is operating.

The shock setup screen 1740 at FIG. 17C appears on an interactive touch screen, in one embodiment, which includes displays a representation of the extent to which each shock absorber is functioning under a particular control mode. For example, the front right shock setup 1742 is shown to be functioning under all four control mode settings ("Firm Comp" 1744, "Firm Reb" 1746, "Soft Comp" 1748, and

“Soft Reb” 1750) at varying levels, as is represented by the color indicator extending from each control mode setting label.

It should be noted that any of the features disclosed herein may be useful alone or in any suitable combination. While the foregoing is directed to embodiments of the present invention, other and further embodiments of the invention may be implemented without departing from the scope of the invention, and the scope thereof is determined by the claims that follow.

What we claim is:

1. A method for adjusting a suspension damper based upon sensor input, said method comprising:
 receiving said sensor input corresponding to freefall information, said freefall information indicating that a vehicle to which said suspension damper is coupled is experiencing a resultant acceleration of less than 1 g, said sensor input obtained from a sensor; and
 changing a valve setting in said suspension damper based upon said sensor input, wherein said sensor input corresponding to said freefall information is generated by said sensor, wherein said sensor input is adjusted by a low-pass filter to ignore vibrations from an engine of said vehicle such that only an acceleration of the vehicle is included in said sensor input, and wherein a freefall timer is activated when said freefall information is generated by said sensor, wherein said valve setting in said suspension damper places said suspension damper in a firm mode when said freefall information is generated by said sensor, wherein, when said suspension damper is in said firm mode, said valve setting is at a most restrictive setting selected from a plurality of valve settings available to a user of said suspension damper.

2. The method for adjusting a suspension damper based upon sensor input as recited in claim 1, wherein said sensor input corresponding to said freefall information is generated by said sensor detecting that said vehicle is in a freefall condition.

3. The method for adjusting a suspension damper based upon sensor input as recited in claim 1, wherein a plurality of said suspension dampers are adjusted based upon said sensor input corresponding to said freefall information obtained by said sensor detecting a freefall condition for said vehicle.

4. The method for adjusting a suspension damper based upon sensor input as recited in claim 1, wherein said sensor input corresponding to said freefall information is generated by said sensor detecting a resultant magnitude of X, Y, and Z accelerations for said vehicle being less than a predetermined threshold value.

5. The method for adjusting a suspension damper based upon sensor input as recited in claim 1, wherein said sensor input corresponding to said freefall information is generated by a plurality of sensors detecting a resultant magnitude of X, Y, and Z acceleration for said vehicle being less than a predetermined threshold value.

6. The method for adjusting a suspension damper based upon sensor input as recited in claim 1, wherein said sensor input corresponding to said freefall information is generated by a plurality of sensors detecting a resultant magnitude of X, Y, and Z acceleration for said vehicle in the range of approximately 0 g and 1.0 g.

7. The method for adjusting a suspension damper based upon sensor input as recited in claim 1, wherein said sensor input corresponding to said freefall information is generated by said sensor detecting a non-zero g threshold acceleration value for said vehicle.

* * * * *