

(51) International Patent Classification:

B29C 65/36 (2006.01) B29C 65/74 (2006.01)
B65B 51/22 (2006.01) B29L 9/00 (2006.01)
B65B 51/30 (2006.01)

(21) International Application Number:

PCT/EP2017/060146

(22) International Filing Date:

28 April 2017 (28.04.2017)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

16167841.2 02 May 2016 (02.05.2016) EP

(71) Applicant: TETRA LAVAL HOLDINGS & FINANCE
S.A. [CH/CH]; 70, Avenue Général-Guisan, CH-1009
PULLY (CH).

(72) Inventor: PALMQUIST, Patrik; Fullriggaregatan 32, SE
23442 Lomma (SE).

(74) Agent: TETRA PAK - PATENT ATTORNEYS SE; AB
Tetra Pak, Patent Department Ruben Rausing's gata, 22186
LUND (SE).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ,

CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO,
DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN,
HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KH, KN, KP, KR,
KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG,
MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM,
PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC,
SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: IMPROVED INDUCTION SEALING SYSTEM




Fig. 2

(57) Abstract: The invention relates to an induction sealing system for heat sealing packaging material for producing sealed packages of pourable food products, said sealing system comprising: a sealing jaw (15) comprising at least one inductor device (20, 21) which interact with said packaging material by means of at least one active surface (25, 26); at least one flux-concentrating insert (30); a supporting body (24) comprising heat-conducting material and housing said inductor device (20, 21) and said flux-concentrating insert (30); and an interactive surface (31) for pressing against said package material; and a counter-jaw (16) comprising at least one pressure pad (52) made of elastomeric material, said pressure pad (52) being arranged to present a counter pressure to the sealing jaw (15), wherein said pressure pad (52) has an arched convex contact area (53) with height in the direction towards the sealing jaw (15).

IMPROVED INDUCTION SEALING SYSTEM

TECHNICAL FIELD

5 The present invention relates to an induction sealing system for heat sealing packaging material for producing sealed packages of pourable food products. More particular, the invention relates to an induction sealing system according to the introductory parts of claim 1.

10 BACKGROUND OF THE INVENTION

Many pourable food products, such as fruit juice, UHT milk, wine, tomato sauce, etc., are sold in packages made of sterilized packaging material.

15 A typical example of this type of package is the parallelepiped-shaped package for liquid or pourable food products known as Tetra Brik Aseptic (registered trademark), which is made by folding and sealing laminated strip packaging material.

20 The packaging material has a multilayer structure substantially comprising a base layer for stiffness and strength, which may comprise a layer of fibrous material, e.g. paper, or mineral-filled polypropylene material; and a number of layers of heat-seal plastic material, e.g. polyethylene films, covering both sides of the base layer.

25 In the case of aseptic packages for long-storage products, such as UHT milk, the packaging material also comprises a layer of gas- and light-barrier material, e.g. aluminium foil or ethyl vinyl alcohol (EVOH) film, which is superimposed on a layer of heat-seal plastic material, and is in turn covered with another layer of heat-seal plastic material forming the inner face of the package eventually contacting the food product.

As is known, packages of this sort are produced on fully automatic

packaging units, on which a continuous tube is formed from the web-fed packaging material; the web of packaging material is sterilized on the packaging unit, e.g. by applying a chemical sterilizing agent, such as a hydrogen peroxide solution, which, once sterilization is completed, is removed from the surfaces of the packaging material, e.g. evaporated by heating; and the web of packaging material so sterilized is maintained in a closed, sterile environment, and is folded and sealed longitudinally to form a vertical tube.

The tube is fed continuously in a first vertical direction, is filled with the sterilized or sterile-processed food product, and is gripped at equally spaced cross sections by two pairs of jaws. More specifically, the two pairs of jaws act cyclically and successively on the tube, and heat seal the packaging material of the tube to form a continuous strip of pillow packs connected to one another by respective transverse sealing bands, i.e. extending in a second direction perpendicular to said first direction.

The pillow packs are separated by cutting the relative transverse sealing bands, and are then fed to a final folding station where they are folded mechanically into the finished parallelepiped shape.

The tube portion gripped between each pair of jaws is heat sealed by heating means fitted to one of the jaws, known as the sealing jaw, and which locally melt the two layers of heat-seal plastic material gripped between the jaws.

More specifically, packaging material in which the layer of barrier material comprises a sheet of electrically conductive material, e.g. aluminium, is normally heat sealed by a so-called induction heat-sealing process, in which, when the tube is gripped by the two jaws, loss current is induced in, and locally heats, the aluminium sheet, thus melting the heat-seal plastic material locally.

More specifically, in induction heat sealing, the heating means sub-

stantially comprise an inductor powered by a high-frequency current generator and substantially comprising one or more inductor bars made of electrically conductive material, extending parallel to the second direction, and which interact with the tube material to induce a loss current in it and heat it
5 to the necessary sealing temperature.

The other jaw, known as the counter-jaw, on the other hand, is fitted with pressure pads made of elastomeric material, and which cooperate with the inductor bars to heat seal the tube along a relative transverse sealing band.

10 Sealing jaw sealing devices comprising inductors of the above type are known, e.g. from the patent documents EP 1 270 182 and EP 2 008 795.

More specifically, known sealing devices may comprise a plastic supporting body connected integrally to the sealing jaw and defining two
15 front seats for housing respective inductor bars; and an insert made of magnetic flux-concentrating material - in particular, a composite material comprising ferrite - and housed inside the supporting body, close to the inductor bars.

More specifically, the plastic supporting body cooperates with the insert, and defines a peripheral portion of the sealing device surrounding the
20 inductor bars and the insert of magnetic flux-concentrating material.

Further, the plastic supporting body and the insert may be replaced by a moulded flux-concentrating insert made of a polymer mixed with magnetic particles as e.g. ferrite. The moulded insert will then present the seats
25 for the counter jaw.

Known sealing jaws normally have a ridge formed by part of the inductor bars to create an extended pressure to the packing material along a line of the sealing.

The applicant has observed that the ridge made of the inductor bar that is usually made of copper will corrode and reduce the lifetime of the sealing jaw.

A further problem with transversal inductors is that sealing quality requirements on the packages are not always met due to occasional integrity issues when particles from the product that is filled into the package are trapped in the sealing area. Particles trapped in the sealing may damage the seal and puncture the package.

Finally, known transversal inductors have a high cost due to a complex manufacturing and the use of expensive materials.

There is thus a need for a transversal inductor which has an improved design, increased mechanical strength and increased lifetime, while maintaining or improving functionalities of the transversal inductor.

15

SUMMARY OF THE INVENTION

It is an object of the present invention to improve the current state of the art, to solve problems of the prior art, and to provide an improved induction sealing system for heat sealing packaging material for producing sealed packages of pourable food products that is simpler, cheaper, and more robust.

These and other objects are achieved by an induction sealing system for heat sealing packaging material for producing sealed packages of pourable food products, said sealing system comprising: a sealing jaw comprising at least one inductor device which interact with said packaging material by means of at least one active surface; at least one flux-concentrating insert; a supporting body comprising heat-conducting material and housing said inductor device and said flux-concentrating insert; and an interactive surface for pressing against said package material; and a counter-jaw comprising at least one pressure pad made of elastomeric material, said pres-

sure pad being arranged to present a counter pressure to the induction jaw, wherein said pressure pad has an arched convex contact area with height in the direction towards the sealing jaw.

5 By having a pressure pad or pressure pads that have an arched convex surface and since the pressure pad is made of elastomeric material, the contact between the sealing jaw and the counter-jaw will be gradual from the first contact of the highest point of the arched convex surface of the pressure pad with the sealing jaw until all of the arched convex contact area
10 is in contact with the sealing jaw. In that way food already filled into the package material will be gradually pressed out to the sides of the pressure pad when the sealing jaw is pressed against the counter-jaw before the actual induction sealing of the package by induction heating. Problems with seeds or other particle getting caught in the sealing will be overcome as the
15 particles will be gradually pressed out from the contact surfaces between the jaws avoiding being caught in the sealing.

The interactive surface of the sealing jaw is either the top of a plastic part that is moulded on top of the induction device to keep it and the flux concentrating insert in place, or it may be the top surface of the flux concentrating insert in case the flux concentrating insert is moulded. A moulded
20 flux concentrating insert may e.g. be made by a polymer mixed with ferrite particles or other magnetic particles.

According to a further aspect of the present invention the jaws of the induction sealing system are oblong having a length and a width so that
25 said induction device, said interactive surface and said active surface extend along the length of the inductor device; and said pressure pad of the counter-jaw extend along the length of the counter-jaw; wherein the width of the pressure pad is equal to or larger than the combined width of said active surface and said interactive surface.

30

The direction of the length is the same direction as the transversal direction of a transversal sealing system and the same direction as the band sealing direction on the band sealing being the end product of an induction

sealing made by the induction sealing system.

By having a width of the pressure pad that is as wide or wider than the width of the sealing jaw contact surfaces (the active surface and the interactive surface), the width of the induction sealing area is maximized and the magnetic field of the induction device is maximally utilized. After the package has been completely sealed it is in most cases folded at a later stage in the process of making the product package. The sealing is then usually folded towards a side of the package at the inner end of the sealing band. Traditionally it has been assumed that the band sealing is as wide as the sealing jaw, although the sealing is only as wide as the width of the pressure pad on the counter-jaw. Particles were therefore previously trapped close to the sealing and in the folding line creating problems with punctured packages. By having a wider sealing extending all the way to said folding line, particles will not be able to be trapped near the sealing in the folding process.

According to a still further aspect of the present invention the at least one pressure pad of the counter-jaw has a width that is equal to or larger than the combined width of said active surface and said interactive surface when the pressure pad is compressed during use. The pressure pad may thus have a slightly smaller width than the corresponding combined width of said active surface and said interactive surface since the elastic material of the pressure pad will expand in width when the jaws are pressed towards each other so that width of the pressure pads is as wide as the combined width of the active surface and the interactive surface at the time of the induction heat sealing process.

According to a still further aspect of the present invention the inductor device has a ridge extending in the direction of the length of the sealing jaw, said ridge being aligned to meet the highest portion of the arched convex surface of a pressure pad. The ridge of the sealing jaw is intended to form a line where the pressure is increased locally. To be able to squeeze out any

particles and food from the sealing area between the jaws, it is important that the ridge is placed so that the ridge and the highest point of the pressure pad meet the package material at the same point but on opposite sides of the package material.

5

According to a still further aspect of the present invention the inductor device has a ridge extending in the direction of the length of the inductor device, wherein said ridge being arranged in the center of said width, and the highest portion of said arched convex surface of a pressure pad is arranged in the center of the width of the pressure pad so as to meet said ridge first during use.

10

According to a still further aspect of the present invention the induction sealing system has a ridge that is made by a protruding part of said active surface of said inductor device. The active part of the inductor device is the conductor for the induction current, and is therefore preferably made of copper. Copper has a tendency to corrode, which in combination with the intense pressure changes during operation of the induction sealing system will reduce the lifetime of the sealing jaw. The ridge may, however, also be made by a protruding part of said interactive surface of said sealing jaw. Since the interactive surface is either pure plastic or a plastic material with particles in it, the material will not corrode. By placing the ridge in the interactive surface, corrosion of the ridge may be avoided and the lifetime of the sealing jaw is prolonged.

15

20

25

According to a still further aspect of the present invention the induction sealing system comprises a sealing jaw comprising two inductor devices in between which a cutting groove is arranged; and wherein said counter-jaw comprises two pressure pads in between which a knife is arranged. The induction sealing system will then simultaneously make two parallel transversal sealing bands which are separated from each other by the knife being moved from the counter jaw into the cutting groove of the sealing jaw.

30

DESCRIPTION OF THE DRAWINGS

In the following the present invention will be described in greater detail together with the accompanying drawings, in which

5 Figure 1 is cross sectional view of a package unit comprising two induction sealing systems according to the prior art.

Figure 2 is cross sectional view of the induction sealing system according to the present invention having a sealing jaw and a counter-jaw.

10

DETAILED DESCRIPTION

Number 1 in Figure 1 indicates as a whole a packaging unit for producing aseptic sealed packages 2 of a pourable food product, such as pasteurized or UHT milk, fruit juice, wine, etc., from a tube 3 of packaging material.

The packaging material has a multilayer structure (not shown), and comprises a layer of fibrous material, normally paper, covered on both sides with respective layers of heat-seal plastic material, e.g. polyethylene; and the side of the packaging material eventually contacting the food product in package 2 also has a layer of electrically conductive barrier material, e.g. aluminium, in turn covered with one or more layers of heat-seal plastic material.

25

Tube 3 is formed in known manner upstream from unit 1 by longitudinally folding and sealing a web of heat-seal sheet material, is filled with the sterilized or sterile-processed food product, and is fed by known devices (not shown) along a vertical path in a direction A.

30

Unit 1 comprises two forming assemblies 4, which move vertically along respective rails (not shown) and interact cyclically and successively with tube 3 to grip it at equally spaced cross sections and perform induction heat-seal and cutting operations on tube 3.

5

Each forming assembly 4 substantially comprises a slide (not shown) which runs along the respective rail; and two jaws 5, 6 (only shown as necessary for a clear understanding of the present invention) hinged to the slide about respective horizontal axes, and movable between a closed position and a fully-open position.

10

In the example shown, jaws 5, 6 of each forming assembly 4 have respective arms 7, 8, which interact with tube 3, extend parallel to a direction B perpendicular to direction A, and are located on opposite sides of tube 3.

15

Each forming assembly 4 also comprises two facing forming shells 9, 10 hinged to respective jaws 5, 6 and movable between an open position, into which they are pushed by elastic means (not shown), and a closed position, in which they mate to form a space defining the shape and volume of package 2 to be formed in between.

20

Each forming assembly 4 also comprises an induction sealing jaw 15 and a counter-jaw 16 comprising a cutting knife 32 for respectively performing, on each cross section of tube 3 of packaging material gripped between relative jaws 5, 6, an induction heat-seal operation and a cutting operation along the centre line of the cross section.

25

The induction sealing system has two sets of jaw-pairs 5, 6 according

to the prior art for sealing the tube to make separate pillows intended to become separate packages when cut from each other and folded properly. The induction sealing system has a transversal induction sealing jaw 15 having a supporting body 24 housing a flux-concentrating insert 30 which
5 flux-concentrating insert 30 houses inductor device 20, 21. The inductor device have active surfaces adapted to be pressed against a packing material surface (not shown) to induce current and thereby heat in a metal layer of the packing material during a sealing process. The inductor device 20, 21 and the flux-concentrating insert 30 are locked to the supporting body by a
10 moulded plastic member. The plastic member will also have an outer surface that will be pressed against the packing material during a sealing operation.

The induction sealing system of the prior art also comprises a counter-jaw 15 comprising two pressure pads 31 made of heat-resistant elastomeric material, preferably nitrile rubber, and housed in respective front cavities of the same shape formed in jaw 5 of relative forming assembly 4 and located symmetrically on opposite sides of the centre line A. Pressure pads 31 of each jaw 5 cooperate with active surfaces 25, 26 of inductors 20, 21
20 of relative jaw 6 to grip and heat seal tube 3 on opposite sides of the centre line A.

With reference to Figure 1, counter-jaw 16 comprises a substantially flat cutting member 32, which is housed in sliding manner inside a front seat
25 on jaw 5 of relative forming assembly 4, is movable towards the centre line A, and is activated in known manner, not shown, by a hydraulic cylinder built into jaw 5.

Cutting member 32 is normally maintained in a withdrawn rest position, housed completely inside jaw 5, by known elastic means (not shown),
30

and is moved by the relative hydraulic cylinder into a forward cutting position, in which it projects frontwards from jaw 5, engages recess 33 in sealing jaw 15 of relative jaw 6, and cuts along the centre line of the relative cross section of tube 3.

5

Figure 2 is cross sectional view of the induction sealing system according to the present invention having a sealing jaw 15 and a counter-jaw 16. The sealing jaw 15 has a supporting body 24 housing a flux-concentrating insert 30, two inductor devices 20, 21 on each side of the cutting groove 33. The parts are fastened by the plastic member 19 comprising the interactive surface 55 surrounding the active surfaces 25, 26 of the inductor devices 20, 21. A ridge 51 is present protruding from the plastic member 19 on each side of the cutting groove along the centre line C of each side of the sealing jaw 15.

15

The counter jaw 16 comprises a supporting body 56 housing two pressure pads 52. The pressure pads have arced convex contact surfaces 53 where the greatest height of the convex shape, in the direction towards the sealing jaw, of each of the pressure pads, is aligned with the centre line C. The pressure pads 52 are thus arranged to meet the ridges 51 on opposite sides of the package material (not shown in Fig. 2). The arced convex contact surfaces 53 will be compressed the jaws 15, 16 are pressed together. The shape of the pressure pads 52 are made so that the pressure pads 52 will present a uniform pressure to the sealing jaw 15 when the jaws 15, 16 are completely pressed together and the pressure pads 52 are compressed. When compressed, the width (perpendicular to the centre line C) of the pressure pads 52 will increase so that the entire contact area, 55, 25, 51, 26 of the sealing jaw 15 is exposed to the uniform pressure by the coun-

25

ter-jaw 16. The pressure will naturally still be higher at centre line where the ridges 51 will create a locally increased pressure.

It is to be understood that the ridge 51 protruding from the plastic member 19 on each side of the cutting groove can be arranged over or between the active surface 25, 26 depending on the application. The pressure pads having arced convex contact surfaces 53 where the greatest height of the convex shape, in the direction towards the sealing jaw, of each of the pressure pads, are arranged to meet the ridges 51 on opposite sides of the package material (not shown in Fig. 2). The arced convex contact surfaces 53 are thus placed to align with the ridge 51.

It is understood that other variations in the present invention are contemplated and in some instances, some features of the invention may be employed without a corresponding use of other features. Accordingly, it is appropriate that the appended claims be construed broadly in a manner consistent with the scope of the invention.


CLAIMS

1. An induction sealing system for heat sealing packaging material for producing sealed packages of pourable food products, said sealing system comprising:
- 5 - a sealing jaw (15) comprising
- at least one inductor device (20, 21) which interact with said packaging material by means of at least one active surface (25, 26);
- an insert (30) made of magnetic flux-concentrating material,
- 10 a supporting body (24) comprising heat-conducting material and housing said inductor device (20, 21) and said flux-concentrating insert (30); and
- an interactive surface (55) for pressing against said package material;
- 15 and
- a counter-jaw (16) comprising at least one pressure pad (52) made of elastomeric material, said pressure pad (52) being arranged to present a counter pressure to the sealing jaw (15),
- wherein said pressure pad (52) has an arched convex contact area (53)
- 20 with height in the direction towards the sealing jaw (15).
2. The induction sealing system according to claim 1, wherein said jaws (15, 16) are oblong having a length (x) and a width (y) so that said inductor device (20, 21), said interactive surface (55) and said active surface (25, 26) extend along the length of the inductor device (x); and
- 25 said pressure pad (52) of the counter-jaw (16) extend along the length (x) of the counter-jaw (16);
- wherein the width of the pressure pad (52) is equal to or larger than the combined width of said active surface (25, 26) and said interactive surface (55).
- 30 3. The induction sealing system according to claim 2, wherein said at least one pressure pad (52) of the counter-jaw (16) has a width that is equal


to or larger than the combined width of said active surface (25, 26) and said interactive surface when the pressure pad (52) is compressed during use.

- 5 4. The induction sealing system according to any one of the preceding claims, wherein said inductor device has a ridge (51) extending in the direction (x) of the length of the sealing jaw (15), said ridge (51) being aligned to meet the highest portion of the arched convex surface (53) of a pressure pad (52).
- 10
5. The induction sealing system according to any one of the preceding claims, wherein said inductor device has a ridge (51) extending in the direction (x) of the length of the inductor device, wherein said ridge being arranged in the center of said width and wherein the highest portion
- 15 of said arched convex surface of a pressure pad is arranged in the center of the width of the pressure pad so as to meet said ridge first during use.
6. The induction sealing system according to any one of claims 4-5,
- 20 wherein said ridge (51) is made by a protruding part of said active surface (25, 26) of said inductor device (20, 21).
7. The induction sealing system according to any one of claims 4-5,
- 25 wherein said ridge (51) is made by a protruding part of said interactive surface (55) of said sealing jaw (15).
8. The induction sealing system according to any one of the preceding claims, wherein said sealing jaw (15) comprises two inductor devices (20, 21) in between which a cutting groove (33) is arranged; and where-
- 30 in said counter-jaw (16) comprises two pressure pads (52) in between which a knife is arranged.

1/2



2/2



INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2017/060146

A. CLASSIFICATION OF SUBJECT MATTER
INV. B29C65/36 B65B51/22 B65B51/30
ADD. B29C65/74 B29L9/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
B29C B65B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 3 000 584 A1 (TETRA LAVAL HOLDINGS & FINANCE [CH]) 30 March 2016 (2016-03-30) paragraphs [0047], [0061]; figures 1,2 -----	1-8
Y	WO 2005/105579 A1 (TETRA LAVAL HOLDINGS & FINANCE [CH]; SHOKRI EBI [SE]; PALMQUIST ROLAND) 10 November 2005 (2005-11-10) page 9, lines 25-27; figures 7,8 page 10, lines 34-35 -----	1-8
A	EP 2 008 795 A1 (TETRA LAVAL HOLDINGS & FINANCE [CH]) 31 December 2008 (2008-12-31) cited in the application figures 1,2 ----- -/-	1



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

10 July 2017

Date of mailing of the international search report

18/07/2017

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Carré, Jérôme

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2017/060146

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 2 468 480 A1 (TETRA LAVAL HOLDINGS & FINANCE [CH]) 27 June 2012 (2012-06-27) figures 1,2 -----	1
A	FR 2 776 616 A1 (TETRA LAVAL HOLDINGS & FINANCE [CH]) 1 October 1999 (1999-10-01) figures 4,3 -----	1
A	EP 1 300 340 A1 (TETRA LAVAL HOLDINGS & FINANCE [CH]) 9 April 2003 (2003-04-09) figure 2 -----	1
A	WO 2014/072477 A1 (TETRA LAVAL HOLDINGS & FINANCE [CH]) 15 May 2014 (2014-05-15) figures -----	1
A	WO 2015/040173 A1 (TETRA LAVAL HOLDINGS & FINANCE [CH]) 26 March 2015 (2015-03-26) figures 1,3 -----	1
A	US 7 003 934 B1 (YANO KEIJI [JP]) 28 February 2006 (2006-02-28) figures 4,5 -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2017/060146

Patent document cited in search report		Publication date		Patent family member(s)		Publication date
EP 3000584	A1	30-03-2016	CN	106573418 A		19-04-2017
			EP	3000584 A1		30-03-2016
			KR	20170057255 A		24-05-2017
			WO	2016045967 A1		31-03-2016

WO 2005105579	A1	10-11-2005	AT	431294 T		15-05-2009
			AU	2005237936 A1		10-11-2005
			BR	PI0509962 A		25-09-2007
			CA	2559812 A1		10-11-2005
			CN	1938193 A		28-03-2007
			EP	1744957 A1		24-01-2007
			ES	2324943 T3		20-08-2009
			HK	1103233 A1		12-03-2010
			JP	4443602 B2		31-03-2010
			JP	2007534572 A		29-11-2007
			KR	20070010036 A		19-01-2007
			PT	1744957 E		26-06-2009
			RU	2359882 C2		27-06-2009
			SE	0401101 A		30-10-2005
			UA	83739 C2		11-08-2008
			US	2007251196 A1		01-11-2007
			WO	2005105579 A1		10-11-2005

EP 2008795	A1	31-12-2008	AT	522343 T		15-09-2011
			BR	PI0811163 A2		23-12-2014
			CN	101687365 A		31-03-2010
			EP	2008795 A1		31-12-2008
			ES	2372874 T3		27-01-2012
			JP	5132769 B2		30-01-2013
			JP	2010531282 A		24-09-2010
			KR	20100027172 A		10-03-2010
			RU	2010102789 A		10-08-2011
			UA	99829 C2		10-10-2012
			US	2010180545 A1		22-07-2010
			WO	2009000928 A2		31-12-2008

EP 2468480	A1	27-06-2012	CN	103260856 A		21-08-2013
			EP	2468480 A1		27-06-2012
			JP	6131405 B2		24-05-2017
			JP	2014505638 A		06-03-2014
			US	2013263556 A1		10-10-2013
			WO	2012084510 A1		28-06-2012

FR 2776616	A1	01-10-1999	DE	19912820 A1		30-09-1999
			FR	2776616 A1		01-10-1999
			JP	4344417 B2		14-10-2009
			JP	H11310209 A		09-11-1999
			US	6216420 B1		17-04-2001

EP 1300340	A1	09-04-2003	AT	371586 T		15-09-2007
			DE	60130216 T2		29-05-2008
			EP	1300340 A1		09-04-2003
			ES	2291289 T3		01-03-2008
			JP	4291990 B2		08-07-2009
			JP	2003155005 A		27-05-2003
			PT	1300340 E		06-12-2007

WO 2014072477	A1	15-05-2014	CN	104768732 A		08-07-2015

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2017/060146

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
		EP 2917021 A1	16-09-2015
		JP 2015535511 A	14-12-2015
		US 2015266603 A1	24-09-2015
		WO 2014072477 A1	15-05-2014

WO 2015040173 A1	26-03-2015	CN 105555505 A	04-05-2016
		EP 3046744 A1	27-07-2016
		JP 2016533974 A	04-11-2016
		US 2016229118 A1	11-08-2016
		WO 2015040173 A1	26-03-2015

US 7003934 B1	28-02-2006	AU 6487999 A	22-05-2000
		JP 4232922 B2	04-03-2009
		JP 2002249110 A	03-09-2002
		US 7003934 B1	28-02-2006
		WO 0026089 A1	11-05-2000
