

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
13 September 2007 (13.09.2007)

PCT

(10) International Publication Number  
**WO 2007/103547 A2**

(51) International Patent Classification:  
**B01F 11/02** (2006.01)

(21) International Application Number:  
PCT/US2007/006018

(22) International Filing Date: 9 March 2007 (09.03.2007)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
11/372,492 9 March 2006 (09.03.2006) US  
11/372,226 9 March 2006 (09.03.2006) US

(71) Applicant (for all designated States except US):  
**SEARETE LLC** [US/US]; 1756 - 114th Ave. SE,  
Suite 110, Bellevue, WA 98004 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **HOOD, Leroy,**


**E.** [US/US]; 6411 N.E. Windermere Road, Seattle, WA 98105 (US). **ISHIKAWA, Muriel, Y.** [US/US]; 1185 Hillcrest Avenue, Livermore, CA 94550 (US). **JUNG, Edward, K.Y.** [US/US]; 13420 NE 36th Street, Bellevue, WA 98005-1403 (US). **LANGER, Robert** [US/US]; 98 Montvale Road, Newton, MA 02459 (US). **TEGREENE, Clarence, T.** [US/US]; 1756 - 114th Avenue SE, Ste. 110, Bellevue, WA 98004 (US). **WOOD, Lowell, L.** [US/US]; 989 112th Avenue NE #2310, Bellevue, WA 98004 (US). **WOOD, Victoria, Y.H.** [US/US]; 1185 Hillcrest Avenue, Livermore, CA 94550-4921 (US).

(74) Agent: **TEGREENE, Clarence, T.**; 1756 - 114th Avenue SE, Ste. 110, Bellevue, WA 98004 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, MG, MK, MN, MW, MX, MY, MZ,

[Continued on next page]

(54) Title: ACOUSTICALLY CONTROLLED SUBSTANCE DELIVERY DEVICE



(57) Abstract: Embodiments of a system including a remotely controlled substance delivery device and associated controller are described. Methods of use and control of the device are also disclosed. According to some embodiments, a deliverer device or related device may be placed in an environment in order to pump a material into the environment or into an additional fluid handling structure within the device. Exemplary environments include a body of an organism, a body of water, or an enclosed volume of a fluid. The concentration of a substance in the fluid to be delivered may be modified by a remote control signal. In selected embodiments, an acoustic control signal may be used.



NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU,  
SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR,  
TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM,  
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**(84) Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, PL,

**Published:**

— *without international search report and to be republished upon receipt of that report*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

## **Acoustically Controlled Substance Delivery Device**

**Inventor(s): Leroy E. Hood, Muriel Y. Ishikawa, Edward  
K.Y. Jung, Robert Langer, Clarence T. Tegreene, Lowell  
L. Wood, Jr., and Victoria Y.H. Wood**

### **CROSS-REFERENCE TO RELATED APPLICATIONS**

The present application is related to and claims the benefit of the earliest available effective filing date(s) from the following listed application(s) (the "Related Applications") (*e.g.*, claims earliest available priority dates for other than provisional patent applications or claims benefits under 35 USC § 119(e) for provisional patent applications, for any and all parent, grandparent, great-grandparent, etc. applications of the Related Application(s)).

#### **Related Applications:**

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application No. 11/271,145, entitled REACTION DEVICE CONTROLLED BY MAGNETIC CONTROL SIGNAL, naming Leroy E. Hood, Muriel Y. Ishikawa, Edward K.Y. Jung, Robert Langer, Clarence T. Tegreene, Lowell L. Wood, Jr. and Victoria Y. H. Wood as inventors, filed November 9, 2005, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application

No. 11/271,146, entitled REACTION DEVICE CONTROLLED BY RF CONTROL SIGNAL, naming Leroy E. Hood, Muriel Y. Ishikawa, Edward K.Y. Jung, Robert Langer, Clarence T. Tegreene, Lowell L. Wood, Jr. and Victoria Y. H. Wood as inventors, filed November 9, 2005, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application No. 11/270,799, entitled REMOTE CONTROLLED IN SITU REACTION METHOD, naming Leroy E. Hood, Muriel Y. Ishikawa, Edward K.Y. Jung, Robert Langer, Clarence T. Tegreene, Lowell L. Wood, Jr. and Victoria Y. H. Wood as inventors, filed November 9, 2005, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application No. 11/272,455, entitled REMOTE CONTROLLER FOR IN SITU REACTION DEVICE, naming Leroy E. Hood, Muriel Y. Ishikawa, Edward K.Y. Jung, Robert Langer, Clarence T. Tegreene, Lowell L. Wood, Jr. and Victoria Y. H. Wood as inventors, filed November 9, 2005, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application No. 11/272,572, entitled REMOTE CONTROLLED IN VIVO REACTION METHOD, naming Leroy E. Hood, Muriel Y. Ishikawa, Edward K.Y. Jung, Robert Langer, Clarence T. Tegreene, Lowell L. Wood, Jr. and Victoria Y. H. Wood as inventors, filed November 9, 2005, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application No. 11/272,573, IN SITU REACTION DEVICE, naming Leroy E. Hood, Muriel Y. Ishikawa, Edward K.Y. Jung, Robert Langer, Clarence T. Tegreene, Lowell L. Wood, Jr. and Victoria Y. H. Wood as inventors, filed November 9, 2005, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application No. 11/272,524, entitled REMOTE CONTROLLED IN SITU REACTION DEVICE, naming Leroy E. Hood, Muriel Y. Ishikawa, Edward K.Y. Jung, Robert Langer, Clarence T. Tegreene, Lowell L. Wood, Jr. and Victoria Y. H. Wood as inventors, filed November 9, 2005, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application No. 11/302,449, entitled OSMOTIC PUMP WITH REMOTELY CONTROLLED OSMOTIC PRESSURE GENERATION, naming Leroy E. Hood, Muriel Y. Ishikawa, Edward K.Y. Jung, Robert Langer, Clarence T. Tegreene, Lowell L. Wood, Jr. and Victoria Y. H. Wood as inventors, filed December 13, 2005, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application No. 11/335,785, entitled REMOTELY CONTROLLED SUBSTANCE DELIVERY DEVICE, naming Leroy E. Hood, Muriel Y. Ishikawa, Edward K.Y. Jung, Robert Langer, Clarence T. Tegreene, Lowell L. Wood, Jr. and Victoria Y. H. Wood as inventors, filed January 18, 2006, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application No. 11/302,321, entitled OSMOTIC PUMP WITH REMOTELY CONTROLLED OSMOTIC FLOW RATE, naming Leroy E. Hood, Muriel Y. Ishikawa, Edward K.Y. Jung, Robert Langer, Clarence T. Tegreene, Lowell L. Wood, Jr. and Victoria Y. H. Wood as inventors, filed December 13, 2005, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application No. 11/302,407, entitled REMOTE CONTROL OF OSMOTIC PUMP DEVICE, naming Leroy E. Hood, Muriel Y. Ishikawa, Edward K.Y. Jung, Robert Langer, Clarence T. Tegreene, Lowell L. Wood, Jr. and Victoria Y. H. Wood as inventors, filed December 13, 2005, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application No. 11/302,450, entitled METHOD AND SYSTEM FOR CONTROL OF OSMOTIC PUMP DEVICE, naming Leroy E. Hood, Muriel Y. Ishikawa, Edward K.Y. Jung, Robert Langer, Clarence T. Tegreene, Lowell L. Wood, Jr. and Victoria Y. H. Wood as inventors, filed December 13, 2005, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application No. 11/335,786, entitled SUBSTANCE DELIVERY SYSTEM, naming Leroy E. Hood, Muriel Y. Ishikawa, Edward K.Y. Jung, Robert Langer, Clarence T. Tegreene, Lowell L. Wood, Jr. and Victoria Y. H. Wood as inventors, filed January 18, 2006, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application No. 11/335,788, entitled REMOTE CONTROL OF SUBSTANCE DELIVERY SYSTEM, naming Leroy E. Hood, Muriel Y. Ishikawa, Edward K.Y. Jung, Robert Langer, Clarence T. Tegreene, Lowell L. Wood, Jr. and Victoria Y. H. Wood as inventors, filed January 18, 2006, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application No. 11/335,911, entitled REMOTE CONTROLLER FOR SUBSTANCE DELIVERY SYSTEM, naming Leroy E. Hood, Muriel Y. Ishikawa, Edward K.Y. Jung, Robert Langer, Clarence T. Tegreene, Lowell L. Wood, Jr. and Victoria Y. H. Wood as inventors, filed January 18, 2006, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application No. \_\_\_\_\_, entitled ACOUSTICALLY CONTROLLED REACTION DEVICE, naming Leroy E. Hood, Muriel Y. Ishikawa, Edward K.Y. Jung, Robert Langer, Clarence T. Tegreene, Lowell L. Wood, Jr. and Victoria Y. H. Wood as inventors, filed March 9, 2006, which is currently co-pending, or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

The United States Patent Office (USPTO) has published a notice to the effect that the USPTO's computer programs require that patent applicants reference both a serial number and indicate whether an application is a continuation or continuation-in-part. Stephen G. Kunin, *Benefit of Prior-Filed Application*, USPTO Official Gazette March 18, 2003, available at <http://www.uspto.gov/web/offices/com/sol/og/2003/week11/patbene.htm>. The present applicant entity has provided above a specific reference to the application(s) from which priority is being claimed as recited by statute. Applicant entity

understands that the statute is unambiguous in its specific reference language and does not require either a serial number or any characterization, such as "continuation" or "continuation-in-part," for claiming priority to U.S. patent applications. Notwithstanding the foregoing, applicant entity understands that the USPTO's computer programs have certain data entry requirements, and hence applicant entity is designating the present application as a continuation-in-part of its parent applications as set forth above, but expressly points out that such designations are not to be construed in any way as any type of commentary and/or admission as to whether or not the present application contains any new matter in addition to the matter of its parent application(s).

All subject matter of the Related Applications and of any and all parent, grandparent, great-grandparent, etc. applications of the Related Applications is incorporated herein by reference to the extent such subject matter is not inconsistent herewith.

## **TECHNICAL FIELD**

The present application relates, in general, to the field of devices, systems and/or methods for remotely controlled delivery of materials.

## **BACKGROUND**

Implantable controlled release devices for drug delivery have been developed. Certain devices rely upon the gradual release of a drug from a polymeric carrier over time, due to degradation of the carrier. Polymer-based drug release devices are being developed that include a drug in a ferropolymer that may be heated by an externally applied magnetic field, thus influencing the drug release. MEMS based drug release devices that include integrated electrical circuitry are also under development, as are MEMS based systems for performing chemical reactions. Implantable delivery devices have been developed for drug delivery purposes. Wireless transmission of electromagnetic signals of various frequencies is well known in the areas of communications and data transmission, as well as in selected biomedical applications.



## SUMMARY

The present application relates, in general, to the field of fluid delivery devices, systems, and methods. In particular, the present application relates to remotely controlled delivery devices in which the concentration of a material in a fluid to be delivered may be varied. Control signals may be carried between a remote controller and a delivery device in an environment by electrical, magnetic, or electromagnetic fields or radiation. Embodiments of a system including a remotely controlled delivery device and associated controller are described. Methods of use and control of the device are also disclosed. According to various embodiments, a delivery device may be placed in an environment in order to eject or release a material into the environment. Exemplary environments include a body of an organism, a body of water or other fluid, or an enclosed volume of a fluid. According to some embodiments, a delivery device may provide for delivery of a fluid into a downstream fluid-handling structure. The foregoing summary is illustrative only and is not intended to be in any way limiting. In addition to the illustrative aspects, embodiments, and features described above, further aspects, embodiments, and features will become apparent by reference to the drawings and the following detailed description.

## BRIEF DESCRIPTION OF THE FIGURES

FIG. 1 depicts an embodiment of a delivery system for use in a human subject;

FIG. 2 depicts an embodiment of a delivery system including a remote controller;

FIG. 3 depicts another embodiment of a delivery system including a remote controller;

FIGS. 4A and 4B illustrate in schematic form a change in concentration in a fluid to be delivered by an embodiment of a delivery device;

FIG. 5 depicts an electromagnetically responsive control element including a polymer and magnetically or electrically active components;

FIG. 6A – 6D show examples of first active and second forms of primary material in delivery fluid;

FIGS. 7A and 7B illustrate a change in concentration in delivery fluid in exemplary delivery device including an osmotic pump;

FIGS. 8A and 8B illustrate a change in concentration in a delivery fluid produced by a heating element;

FIGS. 9A and 9B illustrate a change in concentration in a delivery fluid produced by a cooling element;

FIGS. 10A and 10B illustrate a change in concentration in a delivery fluid produced by interaction of a primary material with an interaction region;

FIGS. 11A and 11B illustrate a change in concentration of primary material influenced by secondary material in a delivery fluid;

FIG. 12A depicts an exemplary interaction region;

FIG. 12B depicts expansion of the interaction region of FIG. 12A in a first direction;

FIG. 12C depicts expansion of the interaction region of FIG. 12A in a second direction;

FIG. 12D depicts expansion of the interaction region of FIG. 12A in first and second directions;

FIGS. 13A and 13B depict unfolding of a pleated interaction region;

FIGS. 14A and 14B depict another embodiment of an interaction region;

FIGS. 15A and 15B depict an example of an effect of stretching an interaction region;

FIG. 16A and 16B depict another example of an effect of stretching an interaction region;

FIG. 17A and 17B depict an exemplary embodiment of an interaction region;

FIG. 18A and 18B depict another exemplary embodiment of an interaction region;

FIG. 19A and 19B depict another exemplary embodiment of an interaction region;

FIG. 20A and 20B illustrate expansion of a delivery reservoir of a delivery device;

FIG. 21 is a schematic diagram of an embodiment of a delivery device;

FIG. 22 is a schematic diagram of another embodiment of a delivery device;

FIG. 23 depicts an embodiment of a system including a remotely controlled delivery device;

FIG. 24 depicts another embodiment of a system including a remotely controlled delivery device;

FIG. 25 depicts another embodiment of a system including a remotely controlled delivery device;

FIG. 26 illustrates a control signal generated from stored pattern data;

FIG. 27 illustrates a control signal calculated from a model based on stored parameters;

FIG. 28 is a schematic diagram of a remote controller;

FIG. 29 depicts an exemplary control signal;

FIG. 30 depicts another exemplary control signal;

FIG. 31 depicts another exemplary control signal;

FIG. 32 illustrates an embodiment of a delivery device including a downstream fluid handling structure;

FIG. 33 illustrates another embodiment of a delivery device including a downstream fluid handling structure;

FIG. 34 illustrates an embodiment of a delivery device including a fluid containing structure;

FIG. 35 illustrates an embodiment of a delivery device including an environmental interface;

FIG. 36 is a flow diagram of a method of delivering a fluid;

FIG. 37 is a flow diagram of a further method of delivering a fluid;

FIG. 38 is a flow diagram of a further method of delivery a fluid;

FIG. 39 is a schematic diagram of an embodiment of a system including a remote controller and a delivery device;

FIG. 40 is a diagram of an embodiment of a delivery system including a delivery device with an RFID;

FIG. 41 is a schematic diagram of an embodiment a system including a remote controller, a delivery device, and a sensor;

FIG. 42 is a schematic diagram of an embodiment a system including a remote controller and a delivery device including a sensor;

FIG. 43 is a schematic diagram of another embodiment of system including a remote controller and a delivery device; and

FIG. 44 is an embodiment of a system including a remote controller and a plurality of delivery devices in an environment.

FIG. 45 is a schematic of an embodiment of a delivery system;

FIG. 46 is a schematic of a further embodiment of a delivery system;

FIG. 47 is a schematic of a further embodiment of a delivery system;

FIG. 48 is a schematic of another embodiment of a delivery system;

FIG. 49 depicts an embodiment of a delivery system including encryption;

FIG. 50 depicts an embodiment of a delivery system that utilizes an authentication procedure;

FIG. 51 is a flow diagram of a method of delivering a fluid;

FIG. 52 is a flow diagram of a method of delivering a material;

FIG. 53 is a flow diagram of a portion of a method of delivering a material;

FIG. 54 is a flow diagram of another method of delivering a material;

FIG. 55 is a flow diagram of an expansion of the method of FIG. 54;

FIG. 56 is a flow diagram of an expansion of the method of FIG. 54;

FIG. 57 is a flow diagram of a further method of delivering a material;

FIG. 58 is a flow diagram of a method of controlling a delivery device;

FIG. 59 is an expansion of the method of FIG. 58;

FIG. 60 is a flow diagram of additional steps for controlling a delivery device;

FIG. 61 is a flow diagram of alternative additional steps for controlling a delivery device;

FIG. 62 is a flow diagram of further alternative additional steps for controlling a delivery device;

FIG. 63 is a further expansion of the method of FIG. 58;

FIG. 64 is another expansion of the method of FIG. 58;

FIG. 65 is still another expansion of the method of FIG. 58;

FIG. 66 is a schematic diagram of another embodiment of a delivery system;

FIG. 67 is a flow diagram of a method of controlling a delivery device;

FIG. 68 is a flow diagram showing alternative details of the method shown in FIG. 67; and

FIG. 69 is a flow diagram showing further alternative details of the method shown in FIG. 67.

## DETAILED DESCRIPTION

In the following detailed description, reference is made to the accompanying drawings, which form a part hereof. In the drawings, similar symbols typically identify similar components, unless context dictates otherwise. The illustrated embodiments described in the detailed description, drawings, and claims are not meant to be limiting. Other embodiments may be utilized, and other changes may be made, without departing from the spirit or scope of the subject matter presented here.

FIG. 1 depicts a first exemplary embodiment of a delivery system 10. In the embodiment of FIG. 1, delivery system 10 includes delivery device 12 located in an environment 14, (which in this particular example is a human body) and remote controller 16. As used herein, the term “remote” refers to the transmission of information (e.g. data or control signals) or power signals or other interactions between spatially separated devices or apparatuses, such as the remote controller or the delivery system, without a connecting element such as a wire or cable linking the remote controller and the delivery system, and does not imply a particular spatial relationship between the remote controller and the delivery device, which may, in various embodiments, be separated by relatively large distances (e.g. miles or kilometers) or a relatively small distances (e.g. inches or millimeters). Delivery device 12 includes an electromagnetically or acoustically responsive control element 18 that is responsive to an electromagnetic or acoustic control signal generated by remote controller 16.

FIG. 2 depicts an embodiment of a delivery system 20 including a delivery device 22 controlled by remote controller 24. In the embodiment of FIG. 2, delivery device 22 includes pump 26 and delivery reservoir 28 which contains delivery fluid 30. Remote controller 24 transmits electromagnetic control signal 32 to electromagnetically responsive control element 34 to control the concentration of primary material 36 in

delivery fluid 30. Pump 26 pumps delivery fluid 30 containing primary material 36 from delivery reservoir 28 via outlet 37. Delivery device 22 also includes a body structure 38. In this and various other embodiments, as an alternative, the system may utilize an acoustic, rather than electromagnetic, control signal, and an acoustically responsive control element. In this and other embodiments described herein, although a single outlet is depicted, any number of outlets may be used. Moreover, while in some embodiments an outlet may be a simple opening, in others the outlet may include a permeable or semi-permeable membrane, filter or other some structure which permits the exit of delivery fluid (or components of thereof) from the delivery reservoir.

FIG. 3 depicts another embodiment of a delivery system 40 including a delivery device 42 controlled by remote controller 44. In the embodiment of FIG. 3, delivery device 42 includes pump 46 and delivery reservoir 28, which contains delivery fluid 30. Remote controller 44 transmits electromagnetic distribution control signal 32 to electromagnetically responsive control element 34 to control the concentration of primary material 36 in delivery fluid 30. Remote controller 44 also transmits electromagnetic delivery control signal 48 to receiving element 50 in pump 46 to control the pumping of delivery fluid 30 from delivery reservoir 28. Outlet 37 and body structure 38 are also included in delivery device 48.

FIGS. 4A and 4BA illustrate in schematic form a delivery device 60 comprising a delivery reservoir 62 configured to contain a delivery fluid, the delivery reservoir having at least one outlet 64 through which the delivery fluid may exit the delivery reservoir; a delivery fluid 66 contained within the delivery reservoir 62; a primary material 68 contained within the delivery reservoir 62 and having a controllable effective concentration in the delivery fluid; and at least one electromagnetically responsive control element 70 adapted for modifying the distribution of the primary material between a first active form carried in the delivery fluid and a second form in response to an incident electromagnetic control signal, the effective concentration being the concentration of the first active form in the delivery fluid. Delivery fluid may exit delivery reservoir 66 by diffusion, or by being moved out of delivery reservoir 66 by positive pressure applied to delivery reservoir 62 (e.g. by a pump) or negative pressure generated downstream of delivery reservoir 62. FIG. 4A illustrates a first state of

electromagnetically responsive control element 70, which causes primary material 68 to be in a first active form in delivery fluid 66. FIG. 4B illustrates a second state of electromagnetic control element 70, which causes the primary material to be in a second form 68', which is not an active form carried in delivery fluid 66, but may be, for example, insoluble in delivery fluid 66 as depicted in FIG. 4B.

In order to modify the distribution of primary material between the first active form and the second form, the electromagnetically responsive control element used in this and other embodiments (e.g., 34 in FIGS. 2 and 3 or 70 in FIGS. 4A and 4B) may have various functional characteristics. In some embodiments, the electromagnetically responsive control element may include or form a heating element (e.g., a resistive element) or a cooling element (which may be, for example, a thermoelectric device). In some embodiments, the electromagnetically responsive control element may be an expanding element. In some embodiments, an electromagnetically responsive control element may include a receiving element such as an antenna or other geometric gain structure to enhance the receiving of an electromagnetic control signal transmitted from a remote control signal generator. The response of the electromagnetically responsive control element to an electromagnetic field may be due to absorption of energy from the electromagnetic signal or due to torque or traction on all or a portion of the electromagnetically responsive control element due to the electromagnetic field. The response will depend upon the intensity, the relative orientation and the frequency of the electromagnetic field and upon the geometry, composition and preparation of the material of the electromagnetically responsive control element. A response may occur on the macro level, on a microscopic level, or on a nanoscopic or molecular level. In some embodiments, the electromagnetically responsive control element may respond to the control signal by changing shape. In some embodiments, the electromagnetically responsive control element may respond to the control signal by changing in at least one dimension. The response of the electromagnetically responsive control element may include one or more of heating, cooling, vibrating, expanding, stretching, unfolding, contracting, deforming, softening, or folding globally or locally. In some embodiments, the electromagnetically responsive control element may be configured to selectively respond to an electromagnetic field having a specific frequency and orientation.

Frequency selectivity may be conferred by appropriate selection of electromagnetically responsive control element size relative to the wavelength of the electromagnetic signal, while directional selectivity may be conferred by the configuration and orientation of the electromagnetically responsive control element.

Electromagnetically responsive control elements used in various embodiments of delivery devices and systems may include one or more electromagnetically active materials. The electromagnetically responsive control element may include a magnetically or electrically active material. Examples of magnetically active materials include permanently magnetizable materials, ferromagnetic materials such as iron, nickel, cobalt, and alloys thereof, ferrimagnetic materials such as magnetite, ferrous materials, ferric materials, diamagnetic materials such as quartz, paramagnetic materials such as silicate or sulfide, and antiferromagnetic materials such as canted antiferromagnetic materials which behave similarly to ferromagnetic materials; examples of electrically active materials include ferroelectrics, piezoelectrics, dielectric materials, including permanently 'poled' dielectrics and dielectrics having both positive and negative real permittivities, and metallic materials.

In some embodiments, the electromagnetically responsive control element may include a hydrogel, ferrogel, or ferroelectric. The electromagnetically responsive control element may include a polymer, ceramic, dielectric, or metal. The electromagnetically responsive control element may include various materials, such as polymers, ceramics, plastics, dielectrics or metals, or combinations thereof. In some embodiments, the electromagnetically responsive control element may include a polymer and a magnetically or electrically active component. In some embodiments, the electromagnetically responsive control element may include a shape memory material such as a shape memory polymer or a shape memory metal, or a composite structure such as a bimetallic structure.

In some embodiments, the remotely activatable control element may be responsive to an acoustic control signal. The remotely activatable control element may respond to the control signal by changing shape. In some embodiments, the remotely activatable control element may respond to the control signal by changing in at least one dimension. The response of the remotely activatable control element may include one or



more of heating, cooling, vibrating, expanding, stretching, unfolding, contracting, deforming, softening, or folding globally or locally. The remotely activatable control element may include various materials, such as polymers, ceramics, crystalline materials, or combinations thereof. Effects of acoustic energy applied to a material may include heating or cavitation (formation of gas bubbles due to local reduction in pressure), acoustic torque or streaming, and, at the molecular level, rotation, translation, or vibration. Heating may be produced when acoustic energy is absorbed by a material, rather than being reflected from or transmitted through the material. In body tissues, absorption is relatively lower in tissues having high water content, and relatively higher in tissues having high protein content. Higher heating may be obtained the interface of materials having different acoustic impedances, for example, at soft tissue-bone interface. Reflection of acoustic energy at interfaces may lead to standing waves or hot spots; and the larger the difference in acoustic impedance at an interface between two materials or tissues, the more energy will be reflected at the interface. Higher levels of heating may be obtained at gas bubbles than in surrounding fluid/tissue. Materials that may respond to an acoustic signal by producing an electrical signal include piezoelectric materials, including natural crystals such as quartz, as well as synthetic ceramics such as lead zirconate titanate (e.g., PZT-4, PZT-8), lead zirconate, lead titanate, barium titanate, nickel cobalt, and ceramic/polymer composites. Moreover, response to acoustic signals may be indirect, as well. For example, a MEMS structure may respond by physically deforming responsive to an acoustic signal. Known structures can convert deformation in MEMS structures to electrical or other signals. For example, piezoresistive structures may be integral to or coupled to a deforming region of a MEMS structure. In still another approach, capacitive or inductive coupling between a deforming region and additional electrical circuitry or movement of a magnetic material relative to a conductor can produce electrical signals responsive to an acoustic signal, in some cases similarly to a microphone transducer. Papers describing heating effects of ultrasound include "Experimental validation of a tractable numerical model for focused ultrasound heating in flow through tissue phantom," Huang et al., J. Acoust. Soc. Am. 116(4), Pt. 1, Oct 2004, "Effect of pulse characteristics on temperature rise due to ultrasound absorption at a bone/soft tissue interface," Myers, J. Acoust. Soc. Am. 117(5), May 2005, and "MRI

guided gas bubble enhanced ultrasound heating in the in vivo rabbit thigh,” Sokka et al., *Phys. Med. Biol.* 48 (2003): 223-241, all of which are incorporated herein by reference. An example of a paper in which increased chemical reactivity of chemical compounds caused by exposure to ultrasound is reported is “The ultrasonically induced reaction of benzoyl chloride with nitro benzene: an unexpected sonochemical effect and a possible mechanism,” Vinatoru et al., *Ultrasonics Sonochemistry* Vo. 9, No. 5, Oct. 2002, pp. 245 – 249, which is also incorporated herein by reference.

In some embodiments, the electromagnetically responsive control element may include a polymer and an electrically active component (including highly polarizable dielectrics) or a magnetically active component (including ferropolymers and the like). In embodiments in which the electromagnetically responsive control element includes one or more electrically or magnetically active components, the electrically or magnetically active component may respond to an electromagnetic control signal in a first manner (e.g., by heating) and the response of the electromagnetically responsive control element may be produced in response to the electrically or magnetically active component (e.g. expansion or change in shape in response to heating of the electrically or magnetically active component). Electromagnetically responsive control elements may, in some embodiments, be composite structures. Heating may be produced in response to acoustic (e.g. ultrasound) signals rather than electromagnetic signals in selected embodiments.

FIG. 5 depicts an example of an electromagnetically responsive control element 100 including a composite structure formed from a polymer 102 and multiple electrically or magnetically active components in the form of multiple particles 104 distributed through polymer 102. In some embodiments, the electrically or magnetically active components may be heatable by the electromagnetic control signal, and heating of the electrically or magnetically active components may cause the polymer to undergo a change in configuration. An example of a magnetically responsive polymer is described, for example, in Neto, et al, “Optical, Magnetic and Dielectric Properties of Non-Liquid Crystalline Elastomers Doped with Magnetic Colloids”; *Brazilian Journal of Physics*; bearing a date of March 2005; pp. 184-189; Volume 35, Number 1, which is incorporated herein by reference. Other exemplary materials and structures are described in Agarwal

et al., "Magnetically-driven temperature-controlled microfluidic actuators"; pp. 1-5; located at:

[http://www.unl.im.dendai.ac.jp/INSS2004/INSS2004\\_papers/OralPresentations/C2.pdf](http://www.unl.im.dendai.ac.jp/INSS2004/INSS2004_papers/OralPresentations/C2.pdf) or U.S. Patent 6,607,553, both of which are incorporated herein by reference. Similar composite structures may be formed with an acoustically responsive material and a polymer.

As mentioned in connection with FIGS. 2 – 4B, the delivery device may contain a primary material (the material that is intended to be delivered to an environment or other downstream location) in a delivery fluid. The primary material may be distributed between a first active form (in which it is usable or active) and a second form in which it is inactive, inaccessible, or otherwise unavailable or unusable). The first active form of the primary material may be carried in solution, in suspension, in emulsion, or in colloidal suspension in the delivery fluid, so that it may be delivered from the delivery device along with the delivery fluid. In some embodiments, the second form may be an inactive form of the primary material, which may be carried in the delivery fluid along with the first active form. The second form may be carried in the delivery fluid in solution, in suspension, in emulsion, or in colloidal dispersion, for example.

In some such embodiments, the second form may be a chemically inactive form. This case is depicted in FIG. 6A, in which the first active form is indicated by reference number 150, and the second (chemically inactive) form is indicated by reference number 152. Delivery reservoir 154, including outlet 156 and electromagnetically responsive control element 158 are also indicated. Both first active form 150 and second form 152 are carried in delivery fluid 153.

In other embodiments, as illustrated in FIG. 6B, the second form 160 may include a chemically active form of the primary material 162 contained in a carrier structure 164, while the first active form 166 is not contained in a carrier structure. The carrier structure may be, for example, a capsule, microcapsule, micelle, or fullerene, or other carrier structure known to those of skill in the relevant art. Delivery reservoir 154 includes outlet 156 and electromagnetically responsive control element 168.

In still other embodiments, as illustrated in FIG. 6C, the second form 176 may be bound or associated with an interaction region 178 in the delivery reservoir 154, while

the first active form 150 is carrier in delivery fluid 153. Interaction of second form 176 with interaction region 178 may be controlled by electromagnetically responsive control element 180.

As shown in FIG. 6D, in some embodiments, the second form 186 may be insoluble in the delivery fluid 153; for example, the second form 186 may be precipitated out of the delivery fluid while first active form 188 is carried in delivery fluid 153. As illustrated in FIG. 6D, the delivery reservoir 154 may include filter 190 located between the delivery reservoir 154 and the outlet 156 and configured for removing the second form 186 from the delivery fluid 153. For example, openings 192 in filter 190 may be large enough to allow first form 188 to pass through, but too small to allow precipitated second form 186 to pass through the filter. In other embodiments, the filter may operate based upon increased affinity for the second form over the first active form, or other filtering principle, as is well known in the field of filtration. The term 'filter' is intended to encompass various types of materials-separating device.

The primary material may have a different immunogenicity, reactivity, stability, or activity when it is in the first active form than when it is in the second form. The primary material may be any of a wide variety of materials, including single materials or mixtures of materials. For example, the primary material may be a pharmaceutical material or a nutraceutical material. The primary material may be a biologically active material. In some embodiments, the primary material may include at least one nutrient, hormone, growth factor, medication, therapeutic compound, enzyme, genetic material, vaccine, vitamin, neurotransmitter, cytokine, cell-signaling material, pro- or anti-apoptotic agent, imaging agent, labeling agent, diagnostic compound, nanomaterial, inhibitor, or blocker. In some embodiments, the primary material may be a component or precursor of a biologically active material; for example, the primary material may include at least one precursor or component of a nutrient, hormone, growth factor, medication, therapeutic compound, enzyme, genetic material, vaccine, vitamin, neurotransmitter, cytokine, cell-signaling material, pro- or anti-apoptotic agent, imaging agent, labeling agent, diagnostic compound, nanomaterial, inhibitor, or blocker. Such precursors, may include, for example, prodrugs (see, e.g., "Liver-Targeted Drug Delivery Using HepDirect1 Prodrugs," Erion et al., Journal of Pharmacology and Experimental

Therapeutics Fast Forward, JPET 312:554-560, 2005 (first pub 8/31/2004) and "LEAPT: Lectin-directed enzyme-activated prodrug therapy", Robinson et al., PNAS October 5, 2004 vol. 101, No. 40, 14527-14532, published online before print September 24, 2004 (<http://www.pnas.org/cgi/content/full/101/40/14527>), both of which are incorporated herein by reference. Beneficial materials may be produced, for example, by conversion of pro-drug to drug, enzymatic reaction of material in bloodstream (CYP450, cholesterol metabolism, e.g., with cholesterol monooxygenase, cholesterol reductase, cholesterol oxidase). Depending on the intended application or use environment for the delivery device, the primary material may include at least one fertilizer, nutrient, remediation agent, antibiotic, microbicide, herbicide, fungicide, transfection agent, nanomaterial, disinfectant, metal salt, a material for adjusting a chemical composition or pH, such as buffer, acid, base, chelating agent, emulsifying agent, or surfactant. In some embodiments, the primary material may include a tissue-specific marker or targeting molecule, which may be, for example, a tissue-specific endothelial protein. A tissue-specific marker or targeting molecule may assist in targeting of the primary material to a specific location or tissue within a body of an organism.

The term "delivery fluid" as used herein, is intended to cover materials having any form that exhibits fluid or fluid-like behavior, including liquids, gases, powders or other solid particles in a liquid or gas carrier. The delivery fluid may be a solution, suspension, or emulsion.

Typically, the effective concentration of the primary material will be the concentration of the first active form of the primary material in the delivery fluid, which may differ from the total concentration of primary material in the delivery fluid, which is the combined concentration of both the first active and second forms of the primary material. The effective rate of delivery of primary material from the delivery device will generally equal the rate at which delivery fluid is pumped (or otherwise moves or is moved) out of the delivery reservoir multiplied by the effective concentration of primary material in the delivery fluid. A delivery device may include a pump for pumping delivery fluid from the delivery reservoir. Alternatively, in some cases the primary material may simply diffuse out of the delivery device. Various types of pumps may be

used, without limitation. Suitable pumps may include, for example, osmotic, mechanical, displacement, centrifugal, and peristaltic pumps.

FIGS. 7A and 7B illustrate an embodiment of a delivery device that includes an osmotic pump. Delivery device 250 includes delivery reservoir 252, which contains delivery fluid 254 and may have an outlet 256. Electromagnetically (or acoustically) responsive control element 258 is located in delivery reservoir 252 to control the distribution of primary material, which in FIG. 7A is shown in the second (inactive, inaccessible or unusable) form 260. Osmotic pump 262 includes osmotic chamber 264 containing osmotic pressure generating material 266. Semi-permeable membrane 268 is permeable to osmotic fluid 270 but not to osmotic pressure generating material 266. Osmotic fluid 270 thus flows into osmotic chamber 264. This causes movable barrier 274 (which may be a rigid movable barrier or a flexible membrane) to move into delivery reservoir 252, thus pumping delivery fluid 254 out of outlet 256. As shown in FIG. 7B, activation of electromagnetically responsive control element 258 may cause primary material to be converted to first active form 272.

Various different osmotic pressure-generating materials may be used in delivery systems as described herein. For example, the osmotic pressure-generating material may include ionic and non-ionic water-attracting or water absorbing materials, non-volatile water-soluble species, salts, sugars, polysaccharides, polymers, hydrogels, osmopolymers, hydrophilic polymers, and absorbent polymers, among others. Water-attracting materials may include non-volatile, water-soluble species such as magnesium sulfate, magnesium chloride, potassium sulfate, sodium chloride, sodium sulfate, lithium sulfate, sodium phosphate, potassium phosphate, d-mannitol, sorbitol, inositol, urea, magnesium succinate, tartaric acid, raffinose, various monosaccharides, oligosaccharides and polysaccharides, such as sucrose, glucose, lactose, fructose, dextran, and mixtures thereof. Water absorbing materials include osmopolymers, for example hydrophilic polymers that swell upon contact with water. Examples of water-absorbing materials include poly(hydroxyl alkyl methacrylates) MW 30,000-5,000,000, polyvinylpyrrolidone MW 10,000-360,000, anionic and cationic hydrogels, polyelectrolyte complexes, poly(vinyl alcohol) having low acetate residual, optionally cross linked with glyoxal, formaldehyde, or glutaraldehyde and having a degree of polymerization of 200 to 30,000,

mixtures of e.g., methylcellulose, cross linked agar and carboxymethylcellulose; or hydroxypropyl methylcellulose and sodium carboxymethylcellulose; polymers of N-vinyl lactams, polyoxyethylene polyoxypropylene gels, polyoxybutylene-polyoxethylene block copolymer gels, carob gum, polyacrylic gels, polyester gels, polyuria gels, polyether gels, polyamide gels, polypeptide gels, polyamino acid gels, polycellulosic gels, carbopol acidic carboxy polymers MW 250,000-4,000,000, cyanamer polyacrylamides, cross-linked indene-maleic anhydride polymers, starch graft copolymers, acrylate polymer polysaccharides. Other water attracting and/or water absorbing materials include absorbent polymers such as poly(acrylic acid) potassium salt, poly(acrylic acid) sodium salt, poly(acrylic acid-co-acrylamide) potassium salt, poly(acrylic acid) sodium salt-graft-poly(ethylene oxide), poly(2-hydroxyethyl methacrylate) and/or poly(2-hydroxypropyl methacrylate) and poly(isobutylene-co-maleic acid). A variety of osmotic pressure-generating materials and/or water-absorbing materials are described in US 2004/0106914 and US 2004/0015154, both of which are incorporated herein by reference in their entirety.

The osmotic pressure-generating ability of the osmotic pressure-generating material may depend on the solubility of the osmotic pressure-generating material in the osmotic fluid, and/or upon the concentration of the osmotic pressure-generating material in the osmotic fluid, and varying either concentration or solubility may modify the osmotic-pressure generating ability of the osmotic pressure-generating material. Concentration of the osmotic pressure-generating material in the osmotic fluid may be modifiable by a change in solubility of the osmotic pressure-generating material in response to an electromagnetic field (or acoustic) control signal or by a change in the osmotic fluid in response to an electromagnetic field (or acoustic) control signal.

FIGS. 8A and 8B depict an embodiment of a delivery device 300 in which the electromagnetically responsive control element 302 includes an electromagnetic field responsive heating element that may respond to the control signal by producing heat. Primary material 304 is contained within delivery reservoir 306 in delivery fluid 307. Electromagnetically responsive control element 302 may be located in the wall of delivery reservoir 306. Electromagnetically responsive control element 302 has an initial temperature  $T_1$ . Following heating of electromagnetically responsive control element

302 in response to an electromagnetic control signal, electromagnetically responsive control element 302 has a subsequent temperature  $T_2$ , as shown in FIG. 8B. The change in temperature of electromagnetically responsive control element 302 may modify the concentration of primary material 304 within delivery reservoir 306. In FIG. 8A, portion 305 of primary material 304 is insoluble, while in FIG. 8B, all of primary material 304 has gone into solution, due to the change in temperature of delivery fluid 307. The electromagnetic field responsive control element 302 may include a ferrous, ferric, or ferromagnetic material, or other material with a significant electromagnetic "loss tangent" or resistivity. In the present example, the solubility of the primary material 304 in the delivery fluid 307 is depicted as increasing with increasing temperature, but in some embodiments, the solubility may decrease with increasing temperature. As in previously described embodiment, delivery device 300 may also include pump 308 and outlet 310. A similar device may be made with an acoustically responsive control element that responds to an acoustic control signal by producing heat.

FIGS. 9A and 9B depict another embodiment of a delivery device 350, in which the at least one electromagnetically responsive control element 352 may include an electromagnetic field responsive cooling element. The electromagnetic field responsive cooling element may be capable of producing a decrease in temperature in the delivery fluid, wherein the primary material 354 has a solubility in the delivery fluid 356 that changes in response to a decrease in temperature of the delivery fluid. The electromagnetic field responsive cooling element 352 may include a thermoelectric element, for example. Methods and/or mechanisms of producing cooling may include, but are not limited to, thermoelectric (Peltier Effect) and liquid-gas-vaporization (Joule-Thomson) devices, or devices which employ "phase-changing" materials or systems involving significant enthalpies of transition. The solubility of the primary material 354 may increase with decreasing temperature, or it may decrease with decreasing temperature, as depicted in FIGS. 9A and 9B. In FIG. 9A, for example, cooling element 352 is not producing cooling, and the temperature is at a higher temperature  $T_1$  and primary material 354 is substantially all in solution in delivery fluid 356. In FIG. 9B, cooling element 352 may be activated to produce cooling, so that the temperature of delivery fluid 356 decreases to temperature  $T_2$ . At temperature  $T_2$  a portion 358 or



primary material goes out of solution, resulting in a lower effective concentration of primary material in delivery fluid 356.

In some embodiments of the delivery device, the at least one electromagnetically (or acoustically) responsive control element may be a shape-changing structure that changes in at least one dimension in response to an electromagnetic (or acoustic) control signal. FIGS. 10A and 10B depict delivery device 400 that includes an electromagnetically responsive control element 402 that is a shape-changing structure located in the wall of delivery reservoir 404. An interaction region 406 including interaction sites 408 may be located on or adjacent to electromagnetically responsive control element 402, so that the dimension of interaction region 406 is modified with the change in dimension of electromagnetically responsive control element 402. Interaction sites 408 may bind primary material 410, thus keeping it out of solution, and maintaining a lower effective concentration in delivery reservoir 404; a change in spacing or exposure of interaction sites 408 may modify the interaction of primary material 410 with interaction sites 408, and thus modifies the effective concentration in delivery reservoir 404. For example, in FIG. 10B, the electromagnetically responsive control element 402 has contracted in at least one dimension to produce a corresponding decrease in size of interaction region 406, and reduction in spacing between interaction sites 408. In the example depicted in FIG. 10B, the reduction in interaction site spacing reduces interactions with primary material 410, causing it to go into solution in delivery fluid 412 in higher concentration.

Interaction sites may be localized to an interaction region, as depicted in FIGS 10A and 10B, or, in alternative embodiments, the interaction sites may be distributed to various locations within the delivery reservoir. The delivery device may include a plurality of interaction sites for the primary material within the delivery reservoir, the likelihood of interaction of the primary material with the interaction sites controllable by the electromagnetic field control signal, wherein interaction of the primary material with the interaction sites causes a change in effective concentration within the delivery reservoir. The interaction sites may be capable of interacting with the primary material by one or more of binding, reacting, interacting, or forming a complex with the primary material. The interaction sites may be responsive to an electromagnetic field control

signal by a change in at least one characteristic, the change in the at least one characteristic modifying the interaction between the interaction sites and the primary material. The at least one characteristic may include, but is not limited to, at least one of a solubility, a reactivity, a distribution within the delivery reservoir, a density, a temperature, a conformation, an orientation, an alignment, or chemical potential, for example.

In some embodiments, the at least one electromagnetically responsive control element may be an electromagnetic field responsive molecule in the delivery fluid, and wherein the electromagnetic field responsive molecule undergoes a change in conformation from a first conformation state to a second conformation state in response to the electromagnetic control signal, and wherein the first conformation state has a first solubility in the delivery fluid and wherein the second conformation state has a second solubility in the delivery fluid. Such an electromagnetic field responsive molecule may form at least a portion of the primary material in the delivery fluid, or alternatively, the electromagnetic field responsive molecule may form at least a portion of a secondary material that influences the solubility of the primary material in the delivery fluid, as illustrated in FIGS. 11A and 11B.

FIG. 11A depicts a delivery device 420 including delivery reservoir 422 and pump 424. Delivery reservoir 422 contains delivery fluid 425, primary material 426, and secondary material 428. Delivery fluid 424 may exit delivery reservoir 422 via outlet 430. In FIG. 11A, secondary material 428 is all in solution, and a portion 432 of primary material has been forced out of solution. In FIG. 11B, in response to a change in the electromagnetic field control signal, a portion 434 of secondary material 428 has gone out of solution, with the effect that a larger amount of primary material 426 goes into solution, thus increasing the concentration of primary material 426 in delivery fluid 242. Secondary material 428 may influence the concentration of primary material 426 by modifying the pH, polarity or other characteristic of delivery fluid 244, or by interacting or reacting with primary material 426 directly to modify its solubility in delivery fluid 424.

FIGS. 10A and 10B depict one method of using a shape changing material to vary the effective concentration of a primary material in a delivery device. Other

embodiments that utilize shape-changing materials are also contemplated. A shape-changing structure may include a polymeric material, a ferropolymer, a hydrogel, a bimetallic structure, or a shape memory material. In some embodiments, the shape-changing structure may be an expanding or contracting structure, wherein the change in at least one dimension includes an expansion or contraction in at least one dimension. Expansion or contraction of the expanding or contracting structure may modify the volume of a delivery reservoir, or expose molecular structures to the delivery fluid that modify the solubility of the primary material in the delivery fluid, as will be discussed in the following example.

A change in surface area may be produced by stretching a portion of the delivery reservoir, as depicted in FIGS. 12A – 12D, or a change in surface area may be produced by unfolding a portion of the delivery reservoir, as depicted in FIGS. 13A and 13B, or by some of change in conformation of at least a portion of the delivery reservoir.

FIGS. 12A – 12D depict the effect of changes in one or two dimensions on an interaction region 450. Such an interaction region may be formed, for example, on an electromagnetically responsive control element that expands in response to a control signal. Interaction region 450 may include a plurality of reaction sites 452, and having initial length of  $x_1$  in a first dimension and  $y_1$  in a second dimension. FIG. 12B depicts interaction region 450 following a change in the first dimension, to a length  $x_2$ . FIG. 12C depicts interaction region 450 following a change in the second dimension, to a length  $y_2$ , and FIG. 12D depicts interaction region 450 following a change in both the first and second dimensions, to a size of  $x_2$  by  $y_2$ . In each case, a change in dimension results in a change in distance between reaction sites 452. The dimension change depicted in FIGS. 12A – 12D may be viewed as a ‘stretching’ or ‘expansion’ of the interaction region. Increasing the surface area of the interaction region may increase the rate of the reaction. Increasing the surface area of the interaction region (e.g., by stretching the surface) may increase the distance between reaction sites on the interaction region. An increased distance between reaction sites may lead to an increase in reaction rate (for example, in cases where smaller spacing between reaction sites leads to steric hindrance that blocks access of reactants to reaction sites).

In addition to increasing surface areas or reaction volumes, expansion of an electromagnetically (or acoustically) responsive control element may also have the effect of exposing additional portions of an interaction region or exposing additional functional group to influence a reaction condition. Increasing the surface area of the interaction region by unfolding or other forms of 'opening' of the interaction region structure of at least a portion of the reaction area may increase the number of reaction sites on the interaction region (e.g. by exposing additional reaction sites that were fully or partially hidden or obstructed when the interaction region was in a folded configuration). For example, the area of an interaction region may be increased by the unfolding of at least a portion of the reaction area to expose additional portions of the reaction area, as depicted in FIGS. 13A and 13B. In FIG. 13A, an interaction region 500, which includes or is made up of an electromagnetically responsive control element, can be expanded by unfolding to the form depicted in FIG. 13B. Interaction region 500 has a pleated structure that includes ridges 502a – 502e and valleys 504a – 504d. Reaction sites 506 may be located in or on ridges 502a-502e and valleys 504a-504d. In the folded form illustrated in FIG. 13A, reaction sites 506 located in valleys 504a-504d are 'hidden' in the sense that reactants may not fit into the narrow valleys to approach those reaction sites, while reaction sites on ridges 502a-502e remain exposed. When interaction region 500 is unfolded to the form shown in FIG. 13B, reaction sites 506 in valleys 504a-506d are exposed, because the open valleys permit access of reactants to the reaction sites in the valleys. Examples of materials that unfold in response to electromagnetic fields include ionic polymer-metal composites (IPMC) as described in Shahinpoor et al., "Artificial Muscle Research Institute: Paper: Ionic Polymer-Metal Composites (IPMC) As Biomimetic Sensors, Actuators and Artificial Muscles-A Review"; University of New Mexico; printed on 10/21/2005; pp. 1-28; located at: <http://www.unm.edu/~amri/paper.html>, which is incorporated herein by reference.

Increasing the surface area of the interaction region may decrease the rate of the interaction in some circumstances and increase the rate of interaction in others. Exposure of additional portions of the interaction region may expose additional functional groups that are not reaction sites, but that may produce some local modification to a surface property of the interaction region that in turn modifies the rate or kinetics of the reaction.

For example, exposed functional groups may produce at least a local change in pH, surface energy, or surface charge. See, for example, U.S. patent publication 2003/0142901 A1, which is incorporated herein by reference. A related modification of the interaction region may include an increase in porosity or decrease in density of an electromagnetically responsive control element. An increase in porosity may have a similar effect to unfolding with respect to modifying the spacing or exposure of reaction sites, functional groups, etc. See, for example U.S. Patents 5,643,246, 5,830,207, and 6,755,621, all of which are incorporated herein by reference. FIGS. 14A and 14B depict an electromagnetically responsive control element 530 that expands in response to an electromagnetic control signal, with a corresponding increase in size of pores 532 in FIG. 14B relative to the size of pores 532 in FIG. 14A.

A change in the spacing of interaction sites may increase or decrease the rate of interaction, or modify another parameter of an interaction, in a manner that depends on the specific reaction and reactants. Heating or cooling of a reaction volume may also modify a chemical reaction by modifying the pressure or the pH or the osmolality or other reaction-pertinent chemical variables within the reaction space. In some embodiments, a delivery device may include at least one interaction region capable of interacting with the primary material by one or more of binding, reacting, interacting, or forming a complex with the primary material. The at least one interaction region may be responsive to the electromagnetic control signal by a change in at least one characteristic, the change in the at least one characteristic modifying the interaction between the at least one interaction region and the primary material. For example, the at least one characteristic may include at least one solubility, reactivity, temperature, conformation, orientation, alignment, binding affinity, chemical potential, surface energy, porosity, osmolality, pH, distribution within the delivery reservoir, or density. In some embodiments, at least a portion of the delivery reservoir containing the at least one interaction region may be responsive to an electromagnetic control signal by a change in the surface area of the portion of the delivery reservoir, the change in surface area modifying the likelihood of interaction of the primary material with the at least one interaction region. For example, the change of surface area may be produced by

stretching or expansion of the portion of the delivery reservoir, or by unfolding of the portion of the delivery reservoir.

The influence of modifying the surface area of an interaction region is described further in connection with FIGS. 15A and 15B and 16A and 16B. FIGS. 15A and 15B illustrate how an increase of the surface area of an interaction region by stretching or expansion may increase the rate of the interaction occurring at the interaction region. Multiple interaction sites 552 are located in interaction region 550. As shown in FIG. 15A, prior to stretch or expansion, interaction sites 552 are close together, and primary material 554, which binds to the interaction sites 552, is sufficiently large that it is not possible for primary material 554 to bind to each interaction site 552. When interaction region 550 has been stretched or expanded to expanded form 550' as depicted in FIG. 15B, so that the interaction sites 552 are further apart, it is possible for primary material 554 to bind to a larger percentage of the interaction sites, thus increasing the rate of interaction.

In some embodiments, an increase in the surface area of the interaction region by stretching or expansion may decrease the interaction rate (for example, in cases where a particular spacing is needed to permit binding or association of primary material with several interaction sites simultaneously). FIGS. 16A and 16B illustrate how an increase in the surface area of an interaction region 570 by stretching or expansion may decrease the rate of the interaction occurring at the interaction region. Again, multiple interaction sites 572 and 574 are located in the interaction region 570, as depicted in FIG. 16A. In the present example binding of a primary material 576 to interaction region 570 requires binding of a primary material 576 to two interaction sites 572 and 574. When interaction region 570 is stretched or expanded to expanded form 570' as depicted in FIG. 16B, the spacing of the two interaction sites 572 and 574 is changed so that primary material 576 does not readily bind to interaction region in the expanded form 570', thus reducing the rate of interaction.

Many materials expand when thermal energy is applied. By combining materials as in polymer gels one can use the differing properties of individual components to affect the whole. Thermally-responsive materials include thermally responsive gels (hydrogels) such as thermosensitive N-alkyl acrylamide polymers, Poly(N-isopropylacrylamide)

(PNIPAAm), biopolymers, crosslinked elastin-based networks, materials that undergo thermally triggered hydrogelation, memory foam, resin composites, thermochromic materials, proteins, memory shape alloys, plastics, and thermoplastics. Materials that contract or fold in response to heating may include thermally-responsive gels (hydrogels) that undergo thermally triggered hydrogelation (e.g. Polaxamers, uncross-linked PNIPAAm derivatives, chitosan/glycerol formulations, elastin-based polymers), thermosetting resins (e.g. phenolic, melamine, urea and polyester resins), dental composites (e.g. monomethylacrylates), and thermoplastics.

Some examples of reactions that may be sped up by change in distance between reaction sites include those involving drugs designed with spacers, such as dual function molecules, biomolecules linked to transition metal complexes as described in Paschke et al, "Biomolecules linked to transition metal complexes—new chances for chemotherapy"; *Current Medicinal Chemistry*; bearing dates of October 2003 and October 18, 2005, printed on 10/24/2005; pp. 2033-44 (pp. 1-2); Volume 10, Number 19; PubMed; located at:

[http://www.ncbi.nlm.nih.gov/entrez/query.fcgi?cmd=Retrieve&db=PubMed&list\\_uids=12871101&dopt=Abstract](http://www.ncbi.nlm.nih.gov/entrez/query.fcgi?cmd=Retrieve&db=PubMed&list_uids=12871101&dopt=Abstract), and Schiff bases as described in Puccetti et al., "Carbonic anhydrase inhibitors", *Bioorg. Med. Chem. Lett.* 2005 June 15; 15(12): 3096-101 (Abstract only), both of which are incorporated herein by reference. Other reactions include reactions responding to conformational (allosteric) changes including regulation by allosteric modulators, and reactions involving substrate or ligand cooperativity in multiple-site proteins, where binding affects the affinity of subsequent binding, e.g., binding of a first O<sub>2</sub> molecule to Heme increases the binding affinity of the next such molecule, or influence of Tau on Taxol, as described in Ross et al., "Tau induces cooperative Taxol binding to microtubules"; *PNAS*; Bearing dates of August 31, 2004 and 2004; pp. 12910-12915; Volume 101, Number 35; The National Academy of Sciences of the USA; located at:

<http://gabriel.physics.ucsb.edu/~deborah/pub/RossPNASv101p12910y04.pdf>, which is incorporated herein by reference. Reactions or interactions that may be slowed down by increased reaction site spacing include reactions responsive to conformational (allosteric) changes, influence of pH, or crosslinking. See for example Boniface et al., "Evidence for

a Conformational Change in a Class II Major Histocompatibility Complex Molecule Occuring in the Same pH Range Where Antigen Binding Is Enhanced"; J. Exp. Med.; Bearing dates of January 1996 and June 26, 2005; pp. 119-126; Volume 183; The Rockefeller University Press; located at: <http://www.jem.org> also incorporated herein by reference or Sridhar et al., "New bivalent PKC ligands linked by a carbon spacer: enhancement in binding affinity"; J Med Chem.; Bearing dates of September 11, 2003 and October 18, 2005, printed on 10/24/2005; pp. 4196-204 (pp. 1-2); Volume 46, Number 19; PubMed (Abstract); Located at: [http://www.ncbi.nlm.nih.gov/entrez/query.fcgi?cmd=Retrieve&db=PubMed&list\\_uids=12954072&dopt=Abstract](http://www.ncbi.nlm.nih.gov/entrez/query.fcgi?cmd=Retrieve&db=PubMed&list_uids=12954072&dopt=Abstract), also incorporated herein by reference.

In some embodiments, the interaction region may include interaction sites that include a secondary material capable of interacting with or influencing the solubility of the primary material. The electromagnetically responsive control element may modify the influence of the secondary material. In some embodiments the secondary material may not be localized to an interaction region, but may be distributed within the delivery reservoir, but responsive to an electromagnetic control signal. The secondary material may interact with or influence primary material in a variety of ways. As a first example, the secondary material may be a receptor or other binding location that binds or sequesters the primary material, either specifically or non-specifically, to take it out of solution. FIGS. 17A and 17B depict an interaction between primary material 600 and secondary material 602 in interaction region 604. In FIG. 17A, prior to activation of electromagnetically responsive control element 606, primary material 600 does not bind to secondary material 602 in interaction region 604. Following activation of electromagnetically responsive control element 606, secondary material 602 undergoes a change to modified form 602' as depicted in FIG. 17B, which allows primary material 600 to bind to it and go out of solution, thus reducing the effective concentration of the primary material in the delivery fluid.

In the example shown in FIG. 18A and 18B, secondary material 630 is not itself a receptor or binding site for the primary material 632, but modifies interaction between the primary material 632 and an interaction site 634 (which may be, for example, a binding or receptor site) in interaction region 636. In FIG. 18A, the secondary material 630 is in



a first configuration which blocks access of primary material 632 to interaction site 634. In FIG. 18B, under the influence of electromagnetically responsive control element 638, secondary material 630 has assumed a second configuration 630' which permits access of primary material 632 to interaction site 634. Secondary material 630 may be a material that modifies the rate or nature of the interaction between primary material 632 and interaction site 634 in response to an electromagnetic control signal by steric effects, by modifying the polarity of at least a portion of an interaction region, such as e.g., hydrophobic or hydrophilic groups; by modifying the pH of at least a portion of the interaction region, with acids or acidifiers (e.g., ammonium chloride), bases or alkalizers (sodium bicarbonate, sodium acetate) or buffering agents (e.g., mono- or di-hydrogen phosphates); or it may be a material that modifies the charge of at least a portion of the interaction region, such as including various enzyme, neuraminidase, transferase, antioxidants, and charge donors.

In the example of FIGS. 19A and 19B, secondary material 640 is a reactant that reacts with primary material 642 to produce reaction product 644. Primary material 642 approaches secondary material 640 in interaction region 646 in FIG. 19A, and reaction product 644 leaves interaction region 646 in FIG. 19B. The reaction between secondary material 640 and primary material 642 is caused, produced, facilitated, or otherwise increased or enhanced by activation of electromagnetically responsive control element 648, (e.g., to produce heating, cooling, a change in surface charge, conformation, etc.) Reaction product 646 may have a different effective concentration in the delivery fluid than primary material 642 due to different solubility, or chemical activity, for example, or because the reaction results in an increase or decrease in the number of chemically active molecules in the reaction chamber. A reaction by-product 610 may remain at interaction region 646, as depicted in FIG. 19B, or secondary material 640 may be completely consumed by the reaction.

The influence of the electromagnetically responsive control element in the examples depicted in FIGS. 17A – 19B may be any of various influences, including but not limited to those described herein; e.g., modifying the temperature of the interaction region or exposing reaction sites or functional groups. As noted elsewhere herein, in related embodiments, an acoustically responsive control element may be used in place of

an electromagnetically responsive control element. The interaction that takes place at the interaction region may change the effective concentration of primary material within the delivery reservoir by producing reaction products in different quantities or with different solubility or chemical activity than the reactants. In some embodiments, the interaction region may include a catalyst that facilitates a chemical reaction but is not modified by the chemical reaction, for example, metals such as platinum, acid-base catalysts, catalytic nucleic acids such as ribozymes or DNAzymes. The interaction region may include an enzyme, such as an oxidoreductase (e.g. glucose oxidase), transferase (including glycosyltransferase, kinase/phosphorylase), hydrolase, lyase, isomerase, ligase, and enzymatic complexes and/or cofactors. Various examples of catalysts are provided in Kozhevnikov, "Catalysts for Fine Chemical Synthesis, Volume 2, Catalysis by Polyoxometalates"; Chipsbooks.com; Bearing dates of 2002 and 1998-2006, printed on 10/21/2005; pp 1-3 (201 pages); Volume 2; Culinary and Hospitality Industry Publications Services; located at: <http://www.chipsbooks.com/catcem2.htm>, which is incorporated herein by reference.

Modifying a reaction condition at the interaction region may also be accomplished by heating or cooling at least a portion of the interaction region, or by modifying the osmolality or pH, surface charge, or surface energy of at least a portion of the interaction region. Similarly, modifying a reaction condition at the interaction region may include modifying a parameter of a reaction space within the delivery device, the reaction space containing the interaction region, e.g. by modifying the volume of the reaction space, heating or cooling at least a portion of the reaction space, or modifying the osmolality, pH, pressure, temperature, chemical composition, or chemical activity of at least a portion of the reaction space.

In some embodiments, expansion or other conformation change of an electromagnetically responsive control element may produce other modifications to a condition in the delivery reservoir. For example, a volume of a delivery reservoir containing the interaction region may be increased by expansion of an electromagnetically responsive control element, as depicted in FIGS. 20A and 20B. Delivery device 650 includes delivery reservoir 652 containing primary material 654 and delivery fluid 656 and having a first volume as shown in FIG. 20A. An

electromagnetically responsive control element 658 that changes dimension in response to an electromagnetic control signal forms an expandable portion of the wall of delivery reservoir 652. Upon expansion of electromagnetically responsive control element to expanded form 658' shown in FIG. 20B, the volume of delivery reservoir 652 is increased, and the concentration of primary material 654 within delivery reservoir 652 is thus decreased. In this and other embodiments, the delivery device may include at least one sensor 660 for detecting at least one parameter from the delivery reservoir. For example, the sensor may detect a quantity or concentration of primary material in the delivery reservoir. In other embodiments, the delivery device may include at least one sensor for detecting a concentration or activity of a chemical within at least a portion of an environment surrounding the delivery device. Examples of sensors are described in, U.S. Patent 6,935,165, and U.S. Patent Publication 2004/0007051, both of which are incorporated herein by reference.

FIG. 21 depicts in schematic form an embodiment of a delivery device 700 including an electromagnetically responsive control element 702 that includes an active portion 704 and a power receiving structure 706. Delivery device also includes delivery reservoir 708 and outlet 710. Power receiving structure 706 may be any structure that has a size, shape, and material that is suitable for receiving and transducing electromagnetic energy of a particular frequency or frequency band. The power receiving structure may include an antenna. The power receiving structure may include a resonant structure. The resonant structure may be a resonant circuit, a molecular bond, or a mechanically resonant structure. In some embodiments, power receiving structure 706 may be highly frequency-selective, while in other embodiments it may react usefully over a wide frequency band, or over multiple frequency bands. Power receiving structure 706 may be formed of various metallic or electrically or magnetically active materials. Active portion 704 may include various materials that respond mechanically, thermally or chemically to electromagnetic energy received and transduced by power receiving structure 706 to influence the effective concentration of primary material in delivery reservoir.

FIG. 22 depicts an embodiment of a delivery device 750 including an RFID 752. Delivery device 750 includes delivery reservoir 754, outlet 756 and electromagnetically

responsive control element 758. RFID 752 may store a unique identification code that allows delivery device 750 to be identified by a remote controller (not shown) that includes RFID detection circuitry. This provides for selective control of particular delivery devices, for example.

Delivery devices as described herein may be configured for use in a variety of environments. A delivery device of the type disclosed herein may include a body structure (e.g., body structure 38 in FIGS. 2 and 3) adapted for positioning in an environment selected from a body of an organism, as depicted in FIG. 1, or a body of water, or a contained fluid volume. The delivery reservoir may be located within the body structure. The body structure adapted for positioning in a contained fluid volume selected from an industrial fluid volume, an agricultural fluid volume, a swimming pool, an aquarium, a drinking water supply, a potable water supply, and an HVAC system cooling water supply.

Various embodiments may be used in connection with selected biomedical applications (e.g., with delivery devices adapted for placement in the body of a human or other animal). It is also contemplated that delivery systems as described herein may be used in a variety of environments, not limited to the bodies of humans or other animals. Delivery devices may be placed in other types of living organisms (e.g., plants). The environments for use of embodiments described herein are merely exemplary, and the delivery systems as disclosed herein are not limited to use in the applications presented in the examples.

FIG. 23 illustrates an exemplary embodiment of a delivery system 770 in which a delivery device 772 is located in a small enclosed fluid volume 774 (e.g., an aquarium). A remote controller 776 is located outside enclosed fluid volume 774.

FIG. 24 illustrates a further exemplary embodiment of a delivery system 780 in which a delivery device 782 is located in a larger enclosed fluid volume 784 (which may be, for example, a water storage tank, an HVAC system cooling water tank, a tank containing an industrial fluid or an agricultural fluid). A remote controller 786 is located outside enclosed fluid volume 784.

FIG. 25 illustrates a further exemplary embodiment of a delivery system 790 in which a delivery device 792 is located in a body of water 794 (a lake or pond is depicted

here, but such delivery systems may also be designed for use in rivers, streams, or oceans). A remote controller 796 is shown located outside of body of water 794, though in some embodiments it may be advantageous to place remote controller 796 at a location within body of water 794.

The body structure of the delivery device may be adapted for a specific environment. The size, shape, and materials of the body structure influence suitability for a particular environment. For example, a device intended for use in a body of a human or other organism would typically have suitable biocompatibility characteristics. For use in any environment, the body structure (and device as a whole) may be designed to withstand environmental conditions such as temperature, chemical exposure, and mechanical stresses. Moreover, the body structure may include features that allow it to be placed or positioned in a desired location in the environment, or targeted to a desired location in the environment. Such features may include size and shape features, tethers or gripping structures to prevent movement of the body structure in the environment (in the case that the device is placed in the desired location) or targeting features (surface chemistry, shape, etc.) that may direct the device toward or cause it to be localized in a desired location. The body structure may include a tissue-specific marker or targeting molecule. For example, the tissue specific marker or targeting molecule may be a tissue specific endothelial protein. Small devices (e.g. as may be used for placement in the body of an organism) may be constructed using methods known to those in skill of the art of microfabrication. In applications where size is not a constraint, a wide variety of fabrication methods may be employed. The body structure of the delivery device may be formed from various materials or combinations of materials, including but not limited to plastics and other polymers, ceramics, metals, and glasses, and by a variety of manufacturing techniques.

In some embodiments, the delivery device may be a MEMS device or other microfabricated device. The delivery device may be constructed from at least one polymer, ceramic, glass, or semiconductor material. In some embodiments, the delivery device may be a battery-free device, powered by power beaming, inductive coupling, or an environmental power source. In still other embodiments, the device may include a battery or other on-board power source. In some embodiments, the delivery device may

include an electromagnetic control signal generator, which may be located substantially in, on or adjacent to the delivery reservoir. In other embodiments, the electromagnetic control signal generator may be located at a location remote from the delivery reservoir.

As discussed herein, a remote controller for a delivery device may include an electromagnetic signal generator capable of producing an electromagnetic signal sufficient to activate an electromagnetically responsive control element of a delivery device located in an environment to change a concentration of a primary material within a delivery reservoir of the delivery device; and an electromagnetic signal transmitter capable of wirelessly transmitting the electromagnetic signal to the electromagnetically responsive control element. Various types and frequencies of electromagnetic control signals may be used in delivery systems as described herein. For example, in some embodiments, the delivery system may include a remote controller configured to generate a static or quasi-static electrical field control signal or static or quasi-static magnetic field control sufficient to activate the electromagnetically responsive control element to control the effective concentration of primary material in a desired manner. In other embodiments, the remote controller may be configured to generate a radio-frequency, microwave, infrared, millimeter wave, optical, or ultraviolet electromagnetic field control signal sufficient to activate the electromagnetically responsive control element to control the effective concentration of primary material in a desired manner.

The electromagnetic control signal may be produced based at least in part upon a predetermined activation pattern. As shown in FIG. 26, a predetermined activation pattern may include a set of stored data 1002a, 1002b, 1002c, 1002d, ... 1002e, having values  $f(t_1)$ ,  $f(t_2)$ ,  $f(t_3)$ ,  $f(t_4)$ , ...  $f(t_n)$ , stored in a memory location 1000. The activation pattern upon which the electromagnetic signal is based is depicted in plot 1004 in FIG. 26. In plot 1004, time  $t_n$  is indicated on axis 1006 and signal amplitude  $f(t_n)$ , which is a function of  $t_n$ , is indicated on axis 1008. The value of the electromagnetic signal over time is represented by trace 1010. The predetermined activation pattern represented by data 1002a, 1002b, 1002c, 1002d, ... 1002e may be based upon calculation, measurements, or any other method that may be used for producing an activation pattern suitable for activating an electromagnetically responsive control element. Memory 1000 may be a memory location in a remote controller. As an example, a simple remote

controller may include a stored activation pattern in memory and include electrical circuitry configured to generate an electromagnetic control signal according to the pattern for a preset duration or at preset intervals, without further input of either feedback information or user data. In a more complex embodiment, a predetermined activation pattern may be generated in response to certain feedback or user input conditions.

In some embodiments, an electromagnetic signal may be produced based upon a model-based calculation. As shown in FIG. 27, an activation pattern  $f(t_n)$  may be a function not only of time ( $t_n$ ) but also of model parameters  $P_1, P_2, \dots, P_k$ , as indicated by equation 1050. Data 1052a, 1052b, .... 1052c having values  $P_1, P_2, \dots, P_k$  may be stored in memory 1054. An electromagnetic control signal may be computed from the stored model parameters and time information. For example, as indicated in plot 1056, time is indicated on axis 1058 and the strength or amplitude of the electromagnetic control signal is indicated on axis 1060, so that trace 1061 represents  $f(t_n)$ . Memory 1054 may be a memory location in a remote controller. The remote controller may generate an electromagnetic control signal based upon the stored function and corresponding parameters. In some embodiments, the electromagnetic control signal may also be a function of one or more feedback signals (from the delivery device or the environment, for example) or of some user input of data or instructions. An acoustic control signal may be produced from a predetermined pattern or calculated from a model in an analogous fashion.

FIG. 28 depicts a remote controller 1100 having a memory 1104 capable of storing pre-determined data values or parameters used in model-based calculation, as described in connection with FIGS. 29 and 30. Remote controller 1100 may also include electrical circuitry 1102, signal generator 1112, and signal transmitter 1114 for transmitting electromagnetic control signal 1116. Memory 1104 may include memory location 1106 for containing a stored activation pattern or model parameters; portions of memory 1104 may also be used for storing operating system, program code, etc. for use by processor 1102. The controller 1100 may also include a beam director 1118, such as an antenna, optical element, mirror, transducer, or other structure that may impact control of electromagnetic signaling. The electrical circuitry may include any or all of analog circuitry, digital circuitry, one or more microprocessors, computing devices, memory

devices, and so forth. Remote controller may include at least one of hardware, firmware, or software configured to control generation of the electromagnetic control field signal. Software may include, for example, instructions for controlling the generation of the electromagnetic control signal and instructions for controlling the transmission of the electromagnetic control signal to the electromagnetically responsive control element.

Remote controller 1100 may be configured to produce an electromagnetic control signal having various characteristics, depending upon the intended application of the system. Design specifics of electrical circuitry, signal generator, and signal transmitter will depend upon the type of electromagnetic control signal. The design of circuitry and related structures for generation and transmission of electromagnetic signals can be implemented using tools and techniques known to those of skill in the electronic arts. See, for example, *Electrodynamics of Continuous Media*, 2nd Edition, by L.D. Landau, E.M. Lifshitz and L.P. Pitaevskii, Elsevier Butterworth-Heinemann, Oxford, especially but not exclusively pp. 1 – 13- and 199 – 222, which is incorporated herein by reference, for discussion of theory underlying the generation and propagation of electrical, magnetic, and electromagnetic signals.

FIG. 66 depicts a system 3050 including remote controller 3052 that transmits an acoustic control signal 3054 to delivery device 3056. Delivery device 3056 is positioned in environment 3058 and includes body structure 3060, remotely activatable control element 3062, and delivery reservoir 3064 containing delivery fluid 3065. The concentration of a primary material in delivery fluid 3065 may be controlled by remotely activatable control element 3062 in response to acoustic control signal 3054 from remote controller 3052. Remote controller 3052 includes electrical circuitry 3066, electrical driving signal generator 3068, and acoustic signal generator 3070. Electrical driving signal generator 3068 produces electrical driving signal 3072, which causes acoustic signal generator 3070 to produce acoustic control signal 3054. Electrical circuitry 3066 may include various types of electrical circuitry and may communicate with electrical driving signal generator 3068 via data line 3074. The manufacture of acoustic signal generators or transducers of various types is well known to those of skill in the art, and the underlying theory as well as the design of devices for producing acoustic signals having various signal properties is well established.



[www.electrotherapy.org/electro/downloads/therapeutic%20ultrasound.pdf](http://www.electrotherapy.org/electro/downloads/therapeutic%20ultrasound.pdf), and "Transducer design for a portable ultrasound enhanced transdermal drug-delivery system", IEEE Trans. On Ultrasonics, Ferroelectrics and Frequency Control, Vo. 49, No. 10, Oct. 2002, which are incorporated herein by reference, are just a few of the many references describing the theory and construction of ultrasound transducers. Acoustic signal generator 3070 may include, for example, one or more piezoelectric crystals that will vibrate in response to an applied electrical field. The acoustic signal generator may include a phased array of piezoelectric crystals in order to generate a focused acoustic signal, as is known by those of skill in the art (see, for example, "A 63 element 1.75 dimensional ultrasound phased array for the treatment of benign prostatic hyperplasia," Saleh et al., BioMed. Engr. OnLine 2005, 4:49, 17 June 2005, <http://www.biomedical-engineering-online.com/content/4/1/39>, which is incorporated herein by reference). Phase conjugation may be used in order to compensate for inhomogeneities in the medium through which the acoustic signal is to be transmitted.

Remote controller 1100 may be configured to produce an electromagnetic control signal having various characteristics, depending upon the intended application of the system. In some embodiments, a specific remote controller may be configured to produce only a specific type of signal (e.g., of a specific frequency or frequency band) while in other embodiments, a specific remote controller may be adjustable to produce a signal having variable frequency content. Signals may include components which contribute a DC bias or offset in some cases, as well as AC frequency components. Generation of radio frequency electromagnetic signals is described, for example, in The ARRL Handbook for Radio Communications 2006, R. Dean Straw, Editor, published by ARRL, Newington, CT, which is incorporated herein by reference. Electromagnetic signal generator 1112 may be capable of producing an electromagnetic control signal sufficient to activate an electromagnetically responsive control element of a delivery device located in an environment to change an effective concentration of a primary material in a delivery fluid within a fluid-containing structure of the delivery device; and an electromagnetic signal transmitter capable of wirelessly transmitting the electromagnetic control signal to the electromagnetically responsive control element of a delivery device in an environment. Signal transmitter 1114 may include a sending device

which may be, for example, an antenna or waveguide suitable for use with an electromagnetic signal. Static and quasistatic electrical fields may be produced, for example, by charged metallic surfaces, while static and quasistatic magnetic fields may be produced, for example, by passing current through one or more wires or coils, or through the use of one or more permanent magnets, as known to those of skill in the art. As used herein, the terms transmit, transmitter, and transmission are not limited to only transmitting in the sense of radiowave transmission and reception of electromagnetic signals, but are also applied to wireless coupling and/or conveyance of magnetic signals from one or more initial locations to one or more remote locations.

The remote controller may be modified as appropriate for its intended use. For example, it may be configured to be wearable on the body of a human (or other organism) in which a delivery device has been deployed, for example on a belt, bracelet or pendant, or taped or otherwise adhered to the body of the human. Alternatively, it may be configured to be placed in the surroundings of the organism, e.g., as a table-top device for use in a home or clinical setting.

In various embodiments, the delivery device may include a remote controller configured to generate a static or quasi-static electrical field control signal, a static or quasi-static magnetic field control signal, a radio-frequency electromagnetic control signal, a microwave electromagnetic control signal, an infrared electromagnetic control signal, a millimeter wave electromagnetic control signal, an optical electromagnetic control signal, or an ultraviolet electromagnetic control signal sufficient to activate the electromagnetically responsive control element to control the effective concentration of the primary material in the delivery fluid.

Various types of electromagnetic field control signals may be used to activate the electromagnetically responsive control element. The electromagnetically responsive control element may be responsive to a static or quasi-static electrical field or a static or quasi-static magnetic field. It may be responsive to various types of non-ionizing electromagnetic radiation, or in some cases, ionizing electromagnetic radiation. Electromagnetic field control signals that may be used in various embodiments include radio-frequency electromagnetic radiation, microwave electromagnetic radiation, infrared

electromagnetic radiation, millimeter wave electromagnetic radiation, optical electromagnetic radiation, or ultraviolet electromagnetic radiation.

The electromagnetic (or alternatively, acoustic) signal generator may include electrical circuitry and/or a microprocessor. In some embodiments, the electromagnetic signal may be produced at least in part according to a pre-determined activation pattern. The remote controller may include a memory capable of storing the pre-determined activation pattern. In some embodiments, the electromagnetic (or acoustic) signal may be produced based on a model-based calculation; the remote controller may include a memory capable of storing model parameters used in the model-based calculation.

In some embodiments, the remote controller may produce an electromagnetic signal having one or both of a defined magnetic field strength or defined electric field strength. In general, the term field strength, as applied to either magnetic or electric fields, may refer to field amplitude, squared-amplitude, or time-averaged squared-amplitude. The electromagnetic signal may have signal characteristics sufficient to produce a change in dimension of the electromagnetically responsive control element, a change in temperature of the electromagnetically responsive control element, a change in conformation of the electromagnetically responsive control element, or a change in orientation or position of the electromagnetically responsive control element. In some embodiments, the electromagnetic signal generator may include an electromagnet or electrically-polarizable element, or at least one permanent magnet or electret. The electromagnetic signal may be produced at least in part according to a pre-programmed pattern. The electromagnetic signal may have signal characteristics sufficient to produce a change in dimension in the electromagnetically responsive control element, the change in dimension causing a change in the concentration of the primary material within the delivery reservoir of the delivery device. It may have signal characteristics sufficient to produce a change in temperature of the electromagnetically responsive control element, the change in temperature causing a change in the concentration of the primary material within the delivery reservoir of the delivery device. In some embodiments, it may have signal characteristics sufficient to produce a change in one or more of shape, volume, surface area or configuration of the electromagnetically responsive control element, the change in dimension in one or more of shape, volume, surface area or configuration of

the electromagnetically responsive control element causing a change in the concentration of the primary material within the delivery reservoir of the delivery device. The electromagnetic signal may have signal characteristics sufficient to produce a change in shape in an electromagnetically responsive control element including a shape memory material, a bimetallic structure, or a polymeric material. The electromagnetic signal may have a defined magnetic field strength or spatial orientation, or a defined electric field strength or spatial orientation.

In some embodiments, the remote controller may be configured to generate and transmit an electromagnetic control signal having at least one of frequency and orientation that are selectively receivable by the at least one magnetically responsive control element. In some embodiments, the remote controller may include at least one of hardware, software, or firmware configured to perform encryption of electromagnetic control signal to produce an encrypted electromagnetic control signal.

FIG. 29 depicts an example of an electromagnetic waveform of a type that may be used to activate an electromagnetically responsive control element. In plot 1150, time is plotted on axis 1152, and electromagnetic field strength is plotted on axis 1154. Trace 1156 has the form of a square wave, switching between zero amplitude and a non-zero amplitude, A.

FIG. 30 depicts another example of an electromagnetic waveform. In plot 1200, time is plotted on axis 1202, and electromagnetic field strength is plotted on axis 1204. Trace 1206 includes bursts 1208 and 1210, during which the field strength varies between A and -A, at a selected frequency, and interval 1212, during which field strength is zero.

FIG. 31 depicts another example of an electromagnetic waveform. In plot 1250, time is plotted on axis 1252, and electromagnetic field strength is plotted on axis 1254. Trace 1256 includes bursts 1258, and 1262, during which the field strength varies between A and -A at a first frequency, and burst 1260, during which the field strength varies between B and -B at a second (lower) frequency. Different frequencies may be selectively received by certain individuals or classes of electromagnetically responsive control elements within a device or system including multiple electromagnetically responsive control elements. An electromagnetic control signal may be characterized by one or more frequencies, phases, amplitudes, or polarizations. An electromagnetic

control signal may have a characteristic temporal profile and direction, and characteristic spatial dependencies. Acoustic control signals may be controlled in a similar manner and may include bursts of acoustic energy at various frequencies, intensities, duration, waveforms, etc. In some embodiments, an acoustic control signal may include bursts or pulses of acoustic energy, in which case the signal may also be characterized by a burst/pulse duration and inter-pulse/inter-burst interval. Frequency may be selected to provide desired tissue penetration and absorption properties. Lower frequency acoustic signals will generally penetrate deeper into the body, while higher frequency acoustic signals are more readily absorbed to produce heating. Audible acoustic signals may have frequencies between about 16Hz and 20kHz, while ultrasound signals have frequencies greater than about 20kHz. Frequencies suitable for producing heating may be between about 0.5 and about 3 MHz, for example. Such frequencies are examples and not intended to be limiting; other frequencies may be used, and selection of appropriate frequencies may be determined for specific applications by those of skill in the art. Moreover, the acoustic signal may include more than one frequency and/or a series of frequencies (e.g., a “chirped” signal).

The magnetic or electric field control signal produced by the remote controller may have one or both of a defined magnetic field strength or a defined electric field strength. At low frequencies the electrical and magnetic components of an electromagnetic field are separable when the field enters a medium. Therefore, in static and quasi-static field application, the electromagnetic field control signal may be considered as an electrical field or a magnetic field. A quasi-static field is one that varies slowly, i.e., with a wavelength that is long with respect to the physical scale of interest or a frequency that is low compared to the characteristic response frequency of the object or medium; therefore, the frequency beyond which a field will no longer be considered ‘quasi-static’ is dependent upon the dimensions or electrodynamic properties of the medium or structure(s) influenced by the field.

As depicted in various embodiments, e.g., as shown in FIGS. 6A – 10B, the delivery reservoir may include an outlet through which the delivery fluid moves into an environment, for example by pumping or diffusion. In other embodiments, as depicted in FIG. 32, a delivery system 1300 may include a downstream fluid handling structure 1302

in fluid communication with the delivery reservoir 1304 and configured to receive fluid 1306 ejected from the delivery reservoir 1304 in response to the change in at least one of pressure or volume in the delivery reservoir 1304. The downstream fluid handling structure 1302 may include a chamber, as depicted in FIG. 32. Delivery device 1300 may also include a pump (e.g., and osmotic pump 1308) and an electromagnetically (or acoustically) responsive control element 1310.

In other embodiments, e.g. delivery device 1350 shown in FIG. 33, a downstream fluid handling structure 1352 may include one or more channels 1354, chambers 1356, splitters 1358, mixers 1360, or other fluid handling structures, or various combinations thereof. Delivery device 1350 also includes pump 1362, delivery reservoir 1364, and outlet 1366. Examples of fluid handling structures suitable for use in selected embodiments are described in U.S. Patents 6,146,103 and 6,802,489, and in Krauß et al., "Fluid pumped by magnetic stress"; Bearing a date of July 1, 2004; pp. 1-3; located at: [http://arxiv.org/PS\\_cache/physics/pdf/0405/0405025.pdf](http://arxiv.org/PS_cache/physics/pdf/0405/0405025.pdf), all of which are incorporated herein by reference. Fluid handling structures may include, but are not limited to, channels, chambers, valves, mixers, splitters, accumulators, pulse-flow generators, and surge-suppressors, among others.

Previously described embodiments of delivery devices have include a delivery reservoir that is substantially chamber-like in shape. However, delivery fluid may be contained in fluid-containing structures having various shapes and configurations. FIG. 34 illustrates a delivery device 1400 that includes a fluid-containing structure 1402 that takes the form of a channel. The fluid-containing structure 1402 may have at least one outlet 1404 through which a fluid may exit the fluid-containing structure 1402 to a downstream location; a delivery fluid 1406 contained within the fluid-containing structure 1402; a primary material contained within the fluid-containing structure and having a controllable effective concentration in the delivery fluid; at least one electromagnetically (or acoustically) responsive control element adapted 1408 for controlling the distribution of the primary material between a first active form 1410 carried in the delivery fluid and a second form 1412 in response to an incident electromagnetic control signal, the effective concentration being the concentration of the

first active form in the delivery fluid; and a pump 1414 configured for pumping delivery fluid from the fluid-containing structure to the downstream location.

As noted previously, delivery devices as described herein may include various types of pumps. A pump suitable for use in a delivery device may include a mechanical pump, a displacement pump, a centrifugal pump, or a peristaltic pump. The choice of pump and method of construction thereof may depend upon the intended use of the delivery device, the delivery site, the dimensions of the delivery device, among other factors, as will be apparent to those of skill in the art. In some embodiments, the downstream location may be an environment. In some embodiments, the downstream location may be a downstream fluid handling structure, and in some embodiments, the downstream location may include a downstream environmental interface. An environmental interface may function to facilitate the distribution of a primary material into an environment.

FIG. 35 depicts an example of a delivery device 1450 including an environmental interface 1452. In the example of FIG. 35, the environmental interface 1452 provides for the delivery of primary material 1454 into blood flowing through capillaries 1456. Delivery device 1450 includes pump 1458 and a fluid-containing structure 1460 (here depicted as a delivery reservoir) containing delivery fluid 1462 carrying primary material 1454. Environmental interface 1452 includes substrate material 1464 capable of supporting growth of capillaries 1456. Distribution channel 1466 distributes delivery fluid 1462 to substrate material 1464, where primary material 1454 may diffuse into capillaries 1456 and be picked up by the blood.

In other embodiments, a delivery device as depicted generally in FIG. 34 may include any of various types of downstream fluid handling structures. The downstream fluid handling structure may include at least one channel, of the type depicted in FIG. 33, or at least one chamber, for example as depicted in FIGS. 32 or 33. The downstream fluid handling structure may include at least one mixer (e.g. 1360 in FIG. 33 or at least one splitter (e.g. 1354 in FIG. 33). In some embodiments, the downstream fluid handling structure may include a filter, for example, of the type depicted in FIG. 6D; it is contemplated that one or more filter may be placed at various downstream locations, not

only at the outlet of the fluid-containing structure but potentially further downstream instead, or in addition.

FIG. 36 depicts a method of delivery a fluid through the use of a delivery device as described herein. The basic method includes receiving an electromagnetic control signal from a remote controller at step 1502; and responsive to the electromagnetic control signal, modifying an effective concentration of a primary material in a delivery fluid within a delivery reservoir at step 1504.

As shown in FIG. 37, an expanded version of the method may include receiving an electromagnetic control signal from a remote controller at step 1552; and responsive to the electromagnetic control signal, modifying an effective concentration of a primary material in a delivery fluid within a delivery reservoir at step 1554; followed by an additional step of 1556 of ejecting the delivery fluid from the delivery reservoir.

FIG. 38 provides further detail on a method including receiving an electromagnetic control signal from a remote controller at step 1602; and responsive to the electromagnetic control signal, modifying an effective concentration of a primary material in a delivery fluid within a delivery reservoir at step 1604 (comparable to steps 1502 and 1504 as shown in FIG. 36). The method may include modifying the effective concentration of the primary material in the delivery fluid by modifying at least one characteristic of the delivery fluid, the effective concentration of the primary material in the delivery fluid dependent upon the at least one characteristic of the delivery fluid, as shown in alternative step 1608 in FIG. 38. In this and other figures boxes containing optional or alternative steps are surrounded by a dashed line. The at least one characteristic may include, for example, temperature, pH, polarity, osmolality or chemical activity. As another alternative, as indicated at alternative step 1612 in FIG. 38, the method may include modifying the effective concentration of the primary material in the delivery fluid by modifying at least one characteristic of the primary material, the solubility of the primary material in the delivery fluid being dependent upon the at least one characteristic of the primary material. The at least one characteristic includes temperature, charge, polarity, osmolality, conformation, orientation, or chemical activity. As a further alternative, indicated at 1610 in FIG. 38, the method may include modifying the effective concentration of the primary material in the delivery fluid by modifying at



least one of a number of interaction sites in the delivery reservoir or an affinity of at least one interaction site in the delivery reservoir for the primary material. The affinity of the at least one interaction site for the primary material may be modified by modifying the temperature, charge, polarity, osmolality, surface energy, orientation, conformation, chemical activity or chemical composition of the at least one interaction site or in the vicinity of the at least one interaction site. The number of interaction sites may be modified by stretching, compressing, unfolding, or changing a conformation of at least a portion of the delivery reservoir, for example.

A method as shown in FIGS. 36 - 48 may include receiving the electromagnetic control signal with an electromagnetically responsive material, which may include, for example, a permanently magnetizable material, a ferromagnetic material, a ferrimagnetic material, a ferrous material, a ferric material, a dielectric or ferroelectric or piezoelectric material, a diamagnetic material, a paramagnetic material, and an antiferromagnetic material. The method may include a step of ejecting the delivery fluid into an environment, which may include, for example, the body of an organism, a body of water, or a contained fluid volume. Alternative, the method may include ejecting the delivery fluid into a downstream environmental interface or a downstream fluid-handling structure, which may include a channel, a chamber, a mixer, a separator, or combinations thereof.

FIG. 39 depicts a delivery system 1650 that includes a delivery device 1652 and a remote controller 1654. Delivery device 1652 includes fluid-containing structure 1656 having at least one outlet 1658 through which fluid may exit the fluid-containing structure 1656; a delivery fluid 1660 contained within the fluid-containing structure 1656; a primary material 1662 contained within the fluid-containing structure 1656 and having a controllable effective concentration in the delivery fluid 1660; and at least one electromagnetically responsive control element 1664 adapted for modifying the distribution of the primary material 1662 between a first active form carried in the delivery fluid and a second form in response to an incident electromagnetic control signal to modify the effective concentration of the primary material in the delivery fluid, the effective concentration being the concentration of the first active form in the delivery fluid. Remote controller 1654 includes an electromagnetic signal generator 1668 capable

of producing an electromagnetic control signal sufficient to activate the electromagnetically responsive control element 1664 of the delivery device 1652 located in an environment 1653 to change the effective concentration of the primary material in the delivery fluid 1660 within the fluid-containing structure 1656 of the delivery device 1652; and an electromagnetic signal transmitter 1670 capable of wirelessly transmitting the electromagnetic control signal 1672 to the electromagnetically responsive control element of the delivery device in the environment. The remote controller may include electrical circuitry 1674, which may include at least one of hardware, firmware, or software configured to control generation of the electromagnetic control signal. The remote controller 1654 may include an electromagnetic signal generator 1668 configured to generate a static or quasi-static electrical field control signal, a static or quasi-static magnetic field control signal, a radio-frequency electromagnetic control signal sufficient, a microwave electromagnetic control, an infrared electromagnetic control signal, a millimeter wave electromagnetic control signal, an optical electromagnetic control signal, or an ultraviolet electromagnetic control signal sufficient to activate the electromagnetically responsive control element to control the effective concentration of the primary material within the fluid-containing structure. The remote controller may include an electromagnetic signal generator configured to generate a rotating electromagnetic control signal.

Delivery device 1652 may include a body structure 1676 adapted for positioning in an environment 1653 selected from a body of an organism, a body of water, or a contained fluid volume. For example, body structure 1676 may be adapted for positioning in a contained fluid volume selected from an industrial fluid volume, an agricultural fluid volume, a swimming pool, an aquarium, a drinking water supply, a potable water supply, and an HVAC system cooling water supply. Delivery device 1652 may include a pump 1678, as described generally elsewhere herein.

The electromagnetically responsive control element 1664 may include a magnetically or electrically active material including at least one permanently magnetizable material, ferromagnetic material, ferrimagnetic material, ferrous material, ferric material, dielectric material, ferroelectric material, piezoelectric material, diamagnetic material, paramagnetic material, metallic material, or antiferromagnetic

material. In some embodiments, the electromagnetically responsive control element may include a polymer, ceramic, dielectric, metal, shape memory material, or a combination of a polymer and a magnetically or electrically active component.

FIG. 40 depicts a delivery system 1700, including remote controller 1702, and delivery device 1704. Delivery device 1704 includes fluid-containing structure 1656, having outlet 1658 and containing delivery fluid 1660 and primary material 1662. Delivery device 1704 also includes electromagnetically responsive control element 1664 for controlling the effective concentration of primary material 1662 in delivery fluid 1660. Delivery device 1704 may include body structure 1676 adapted for placement in environment 1653, and pump 1678. Delivery device 1704 may also include RFID 1700. Remote controller 1702 includes RF interrogation signal generator 1706 for generating an RF interrogation signal 1708, which may be tuned to the RFID. Remote controller 1702 includes electromagnetic signal generator 1668, electromagnetic signal transmitter 1670, electrical circuitry 1674, which function generally as described in connection with FIG. 39.

FIG. 41 illustrates a delivery system including a remote controller 1850 that produces electromagnetic control signal 1852 that is transmitted to delivery device 1854 in environment 1856. Electromagnetic control signal 1852 is received by electromagnetically responsive control element 1858 in delivery device 1854. Remote controller 1850 may include a signal input 1851 adapted for receiving a feedback signal 1860 sensed from an environment 1856 by a sensor 1862, wherein the electromagnetic signal 1852 is produced based at least in part upon the feedback signal 1860 sensed from the environment. For example, the feedback signal 1852 may correspond to the osmolality or the pH of the environment, the concentration or chemical activity of a chemical in the environment, a temperature or pressure of the environment, or some other sensed signal. Remote controller 1850 may include electrical circuitry 1864, signal generator 1866, signal transmitter 1868, and memory 1870. Feedback from sensor 1862 may be sent over a wire connection or, in some embodiments, transmitted wirelessly. Remote controller may include a signal input adapted for receiving a feedback signal corresponding to one or more parameters sensed from the environment, wherein the electromagnetic control signal is produced based at least in part upon the feedback signal

sensed from the environment. For example, the feedback signal corresponds to the concentration or chemical activity of a chemical in the environment.

FIG. 42 illustrates another embodiment of a delivery system, including remote controller 1900, which transmits electromagnetic control signal 1902 to delivery device 1904 in environment 1906. Remote controller 1900 may include a signal input 1908 adapted for receiving a feedback signal 1912 from sensor 1910 in delivery device 1904. Electromagnetic control signal 1902 may be produced based at least in part upon the feedback signal 1912 corresponding to one or more parameters sensed from the delivery device. In some embodiments, the feedback signal may correspond to the concentration or chemical activity of a chemical within or around the delivery device. In some embodiments, the feedback signal from the delivery device may correspond to the osmolality or the pH within or around the delivery device, the concentration or chemical activity of a chemical within or around the delivery device, a temperature or pressure within or around the delivery device, the pumping rate of the delivery device, or some other parameter sensed from the delivery device. In others, the feedback signal may correspond to the pumping rate of the delivery device, produced, for example, by pump 1922. In some embodiments, sensor 1910 may be configured for detecting at least one parameter from at least a portion of an environment surrounding the delivery device. The electromagnetic signal 1902 may be determined based at least in part upon the feedback signal 1912. Examples of sensors are described in U.S. Patent 6,935,165, and U.S. Patent Publication 2004/0007051, both of which are incorporated herein by reference. Delivery device 1904 includes electromagnetically responsive control element 1920. Feedback signal 1912 may be transmitted wirelessly back to remote controller 1900. Remote controller 1900 may include processor 1914, signal generator 1916, signal transmitter 1918, and memory 1924.

As illustrated in FIG. 43, in some embodiments, the remote controller may be configured to receive user input of control parameters. Remote controller 1950 includes input 1960 for receiving input of information or instructions from a user such as, for example, commands, variables, durations, amplitudes, frequencies, waveforms, data storage or retrieval instructions, patient data, etc. As in the other embodiments, remote controller 1950 transmits electromagnetic control signal 1952 to delivery device 1954 in

environment 1956, where it activates electromagnetically responsive control element 1958. Input 1960 may include one or more input devices such as a keyboard, keypad, microphone, mouse, etc. for direct input of information from a user, or input 1960 may be any of various types of analog or digital data inputs or ports, including data read devices such as disk drives, memory device readers, and so forth in order to receive information or data in digital or electronic form. Data or instructions entered via input 1960 may be used by electrical circuitry 1962 to modify the operation of remote controller 1950 to modulate generation of an electromagnetic control signal 1952 by signal generator 1964 and transmission of the control signal 1952 by transmitter 1966. Any of the systems depicted in FIGS. 39 – 43 may be implemented using acoustic control signals, in addition to or instead of electromagnetic control and/or feedback signals, and such embodiments are considered to fall within the scope of the present disclosure.

FIG. 44 illustrates a delivery system that includes a plurality of delivery devices, where two or more of the plurality of delivery devices are controlled by the remote controller. A delivery device may include a plurality of selectively activatable control elements, each associated with a particular fluid handling element, which may thus be controlled to perform multiple fluid-handling or reaction steps in a particular sequence. It is also contemplated that a delivery system may include a plurality of delivery devices which may be of the same or different types. As shown in FIG. 44, a delivery system 2000 may include a plurality of identical delivery devices 2002 distributed throughout an environment 2004 in order to perform a particular chemical reaction or process at a plurality of locations within the environment, and controlled by a remote controller 2006. Alternatively, a delivery system may include a plurality of different delivery devices at different locations within an environment, each performing or controlling a reaction suited for the particular location. The invention as described herein is not limited to devices or systems including any specific number or configuration of electromagnetically or acoustically responsive control elements within a delivery device, or specific number or configuration of delivery devices or remote controllers within a delivery system. Depending upon the particular application of a system, electromagnetically responsive control elements and/or delivery devices may be controlled in a particular pattern to producing a desired distribution of a delivery material in an environment. Control of

such systems may be performed with the use of suitable hardware, firmware, and/or software, through one or a plurality of remote controllers.

The remote controller used in the system depicted in FIG. 44 may include an electromagnetic signal generator capable of producing an electromagnetic control signal sufficient to activate electromagnetically responsive control elements in a plurality of delivery devices located in an environment to change an effective concentration of primary material in a delivery fluid within a fluid-containing structure of each of the devices. In a related embodiment, the remote controller may include a plurality of signal inputs adapted for receiving signals from the plurality of delivery devices, the plurality of signal inputs coupled to a microprocessor configured to generate the electromagnetic control signal based upon the plurality of signals.

Selective activation or control of electromagnetically responsive control elements may be achieved by configuring electromagnetically responsive control elements to be activated by electromagnetic control signals having particular signal characteristics, which may include, for example, particular frequency, phase, amplitude, temporal profile, polarization, and/or directional characteristics, and spatial variations thereof. For example, different control elements may be responsive to different frequency components of a control signal, thereby allowing selective activation of the different control elements. The remote controller may be configured to produce a rotating electromagnetic signal, the rotating electromagnetic signal capable of activating the two or more delivery devices independently as a function of the orientation of the rotating electromagnetic signal.

As shown in FIG. 45, in still other embodiments, a delivery system 2050 may include a delivery device 2052 that includes a plurality of electromagnetically responsive control elements 2054, responsive to one or more remote controller 2056. A plurality of control elements 2054 may be used, for example, to control a plurality of locations or functions in delivery device 2052.

As shown in FIG. 46, in some embodiments, a delivery system 2101 or may include a plurality of delivery devices 2102, 2104, 2106, and 2108, and a plurality of remote controllers 2100a, 2100b, 2100c. As shown in FIG. 46, each delivery device may be controlled by one or more control signals produced in a distributed fashion by two or more of the plurality of remote controllers 2100 a – 2100c.

As shown in FIG. 47, in some embodiments a delivery system 2151 may include a plurality of delivery devices 2152a, 2152b, and 2152c and a plurality of remote controllers 2150a, 2150b, and 2150c, each delivery device may be controlled by a separate remote controller, for example delivery device 2152a controlled by remote controller 2150a, delivery device 2152b controlled by remote controller 2150b, and delivery device 2152c controlled by remote controller 2150c.

In still other embodiments, as shown in FIG. 48, a remote controller 2200 may include a plurality of transmission channels 2204a, 2204b, 2204c, and 2204d, for example (more or fewer channels may be used, without limitation). Remote controller 2200 may also include channel allocation hardware or software 2206 configured to allocate usage of the plurality of transmission channels 2204a – 2204d for the transmission of the electromagnetic control signal from signal transmitter 2208 to selected delivery devices of the plurality of delivery devices 2202a – 2202f.

In another embodiment of a delivery system 2250 shown in FIG. 49, the remote controller 2252 may include encryption hardware or software 2262 configured to encrypt one or more control signal components, wherein the encrypted one or more control signal components are receivable by a delivery device 2254 including a corresponding decryption key 2264. Remote controller 2252 may include signal generator 2256, signal transmitter 2258, and electrical circuitry 2260, as described generally elsewhere.

In another embodiment of a delivery system 2300 shown in FIG. 50, the remote controller 2302 may include authentication hardware or software 2312 configured to perform an authentication procedure with a delivery device 2304, wherein the remote controller 2302 is configured to produce activation of the electromagnetically responsive control element 2316 of an authenticated delivery device but not the electromagnetically responsive control element of a non-authenticated delivery device. Again, remote controller 2302 may include signal generator 2306, signal transmitter 2308, and electrical circuitry 2310, as described generally elsewhere, and authentication portion 2314, which may include hardware, firmware or software configured for performing an authentication protocol with remote controller 2302.

Referring back to FIG. 40, remote controller 1702 may include an interrogation signal generator 1706 for generating a transmittable RFID interrogation signal. The

remote controller may also include an interrogation signal transmitter for transmitting the transmittable RFID interrogation signal; an interrogation signal receiver for receiving a returned RFID interrogation signal from an RFID in a delivery device; and RFID detection circuitry configured to detect the presence of a selected RFID from a returned RFID interrogation signal. Upon detection of the presence of the selected RFID, to remote controller 1702 may generate and transmit a control signal configured for receipt by the delivery device including the selected RFID.

In various embodiments of the remote controller described herein, the generated electromagnetic control signal may have a defined magnetic field strength, or alternatively, or in addition, a defined electric field strength. Depending upon the intended application, the electromagnetic control signal may have signal characteristics sufficient to produce a change in dimension of the electromagnetically responsive control element, a change in temperature of at least a portion of the electromagnetically responsive control element, a change in conformation or configuration of the electromagnetically responsive control element, or a change in orientation or position of the electromagnetically responsive control element. The remote controller may include an electromagnetic signal generator that includes an electromagnet or electrically-polarizable element, or at least one permanent magnet or electret. Systems as depicted in FIGS. 44 – 50 may utilize acoustic rather than electromagnetic control signals.

FIG. 51 depicts the steps of a method of delivering a material, comprising delivering an electromagnetic distribution control signal to an environment containing a delivery device, the delivery device including an electromagnetically responsive control element and a fluid-containing structure containing a delivery fluid and a quantity of a primary material distributed between a first active form carried in the delivery fluid and a second form according to a first distribution, the primary material distributed according to the first distribution having a first effective concentration in the delivery fluid equal to the concentration of the first active form in the delivery fluid, the electromagnetic distribution control signal having signal characteristics receivable by the electromagnetically responsive control element and sufficient to produce a change in the distribution of the primary material between the first active form and the second form to a second distribution, the primary material distributed according to the second distribution



having a second active concentration in the delivery fluid, at step 2352; and delivering an electromagnetic delivery control signal to the environment containing the delivery device, the electromagnetic delivery control signal sufficient to produce pumping of the delivery fluid out of the fluid-containing structure, the delivery fluid containing the primary material at the second effective concentration in the delivery fluid at step 2354.

FIG. 52 shows further variations of the method of FIG. 51. The method of FIG. 52 include steps of delivering and electromagnetic distribution control signal at step 2402 and delivering an electromagnetic delivery control signal at step 2404 (e.g., as in FIG. 51), followed by a step of generating an electromagnetic control signal according to a number of optional steps. For example, the method may include generating and transmitting the electromagnetic control signal to the delivery device with a remote controller, as shown at 2406a. Alternatively, the method may include generating a first electromagnetic control signal sufficient to produce a change in effective concentration of a primary material in a delivery fluid in a delivery reservoir of a delivery device; and generating a second electromagnetic control signal sufficient to cause delivery fluid containing primary material in solution to be released from the delivery reservoir into the environment, as shown at 2406b. Or, the method may include generating a first electromagnetic control signal having frequency and magnitude sufficient to produce heating of a heating element in or near the delivery reservoir, as shown at 2406c. Alternatively, the method may include generating a first electromagnetic control signal having frequency and magnitude sufficient to produce cooling of a cooling element in or near the delivery reservoir, as shown at 2406d, generating a first electromagnetic field having frequency and magnitude sufficient to produce a conformation change of a molecular structure, as shown at 2406e, or generating a first electromagnetic field having frequency and magnitude sufficient to produce a volume change of a material a molecular structure, as shown at 2406f.

FIG. 53 shows a method of delivering a material including pumping a delivery fluid containing a primary material from a delivery reservoir of a delivery device to a downstream location at a first pumping rate at step 2452; and controlling the effective concentration of the primary material in the delivery fluid in response to a remotely transmitted electromagnetic control signal at step 2454. In some embodiments, the first

pumping rate may be a constant pumping rate. In some embodiment, the method may include varying the rate of delivery of the primary material to the downstream location by varying the effective concentration of the primary material in the delivery fluid in response to the remotely transmitted electromagnetic control signal. In other embodiments, the first pumping rate may be a time-varying pumping rate. In such embodiments, the method may include controlling the rate of delivery of the primary material to the downstream location by controlling both the effective concentration of the primary material in the delivery fluid and the pumping rate. The first pumping rate is modifiable in response to a remotely transmitted electromagnetic control signal, for example. The method may include controlling the effective concentration of the primary material in the delivery fluid through activation of an electromagnetically responsive control element in the delivery device by the remotely transmitted electromagnetic control signal, for example by heating of the electromagnetically responsive control element, cooling of the electromagnetically responsive control element. In some variants of the method, activation of the electromagnetically responsive control element may include a change in at least one dimension of the electromagnetically responsive control element, a change in orientation of the electromagnetically responsive control element, or a change in conformation of the electromagnetically responsive control element.

FIG. 54 shows a method of delivering a material, including receiving a first electromagnetic control signal with a first electromagnetically responsive control element in a delivery device, the delivery device including a fluid-containing structure containing a delivery fluid and a primary material distributed between a first active form carried in the delivery fluid and a second form, the primary material having a first effective concentration in the delivery fluid equal to the concentration of the first active form in the delivery fluid at step 2502; responsive to receipt of the first electromagnetic control signal by the first electromagnetically responsive control element, modifying the distribution of the primary material between the first active form and the second form, the primary material having a second effective concentration in the delivery fluid following the modification of the distribution of the primary material between the first active form and the second form at step 2504; and pumping the delivery fluid containing the primary material at the second effective concentration from the fluid-containing structure of the

delivery device to a downstream location at step 2506. In the method of FIG. 54, the primary material has a different stability in the first active form than in the second form, a different immunogenicity in the first active form than in the second form, a different reactivity in the first active form than in the second form, or a different activity in the first active form than in the second form.

In a variant of the method of FIG. 54, shown in FIG. 55 (with steps 2552 – 2556 the same as steps 2502 – 2506), the method may include the additional step of filtering the second form of the primary material from the delivery fluid prior to pumping the delivery fluid containing the primary material at the second effective concentration from the fluid-containing structure of the delivery device to a downstream location 2558.

In the method of FIG. 54, in some embodiments the first effective concentration may be lower than the second effective concentration, and some embodiments first effective concentration may be higher than the second effective concentration. The method may include modifying the rate of pumping of the delivery fluid to the downstream location responsive to receipt of a second electromagnetic control signal by a second electromagnetically responsive control element. In some embodiments, the first electromagnetic control signal and the second electromagnetic control signal may be the same electromagnetic control signal. In other embodiments, the first electromagnetic control signal may be different than the second electromagnetic control signal. In some embodiments, the first electromagnetically responsive control element and the second electromagnetically responsive control element may be the same electromagnetically responsive control element, while in other embodiments, the first electromagnetically responsive control element may be a different control element than the second electromagnetically responsive control element. “Different” control elements may be control elements of different types, or distinct control elements that are of the same type.

FIG. 56 depicts further variants on the method of FIG. 54. Steps 2602 through 2606 are the same as steps 2502 – 2506 in FIG. 54. Steps 2608a – 2608f alternative steps for modifying the distribution of primary material between the first active form and the second form. Step 2608a includes modifying the distribution of primary material in response to receipt of the first electromagnetic control signal by modifying a pressure within the fluid containing structure, step 2608b includes modifying the distribution of

primary material in response to receipt of the first electromagnetic control signal by modifying a temperature within the fluid containing structure, step 2608c includes modifying the distribution of primary material in response to receipt of the first electromagnetic control signal by modifying a volume of the fluid containing structure, step 2608d includes modifying the distribution of primary material in response to receipt of the first electromagnetic control signal by producing vibration within the fluid containing structure, step 2608e includes modifying the distribution of primary material in response to receipt of the first electromagnetic control signal by producing fluid mixing within the fluid containing structure, and step 2608f includes modifying the distribution of primary material in response to receipt of the first electromagnetic control signal by modifying a number of available interaction sites within the fluid containing structure, the available interaction sites capable of interacting with the primary material to produce the second form of the primary material.

FIG. 57 illustrates a method of delivering a material, including, at step 2652, introducing a delivery device into an environment, the delivery device including an electromagnetically responsive control element, a pump, a fluid-containing structure containing a delivery fluid and a quantity of a primary material, the primary material being distributed between a first active form carried in the delivery fluid and a second form according to a first distribution in which the primary material has a first effective concentration in the delivery fluid equal to the concentration of the first active form in the delivery fluid, and wherein the electromagnetically responsive control element is configured to modify the distribution of primary material between the first active form and the second form, and a pump, the pump being activatable for pumping delivery fluid from the fluid-containing structure to a downstream location. At step 2654, the method includes a step of delivering an electromagnetic distribution control signal to the environment with signal characteristics selectively receivable by the electromagnetically responsive control element and sufficient to produce a change in the distribution of the primary material between the first active form and the second form to a second distribution, the primary material distributed according to the second distribution having a second effective concentration in the delivery fluid. The pump may be activated to pump delivery fluid containing the primary material at the second effective concentration

out of the fluid containing structure. In one variant, the pump may be activated prior to introducing the delivery device into the environment. In another variant, the pump may be activated upon introduction of the delivery device into the environment. In still another variant, the pump may be activated subsequent to introducing the delivery device into the environment. The method as depicted in FIG. 57 may also include delivering an electromagnetic delivery control signal having signal characteristics selectively receivable by a second electromagnetically responsive control element in the delivery device to produce the pumping of the delivery fluid containing the primary material at the second effective concentration out of the fluid-containing structure. The primary material may have a different immunogenicity, reactivity, or stability when it is in the first active form than when it is in the second form.

FIG. 58 illustrates a method of controlling a delivery device, which includes the steps of generating an electromagnetic control signal including frequency components absorbable by an electromagnetically responsive control element of a delivery device in an environment, the delivery device including a fluid-containing structure containing a delivery fluid and a quantity of primary material, the primary material being distributed between a first active form and a second form and having an effective concentration in the delivery fluid equal to the concentration of the first active form in the delivery fluid, wherein the effective concentration of the primary material in the delivery fluid is controllable by the electromagnetically responsive control element at 2702; and remotely transmitting the electromagnetic control signal to the delivery device with signal characteristics sufficient to activate the electromagnetically responsive control element in the delivery device to control the effective concentration of primary material in the delivery fluid in the delivery device at 2704.

FIG. 59 illustrates an expansion of the method shown in FIG. 58, with steps 2752 and 2754 being the same as steps 2702 and 2704, respectively, in FIG. 58, with a number of alternative steps relating to generation of the electromagnetic control signal. Step 2756a includes generating the electromagnetic control signal and transmitting the electromagnetic control signal to the delivery device with a remote controller. Step 2756b includes generating the electromagnetic control signal and transmitting the electromagnetic control signal to the delivery device with two or more remote controllers.

Step 2756c includes generating the electromagnetic control signal from a model-based calculation. Step 2756d includes generating the electromagnetic control signal based on a stored pattern. As yet another alternative, step 2756e includes generating the electromagnetic control signal based upon a feedback control scheme. A feedback control scheme may be, for example, a variable feedback control scheme.

A further expansion the method shown in FIG. 58 may include the additional steps depicted in FIG. 60, namely receiving a feedback signal corresponding to one or more parameters sensed from the environment at 2802; and based upon the feedback signal, generating the electromagnetic control signal with signal characteristics expected to produce a desired feedback signal, at 2804. In some embodiments, receiving the feedback signal from the environment may include receiving signals from at least one sensor in the environment, while in other embodiments it may include receiving the feedback signal from the environment includes receiving signals from two or more sensors in the environment. Receiving the feedback signal from the environment may include receiving a measure of the concentration or chemical activity of a chemical within at least a portion of the environment.

In another variation of the method shown in FIG. 58, shown in FIG. 61, the method may include the additional steps of receiving a feedback signal from the delivery device at 2852; and based upon the feedback signal, generating an electromagnetic control signal having signal characteristics that are expected to produce a desired feedback signal at 2854. Receiving a feedback signal from the delivery device may include receiving signals from at least one sensor in the delivery device, or alternatively, receiving a feedback signal from the delivery device may include receiving signals from two or more sensors in the delivery device. For example, receiving the feedback signal from the delivery device may include receiving a signal representing a concentration or chemical activity of a chemical within or around the delivery device.

Another variation of the method depicted in FIG. 58, shown in FIG. 62, may include the additional steps of receiving user input of one or more control parameters at 2892; and based upon the one or more control parameters, generating an electromagnetic control signal having signal characteristics expected to produce a desired effective concentration of primary material in the delivery fluid, as 2894. The desired effective

concentration of primary material in the delivery fluid may be an effective concentration sufficient to produce a desired rate of delivery of the first active form of the primary material to the environment by the delivery device.

Further additions to the method depicted in FIG. 58 include steps of activating the electromagnetically responsive control element to produce heating or cooling, or activating the electromagnetically responsive control element to produce a change in configuration of the electromagnetically responsive control element. Steps of generating an electromagnetic control signal and remotely transmitting the electromagnetic control signal to the delivery device, as shown in FIG. 58, may be performed according to instructions provided in the form of software, hardware or firmware. In some method embodiments, the steps of generating an electromagnetic control signal and remotely transmitting the electromagnetic control signal to the delivery device may be performed according to instructions distributed among a plurality of controllers or transmitters.

Generating the electromagnetic control signal includes generating a static or quasi-static magnetic field, static or quasi-static electrical field, radio-frequency electromagnetic signal, microwave electromagnetic signal, millimeter wave electromagnetic signal, optical electromagnetic signal, which may be an optical electromagnetic signal is an infrared electromagnetic signal, or generating an ultraviolet electromagnetic signal. Generating the electromagnetic control signal may be performed under software control.

FIG. 63 depicts a further variation of the method shown in FIG. 58, with steps 2902 and 2904 corresponding to steps 2702 and 2704, respectively. The method includes the additional step of modifying the concentration of the primary material within the delivery fluid in the fluid-containing structure of the delivery device by modifying the area of an interaction region within the fluid containing structure of the delivery device at 2906. Modifying the area of the interaction region includes increasing the area of the interaction region, as at 2906a, or alternatively, decreasing the area of the interaction region, as 2906b. In the case that the area is increased, and the interaction region includes interaction sites, and increasing the area of the interaction region may include increasing the distances between interaction sites in the interaction region, as at 2908a, or increasing the area of the interaction region includes increasing a number of interaction

sites in the reaction area, as at 2908b. In the case that the area is decreased, as at 2906b, and the interaction region includes interaction sites, decreasing the area of the interaction region may include decreasing distances between one or more interaction sites in the interaction region, as at 2910a, or decreasing a number of interaction sites in the reaction area as at 2910b.

FIG. 64 depicts a further variation of the method shown in FIG. 58, with steps 2952 and 2954 corresponding to steps 2702 and 2704, respectively. The method further includes a further step of modifying the concentration of the primary material in the delivery fluid by modifying a condition at an interaction region within the fluid-containing structure, at 2956. Modifying a condition at the interaction region may include heating or cooling at least a portion of the interaction region, as shown at 2958a, modifying the osmolality or the pH of at least a portion of the interaction region, at 2958b, modifying the surface charge of at least a portion of the interaction region, at 2958c, or modifying the surface energy of at least a portion of the interaction region, as 1958d.

In another variation, shown in FIG. 65, the method includes a further step of modifying a condition at the interaction region by modifying a condition within the fluid-containing structure, as indicated at step 3006 (steps 3002 and 3004 correspond to steps 2702 and 2704 in FIG. 58). Modifying a condition within the fluid-containing structure may include modifying the volume of the fluid-containing structure, as shown at 3008a, heating or cooling at least a portion of the fluid-containing structure, as shown at 3008b, or modifying the osmolality or the pH within at least a portion of the fluid-containing structure, as shown at 3008c.

FIG. 67 is a flow diagram of a method of controlling a delivery device. At step 3102, the method includes generating an acoustic control signal including frequency components absorbable by an acoustically responsive control element of a delivery device in an environment, the delivery device including a fluid-containing structure containing a delivery fluid and a quantity of primary material, the primary material being distributed between a first active form and a second form and having an effective concentration in the delivery fluid equal to the concentration of the first active form in the delivery fluid, wherein the effective concentration of the primary material in the delivery



fluid is controllable by the acoustically responsive control element. At step 3104, the method include remotely transmitting the acoustic control signal to the delivery device with signal characteristics sufficient to activate the acoustically responsive control element in the delivery device to control the effective concentration of primary material in the delivery fluid in the delivery device.

FIG. 68 provides further detail on the method steps depicted in FIG. 67. As before, the method includes generating an acoustic control signal including frequency components absorbable by an acoustically responsive control element of a delivery device in an environment, the delivery device including a fluid-containing structure containing a delivery fluid and a quantity of primary material, the primary material being distributed between a first active form and a second form and having an effective concentration in the delivery fluid equal to the concentration of the first active form in the delivery fluid, wherein the effective concentration of the primary material in the delivery fluid is controllable by the acoustically responsive control element, at step 3152, and remotely transmitting the acoustic control signal to the delivery device with signal characteristics sufficient to activate the acoustically responsive control element in the delivery device to control the effective concentration of primary material in the delivery fluid in the delivery device, at step 3154. Step 3152 can be carried out in a number of different ways (with different options indicated in dashed boxes), including generating the acoustic control signal from a model-based calculation, as indicated at 3158, generating the acoustic control signal based on a stored pattern, as indicated at 3160, or generating the acoustic control signal based upon a feedback control scheme, as indicated at 3162.

FIG. 69 details further alternative embodiments of the method of controlling a delivery device shown in FIG. 67. As before, the method includes generating an acoustic control signal including frequency components absorbable by an acoustically responsive control element of a delivery device in an environment, the delivery device including a fluid-containing structure containing a delivery fluid and a quantity of primary material, the primary material being distributed between a first active form and a second form and having an effective concentration in the delivery fluid equal to the concentration of the first active form in the delivery fluid, wherein the effective concentration of the primary

material in the delivery fluid is controllable by the acoustically responsive control element, at step 3202, and remotely transmitting the acoustic control signal to the delivery device with signal characteristics sufficient to activate the acoustically responsive control element in the delivery device to control the effective concentration of primary material in the delivery fluid in the delivery device, at step 3204. As indicated in the dashed boxes, the method may also include additional steps such as receiving a feedback signal corresponding to one or more parameters sensed from the environment, and, based upon the feedback signal, generating the acoustic control signal with signal characteristics expected to produce a desired feedback signal, as shown at 3208.

Alternatively, the method may include receiving a feedback signal from the delivery device and, based upon the feedback signal, generating the acoustic control signal with signal characteristics expected to produce a desired feedback signal, as shown at 3210. In still other embodiments, the method may include receiving user input of one or more control parameters, and based upon the one or more control parameters, generating the acoustic control signal with signal characteristics expected to produce a desired effective concentration of primary material in the delivery fluid.

In methods as illustrated in FIGS. 67 – 69, some or all of the steps of generating an acoustic control signal and remotely transmitting the acoustic control signal to the delivery device may be performed according to instructions provided in the form of software, hardware or firmware. Some or all of the steps of generating an acoustic control signal and remotely transmitting the acoustic control signal to the delivery device may be performed according to instructions distributed among a plurality of controllers or transmitters. The acoustic control signal may be generated under software control in some embodiments.

Software may be used in performing various of the methods as described herein. Such software includes software for controlling delivery of a material from a delivery device, including instructions for generating an electromagnetic control signal including frequency components absorbable by an electromagnetically responsive control element of a delivery device in an environment, the delivery device including a fluid-containing structure containing a delivery fluid and a quantity of primary material, the primary material being distributed between a first active form and a second form and having an

effective concentration in the delivery fluid equal to the concentration of the first active form in the delivery fluid, wherein the effective concentration of the primary material in the delivery fluid is controllable by the electromagnetically responsive control element; and instructions for controlling the transmission of the electromagnetic control signal to the delivery device with signal characteristics sufficient to activate the electromagnetically responsive control element in the delivery device to control the effective concentration of primary material in the delivery fluid in the delivery device.

The software may include instructions for generating the electromagnetic control signal include instructions for calculating the electromagnetic control signal based on a model. The instructions for generating the electromagnetic control signal may include instructions for generating the electromagnetic control signal based on a pattern stored in a data storage location, or instructions for generating the electromagnetic control signal based upon a feedback control algorithm. For example, the instructions for generating the electromagnetic control signal may include instructions for generating the electromagnetic control signal based upon a variable feedback control algorithm. The software may include instructions for receiving a feedback signal corresponding to one or more parameters sensed from the environment; and instructions for generating the electromagnetic control signal based at least in part upon the received feedback signal, the electromagnetic control signal having signal characteristics expected to produce a desired feedback signal. Some embodiments of the software may include instructions for receiving a feedback signal from the delivery device; and instructions for generating the electromagnetic control signal based at least in part on the received feedback signal, the electromagnetic control signal having frequency composition and amplitude expected to produce a desired feedback signal. In some embodiments, the software may include instructions for receiving user input of one or more control parameters; and instructions for generating the electromagnetic control signal based at least in part upon the one or more control parameters. In some embodiments, the software may include instructions for performing encryption of the electromagnetic control signal. Instruction may be included for performing an authentication procedure between a remote controller transmitting the electromagnetic control signal and a delivery device including the electromagnetically responsive control element intended to be activated by the

electromagnetic control signal. At least a portion of the instructions generating the electromagnetic control signal and the instruction for controlling the transmission of the electromagnetic control signal are executable in distributed fashion on a plurality of microprocessors. Some embodiments of the software may include channel allocation instructions configured to control the allocation of control signal transmission channels for transmission of a plurality of control signals to a corresponding plurality of delivery devices.

With regard to the hardware and/or software used in the control of devices and systems according to the present embodiments, and particularly to the sensing, analysis, and control aspects of such systems, those having skill in the art will recognize that the state of the art has progressed to the point where there is little distinction left between hardware and software implementations of aspects of systems; the use of hardware or software is generally (but not always, in that in certain contexts the choice between hardware and software can become significant) a design choice representing cost vs. efficiency or implementation convenience tradeoffs. Those having skill in the art will appreciate that there are various vehicles by which processes and/or systems described herein can be effected (e.g., hardware, software, and/or firmware), and that the preferred vehicle will vary with the context in which the processes are deployed. For example, if an implementer determines that speed and accuracy are paramount, the implementer may opt for a hardware and/or firmware vehicle; alternatively, if flexibility is paramount, the implementer may opt for a solely software implementation; or, yet again alternatively, the implementer may opt for some combination of hardware, software, and/or firmware. Hence, there are several possible vehicles by which the processes described herein may be effected; none of which is inherently superior to the other in that any vehicle to be utilized is a choice dependent upon the context in which the vehicle will be deployed and the specific concerns (e.g., speed, flexibility, or predictability) of the implementer, any of which may vary.

The foregoing detailed description has set forth various embodiments of the devices and related processes or methods via the use of block diagrams, flowcharts, and/or examples. Insofar as such block diagrams, flowcharts, and/or examples contain one or more functions and/or operations, it will be implicitly understood by those with

skill in the art that each function and/or operation within such block diagrams, flowcharts, or examples can be implemented, individually and/or collectively, by a wide range of hardware, software, firmware, or virtually any combination thereof. In one embodiment, several portions of the subject matter described herein may be implemented via Application Specific Integrated Circuits (ASICs), Field Programmable Gate Arrays (FPGAs), digital signal processors (DSPs), or other integrated formats. However, those skilled in the art will recognize that some aspects of the embodiments disclosed herein, in whole or in part, can be equivalently implemented in standard integrated circuits, as one or more computer programs running on one or more computers (e.g., as one or more programs running on one or more computer systems), as one or more programs running on one or more processors (e.g., as one or more programs running on one or more microprocessors), as firmware, or as virtually any combination thereof, and that designing the circuitry and/or writing the code for the software and/or firmware would be well within the capabilities of one of skill in the art in light of this disclosure. In addition, those skilled in the art will appreciate that certain mechanisms of the subject matter described herein are capable of being distributed as a program product in a variety of forms, and that an illustrative embodiment of the subject matter described herein applies equally regardless of the particular type of signal bearing media used to actually carry out the distribution. Examples of a signal bearing media include, but are not limited to, the following: recordable type media such as floppy disks, hard disk drives, CD ROMs, digital tape, and computer memory; and transmission type media such as digital and analog communication links using TDM or IP based communication links (e.g., links carrying packetized data).

In a general sense, those skilled in the art will recognize that the various aspects described herein which can be implemented, individually and/or collectively, by a wide range of hardware, software, firmware, or any combination thereof can be viewed as being composed of various types of "electrical circuitry." Consequently, as used herein "electrical circuitry" includes, but is not limited to, electrical circuitry having at least one discrete electrical circuit, electrical circuitry having at least one integrated circuit, electrical circuitry having at least one application specific integrated circuit, electrical circuitry forming a general purpose computing device configured by a computer program

(e.g., a general purpose computer configured by a computer program which at least partially carries out processes and/or devices described herein, or a microprocessor configured by a computer program which at least partially carries out processes and/or devices described herein), electrical circuitry forming a memory device (e.g., forms of random access memory), and/or electrical circuitry forming a communications device (e.g., a modem, communications switch, or optical-electrical equipment).

Those skilled in the art will recognize that it is common within the art to describe devices for detection or sensing, signal processing, and device control in the fashion set forth herein, and thereafter use standard engineering practices to integrate such described devices and/or processes into fluid handling and/or delivery systems as exemplified herein. That is, at least a portion of the devices and/or processes described herein can be integrated into a fluid handling and/or delivery system via a reasonable amount of experimentation.

Those having skill in the art will recognize that systems as described herein may include one or more of a memory such as volatile and non-volatile memory, processors such as microprocessors and digital signal processors, computational-supporting or – associated entities such as operating systems, user interfaces, drivers, sensors, actuators, applications programs, one or more interaction devices, such as data ports, control systems including feedback loops and control implementing actuators (e.g., devices for sensing osmolality, pH, pressure, temperature, or chemical concentration, signal generators for generating electromagnetic control signals). A system may be implemented utilizing any suitable available components, combined with standard engineering practices.

The foregoing-described aspects depict different components contained within, or connected with, different other components. It is to be understood that such depicted architectures are merely exemplary, and that in fact many other architectures can be implemented which achieve the same functionality. In a conceptual sense, any arrangement of components to achieve the same functionality is effectively "associated" such that the desired functionality is achieved. Hence, any two components herein combined to achieve a particular functionality can be seen as "associated with" each other such that the desired functionality is achieved, irrespective of architectures or

intermediate components. Likewise, any two components so associated can also be viewed as being "operably connected", or "operably coupled", to each other to achieve the desired functionality.

While particular aspects of the present subject matter described herein have been shown and described, it will be obvious to those skilled in the art that, based upon the teachings herein, changes and modifications may be made without departing from this subject matter described herein and its broader aspects and, therefore, the appended claims are to encompass within their scope all such changes and modifications as are within the true spirit and scope of this subject matter described herein. In particular, while selected examples of systems, devices, components and methods employing acoustic signal generation, transmission, and reception are specifically described, it will be appreciated that various other systems, devices, components and methods described herein in connection with the use of electromagnetic, electrical, or magnetic control signals may be modified to instead employ acoustic control signals, and that such modification will be apparent to those of skill in the art, and such modifications are considered to fall within the scope of the subject matter described herein. Furthermore, it is to be understood that the invention is defined by the appended claims. It will be understood by those within the art that, in general, terms used herein, and especially in the appended claims (e.g., bodies of the appended claims) are generally intended as "open" terms (e.g., the term "including" should be interpreted as "including but not limited to," the term "having" should be interpreted as "having at least," the term "includes" should be interpreted as "includes but is not limited to," etc.). It will be further understood by those within the art that if a specific number of an introduced claim recitation is intended, such an intent will be explicitly recited in the claim, and in the absence of such recitation no such intent is present. For example, as an aid to understanding, the following appended claims may contain usage of the introductory phrases "at least one" and "one or more" to introduce claim recitations. However, the use of such phrases should NOT be construed to imply that the introduction of a claim recitation by the indefinite articles "a" or "an" limits any particular claim containing such introduced claim recitation to inventions containing only one such recitation, even when the same claim includes the introductory phrases "one or more" or "at least one" and

indefinite articles such as "a" or "an" (e.g., "a" and/or "an" should typically be interpreted to mean "at least one" and/or "one or more"); the same holds true for the use of definite articles used to introduce claim recitations. In addition, even if a specific number of an introduced claim recitation is explicitly recited, those skilled in the art will recognize that such recitation should typically be interpreted to mean at least the recited number (e.g., the bare recitation of "two recitations," without other modifiers, typically means at least two recitations, or two or more recitations). Furthermore, in those instances where a convention analogous to "at least one of A, B, and C, etc." is used, in general such a construction is intended in the sense of one having skill in the art would understand the convention (e.g., "a system having at least one of A, B, and C" would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together). In those instances where a convention analogous to "at least one of A, B, or C, etc." is used, in general such a construction is intended in the sense of one having skill in the art would understand the convention (e.g., "a system having at least one of A, B, or C" would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together).

Although the methods, devices, systems and approaches herein have been described with reference to certain preferred embodiments, other embodiments are possible. As illustrated by the foregoing examples, various choices of remote controller, system configuration and fluid handling/delivery device may be within the scope of the invention. As has been discussed, the choice of system configuration may depend on the intended application of the system, the environment in which the system is used, cost, personal preference or other factors. System design, manufacture, and control processes may be modified to take into account choices of use environment and intended application, and such modifications, as known to those of skill in the arts of device design and construction, may fall within the scope of the invention. Therefore, the full spirit or scope of the invention is defined by the appended claims and is not to be limited to the specific embodiments described herein.

While various aspects and embodiments have been disclosed herein, other aspects and embodiments will be apparent to those skilled in the art. It is intended that the



various aspects and embodiments disclosed herein are for purposes of illustration and are not intended to be limiting, with the true scope and spirit being indicated by the following claims.

What is claimed is:

1. A delivery device comprising:
  - a delivery reservoir configured to contain a delivery fluid, the delivery reservoir having at least one outlet through which the delivery fluid may exit the delivery reservoir;
  - a delivery fluid contained within the delivery reservoir;
  - a primary material contained within the delivery reservoir and having a controllable effective concentration in the delivery fluid; and
  - at least one acoustically responsive control element adapted for modifying the distribution of the primary material between a first active form carried in the delivery fluid and a second form in response to an acoustic control signal, the effective concentration being the concentration of the first active form in the delivery fluid.
2. The delivery device of claim 1, wherein the first active form is carried in solution in the delivery fluid.
3. The delivery device of claim 1, wherein the first active form is carried in suspension in the delivery fluid.
4. The delivery device of claim 1, wherein the first active form is carried in emulsion in the delivery fluid.
5. The delivery device of claim 1, wherein the first active form is carried in colloidal dispersion in the delivery fluid.
6. The delivery device of claim 1, wherein the second form is an inactive form of the primary material carried in the delivery fluid.

7. The delivery device of claim 6, wherein the second form is a chemically inactive form.
8. The delivery device of claim 6, wherein the second form is a chemically active form contained in a carrier structure.
9. The delivery device of claim 8, wherein the carrier structure is a capsule, microcapsule, micelle, or fullerene.
10. The delivery device of claim 6, wherein the second form is carried in solution in the delivery fluid.
11. The delivery device of claim 6, wherein the second form is carried in suspension in the delivery fluid.
12. The delivery device of claim 6, wherein the second form is carried in emulsion in the delivery fluid.
13. The delivery device of claim 6, wherein the second form is carried in colloidal dispersion in the delivery fluid.
14. The delivery device of claim 1, wherein the second form is bound or associated with an interaction region in the delivery reservoir.
15. The delivery device of claim 1, wherein the second form is insoluble in the delivery fluid.
16. The delivery device of claim 15, including a filter located between the delivery reservoir and the outlet and configured for removing the second form from the delivery fluid.

17. The delivery device of claim 1, wherein the second form is precipitated out of the delivery fluid.
18. The delivery device of claim 1, wherein the at least one acoustically responsive control element is an acoustically responsive molecule in the delivery fluid, and wherein the acoustically responsive molecule undergoes a change in conformation from a first conformation state to a second conformation state in response to the acoustic control signal, and wherein the first conformation state has a first solubility in the delivery fluid and wherein the second conformation state has a second solubility in the delivery fluid.
19. The delivery device of claim 18, wherein the acoustically responsive molecule forms at least a portion of the primary material in the delivery fluid.
20. The delivery device of claim 18, wherein the acoustically responsive molecule forms at least a portion of a secondary material that influences the solubility of the primary material in the delivery fluid.
21. The delivery device of claim 1, wherein the at least one acoustically responsive control element includes an acoustically responsive heating element.
22. The delivery device of claim 1, wherein the at least one acoustically responsive control element includes a shape memory material.
23. The delivery device of claim 22, wherein the shape memory material includes a shape memory polymer or a shape memory metal.
24. The delivery device of claim 1, wherein the at least one acoustically responsive control element includes a bimetallic structure.

25. The delivery device of claim 1, wherein the at least one acoustically responsive control element includes a polymer, ceramic, crystalline material, piezoelectric material, or combination thereof.
26. The delivery device of claim 1, wherein the at least one acoustically responsive control element includes at least one hydrogel, ferrogel or ferroelectric.
27. The delivery device of claim 1, wherein the at least one acoustically responsive control element includes a polymer and an acoustically active component.
28. The delivery device of claim 1, wherein the at least one acoustically responsive control element includes an acoustically responsive cooling element.
29. The delivery device of claim 28, wherein the acoustically responsive cooling element includes at least one thermoelectric device, liquid-gas vaporization device, or phase-change material or system.
30. The delivery device of claim 1, wherein the at least one acoustically responsive control element is configured to selectively respond to an acoustic field having a specific frequency and orientation.
31. The delivery device of claim 1, wherein the at least one acoustically responsive control element is a shape-changing structure that changes in at least one dimension in response to an acoustic control signal.
32. The delivery device of claim 31, wherein the shape-changing structure includes a polymeric material, a hydrogel, a bimetallic structure, or a shape memory material.
33. The delivery device of claim 31, wherein the shape-changing structure is an expanding or contracting structure, and wherein the change in at least one dimension includes an expansion or contraction in at least one dimension.

34. The delivery device of claim 33, wherein expansion or contraction of the expanding or contracting structure modifies the volume of the delivery reservoir.
35. The delivery device of claim 33, wherein expansion or contraction of the expanding or contracting structure exposes molecular structures to the delivery fluid that modify the solubility of the primary material in the delivery fluid.
36. The delivery device of claim 35, wherein the molecular structures modify the pH of at least a portion of the delivery fluid.
37. The delivery device of claim 35, wherein the molecular structures modify the polarity of at least a portion of the delivery fluid.
38. The delivery device of claim 35, wherein the molecular structures are interaction sites for the primary material, whereby primary material bound by the interaction sites is removed from the delivery fluid.
39. The delivery device of claim 1, wherein the primary material has a different immunogenicity when it is in the first active form than in the second form.
40. The delivery device of claim 1, wherein the primary material has a different reactivity when it is in the first active form than in the second form.
41. The delivery device of claim 1, wherein the primary material has a different stability when it is in the first active form than in the second form.
42. The delivery device of claim 1, wherein the primary material is a pharmaceutical material or a nutraceutical material.

43. The delivery device of claim 1, wherein the primary material is a biologically active material.

44. The delivery device of claim 1, wherein the primary material includes at least one nutrient, hormone, growth factor, medication, therapeutic compound, enzyme, genetic material, vaccine, vitamin, neurotransmitter, cytokine, cell-signaling material, pro- or anti-apoptotic agent, imaging agent, labeling agent, diagnostic compound, nanomaterial, inhibitor, or blocker.

45. The delivery device of claim 1, wherein the primary material is a component or precursor of a biologically active material.

46. The delivery device of claim 45, wherein the primary material includes at least one precursor or component of a nutrient, hormone, growth factor, medication, therapeutic compound, enzyme, genetic material, vaccine, vitamin, neurotransmitter, cytokine, cell-signaling material, pro- or anti-apoptotic agent, imaging agent, labeling agent, diagnostic compound, nanomaterial, inhibitor, or blocker.

47. The delivery device of claim 1, wherein the primary material includes at least one fertilizer, nutrient, remediation agent, antibiotic, microbicide, herbicide, fungicide, transfection agent, nanomaterial, disinfectant, metal salt, buffer, acid, base, chelating agent, emulsifying agent, or surfactant.

48. The delivery device of claim 1, wherein the primary material includes a tissue-specific marker or targeting molecule.

49. The delivery device of claim 48, wherein the tissue specific marker or targeting molecule is a tissue-specific endothelial protein.

50. The delivery device of claim 1, including an RFID.

51. The delivery device of claim 1, including a body structure adapted for positioning in an environment selected from a body of an organism, a body of water, or a contained fluid volume, the delivery reservoir located within the body structure.
52. The delivery device of 51, wherein the body structure includes a tissue-specific marker or targeting molecule.
53. The delivery device of claim 52, wherein the tissue specific marker or targeting molecule is a tissue specific endothelial protein.
54. The delivery device of claim 1, including a body structure adapted for positioning in a contained fluid volume selected from an industrial fluid volume, an agricultural fluid volume, a swimming pool, an aquarium, a drinking water supply, a potable water supply, and an HVAC system cooling water supply.
55. The delivery device of claim 1, including at least one interaction region capable of interacting with the primary material by one or more of binding, reacting, interacting, or forming a complex with the primary material.
56. The delivery device of claim 55, wherein the at least one interaction region is responsive to the acoustic control signal by a change in at least one characteristic, the change in the at least one characteristic modifying the interaction between the at least one interaction region and the primary material.
57. The delivery device of claim 56, wherein the at least one characteristic includes at least one solubility, reactivity, temperature, conformation, orientation, alignment, binding affinity, chemical potential, surface energy, porosity, osmolality, pH, distribution within the delivery reservoir, or density.
58. The delivery device of claim 55, wherein at least a portion of the delivery reservoir containing the at least one interaction region is responsive to the acoustic control signal



by a change in the surface area of the portion of the delivery reservoir, the change in surface area modifying the likelihood of interaction of the primary material with the at least one interaction region.

59. The delivery device of claim 58, wherein the change of surface area is produced by stretching or expansion of the portion of the delivery reservoir.

60. The delivery device of claim 58, wherein the change of surface area is produced by unfolding of the portion of the delivery reservoir.

61. The delivery device of claim 1, wherein the delivery device is a MEMS device.

62. The delivery device of claim 1, wherein the delivery device is constructed from at least one polymer, ceramic, glass, or semiconductor material

63. The delivery device of claim 1, wherein the delivery device is a battery-free device.

64. The delivery device of claim 1, including at least one sensor for detecting at least one parameter from the delivery reservoir.

65. The delivery device of claim 64, including at least one sensor for detecting a quantity or concentration of primary material in the delivery reservoir.

66. The delivery device of claim 1, including at least one sensor for detecting at least one parameter from at least a portion of an environment surrounding the delivery device.

67. The delivery device of claim 66, including at least one sensor for detecting a concentration or activity of a chemical within at least a portion of an environment surrounding the delivery device.

68. The delivery device of claim 1, including a pump configured for pumping delivery fluid from the fluid-containing structure to the downstream location.
69. The delivery device of claim 68, wherein the pump includes an osmotic pump.
70. The delivery device of claim 68, wherein the pump includes a mechanical pump.
71. The delivery device of claim 68, wherein the pump includes a displacement pump.
72. The delivery device of claim 68, wherein the pump includes a centrifugal pump.
73. The delivery device of claim 68, wherein the pump includes a peristaltic pump.
74. The delivery device of claim 68, wherein the downstream location is an environment.
75. The delivery device of claim 68, wherein the downstream location includes a downstream environmental interface.
76. The delivery device of claim 68, wherein the downstream location includes a downstream fluid handling structure.
77. The delivery device of claim 76, wherein the downstream fluid handling structure includes at least one channel.
78. The delivery device of claim 76, wherein the downstream fluid handling structure includes at least one chamber.
79. The delivery device of claim 76, wherein the downstream fluid handling structure includes at least one mixer.

80. The delivery device of claim 76, wherein the downstream fluid handling structure includes at least one splitter.
81. The delivery device of claim 76, wherein the downstream fluid handling structure includes at least one filter.
82. A method of controlling a delivery device, comprising:  
generating an acoustic control signal including frequency components absorbable by an acoustically responsive control element of a delivery device in an environment, the delivery device including a fluid-containing structure containing a delivery fluid and a quantity of primary material, the primary material being distributed between a first active form and a second form and having an effective concentration in the delivery fluid equal to the concentration of the first active form in the delivery fluid, wherein the effective concentration of the primary material in the delivery fluid is controllable by the acoustically responsive control element; and  
remotely transmitting the acoustic control signal to the delivery device with signal characteristics sufficient to activate the acoustically responsive control element in the delivery device to control the effective concentration of primary material in the delivery fluid in the delivery device.
83. The method of claim 82, including generating the acoustic control signal and transmitting the acoustic control signal to the delivery device with a remote controller.
84. The method of claim 82, including generating the acoustic control signal and transmitting the acoustic control signal to the delivery device with two or more remote controllers.
85. The method of claim 82, including generating the acoustic control signal from a model-based calculation.

86. The method of claim 82, including generating the acoustic control signal based on a stored pattern.

87. The method of claim 82, including generating the acoustic control signal based upon a feedback control scheme.

88. The method of claim 87, including generating the acoustic control signal based upon a variable feedback control scheme.

89. The method of claim 82, including:  
receiving a feedback signal corresponding to one or more parameters sensed from the environment; and  
based upon the feedback signal, generating the acoustic control signal with signal characteristics expected to produce a desired feedback signal.

90. The method of claim 89, wherein receiving the feedback signal from the environment includes receiving signals from at least one sensor in the environment.

91. The method of claim 89, wherein receiving the feedback signal from the environment includes receiving signals from two or more sensors in the environment.

92. The method of claim 89, wherein receiving the feedback signal from the environment includes receiving a measure of the concentration or chemical activity of a chemical within at least a portion of the environment.

93. The method of claim 82, including:  
receiving a feedback signal from the delivery device; and  
based upon the feedback signal, generating the acoustic control signal with signal characteristics expected to produce a desired feedback signal.

94. The method of claim 93, wherein receiving a feedback signal from the delivery device includes receiving signals from at least one sensor in the delivery device.

95. The method of claim 93, wherein receiving a feedback signal from the delivery device includes receiving signals from two or more sensors in the delivery device.

96. The method of claim 93, wherein receiving the feedback signal from the delivery device includes receiving a signal representing a concentration or chemical activity of a chemical within or around the delivery device.

97. The method of claim 82, including:  
receiving user input of one or more control parameters; and  
based upon the one or more control parameters, generating the acoustic control signal with signal characteristics expected to produce a desired effective concentration of primary material in the delivery fluid.

98. The method of claim 97, wherein the desired effective concentration of primary material in the delivery fluid is an effective concentration sufficient to produce a desired rate of delivery of the first active form of the primary material to the environment by the delivery device.

99. The method of claim 82, including activating the acoustically responsive control element to produce heating or cooling.

100. The method of claim 82, including activating the acoustically responsive control element to produce a change in configuration of the acoustically responsive control element.

101. The method of claim 82, wherein the steps of generating an acoustic control signal and remotely transmitting the acoustic control signal to the delivery device are performed according to instructions provided in the form of software, hardware or firmware.

102. The method of claim 82, wherein the steps of generating an acoustic control signal and remotely transmitting the acoustic control signal to the delivery device are performed according to instructions distributed among a plurality of controllers or transmitters.

103. The method of claim 82, including generating the acoustic control signal under software control.

104. The method of claim 82, wherein modifying the concentration of the primary material in the delivery fluid within the fluid-containing structure of the delivery device includes modifying a condition at an interaction region within the fluid-containing structure.

105. The method of claim 104, wherein modifying a condition at the interaction region includes heating or cooling at least a portion of the interaction region.

106. The method of claim 104, wherein modifying a condition at the interaction region includes modifying the osmolality or the pH of at least a portion of the interaction region.

107. The method of claim 104, wherein modifying a condition at the interaction region includes modifying the surface charge of at least a portion of the interaction region.

108. The method of claim 104, wherein modifying a condition at the interaction region includes modifying the surface energy of at least a portion of the interaction region.

109. The method of claim 82, wherein modifying a condition at the interaction region includes modifying a condition within the fluid-containing structure.

110. The method of claim 109, wherein modifying a condition within the fluid-containing structure includes modifying the volume of the fluid-containing structure.

111. The method of claim 109, wherein modifying a condition within the fluid-containing structure includes heating or cooling at least a portion of the fluid-containing structure.

112. The method of claim 109, wherein modifying a condition within the fluid-containing structure includes modifying the osmolality or the pH within at least a portion of the fluid-containing structure.

113. Software for controlling delivery of a material from a delivery device, comprising:  
instructions for generating an acoustic control signal including frequency components absorbable by an acoustically responsive control element of a delivery device in an environment, the delivery device including a fluid-containing structure containing a delivery fluid and a quantity of primary material, the primary material being distributed between a first active form and a second form and having an effective concentration in the delivery fluid equal to the concentration of the first active form in the delivery fluid, wherein the effective concentration of the primary material in the delivery fluid is controllable by the acoustically responsive control element; and  
instructions for controlling the transmission of the acoustic control signal to the delivery device with signal characteristics sufficient to activate the acoustically responsive control element in the delivery device to control the effective concentration of primary material in the delivery fluid in the delivery device.

114. The software of claim 113, wherein the instructions for generating the acoustic control signal include instructions for calculating the acoustic control signal based on a model.

115. The software of claim 113, wherein the instructions for generating the acoustic control signal include instructions for generating the acoustic control signal based on a pattern stored in a data storage location.

116. The software of claim 113, wherein the instructions for generating the acoustic control signal include instructions for generating the acoustic control signal based upon a feedback control algorithm.

117. The software of claim 116, wherein the instructions for generating the acoustic control signal include instructions for generating the acoustic control signal based upon a variable feedback control algorithm.

118. The software of claim 113, including:

instructions for receiving a feedback signal corresponding to one or more parameters sensed from the environment; and

instructions for generating the acoustic control signal based at least in part upon the received feedback signal, the acoustic control signal having signal characteristics expected to produce a desired feedback signal.

119. The software of claim 113, including:

instructions for receiving a feedback signal from the osmotic pump device; and

instructions for generating the acoustic control signal based at least in part on the received feedback signal, the acoustic control signal having frequency composition and amplitude expected to produce a desired feedback signal.

120. The software of claim 113, including:

instructions for receiving user input of one or more control parameters; and

instructions for generating the acoustic control signal based at least in part upon the one or more control parameters.

121. The software of claim 113, including instructions for performing encryption of the acoustic control signal.

122. The software of claim 113, including instructions for performing an authentication procedure between a remote controller transmitting the acoustic control signal and a



delivery device including the acoustically responsive control element intended to be activated by the acoustic control signal.

123. The software of claim 113, wherein at least a portion of the instructions generating the acoustic control signal and the instruction for controlling the transmission of the acoustic control signal are executable in distributed fashion on a plurality of microprocessors.

124. The software of claim 113, including channel allocation instructions configured to control the allocation of control signal transmission channels for transmission of a plurality of control signals to a corresponding plurality of delivery devices.

1/51






FIG. 1



3/51




FIG. 4A




FIG. 4B

4/51








FIG. 5

5/51



6/51




FIG. 7A




FIG. 7B

7/51




FIG. 8A




FIG. 8B



8/51




FIG. 9A

$$T_1 > T_2$$






FIG. 9B

9/51



10/51




FIG. 11A




FIG. 11B

11/51




FIG. 12A




FIG. 12B




FIG. 12C




FIG. 12D

12/51




FIG. 13A

FIG. 13B




FIG. 14A

FIG. 14B

13/51




FIG. 15A




FIG. 15B




FIG. 16A




FIG. 16B

14/51




FIG. 17A




FIG. 17B




FIG. 18A




FIG. 18B




FIG. 19A




FIG. 19B

15/51




FIG. 20A




FIG. 20B



16/51




FIG. 21







FIG. 22

17/51



18/51




FIG. 26

$$f(t_n) = F(n, P_1, P_2, \dots, P_k) \quad 1050$$




FIG. 27




FIG. 28




FIG. 29

20/51




FIG. 30




FIG. 31

21/51




FIG. 32




FIG. 33

22/51




FIG. 34




FIG. 35

23/51




FIG. 36



24/51




FIG. 37

25/51






FIG. 38

26/51



27/51




FIG. 41

28/51




FIG. 42




FIG. 43

29/51




FIG. 44




FIG. 45




FIG. 46

31/51




FIG. 47




FIG. 48






FIG. 49




FIG. 50

33/51




FIG. 51

34/51




FIG. 52

35/51




FIG. 53

36/51




FIG. 54

37/51




FIG. 55

38/51




FIG. 56

39/51




FIG. 57



40/51




FIG. 58

41/51




FIG. 59

42/51




FIG. 60

43/51




FIG. 61

44/51




FIG. 62

45/51




FIG. 63

46/51




FIG. 64

47/51




FIG. 65



48/51




FIG. 66

49/51




FIG. 67

50/51




FIG. 68

51/51




FIG. 69