



US009270956B2

(12) **United States Patent**
Whitehead et al.

(10) **Patent No.:** **US 9,270,956 B2**
(45) **Date of Patent:** **Feb. 23, 2016**

(54) **IMAGE DISPLAY**

(71) Applicant: **Dolby Laboratories Licensing Corporation**, San Francisco, CA (US)

(72) Inventors: **Lorne A. Whitehead**, Vancouver (CA); **Gregory John Ward**, Berkeley, CA (US); **Wolfgang Stuerzlinger**, Toronto (CA); **Helge Seetzen**, Vancouver (CA); **Don Graham**

(73) Assignee: **Dolby Laboratories Licensing Corporation**, San Francisco, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/521,832**

(22) Filed: **Oct. 23, 2014**

(65) **Prior Publication Data**

US 2015/0043050 A1 Feb. 12, 2015

Related U.S. Application Data

(63) Continuation of application No. 13/774,563, filed on Feb. 22, 2013, now Pat. No. 8,890,799, which is a continuation of application No. 13/358,311, filed on Jan. 25, 2012, now Pat. No. 8,446,351, which is a continuation of application No. 11/831,827, filed on Jul. 31, 2007, now Pat. No. 8,125,425, which is a continuation of application No. 10/507,460, filed as application No. PCT/CA03/00350 on Mar. 13, 2003, now Pat. No. 7,403,332.

(60) Provisional application No. 60/363,563, filed on Mar. 13, 2002.

(51) **Int. Cl.**
G02B 26/00 (2006.01)
H04N 9/31 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **H04N 9/3102** (2013.01); **G02F 1/01** (2013.01); **G02F 1/1347** (2013.01); **G02F 1/133603** (2013.01); **G09G 3/32** (2013.01); **G09G 3/3426** (2013.01); **G09G 3/3611**

(2013.01); **H01J 63/06** (2013.01); **H04N 9/3126** (2013.01); **H04N 9/3155** (2013.01); **H04N 9/3194** (2013.01); **H04N 9/3197** (2013.01); **H05B 33/0857** (2013.01); **G02F 1/133524** (2013.01); **G02F 2001/133613** (2013.01); **G09G 3/34** (2013.01);
(Continued)

(58) **Field of Classification Search**
USPC 359/238
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,170,771 A 10/1979 Bly
4,229,095 A 10/1980 Mir

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0730371 A2 9/1996
EP 0829747 A1 3/1998

(Continued)

OTHER PUBLICATIONS

Funamoto et al., "High-Picture-Quality Technique for LCD Televisions: LCD-A1", Proc. Sid, International Display Workshop (IDW '00), Nov. 2000, p. 1157-1158.


(Continued)

Primary Examiner — Jack Dinh

(57) **ABSTRACT**

A display has a screen which incorporates a light modulator. The screen may be a front projection screen or a rear-projection screen. The screen is illuminated with light from a light source comprising an array of controllable light-emitters. The controllable-emitters and elements of the light modulator may be controlled to adjust the intensity of light emanating from corresponding areas on the screen. The display may provide a high dynamic range.

21 Claims, 15 Drawing Sheets



(51)	Int. Cl.		6,111,559 A	8/2000	Motomura et al.
	G02F 1/1347	(2006.01)	6,111,560 A	8/2000	May
	G09G 3/32	(2006.01)	6,120,588 A	9/2000	Jacobson
	G09G 3/36	(2006.01)	6,120,839 A	9/2000	Comiskey et al.
	H01J 63/06	(2006.01)	6,144,162 A	11/2000	Smith
	H05B 33/08	(2006.01)	6,163,621 A	12/2000	Paik et al.
	G02F 1/01	(2006.01)	6,172,798 B1	1/2001	Albert et al.
	G02F 1/1335	(2006.01)	6,184,969 B1	2/2001	Ferguson
	G09G 3/34	(2006.01)	6,204,913 B1	3/2001	Miyawaki et al.
			6,215,920 B1	4/2001	Whitehead et al.
			6,229,558 B1	5/2001	Saigo et al.
(52)	U.S. Cl.		6,229,588 B1	5/2001	Abileah et al.
	CPC <i>G09G 2300/023</i> (2013.01); <i>G09G 2310/024</i>		6,243,055 B1	6/2001	Ferguson
	(2013.01); <i>G09G 2320/0233</i> (2013.01); <i>G09G</i>		6,243,068 B1	6/2001	Evanicky et al.
	<i>2320/0271</i> (2013.01); <i>G09G 2320/043</i>		6,268,843 B1	7/2001	Arakawa
	(2013.01); <i>G09G 2320/064</i> (2013.01); <i>G09G</i>		6,276,801 B1	8/2001	Fielding
	<i>2320/066</i> (2013.01); <i>G09G 2320/0626</i>		6,300,932 B1	10/2001	Albert
	(2013.01); <i>G09G 2320/0633</i> (2013.01); <i>G09G</i>		6,323,989 B1	11/2001	Jacobson et al.
	<i>2320/0646</i> (2013.01); <i>G09G 2320/0693</i>		6,327,072 B1	12/2001	Comiskey et al.
	(2013.01); <i>G09G 2330/08</i> (2013.01); <i>G09G</i>		6,381,372 B1	4/2002	Loce
	<i>2360/145</i> (2013.01); <i>G09G 2360/16</i> (2013.01)		6,414,661 B1	7/2002	Shen et al.
			6,421,103 B2	7/2002	Yamaguchi
			6,428,189 B1	8/2002	Hochstein
			6,435,691 B1	8/2002	Macey et al.
			6,437,769 B1	8/2002	Kobayashi et al.
			6,439,731 B1	8/2002	Johnson et al.
			6,448,951 B1	9/2002	Sakaguchi et al.
			6,448,955 B1	9/2002	Evanicky et al.
			6,483,643 B1	11/2002	Zuchowski
			6,520,646 B2	2/2003	Rodriguez, Jr. et al.
			6,590,561 B1	7/2003	Kabel et al.
			6,608,614 B1	8/2003	Johnson
			6,618,115 B1	9/2003	Hiroki
			6,621,482 B2	9/2003	Fuller
			6,631,995 B2	10/2003	Stanton et al.
			6,644,832 B2	11/2003	Yoshida et al.
			6,654,156 B1	11/2003	Crossland et al.
			6,657,607 B1	12/2003	Evanicky et al.
			6,671,008 B1	12/2003	Li et al.
			6,680,834 B2	1/2004	Williams
			6,683,657 B1	1/2004	Miyawaki
			6,728,023 B1	4/2004	Alioshin et al.
			6,753,661 B2	6/2004	Muthu et al.
			6,796,658 B2	9/2004	Hubel et al.
			6,803,901 B1	10/2004	Numao
			6,816,141 B1	11/2004	Ferguson
			6,817,717 B2	11/2004	Childers et al.
			6,831,624 B1	12/2004	Harrold
			6,831,711 B2	12/2004	Choi et al.
			6,863,401 B2	3/2005	Penn
			6,888,663 B2	5/2005	Bourdelaïs et al.
			6,891,672 B2	5/2005	Whitehead et al.
			6,952,195 B2	10/2005	Arakawa
			6,980,176 B2	12/2005	Matsumoto et al.
			6,980,195 B2	12/2005	Lonoco et al.
			6,985,272 B2	1/2006	Bridgwater et al.
			7,002,533 B2	2/2006	Sayag
			7,018,046 B2	3/2006	Childers et al.
			7,050,122 B2	5/2006	Gibbon et al.
			7,052,152 B2	5/2006	Harbers et al.
			7,053,881 B2	5/2006	Itoh
			7,064,740 B2	6/2006	Daly
			7,071,907 B1	7/2006	Duboc, Jr. et al.
			7,106,505 B2	9/2006	Whitehead et al.
			7,118,225 B2	10/2006	Penn
			7,172,297 B2	2/2007	Whitehead et al.
			7,175,281 B1	2/2007	Berman
			7,403,332 B2	7/2008	Whitehead et al.
			7,413,309 B2	8/2008	Whitehead et al.
			7,419,267 B2	9/2008	Whitehead
			7,532,192 B2	5/2009	Feng et al.
			7,942,531 B2	5/2011	Whitehead et al.
			8,172,401 B2	5/2012	Whitehead et al.
			2001/0013854 A1	8/2001	Ogoro
			2001/0019390 A1	9/2001	Itoh et al.
			2001/0035853 A1	11/2001	Hoelen et al.
			2001/0043179 A1	11/2001	Yoshinaga et al.
			2002/0003522 A1	1/2002	Baba et al.
			2002/0050957 A1	5/2002	Nagano
(56)	References Cited				
	U.S. PATENT DOCUMENTS				
	4,316,196 A	2/1982	Jacobs		
	4,364,039 A	12/1982	Penz		
	4,374,397 A	2/1983	Mir		
	4,378,568 A	3/1983	Mir		
	4,441,791 A	4/1984	Hornbeck		
	4,559,480 A	12/1985	Nobs		
	4,580,877 A	4/1986	Washo		
	4,637,150 A	1/1987	Geluk		
	4,726,663 A	2/1988	Buzak		
	4,801,194 A	1/1989	Agostinelli et al.		
	4,853,824 A	8/1989	Tsuzurahara		
	4,868,668 A	9/1989	Tavernetti		
	4,933,754 A	6/1990	Reed et al.		
	4,954,789 A	9/1990	Sampsell		
	4,987,410 A	1/1991	Berman et al.		
	4,995,719 A	2/1991	Shanks		
	5,029,967 A	7/1991	Livezey et al.		
	5,075,789 A	12/1991	Jones et al.		
	5,103,328 A	4/1992	Numao		
	5,122,791 A	6/1992	Gibbons et al.		
	5,144,292 A	9/1992	Shiraishi et al.		
	5,247,366 A	9/1993	Ginosar et al.		
	5,359,345 A	10/1994	Hunter		
	5,386,253 A	1/1995	Fielding		
	5,422,691 A	6/1995	Ninomiya et al.		
	5,504,504 A	4/1996	Markandey et al.		
	5,537,233 A	7/1996	Miura et al.		
	5,537,256 A	7/1996	Ferguson		
	5,572,341 A	11/1996	Ferguson		
	5,592,193 A	1/1997	Chen		
	5,638,167 A	6/1997	Nakamura		
	5,639,158 A	6/1997	Sato		
	5,646,702 A	7/1997	Akinwande et al.		
	5,652,672 A	7/1997	Huignard et al.		
	5,666,226 A	9/1997	Ezra et al.		
	5,684,354 A	11/1997	Gleckman		
	5,715,029 A	2/1998	Ferguson		
	5,717,422 A	2/1998	Ferguson		
	5,724,062 A	3/1998	Hunter		
	5,729,242 A	3/1998	Margerum et al.		
	5,748,828 A	5/1998	Steiner et al.		
	5,784,181 A	7/1998	Loiseaux et al.		
	5,809,215 A	9/1998	Heydinger et al.		
	5,815,303 A	9/1998	Berlin		
	5,889,567 A	3/1999	Swanson et al.		
	5,892,325 A	4/1999	Gleckman		
	5,926,239 A	7/1999	Kumar et al.		
	5,959,777 A	9/1999	Whitehead		
	5,978,142 A	11/1999	Blackham et al.		
	5,986,628 A	11/1999	Tuenge et al.		
	6,043,591 A	3/2000	Gleckman		

(56)

References Cited

U.S. PATENT DOCUMENTS

2002/0050958 A1 5/2002 Matthies et al.
 2002/0057238 A1 5/2002 Nitta et al.
 2002/0057253 A1 5/2002 Lim et al.
 2002/0135553 A1 9/2002 Nagai et al.
 2002/0159002 A1 10/2002 Chang
 2002/0163606 A1 11/2002 Kitai et al.
 2002/0171617 A1 11/2002 Fuller
 2003/0048393 A1 3/2003 Sayag
 2003/0085857 A1 5/2003 Ramanujan
 2003/0090455 A1 5/2003 Daly
 2003/0137501 A1 7/2003 Richards
 2003/0151569 A1 8/2003 Lee et al.
 2003/0206245 A1 11/2003 Lin et al.
 2004/0012551 A1 1/2004 Ishii
 2004/0057017 A1 3/2004 Childers et al.
 2004/0218388 A1 11/2004 Suzuki
 2005/0083295 A1 4/2005 Daly
 2005/0083296 A1 4/2005 Daly
 2005/0162737 A1 7/2005 Whitehead et al.
 2005/0248554 A1 11/2005 Feng et al.
 2005/0285841 A1 12/2005 Lin
 2006/0028156 A1 2/2006 Jungwirth
 2006/0092183 A1 5/2006 Malmberg
 2006/0125745 A1 6/2006 Evanicky
 2006/0139954 A1 6/2006 Kobori et al.
 2006/0227085 A1 10/2006 Boldt, Jr. et al.
 2006/0232969 A1 10/2006 Bogner et al.
 2007/0024576 A1 2/2007 Hassan
 2007/0035706 A1 2/2007 Margulis
 2007/0097321 A1 5/2007 Whitehead et al.
 2007/0126992 A1 6/2007 Penn
 2007/0132956 A1 6/2007 Whitehead et al.
 2007/0146257 A1 6/2007 Whitehead et al.
 2007/0247833 A1 10/2007 Lee et al.
 2007/0268211 A1 11/2007 Whitehead et al.
 2007/0268224 A1 11/2007 Whitehead et al.
 2007/0268577 A1 11/2007 Whitehead et al.
 2008/0018985 A1 1/2008 Whitehead et al.
 2008/0030449 A1 2/2008 Lee et al.
 2008/0043034 A1 2/2008 Whitehead et al.
 2008/0043303 A1 2/2008 Whitehead et al.
 2008/0074060 A1 3/2008 Ye et al.
 2008/0150878 A1 6/2008 Kang
 2008/0150879 A1 6/2008 Kang
 2012/0120131 A1 5/2012 Whitehead et al.

FOREIGN PATENT DOCUMENTS

EP 1003064 A1 5/2000
 EP 1098291 A2 5/2001
 EP 1136874 A1 9/2001
 EP 1202244 A1 5/2002
 EP 1431653 A2 6/2004
 EP 1521235 A2 4/2005
 FR 2702299 9/1994
 JP S60-54120 A2 4/1985
 JP S60-54174 A2 4/1985
 JP 62-234185 A 10/1987
 JP S62-234133 A2 10/1987
 JP H2-162389 A2 6/1990
 JP H3-71111 A1 3/1991
 JP H3-198026 A1 8/1991
 JP H4-204591 A2 7/1992
 JP H05-45605 A 2/1993

JP H05-196959 A 8/1993
 JP H06-11679 A 1/1994
 JP H07-104310 A 4/1995
 JP H7-121120 A2 5/1995
 JP H08-76077 A 3/1996
 JP H8-334742 A1 12/1996
 JP H09-116840 A 5/1997
 JP 09-189893 A 7/1997
 JP H10-269802 A2 10/1998
 JP H10-282470 A 10/1998
 JP H11-52412 A 2/1999
 JP H11-064820 A2 3/1999
 JP H11-194336 A 7/1999
 JP H11-237608 A 8/1999
 JP H11-271889 A 10/1999
 JP 2000-35576 A1 2/2000
 JP 2000-214827 A2 8/2000
 JP 2000-275595 A 10/2000
 JP 2001-100689 A 4/2001
 JP 2001-142409 A 5/2001
 JP 2002-91385 A1 3/2002
 JP 2002-99250 A2 4/2002
 JP 2002-140038 5/2002
 JP 2005-520188 7/2005
 JP 2005-309338 A 11/2005
 JP 2009-053370 3/2009
 JP 2011-203323 A 10/2011
 JP 2012-008199 A 1/2012
 WO 91/15843 A2 10/1991
 WO 9406249 A1 3/1994
 WO 96/33483 A1 10/1996
 WO 99/19767 A1 4/1999
 WO 00/23831 A1 4/2000
 WO 00/40018 A1 7/2000
 WO 00/75720 A2 12/2000
 WO 0119092 A1 3/2001
 WO 01/69584 A1 9/2001
 WO 01/69941 A2 9/2001
 WO 02/03687 A2 1/2002
 WO 02/069030 A2 9/2002
 WO 02/079862 A2 10/2002
 WO 03/077013 A2 9/2003
 WO 2004031844 A1 4/2004
 WO 2005101309 A1 10/2005
 WO 2006010244 A1 2/2006
 WO 2006115852 A2 11/2006

OTHER PUBLICATIONS

International Search Report and Written Opinion for PCT/US07/02788 filed Jan. 31, 2007.
 Suzuki, Y., "Liquid Crystal Applications", Television Technology Institute Reports, 1983.
 Ohara, A., "Backlight for Liquid Crystal Displays", J. Illum. Institute of Japan, 1989, vol. 73(12).
 Mitsuhashi, Y. "Regarding LED Backlight Systems for LCDs", Television Technology Institute Reports, 1986.
 Endo, N., "Transmissive Type Liquid Crystal Display Device", Toshiba Technology Publication Collection, 1996.
 Funamoto, T. et al., "Technology for LCD Televisions with High Image Quality", Matsushita Technical Journal, 2000, vol. 46(3).
 Ward, Greg, "A Wide Field, High Dynamic Range, Stereographic Viewer", 2003.
 Ward, Greg, "A Wide-Field Stereoscopic High Dynamic Range Viewer", Mar. 30, 2001.
<http://www.son-video.com/Lexique/LexiqueL.html>, published Jan. 31, 2001.




FIGURE 1




FIGURE 1A




FIGURE 2




FIGURE 3




FIGURE 4




FIGURE 5




FIGURE 5A




FIGURE 6





FIGURE 6A




FIGURE 6B




FIGURE 7





FIGURE 7A






FIGURE 8A




FIGURE 8B




FIGURE 8C

FIGURE 8E




FIGURE 8D




FIGURE 8F




FIGURE 8G




FIGURE 9A




FIGURE 9B




FIGURE 9C




FIGURE 10




FIGURE 11




FIGURE 11B




FIGURE 11A




FIGURE 11C




FIGURE 11D




FIGURE 11E

RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 13/774,563 filed 22 Feb. 2013, which is a continuation of U.S. patent application Ser. No. 13/358,311 filed 25 Jan. 2012 now U.S. Pat. No. 8,446,351, which is a continuation of U.S. patent application Ser. No. 11/831,827 filed 31 Jul. 2007 now U.S. Pat. No. 8,125,425, which is a continuation of U.S. patent application Ser. No. 10/507,460 filed 10 Sep. 2004 now U.S. Pat. No. 7,403,332, which is the U.S. National Stage of International Application No. PCT/CA03/00350 filed 13 Mar. 2003, which claims the benefit of the filing date of U.S. provisional patent application No. 60/363,563 filed 13 Mar. 2002 and entitled HIGH DYNAMIC RANGE DISPLAY DEVICES.

The claimed invention was made as a result of activities undertaken within the scope of a joint research agreement as defined under 35 U.S.C. 103(c) between the National Sciences and Engineering Research Council of Canada, Lorne Whitehead of the University of British Columbia, Wolfgang Stuerzlinger and Hugh Wilson of York University, and Avi Chaudhuri of McGill University.

TECHNICAL FIELD

The invention relates to displays for displaying digital images.

BACKGROUND

Dynamic range is the ratio of intensity of the highest luminance parts of a scene and the lowest luminance parts of a scene. For example, the image projected by a video projection system may have a maximum dynamic range of 300:1.

The human visual system is capable of recognizing features in scenes which have very high dynamic ranges. For example, a person can look into the shadows of an unlit garage on a brightly sunlit day and see details of objects in the shadows even though the luminance in adjacent sunlit areas may be thousands of times greater than the luminance in the shadow parts of the scene. To create a realistic rendering of such a scene can require a display having a dynamic range in excess of 1000:1. The term "high dynamic range" means dynamic ranges of 800:1 or more.

Modern digital imaging systems are capable of capturing and recording digital representations of scenes in which the dynamic range of the scene is preserved. Computer imaging systems are capable of synthesizing images having high dynamic ranges. However, current display technology is not capable of rendering images in a manner which faithfully reproduces high dynamic ranges.

Blackham et al., U.S. Pat. No. 5,978,142 discloses a system for projecting an image onto a screen. The system has first and second light modulators which both modulate light from a light source. Each of the light modulators modulates light from the source at the pixel level. Light modulated by both of the light modulators is projected onto the screen.

Gibbon et al., PCT application No. PCT/US01/21367 discloses a projection system which includes a pre modulator. The pre modulator controls the amount of light incident on a deformable mirror display device. A separate pre-modulator may be used to darken a selected area (e.g. a quadrant).

There exists a need for cost effective displays capable of reproducing a wide range of light intensities in displayed images.

This invention provides displays for displaying images. One embodiment of the invention provides a display comprising: a light source comprising an array of light-emitting elements. Each of the elements has a controllable light output; and, a spatial light modulator comprising a plurality of controllable elements located to modulate light from the light source. A diffuser directs light from the light source which has been modulated by the spatial light modulator to a viewing area.

Another aspect of the invention provides a display comprising: a spatial light modulator comprising an array of controllable elements, each of the controllable elements providing a controllable light transmission; a light source comprising an array of solid state light-emitting elements each located to illuminate a plurality of corresponding controllable elements of the spatial light modulator and each having a controllable light output; and, a diffuser. Brightness of a point on the diffuser may be controlled by controlling the light output of one of the light-emitting elements corresponding to the point and controlling the light transmission of one of the controllable elements corresponding to the point.

A further aspect of the invention provides a display comprising: light provision means for providing light spatially modulated at a first spatial resolution; spatial modulation means for further spatially modulating the light at a second resolution different from the first resolution; and, means for controlling the first and second spatial modulation means to display an image defined by image data.

The invention also provides a method for displaying an image. The method comprises controlling an array of individually-controllable light-emitting elements to have brightnesses determined by a first set of image data; illuminating a face of a spatial light modulator with light from the array of light-emitting elements, the spatial light modulator comprising an array of elements, each of the elements having a controllable transmissivity; and, controlling the transmissivity of the elements of the spatial light modulator with a second set of image data.

Further aspects of the invention and features of specific embodiments of the invention are described below.

BRIEF DESCRIPTION OF THE DRAWINGS

In drawings which illustrate non-limiting embodiments of the invention,

FIG. 1 is a schematic illustration of a display according to one embodiment of the invention;

FIG. 1A is a schematic illustration of a specific implementation of the display of FIG. 1;

FIG. 2 is a schematic illustration of a display according to an alternative embodiment of the invention comprising four spatial light modulators;

FIG. 3 is a schematic illustration of a rear-projection-type display according to a further embodiment of the invention;

FIG. 4 is a schematic illustration of a front-projection-type display according to a still further embodiment of the invention;

FIG. 5 is a drawing illustrating a possible relationship between pixels in a higher-resolution spatial light modulator and pixels in a lower-resolution spatial light modulator in a display according to the invention;

FIG. 5A illustrates an effect of providing one light modulator which has lower resolution than another light modulator;

FIG. 6 is a schematic illustration of a front-projection-type color display having an alternative projector construction;

FIGS. 6A and 6B are expanded cross-sectional views of portions of the front-projection screen of the color display of FIG. 6;

FIG. 7 is a graph illustrating how light imaged onto a higher-resolution light modulator from pixels of a lower-resolution light modulator can overlap to yield a smooth variation in light intensity with position;

FIG. 7A is a graph illustrating how the variation in light intensity with position for the image of a pixel of a light modulator can be represented as the convolution of a square profile and a spread function;

FIG. 8 is a schematic cross-section of a display according to an alternative embodiment of the invention and FIG. 8A is a schematic front view thereof;

FIG. 8B is a schematic cross section of a display in which a spatial light modulator is spaced in front of an array of light sources;

FIG. 8C is a schematic view of a display having a grid interposed between an array of light sources and a spatial light modulator;

FIG. 8D is an isometric view of a hexagonal grid;

FIG. 8E is a schematic representation of one channel through a grid illustrating reflected and non-reflected light components impinging on a spatial light modulator;

FIG. 8F is a graph showing how reflected and non-reflected light components can sum to provide improved uniformity of illumination;

FIG. 8G is a schematic representation of a display wherein internally reflecting members which form a grid are formed integrally with the material encapsulating LEDs;

FIGS. 9A and 9B illustrate two possible configurations for an array of light emitting elements which could be used in the embodiment of FIG. 8;

FIG. 9C illustrates the use of light barriers to provide increased sharpness;

FIG. 10 is a schematic illustration of a projection-type display according to an alternative embodiment of the invention;

FIG. 11 is a block diagram of a calibration mechanism;

FIG. 11A is a depiction of an LED illustrating paths by which stray light exits the LED; and,

FIGS. 11B, 11C, 11D and 11E are schematic diagrams of alternative calibration mechanisms.

DESCRIPTION

Throughout the following description, specific details are set forth in order to provide a more thorough understanding of the invention. However, the invention may be practiced without these particulars. In other instances, well known elements have not been shown or described in detail to avoid unnecessarily obscuring the invention. Accordingly, the specification and drawings are to be regarded in an illustrative, rather than a restrictive, sense.

This invention provides displays capable of rendering images with high dynamic ranges. Displays according to the invention comprise two light modulating stages. Light passes through the stages in series to provide an image which has an increased dynamic range.

FIG. 1 illustrates schematically a display 10 according to a simple embodiment of the invention. The sizes of elements and distances between them in FIG. 1 are not to scale. Display 10 comprises a light source 12. Light source 12 may, for example, comprise a projection lamp such as an incandescent lamp or an arc lamp, a laser, or another suitable source of light. Light source 12 may comprise an optical system com-

prising one or more mirrors, lenses or other optical elements which cooperate to deliver light to the rest of display 10.

In the illustrated embodiment, light from light source 12 is directed toward a first light modulator 16. Light source 12 preferably provides substantially uniform illumination of first light modulator 16. Light modulator 16 comprises an array of individually addressable elements. Light modulator 16 may comprise, for example, a LCD (liquid crystal display), which is an example of a transmission-type light modulator or a DMD (deformable mirror device), which is an example of a reflection-type light modulator. Display driver circuitry (not shown in FIG. 1) controls the elements of light modulator 16 according to data which defines an image being displayed.

Light which has been modulated by first light modulator 16 is imaged onto a rear-projection screen 23 by a suitable optical system 17. Light from a small area of first light modulator 16 is directed by optical system 17 to a corresponding area on rear-projection screen 23. In the illustrated embodiment, optical system 17 comprises a lens having a focal length f . In general, the optical system 17 which images light modulated by first light modulator 16 onto rear-projection screen 23 may comprise one or more mirrors, lenses or other optical elements. Such an optical system has the function of imaging light modulated by the first light modulator onto a second light modulator. Optical system 17 may be termed an imaging means.

In the illustrated embodiment, rear-projection screen 23 comprises a second light modulator 20 and a collimator 18. A main function of collimator 18 is to cause light which passes through rear-projection screen 23 to be directed preferentially toward a viewing area. Collimator 18 may comprise a Fresnel lens, a holographic lens, or, in the alternative, another arrangement of one or more lenses and/or other optical elements which operate to guide light in the direction of a viewing area.

In the illustrated embodiment, collimator 18 causes light to travel through the elements of second light modulator 20 in a direction which is generally normal to screen 23. As light incident from collimator 18 travels through second light modulator 20 it is further modulated. The light then passes to a diffuser 22 which scatters the outgoing light through a range of directions so that a viewer located on an opposite side of diffuser 22 from first light modulator 16 can see light originating from the whole area of screen 23. In general, diffuser 22 may scatter light to a different angular extent in the horizontal and vertical planes. Diffuser 22 should be selected so that light modulated by second light modulator 20 is scattered through a range of angles such that the maximum scatter angle is at least equal to the angle subtended by screen 23 when viewed from a desired viewing location.

Rear-projection screen 23 may differ in area from first light modulator 16. For example, rear-projection screen 23 may be larger in area than first light modulator 16. Where this is the case, optical system 17 expands the beam of light modulated by first light modulator 16 to illuminate a corresponding area on rear-projection screen 23 which is larger than first light modulator 16.

Second light modulator 20 may be of the same type as first light modulator 16 or a different type. Where first and second light modulators 16 and 20 are both of types that polarize light, second light modulator 20 should, as much as is practical, be oriented so that its plane of polarization matches that of the light incident on it from first light modulator 16.

Display 10 may be a color display. This may be achieved in various ways including:

making one of first light modulator 16 and second light modulator 20 a color light modulator;

5

providing a plurality of different first light modulators **16** operating in parallel on different colors; and, providing a mechanism for rapidly introducing different color filters into the light path ahead of second light modulator **20**.

As an example of the first approach above, second light modulator **20** may comprise an LCD panel having a plurality of pixels each comprising a number of colored sub-pixels. For example, each pixel may comprise three sub-pixels, one associated with a red filter, one associated with a green filter and one associated with a blue filter. The filters may be integral with the LCD panel.

As shown in FIG. 1A, light source **12**, first light modulator **16** and optical system **17** may all be parts of a digital video projector **37** located to project an image defined by a signal **38A** from a controller **39** onto the back side of rear-projection screen **23**. The elements of second light modulator **20** are controlled by a signal **38B** from controller **39** to provide an image to a viewer which has a high dynamic range.

Controller **39** may comprise any suitable data processor. Controller **39** may comprise one or more microprocessors running suitable control software together with interfaces which permit controller **39** to control the operation of a display according to the invention. The general construction of such controllers and general techniques for programming such controllers to provide desired functions are well known to those skilled in the art and will not be described in detail herein.

As shown in FIG. 2, a display **10A** according to the invention may comprise one or more additional light modulation stages **24**. Each additional light modulation stage **24** comprises a collimator **25**, a light modulator **26** and an optical system **27** which focuses light from light modulator **26** onto either the next additional light modulation stage **24** or on collimator **18**. In device **10A** of FIG. 2 there are two additional light modulation stages **24**. Devices according to this embodiment of the invention may have one or more additional light modulation stages **24**.

The luminance of any point on output diffuser **22** can be adjusted by controlling the amount of light passed on by corresponding elements of light modulators **16**, **20** and **26**. This control may be provided by a suitable control system (not shown in FIG. 2) connected to drive each of light modulators **16**, **20** and **26**.

As noted above, light modulators **16**, **20** and **26** may all be of the same type or may be of two or more different types. FIG. 3 illustrates a display **10B** according to an alternative embodiment of the invention which includes a first light modulator **16A** which comprises a deformable mirror device. A deformable mirror device is a "binary" device in the sense that each pixel may be either "on" or "off". Different apparent brightness levels may be produced by turning a pixel on and off rapidly. Such devices are described, for example, in U.S. Pat. No. 4,441,791 and, U.S. Pat. No. 4,954,789 and are commonly used in digital video projectors. Light source **12** and first light modulator **16** (or **16A**) may be the light source and modulator from a commercial digital video projector, for example.

FIG. 4 illustrates a front-projection-type display **10C** according to the invention. Display **10C** comprises a screen **34**. A projector **37** projects an image **38** onto screen **34**. Projector **37** comprises a suitable light source **12**, a first light modulator **16** and an optical system **17** suitable for projecting an image defined by first light modulator **16** onto screen **34**. Projector **37** may comprise a commercially available display projector. Screen **34** incorporates a second light modulator **36**. Second light modulator **36** comprises a number of address-

6

sable elements which can be individually controlled to affect the luminance of a corresponding area of screen **34**.

Light modulator **36** may have any of various constructions. For example, light modulator **36** may comprise an array of LCD elements each having a controllable transmissivity located in front of a reflective backing. Light projected by projector **37** passes through each LCD element and is reflected back through the LCD element by the reflective backing. The luminance at any point on screen **34** is determined by the intensity of light received at that point by projector **37** and the degree to which light modulator **36** (e.g. the LCD element at that point) absorbs light being transmitted through it.

Light modulator **36** could also comprise an array of elements having variable retro-reflection properties. The elements may be prismatic. Such elements are described, for example, in Whitehead, U.S. Pat. No. 5,959,777 entitled Passive High Efficiency Variable Reflectivity Image Display Device and, Whitehead et al., U.S. Pat. No. 6,215,920 entitled Electrophoretic, High Index and Phase Transition Control of Total Internal Reflection in High Efficiency Variable Reflectivity Image Displays.

Light modulator **36** could also comprise an array of electrophoretic display elements as described, for example, in Albert et al., U.S. Pat. No. 6,172,798 entitled Shutter Mode Microencapsulated Electrophoretic Display; Comiskey et al., U.S. Pat. No. 6,120,839 entitled Electro-osmotic Displays and Materials for Making the Same; Jacobson, U.S. Pat. No. 6,120,588 entitled: Electronically Addressable Microencapsulated Ink and Display; Jacobson et al., U.S. Pat. No. 6,323,989 entitled Electrophoretic Displays Using Nanoparticles; Albert, U.S. Pat. No. 6,300,932 entitled Electrophoretic Displays with Luminescent Particles and Materials for Making the Same or, Comiskey et al., U.S. Pat. No. 6,327,072 entitled Microcell Electrophoretic Displays.

As shown in FIGS. 6A and 6B, screen **34** preferably comprises a lens element **40** which functions to direct light preferentially toward the eyes of viewers. In the illustrated embodiment, lens element **40** comprises a Fresnel lens having a focal point substantially coincident with the apex of the cone of light originating from projector **37**. Lens element **40** could comprise another kind of lens such as a holographic lens. Lens element **40** incorporates scattering centers **45** which provide a desired degree of diffusion in the light reflected from screen **34**. In the illustrated embodiment, second light modulator **36** comprises a reflective LCD panel having a large number of pixels **42** backed by a reflective layer **43** and mounted on a backing **47**.

Where light modulator **36** comprises an array of elements having variable retro-reflection properties, the elements themselves could be designed to direct retro-reflected light preferentially in a direction of a viewing area in front of screen **34**. Reflective layer **43** may be patterned to scatter light to either augment the effect of scattering centers **45** or replace scattering centers **45**.

As shown in FIG. 4, a controller **39** provides data defining image **38** to each of first light modulator **16** and second light modulator **36**. Controller **39** could comprise, for example, a computer equipped with a suitable display adapter. The luminance of any point on screen **34** is determined by the combined effect of the pixels in first light modulator **16** and second light modulator **36** which correspond to that point. There is minimum luminance at points for which corresponding pixels of the first and second light modulators are set to their "darkest" states. There is maximum luminance at points for which corresponding pixels of the first and second light modulators are set to their "brightest" states. Other points

have intermediate luminance values. The maximum luminance value might be, for example, on the order of 10^5 cd/m². The minimum luminance value might be, for example on the order of 10^{-2} cd/m².

The cost of a light modulator and its associated control circuitry tends to increase with the number of addressable elements in the light modulator. In some embodiments of the invention one of the light modulators has a spatial resolution significantly higher than that of one or more other ones of the light modulators. When one or more of the light modulators are lower-resolution devices the cost of a display according to such embodiments of the invention may be reduced. In color displays comprising two or more light modulators, one of which is a color light modulator (a combination of a plurality of monochrome light modulators may constitute a color light modulator as shown, for example, in FIG. 6) and one of which is a higher-resolution light modulator, the higher-resolution light modulator should also be the color light modulator. In some embodiments the higher-resolution light modulator is imaged onto the lower-resolution light modulator. In other embodiments the lower-resolution light modulator is imaged onto the higher-resolution light modulator.

FIG. 5 illustrates one possible configuration of pixels in a display 10 as shown in FIG. 1. Nine pixels 42 of a second light modulator 20 correspond to each pixel 44 of a first light modulator 16. The number of pixels 42 of second light modulator 20 which correspond to each pixel 44 of first light modulator 16 may be varied as a matter of design choice. Pixels 44 of the higher-resolution one of first and second light modulators 16 and 20 (or 36) should be small enough to provide a desired overall resolution. In general there is a trade off between increasing resolution and increasing cost. In a typical display the higher-resolution light modulator will provide an array of pixels having at least a few hundred pixels in each direction and more typically over 1000 pixels in each direction.

The size of pixels 42 of the lower-resolution one of the first and second light modulators determines the scale over which one can reliably go from maximum intensity to minimum intensity. Consider, for example, FIG. 5A which depicts a situation where one wishes to display an image of a small maximum-luminance spot on a large minimum-luminance background. To obtain maximum luminance in a spot 47, those pixels of each of the first and second light modulators which correspond to spot 47 should be set to their maximum-luminance values. Where the pixels of one light modulator are lower in resolution than pixels of the other light modulator then some pixels of the lower-resolution light modulator will straddle the boundary of spot 47. This is the case, for example, in FIG. 5A.

Outside of spot 47 there are two regions. In region 48 it is not possible to set the luminance to its minimum value because in that region the lower-resolution light modulator is set to its highest luminance value. In region 49 both of the light modulators can be set to their lowest-luminance values. If, for example, each of the first and second light modulators has a luminance range of 1 to 100 units, then region 47 might have a luminance of $100 \times 100 = 10,000$ units, region 48 would have a luminance of $100 \times 1 = 100$ units and region 49 would have a luminance of $1 \times 1 = 1$ units.

As a result of having one of the light modulators lower in resolution than the other, each pixel of the lower-resolution light modulator corresponds to more than one pixel in the higher-resolution light modulator. It is not possible for points corresponding to any one pixel of the lower-resolution light modulator and different pixels of the higher-resolution light modulator to have luminance values at extremes of the

device's dynamic range. The maximum difference in luminance between such points is determined by the dynamic range provided by the higher-resolution light modulator.

It is generally not a problem that a display is not capable of causing closely-spaced points to differ in luminance from one another by the full dynamic range of the display. The human eye has enough intrinsic scatter that it is incapable of appreciating large changes in luminance which occur over very short distances in any event.

In a display according to the invention which includes both a lower-resolution spatial light modulator and a higher-resolution spatial light modulator, controller 39 may determine a value for each pixel of the lower-resolution spatial light modulator and adjust the signals which control the higher-resolution spatial light modulator to reduce artifacts which result from the fact that each pixel of the lower-resolution spatial light modulator is common to a plurality of pixels of the higher-resolution spatial light modulator. This may be done in any of a wide number of ways.

To take but one example, consider the case where each pixel of the lower-resolution spatial light modulator corresponds to a plurality of pixels of the higher-resolution spatial light modulator. Image data specifying a desired image is supplied to the controller. The image data indicates a desired luminance for an image area corresponding to each of the pixels of the higher-resolution spatial light modulator. The controller may set the pixels of the lower-resolution light modulator to provide an approximation of the desired image. This could be accomplished, for example, by determining an average or weighted average of the desired luminance values for the image areas corresponding to each pixel of the lower-resolution display.

The controller may then set the pixels of the higher-resolution display to cause the resulting image to approach the desired image. This could be done, for example, by dividing the desired luminance values by the intensity of light incident from the lower-resolution light modulator on the corresponding pixels of the higher-resolution light modulator. The intensity of light incident from the lower-resolution light modulator on a pixel of the higher-resolution light modulator can be computed from the known way that light from each pixel of the lower resolution spatial light modulator is distributed on the higher resolution spatial light modulator. The contributions from one or more of the pixels of the lower resolution spatial light modulator can be summed to determine the intensity with which any pixel of the higher resolution spatial light modulator will be illuminated for the way in which the pixels of the lower resolution spatial light modulator are set.

If the low-resolution pixels are too large then a viewer may be able to discern a halo around bright elements in an image. The low resolution pixels are preferably small enough that the appearance of bright patches on dark backgrounds or of dark spots on bright backgrounds is not unacceptably degraded. It is currently considered practical to provide in the range of about 8 to about 144, more preferably about 9 to 36, pixels on the higher-resolution light modulator for each pixel of the lower-resolution light modulator.

The sizes of steps in which each of pixels 42 and 44 can adjust the luminance of point(s) on the image are not necessarily equal. The pixels of the lower-resolution light modulator may adjust light intensity in coarser steps than the pixels of the higher-resolution light modulator. For example, the lower-resolution light modulator may permit adjustment of light intensity for each pixel over an intensity range of 1 to 512 units in 8 steps while the higher-resolution light modulator may permit adjustment of the light intensity for each pixel over a similar range in 512 steps. While pixels 42 and 44

are both illustrated as being square in FIG. 5, this is not necessary. Pixels 42 and/or 44 could be other shapes, such as rectangular, triangular, hexagonal, round, or oval.

The pixels of the lower-resolution light modulator preferably emit light which is somewhat diffuse so that the light intensity varies reasonably smoothly as one traverses pixels of the lower-resolution light modulator. This is the case where the light from each of the pixels of the lower-resolution light modulator spreads into adjacent pixels, as shown in FIG. 7. As shown in FIG. 7A, the intensity profile of a pixel in the lower-resolution light modulator can often be approximated by gaussian spread function convolved with a rectangular profile having a width d_1 equal to the active width of the pixel. The spread function preferably has a full width at half maximum in the range of $0.3 \times d_2$ to $3 \times d_2$, where d_2 is the center-to-center inter-pixel spacing, to yield the desired smoothly varying light intensity. Typically d_1 is nearly equal to d_2 .

In the embodiment of FIG. 5, each pixel 42 comprises three sub pixels 43R, 43G and 43B (for clarity FIG. 5 omits sub pixels for some pixels 42). Sub-pixels 43R, 43G and 43B are independently addressable. They are respectively associated with red, green and blue color filters which are integrated into second light modulator 20. Various constructions of LCD panels which include a number of colored sub-pixels and are suitable for use in this invention are known in the art.

For front projection-type displays (for example the display 10C of FIG. 4), it is typically most practical for first light modulator 16 to comprise a high-resolution light modulator which provides color information and for light modulator 36 to comprise a monochrome light modulator. Light modulator 36 preferably has reasonably small addressable elements so that the boundaries of its elements do not form a visually distracting pattern. For example, light modulator 36 may have the same number of addressable elements as projector 37 (although each such element will typically have significantly larger dimensions than the corresponding element in light modulator 16 of projector 37).

Projector 37 may have any suitable construction. All that is required is that projector 37 be able to project light which has been spatially modulated to provide an image onto screen 34. FIG. 6 illustrates a display system 10D according to a further alternative embodiment of the invention. System 10D comprises a screen 34 which has an integrated light modulator 36 as described above with reference to FIG. 4. System 10D comprises a projector 37A which has separate light modulators 16R, 16G and 16B for each of three colors. Light modulated by each of light modulators 16R, 16G and 16B is filtered by a corresponding one of three colored filters 47R, 47G and 47B. The modulated light is projected onto screen 34 by optical systems 17. A single light source 12 may supply light to all three light modulators 16R, 16G, and 16B, or separate light sources (not shown) may be provided.

In the embodiments described above, light from a light source is spatially modulated by a first light modulator and then imaged onto a second light modulator. The inventors have realized that the functions of the light source and first light modulator can be combined by providing a light source comprising an array of light-emitting elements which each have a controllable brightness. The light-emitting elements may be solid state devices. For example, the light-emitting elements may comprise light-emitting diodes (LEDs). Each of the LEDs may be driven by a driver circuit which allows the current flowing through the LED, and consequently the brightness of the light emitted by the LED, to be controlled. The controller may also, or in the alternative, control a duty cycle of the corresponding LED. As discussed below, the driving circuit may monitor current being delivered to each

LED or each group of LEDs and may generate an error signal if the magnitude of the current being delivered to each LED or each group of LEDs has an unexpected value. Such error signals may be used by a controller to compensate for failed LEDs.

In a preferred embodiment of the invention, the LEDs are of a type which emit white light. For example, the LEDs may comprise an array of tri-color LEDs. Tri-color LEDs which each include red, green and blue LEDs all encapsulated within a single housing are commercially available. One or more white LEDs may be used to illuminate each group of pixels of the second light modulator.

FIG. 8 shows a section through a display 60 according to an embodiment of the invention in which a rear-projection screen 53 comprising a diffusing layer 22 is illuminated by an array 50 of LEDs 52. The brightness of each LED 52 is controlled by a controller 39. Screen 53 includes a light modulator 20. The rear face of light modulator 20 is illuminated by LED array 50. FIG. 8A is a schematic front view of a portion of display 60 for a case where controllable elements (pixels) 42 of light modulator 20 correspond to each LED 52. Each of the controllable elements 42 may comprise a plurality of colored sub-pixels.

LEDs 52 may be arranged in any suitable manner in array 50. Two likely arrangements of LEDs 52 are shown in FIGS. 9A and 9B. FIG. 9A illustrates a rectangular array 50A of light sources 51. FIG. 9B illustrates a hexagonal array 50B of light sources 51. Light sources 51 may comprise LEDs 52. Where light sources 51 comprise discrete devices, a regular spacing between light sources 51 may be maintained by packing light sources 51 together as illustrated in FIG. 9A or 9B, for example.

A diffuser 22A in conjunction with the light-emitting characteristics of LEDs 52 causes the variation in intensity of light from LEDs 52 over the rear face of light modulator 20 to be smooth.

A similar effect can be obtained without a diffuser 22A by spacing light modulator 20 away from LEDs 52. Where light modulator 20 is spaced away from LEDs 52, light from each LED 52 can contribute to illuminating edges of the areas of spatial light modulator 20 corresponding to neighboring LEDs 52.

In cases where it is necessary that the display be viewable through a large range of angles, such spacing can cause a parallax problem. Where a viewer is not viewing a display head-on, as shown in FIG. 8B, the viewer may see a pixel of spatial light modulator 20 illuminated by an LED 52 which does not correspond to the pixel. For example, in FIG. 8B, area 21A corresponds to LED 52A and area 21B corresponds to LED 52B. However, due to parallax, the viewer sees pixels in area 21A as being illuminated by LED 52B.

FIG. 8C shows an alternative construction which avoids the parallax problem illustrated by FIG. 8B. In FIG. 8C, a grid 122 of reflective-walled channels 123 is disposed between array 50 and spatial light modulator 20. In a preferred embodiment, channels 123 are hexagonal in cross section and grid 122 comprises a honeycomb structure as shown in FIG. 8D. Channels 123 could also have other cross sectional shapes such as square, triangular, rectangular or the like. The walls which define channels 123 are preferably thin. Grid 122 could comprise, for example, a section of aluminum honeycomb material.

Channels 123 may be, but are not necessarily hollow. Channels 123 may be provided by columns of light-transmitting material having walls at which light is internally reflected, preferably totally internally reflected. The columns may be separated by thin air gaps or clad in one or more

materials which provide an interface at which light is internally reflected. The columns may be integral with the material in which LEDs 52 are encapsulated. FIG. 8G shows an embodiment of the invention in which columns 123A having internally reflecting walls are integrally formed with LEDs 52C. Columns 123A may have various cross sectional shapes such as hexagonal, triangular, square or the like.

Light from each LED 52 passes through a channel 123. As shown in FIG. 8E, some light from an LED passes straight through channel 123 and some light is reflected from reflective walls 124 of channel 123. The luminance at a point on spatial light modulator 20 is contributed to by both reflected and non-reflected light. The reflected component tends to be more intense around the edges of channel 123 while the non-reflected component tends to be more intense toward the center of channel 123. The result is that the uniformity with which each LED 52 illuminates the corresponding portion of spatial light modulator 20 is improved by the presence of grid 122. The increase in uniformity is illustrated in FIG. 8F.

Grid 122 is spaced slightly away from spatial light modulator 20 by a gap 57 (see FIGS. 8C and 8E) to avoid perceptible shadows cast by the walls which separate adjacent channels 123 of grid 122.

The geometry of channels 123 may be varied to achieve design goals. The width of each channel 123 largely determines the resolution with which the intensity of light falling on spatial light modulator 20 can be varied. For a given channel width and cross sectional shape, the uniformity of illumination provided by each channel 123 can be increased by making the channel 123 longer. This, however, reduces the efficiency with which light is passed to spatial light modulator 20.

A reasonable trade off between efficiency and uniformity of illumination may be achieved by providing channels 123 which have lengths L such that near the channel edges non-reflected and once-reflected light components are each approximately half of the intensity of the non-reflected component on the axis of LED 52. One way to approximately achieve this is to choose length L such that the angle \checkmark between the axis of LED 52 and the edge of channel 123 is equal to the half angle $\checkmark_{1/2}$ of the LED 52. The half angle is the angle at which the illumination provided by LED 52 has an intensity equal to one half of the intensity of illumination in a forward direction on the axis of LED 52. This condition is provided by making L satisfy the condition of equation (1), where R is the half-width of channel 123.

$$L = \frac{R}{\tan(\checkmark_{1/2})} \quad (1)$$

It is generally desirable to provide one channel 123 for each LED or other light source. In some embodiments of the invention each channel 123 has a plurality of LEDs. In one embodiment of the invention each channel 123 has three LEDs of different colors, for example, red, green and blue. In such embodiments it is important that the channel 123 be long enough that light from each of the LEDs be uniformly distributed at spatial light modulator 20 as the human eye is sensitive to variations in color.

As described above, with reference to FIGS. 7 and 7A, light modulator 20 is preferably illuminated in a manner such that the illumination of light modulator 20 by LED array 50 changes smoothly with position on light modulator 20. This can be accomplished by providing LEDs 52 in LED array 50 which emit light in patterns which overlap somewhat on light

modulator 20. The light emitted by each LED 52 may be characterized by a spread function such that the variation of the intensity of light from an LED 52 incident on light modulator 20 is the convolution of a rectangular profile and the spread function. The spread function preferably has a full width at half maximum in the range of $0.3 \times d_2$ to $3 \times d_2$, where d_2 is the center-to-center spacing on light modulator 20 between the illumination patterns of adjacent LEDs 52 on light modulator 20. A diffuser 22A (shown in dashed lines FIG. 8) may be interposed between array 50 and light modulator 20 to broaden the illumination patterns of LEDs 52 on light modulator 20.

For some applications it may be desirable to provide a display on which the level of illumination of closely spaced pixels may be greatly different. This may be achieved, at the cost of some smoothness, by confining light originating from each of the light sources of array 50 so that the illumination patterns of adjacent light sources on light modulator 20 do not overlap significantly. This may be achieved, for example, by providing light barriers 56 which limit the spread of light from each of the light sources of array 50 as shown in FIG. 9C. With light barriers 56, each light source of array 50 illuminates only corresponding pixels of light modulator 20. This may also be achieved by providing light sources 52 which project substantially non-overlapping illumination patterns onto light modulator 20. In either case, the resulting image displayed to a viewer may appear somewhat sharper than in embodiments wherein light from each light source 52 is permitted to spread sufficiently that it provides significant illumination to some pixels corresponding to adjacent light sources. In many cases, limitations of the human eye will make this increased level of sharpness unnoticeable.

Light modulator 20 may be a monochrome light modulator. In the alternative, light modulator 20 may be a high resolution color light modulator. Light modulator 20 may comprise, for example, a LCD array. Display 60 can be quite thin. For example, display 60 may be 10 centimeters or less in thickness.

FIG. 10 shows a projection-type display 70 which is similar to display 60 of FIG. 8 except that an array 50 of light sources 52 is imaged onto a light modulator 20 by a suitable optical system 17.

A controller 39 may control the elements of array 50 to provide a low-resolution version of an image to be displayed on spatial light modulator 20. Controller 39 may control the elements of spatial light modulator 20 to supply features having a high spatial resolution and to otherwise correct the image provided by array 50 as described above.

One problem with using LEDs 52 as light sources in a high resolution high quality display is that the brightness of light emitted at a specific current level can vary significantly between individual LEDs. This variation is due to manufacturing process variations. Further, the brightness of light that a LED 52 will produce tends to slowly decrease in an unpredictable manner as the LED ages. It is therefore desirable to provide a mechanism for calibrating an LED array 50 to compensate for differences in brightness between different LEDs 52 in array 50.

One calibration mechanism 78 which is illustrated schematically in FIG. 11 provides a light detector 80 which detects light emitted by each of LEDs 52. Light detector 80 may be moved into different positions for capturing light from different LEDs 52. In the alternative, a suitable optical system may be provided to direct light from LEDs 52 to light detector 80. Controller 39 receives a signal 81 from light detector 80. Signal 81 indicates the brightness of light emitted by each LED 52 in array 50 for a given current. If the bright-

13

ness of light emitted by an LED 52 differs from a desired value then controller 39 determines a correction to be applied to the current applied to each LED 52. Controller 39 subsequently applies the correction. Calibration mechanism 78 may be used for initial calibration of a display. Calibration mechanism 78 may optionally include a calibration controller 39A which performs some calibration tasks, such as determining a correction to be applied to the current applied to each LED 52, and making the resulting calibration information available to controller 39.

It is desirable to provide a calibration mechanism that does not interfere with the normal operation of a display. One way to achieve this is to detect light which is emitted by an LED in a direction other than the forward direction. FIG. 11A shows a typical LED 52. Most light emitted by LED 52 is directed in a forward direction as shown by arrow 55A. A very small fraction of the light emitted by each LED 52 is emitted sideways as indicated by arrows 55B or rearwardly as indicated by arrow 55C. Light emitted in a direction other than the forward direction may be termed "stray light". One or more light detectors 80A may be located to detect stray light from each LED 52.

A calibration mechanism 90 according to one embodiment of the invention is shown in FIG. 11B. In calibration mechanism 90, small optical waveguides 82 carry stray light from LEDs 52 to a light detector 80. Only a small fraction of the light emitted by each LED 52 is captured by waveguides 82. As long as the coupling between a waveguide 82 and the corresponding LED 52 does not change, the proportion of the light emitted by an LED 52 which is captured by waveguide 82 remains constant. One light detector 80A or a few light detectors 80A may be located at convenient locations such as at edges of array 50.

FIG. 11C shows a calibration mechanism 90A according to another embodiment of the invention. In mechanism 90A, individual optical waveguides 82 are replaced by a planar optical waveguide 82A. Power leads for LEDs 52 pass through holes 83 in waveguide 82A. One or more light detectors 80A are located at edges of optical waveguide 82A. Light emitted in the rearward direction by any of LEDs 52 is trapped within optical waveguide 82A and detected by light detector(s) 80A.

FIG. 11D shows another optical calibration mechanism 90B wherein a planar optical waveguide 82B collects light emitted by LEDs 52 in sideways directions and carries that light to one or more light detectors 80A.

FIG. 11E shows another optical calibration mechanism 90C wherein a planar optical waveguide 82C collects a small fraction of the light emitted by LEDs 52 in the forward direction and carries that light to one or more light detectors 80A. Waveguide 82C is constructed so that some light passing through it in the forward direction is trapped in waveguide 82C and carried to light detector(s) 80A. To achieve this, one surface of waveguide 82C, typically the surface facing LEDs 52 may be roughened slightly to scatter some light generally into the plane of waveguide 82C or some scattering centers may be provided in the material of waveguide 82C. In the illustrated embodiment, waveguide 82C acts as a spacer which maintains a gap 57 between a grid 122 and spatial light modulator 20. Calibration mechanism 80C has the advantage that optical waveguide 82C does not need to be penetrated by holes 83 which can interfere with the propagation of light to light detector(s) 80A.

In operation, an array 50 is first factory calibrated, for example, with a calibration mechanism 78 (FIG. 11). After, or during, factory calibration LEDs 52 are turned on one at a time with current at a calibration level. Light detector(s) 80A

14

are used to measure stray light for each LED 52. Information about the amount of stray light detected for each LED 52 may be stored as a reference value. Over the life of LED array 50, mechanism 90 can be used to monitor the brightness of each LED 52. Depending upon the application, such brightness measurements may be made at times when the display is initialized or periodically while the display is in use. Brightness measurements of one or more LEDs 52 may be made in intervals between the display of successive image frames.

If mechanism 90 detects that the brightness of an LED 52 has changed over time (typically as indicated by a decrease in the amount of stray light detected by light detector(s) 80A in comparison to the stored reference value) then controller 39 can automatically adjust the current provided to that LED 52 to compensate for its change in brightness.

A calibration mechanism 90 can also be used to detect failures of LEDs 52. Although LEDs 52 tend to be highly reliable they can fail. Calibration mechanism 90 can detect failure of an LED 52 by detecting no light from LED 52 when controller 39 is controlling LED 52 to be "ON". Certain failure modes of an LED 52 or a row of LEDs 52 may also be detected by LED driving electronics associated with controller 39. If the driving electronics detect that no current, or a current having an unexpected value, is being delivered at a time when current should be passing through one or more LEDs 50 then the driving electronics may generate an error signal detectable by controller 39.

Where controller 39 detects a failure of one or more LEDs 52, controller 39 may compensate for the failure(s) by increasing brightness of one or more neighboring LEDs 52, adjusting the elements of spatial light modulator 20 which correspond to the failed LED 52 to provide greater light transmission, or both. In fault tolerant displays according to this embodiment of the invention, after failure of an LED 52, spill over light from adjacent LEDs 52 illuminates the area corresponding to the failed LED 52 sufficiently to make the image visible in the area.

Where controller 39 is configured to increase the brightness of neighboring LEDs 52, controller 39 may determine the amount of increase based in part upon the image content of the area of spatial light modulator 20 corresponding to the failed LED. If the image content calls for the area to be bright then the brightness of neighboring LEDs may be increased more than if the image content calls for the area to be dark. The resulting image quality will be degraded but catastrophic failure will be avoided.

In some embodiments of the invention each LED 52 is dimmed or turned off during those times when the corresponding elements of spatial light modulator are being refreshed. Some spatial light modulators refresh slowly enough that the refresh can be perceived by a viewer. This causes an undesirable effect called "motion blur".

With proper timing, at those times when each row of spatial light modulator 20 is being refreshed, corresponding LEDs 52 can be off or dimmed. At other times the corresponding LEDs 52 can be overdriven sufficiently that a viewer perceives a desired brightness. The viewer's eye cannot perceive rapid flickering of LEDs 52. Instead, the viewer perceives an average brightness. It is typically desirable to multiplex the operation of LEDs 52. Where LEDs are operated in a multiplexed manner, correcting for motion blur can be performed by synchronizing the multiplexing of LEDs 52 with the refreshing of spatial light modulator 52.

As will be apparent to those skilled in the art in the light of the foregoing disclosure, many alterations and modifications are possible in the practice of this invention without departing from the spirit or scope thereof. For example:

15

diffuser **22** and collimator **18** could be combined with one another;

diffuser **22** and collimator **18** could be reversed in order; multiple cooperating elements could be provided to perform light diffusion and/or collimation;

the function of diffuser **22** could be provided by another element which both diffuses light and performs some other function. In such cases, the other element may be said to comprise a diffuser and an apparatus comprising such an element comprises a diffuser;

the order in screen **23** of second light modulator **20** collimator **18** and diffuser **22** could be varied;

the signal **38A** driving first light modulator **16** may comprise the same data driving second light modulator **20** or may comprise different data.

Instead of or in addition to providing measuring light output for fixed calibration currents, calibration mechanisms **78** and/or **90** could adjust current to a LED **52** until the LED **52** provides a desired brightness.

Accordingly, the scope of the invention includes, but is not limited to, the substance defined by the following claims.

What is claimed is:

1. A display comprising:

a first light modulation stage combining a light source and light modulation in the form of a plurality of independently-controllable pixels each arranged to emit light having an intensity that is variable, the first light-modulation stage operative to produce light modulated according to image data;

a second light-modulation stage in series with the first light-modulation stage;

an optical system comprising one or more mirrors and a diffuser in an optical path between the first and second light-modulation stages, the optical system configured to image the light modulated by the first light-modulation stage onto the second light modulation stage such that light from different pixels of the first light-modulation stage overlaps on the second light-modulation stage to provide light having a smooth variation in light intensity with position for further modulation by the second light-modulation stage;

a controller connected to control the pixels of the first light-modulation stage and controllable-elements of the second light-modulation stage to supply image features having a high spatial resolution.

2. A display according to claim **1** wherein the display is 10 centimeters or less in thickness.

3. A display according to claim **1** comprising a light guide arranged to capture light from the pixels of the first light-modulation stage.

4. A display according to claim **1** wherein the first light modulation stage comprises a pass-through modulator.

5. A display according to claim **4** wherein the first light modulation stage comprises an LCD panel.

6. A display according to claim **1** wherein the first light modulation stage comprises a reflective modulator.

16

7. A display according to claim **1** wherein the first light modulation stage comprises a DMD.

8. A display according to claim **1** wherein the first light modulation stage comprises a plurality of separate light sources.

9. A display according to claim **1** wherein the second light modulation stage comprises a retroreflective modulator.

10. A display according to claim **1** wherein the second light modulation stage comprises a color light modulator.

11. A display according to claim **10** wherein the second light modulation stage comprises an LCD panel.

12. A display according to claim **1** wherein the controller is configured to estimate a light intensity at a controllable element of the second light-modulation stage by adding estimates of the light from a plurality of pixels of the first light-modulation stage that overlap at the controllable element.

13. A display according to claim **12** wherein the controller is configured to control modulation performed by the controllable element in response to the estimated light intensity at the controllable element.

14. A display according to claim **13** wherein the controller is configured to set the controllable element to transmit light in proportion to desired luminance value for the controllable element as specified by the image data divided by the estimated light intensity at the controllable element.

15. A display according to claim **1** wherein the first and second light-modulation stages adjust luminance in steps that are not equal.

16. A display according to claim **1** wherein the second light-modulation stage has a higher resolution than the first light modulation stage.

17. A display according to claim **16** wherein the controller is configured to determine the intensity with which any pixel of the second light modulation stage will be illuminated for the way in which the pixels of the first light modulation stage are set by summing contributions from the pixels of the first light-modulation stage.

18. A display according to claim **1** wherein the light emitted by each of the pixels of the first light modulation stage is distributed non-uniformly on the second light-modulation stage.

19. A display according to claim **18** wherein the light emitted by each of the pixels of the first light modulation stage has a peaked distribution having an intensity that diminishes with distance away from a corresponding point on the second light-modulation stage.

20. A display according to claim **19** wherein different ones of the pixels of the first light-modulation stage have different corresponding points on the second light-modulation stage that are spaced apart from one another.

21. A display according to claim **19** wherein the light from a pixel of the first light-modulation stage illuminates more than 9 of the controllable elements of the second light-modulation stage.

* * * * *