

(19) **DANMARK**



Patent- og
Varemærkestyrelsen

(12)

Oversættelse af europæisk patentskrift

(10) **DK/EP 4093035 T3**

- (51) Int.Cl.: **H 04 N 19/70 (2014.01)** **H 04 N 5/202 (2023.01)** **H 04 N 19/85 (2014.01)**
H 04 N 19/98 (2014.01) **H 04 N 21/2343 (2011.01)** **H 04 N 21/236 (2011.01)**
H 04 N 21/434 (2011.01) **H 04 N 21/4402 (2011.01)**
- (45) Oversættelsen bekendtgjort den: **2024-01-29**
- (80) Dato for Den Europæiske Patentmyndigheds bekendtgørelse om meddelelse af patentet: **2023-11-15**
- (86) Europæisk ansøgning nr.: **22184370.9**
- (86) Europæisk indleveringsdag: **2015-11-27**
- (87) Den europæiske ansøgnings publiceringsdag: **2022-11-23**
- (30) Prioritet: **2014-12-03 US 201462087035 P** **2015-11-09 JP 2015219859**
- (62) Stamansøgningsnr: **20164484.6**
- (84) Designerede stater: **AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR**
- (73) Patenthaver: **Panasonic Intellectual Property Management Co., Ltd., 1-61, Shiromi 2-chome, Chuo-ku, Osaka-shi, Osaka 540-6207, Japan**
- (72) Opfinder: **DRUGEON, Virginie, , 63225 Langen, Tyskland**
NISHI, Takahiro, , Osaka 540-6207, Japan
TOMA, Tadamasu, , Osaka 540-6207, Japan
- (74) Fuldmægtig i Danmark: **Dennemeyer & Associates S.A, P.O. Box 700425, DE-81304 Munich, Tyskland**
- (54) Benævnelse: **DATAGENERERINGSSENHED**
- (56) Fremdragne publikationer:
WO-A1-2014/178286
RUSANOVSKYY D ET AL: "Report on CE2.1.3 test: Single-layer HDR video coding based on m36256", 113. MPEG MEETING; 19-10-2015 - 23-10-2015; GENEVA; (MOTION PICTURE EXPERT GROUP OR ISO/IEC JTC1/SC29/WG11), no. m37064, 10 October 2015 (2015-10-10), XP030065432,
COTTON A ET AL: "BBC's response to CfE for HDR Video Coding (Category 3a)", 112. MPEG MEETING; 22-6-2015 - 26-6-2015; WARSAW; (MOTION PICTURE EXPERT GROUP OR ISO/IEC JTC1/SC29/WG11), no. m36249, 18 June 2015 (2015-06-18), XP030064617,
FLYNN D ET AL: "HEVC Range Extensions Draft 5", 15. JCT-VC MEETING; 23-10-2013 - 1-11-2013; GENEVA; (JOINT COLLABORATIVE TEAM ON VIDEO CODING OF ISO/IEC JTC1/SC29/WG11 AND ITU-T SG.16); URL: HTTP://WFTP3.ITU.INT/AV-ARCH/JCTVC-SITE/, no. JCTVC-O1005, 19 November 2013 (2013-11-19), XP030115459,
LE GALL (AMBARELLA) D ET AL: "High Dynamic Range with HEVC Main10", 21. JCT-VC MEETING; 19-6-2015 - 26-6-2015; WARSAW; (JOINT COLLABORATIVE TEAM ON VIDEO CODING OF ISO/IEC JTC1/SC29/WG11 AND ITU-T SG.16); URL: HTTP://WFTP3.ITU.INT/AV-ARCH/JCTVC-SITE/, no. JCTVC-U0045, 10 June 2015 (2015-06-10), XP030117462,
Whp 283 ET AL: "Research & Development White Paper Non-linear Opto-Electrical Transfer Functions for High

Fortsættes ...

Dynamic Range Television", , 30 July 2014 (2014-07-30), XP055373120, Retrieved from the Internet:
URL:<http://downloads.bbc.co.uk/rd/pubs/whp/whp-pdf-files/WHP283.pdf> [retrieved on 2017-05-16]
"Draft Requirements and Explorations for HDR and WCG Content", 110. MPEG MEETING;20-10-2014 - 24-10-2014; STRASSBOURG; (MOTION PICTURE EXPERT GROUP OR ISO/IEC JTC1/SC29/WG11), no. N15029, 27 October 2014 (2014-10-27), XP030021762,
SEGALL A ET AL: "Tone mapping SEI", 19. JVT MEETING; 31-03-2006 - 07-04-2006; GENEVA, CH; (JOINT VIDEOTEAM OF ISO/IEC JTC1/SC29/WG11 AND ITU-T SG.16), no. JVT-S087, 1 April 2006 (2006-04-01), XP030006466, ISSN: 0000-0409

DESCRIPTION

TECHNICAL FIELD

[0001] The present disclosure relates to data generation methods, data reproduction methods, data generation devices, and data reproduction devices.

BACKGROUND ART

[0002] As a technique for generating, encoding, and multiplexing video, there are the techniques disclosed in non-patent literatures (NPLs) 1 to 3. Moreover, document WO 2014/178286 A1 discloses to insert tone mapping SEI information and HDR conversion SEI information into a video stream.

Citation List

Non-Patent Literature

[0003]

NPL 1: ITU-T H.265 "High efficiency video coding", October, 2014

NPL 2: Recommendation ITU-R BT.709-5 (04/2002) "Parameter values for the HDTV standards for production and international programme exchange"

NPL 3: Recommendation ITU-R BT.2020-1 (06/2014) "Parameter values for ultra-high definition television systems for production and international programme exchange"

SUMMARY OF THE INVENTION

TECHNICAL PROBLEM

[0004] For such video data generation, new methods have always been devised, and there is a demand for backward compatibility with existing devices.

[0005] Thus, an object of the present disclosure is to provide a data generation method, a data reproduction method, a data generation device, or a data reproduction device with backward compatibility.

SOLUTIONS TO PROBLEM

[0006] This is achieved by the features of the appended claim, which provides a data generation device embodied by the data generation device 110 described below. Examples and embodiments related to data generation methods, data reproduction methods, as well as data reproduction devices in isolation from data generation devices according to the appended claim are not part of the claimed invention and are provided for illustrative purposes.

[0007] Note that these general and specific aspects may be implemented using a system, a method, an integrated circuit, a computer program, or a computer-readable recording medium such as a compact disc read-only memory (CD-ROM), or any combination of systems, methods, integrated circuits, computer programs, or recording media.

ADVANTAGEOUS EFFECT OF INVENTION

[0008] The present disclosure can provide a data generation method, a data reproduction method, a data generation device, or a data reproduction device with backward compatibility.

BRIEF DESCRIPTION OF DRAWINGS

[0009]

FIG. 1 illustrates a configuration of a system according to an embodiment.

FIG. 2 illustrates one example of an OETF according to an embodiment.

FIG. 3 illustrates a configuration example of a VUI according to an embodiment.

FIG. 4 illustrates an example of an OETF according to an embodiment.

FIG. 5 illustrates an example of extension for OETFs according to an embodiment.

FIG. 6 illustrates a configuration example of an SEI message according to an embodiment.

FIG. 7 illustrates a configuration example of an SEI message according to an embodiment.

FIG. 8 illustrates a configuration example of an SPS according to an embodiment.

FIG. 9 illustrates a configuration example of a hybrid descriptor according to an embodiment.

FIG. 10 illustrates a configuration example of a hybrid descriptor according to an embodiment.

FIG. 11 illustrates a configuration example of an HEVC descriptor according to an embodiment.

FIG. 12 illustrates a stream and an operation of a data reproduction device according to an embodiment.

FIG. 13 is a flowchart illustrating an operation of a data generation device according to an embodiment.

FIG. 14 is a flowchart illustrating an operation of a data reproduction device according to an embodiment.

DESCRIPTION OF EXEMPLARY EMBODIMENT

(Underlying Knowledge Forming Basis of the Present Disclosure)

[0010] The high dynamic range (HDR) has been gaining attention as a scheme covering a luminance range with an increased maximum luminance value in order to represent bright light such as mirror-reflected light, which cannot be represented using current TV signals, with brightness closer to its actual brightness while maintaining dark grayscale values of existing video. Specifically, the scheme covering the luminance range supported by the existing TV signals is called the standard dynamic range (SDR) and has the maximum luminance value of 100 nit, and the HDR is expected to have an increased maximum luminance value of at least 1,000 nit.

[0011] It is desired that video data covering such an HDR be reproducible even by an existing reproduction device that supports only the SDR. In other words, there is a demand for video data that is reproducible as HDR video by a reproduction device supporting the HDR and reproducible as SDR video by a reproduction device supporting the SDR.

[0012] The data generation method according to one aspect of the present disclosure is a data generation method for generating video data that covers a second luminance dynamic range wider than a first luminance dynamic range and has reproduction compatibility with a first device that does not support reproduction of video having the second luminance dynamic range and supports reproduction of video having the first luminance dynamic range, and the data generation method includes: generating a video signal to be included in the video data using a second opto-electrical transfer function (OETF) to be referred to by a second device when the second device decodes the video data, the second device supporting reproduction of video having the second luminance dynamic range; storing, into video usability information (VUI) in the video data, first transfer function information for identifying a first OETF to be

referred to by the first device when the first device decodes the video data; and storing, into supplemental enhancement information (SEI) in the video data, second transfer function information for identifying the second OETF.

[0013] Accordingly, a device that only supports reproduction of video having the first luminance dynamic range can reproduce video data using the first transfer function information, and a device that supports reproduction of video having the second luminance dynamic range can reproduce video data using the second transfer function information. Thus, in the data generation method, video data having backward compatibility can be generated.

[0014] For example, the data generation method may further include storing, into a descriptor of a multiplexing layer, hybrid information indicating whether or not the video data is video data covering the second luminance dynamic range.

[0015] Accordingly, in the data reproduction device that reproduces video data, switching of reproduction schemes can be prepared in advance using the hybrid information in the multiplexing layer. This allows smooth switching of the reproduction schemes in the data reproduction device.

[0016] For example, the first OETF may be an OETF defined by a linear term of luminance of the video data in a first range of the luminance of the video data and defined by an exponential term of the luminance of the video data in a second range of the luminance of the video data which is greater than the first range.

[0017] For example, the second OETF may be an OETF defined by a linear term of luminance of the video data in a third range of the luminance of the video data, defined by an exponential term of the luminance of the video data in a fourth range of the luminance of the video data which is greater than the third range, and defined by a logarithmic term of the luminance of the video data in a fifth range of the luminance of the video data which is greater than the fourth range.

[0018] For example, the first OETF may be an OETF defined by an exponential term of luminance of the video data.

[0019] For example, the second OETF may be an OETF defined by an exponential term of luminance of the video data in a sixth range of the luminance of the video data and defined by a logarithmic term of the luminance of the video data in a seventh range of the luminance of the video data which is greater than the sixth range.

[0020] For example, the first OETF may be an OETF defined in one of BT. 709 and BT. 2020, and the second OETF may be a hybrid gamma OETF.

[0021] For example, the data generation method may further include storing, into the SEI, dynamic range increase information indicating a difference between a luminance dynamic

range of the video data and the first luminance dynamic range.

[0022] For example, the data generation method may further include storing, into the SEI, maximum average picture level information indicating a highest average luminance value among average luminance values of all pictures included in a video sequence.

[0023] Furthermore, the data reproduction method according to one aspect of the present disclosure is a data reproduction method for reproducing video data that covers a second luminance dynamic range wider than a first luminance dynamic range and has reproduction compatibility with a first device that does not support reproduction of video having the second luminance dynamic range and supports reproduction of video having the first luminance dynamic range, the video data including: video usability information (VUI) storing first transfer function information for identifying a first opto-electrical transfer function (OETF) to be referred to by the first device when the first device decodes the video data; and supplemental enhancement information (SEI) storing second transfer function information for identifying a second OETF to be referred to by a second device when the second device decodes the video data, the second device supporting reproduction of video having the second luminance dynamic range, and the data reproduction method includes: obtaining the second transfer function information included in the SEI; and reproducing a video signal included in the video data by referring to the second OETF identified in the second transfer function information obtained.

[0024] Accordingly, in the data reproduction method, video data having backward compatibility can be reproduced.

[0025] For example, the video data may further include hybrid information indicating whether or not the video data is video data covering the second luminance dynamic range, the hybrid information being stored in a descriptor of a multiplexing layer, and the data reproduction method may further include: obtaining the hybrid information from the video data; preparing for switching between the reproduction of the video having the first luminance dynamic range and the reproduction of the video having the second luminance dynamic range, based on the hybrid information obtained; and switching the reproduction of the video having the first luminance dynamic range and the reproduction of the video having the second luminance dynamic range at a timing of a change in a video sequence.

[0026] Accordingly, switching of reproduction schemes can be prepared in advance using the hybrid information in the multiplexing layer. This allows smooth switching of the reproduction schemes.

[0027] For example, the first OETF may be an OETF defined by a linear term of luminance of the video data in a first range of the luminance of the video data and defined by an exponential term of the luminance of the video data in a second range of the luminance of the video data which is greater than the first range.

[0028] For example, the second OETF may be an OETF defined by a linear term of luminance of the video data in a third range of the luminance of the video data, defined by an exponential term of the luminance of the video data in a fourth range of the luminance of the video data which is greater than the third range, and defined by a logarithmic term of the luminance of the video data in a fifth range of the luminance of the video data which is greater than the fourth range.

[0029] For example, the first OETF may be an OETF defined by an exponential term of luminance of the video data.

[0030] For example, the second OETF may be an OETF defined by an exponential term of luminance of the video data in a sixth range of the luminance of the video data and defined by a logarithmic term of the luminance of the video data in a seventh range of the luminance of the video data which is greater than the sixth range.

[0031] For example, the first OETF may be an OETF defined in one of BT. 709 and BT. 2020, and the second OETF may be a hybrid gamma OETF.

[0032] For example, the data reproduction method may further include obtaining, from the SEI, dynamic range increase information indicating a difference between a luminance dynamic range of the video data and the first luminance dynamic range.

[0033] For example, the data reproduction method may further include obtaining, from the SEI, maximum average picture level information indicating a highest average luminance value among average luminance values of all pictures included in a video sequence.

[0034] The data generation device according to one aspect of the present disclosure is a data generation device which generates video data that covers a second luminance dynamic range wider than a first luminance dynamic range and has reproduction compatibility with a first device that does not support reproduction of video having the second luminance dynamic range and supports reproduction of video having the first luminance dynamic range, and the data generation device includes: a generator that generates a video signal to be included in the video data using a second opto-electrical transfer function (OETF) to be referred to by a second device when the second device decodes the video data, the second device supporting reproduction of video having the second luminance dynamic range; a first storage that stores, into video usability information (VUI) in the video data, first transfer function information for identifying a first OETF to be referred to by the first device when the first device decodes the video data; and a second storage that stores, into supplemental enhancement information (SEI) in the video data, second transfer function information for identifying the second OETF.

[0035] Accordingly, a device that only supports reproduction of video having the first luminance dynamic range can reproduce video data using the first transfer function information, and a device that supports reproduction of video having the second luminance dynamic range can reproduce video data using the second transfer function information. Thus, the data generation

device can generate video data having backward compatibility.

[0036] The data reproduction device according to an illustrative example of the present disclosure is a data reproduction device which reproduces video data that covers a second luminance dynamic range wider than a first luminance dynamic range and has reproduction compatibility with a first device that does not support reproduction of video having the second luminance dynamic range and supports reproduction of video having the first luminance dynamic range, the video data including: video usability information (VUI) storing first transfer function information for identifying a first opto-electrical transfer function (OETF) to be referred to by the first device when the first device decodes the video data; and supplemental enhancement information (SEI) storing second transfer function information for identifying a second OETF to be referred to by a second device when the second device decodes the video data, the second device supporting reproduction of video having the second luminance dynamic range, and the data reproduction device includes: an obtainer that obtains the second transfer function information included in the SEI; and a reproducer that reproduces a video signal included in the video data by referring to the second OETF identified in the second transfer function information obtained.

[0037] Accordingly, the data reproduction device can reproduce video data having backward compatibility.

[0038] Note that these general and specific aspects may be implemented using a system, a method, an integrated circuit, a computer program, or a computer-readable recording medium such as a compact disc read-only memory (CD-ROM), or any combination of systems, methods, integrated circuits, computer programs, or recording media.

[0039] Hereinafter, an embodiment will be specifically described with reference to the drawings.

[0040] Note that each embodiment described below shows a specific example of the present disclosure. The numerical values, shapes, materials, structural elements, the arrangement and connection of the structural elements, steps, the processing order of the steps etc. shown in the following embodiment are mere examples, and are not intended to limit the scope of the present disclosure. Furthermore, among the structural elements in the following embodiment, structural elements not recited in the claims indicating the broadest concepts of the present disclosure are described as arbitrary structural elements.

[0041] Although detailed descriptions of terms, data configuration, and processing, etc., may be omitted below, specific examples thereof are based on the descriptions in NPL 1, NPL2, and NPL 3, for example.

[0042] First, the configuration of a system according to an embodiment of the invention will be described. FIG. 1 is a block diagram illustrating the configuration of the system according to the present embodiment. The system illustrated in FIG. 1 includes data generation device 110

according to the appended claim and data reproduction device 120.

[0043] Data generation device 110 generates video data that covers a second luminance dynamic range (for example, the HDR) wider than a first luminance dynamic range (for example, the SDR) and has reproduction compatibility with a first device that does not support reproduction of video having the second luminance dynamic range and supports reproduction of video having the first luminance dynamic range.

[0044] Data generation device 110 include video signal generator 111, encoder 112, and multiplexer 113.

[0045] Image signal generator 111 converts a luminance value of a source image covering the HDR into a code value using an opto-electrical transfer function (OETF). The OETF is a function for converting the luminance value of the source image into the code value, as illustrated in FIG. 2. Specifically, video signal generator 111 uses an SDR-compatible HDR OETF. This will be described in detail later.

[0046] Encoder 112 generates a video elementary stream by encoding the obtained code values according to a video coding standard such as the high efficiency video coding (HEVC). Multiplexer 113 generates a transport stream (for example, a DVB transport stream) by multiplexing video elementary streams.

[0047] The generated transport stream is transmitted to data reproduction device 120 by broadcast waves or the like, for example. Note that an example in which the broadcast waves are used will be described herein, but a network or the like may be used for transmission, or a recording medium such as a Blu-ray Disc (BD) may be used for transmission.

[0048] Data reproduction device 120 generates the video data generated by data generation device 110. Data reproduction device 120 includes demultiplexer 121, decoder 122, and reproducer 123.

[0049] Demultiplexer 121 generates a video elementary stream by demultiplexing the video data (the transport stream). Decoder 122 generates codes values by decoding the obtained video elementary stream according to a video coding standard such as the HEVC.

[0050] Reproducer 123 reconstructs video by converting the obtained code values into luminance values using an electro-optical transfer function (EOTF) corresponding to the OETF stated above. The EOTF is the inverse function which reverses the OETF and is used for converting the code values into the luminance values. The obtained video is displayed on a display, etc., included in data reproduction device 120 or connected to data reproduction device 120.

[0051] Signalling of the transfer function (OETF) according to the present embodiment will be described below.

[0052] The transfer function is signalled using `transfer_characteristics` within video usability information (VUI) included in a sequence parameter set (SPS) in the HEVC and AVC video coding standards.

[0053] The OETF alone is signalled, and the EOTF is not signalled.

[0054] FIG. 3 illustrates the syntax of a VUI parameter. As illustrated in FIG. 3, the VUI includes first transfer function information (`transfer_characteristics`). FIG. 4 is a table indicating the semantics of `transfer_characteristics`. Values 1 and 14 are assigned to SDR OETFs supported by digital video broadcasting (DVB) ultra HD (UHD) phase 1 receivers.

[0055] As described in NPL 1 and the like, `transfer_characteristics` indicates the opto-electrical voltage characteristics (the opto-electrical transfer characteristics) of the source image.

[0056] Note that signalling means including, in a transfer signal, a signal for identifying desired information or a signal indicating such information itself so that the receiver side can obtain the desired information. For example, in the example in FIG. 3 and FIG. 4, `transfer_characteristics` for identifying the OETF is included in the transfer signal, and the receiver side identifies the OETF on the basis of the received `transfer_characteristics`.

[0057] An example of extension for new OETFs according to the present embodiment will be described below.

[0058] The HEVC and AVC standards have reserved values for further extension. Thus, the reserved values can be assigned to SDR-compatible HDR OETFs (hereinafter referred to as hybrid OETFs). For example, as illustrated in FIG. 5, the hybrid OETFs are assigned to values 18 to 20 which are the reserved values.

[0059] In this case, however, a legacy data reproduction device (receiver) that does not support the HDR is not capable of recognizing the new values and recognizes them as the reserved values. Thus, there is the problem that when a new value is used for the hybrid OETF, it is not possible to provide the backward compatibility. The hybrid OETF is, for example, an OETF including a part expressed as a power of luminance and a part expressed as a logarithm of luminance, such as a BBC hybrid gamma OETF.

[0060] In the present embodiment, the value of the first transfer function information (`transfer_characteristics`) is set to 1 (BT.709) or 14 (BT.2020) as in an existing SDR.

[0061] Furthermore, in order to identify the hybrid OETF, the second transfer function information (`HDR_transfer_characteristic`) is signalled separately from the first transfer function information. Thus, in the data reproduction device that does not support the HDR, the OETF for SDR can be identified using the first transfer function information (`transfer_characteristics`), while, in the data reproduction device that supports the HDR, the OETF for HDR can be

identified using the second transfer function information.

[0062] The second transfer function information (HDR_transfer_characteristic) is used for signalling of the OETF for HDR. Specifically, the OETF for HDR has compatibility with the OETF for SDR identified using the first transfer function information (transfer_characteristics).

[0063] For example, the second transfer function information (HDR_transfer_characteristic) indicates any of the three hybrid OETFs indicated in FIG. 5. Note that the second transfer function information may be information indicating whether or not to use the hybrid OETF. The number of selectable hybrid OETFs may be any number greater than or equal to one.

[0064] As illustrated in FIG. 2, the characteristics of the hybrid OETF substantially match the characteristics of the SDR OETF in a low luminance range. Specifically, in the low luminance range, the luminance of video reproduced using the hybrid OETF from the video signals generated using the hybrid OETF and the luminance of video reproduced using the SDR OETF from the video signals generated using the hybrid OETF are almost the same. Thus, it is possible to reduce the difference in luminance value between when the video is reproduced by an HDR device and when the video is reproduced by an SDR device, and therefore video that is less likely to provide a feeling of discomfort can be reproduced even when the video is reproduced using the SDR OETF.

[0065] Methods of storing the second transfer function information will be described below. The methods are roughly classified as a method in which the second transfer function information is stored into a video coding layer and a method in which the second transfer function information is stored into a multiplexing layer.

[0066] First, the method in which the second transfer function information is stored into the video coding layer will be described.

[0067] FIG. 6 illustrates the syntax of an HDR hybrid gamma SEI message (hereinafter referred to as a hybrid SEI message) according to the present embodiment. As illustrated in FIG. 6, the second transfer function information (HDR_transfer_characteristic) is included in the hybrid SEI message.

[0068] The hybrid SEI message is present only in an IRAP NAL unit or an I-picture and is valid for the remainder of a coded video sequence.

[0069] Note that the hybrid SEI message may be a prefix or a suffix SEI message.

[0070] The presence of this SEI message may be made mandatory in application standardization bodies when HDR_transfer_characteristic is a predetermined fixed value.

[0071] Furthermore, as illustrated in FIG. 7, the hybrid SEI message may include, in addition to the second transfer function information stated above or instead of the second transfer

function information, dynamic range increase information (dynamic_range_increase) and maximum average picture level information (maximum_average_picture_level).

[0072] The dynamic range increase information (dynamic_range_increase) is used to calculate coefficient k and has value 0, 1, or 2 only. Coefficient k indicates a difference from dynamic range SDR and is determined according to the following Expression 1. Specifically, coefficient k indicates a scaling factor for the dynamic range of current video with respect to dynamic range SDR.

$$k = 2 \times \text{dynamic_range_increase} + 4 \quad (\text{Expression 1})$$

[0073] The maximum average picture level information (maximum_average_picture_level) indicates the highest average picture level among all the pictures included in a video sequence. The average picture level means the average value of pixel luminance expressed in percentage of the maximum luminance.

[0074] Thus, the use of the dynamic range increase information and the maximum average picture level information allows the difference from the SDR to be set within an arbitrary range.

[0075] The presence of this SEI message may be made mandatory in application standardization bodies when k is a predetermined fixed value. For example, k is equal to 4 for DVB, and k is equal to 8 for BDA.

[0076] FIG. 8 illustrates the configuration of an extended SPS. As illustrated in FIG. 8, the dynamic range increase information (dynamic_range_increase) and the maximum average picture level information (maximum_average_picture_level) may be included in the SPS.

[0077] Next, an exemplary the method, not covered by the claimed invention, in which the second transfer function information is stored into the multiplexing layer will be described.

[0078] FIG. 9 illustrates the configuration of a hybrid descriptor (HDR_hybrid_gamma_descriptor) which is a new descriptor at the MPEG2-TS level according to the present embodiment.

[0079] As illustrated in FIG. 9, the hybrid descriptor includes a hybrid OETF flag (HDR_hybrid_gamma OETF flag) and the second transfer function information (HDR_transfer_characteristic).

[0080] The hybrid OETF flag (HDR_hybrid_gamma OETF flag) indicates whether or not the content is HDR coded using the hybrid OETF. For example, when the hybrid OETF flag is 1, the content is HDR coded using the hybrid OETF.

[0081] Note that the hybrid OETF flag is not always necessary, and it may be possible to use only the second transfer function information.

[0082] The hybrid descriptor is stored into at least one of a program map table (PMT) specified by the MPEG, a service description table (SDT) specified by the DVB in the DVB-SI standard, and an event information table (EIT) specified by the DVB in the DVB-SI standard.

[0083] The PMT indicates the PID of a TS packet in which an image, audio, or the like is stored. By obtaining the PID for a desired image, audio, or the like from the PMT, the data reproduction device can extract the TS packet for the desired image or audio.

[0084] The SDT indicates the name of a channel (a service), the type of the EIT sent through each channel, digital copy control information, and the like.

[0085] The EIT indicates information related to a program, such as the title, the broadcast date and time, and the broadcast content of the program.

[0086] When the hybrid descriptor is included in the PMT, the hybrid descriptor is applied to the video elementary stream only. In this case, however, a broadcaster needs to control modification of the PMT, and this modification may be difficult.

[0087] When the hybrid descriptor is included in the SDT, the content of the hybrid descriptor is not updated often. Thus, the SDT is preferred when the content of the hybrid descriptor is applied to the whole service.

[0088] When the hybrid descriptor is included in the EIT, it is advantageous that the content of the hybrid descriptor can be changed on an event basis.

[0089] FIG. 10 illustrates another configuration example of the hybrid descriptor according to the present embodiment. As illustrated in FIG. 10, the hybrid descriptor may include, in addition to the second transfer function information stated above or instead of the second transfer function information, dynamic range increase information (dynamic_range_increase) and maximum average picture level information (maximum_average_picture_level).

[0090] FIG. 11 illustrates the configuration of an HEVC descriptor (HEVC_descriptor) according to the present embodiment. The HEVC descriptor is a descriptor at the MPEG2-TS level. As illustrated in FIG. 11, the reserved values of the HEVC descriptor are replaced with a hybrid coded flag (hdr hybrid_gamma coded content flag) and dynamic range increase information (dynamic_range_increase). Note that the hybrid coded flag is the same as or similar to the hybrid OETF flag (HDR_hybrid_gamma_OETF_flag) described above. Furthermore, other information described above (the second transfer function information and the maximum average picture level information) may be included in the HEVC descriptor.

[0091] The same or like extension may be applied to an AVC descriptor (AVC_video_descriptor).

[0092] The hybrid descriptor (HDR_hybrid_gamma_descriptor) described above may be combined with signalling of the OETF to the video elementary stream (the HDR hybrid gamma SEI message). This allows smooth switching of parameters in the data reproduction device.

[0093] Hereinafter, this operation will be described in detail. FIG. 12 illustrates the configuration of the stream and the operation of the data reproduction device.

[0094] Transmission of the hybrid descriptor (HDR_hybrid_gamma_descriptor) including the hybrid OETF flag (HDR hybrid_gamma OETF flag) starts slightly before an actual change. The data reproduction device that received this hybrid OETF flag prepares for the change between the SDR and the HDR.

[0095] An end of sequence (EOS) indicating the end of a video sequence is inserted into the video elementary stream in order that the parameter change becomes active. The hybrid SEI message adapted to the last signalled hybrid descriptor may be or may not be stored at a random access point (RAP) following the EOS.

[0096] The data reproduction device detects whether or not the EOS and the hybrid SEI message are present and makes a change according to the detection result.

[0097] In the example illustrated in FIG. 12, the data reproduction device obtains the hybrid descriptor containing HDR_hybrid_gamma_OETF_flag = 0 in the HDR operating state. This allows the data reproduction device to start preparing for switching operations from the HDR to the SDR. Next, the data reproduction device switches the HDR to the SDR at the timing when the EOS is obtained. The hybrid SEI message is not present within a SDR video elementary stream, and thus the data reproduction device does not obtain the hybrid SEI message.

[0098] Next, the data reproduction device obtains the hybrid descriptor containing HDR_hybrid_gamma_OETF_flag = 1 in the SDR operating state. This allows the data reproduction device to start preparing for switching operations from the SDR to the HDR. Next, the data reproduction device switches the SDR to the HDR at the timing when the EOS is obtained.

[0099] Hereinafter, the operations of data generation device 110 and data reproduction device 120 based on the above description will be described.

[0100] FIG. 13 is a flowchart of an operation of data generation device 110 according to the present embodiment. Data generation device 110 generates HDR video data having reproduction compatibility with the first device that does not support reproduction of HDR video and supports reproduction of SDR video.

[0101] First, video signal generator 111 generates a video signal by converting a luminance value of a source image into a code value using the second OETF (S101). Next, encoder 112 generates a video elementary stream by encoding the video signal. At this time, encoder 112

stores, into the VUI in the video data (the video elementary stream), the first transfer function information for identifying the first OETF to be referred to by the first device supporting only the SDR when the first device reproduces the video data. Furthermore, the second transfer function information for identifying the second OETF to be referred to by the second device supporting the HDR when the second device decodes the video data is stored into the SEI in the video data (S102).

[0102] The VUI and the SEI belong to the video coding layer. The first OETF is, for example, the OETF defined in BT. 709 or BT. 2020, and the second OETF is, for example, a BBC hybrid gamma OETF.

[0103] Furthermore, encoder 112 may store, into the SEI, dynamic range increase information indicating a difference between the luminance dynamic range of the video data and luminance dynamic range SDR. Moreover, encoder 112 may store, into the SEI, maximum average picture level information indicating the highest average luminance value among the average luminance values of all the pictures included in the video sequence.

[0104] Next, multiplexer 113 generates a transport stream by multiplexing video elementary stream data. At this time, multiplexer 113 stores, into the hybrid descriptor of the multiplexing layer, hybrid information (a hybrid OETF flag) indicating whether or not the video data is HDR video data (S103).

[0105] Note that although the example in which the hybrid descriptor includes at least the hybrid OETF flag is illustrated in FIG. 12, the hybrid descriptor may further include the second transfer function information, the dynamic range increase information, or the maximum average picture level information.

[0106] Likewise, it is sufficient that the hybrid SEI message include at least one of the hybrid OETF flag, the second transfer function information, the dynamic range increase information, and the maximum average picture level information.

[0107] Furthermore, although each of the hybrid OETF flag and the second transfer function information is stated as individual information in the above description, the second transfer function information may be used instead of the hybrid OETF flag. This means that it is not necessary to use the hybrid OETF flag. For example, whether or not the video data is the HDR video data (whether or not to use the hybrid OETF) can be signalled according to whether or not the second transfer function information is included in the video data. Alternatively, whether or not the video data is the HDR video data may be signalled according to whether the second transfer function information indicates the hybrid OETF or the SDR OETF.

[0108] Note that the example in which the second transfer function information indicates the hybrid OETF is described above, but when HDR video and SDR video are mixed in video data, as illustrated in FIG. 12, the second transfer function information may indicate the SDR OETF for the SDR video as well. Accordingly, the data reproduction device supporting the HDR may

always refer to the second transfer function information regardless of whether the video data has the SDR or the HDR. In other words, said data reproduction device does not need to refer to the first transfer function information. This allows the process of the data reproduction device to be simplified.

[0109] FIG. 14 is a flowchart of an operation of data reproduction device 120 according to the present embodiment. Data reproduction device 120 reproduces HDR video data having reproduction compatibility with the first device that does not support reproduction of HDR video and supports reproduction of SDR video. This video data is the video data generated by data generation device 110, for example.

[0110] First, demultiplexer 121 generates a video elementary stream by demultiplexing the video data (the transport stream). At this time, demultiplexer 121 obtains hybrid information (for example, the hybrid OETF flag) from the hybrid descriptor of the video data (S121). Note that demultiplexer 121 may further obtain at least one of the dynamic range increase information and the maximum average picture level information from the hybrid descriptor.

[0111] Next, data reproduction device 120 prepares for switching between reproduction of SDR video and reproduction of HDR video on the basis of the obtained hybrid information (S122).

[0112] Next, decoder 122 generates a video signal (a code value) by decoding the video elementary stream. When the last hybrid OETF flag indicates the use of the hybrid OETF, decoder 122 obtains the second transfer function information included in the hybrid SEI within the video elementary stream (S123). Note that decoder 122 may further obtain at least one of the dynamic range increase information and the maximum average picture level information from the hybrid SEI.

[0113] Reproducer 123 reproduces a video signal included in the video data by referring to the second OETF identified in the obtained second transfer function information (S124). Furthermore, reproducer 123 switches reproduction of SDR video and reproduction of HDR video at the timing of a change in the video sequence. Specifically, reproducer 123 reproduces data following the EOS by the scheme after the change. When the dynamic range increase information or the maximum average picture level information is obtained, this information is used for the reproduction.

[0114] Note that when the last hybrid OETF flag indicates that the hybrid OETF has not been used, decoder 122 obtains the first transfer function information included in the VUI within the video elementary stream in Step S123. In Step S124, reproducer 123 reproduces a video signal included in the video data by referring to the second OETF identified in the obtained first transfer function information. Note that as described above, when the second transfer function information selectively indicates the first OETF or the second OETF, decoder 122 may always obtain the second transfer function information, and reproducer 123 may refer to the first OETF or the second OETF indicated in the second transfer function information.

[0115] As described above, in addition to the first transfer function information which is stored into the VUI, the second transfer function information is stored into the SEI message in the present embodiment. This makes it possible to implement HDR coding in which the hybrid OETF such as the BBC hybrid gamma OETF is used.

[0116] Specifically, whether the content is HDR coded using the hybrid OETF can be indicated through signalling to the multiplexing layer using a descriptor.

[0117] Furthermore, the combination of a new SEI message and a new descriptor allows the data reproduction device to smoothly switch between the HDR and the SDR.

[0118] The first OETF may be the function determined according to Expression 2 below.

[Math. 1]

$$V = \begin{cases} \alpha L (0 \leq L < \beta) \\ \gamma L^\delta - \rho (\beta \leq L \leq 1) \end{cases} \quad (\text{Expression 2})$$

[0119] In the expression, L is the luminance of an image and is standardized as $0 \leq L \leq 1$ at a reference white level, V is a numerical value corresponding to an electric signal, and α , β , γ , δ , and ρ are each a constant and specific numerical examples thereof are $\alpha = 4.5$, $\beta = 0.018$, $\gamma = 1.099$, $\delta = 0.45$, and $\rho = 0.099$.

[0120] In other words, as represented by Expression 2, the first OETF may be an OETF defined by a linear term of the luminance of video data in a first range of the luminance of the video data and defined by an exponential term of the luminance of the video data in a second range of the luminance of the video data greater than the first range.

[0121] Furthermore, the first OETF may be the function represented by Expression 3 below.

[Math. 2]

$$E' = \begin{cases} \alpha E (0 \leq E < \beta) \\ \gamma E^\delta - (\gamma - 1) (\beta \leq E \leq 1) \end{cases} \quad (\text{Expression 3})$$

[0122] In this expression, L is the luminance of an image and defined as $0 \leq L \leq 1$, E is a numerical value corresponding to the voltage standardized at a reference white level and is proportional to the absolute light intensity detected in reference camera color channels RGB, resulting in E' being a non-linear signal, and α , β , γ , δ , and ρ are each a constant and specific numerical examples thereof are $\alpha = 4.5$, $\beta = 0.018$ (for 10-bit system) or 0.0181 (for 12-bit system), $\gamma = 1.099$ (for 10-bit system) or 1.0993 (for 12-bit system), $\delta = 0.45$, and $\rho = 0.099$.

[0123] Furthermore, the second OETF may be the function determined according to Expression 4 below, and in this OETF, a conversion function is defined by a logarithmic term in

the range of high luminance.

[Math. 3]

$$V = \begin{cases} \alpha L (0 \leq L < \beta) \\ \gamma L^\delta - (\gamma - 1)(\beta \leq L \leq \mu) \\ \eta \ln(L) + \rho (L > \mu) \end{cases} \quad (\text{Expression 4})$$

[0124] In the expression, L is the luminance of an image and standardized at a reference white level, where V may exceed 1, meaning that this conversion function also supports luminance greater than the reference white, V is a numerical value corresponding to an electric signal, μ is a breakpoint between a gamma curve and a logarithmic curve and determines the maximum value of L where V is 1 or less, and α , β , γ , δ , and ρ are each a constant and specific numerical examples thereof are $\alpha = 4.5$, $\beta = 0.018$, $\gamma = 1.099$, $\delta = 0.45$, and $\rho = 0.099$.

[0125] In other words, as represented by Expression 4, the second OETF may be an OETF defined by a linear term of the luminance of video data in a third range of the luminance of the video data, defined by an exponential term of the luminance of the video data in a fourth range of the luminance of the video data greater than the third range, and defined by a logarithmic term of the luminance of the video data in a fifth range of the luminance of the video data greater than the fourth range.

[0126] The first OETF may be the function determined according to Expression 5 below.

[Math. 4]

$$V = L^\alpha \quad (\text{Expression 5})$$

[0127] In this expression, L is the luminance of an image and standardized as $0 \leq L \leq 1$ at a reference white level, V is a numerical value corresponding to an electric signal, and α is a constant and a specific numerical example thereof is $\alpha = 0.5$.

[0128] In other words, as represented by Expression 5, the first OETF may be an OETF defined by an exponential term of the luminance of the video data.

[0129] The second OETF may be the function determined according to Expression 6 below. In this OETF, a conversion function is defined by a logarithmic term in the range of high luminance.

[Math. 5]

$$V = \begin{cases} L^\alpha (0 \leq L \leq \mu) \\ \eta \ln(L) + \rho (L > \mu) \end{cases} \quad (\text{Expression 6})$$

[0130] In this expression, α is a constant and a specific numerical example thereof is $\alpha = 0.5$.

[0131] In other words, as represented by Expression 6, the second OETF may be an OETF defined by an exponential term of the luminance of video data in a sixth range of the luminance of the video data and defined by a logarithmic term of the luminance of the video data in a seventh range of the luminance of the video data greater than the sixth range.

[0132] Although the data generation device (the data generation method) and the data reproduction device (the data reproduction method) according to one or more aspects are described thus far based on the embodiment, the present disclosure is not limited to this embodiment. Various modifications of the present embodiment as well as embodiments resulting from combinations of structural elements of the different embodiments that may be conceived by those skilled in the art may be included within the scope of a data generation device according to the present invention as defined by the appended claim.

[0133] For example, in each embodiment described above, each of the structural elements may be configured in the form of an exclusive hardware product such as a circuit, or may be realized by executing a software program suitable for each of the structural elements. Each of the structural elements may be realized by means of a program executing unit, such as a central processing unit (CPU) and a processor, reading and executing the software program recorded on a recording medium such as a hard disk or a semiconductor memory.

INDUSTRIAL APPLICABILITY

[0134] The present disclosure can be applied to a data transmission device or a data reproduction device such as a BD device.

REFERENCE MARKS IN THE DRAWINGS

[0135]

- 110 data generation device
- 111 video signal generator
- 112 encoder
- 113 multiplexer
- 120 data reproduction device
- 121 demultiplexer

122

decoder

123

reproducer

REFERENCES CITED IN THE DESCRIPTION

Cited references

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- WO2014178286A1 [0002]

Non-patent literature cited in the description

- High efficiency video codingITU-T H.265, 2014, [0003]
- Parameter values for the HDTV standards for production and international programme exchangeRecommendation ITU-R BT.709-5, 2002, [0003]

DATAGENERERINGSSENHED**PATENTKRAV**

1. Datagenereringsenhed (110), der omfatter:

et genereringskredsløb (111), der er konfigureret til at generere videodata ifølge en avanceret videokodningsstandard, AVC (Advanced Video Coding), og en anden optoelektrisk overførselsfunktion, OETF (opto-electrical transfer function); og

et lager til opbevaring:

af informationer brugbare for video, VUI (video usability information), der indbefatter en første værdi, der angiver en første OETF; og

supplerende informationer til forbedring, SEI (supplemental enhancement information), der indbefatter en anden værdi, der angiver den anden OETF, hvor VUI og SEI er indbefattet i videodataene; hvor

den første OETF og den anden OETF understøtter hhv. standard dynamisk område, SDR (standard dynamic range), og højt dynamisk område, HDR (high dynamic range);

den første værdi skal refereres til af en dekoderanordning, der ikke understøtter HDR, når dekoderanordningen afkoder videodataene; og

den anden OETF er kompatibel med den første OETF; hvor

den første OETF er en OETF defineret i ét ud af BT. 709 og BT. 2020; og

SEI er i en IRAP NAL-enhed eller et I-billede; hvor

videodata dækker et andet dynamisk interval for luminans for HDS, som er bredere end et første dynamisk interval for luminans for SDR og har kompatibilitet med dekoderanordningen, der ikke understøtter HDR, således at dekoderanordningen reproducerer videodata baseret på SDR.

DRAWINGS

FIG. 1




FIG. 2




FIG. 3

vui_parameters0 {	Descriptor
...	
colour_description_present_flag	u(1)
if(colour_description_present_flag) {	
colour_primaries	u(8)
transfer_characteristics	u(8)
matrix_coeffs	u(8)
}	
...	
}	

FIG. 4

Value	Transfer Characteristic	Informative Remark
0	Reserved	For future use by ITU-T ISO/IEC
1	$V = \alpha * L_C^{0.45} - (\alpha - 1)$ for $1 \geq L_C \geq \beta$ $V = 4.500 * L_C$ for $\beta > L_C \geq 0$	Rec. ITU-R BT.709-5 Rec. ITU-R BT.1361 conventional colour gamut system (functionally the same as the values 6, 14, and 15)
...		
14	$V = \alpha * L_C^{0.45} - (\alpha - 1)$ for $1 \geq L_C \geq \beta$ $V = 4.500 * L_C$ for $\beta > L_C \geq 0$	Rec. ITU-R BT.2020 (functionally the same as the values 1, 6, and 15)
...		
18..255	Reserved	For future use by ITU-T ISO/IEC

FIG. 5

Value	Transfer Characteristic	Informative Remark
0	Reserved	For future use by ITU-T ISO/IEC
1	$V = \alpha * L_c^{0.45} - (\alpha - 1)$ for $1 \geq L_c \geq 8$ $V = 4.500 * L_c$ for $\beta > L_c \geq 0$	Rec. ITU-R BT.709-5 Rec. ITU-R BT.1361 conventional colour gamut system (functionally the same as the values 6, 14, and 15)
...		
14	$V = \alpha * L_c^{0.45} - (\alpha - 1)$ for $1 \geq L_c \geq 8$ $V = 4.500 * L_c$ for $\beta > L_c \geq 0$	Rec. ITU-R BT.2020 (functionally the same as the values 1, 6, and 15)
...		
18	$V = \eta * \ln(\kappa L) + \rho$ for $1 \geq L > \mu \div \kappa$ $V = \sqrt{\kappa L}$ for $\mu \div \kappa \geq L \geq 0$ with $\kappa = 4$ and μ, η and ρ being the solution to the equations $\kappa = \mu * \exp(2 * ((1 \div \sqrt{\mu}) - 1)) = 4$ $\mu = \sqrt{\mu} \div 2$ $\rho = \sqrt{\mu} * (1 - \ln(\sqrt{\mu}))$	BBC Hybrid Gamma OETF with $\kappa = 4$ as proposed in document ITU-R 6C/349-E from 30 October 2014
19	$V = \eta * \ln(\kappa L) + \rho$ for $1 \geq L > \mu \div \kappa$ $V = \sqrt{\kappa L}$ for $\mu \div \kappa \geq L \geq 0$ with $\kappa = 6$ and μ, η and ρ being the solution to the equations $\kappa = \mu * \exp(2 * ((1 \div \sqrt{\mu}) - 1)) = 6$ $\mu = \sqrt{\mu} \div 2$ $\rho = \sqrt{\mu} * (1 - \ln(\sqrt{\mu}))$	BBC Hybrid Gamma OETF with $\kappa = 6$ as proposed in document ITU-R 6C/349-E from 30 October 2014
20	$V = \eta * \ln(\kappa L) + \rho$ for $1 \geq L > \mu \div \kappa$ $V = \sqrt{\kappa L}$ for $\mu \div \kappa \geq L \geq 0$ with $\kappa = 8$ and μ, η and ρ being the solution to the equations $\kappa = \mu * \exp(2 * ((1 \div \sqrt{\mu}) - 1)) = 8$ $\mu = \sqrt{\mu} \div 2$ $\rho = \sqrt{\mu} * (1 - \ln(\sqrt{\mu}))$	BBC Hybrid Gamma OETF with $\kappa = 8$ as proposed in document ITU-R 6C/349-E from 30 October 2014
21..255	Reserved	For future use by ITU-T ISO/IEC

FIG. 6

HDR_hybrid_gamma(payloadSize) {	Descriptor
HDR_transfer_characteristics	u(8)
/* The SEI message could convey other information about the HDR content if necessary */	
}	

FIG. 7

HDR_hybrid_gamma(payloadSize) {	Descriptor
dynamic_range_increase	u(2)
maximum_average_picture_level	u(7)
/* The SEI message could convey other information about the HDR content if necessary */	
}	

FIG. 8

	Descriptor
seq_parameter_set_rbsp(){	
...	
sps_extension_present_flag	u(1)
if(sps_extension_present_flag) {	
sps_range_extension_flag	u(1)
sps_multilayer_extension_flag	u(1)
sps_hdr_hybrid_gamma_extension_flag	u(1)
sps_extension_5bits	u(5)
{	
if(sps_range_extension_flag)	
sps_range_extension()	
if(sps_multilayer_extension_flag)	
sps_multilayer_extension() /* specified in Annex F */	
if(sps_hdr_hybrid_gamma_extension_flag)	
sps_hdr_hybrid_gamma_extension()	
if(sps_extension_5bits)	
while(more_rbsp_data())	
sps_extension_data_flag	u(1)
...	
}	
}	

sps_hdr_hybrid_gamma_extension(){	
dynamic_range_increase	u(2)
maximum_average_picture_level	u(7)
/* The SPS extension could convey other information about the HDR content if necessary */	
}	

FIG. 9

Syntax	No. Of bits	Mnemonic
HDR_hybrid_gamma_descriptor() { descriptor_tag descriptor_length HDR_hybrid_gamma_OETF_flag reserved if (HDR_hybrid_gamma_OETF_flag == '1') { HDR_transfer_characteristics /* The descriptor could convey other information about the HDR content if necessary */ } }	8 8 1 7 8	uimbsf uimbsf bslbf bslbf uimbsf

FIG. 10

Syntax	No. Of bits	Mnemonic
HDR_hybrid_gamma_descriptor() { descriptor_tag descriptor_length HDR_hybrid_gamma_OETF_flag reserved if (HDR_hybrid_gamma_OETF_flag == '1') { dynamic_range_increase maximum_average_picture_level reserved /* or any other information about the HDR content */ } }	8 8 1 7 2 7 7	uimbsf uimbsf bslbf bslbf uimbsf uimbsf bslbf

FIG. 11

Syntax	No. Of bits	Mnemonic
HEVC_descriptor0 { ... temporal_layer_subset_flag HEVC_still_present_flag HEVC_24hr_picture_present_flag reserved if (temporal_layer_subset_flag == '1') { reserved temporal_id_min reserved temporal_id_max }	1 1 1 5	bslbf bslbf bslbf bslbf
REPLACE WITH		
HEVC_descriptor0 { ... hdr_hybrid_gamma_coded_content_flag if (hdr_hybrid_gamma_coded_content_flag == '1') dynamic_range_increase else reserved reserved ... }	1 2 2 2 2	bslbf uimbsf bslbf bslbf

FIG. 13




FIG. 14

