

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 577 610 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
09.10.1996 Bulletin 1996/41

(51) Int Cl.⁶: **G03G 15/16**

(86) International application number:
PCT/NL92/00014

(21) Application number: **92904441.0**

(87) International publication number:
WO 92/14193 (20.08.1992 Gazette 1992/22)

(22) Date of filing: **21.01.1992**

(54) **IMAGING SYSTEM**
BILDERZEUGUNGSSYSTEM
SYSTEME D'IMAGERIE

(84) Designated Contracting States:
DE FR GB IT

(30) Priority: **12.02.1991 US 653953**

(43) Date of publication of application:
12.01.1994 Bulletin 1994/02

(73) Proprietor: **INDIGO N.V.**
6229 GA Maastricht (NL)

(72) Inventors:
• **PINHAS, Hanna**
58 331 Holon (IL)

• **NIV, Yehuda**
Ness Ziona 70400 (IL)

(74) Representative: **de Bruijn, Leendert C. et al**
Nederlandsch Octroolbureau
P.O. Box 29720
2502 LS Den Haag (NL)

(56) References cited:
US-A- 3 784 300 **US-A- 4 233 381**
US-A- 4 506 971 **US-A- 4 695 152**
US-A- 5 006 902

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 0 577 610 B1

Description

FIELD OF THE INVENTION

The present invention relates generally to electrostatic imaging and particularly to apparatus and a method for treating a developed image before transfer.

BACKGROUND OF THE INVENTION

Systems for electrostatic image reproduction are known in the art. These systems include apparatus for creating a latent electrostatic image on an image forming surface, such as a photoreceptor, through the definition of image and background portions on the photoreceptor surface at different electrical potentials, apparatus for developing the latent image including contacting the latent image with a toner including charged toner particles and apparatus for transferring the developed electrostatic image to a final substrate. This transfer may include the step of first transferring the developed image to an intermediate transfer member for subsequent transfer to the final substrate.

In general, transfer of the developed image from the photoreceptor is aided by an electric field which is generated by the electrical potential difference between a substrate (which can be the final substrate or an intermediate transfer member if one is present) and the image portions on the photoreceptor underlying the developed image. In order to assure good transfer the electric field must be maintained within a given range. In so-called direct copiers (or in "write-white" printers), projections of the image areas of the original (i.e., those areas which are black) on a photoreceptor do not discharge corresponding image portions of the photoreceptor. Projections of the background areas, which are lighter, discharge the voltage on corresponding background portions of the photoreceptor. The potential difference between the background portions (which are near zero volts) and the image portions are of the order of 500 to 1000 volts. In order to assure good transfer, the potential generally required on the substrate is substantially greater than this potential difference, causing electrical discharge between the background portions and the substrate.

It is known for this direct imaging case to irradiate the photoconductor, before transfer of the image therefrom, with strong light which penetrates through the developed image and discharges the charged regions underlying the developed image. The electrical potential on the paper or intermediate transfer member can then be greatly reduced. Examples of this process are shown in U.S. Patents 3,784,300, 4,039,257, 4,853,736 and 5,006,902.

SUMMARY OF THE INVENTION

It is an object of a preferred embodiment of the in-

vention to reduce electrical discharge between the substrate and the image forming surface.

There is therefore provided, in a preferred embodiment of the invention, imaging apparatus including an image forming surface, preferably a photoconductive image forming surface, image forming apparatus for defining an electrostatic latent image on the image forming surface, the latent image having image portions and background portions, development apparatus for developing the electrostatic latent image in a reversal mode, using electrically charged pigmented toner particles to form a developed image overlying the image portions, whereby the developed image on the image forming surface is at a first electrical potential and the background portions on the forming surface are at a second electrical potential, discharge apparatus for partially discharging the image forming surface so that the developed image is at a third electrical potential and the background portions are at a fourth potential and an image receiving surface at a fifth potential, operative for receiving the developed image from the image forming surface, wherein the difference between the fourth potential and the fifth potential is low enough such that substantially no electrical discharge occurs between the image receiving surface and the background portions.

There is further provided in accordance with a preferred embodiment of the invention, imaging apparatus including an image forming surface, preferably a photoconductive image forming surface, image forming apparatus for defining an electrostatic latent image on the image forming surface, the latent image having image portions and background portions, development apparatus for developing the electrostatic latent image in a reversal mode, using electrically charged pigmented toner particles to form a developed image overlying the image portions, whereby the developed image on the image forming surface is at a first electrical potential and the background portions on the image forming surface are at a second electrical potential, an image receiving surface at a third potential, different from the first potential by an image transfer potential difference for receiving the developed image from the image forming surface and discharge apparatus for changing at least one of the first potential and the second potential to change the difference therebetween whereby the absolute value of the potential difference between the second potential and the third potential is reduced to a value below 360 volts.

There is further provided in accordance with a preferred embodiment of the invention, imaging apparatus including an image forming surface preferably a photoconductive image forming surface, image forming apparatus for defining an electrostatic latent image on the image forming surface, the latent image comprising image portions and background portions, development apparatus for developing the electrostatic latent image in a reversal mode, using electrically charged pigmented toner particles to form a developed image overlying the

image portions, whereby the developed image on the image forming surface is at a first electrical potential and the background portions on the image forming surface are at a second electrical potential, an image receiving surface at a third potential, different from the first potential by an image transfer potential difference, for receiving the developed image from the image forming surface and discharge apparatus for changing at least one of the first potential and the second potential to change the difference therebetween such that the potential difference between the second potential and the third potential is reduced to a value low enough so that substantially no electrical discharge occurs between the image receiving surface and the background portions.

In a preferred embodiment of the invention the discharge apparatus includes a light source for discharging the background portions of the photoconductive image forming surface. In a preferred embodiment of the invention the light source includes a light emitting diode array preferably including diodes which emit colored light wherein the colored light includes colors that are complementary to the colors of the pigmented toner.

In a preferred embodiment of the invention the light source includes a light source and at least one colored filter which preferably produces colored light which includes colors that are complementary to the colors of the pigmented toner.

In a preferred embodiment of the invention the development apparatus utilizes liquid toner including the toner particles and carrier liquid and wherein the development means includes an electrified squeegee roller for compacting the image and removing excess liquid.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be more fully understood and appreciated from the following detailed description, taken in conjunction with the drawings in which:

Fig. 1 is a generalized schematic illustration of a portion of an imaging system constructed and operative in accordance with a preferred embodiment of the invention.

Fig. 2 is a schematic illustration of the electrical potential on an image forming surface after development of a latent image thereon;

Fig. 3 shows the potential of background portions of the image forming surface as a function of the illuminating lamp voltage;

Fig. 4 shows A: the potential of the developed image and B: the optimal transfer potential on the intermediate transfer member, each as a function of the illuminating lamp voltage; and

Fig. 5 shows the difference between A: the optimal transfer potential and the potential of background portions of the image forming surface and B: the optimal transfer potential and the potential of the developed image, each as a function of the illuminat-

ing lamp voltage.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Reference is now made to Fig. 1 which illustrates a portion of a multicolor electrostatic imaging system constructed and operative in accordance with a preferred embodiment of the present invention. As seen in Fig. 1 there is provided an image bearing photoconductor surface 12 typically found on a rotating photoconductive drum 10. Drum 10 is driven in any appropriate manner (not shown) in the direction of arrow 18 past charging apparatus 14, preferably a corotron, adapted to charge surface 12 of photoconductive drum 10.

An image to be reproduced is focused by imaging apparatus 16 upon charged surface 12 at least partially discharging photoconductive drum 10 in the portions impinged upon by light to form an electrostatic latent image.

The electrostatic latent image normally includes image portions at a first electrical potential and background portions at another electrical potential. The present invention is especially useful where the image portions are discharged and the background portions remain at full charge. This type of discharge is referred to herein as "reversal" or "write-black" image formation.

Surface 12 typically comprises an organic photoconductor such as the Emerald OPC manufactured by IBM, or other suitable photoconductor. Photoconductor charging apparatus 14 may be any suitable charging apparatus such as is well known in the art. Imaging apparatus 16 may be modulated laser beam scanning apparatus, an optical focusing device for imaging an original on a drum or other imaging apparatus such as is known in the art.

Also associated with photoconductive drum 10 are a multicolor liquid developer spray assembly 20, a developing assembly 22, color specific cleaning blade assemblies 34, an electrified squeegee 26, and discharge apparatus 28 which are operative to develop the latent image to form a developed liquid toner image for transfer to an intermediate transfer member 30.

Developing assembly 22 preferably includes a development roller 38. Development roller 38 is preferably spaced by about 40-150 micrometers from photoconductive drum 10 at a development region 44 and is charged to an electrical potential intermediate that of the image and background portions of photoconductive drum 10. Development roller 38 is thus operative, to apply an electric field in development region 44 to aid development of the latent electrostatic image. In a typical system the background portions are at -900 Volts, the image portions are at -180 Volts and the development roller 38 is at -500 volts when a liquid developer comprising negative toner particles is utilized.

Development roller 38 typically rotates, as indicated by arrow 40, in the same sense as drum 10. This rotation

provides for the surface of drum 10 and development roller 38 to have oppositely directed velocities at development region 44. The rotation speed of development roller 38 is chosen such that development roller 38 acts inter alia as a metering device. This metering effect ensures that very little liquid carries past development region 44.

Multicolor liquid developer spray assembly 20 provides a spray of liquid toner containing electrically charged pigmented toner particles which can be preferably directed onto a portion of the roller 38 or alternatively onto a portion of photoconductive drum 10 or directly into development region 44.

A preferred toner for use in the present invention is prepared by mixing ten parts of Elvax II 5950T (E.I. du Pont) and five parts of Isopar L (Exxon) at low speed in a jacketed double planetary mixer connected to an oil heating unit set at 130°C for one hour. 5 parts of Isopar L are added to the mix and the whole is mixed for a further hour at high speed. Ten parts of Isopar L, preheated to 110°C, are added, and mixing is continued without heating until the temperature of the mixture drops to 40°C. Ninety grams of the resultant product is transferred to a 01 attritor (Union Process) together with 7.5 g. of Mogul L (Cabot) and 120 g. Isopar L. The mixture is ground for 24 hours with water cooling (≈20°C). The resultant toner particles have a median (by weight) diameter of about 2.1 μm. The resultant material is diluted to a non-volatile solids content of 1.5%, using Isopar L and charge director as known in the art is added to charge the toner particles.

Other appropriate liquid toners may alternatively be employed. For colored liquid developers, carbon black is replaced by color pigments as is well known in the art. In an alternate preferred embodiment of the invention the latent image is developed using powder toner as is known in the art.

Color specific cleaning blade assemblies 34 are operatively associated with development roller 38 for separate removal of residual amounts of each colored toner remaining thereon after development. Each one of blade assemblies 34 is selectably brought into operative association with development roller 38 only when toner of a color corresponding thereto is supplied to development region 44 by spray assembly 20. The construction and operation of cleaning blade assembly 34 is more fully described in PCT International Publication number WO 90/14619, the disclosure of which is incorporated herein by reference.

Each of cleaning blade assemblies 34 includes a toner directing member 52 which serves to direct the toner removed by the cleaning blade assemblies 34 from the development roller 38 to respective collecting tanks 54, 56, 58 and 60 and thus to prevent contamination of the various developers by mixing of the colors. The toner thus collected is recycled to corresponding toner reservoirs (not shown) for reuse. A final toner collection member 62 always engages the development

roller 38 and the toner collected thereby is supplied to a clear liquid reservoir (not shown) via a collecting tank 64 and a separator (not shown) which is operative to separate relatively clean carrier liquid from the various colored toner particles. The separator may be typically of the type described in PCT International Publication Number WO90/10896.

An electrically biased squeegee roller 26 such as that described in U.S. Patent 4,286,039, is preferably urged against the surface of drum 10 and is operative to remove substantially all of the liquid carrier from the background portions and to compact the image and remove liquid carrier therefrom in the image portions. Squeegee roller 26 is preferably formed of resilient slightly conductive polymeric material, and is charged to a potential of several hundred to a few thousand volts with a polarity such that an electric field is created between squeegee roller 26 and drum 10 which drives the charged toner particles toward drum 10. Squeegee roller 26 is also operative to further charge the toner particles and photoconductor surface 12 as described below.

Transfer of the developed image to an intermediate transfer member 30 (or to a final substrate) from drum 10 generally requires the imposition of an electric field between drum 10 and the surface of intermediate transfer member 30. It has been found that if a potential sufficient to effect substantially complete transfer of the developed image is impressed on intermediate transfer member 30, then a high potential difference is established between the intermediate transfer member and background portions on the drum 10 causing electrical discharge therebetween.

In a preferred embodiment of the invention, discharge apparatus 28, which is described in more detail below, is operative to irradiate drum 10 with light characterized by a predetermined intensity and spectrum to reduce electrical discharge between drum 10 and intermediate transfer member 30.

Intermediate transfer member 30 may be any suitable intermediate transfer member as is known in the art such as those described in PCT International Publication WO 90/08984 and is maintained at a voltage and temperature suitable for electrostatic transfer of the image thereto from drum 10 and therefrom to a final substrate 72 such as paper.

Intermediate transfer member 30 is preferably associated with a pressure roller 71 for transfer of the image onto final substrate 72 preferably by heat and pressure. In a preferred embodiment of the invention intermediate transfer member 30 is coated with a non-stick, preferably a silicone, coating to aid in subsequent transfer of the developed image therefrom to substrate 72.

Cleaning apparatus 32 is operative to clean the photoconductor surface 12 and includes a cleaning roller 74, a sprayer 76 to spray a non polar cleaning liquid to assist in the cleaning process and a wiper blade 78 to complete the cleaning of surface 12. Cleaning roller 74, which may be formed of any synthetic resin known

in the art for this purpose, is driven in a direction of rotation indicated by arrow 80 which is the same as the direction of rotation of drum 10.

Any residual charge left on the surface of drum 10 is removed by flooding surface 12 with light from a neutralizing lamp assembly 36.

In accordance with a preferred embodiment of the invention, after developing each image in a given color, the single color image is transferred to intermediate transfer member 30. Subsequent images in different colors are sequentially transferred in alignment with the previous image onto intermediate transfer member 30. When all of the desired images have been transferred thereto, the complete multi-color image is transferred from transfer member 30 to substrate 72.

Alternatively, each single color image is transferred to the substrate directly after its transfer to intermediate transfer member 30. In this case the substrate is fed through the machine once for each color or is held on pressure roller 71 and contacted with intermediate transfer member 30 during each image transfer operation.

Reference is now made to Fig. 2 which illustrates typical post-development electrical potentials (before application of squeegee roller 26) on the surface of drum 10 at background portions 110 ($\approx$ 900 volts) and image portions 112 ($\approx$ 180 volts) and on the surface of the developed image 114 ($\approx$ 450 volts). These potentials are not fixed values but rather depend on charge on the photoconductor before development, spectrum and intensity of the image projected by imaging apparatus 16, photoconductor response characteristics, process speed, development roller 38 potential, the toner charge, mobility and viscosity and other factors.

To assure good transfer of the charged toner particles in the developed image from drum 10 to intermediate transfer member 30 a suitable potential difference must be maintained between the surface of intermediate transfer member 30 and image portions 112 on the surface of drum 10. The magnitude of this potential difference is dependent on a number of factors such as the type of toner, the toner layer charge and thickness and the relative affinity of the toner for surface 12 and the surface of intermediate transfer member 30. The magnitude of this potential difference is not believed to be a function of the absolute potential on image portions 112, and a range of potential differences, near an optimum potential difference, give good results.

It is desirable to reduce the potential difference between the surface of intermediate transfer member 30 and background portions 110 of surface 12 to reduce electrical discharge therebetween. This electrical discharge is believed to cause deterioration of the non-stick properties of the silicone surface coating of intermediate transfer member 30 and damage to the photoconductor.

It might have been thought that flooding drum 10 with high intensity light would discharge background portions 110 and be operative to significantly reduce the

discharge. The present inventors have found, however, that light which penetrates the developed image to image portions 112 which underlie the developed image causes not only a reduction in the potential of image portions 112, as expected, but can actually cause image portions 112 to become positively charged in the presence of the negatively charged toner image overlying them. Since the potential of intermediate transfer member 30 must also be adjusted to account for the change in potential of image portions 112, it has been found that the potential difference between background portions 110 and the surface of intermediate transfer member 30 still causes electrical discharge.

In such a case and in a particular example thereof, without any light treatment but after subjecting the image to squeegee roller 26, the optimum transfer potential of intermediate transfer member 30 is -400 volts and the potential of background portions 110 is -1220 volts, resulting in a 820 volt potential difference therebetween. The developed image is at a potential of -960 volts.

After irradiation of drum 10 with strong light, the potential at the developed image falls to -250 volts, and the optimum transfer potential is +400 volts. The background had a potential of about -130 volts resulting in a potential difference between the background portions of the drum and the intermediate transfer member of 530 volts. At this potential difference electrical discharge still occurs. It is believed that for even stronger irradiation, the potential difference increases further until a saturation value is reached.

As previously noted, discharge apparatus 28, is operative to irradiate drum 10 with light characterized by a predetermined intensity and spectrum to reduce electrical discharge between drum 10 and the surface of intermediate transfer member 30. The present inventors have found that controlled irradiation of drum 10 before transfer of the developed image therefrom can allow for optimal transfer of the image without electrical discharge between background portions 110 and intermediate transfer member 30. This controlled irradiation is chosen to be strong enough to substantially discharge background portions 110 to a potential near zero and weak enough so that the attenuated light which passes through the developed image changes the potential of image portions 112 underlying the developed image to a substantially lesser degree.

Reference is made to Figs. 3-5 which illustrate the effect of various amount of light on the various potentials in the system, in accordance with a preferred embodiment of the invention.

Curve "A" of Fig. 3 shows the potential on background portions 110 after illuminating drum 10 with light of varying intensities from a light source comprising a row of miniature incandescent lamps. The light intensity is referenced by the voltage on the light source (i.e. the lamps). Curve "B" shows the potential on background portions 110 which are subjected to squeegee roller 26 electrified to a potential of -2400 volts before they are

illuminated.

Curve "A" of Fig. 4 shows the potential on the developed image 114 as a function of light source voltage, after subjecting the image to squeegee roller 26 at a potential of -2400 volts. As used herein the term "developed image" includes an image which may have been subjected to a squeegee roller or to other post-formation treatment, other than irradiation by light. If the squeegee roller is not used, then for zero light intensity, the potential on the developed image is approximately 500 volts more positive than shown on curve A, i.e., about -450 Volts.

It is believed that the potential change caused by the electrified squeegee roller is in part the result of charging of image portions 112 of drum 10 and in part the result of the addition of further negative charge to the already negatively charged toner particles.

It is noted, however, that irradiation by light causes a change only in the potential of image portions 112 and is not believed to be effective in changing the charge on the toner particles. Thus any change in the image potential of developed image 114 which is caused by light is believed to be caused by changes in the potential of image portions 112.

Also plotted in Fig. 4 as curve "B" is the potential on the intermediate transfer member for "optimal" transfer of the image from the drum to the intermediate transfer member.

Curve "A" of Fig. 5 is the potential difference between background portion 110 and the intermediate transfer member 30 at the optimal transfer potential as a function of light source voltage (i.e., curve "B" of Fig. 3 minus curve "B" of Fig. 4). Curve "B" of Fig. 5 is the potential difference between developed image 114 and intermediate transfer member ("ITM") 30 as a function of light source voltage (i.e., curve "A" of Fig. 4 minus curve "B" of Fig. 4). It should be noted that the image-ITM potential difference is essentially constant, within the ± 50 volt estimated error in measurement of surface potential. This constancy of potential difference required for optimal transfer supports the above mentioned premises that the potential difference required for transfer is not a function of the absolute image portion potential and that light does not change the charge of the toner particles.

Furthermore the image transfer "quality" does not appear to be a function of the light level. On the other hand, as the light level is increased the potential difference between the intermediate transfer member 30 and the background portions 110, which starts at a high value, first falls to a minimum value and then rises again as the light level is further increased.

It should be noted that the potential of image portion 112 is believed to be several hundred volts lower (i.e., more positive) than the potential of the image 114 so that the potential difference between image portion 112 and the ITM is believed to be in the range of approximately 70-350 volts.

For a particular range of light intensities, the potential difference between background portions 110 and the surface of intermediate transfer member 30 is reduced below the minimum producing discharge. As is well known, the discharge voltage between two flat surfaces has a high value for very small and for very large spacings between the surfaces. For intermediate spacings the discharge voltage reaches a minimum, which for air at standard pressure is approximately 360 volts (at a spacing of approximately 8 micrometers). The curve of discharge voltage as a function of spacing is generally known as the Paschen curve and the minimum voltage is called the "minimum of the Paschen Curve". For flat surfaces, discharge cannot occur if the potential difference between the surfaces is less than the minimum of the Paschen Curve. While it is especially preferred to utilize a background-ITM voltage lower than this lowest minimum value, it is believed that somewhat higher potential differences, while they may cause some discharge, do not cause substantial enough discharge to substantially damage the photoconductor or the non-stick coating of the intermediate transfer member.

As can be seen from Fig. 5, for the particular case discussed, there is a range of lamp voltages (and corresponding light intensities), which results in background-ITM potential differences below 360 volts. It is believed that this is a relatively safe value for substantial elimination of discharge. Optimally, the amount of light is adjusted to give a minimum potential difference.

The light source employed in the discharge apparatus 28 in the above described experiments is a row of 14 series connected 0.79 watt incandescent lamps (@ 7.86 VAC each), spaced 26 mm apart and spaced 8 mm from the drum. The drum velocity is 60 cm/sec and a black image having a transmission optical density of approximately 0.7 is used.

In a preferred embodiment of the invention light having a color which is complementary to the color of the image on the drum 10 is used to illuminate drum 10. In this case the amount of light transmitted through the image to image portion 112 is substantially reduced and for a particular light intensity, the background-ITM potential difference may be reduced to a very low value. The source of light may be a series of light emitting diodes which emit colored light complementary to the color of the toner particles in the image. Alternatively, other sources of colored light such as cold cathode discharge sources can be utilized in the practice of the invention. Alternatively, a source of white light with appropriately colored filters is utilized to produce the complementary colors.

The amplitude of each of the sources is preferably matched to the toner optical density and photoreceptor characteristics by varying the intensity of the white light or by use of neutral density filters.

The white light may be from incandescent lamps or may be from fluorescent lamps.

It should be noted that the lower the transparency

of the pigments used (i.e., the higher the density of the image for the given color), the lower the effect on the potential of the portions of the drum underlying the image. For very dense images, the possibility exists that very low, even zero, potential difference between the surface of the intermediate transfer member and the background portion of drum 10 can be achieved at the optimum transfer voltage. Under certain circumstances the minimum of the curve of background-ITM potential difference can reverse sign.

While the invention has been described utilizing a drum photoconductor, a roller developer, liquid toner and for transfer utilizing an intermediate transfer member, it is understood that the invention can be practiced utilizing a belt developer and/or a belt photoconductor, any appropriate liquid or dry toner as is known in the art and/or direct transfer from drum 10 to substrate 72.

Furthermore, while the invention has been described utilizing a controlled source of light for differentially discharging the image and background portions of the image forming surface, other means for selectively discharging are within the scope of the invention.

For a positively chargeable photoconductor, using positive toner particles in a reverse development mode, similar results will be obtained, with only the signs of the potentials reversed.

It will be appreciated by persons skilled in the art that the present invention is not limited by what has been particularly shown and described hereinabove. Rather the scope of the present invention is defined only by the claims which follow:

Claims

1. Imaging apparatus comprising:

an image forming surface (10, 12) having an imaging area;

image forming means (16) for defining an electrostatic latent image in the imaging area, the latent image comprising image portions (112) and background portions (110) at different potentials, said background portions being the most highly charged portions of the imaging area; and

development means (20, 22) for developing the electrostatic latent image, using electrically charged pigmented toner particles to form a developed image (114) overlying the image portions, whereby the developed image on the image forming surface is at a first electrical potential and the background portions on the image forming surface are at a second electrical potential, characterized in that:

the development means develops the electrostatic image in a reversal mode; and in that the imaging apparatus includes:

a source of electromagnetic radiation (28) for at least partially discharging the image forming surface downstream of said development means.

2. Imaging apparatus according to claim 1 wherein the source of electromagnetic radiation is operative to discharge the image forming surface so that the developed image is at a third electrical potential and the background portions are at a fourth potential, and further comprising:

an image receiving surface (30) at a fifth potential, operative for receiving the developed image from the image forming surface, wherein the difference between the fourth potential and the fifth potential is low enough such that substantially no electrical discharge occurs between the image receiving surface and the background portions.

3. Imaging apparatus according to claim 1 and further comprising:

an image receiving surface (30) at a third potential, different from the first potential by an image transfer potential difference, for receiving the developed image from the image forming surface,

wherein the source of electromagnetic radiation is operative for changing at least one of the first potential and the second potential to change the difference therebetween whereby the absolute value of the potential difference between the second potential and the third potential is reduced to a value below about 360 volts.

4. Imaging apparatus according to claim 1 and further comprising:

an image receiving surface (30) at a third potential, different from the first potential by an image transfer potential difference, for receiving the developed image from the image forming surface,

wherein the source of electromagnetic radiation is operative for changing at least one of the first potential and the second potential to change the difference therebetween such that the potential difference between the second potential and the third potential is reduced to a value low enough so that substantially no electrical discharge occurs between the image receiving surface and the background portions.

5. Apparatus according to claim 3 or claim 4 wherein the image transfer potential difference is substantially the same as the image transfer potential difference required in the absence of the electromag-

netic radiation.

6. Apparatus according to any of claims 2-5 wherein the image receiving surface (30) is an image transfer surface adapted to receive developed images from the image forming surface and to transfer them to a further surface. 5
7. Apparatus according to any of the preceding claims wherein the image forming surface (12) is a photoconductive image forming surface. 10
8. Apparatus according to claim 7 wherein the source of electromagnetic radiation (28) includes a light source for discharging the background portions of the photoconductive image forming surface. 15
9. Apparatus according to claim 8 wherein the light source included a light emitting diode array. 20
10. Apparatus according to claim 9 wherein the light emitting diode array includes diodes which emit colored light and wherein the colored light includes colors that are complementary to the colors of the pigmented toner. 25
11. Apparatus according to claim 8 wherein the light source includes a light source and at least one colored filter. 30
12. Apparatus according to claim 11 wherein the light source and the at least one colored filter produce colored light which includes colors that are complementary to the colors of the pigmented toner. 35
13. Apparatus according to any of the preceding claims wherein the development means is adapted to utilize liquid toner comprising the toner particles and carrier liquid and wherein the development means further includes an electrified squeegee roller (26) for compacting the image and removing excess liquid. 40

14. An imaging method comprising the steps of: 45

defining an electrostatic latent image on an image forming surface, the latent image comprising image portions and background portions at different potentials; and
developing the electrostatic latent image, using electrically charged pigmented toner particles to form a developed image overlying the image portions, whereby the developed image on the image forming surface is at a first electrical potential and the background portions on the image forming surface are at a second electrical potential; 50 55

characterized in that:

the step of developing develops the electrostatic latent image in a reversal mode; and
the method comprises the step of:
at least partially discharging the image forming surface by illuminating the image forming surface containing the developed image with electromagnetic radiation.

15. A method according to claim 14 wherein the step of at least partially discharging includes the step of discharging the image forming surface so that the developed image is at a third electrical potential and the background portions are at a fourth potential, and comprising the further step of:

transferring the developed image from the image forming surface to image receiving surface which is electrified to a fifth potential, wherein the difference between the fourth potential and the fifth potential is low enough such that substantially no electrical discharge occurs between the image receiving surface and the background portions.

- 25 16. A method according to claim 14 and comprising the step of:

transferring the developed image from the image forming surface to an image receiving surface at a third potential, different from the first potential by an image transfer potential difference, for receiving the developed image from the image forming surface,
wherein the step of at least partially discharging is operative for changing at least one of the first potential and the second potential whereby the absolute value of the potential difference between the second potential and the third potential is reduced to a value below about 360 volts.

17. A method according to claim 14 and comprising the step of:

transferring the developed image from the image forming surface to an image receiving surface at a third potential, different from the first potential by an image transfer potential difference, for receiving the developed image from the image forming surface,
wherein the step of at least partially discharging is operative for changing at least one of the first potential and the second potential whereby the absolute value of the potential difference between the second potential and the third potential is reduced to a value low enough so that substantially no electrical discharge occurs between the image receiving surface and the background portions.

18. A method according to claim 16 or claim 17 wherein the image transfer potential difference is substantially the same as the image transfer potential difference which would be required in the absence of step of at least partially discharging. 5
19. A method according to any of claims 15-18 wherein the step of transferring includes the step of:
first transferring the developed image to an image transfer surface adapted to receive developed images from the image forming surface and to transfer them to a further surface. 10
20. A method according to any of claims 14-19 wherein the image forming surface is a photoconductive image forming surface. 15
21. A method according to claim 20 wherein the step of at least partially discharging includes the step of utilizing a light source for discharging the background portions of the photoconductive image forming surface. 20
22. A method according to claim 21 wherein the light source includes a light emitting diode array. 25
23. A method according to claim 22 wherein the step of at least partially discharging includes the step of utilizing light emitting diodes which emit colored light and wherein the colored light includes colors that are complementary to the colors of the pigmented toner. 30
24. A method according to claim 21 wherein the step of at least partially discharging includes the step of providing a light source and at least one colored filter. 35
25. A method according to claim 21 or claim 24 wherein the step of at least partially discharging includes the step of illuminating with colors that are complementary to the colors of the pigmented toner. 40
26. A method according to any of claims 14-25 wherein the step of development utilizes liquid toner comprising the toner particles and carrier liquid and wherein the step of developing further comprises the step of compacting the image and removing excess liquid therefrom. 45
50

Patentansprüche

1. Bilderzeugungsvorrichtung mit:
einer bilderzeugenden Oberfläche (10, 12), die eine Abbildungsfläche aufweist;
einer bilderzeugenden Einrichtung (16) zum

Definieren eines elektrostatischen Latentbildes in der Abbildungsfläche, wobei das Latentbild Bildbereiche (112) und Hintergrundbereiche (110) auf unterschiedlichen Potentialen umfaßt, wobei die Hintergrundbereiche die höchstgeladenen Bereiche der Abbildungsfläche sind; und
einer Entwicklungseinrichtung (20, 22) zum Entwickeln des elektrostatischen Latentbildes unter Verwendung elektrisch geladener pigmentierter Tonerteilchen, um ein die Bildbereiche überlagerndes, entwickeltes Bild (114) zu erzeugen, wobei das entwickelte Bild auf der bilderzeugenden Oberfläche auf einem ersten elektrischen Potential liegt und die Hintergrundbereiche auf der bilderzeugenden Oberfläche auf einem zweiten elektrischen Potential liegen, dadurch gekennzeichnet, daß:
die Entwicklungseinrichtung das elektrostatische Bild in einem Umkehrmodus entwickelt; und daß die Bilderzeugungsvorrichtung umfaßt:
eine elektromagnetische Strahlungsquelle (28) zum wenigstens teilweisen Entladen der bilderzeugenden Oberfläche stromabwärts der Entwicklungseinrichtung.

2. Bilderzeugungsvorrichtung nach Anspruch 1, in welcher die elektromagnetische Strahlungsquelle dahin gehend wirksam ist, die bilderzeugende Oberfläche so zu entladen, daß das entwickelte Bild auf einem dritten elektrischen Potential liegt und die Hintergrundbereiche auf einem vierten elektrischen Potential liegen, und ferner umfassend:

eine bildaufnehmende Oberfläche (30) auf einem fünften Potential zur betriebsmäßigen Aufnahme des entwickelten Bildes von der bilderzeugenden Oberfläche, wobei die Differenz zwischen dem vierten Potential und dem fünften Potential gering genug ist, derart, daß zwischen der bildaufnehmenden Oberfläche und den Hintergrundbereichen im wesentlichen keine elektrische Entladung auftritt.

3. Bilderzeugungsvorrichtung nach Anspruch 1 und ferner mit:

einer bildaufnehmenden Oberfläche (30) auf einem dritten Potential, das sich von dem ersten Potential durch eine Bildübertragungspotentialdifferenz unterscheidet, zum Aufnehmen des entwickelten Bildes von der bilderzeugenden Oberfläche, wobei die elektromagnetische Strahlungsquelle eine Änderung wenigstens des ersten Potentials oder des zweiten Potentials bewirkt, um die Differenz zwischen beiden zu verändern, wodurch der absolute Wert der Potentialdifferenz zwischen dem zweiten Potential und dem

dritten Potential auf einen Wert unterhalb etwa 360 Volt verringert ist.

4. Bilderzeugungsvorrichtung nach Anspruch 1 und ferner mit:

einer bildaufnehmenden Oberfläche (30) auf einem dritten Potential, das sich von dem ersten Potential durch eine Bildübertragungspotentialdifferenz unterscheidet, zum Aufnehmen des entwickelten Bildes von der bilderzeugenden Oberfläche, wobei die elektromagnetische Strahlungsquelle eine Änderung wenigstens des ersten Potentials oder des zweiten Potentials bewirkt, um die Differenz zwischen beiden derart zu verändern, daß die Potentialdifferenz zwischen dem zweiten Potential und dem dritten Potential auf einen ausreichend niedrigen Wert verringert ist, so daß zwischen der bildaufnehmenden Oberfläche und den Hintergrundbereichen im wesentlichen keine elektrische Entladung auftritt.

5. Vorrichtung nach Anspruch 3 oder 4, in welcher die Bildübertragungspotentialdifferenz im wesentlichen die gleiche Bildübertragungspotentialdifferenz ist, die bei Nichtvorliegen der elektromagnetischen Strahlung erforderlich ist.

6. Vorrichtung nach einem der Ansprüche 2-5, in welcher die bildaufnehmende Oberfläche (30) eine Bildübertragungsoberfläche ist, die so ausgebildet ist, daß sie entwickelte Bilder von der bilderzeugenden Oberfläche aufnehmen und diese auf eine weitere Oberfläche übertragen kann.

7. Vorrichtung nach einem der vorstehenden Ansprüche, in welcher die bildtragende Oberfläche (12) eine photoleitende, bilderzeugende Oberfläche ist.

8. Vorrichtung nach Anspruch 7, in welcher die elektromagnetische Strahlungsquelle (28) eine Lichtquelle zum Entladen der Hintergrundbereiche der photoleitfähigen, bilderzeugenden Oberfläche umfaßt.

9. Vorrichtung nach Anspruch 8, in welcher die Lichtquelle eine lichtemittierende Diodenanordnung umfaßt.

10. Vorrichtung nach Anspruch 9, in welcher die lichtemittierende Diodenanordnung Dioden umfaßt, welche Farblicht emittieren und in welcher das Farblicht Farben umfaßt, die den Farben des pigmentierten Toners komplementär sind.

11. Vorrichtung nach Anspruch 8, in welcher die Licht-

quelle eine Lichtquelle und wenigstens einen Farbfilter umfaßt.

12. Vorrichtung nach Anspruch 11, in welcher die Lichtquelle und der wenigstens eine Farbfilter ein Farblicht erzeugt, welches Farben umfaßt, die den Farben des pigmentierten Toners komplementär sind.

13. Vorrichtung nach einem der vorstehenden Ansprüche, in welcher die Entwicklungseinrichtung so ausgebildet ist, daß sie Flüssigtoner verwenden kann, der Tonerteilchen und eine Trägerflüssigkeit umfaßt, und in welcher die Entwicklungseinrichtung ferner eine elektrisierte Abstreicherwalze (26) zum Verdichten des Bildes und Entfernen überschüssiger Flüssigkeit umfaßt.

14. Bilderzeugungsverfahren mit den Schritten:

Definieren eines elektrostatischen Latentbildes auf einer bilderzeugenden Oberfläche, wobei das Latentbild Bildbereiche und Hintergrundbereiche auf unterschiedlichen Potentialen aufweist und

Entwickeln des elektrostatischen Latentbildes unter Verwendung elektrisch geladener, pigmentierter Tonerteilchen, um ein die Bildbereiche überlagerndes, entwickeltes Bild zu erzeugen, wodurch das entwickelte Bild auf der bilderzeugenden Oberfläche auf einem ersten elektrischen Potential liegt und die Hintergrundbereiche auf der bilderzeugenden Oberfläche auf einem zweiten elektrischen Potential liegen; dadurch gekennzeichnet, daß:

der Schritt des Entwickelns das elektrostatische Latentbild in einem Umkehrmodus entwickelt; und das Verfahren den Schritt umfaßt: wenigstens teilweises Entladen der bilderzeugenden Oberfläche durch Bestrahlen der das entwickelte Bild enthaltenden, bilderzeugenden Oberfläche mit elektromagnetischer Strahlung.

15. Verfahren nach Anspruch 14, in welchem der Schritt des wenigstens teilweisen Entladens den Schritt umfaßt des Entladens der bilderzeugenden Oberfläche, so daß das entwickelte Bild auf einem dritten elektrischen Potential liegt und die Hintergrundbereiche auf einem vierten Potential liegen, und mit dem weiteren Schritt:

Übertragen des entwickelten Bildes von der bilderzeugenden Oberfläche auf eine bildaufnehmende Oberfläche, welche auf ein fünftes Potential elektrisiert ist, wobei die Differenz zwischen dem vierten Potential und dem fünften Potential gering genug ist, derart, daß zwischen der bildaufnehmenden Oberfläche und den Hintergrundbereichen im wesentlichen keine elektrische Entladung auftritt.

16. Verfahren nach Anspruch 14 und mit dem Schritt:

Übertragen des entwickelten Bildes von der bilderzeugenden Oberfläche auf eine bildaufnehmende Oberfläche mit einem dritten Potential, das sich von dem ersten Potential durch eine Bildübertragungspotentialdifferenz unterscheidet, zum Aufnehmen des entwickelten Bildes von der bilderzeugenden Oberfläche, wobei der Schritt des wenigstens teilweisen Entladens eine Änderung wenigstens des ersten Potentials oder des zweiten Potentials bewirkt, wodurch der absolute Wert der Potentialdifferenz zwischen dem zweiten Potential und dem dritten Potential auf einen Wert unterhalb etwa 360 Volt verringert wird.

17. Verfahren nach Anspruch 14 und mit dem Schritt:

Übertragen des entwickelten Bildes von der bilderzeugenden Oberfläche auf eine bildaufnehmende Oberfläche mit drittem Potential, das sich von dem ersten Potential durch eine Bildübertragungspotentialdifferenz unterscheidet, zum Aufnehmen des entwickelten Bildes von der bilderzeugenden Oberfläche, wobei der Schritt des wenigstens teilweisen Entladens eine Änderung wenigstens des ersten Potentials oder des zweiten Potentials bewirkt, wodurch der absolute Wert der Potentialdifferenz zwischen dem zweiten Potential und dem dritten Potential auf einen so ausreichend geringen Wert verringert wird, daß zwischen der bildaufnehmenden Oberfläche und den Hintergrundbereichen im wesentlichen keine elektrische Entladung auftritt.

18. Verfahren nach Anspruch 16 oder Anspruch 17, in welchem die Bildübertragungspotentialdifferenz im wesentlichen die gleiche ist wie die Bildübertragungspotentialdifferenz, welche bei Nichtvorhandensein des Schrittes des wenigstens teilweisen Entladens erforderlich wäre.

19. Verfahren nach einem der Ansprüche 15-18, in welchem der Schritt des Übertragens den Schritt umfaßt:

erstes Übertragen des entwickelten Bildes auf eine Bildübertragungsoberfläche, die so ausgebildet ist, daß sie die entwickelten Bilder von der bilderzeugenden Oberfläche aufnimmt und diese auf eine weitere Oberfläche überträgt.

20. Verfahren nach einem der Ansprüche 14-19, in welchem die bilderzeugende Oberfläche eine photoleitfähige, bilderzeugende Oberfläche ist.

21. Verfahren nach Anspruch 20, in welchem der

Schritt des wenigstens teilweisen Entladens den Schritt des Verwendens einer Lichtquelle zum Entladen der Hintergrundbereiche der photoleitfähigen, bilderzeugenden Oberfläche umfaßt.

22. Verfahren nach Anspruch 21, in welchem die Lichtquelle eine lichtemittierende Diodenanordnung umfaßt.

23. Verfahren nach Anspruch 22, in welchem der Schritt des wenigstens teilweisen Entladens den Schritt des Verwendens von lichtemittierenden Dioden umfaßt, welche Farblicht emittieren und in welchem das Farblicht Farben umfaßt, die den Farben des pigmentierten Toners komplementär sind.

24. Verfahren nach Anspruch 21, in welchem der Schritt des wenigstens teilweisen Entladens den Schritt des Verwendens einer Lichtquelle und wenigstens eines Farbfilters umfaßt.

25. Verfahren nach Anspruch 21 oder Anspruch 24, in welchem der Schritt des wenigstens teilweisen Entladens den Schritt des Bestrahleins mit Farben umfaßt, die den Farben des pigmentierten Toners komplementär sind.

26. Verfahren nach einem der Ansprüche 14 bis 25, in welchem der Entwicklungsschritt Flüssigtoner verwendet, der die Tonerteilchen und Trägerflüssigkeit umfaßt und in welchem der Schritt des Entwickelns ferner den Schritt des Verdichtens des Bildes und Entferns von überschüssiger Flüssigkeit von diesem umfaßt.

Revendications

1. Appareil de formation d'image comprenant :

- une surface (10, 12) de formation d'image comportant une région de formation d'image,
- un moyen (16) de formation d'image pour définir une image électrostatique latente dans la région de formation d'image, l'image latente comprenant des parties d'image (112) et des parties d'arrière-plan (110) se trouvant à des potentiels différents, lesdites parties d'arrière-plan étant les parties les plus fortement chargées de la région de formation d'image, et
- des moyens de révélation (20, 22) pour révéler l'image électrostatique latente, qui utilisent des particules de toner pigmentées et électriquement chargées pour former une image révélée (114) recouvrant les parties d'image, de telle sorte que l'image révélée se trouvant sur la surface de formation d'image est à un premier potentiel électrique et les parties d'arrière-plan se

trouvant sur la surface de formation d'image sont à un second potentiel électrique,

caractérisé en ce que :

- les moyens de révélation révèlent l'image électrostatique en mode d'inversion,
- et en ce que l'appareil de formation d'image comprend une source de rayonnement électromagnétique (28) pour décharger au moins partiellement la surface de formation d'image en aval desdits moyens de révélation.

2. Appareil de formation d'image selon la revendication 1, dans lequel la source de rayonnement électromagnétique sert à décharger la surface de formation d'image de telle sorte que l'image révélée soit à un troisième potentiel électrique et que les parties d'arrière-plan soient à un quatrième potentiel électrique, et comprenant en outre une surface (30) de réception d'image se trouvant à un cinquième potentiel, servant à recevoir l'image révélée en provenance de la surface de formation d'image, la différence entre le quatrième et le cinquième potentiel étant suffisamment faible pour qu'il ne se produise pratiquement pas de décharge électrique entre la surface de réception d'image et les parties d'arrière-plan.

3. Appareil de formation d'image selon la revendication 1, comprenant en outre une surface (30) de réception d'image se trouvant à un troisième potentiel, qui diffère du premier potentiel par une différence de potentiel de transfert d'image, destinée à recevoir l'image révélée en provenance de la surface de formation d'image, et dans lequel la source de rayonnement électromagnétique sert à modifier l'un au moins des premier et deuxième potentiels pour modifier la différence entre eux de sorte que la valeur absolue de la différence de potentiel entre le deuxième potentiel et le troisième potentiel soit réduite à une valeur inférieure à environ 360 volts.

4. Appareil de formation d'image selon la revendication 1, comprenant en outre une surface (30) de réception d'image se trouvant à un troisième potentiel, qui diffère du premier potentiel par une différence de potentiel de transfert d'image, destinée à recevoir l'image révélée en provenance de la surface de formation d'image, et dans lequel la source de rayonnement électromagnétique sert à modifier l'un au moins des premier et deuxième potentiels pour modifier la différence entre eux de sorte que la différence de potentiel entre les deuxième et troisième potentiels soit réduite à une valeur suffisamment faible pour qu'il ne se produise pratiquement pas de décharge électrique entre la surface de réception d'image et les parties d'arrière-plan.

5. Appareil selon la revendication 3 ou la revendication 4, dans lequel la différence de potentiel de transfert d'image est sensiblement la même que la différence de potentiel de transfert d'image requise en l'absence du rayonnement électromagnétique.

6. Appareil selon l'une quelconque des revendications 2 à 5, dans lequel la surface (30) de réception d'image est une surface de transfert d'image apte à recevoir des images révélées en provenance de la surface de formation d'image et à les transférer sur une autre surface.

7. Appareil selon l'une quelconque des précédentes revendications, dans lequel la surface (12) de formation d'image est une surface de formation d'image photoconductrice.

8. Appareil selon la revendication 7, dans lequel la source de rayonnement électromagnétique (28) comprend une source de lumière pour décharger les parties d'arrière-plan de la surface de formation d'image photoconductrice.

9. Appareil selon la revendication 8, dans lequel la source de lumière comprend un réseau de diodes électroluminescentes.

10. Appareil selon la revendication 9, dans lequel le réseau de diodes électroluminescentes comprend des diodes qui émettent une lumière colorée et dans lequel la lumière colorée contient des couleurs qui sont complémentaires des couleurs du toner pigmenté.

11. Appareil selon la revendication 8, dans lequel la source de lumière comprend une source de lumière et au moins un filtre coloré.

12. Appareil selon la revendication 11, dans lequel la source de lumière et le filtre coloré au nombre d'au moins un produisent de la lumière colorée qui contient des couleurs complémentaires des couleurs du toner pigmenté.

13. Appareil selon l'une quelconque des précédentes revendications, dans lequel le moyen de révélation est apte à utiliser du toner liquide comprenant les particules de toner et un liquide porteur et dans lequel le moyen de révélation comprend en outre un rouleau presseur électrofilé (26) pour compacter l'image et éliminer l'excès de liquide.

14. Procédé de formation d'image comprenant les étapes consistant à :

- définir une image électrostatique latente sur une surface de formation d'image, l'image la-

tente comprenant des parties d'image et des parties d'arrière-plan se trouvant à des potentiels différents, et

- révéler l'image électrostatique latente en utilisant des particules de toner pigmentées et électriquement chargées pour former une image révélée qui recouvre les parties d'image, de sorte que l'image révélée sur la surface de formation d'image est à un premier potentiel électrique et les parties d'arrière-plan sur la surface de formation d'image sont à un second potentiel électrique,

caractérisé en ce que :

- l'étape de révélation révèle l'image électrostatique latente en mode d'inversion, et
- le procédé comprend l'étape consistant à décharger au moins partiellement la surface de formation d'image par éclairage de la surface de formation d'image contenant l'image révélée avec un rayonnement électromagnétique.

15. Procédé selon la revendication 14, dans lequel l'étape de déchargement au moins partiel comprend l'étape consistant à décharger la surface de formation d'image de telle sorte que l'image révélée soit à un troisième potentiel électrique et que les parties d'arrière-plan soient à un quatrième potentiel électrique, et comprenant l'étape supplémentaire consistant à transférer l'image révélée de la surface de formation d'image à une surface de réception d'image qui est chargée à un cinquième potentiel, la différence entre le quatrième potentiel et le cinquième potentiel étant suffisamment faible pour qu'il ne se produise pratiquement pas de décharge électrique entre la surface de réception d'image et les parties d'arrière-plan.
16. Procédé selon la revendication 14, comprenant l'étape consistant à transférer l'image révélée de la surface de formation d'image à une surface de réception d'image se trouvant à un troisième potentiel, qui diffère du premier potentiel par une différence de potentiel de transfert d'image, destinée à recevoir l'image révélée en provenance de la surface de formation d'image, et dans lequel l'étape de déchargement au moins partiel sert à modifier l'un au moins des premier et deuxième potentiels de telle sorte que la valeur absolue de la différence de potentiel entre le second potentiel et le troisième potentiel soit réduite à une valeur inférieure à environ 360 volts.
17. Procédé selon la revendication 14, comprenant l'étape consistant à transférer l'image révélée de la surface de formation d'image à une surface de réception d'image se trouvant à un troisième poten-

tiel, qui diffère du premier potentiel par une différence de potentiel de transfert d'image, destinée à recevoir l'image révélée en provenance de la surface de formation d'image, et dans lequel l'étape de déchargement au moins partiel sert à modifier l'un au moins des premier et deuxième potentiels de telle sorte que la valeur absolue de la différence de potentiel entre le second potentiel et le troisième potentiel soit réduite à une valeur suffisamment faible pour qu'il ne se produise pratiquement pas de décharge électrique entre la surface de réception d'image et les parties d'arrière-plan.

18. Procédé selon la revendication 16 ou la revendication 17, dans lequel la différence de potentiel de transfert d'image est sensiblement la même que la différence de potentiel de transfert d'image qui serait nécessaire en l'absence de l'étape de déchargement au moins partiel.
19. Procédé selon l'une quelconque des revendications 15 à 18, dans lequel l'étape de transfert comprend l'étape consistant à transférer d'abord l'image révélée sur une surface de transfert d'image apte à recevoir des images révélées en provenance de la surface de formation d'image puis à les transférer sur une autre surface.
20. Procédé selon l'une quelconque des revendications 14 à 19, dans lequel la surface de formation d'image est une surface de formation d'image photoconductrice.
21. Procédé selon la revendication 20, dans lequel l'étape de déchargement au moins partiel comprend l'étape consistant à utiliser une source de lumière pour décharger les parties d'arrière-plan de la surface de formation d'image photoconductrice.
22. Procédé selon la revendication 21, dans lequel la source de lumière comprend un réseau de diodes électroluminescentes.
23. Procédé selon la revendication 22, dans lequel l'étape de déchargement au moins partiel comprend l'étape consistant à utiliser des diodes électroluminescentes qui émettent une lumière colorée, et dans lequel la lumière colorée contient des couleurs qui sont complémentaires des couleurs du toner pigmenté.
24. Procédé selon la revendication 21, dans lequel l'étape de déchargement au moins partiel comprend l'étape consistant à utiliser une source de lumière et au moins un filtre coloré.
25. Procédé selon la revendication 21 ou la revendication 24, dans lequel l'étape de déchargement au

moins partiel comprend l'étape d'éclairage avec des couleurs qui sont complémentaires des couleurs du toner pigmenté.

26. Procédé selon l'une quelconque des revendications 14 à 25, dans lequel l'étape de révélation utilise un toner liquide comprenant les particules de toner et un liquide porteur, et dans lequel l'étape de révélation comprend en outre l'étape consistant à compacter l'image et à en éliminer l'excès de liquide.

5

10

15

20

25

30


35

40

45

50

55






FIG.2

Figure 3




Figure 4





Figure 5



REGISTER ENTRY FOR EP0577610

European Application No EP92904441.0 filing date 21.01.1992

Priority claimed:

12.02.1991 in United States of America - doc: 653953

PCT EUROPEAN PHASE

PCT Application PCT/NL92/00014 Publication No WO92/14193 on 20.08.1992

Designated States DE FR GB IT

Title IMAGING SYSTEM.

Applicant/Proprietor

INDIGO N.V., Lange Vijverberg 9, NL-2513 AC Den Haag, Netherlands

[ADP No. 61373130001]

Inventors

HANNA PINHAS, 20, Shrpinzak Steet, 58 331 Holon, Israel

[ADP No. 61541660001]

YEHUDA NIV, Kefar Aharon 11, Ness Ziona 70400, Israel

[ADP No. 61541678001]

Classified to

G03G

Address for Service

BROOKES & MARTIN, High Holborn House, 52-54 High Holborn, LONDON, WC1V

6SE, United Kingdom

[ADP No. 00000471001]

EPO Representative

LEENDERT C. DE BRUIJN, Nederlandsch Octrooibureau Scheveningsweg 82 P.O.

Box 29720, NL-2502 LS Den Haag, Netherlands

[ADP No. 50789197001]

Publication No EP0577610 dated 12.01.1994

Publication in English

Examination requested 04.08.1993

Patent Granted with effect from 09.10.1996 (Section 25(1)) with title IMAGING
SYSTEM

25.03.1994 Notification from EPO of change of Applicant/Proprietor details
from

INDIGO N.V., Lange Vijverberg 9, NL-2513 AC Den Haag, Netherlands

[ADP No. 61373130001]

to

INDIGO N.V., Luchthavenweg 59-VII, NL-5507 SM Veldhoven,

Netherlands

[ADP No. 61373130003]

Entry Type 25.14 Staff ID. RD06 Auth ID. EPT

06.09.1996 Notification from EPO of change of Applicant/Proprietor details
from
INDIGO N.V., Luchthavenweg 59-VII, NL-5507 SM Veldhoven,
Netherlands [ADP No. 61373130003]
to
INDIGO N.V., Limburglaan 5, 6229 GA Maastricht, Netherlands
[ADP No. 61373130003]
Entry Type 25.14 Staff ID. RD06 Auth ID. EPT

06.09.1996 Notification from EPO of change of EPO Representative details from
LEENDERT C. DE BRUIJN, Nederlandsch Octrooibureau Scheveningseweg
82 P.O. Box 29720, NL-2502 LS Den Haag, Netherlands
[ADP No. 50789197001]
to
LEENDERT C. DE BRUIJN, Nederlandsch Octrooibureau P.O. Box 29720,
2502 LS Den Haag, Netherlands [ADP No. 50789197001]
Entry Type 25.14 Staff ID. RD06 Auth ID. EPT

**** END OF REGISTER ENTRY ****

OA80-01
EP

OPTICS - PATENTS

11/11/96 15:05:00
PAGE: 1

RENEWAL DETAILS

PUBLICATION NUMBER

EP0577610

PROPRIETOR(S)

INDIGO N.V., Limburglaan 5, 6229 GA Maastricht, Netherlands

DATE FILED

21.01.1992

DATE GRANTED

09.10.1996

DATE NEXT RENEWAL DUE

21.01.1997

DATE NOT IN FORCE

DATE OF LAST RENEWAL

YEAR OF LAST RENEWAL

00

STATUS

PATENT IN FORCE

**** END OF REPORT ****