


Nov. 13, 1945.

H. R. BAUER ET AL

2,389,104

MULTIPLE CIGARETTE OR THE LIKE

Filed July 25, 1941



UNITED STATES PATENT OFFICE

2,389,104

MULTIPLE CIGARETTE OR THE LIKE

Henry R. Bauer and William A. Bogg, Fairfield,
Conn., said Bogg assignor to said Bauer

Application July 25, 1941, Serial No. 403,956

12 Claims. (Cl. 131—8)

The present invention relates to rolls of tobacco or the like material used for smoking purposes, and, more particularly, to multiple cigarettes, cigars, or the like.

With cigarettes now in use, much of the cigarette is wasted on many occasions due to the fact that the user desires or has only sufficient time to take a "short" smoke. This is especially true of the worker who has or may take a short recess period during which he may smoke. At this time, he lights up a cigarette and after smoking a short part of it he either throws it away or extinguishes it, known as "butting" or "snipping," and stores it until a later time when he may have an opportunity to again smoke it.

If the cigarette is thrown away, a substantial part of it is wasted. This is especially true if the user is smoking a long cigarette.

If the cigarette is extinguished or "butted" and stored, the smoke remains in the unused portion of the cigarette so as to impair its taste and makes it less enjoyable when relighted.

It has been heretofore proposed to make a cigarette in which the wrapper was weakened intermediate the ends so that it could be broken in two to provide short smokes if desired. This, however, was entirely unsatisfactory and impractical, for the broken end of the cigarette produced straggly ends having loose tobacco which are undesirable as they become more or less dry and the tobacco strips and falls therefrom into the pocket or into the pocketbook of a lady smoker.

Further, if the straggly end is lighted, a dangerous condition is present due to the loose lighted tobacco falling therefrom which may damage the clothing and burn the user. If the other end is lighted, then the user is bothered with loose tobacco in his mouth.

The present invention overcomes these and other difficulties by providing the novel cigarette which may be severed completely and cleanly intermediate its ends to produce short cigarettes if desired. Each of the cigarettes thus produced will be a complete unit only shorter in length than the original or a standard length cigarette.

This is accomplished according to the present invention by providing dividing means at suitable intervals in a rod of tobacco or the like filler, and enclosing the entire rod of tobacco with the dividing means therein in a suitable wrapper which may be severed at a point or points adjacent the dividing means so that the cigarette can be separated into a plurality of shorter cigarettes.

The dividing means extends across the rod of tobacco and separates it into complete units. According to the present invention, this means may be a disk or a cap-like or boot-like element disposed therein, or it may comprise a pair of filter tips disposed between the ends of the cigarette. The first two types of filter means may be made of combustible material and provided with draft apertures through which air and fire may pass from one unit of tobacco to the other, in which case the cigarette may be smoked in its entirety should the user desire a long smoke or separated to provide a plurality of short cigarettes.

The wrapper may be provided with means to facilitate the tearing of the same or with suitable indicia to indicate the point adjacent the dividing means at which it is to be severed.

The organization of the dividing means and the wrapper may be such that the dividing means cooperates with the wrapper in the severing thereof, thus facilitating or otherwise insuring the division of the cigarette at the point or points of separation of the tobacco in the rod.

When the disk is used, it may serve as an advertising medium and have suitable indicia thereon, the disk becoming available upon the cigarette being severed into its multiple units.

In its broader aspects, the invention can be applied to cigars or other rolls of material adapted to be smoked in the manner of tobacco. Further, the cigar, cigarette or the like may be arranged so that it can be divided into as many sections as desired by duplicating the dividing means within the length thereof.

Other features and advantages will be apparent from the specification and claims when considered in connection with the drawing, in which:

Figure 1 is a longitudinal sectional view of one form of the invention.

Fig. 2 is a plan view of one of the dividing disks.

Fig. 3 is a plan view of another dividing disk.

Fig. 4 is a longitudinal sectional view of another form of the invention.

Fig. 5 is a perspective view of a pair of caps, or boots, showing the perforations.

Fig. 6 is a longitudinal sectional view of another form of the invention.

Fig. 7 is a side elevational view showing the indicating line.

Fig. 8 is a side elevational view showing the tear string severing means.

Fig. 9 is a view showing the separation of the two sections of the cigarette.

Fig. 10 is a side view, partly in section, of a cigar embodying the present invention.

Fig. 11 shows a modified form of the invention.

Fig. 12 is a view similar to Fig. 1 showing a plurality of disks of Fig. 3 therein.

The present invention is illustrated as applied to a cigarette. While the cigarette may be of any desired length, it is preferable that it be of a size which is longer than the normal standard cigarette.

This cigarette may be divided into two or more parts as required. As shown in the drawing, the present invention includes a rod 10 of tobacco or the like separated by a dividing means 11 so that a plurality of separate units 10a and 10b of tobacco having cleanly cut or packed ends are formed. An overall wrapper 12 of paper or other suitable material surrounds the rod and dividing means. With the rod of tobacco thus separated into complete units, it is only necessary to sever the wrapper intermediate these units and not the entire cigarette to produce a plurality of short cigarettes having a length less than the standard length of the cigarette.

The dividing means shown in Figs. 1 through 3 comprises a stiff disk 11a, 11b having an area substantially the same as the cross-section of the rod of tobacco so as to completely separate the two units of tobacco. The disk is freely supported between the ends of the tobacco and when the wrapper 12 surrounding the rod and disk is severed adjacent the disk, the disk will drop out and two complete short cigarettes will be formed.

The disks may be provided with suitable indicia which may be printed thereon, as shown at 15 in Fig. 2, or formed by perforations in the disk as indicated at 15a in Fig. 3. This indicia may be in the nature of advertising matter and include the brand name and similar material. Inasmuch as the disks will drop out upon the wrapper of the cigarette being severed into a plurality of sections, they may also be used as premium pieces.

It may be that the purchaser of a pack of cigarettes capable of separation would desire to smoke an entire cigarette as a unit or have a "long" smoke. In order that this may be accomplished, the present invention forms the disk 11a of a destructible material, preferably a paper-like combustible substance which will readily burn. Throughout the disk is a plurality of apertures 13 through which air may be easily drawn from end to end of the cigarette. Instead of relying upon the burning of the disk to ignite the next unit of tobacco, the apertures may be made of sufficient size that the fire of the burning tobacco in one unit will be transmitted therethrough to ignite the tobacco in the next adjacent section. It will be seen therefore that the cigarette thus formed can be smoked as a "long" smoke or severed into a plurality of shorter cigarettes to provide "short" smokes.

The dividing means shown in Figs. 4 and 5 comprises a cap or boot 20 made up of a transverse wall 21 and a collar 22 integral therewith or rigidly secured thereto. While one cap would be sufficient to divide the rod 10 of tobacco, in the preferred form of the invention, a pair of caps is employed and disposed with the transverse walls 21 adjacent one another as shown in Fig. 4 or slightly spaced from one another as required. The line of severance of the wrapper is disposed over the adjacent edges of the caps so that as the wrapper is severed, the two complete short cigarettes are formed. It will be noted that in each of these cigarettes the cap will remain and

will form a tip for the cigarette if the smoker desires to use it as such.

In applying the wrapper 12 to enclose the units 10a, 10b of the rod of tobacco of Fig. 4 and the caps 20, the inner surface or the first layer of the paper or the like wrapper may be secured to the collar 22 of each cap. This greatly facilitates the tearing of the wrapper and the separation of the cigarette into shorter units, for, as will be noted in Fig. 9, the two portions of the cigarette can be grasped by the fingers adjacent the caps and twisted. As the caps move relatively to one another with the wrapper secured thereto, they will cause a rupture of the paper intermediate their adjoining ends as at 19 to form the two sections 12a, 12b.

In this form of the invention, if it is desired to provide a cigarette which may be smoked in its entirety as well as in the form of a plurality of units, the caps may be made of destructible material, and, preferably, of a material which will readily burn. The transverse walls 21 of both of the caps are provided with apertures 23 which are aligned and form passages through which air may be drawn, and of sufficient size to pass a fire from the tobacco of one cigarette unit to the other, as in the previously described form of the invention.

Many smokers not only prefer a short smoke, but also desire cigarettes which are provided with filter tips or similar devices. According to the present invention, there is provided a multiple cigarette in which the dividing means comprises a pair of filter tips 30 disposed in end to end relation as shown in Fig. 6, and dividing the rod 10 into units of tobacco 10a and 10b.

These filter tips may be of any desired construction. Herein, they are illustrated as cartridges 31 having transverse walls 32 of foraminous material enclosing a supply of smoke-filtering material 33. If desired, an air space or cooling chamber 34 may be provided between the filter 33 and the rod of tobacco. In this form of the invention, the wrapper is secured to each of the filter tips. Since the cigarette is not to be smoked in its entirety, the wrapper may be perforated adjacent the adjoining portions of the filter tips, so that it can be readily severed at this point. With this construction, when it is desired to separate the cigarettes into shorter cigarettes, it is merely necessary to grip the cigarette adjacent the filters and twist the two parts of the cigarette as shown in Fig. 9. This will rupture the paper adjacent the adjoining ends of the filters and provide two short cigarettes each having a filter tip.

Other means may be provided for severing the cigarettes into their multiple units. One of these is shown in Fig. 3, wherein the disk 11b is provided with a serrated or toothed periphery 14. When this is disposed beneath the wrapper, and the pressure applied to the outer surface of the wrapper as by rolling it with the finger over a hard surface, the serrations will pierce the wrapper and weaken it so that it will be readily separated along this line.

In the cigarette shown in Fig. 7, a line 16 is formed on the outer surface of the wrapper, by printing or other suitable means, and is disposed over the dividing means and indicates the point of severance. The user of the cigarette may pass his fingernail, or a sharp instrument, along this line and use the dividing means, that is, the side of the disk, the space between the ends of 21 of the caps or the space between the ends of

the filter tips, as guiding means to cause complete separation of the several units of the cigarette.

A still further means of severing the wrapper, which is applicable to all forms of dividing means, is shown in Fig. 8, wherein a tear string 17 is included in the wrapper over the point of severance. By pulling the tear string, the wrapper is severed and the cigarette divided into the several short cigarettes.

While the invention has been herein illustrated as being applied to a cigarette, in the broader aspects it may be applied to cigars or other similar devices employing tobacco or other matter intended to be smoked.

Fig. 10 shows the invention applied to a cigar in which the two ends of the cigar are rounded or curved to form tips, and the filler is provided with a dividing means 11c intermediate the ends so as to be separated into units and distinct from one another.

Further, the rod or filter of tobacco may be completely severed units, and, if desired, the adjoining ends of the units at which the cigarette or the like is to be severed may be provided with collars similar to collars 22, as shown in Fig. 4, so as to aid in the severing of the units into short cigarettes when the wrapper enclosing the same is torn.

The number of short cigarettes which may be embodied in a single unit may be varied as required, the variation being accomplished by properly positioning the desired number of dividing means therein as shown in Fig. 11 wherein spaced caps are disposed therein and in Fig. 12 wherein spaced disks are used.

Variations and modifications may be made within the scope of this invention and portions of the improvements may be used without others.

We claim:

1. A multiple cigarette or the like comprising a plurality of physically separate units of tobacco of a relatively short length and having cleanly severed packed ends disposed in end-to-end relation, a separator member of combustible material between the ends, and a wrapper surrounding the tobacco and member and separable about the adjacent ends of the units of tobacco whereby the cigarette may be divided into a plurality of short cigarettes, said member having an edge adapted to cooperate in severing the wrapper during separation of the units.

2. A multiple cigarette or the like comprising a rod of tobacco having caps comprising a disk and supporting rim disposed therein to completely separate the rod into a plurality of short units, said caps being of combustible material and provided with apertures in the disk through which air may pass from end to end of the cigarette, and a wrapper surrounding the tobacco and caps and separable adjacent the disks of the caps whereby the cigarette may be smoked in its entirety and the caps consumed or the cigarette may be severed adjacent the caps into a plurality of short cigarettes.

3. A multiple cigarette or the like comprising a rod of tobacco including a plurality of short units having packed and clean cut ends in end-to-end relation, severing means of combustible material therein having an area substantially the same as the cross-sectional area of the rod disposed in said rod and extending transversely thereof between said ends to divide the rod into separable units of less length than that of the cigarette, and a wrapper surrounding the tobacco and severing

means, said wrapper being transversely divisible at the severing means whereby the cigarette may be divided into a plurality of short cigarettes or smoked as a whole.

4. A multiple cigarette or the like comprising a rod of tobacco including one or more disks of stiff combustible material therein, said disks having an area substantially the same as the cross-sectional area of the rod and extending transversely thereof to divide the rod into units of less length than the cigarette, and having the edges thereof serrated to provide a plurality of sharp projections, and a wrapper surrounding the tobacco and disk and adapted, when pressure is applied to the cigarette adjacent the serrated edge of the disk, to be severed and the cigarette divided into a plurality of complete short cigarettes.

5. A multiple cigarette or the like comprising a rod of tobacco including a plurality of short sections having cleanly cut packed ends in end-to-end relation including one or more disks of stiff material freely supported therein between the adjacent packed ends to divide the rod into units of length less than that of the cigarette, a wrapper surrounding the tobacco and disks and separable adjacent the disks, each of said disks having an edge cooperable to sever the wrapper thereabout and separate the cigarette into a plurality of short cigarettes, the freely supported disks readily separating from the cigarette when the latter is severed into smaller cigarettes and having advertising indicia thereon.

6. A multiple cigarette or the like comprising a rod of tobacco having a plurality of substantially rigid caps disposed therein with the transverse walls thereof adjacent one another, said caps dividing the rod into units of length less than the cigarette, and a wrapper surrounding the tobacco and caps and separable at the adjacent transverse walls of the caps whereby the cigarette may be severed into a plurality of short cigarettes.

7. A multiple cigarette or the like comprising a rod of tobacco having at intervals therein substantially rigid caps dividing the rod into units of length less than the cigarette, said caps enclosing the one end of each unit, and a wrapper surrounding the tobacco and caps and separable at the adjacent transverse walls of the caps whereby the cigarette may be severed into a plurality of short cigarettes each having a tipped end.

8. A multiple cigarette or the like comprising a rod of tobacco having a plurality of substantially rigid caps disposed therein with the transverse walls thereof adjacent one another, said caps dividing the rod into units of length less than the cigarette, and a wrapper surrounding the tobacco and caps and rigidly secured to each of said caps whereby twisting of said caps relative to one another causes the wrapper to tear between said caps and divide the cigarette into a plurality of short cigarettes.

9. A multiple cigarette or the like comprising a rod of tobacco having a plurality of substantially rigid filters disposed therein with the transverse walls thereof adjacent one another, said filters dividing the rod into units of length less than the cigarette, and a wrapper surrounding the tobacco and filters and rigidly secured to each of said filters whereby twisting of said filters relative to one another causes the wrapper to tear between said filters and divide the cigarette into a plurality of short cigarettes.

10. A multiple cigarette or the like comprising a rod of tobacco including a plurality of short sections each having packed ends and dividing

means therein disposed between adjacent packed ends to completely separate the rod into units of length less than the cigarette, said dividing means having means thereon to assist in severing the wrapper therearound, said dividing means being of combustible material and provided with apertures for the passage of air through the cigarette from end to end, and a wrapper surrounding the tobacco and dividing means and separable adjacent the dividing means whereby the cigarette may be smoked in its entirety and the dividing means consumed or the cigarette may be severed adjacent the dividing means into a plurality of short cigarettes.

11. A multiple cigarette or the like comprising a rod of tobacco including a plurality of short sections each having the ends thereof cleanly cut and packed and a disk of combustible material having severing-assisting edges disposed therein between the adjacent packed ends to completely separate the rod into units of a length less than the cigarette, said disk being provided with apertures through which air can pass from end-to-end of said cigarette, and a wrapper surrounding the tobacco and disk, the edge of the disk being oper-

able to sever the wrapper adjacent the disk whereby the cigarette may be smoked in its entirety and the disk of combustible material consumed or the cigarette may be severed adjacent the disk into a plurality of short cigarettes.

12. A cigarette or the like comprising a rod of tobacco having a stiff, paper-like dividing means therein at predetermined intervals to completely separate the rod into units of a length less than the cigarette, each unit having cleanly cut and packed ends, said paper-like dividing means being of burnable material and provided with apertures capable of passing air and fire from one unit of tobacco to the other, and a wrapper surrounding the tobacco and dividing means, said dividing means cooperating to sever the wrapper therearound whereby the cigarette may be smoked in its entirety and the dividing means consumed or the cigarette may be severed adjacent the dividing means into a plurality of short complete cigarettes.

HENRY R. BAUER.
WILLIAM A. BOGG.