



(51) International Patent Classification:
A47J 31/30 (2006.01)

(21) International Application Number:
PCT/EP2008/062511

(22) International Filing Date:
19 September 2008 (19.09.2008)

(25) Filing Language: English

(26) Publication Language: English

(72) Inventor; and

(71) Applicant : BRIZIO, Adriana [IT/CH]; Via Ceresio,
18, CH-6977 Ruvigliana (CH).

(74) Agents: RIPAMONTI, Enrico et al.; GIAMBROCONO
& C. S.p.A., Via Rosolino Pilo, 19/B, I-20129 Milano
(IT).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ,
CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ,

EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN,
HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR,
KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME,
MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO,
NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG,
SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ,
TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI
(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR,
NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: CAN FOR THE EXTEMPORANEOUS PREPARATION OF BEVERAGES BY EXTRACTION AND/OR INFUSION, PROVIDED WITH A SAFETY LID




Fig. 1

(57) Abstract: The can (10; 10A; 10B; 10C) for the
extemporaneous preparation of beverages by extraction
and/or infusion comprises a first chamber (12) intended to
collect the final beverage, a second chamber (14) contain-
ing a drinkable liquid and a filtering device (16) contain-
ing a substance able to produce the required beverage by ex-
traction and/or infusion. The can is foreseen to be put onto
a heating source after opening the can lid (18; 18A, 18B;
18C) and operating the filtering device (16) by the user.
The lid (18; 18A, 18B; 18C) comprises: an outer rim por-
tion (22; 22B) intended to remain fixed to the can lateral
wall (20) when opening the can; an inner removable por-
tion (24; 24A; 24B; 24C) intended to be ripped in order to
open the can; and a predetermined breaking line (34) sepa-
rating said inner removable portion (24; 24A; 24B; 24C)
from said outer rim portion (22; 22B). The breaking line
(34) is provided in an annular portion (28; 28A; 28B; 28C)
forming part of the lid (18; 18A, 18B; 18C) and made of
plastic material. The outer part (32; 32B) of the annular
portion (28; 28A; 28B; 28C) is part of the outer rim por-
tion (22; 22B) while the inner part thereof (24; 24A; 24B;
24C) is part of the inner removable portion (24; 24A; 24B;
24C).

**CAN FOR THE EXTEMPORANEOUS PREPARATION OF BEVERAGES
BY EXTRACTION AND/OR INFUSION, PROVIDED WITH A SAFETY
LID.**

5 The present invention relates to a can usable for the extemporaneous preparation of beverages by extraction and/or infusion().

Cans for the extemporaneous preparation of beverages by extraction and/or infusion are disclosed in EP-A-1610657 and have been recently launched on the market. Said cans have a first chamber intended to
10 collect the final beverage, a second chamber containing a drinkable liquid and a filtering device containing a substance able to produce the required beverage by extraction and/or infusion. The first chamber is closed by the can lid.

Said cans are foreseen to be put onto a heating source after opening the
15 lid and operating the filter by the user. To this purpose, the lid has an outer rim portion, intended to remain fixed to the can vertical wall when opening the can, and an inner removable portion, intended to be ripped by pulling a tab, provided on the lid, in order to open the can, a groove being provided between said inner and outer portions to reduce the
20 thickness and consequently the resistance of the lid structure, so as to enable the hand-ripping of the aforesaid inner portion.

The user, therefore, will pull the tab to partially or totally rip the lid and slip a hand into the can to move the filter device in a given direction, thereby putting the liquid contained in the second chamber in contact with the
25 substance contained in the filtering device.

Upon completion of the aforementioned operations, the user will put the can onto a heating source. In this way, by effect of the pressure increase due to heating, the liquid will be forced to move from the second chamber to the first chamber passing through the substance contained in the filter device and forming an extemporaneously prepared beverage.

This quite new kind of cans has remarkable risks as far as safety is concerned, some risks being in common with the traditional cans, while others being connected to the specific use of the more recent cans above described

10 An incommensurable number of traditional cans, containing conserved food or ready-to-drink beverages, are currently offered on the market. They all are provided with a usual lid which is seamed to the can vertical wall, the lid having an outer rim portion, intended to remain fixed to the can vertical wall when opening the can, and an inner removable portion, 15 intended to be ripped by pulling a tab, in order to open the can, a groove being provided between said inner and outer portions so as to enable the hand-ripping of the aforesaid inner portion.

The most important disadvantage of the aforesaid traditional cans is that, once the inner portion of the lid has been ripped up, the rim portion which 20 remains attached to the vertical can wall, as well as the removed portion, will have sharp edges, so that there is a serious risk of cutting when the user is handling the can to reach the food or beverage contained therein, or when disposing said can. So far, no effective solution to this problem has been found, in spite of the huge value of the involved market branch.

25 Some countries are nowadays planning to pass a rule establishing that

the lid removable portion can be pushed only inside the can and cannot be pulled outwards. Thus, the problem of ensuring safety when the user inserts her/his hand into the can, whether just by mistake or for reaching the food contained therein, as well as when the user is bringing the can to
5 her/his mouth, is not overcome.

At the same time another remarkable problem connected to the specific use of the more recent cans above described, is that the can is foreseen to be put onto a heating source to form an extemporaneous beverage.

It may happen that the user inadvertently puts the can onto the heating
10 source without having previously opened the can lid. In this case, because of the inside liquid transforming into steam, the pressure inside the can may reach very high values, such as to cause the blast of the can. The traditional safety means for discharging the inner pressure, as the known exhausting valves which are usually provided onto the lateral walls
15 of those containers which have the risk of inner overpressure (e.g. moka coffee-makers or pressure cookers), do not comply with the requirements of easy handling, safe packaging and reduced costs, which occur in cans destined to the large-scale distribution.

The present invention aims to solve the problem of ensuring safety when
20 manipulating the lid, as well as to prevent the can from blasting.

According to the present invention, the first problem is solved by a can for the extemporaneous preparation of beverages by extraction and/or infusion, the can being provided with a lid which is seamed to the lateral can wall, the lid comprising: an outer rim portion intended to remain fixed
25 to the can lateral wall when opening the can, an inner removable portion

intended to be ripped in order to open the can, and a predetermined breaking line separating said inner removable portion from said outer rim portion; characterized in that said breaking line is provided in an annular portion forming part of the lid and made of plastic material, the outer part
5 of the annular portion being part of said outer rim portion, while the inner part of the annular portion being part of said inner removable portion.

Therefore, when the inner removable portion of the lid is ripped, since the inner edge of the outer rim portion and the outer edge of the removable inner portion are of plastic material, there is no risk of cutting.

10 Said breaking line preferably comprises a groove or a double groove provided on the outer or on the inner side of the lid, the double groove being formed of two opposite grooves, one groove being provided on the outer side and the other groove being provided on the inner side of the lid. Depending on the shape of the grove or double groove provided within
15 the plastic annular portion, the ripping of the inner removable portion will be total when said groove or double groove follows a continuous, circular line. Alternatively, said groove or double groove may be interrupted or may be less deep in one tract, such that the inner removable portion remains partially attached to the outer rim portion.

20 In any case, once the can has been opened, the user may safely manipulate it.

As mentioned above, the present invention aims also to solve the problem of the can blasting when the user inadvertently omits to open the can lid before putting the same can onto a heating source.

In order to achieve also this aim, the can according to the present invention, comprises tearing means for discharging the inner pressure when the inner pressure exceeds a predetermined value, said tearing means being provided in the annular plastic part or in the removable lid inner portion, if made of plastic material, or in the outer rim portion, id made of plastic material, thereby preventing the can from blasting.

Preferably said tearing means comprise one or more thinner zones able to tear when the inner pressure exceeds said predetermined value..

In a preferred embodiment, the tearing means are obtained by conveniently reducing the thickness of one or more small zones within said plastic component or components, thus forming one or more membranes able to tear at a given can inner pressure. It has to be pointed out, however, that the tearing zone can corresponding totally or partially to the aforesaid breaking line, so that it has a double function, i.e. to allow the opening of the can lid and to provide safety tearing means.

Conveniently the aforesaid tearing means will be positioned and will have a shape such as to discharge the inner pressure in a direction substantially parallel to the can lid.

The invention will be more easily understood from the following description of some embodiments, given merely by way of example, of the can according to the present invention, taken in conjunction with the accompanying drawings, in which:

Fig. 1 is an axial cross-section of a first embodiment of a can according to the invention, in the condition in which it is supplied to the user;

Fig. 2 is a perspective view of the upper part of the can of Fig. 1;

Fig. 3 is an axial cross-section of the upper part of a second embodiment of a can according to the invention;

Fig. 4 shows the situation after removing the inner portion of the lid of the can of Fig. 3;

5 Fig. 5 is similar to Fig. 3, but with the inner removable portion of the lid only partially ripped and still partially attached to the outer rim portion of the lid;

Fig. 6 shows another embodiment of the can according to the invention, in which the outer rim portion, the inner removable portion and the plastic
10 annular portion are made in one piece of the same plastic material;

Fig. 7 shows a further embodiment in which the inner removable portion and the annular portion are made in one piece of plastic material, the annular portion comprising ripping means;

Fig. 8 is a view from the bottom of only the one piece of Fig. 7, comprising
15 the inner portion, the removable portion and the ripping means.

As can be seen in Fig. 1, a can 10 comprises a first chamber 12 intended to collect the final beverage, a second chamber 14 containing a drinkable liquid, and a filtering device 16 containing a substance able to produce the required beverage by extraction and/or infusion. The can 10 is provided
20 with a lid 18 which is seamed to the can vertical wall 20. The Lid 18 has an outer rim portion 22 intended to remain fixed to the can vertical wall 20 when opening the can 10, and an inner removable portion 24 intended to be ripped by pulling a conventional tab 26 in order to open the can 10. A plastic annular part 28 is interposed between the outer rim portion 22 and
25 the inner removable portion 24, the outer side part 30 of said plastic

annular part 28 being fixed to the inner perimeter of the outer rim portion 22 (part 30 being actually part of the rim portion 22) while the inner side part 32 of the annular portion 28 is fixed to the perimeter of the inner removable portion 24 (part 32 being actually part of the inner removable
5 portion 24). A thinner zone or double grooves 34 is provided within the plastic annular portion 28, in which the resistance of the lid structure is reduced, the thinner zone separating said inner (32) and outer (30) side parts, thus enabling the hand-ripping (by means of the tab 26) of the aforesaid inner portion 24, 32. The plastic annular portion 28 is shaped
10 (see Fig. 1) such as to be connected to the remaining portion of the lid (18).

In the can 10A of Fig. 3 the inner removable portions 24A and 32A of the lid 18A are made of plastic material, are integral with the plastic annular portion 28A. A tab 26 is also provided. When the removable inner portions
15 24A and 32A have been ripped away by means of the tab 26, the can 10A appears to be open, as shown in Fig. 4.

Coming back to the can 10, it has to be pointed out that the removable inner portions 24, 32 can be only partially ripped away, so that the removable inner portions 24, 32 are still partially connected to the outer
20 rim portions 22, 30 of the lid 18, as shown in Fig. 5.

The can 10B shown in Fig. 6 has a lid 18B in one piece, the portions 22B, 28B and 24B thereof being consequently made of the same plastic material. In particular, the inner side part 32B of the annular portion 28B is integral with the remaining part (24B) of the removable inner portion (24B,

32B) whereas the outer side part 30B is integral with the remaining part (30B) of the outer rim portions (22B; 30B).

The can 10C in Fig. 7 is similar to the can 10A in Fig. 3, with the difference that the lid 18C is provided with the above mentioned tearing
5 means comprising, in the specific case, four thinner zones 36 (see also Fig. 8) which tears when the pressure in the can 10C exceeds a predetermined value. It has to be pointed out that when the discharge jets through zones 36 tear, they are directed substantially parallel to the bottom of the inner removable portion 24C.

10 It should be evident that tearing zones can be provided also in the plastic portions (28; 28A, 24A; 22B, 28B; 24B respectively) of other cans (10; 10A; 10B respectively) disclosed above. In particular the groove 34 itself can be a tearing means.

CLAIMS

1. A can (10; 10A; 10B; 10C) for the extemporaneous preparation of beverages by extraction and/or infusion, comprising a first chamber (12) intended to collect the final beverage, a second chamber (14) containing a drinkable liquid and a filtering device (16) containing a substance able to produce the required beverage by extraction and/or infusion, the can being foreseen to be put onto a heating source after opening the can lid (18; 18A, 18B; 18C) and operating the filtering device (16) by the user, the lid (18; 18A, 18B; 18C) comprising: an outer rim portion (22; 22B) intended to remain fixed to the can lateral wall (20) when opening the can; an inner removable portion (24; 24A; 24B; 24C) intended to be ripped in order to open the can; and a predetermined breaking line (34) separating said inner removable portion (24; 24A; 24B; 24C) from said outer rim portion (22; 22B) ; characterized in that said breaking line (34) is provided in an annular portion (28; 28A; 28B; 28C) forming part of the lid (18; 18A, 18B; 18C) and made of plastic material, the outer part (32; 32B) of the annular portion (28; 28A; 28B; 28C) being part of the outer rim portion (22; 22B) while the inner part thereof (24; 24A; 24B; 24C) being part of the inner removable portion (24; 24A; 24B; 24C).
2. The can (10; 10A; 10B; 10C) according to claim 1, wherein the breaking line is a groove or two opposing grooves (34).
3. The can (10; 10A; 10B; 10C) according to claim 1, wherein the breaking line (34) is encircling the whole perimeter of the removable inner portion so as to let the removable inner portion to be totally removed from the lid.

4. The can according to claim 1, wherein the breaking line is encircling a part of the perimeter of the inner removable portion, such that this latter may remain partially attached the outer rim portion.
5. The can (10; 10A; 10C) according to claim 1, wherein the outer rim portion (22; 22B), with the exception of the outer part (30) of the plastic annular portion (28; 28A, 28C), is made of metal .
6. The can (10B) according to claim 1, wherein the whole outer rim portion (22B, 30B) is made of plastic material.
7. The can (10) according to claim 1, wherein the inner removable portion (24, 32), with the exception of the inner part (32) of the plastic annular portion (28), is made of metal.
8. The can (10B; 10C) according to claim 1, wherein the whole inner removable portion (24B, 32B) is made of plastic material.
9. The can (10B) according to claim 1, wherein the lid (18B) is in one piece of plastic material.
10. The can (10C) according to claim 1, comprising tearing means (36) for discharging the inner pressure when the inner pressure exceeds a predetermined value, wherein said tearing means (36) are provided in the annular plastic part (28C) and/or in the removable inner portion and/or the outer rim portion (22), if the removable inner portion and/or the outer rim portion are of plastic material.
11. The can (10C) according to 1, wherein the tearing means are obtained by conveniently reducing the thickness of one or more small zones (36) of the plastic portions of the lid (18C) to form one or more thin

membranes able to break at a predetermined inner pressure in the can (10C).

12. The can according to claim 1, wherein the tearing means are positioned and have such a shape as to discharge the can inner pressure
- 5 in a direction substantially parallel to the can lid.




Fig. 2

Fig. 1

2/4




Fig. 3




Fig. 4

3/4




Fig. 5




Fig. 6




Fig. 7




Fig. 8

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2008/062511

A. CLASSIFICATION OF SUBJECT MATTER
INV. A47J31/30

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
A47J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 1 610 657 B (BRIZIO ADRIANA [IT] BRIZIO ADRIANA [CH]) 4 January 2006 (2006-01-04) cited in the application paragraph [0029] paragraphs [0025] - [0042]; figures -----	1-12
A	US 4 167 899 A (MCCORMICK JAMES B) 18 September 1979 (1979-09-18) column 2, line 13 - column 5, line 15; figures -----	1-12
A	US 6 026 733 A (ORRICO MARIO [US] ET AL) 22 February 2000 (2000-02-22) column 4, line 20 - column 9, line 19; figures -----	1-12
	-/--	

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

8 April 2009

Date of mailing of the international search report

17/04/2009

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

De Terlizzi, Marino

INTERNATIONAL SEARCH REPORT

International application No

PCT/EP2008/062511

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 112 086 A (BERARDI FRANCESCO [IT]; FRANCONE ENRICO [IT]; LIZZI LEONARDO PAOLO [IT]) 27 June 1984 (1984-06-27) page 3, line 9 - page 8, line 21; figures -----	1
A	US 2005/109213 A1 (TERADA MASAKI [JP]) 26 May 2005 (2005-05-26) paragraphs [0030] - [0062]; figures -----	1
A	EP 0 344 541 A (BREV SANVITALE S R L [IT]) 6 December 1989 (1989-12-06) column 4, line 13 - column 9, line 49; figures -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2008/062511

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 1610657	B	08-10-2008	AT 410101 T 15-10-2008
		AU 2004212687 A1 02-09-2004	
		BR PI0407692 A 01-03-2006	
		CA 2516417 A1 02-09-2004	
		CN 1750780 A 22-03-2006	
		DK 1610657 T3 02-02-2009	
		EP 1610657 A1 04-01-2006	
		WO 2004073468 A1 02-09-2004	
		ES 2314372 T3 16-03-2009	
		JP 2006518314 T 10-08-2006	
		KR 20050107758 A 15-11-2005	
		MA 27663 A1 01-12-2005	
		MX PA05008831 A 18-10-2005	
		NZ 541719 A 28-09-2007	
		RU 2333715 C2 20-09-2008	
		SI 1610657 T1 28-02-2009	
		US 2006165851 A1 27-07-2006	
ZA 200506404 A 27-12-2006			

US 4167899	A	18-09-1979	NONE

US 6026733	A	22-02-2000	NONE

EP 0112086	A	27-06-1984	DE 3379155 D1 16-03-1989
			ES 8500036 A1 01-01-1985

US 2005109213	A1	26-05-2005	JP 2005152551 A 16-06-2005
			US 2008314254 A1 25-12-2008
			WO 2005051147 A1 09-06-2005

EP 0344541	A	06-12-1989	JP 2036821 A 06-02-1990
			US 5104666 A 14-04-1992
