



## (51) International Patent Classification:

Not classified

## (21) International Application Number:

PCT/IB2020/050433

## (22) International Filing Date:

21 January 2020 (21.01.2020)

## (25) Filing Language:

English

## (26) Publication Language:

English

## (30) Priority Data:

1900780.6 21 January 2019 (21.01.2019) GB

(71) Applicant: **VIBRANT LTD.** [IL/IL]; Hakochav Yokneam Building, P.O.Box 516, 2069206 Yokneam (IL).(72) Inventors: **BEN-TSUR, Lior**; 9 Hanurit Street, 4267000 Netanya (IL). **SHABAT, Roni**; 1935000 Kibbutz Yizra'el (IL). **MOLNAR, Shai**; 2 Ha'ela Street, 2016200 Shorashim (IL).(74) Agent: **SHALOM LAMPERT IP & ENGINEERING LTD.**; 59 Yakinton Street, POB 1064, 2152041 Maalot (IL).

## (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN,


HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, WS, ZA, ZM, ZW.

## (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

**Published:**

- without international search report and to be republished upon receipt of that report (Rule 48.2(g))
- in black and white; the international application as filed contained color or greyscale and is available for download from PATENTSCOPE

## (54) Title: DEVICE AND METHOD FOR DELIVERING A FLOWABLE INGESTIBLE MEDICAMENT INTO THE GASTROINTESTINAL TRACT OF A USER



(57) **Abstract:** A device and a method for delivering a flowable ingestible medicament into the gastrointestinal tract of a user. The device includes a vibrating ingestible capsule attached to, or including, a medicament delivery compartment. The medicament delivery compartment includes a housing including a portal, a medicament reservoir, a reservoir biasing mechanism applying pressure to the reservoir, a conduit extending from the reservoir to the portal, and a valve including a weight and a spring adapted, when closed, to bias the weight against the conduit so as to block flow therethrough, and, when open, to remove the weight from the conduit to allow fluid to flow through the conduit. When the vibrating agitation mechanism is in the vibration mode of operation, vibrations exerted thereby are applied to the valve biasing mechanism and periodically transition the valve between the closed operative orientation and the open operative orientation.

**DEVICE AND METHOD FOR DELIVERING A FLOWABLE INGESTIBLE  
MEDICAMENT INTO THE GASTROINTESTINAL TRACT OF A USER**

**RELATED APPLICATIONS**

- 5           The present application gains priority from GB Patent Application Number 1900780.6 filed January 21, 2019 and entitled **DEVICE AND METHOD FOR DELIVERING A FLOWABLE INGESTIBLE MEDICAMENT INTO THE GASTROINTESTINAL TRACT OF A USER.**

10    **FIELD OF THE INVENTION**

The present invention relates in general to devices and methods for delivery of a flowable ingestible medicament into the body of a user, and specifically to devices and methods for such delivery of a flowable ingestible medicament triggered by vibration of a vibrating capsule.

15

**SUMMARY OF THE INVENTION**

In accordance with an embodiment of the present invention, there is provided a device for delivering a flowable ingestible medicament into the gastrointestinal tract of a user, the device including:

- 20           a housing including a first housing portion and a second housing portion, said second housing portion having a portal formed therein;

          a vibrating agitation mechanism disposed within the housing and adapted such that, in a vibration mode of operation, the housing exerts vibrations on an environment surrounding the device;

- 25           a power supply disposed within the housing and adapted to power the vibrating agitation mechanism; and

          a control element adapted to activate the vibrating agitation mechanism to be operative in the vibration mode of operation; and

          a medicament reservoir dimensioned to contain the flowable ingestible medicament;

- 30           a reservoir biasing mechanism adapted to apply pressure to the flexible and collapsible medicament reservoir;

          a conduit extending from the medicament reservoir to the portal, and sealing the portal; and

a valve including a weight and a valve biasing mechanism adapted, in a closed operative orientation, to bias the weight against the conduit so as to block flow through the conduit, and in an open operative orientation to remove the weight from the conduit so as to allow fluid to flow through the conduit,

5 wherein the valve is functionally associated with at least one of the housing and the vibrating agitation mechanism, such that when the vibrating agitation mechanism is in the vibration mode of operation, at least some of the vibrations exerted by the vibrating agitation mechanism or by the housing are applied to the valve biasing mechanism and periodically transition the valve between the closed operative orientation and the open  
10 operative orientation.

In accordance with another embodiment of the present invention, there is provided a method of delivering an ingestible medicament into a gastrointestinal tract of a user, the method including:

providing to the user the device as described hereinabove, for ingestion by the user;  
15 following the user ingesting the device, controlling the vibrating agitation mechanism such that the vibration mode of operation at least partially transpires within a region of the gastrointestinal tract in which the flowable ingestible medicament is absorbable by the body of the user, thereby to cause the periodic transitioning of the valve between the closed operative orientation and the open operative orientation, and delivery of  
20 the flowable ingestible medicament from the reservoir, via the conduit and the portal, into the environment surrounding the device.

In accordance with yet another embodiment of the present invention, there is provided a medicament delivery compartment, adapted to be attached to a vibrating ingestible capsule having a first housing portion and adapted to operate in a vibrating mode  
25 of operation, for delivery of a flowable ingestible medicament into the gastrointestinal tract of a user, the medicament delivery compartment including:

a second housing portion adapted to be attached to the first housing portion of the vibrating ingestible capsule, and having a portal formed therein;

a flexible and collapsible medicament reservoir dimensioned to contain the flowable  
30 ingestible medicament;

a reservoir biasing mechanism adapted to apply pressure to the flexible and collapsible medicament reservoir;

a conduit extending from the medicament reservoir to the portal, and sealing the portal; and

a valve including a weight and a valve biasing mechanism adapted, in a closed operative orientation, to bias the weight against the conduit so as to block flow through the conduit, and in an open operative orientation to remove the weight from the conduit so as to allow fluid to flow through the conduit.

5 In accordance with a further embodiment of the present invention, there is provided a vibrating ingestible capsule adapted to be attached to a medicament delivery compartment for delivering a flowable ingestible medicament disposed within the medicament delivery compartment into the gastrointestinal tract of a user, the vibrating ingestible capsule including:

10 a housing including an attachment mechanism adapted for mutual attachment to a corresponding attachment mechanism of the medicament delivery compartment;

a vibrating agitation mechanism disposed within the housing and adapted such that, in a vibration mode of operation, the housing exerts vibrations on an environment surrounding the vibrating ingestible capsule;

15 a power supply disposed within the housing and adapted to power the vibrating agitation mechanism; and

a control element adapted to activate the vibrating agitation mechanism to be operative in the vibration mode of operation,

20 wherein at least one vibration parameter of the vibrating agitation mechanism is set so as to promote at least one of delivery of the flowable ingestible medicament from the medicament delivery compartment into an environment surrounding the medicament delivery compartment and absorption of the flowable ingestible medicament into the bloodstream of the user.

25 In accordance with another further embodiment of the present invention, there is provided a method for delivering a flowable ingestible medicament into the gastrointestinal tract of a user, the method including:

providing an ingestible device including:

a housing including a first housing portion and a second housing portion, the second housing portion having a portal formed therein;

30 a vibrating agitation mechanism disposed within the housing and adapted such that, in a vibration mode of operation, the housing exerts vibrations on an environment surrounding the ingestible device;

a power supply disposed within the housing and adapted to power the vibrating agitation mechanism; and

a control element adapted to activate the vibrating agitation mechanism to be operative in the vibration mode of operation; and

a flexible and collapsible medicament reservoir having the flowable ingestible medicament disposed therein;

5 a reservoir biasing mechanism applying pressure to the flexible and collapsible medicament reservoir;

a conduit extending from the medicament reservoir to the portal, and sealing the portal; and

10 a valve including a weight and valve biasing mechanism adapted, in a closed operative orientation, to bias the weight against the conduit so as to block flow through the conduit, and in an open operative orientation to remove the weight from the conduit so as to allow fluid to flow through the conduit, the valve being functionally associated with at least one of the housing and the vibrating agitation mechanism,

15 ingesting the ingestible device by the user; and

following the user ingesting the device, controlling the vibrating agitation mechanism such that in the vibration mode of operation, at least some of the vibrations exerted by the vibrating agitation mechanism or by the housing are applied to the valve biasing mechanism and periodically transition the valve between the closed operative  
20 orientation and the open operative orientation,

wherein, during the controlling, when the vibrating agitation mechanism is in the vibration mode of operation and the valve is in the open operative orientation, pressure applied by the reservoir biasing mechanism to the reservoir causes the flowable ingestible medicament to flow from the reservoir, via the conduit and the portal, to an environment  
25 surrounding the assembly.

In accordance with yet another embodiment of the present invention, there is provided a method for delivering a flowable ingestible medicament into the gastrointestinal tract of a user, the method including:

providing a vibrating ingestible capsule including:

30 a housing;

a vibrating agitation mechanism disposed within the housing and adapted such that, in a vibration mode of operation, the housing exerts vibrations on an environment surrounding the vibrating ingestible capsule;

- a power supply disposed within the housing and adapted to power the vibrating agitation mechanism; and
- a control element adapted to activate the vibrating agitation mechanism to be operative in the vibration mode of operation; and
- 5 forming an ingestible device by attaching to the vibrating ingestible capsule a medicament delivery compartment, the medicament delivery compartment including:
- a second housing portion having a portal formed therein;
- a flexible and collapsible medicament reservoir having the flowable ingestible medicament disposed therein;
- 10 a reservoir biasing mechanism applying pressure to the flexible and collapsible medicament reservoir;
- a conduit extending from the medicament reservoir to the portal, and sealing the portal; and
- a valve including a weight and a valve biasing mechanism adapted, in a closed operative orientation, to bias the weight against the conduit so as to block
- 15 flow through the conduit, and in an open operative orientation to remove the weight from the conduit so as to allow fluid to flow through the conduit, the valve being functionally associated with at least one of the housing and the vibrating agitation mechanism;
- 20 ingesting the ingestible device by the user; and
- following the user ingesting the device, controlling the vibrating ingestible capsule such that in the vibration mode of operation, at least some of the vibrations exerted by the vibrating agitation mechanism or by the housing are applied to the valve biasing mechanism and periodically transition the valve between the closed operative orientation and the open
- 25 operative orientation,
- wherein, during the controlling, when the vibrating agitation mechanism is in the vibration mode of operation and the valve is in the open operative orientation, pressure applied by the reservoir biasing mechanism to the reservoir causes the flowable ingestible medicament to flow from the reservoir, via the conduit and the portal, to an environment
- 30 surrounding the assembly.

### BRIEF DESCRIPTION OF THE FIGURES

The foregoing discussion will be understood more readily from the following detailed description of the invention, when taken in conjunction with the accompanying Figures (1-7), in which:

5           Figure 1 is a schematic block diagram of a device for delivering a flowable ingestible medicament into the gastrointestinal tract of a user according to an embodiment of the present invention;

          Figure 2 is a planar sectional illustration of a device for delivering a flowable ingestible medicament into the gastrointestinal tract of a user according to another  
10           embodiment of the present invention, the device including a medicament reservoir and a valve;

          Figure 3 is a partial perspective sectional illustration of the device of Figure 2;

          Figures 4A and 4B are partial planar sectional illustrations of the device of Figure 2, where the medicament reservoir is full, and the valve is in closed and open operative  
15           orientations, respectively;

          Figure 5 is a partial planar sectional illustration of the device of Figure 2, where the medicament reservoir is empty, and the valve is in a closed operative orientation;

          Figure 6 is a schematic diagram of a device for delivering a flowable ingestible medicament into the gastrointestinal tract of a user according to yet another embodiment of  
20           the present invention; and

          Figure 7 is a schematic flowchart of a method for delivering a flowable ingestible medicament into the gastrointestinal tract of user according to the present invention, the method being based on use of any one of the devices of Figures 1 to 6.

### 25   DESCRIPTION OF THE PREFERRED EMBODIMENTS

          The principles of the inventive devices and methods for delivery of an ingestible medicament into the body of a user, and specifically to devices and methods for such delivery of an ingestible medicament which include a vibrating capsule, may be better understood with reference to the drawings and the accompanying description.

30           Before explaining at least one embodiment of the invention in detail, it is to be understood that the invention is not limited in its application to the details of construction and the arrangement of the components set forth in the following description or illustrated in the drawings. The invention is capable of other embodiments or of being practiced or carried out in various ways. Also, it is to be understood that the phraseology and

terminology employed herein is for the purpose of description and should not be regarded as limiting.

For the purposes of this application, the term “user” relates to a human.

For the purposes of this application, the term “vibrating ingestible capsule” relates to  
5 an ingestible capsule adapted to at least intermittently vibrate, for a cumulative duration of at least one minute, in accordance with a vibration protocol of the capsule.

For the purposes of this application, the term “vibrating agitation mechanism” refers to any type of mechanism that vibrates or causes elements in its vicinity to vibrate, including a motor drive agitator such as a motor drive eccentric weight or a motor drive  
10 pendulum.

For the purposes of this application, the term “intermittently activated vibrating agitation mechanism” refers to a vibration agitation mechanism that vibrates or causes elements in its vicinity to vibrate and is operative at certain times, and does not vibrate or cause elements in its vicinity to vibrate at other times, the activation times being selected by  
15 a control element or other control unit controlling the vibration agitation mechanism.

For the purposes of this application, the term “control element”, and the equivalent term “controller” refer to a component for controlling operation of mechanical and/or electrical components of the capsule, which includes a processing unit functionally associated with a non-tangible computer readable storage medium. The storage medium  
20 stores instructions, which, when executed by the processing unit, cause the processing unit to carry out actions which control the operation of the mechanical and/or electrical components of the capsule. For example, the instructions may include instructions to activate operation of a vibrating agitation mechanism at a specific time, frequency, cycle, and/or for a specific duration. The control element may be functionally associated with, or  
25 may include, a transceiver for receiving input, which input may be used to trigger execution of specific instructions stored in the storage medium.

For the purposes of this application, the term “biasing mechanism” refers to any structure, or device, adapted to apply pressure to a second element, even when the position of the second element changes relative to an anchoring point of the structure or device.  
30 Biasing mechanisms include springs, such as compression springs and extension springs, as well as spring loaded leaves, plungers, and the like.

For the purposes of this application, the term “vibration protocol” relates to a protocol specifying vibration parameters of an intermittently activated vibrating agitation mechanism of a vibrating ingestible capsule. Typically, the vibration protocol relates to an

activation delay for initiating vibration (e.g., a duration between “initial” activation of the capsule and the first activation of the vibration agitation mechanism), a vibration rate (number of vibration cycles per hour), a vibration duration and a repose duration for each vibration cycle, a vibration frequency, an amount of force exerted by the vibrations, and the like.

For the purposes of this application, the term “treatment procedure” relates to parameters of a treatment utilizing vibrating ingestible capsules, which are typically defined by a treating physician or medical practitioner. For example, the treatment procedure may include the number of capsules to be taken within a specific time duration (e.g., 3 capsules per week, 2 capsules per day), the frequency at which capsules should be taken, the time of day at which capsules should be taken, whether the capsule should be taken with or without food, and the like.

For the purpose of this application, the term “treatment protocol” relates to all aspects of treatment of a user with a vibrating ingestible capsule, and includes the treatment procedure as well as the vibration protocol to be used for treating the user.

For the purpose of this application, the term “activation input” relates to an input received by a control element or control element of a vibrating ingestible capsule, which causes the control element or control element of the capsule to activate itself, so as to be able to process inputs and/or to control additional components of the capsule. The activation input may be received from an element forming part of the capsule, such as a sensor sensing specific conditions in which the capsule should be activated, or from a remote source, such as a remote control element, for example by way of a signal transmitted to the capsule, magnetic field applied to the capsule, specific motion applied to the capsule, or any other type of input provided to the capsule from a remote source.

For the purpose of this application, a vibrating ingestible capsule is said to be in an “inoperative state” when the capsule is in a storage condition, intended to preserve the life of a battery thereof. In the inoperative state, components of the capsule which are intended to receive or to provide an activation input, such as specific sensors, transceivers, and/or timing mechanisms may be active at least to a minimal degree. However, in the inoperative state, no vibration takes place, and a control element controlling vibration of the capsule is inactive.

For the purpose of this application, a vibrating ingestible capsule is said to be in an “operative state” when the control element of the capsule is processing inputs and data, and can cause a vibrating agitation mechanism of the capsule to vibrate or cause elements in its

vicinity to vibrate.

For the purpose of this application, an “ingestible medicament” is at least partially absorbable to the bloodstream from within the stomach, small intestine, and large intestine, and more typically, within the stomach or small intestine.

- 5 For the purpose of this application, the term “partially absorbable” is meant to include the possibility that the environment within the gastrointestinal tract (including acids, enzymes, etc. thereof) may chemically modify the ingested medicament in order to achieve the characteristic “partially absorbable”.

- 10 For the purposes of this application the term “flowable ingestible medicament” relates to any dosage form of an ingestible medicament which can flow through a conduit, such as a liquid ingestible medicament, a suspension of an ingestible medicament, a gaseous ingestible medicament, a solution of an ingestible medicament, a dissolved ingestible medicament, a melted ingestible medicament, and the like.

- 15 For the purposes of this application, the disclosure of a commercial name of a material or drug is meant to be a disclosure of the corresponding generic material or drug, and of the active ingredient(s) within the commercial material or drug and/or within the corresponding generic material or drug.

For the purpose of this application, an estimated absorption time may be determined as follows:

- 20 (i) ingestible medicaments that are absorbed in the stomach have an estimated absorption time within a range of 0.5 to 1.5 hours from the time of ingestion of the ingestible medicament;

- (ii) ingestible medicaments that are absorbed in the small intestine have an estimated absorption time within a range of 1.0 to 5 hours from the time of ingestion of the ingestible  
25 medicament;

(iii) ingestible medicaments that are absorbed in both the stomach and the small intestine have an estimated absorption time within a range of 0.5 to 5 hours from the time of ingestion of the ingestible medicament;

- (iv) ingestible medicaments that are absorbed in the large intestine have an estimated  
30 absorption time of at least 4 hours, and more typically, within a range of 4 to 30 hours, 6 to 30 hours, 6 to 20 hours, or 8 to 20 hours from the time of ingestion of the ingestible medicament.

The location within the GI tract at which the particular ingestible medicament is absorbed to the bloodstream may often be public knowledge. This location may be provided

by, or known to, the manufacturer and/or distributor of the particular ingestible medicament. Alternatively or additionally, the location may be known to relevant medical practitioners, including doctors and pharmacists, and more particularly, to a medical practitioner of the user.

- 5           For the purpose of this application, an actual absorption time may be determined from clinical data, *in vivo* or *in vitro*, according to accepted clinical procedures known to those of skill in the art. Since actual absorption is achieved over a period of time, the “actual absorption time” or “actual absorption time period” may be defined by the time period at which between 20% and 80% of the absorption occurs. In the absence of such data, the
- 10           “actual absorption time” or “actual absorption time period” may be defined by determining the “peak” actual absorption time, and building a time period of up to 1 hour on each side of the peak time.

- For the purpose of this application, a recovery time of a resilient conduit relates to the duration from a time from release of a force pinching the resilient conduit such that no
- 15           fluid can flow therethrough, till the conduit is not blocking the flow. This may occur when the conduit is partially recovered, i.e. the force has been removed such that there is a hollow in the conduit but the conduit has not returned to its initial diameter, or when the conduit is fully recovered and has returned to its initial, nominal diameter.

- For the purpose of this application, the term “Parkinsonism” is meant to include
- 20           Parkinson's disease, or symptoms of neurodegeneration associated therewith.

            For the purpose of this application, the term “Parkinsonism” is meant to include progressive supranuclear palsy, or symptoms of neurodegeneration associated therewith.

            For the purpose of this application, the term “Parkinsonism” is meant to include corticobasal degeneration, or symptoms of neurodegeneration associated therewith.

- 25           For the purpose of this application, the term “Parkinsonism” is meant to include multiple system atrophy, or symptoms of neurodegeneration associated therewith.

            For the purpose of this application, the term “Parkinsonism” is meant to include Parkinson-plus syndromes (also known as disorders of multiple system degeneration), or symptoms of neurodegeneration associated therewith.

- 30           For the purpose of this application, the term “Parkinsonism” is meant to include any neurodegenerative disease in which the subject exhibits at least one (and typically at least two or three) of the classical features of Parkinson's disease: tremor, postural instability, and akinesia or bradykinesia.

            For the purpose of this application, the term “Parkinsonism” is meant to include any

neurodegenerative disease in which the subject positively responds to a dopaminergic treatment.

For the purpose of this application, the term “Parkinsonism” is meant to include any neurodegenerative disease in which the particular subject positively responds to an  
5 anticholinergic treatment.

For the purpose of this application, the term “Parkinsonism” is meant to include any neurodegenerative disease in which a dopaminergic treatment is clinically utilized to treat the sufferers or subjects.

For the purpose of this application, the term “Parkinsonism” is meant to include any  
10 neurodegenerative disease in which an anticholinergic treatment is clinically utilized to treat the sufferers or subjects.

For the purpose of this application, the term “Parkinson's disease” (PD) is meant as used by those of skill in the art of neurodegenerative diseases. It is believed that PD is due to the loss of brain cells that produce dopamine. Early signs and symptoms of Parkinson's  
15 disease include at least one of tremors (or trembling), slowness of movement, body rigidity and stiffness, and gait problems.

For the purpose of this application, the term “treatment of Parkinsonism” and the like refers to at least one of: (i) delaying onset of Parkinsonism (e.g., PD); (ii) mitigating the development of Parkinsonism (e.g., PD); and (iii) managing a condition of Parkinsonism  
20 (e.g., PD).

For the purpose of this application, the term “ailment of the GI tract” is meant to include chronic or acute constipation, or symptoms associated therewith.

For the purpose of this application, the term “ailment of the GI tract” is meant to include gastroparesis, or symptoms associated therewith.

25 For the purpose of this application, the term “ailment of the GI tract” is meant to include Crohn's disease, or symptoms associated therewith.

For the purpose of this application, the term “ailment of the GI tract” is meant to include chronic or acute diarrhea, or symptoms associated therewith.

For the purpose of this application, the term “ailment of the GI tract” is meant to  
30 include colitis, or symptoms associated therewith.

For the purpose of this application, the term “ailment of the GI tract” is meant to include dyspepsia or dysphagia, or symptoms associated therewith.

For the purpose of this application, the term “ailment of the GI tract” is meant to include Hirschsprung's disease, or symptoms associated therewith.

For the purpose of this application, the term “ailment of the GI tract” is meant to include irritable bowel syndrome, or symptoms associated therewith.

For the purpose of this application, the term “ailment of the GI tract” is meant to include any disease in which the subject positively responds to an osmotic gastrointestinal  
5 treatment.

For the purpose of this application, the term “ailment of the GI tract” is meant to include any disease in which the particular subject positively responds to a stool softening treatment.

For the purpose of this application, the term “ailment of the GI tract” is meant to include any disease in which the particular subject positively responds to a GI contraction  
10 inducing treatment.

For the purpose of this application, the term “ailment of the GI tract” is meant to include any disease in which the subject positively responds to a GI fluid absorption inducing treatment.

For the purpose of this application, the term “managing a condition of”, with respect to an ailment of the GI tract, is meant to include, *inter alia*, improving absorption of a medicament, such as a medicament used in the treatment of the ailment of the GI tract (e.g., Linaclotide (Linzess®)), into the bloodstream. Such condition management may be manifested by at least one of (i) improved medicament efficacy due to the increased  
20 absorption; and (ii) reduced dosage of the medicament, due to the increased medicament absorption efficacy.

For the purpose of this application, the term “managing a condition of”, with respect to Parkinsonism and the like, is meant to include, *inter alia*, improving absorption of a medicament, such as a medicament used in the treatment of Parkinsonism (e.g., levodopa),  
25 into the bloodstream. Such condition management may be manifested by at least one of (i) improved medicament efficacy due to the increased absorption; and (ii) reduced dosage of the medicament, due to the increased medicament absorption efficacy.

Referring now to the drawings, Figure 1 is a schematic block diagram of a device **100** for delivering a flowable ingestible medicament **102** into the gastrointestinal tract of a user according to an embodiment of the present invention.  
30

It is a particular feature of the present invention that delivery of the flowable ingestible medicament is triggered by, and occurs only during a time at which a vibrating ingestible capsule is a vibration mode of operation, as explained in detail hereinbelow. Stated differently, delivery of the flowable ingestible medicament only occurs when the

vibrating ingestible capsule is actually vibrating, and is triggered by such vibration of the vibrating ingestible capsule.

As seen in Figure 1, device **100** includes vibrating ingestible capsule **110**. Capsule **110** includes a capsule housing or shell **112**, also termed a first housing portion, arranged  
5 along a longitudinal axis **113** and having disposed therein a vibrating agitation mechanism **114**. A control element **116** is adapted to control operation of vibrating agitation mechanism **114**, and at least one power source **118** provides power to vibrating agitation mechanism **114** and control element **116**.

The vibrating ingestible capsule **110** is functionally associated with a medicament  
10 delivery compartment **120**.

In some embodiments, the medicament delivery compartment **120** is distinct from the vibrating ingestible capsule **110**, and is attached thereto, as illustrated in Figure 1 and as explained hereinbelow with respect to Figure 2. In such embodiments, the medicament delivery compartment includes a hollow medicament compartment housing **121**, also termed  
15 a second housing portion, defining a hollow **122**. The hollow compartment housing includes a portal **123** and is attached to housing **112** of capsule **110**.

Medicament compartment housing **120** may be fixedly attached to housing **112** of vibrating ingestible capsule **110**, or removably attached thereto. Medicament compartment housing **120** may be attached to housing **112** of vibrating ingestible capsule **110** using any  
20 suitable attachment method, such as by adhering, by soldering, by snap fit engagement or by threaded engagement.

In some embodiments, housing **112** of vibrating ingestible capsule **110** includes an attachment mechanism, and hollow medicament compartment housing **121** includes a corresponding attachment mechanism, for mutual attachment of vibrating ingestible capsule  
25 **110** to hollow medicament compartment housing **121**. An exemplary arrangement of such attachment mechanisms is illustrated, for example, in Figures 3 to 4B described in detail hereinbelow.

In other embodiments, the medicament delivery compartment **120** may form part of the vibrating ingestible capsule **110**, as explained hereinbelow with respect to Figure 6. In  
30 such embodiments, the portal **123** is formed in housing **112**, and the hollow of the vibrating ingestible capsule includes all components otherwise included in hollow **122**, as explained hereinbelow.

A flexible and collapsible medicament reservoir **124**, which is adapted to have the flowable ingestible medicament **102** disposed therein, is disposed within hollow **122**, and

pressure is constantly applied thereto by a reservoir biasing mechanism 125, which may be anchored to medicament compartment housing 121. A conduit 126, which may be a flexible and/or resilient conduit, extends from medicament reservoir 124 to portal 123, such that a fluid flowing through the conduit is delivered to an environment surrounding device 100.

5 Typically, conduit 126 seals portal 123, to prevent fluid from the environment surrounding device 100 from entering the device.

A valve, which includes a weight 128 and a valve biasing mechanism 129, typically a spring, adapted, in a closed operative orientation, to block flow through the conduit 126 by biasing weight 128 against the conduit thereby to pinch the conduit, and, in an open  
10 operative orientation, to remove weight 128 from applying pressure to conduit 126, such that, following the recovery time of the conduit, fluid may flow through the conduit.

It is a particular feature of the present invention that valve biasing mechanism 129 is functionally associated with housing 112 or with vibrating agitation mechanism 114. When vibrating agitation mechanism 114 is in an inoperative state, or is operative but not in a  
15 vibration mode of operation, valve biasing mechanism 129 biases weight 128 against conduit 126, such that the valve is in the closed operative orientation and fluid cannot flow through the conduit. When vibrating agitation mechanism 114 is in a vibration mode of operation and exerts vibrations on housing 112, at least some of the exerted vibrations are applied to valve biasing mechanism 129, and cause the valve biasing mechanism to move  
20 periodically. Periodic motion of the valve biasing mechanism 129 results in corresponding periodic motion of weight 128 away from conduit 126, thereby transitioning the valve from the closed operative orientation to an open operative orientation and allowing fluid to flow through conduit 126.

Due to the flexibility and resiliency of conduit 126, when the weight 128 is moved  
25 away from the conduit, conduit 126 at least partially recovers such that fluid can flow through the conduit. Because reservoir biasing mechanism 125 constantly applies pressure to reservoir 124, upon recovery of conduit 126, enables the flowable ingestible medicament flows through the conduit, and out of portal 123, into an environment surrounding the device 100. As such, delivery of the flowable ingestible medicament is triggered by, and  
30 controlled by, vibration of the vibrating agitation mechanism 114.

The rate at which the flowable ingestible medicament is delivered into the environment surrounding device 100 is dependent on characteristics of the conduit 126, such as the diameter of the conduit, the thickness of the conduit walls, and the recovery time

of the conduit, as well as on characteristics of the valve, such as the frequency of transitioning between the open and closed operative orientations of the valve.

It will be appreciated that the frequency at which valve biasing mechanism 129 transitions the valve between the open and closed operative orientations, by causing weight 128 to move towards and away from conduit 126, is dependent on the frequency of vibrations exerted by vibrating agitation mechanism 114 or by housing 112, as well as on the characteristics of the valve, such as the mass of weight 128 and the spring constant of the biasing mechanism 129.

In some embodiments, the mass of weight 128 and the length and spring constant of biasing mechanism 129 may be selected such that the valve functions as a gear reducer. In such embodiments, the frequency at which the valve transitions between the closed and open operative orientations (i.e. the frequency at which the valve biasing mechanism 129 draws weight 128 away from conduit 126 and then pushes the weight 128 back to apply pressure to conduit 126) may be smaller than the frequency of vibrations exerted by vibrating agitation mechanism 114.

In some embodiments, valve biasing mechanism 129 is anchored to housing 112. In some embodiments, valve biasing mechanism 129 may be anchored to medicament compartment housing 121, provided that the attachment between the medicament compartment housing 121 and housing 112 of vibrating ingestible capsule 110 does not dampen or reduce the frequency or intensity of vibrations applied to valve biasing mechanism 129, and that the frequency and intensity of vibrations exerted on medicament compartment housing 121 is substantially equal to that of vibrations exerted on housing 112.

Relating now to characteristics of the medicament delivery compartment 120, in some embodiments, in which the medicament delivery compartment 120 is distinct from vibrating ingestible capsule 110, hollow 122 of medicament compartment housing 121 has a volume in the range of  $200\text{mm}^3$  to  $800\text{mm}^3$ ,  $300\text{mm}^3$  to  $700\text{mm}^3$ , or  $400\text{mm}^3$  to  $600\text{mm}^3$ . In other embodiments, in which housing 112 houses components of medicament delivery compartment 120, the housing 112 has a volume in the range of  $1000\text{mm}^3$  to  $4000\text{mm}^3$ .

In some embodiments, medicament reservoir 124 has a maximal volume in the range of  $1\text{mm}^3$  to  $600\text{mm}^3$ ,  $1\text{mm}^3$  to  $10\text{mm}^3$ ,  $5\text{mm}^3$  to  $20\text{mm}^3$ ,  $15\text{mm}^3$  to  $50\text{mm}^3$ ,  $30\text{mm}^3$  to  $200\text{mm}^3$ ,  $100\text{mm}^3$  to  $400\text{mm}^3$ , or  $300\text{mm}^3$  to  $600\text{mm}^3$ .

In some embodiments, medicament reservoir 124 has elastic or elastomeric properties, and may have a low value for Young's modulus, typically smaller than 1 GPa.

In some embodiments, medicament reservoir **124** is formed of a material selected from the group consisting of: silicone rubber, natural rubber, Polyethylene, and PVC.

In some embodiments, reservoir biasing mechanism **125** includes a reservoir spring terminating in a pressure applying surface which engages an exterior surface of medicament reservoir **124**, as illustrated in Figures 2 to 5. In such embodiments, the reservoir spring may be anchored to medicament compartment housing **121**.

In some embodiments, reservoir biasing mechanism **125** has a spring constant  $K$  in the range of 1 N/m to 200 N/m.

In some embodiments, flexible and resilient conduit **126** is integrally formed with flexible and collapsible medicament reservoir **124**. In other embodiments, conduit **126** is formed of a different material than medicament reservoir **124**.

In order to ensure that when vibrating agitation mechanism **114** is in the vibration mode of operation, fluid can be delivered through conduit **126**, the recovery time of the conduit must be sufficiently short for the conduit to recover its nominal diameter, and facilitate passage of fluid therethrough, before the conduit is once again pinched by weight **128**.

As such, in some embodiments, when vibrating agitation mechanism has a frequency  $f$ , a recovery time of conduit **126** is at most equal to  $1/f$ . In other embodiments, when valve biasing mechanism **129** has a frequency  $f_v$  of transitioning the valve between the open and closed operative orientations, a recovery time of conduit **126** is at most equal to  $1/f_v$ .

In some embodiments, a recovery time of conduit **126** is at most 0.1 seconds.

In some embodiments, conduit **126** has a diameter in the range of 0.01mm-0.9mm.

In some embodiments, conduit **126** has a length in the range of 3mm-25mm.

In some embodiments, valve biasing mechanism **129** has a spring constant in the range of 0.1 N/m to 5 N/m.

In some embodiments, weight **128** has a mass in the range of 0.1 grams to 2 grams.

Relating specifically to capsule **110**, power source **118** may be any suitable power source, such as one or more alkaline or silver oxide batteries, primary batteries, rechargeable batteries, capacitors and/or supercapacitors.

Intermittently activated vibrating agitation mechanism **114** is adapted to have a vibration mode of operation (also termed the first mode of operation) and a rest mode of operation (also termed the second mode of operation). In the vibration mode of operation, intermittently activated vibrating agitation mechanism **114** is adapted to exert forces on capsule housing **112**, such that capsule housing **112** exerts vibrations on an environment

surrounding capsule 110 and/or device 100.

In some embodiments, the capsule 110 is in an inoperative state, until the receipt of an activation input, which causes control element 116 to transition the capsule from the inoperative state to an operative state.

5 In some embodiments, control element 116 is functionally associated with, or includes, a timer or timing mechanism 130, such as a clock, universal clock, or stopwatch, powered by power source 118 and adapted to track at least one time characteristic, such as a duration that has passed since an activation input was received, or a duration that has passed since the user ingested capsule 110.

10 In some embodiments, capsule 110 is devoid of any sensors for sensing an environment thereof. In some such embodiments, control element 116 is adapted, in response to receipt of an activation input, to wait a predetermined delay time, and following the predetermined delay time, to activate vibrating agitation mechanism 114 to operate in said first vibration mode of operation.

15 In other embodiments, such as the embodiment illustrated in Figure 1, capsule 110 further includes at least one sensor 132, functionally associated with control element 116. The at least one sensor 132 may be adapted to sense at least one parameter within capsule 110 or in an environment of capsule 110, and may include a temperature sensor, an illumination sensor, a moisture sensor, a pressure sensor, an accelerometer, or any other  
20 suitable sensor. In some embodiments, the at least one sensor 132 is adapted to identify a specific condition in capsule 110 or in the vicinity thereof, and to provide an activation input to control element 116 in response to identification of the condition. For example, in some embodiments the condition is indicative of the user ingesting capsule 110.

For example, in some embodiments sensor 132 may include an illumination sensor,  
25 adapted to identify transition of capsule 110 from an illuminated environment (e.g. outside the human body) to a dark environment (e.g. within the human body) and to provide an activation input in response to identification of such a transition.

As another example, in some embodiments sensor 132 may include a motion or acceleration sensor, such as an accelerometer, adapted to identify an activation motion  
30 carried out by a user on capsule 110 or on device 100 and to provide an activation input in response to identification of such a transition. An example of an accelerometer providing an activation input for a gastrointestinal capsule is provided in US Patent No. 10,314,514, which is incorporated by reference for all purposes as if fully set forth herein.

As another example, in some embodiments sensor **132** may include a pressure sensor adapted identify pressure applied to the capsule **110** or to device **100**, which pressure is indicative of the capsule moving through a pharynx of the user, and to provide an activation input in response to identification of such pressure.

5       As a further example, in some embodiments sensor **132** may include a temperature sensor adapted to identify transition of capsule **110** or of device **100** from an area with ambient temperature (e.g. outside the human body) to an area with a human body temperature and to provide an activation input in response to identification of such a transition.

10       As a further example, in some embodiments sensor **132** may include a moisture sensor adapted to identify transition of capsule **110** or of device **100** from a dry area (e.g. outside the human body) to a moist area (e.g. within the human body) and to provide an activation input in response to identification of such a transition.

15       It will be appreciated by people of skill in the art that sensor **132** need not necessarily be disposed within capsule **110**, as illustrated in Figure 1, and may be disposed anywhere within device **100**, for example within hollow **122** of medicament compartment housing **120**, on an exterior of capsule **110**, or on the exterior of device **100**.

20       In some embodiments, device **100** may be functionally associated with a control unit **140**, which may be remote from device **100** and from capsule **110**, and which is adapted to provide one or more inputs to the capsule. In some such embodiments, capsule **110** further includes a remote input receiving mechanism **136**, functionally associated with control element **116**, and adapted to receive inputs from an input providing mechanism **142** of control unit **140**.

25       In some embodiments, control unit **140** may further include a timing mechanism **146**, adapted to track at least one time characteristic, such as a duration that has passed since a control instruction was provided to capsule **110**.

      In some embodiments, control unit **140** may further include a user input receiver **148**, such as a keyboard, touch screen, or touch pad, adapted to receive input from a user, such as the user, a medical professional treating the user, or a caregiver of the user.

30       Control unit **140** may be any suitable type of control unit. In some embodiments, control unit may be a suitably configured smart phone or a tablet computer.

      In some such embodiments, control unit **140** may provide inputs to capsule **110** by remotely transmitting the inputs from input providing mechanism **142** to remote input receiving mechanism **136**, for example using a short range wireless communication method,

such as radio frequency (RF) communication or Bluetooth® communication. One example of such a mechanism for providing input to a capsule is described in US Patent No. 10,478,373, which is incorporated by reference for all purposes as if fully set forth herein.

5 In some embodiments, control unit **140** is adapted to provide the activation input to control element **116** of capsule **110**. In some such embodiments, control unit **140** provides the activation input prior to the user ingesting device **100** including capsule **110**, whereas in other embodiments control unit **140** provides the activation input following ingestion of device **100** and capsule **110** by the user.

10 Relating to the characteristics of vibrating agitation mechanism **114**, the vibrating agitation mechanism may be any suitable mechanism that can be intermittently activated and can apply suitable forces onto capsule housing **112**.

15 In some embodiments, intermittently activated vibrating agitation mechanism **114** may include a radial agitation mechanism adapted to exert radial forces on capsule housing **112**, in a radial direction with respect to the longitudinal axis of housing **112**. For example, the radial agitation mechanism may include an unbalanced weight attached to a shaft of an electric motor powered by said battery, substantially as described in US Patent Number 9,707,150, which is incorporated by reference for all purposes as if fully set forth herein.

20 In some embodiments, intermittently activated vibrating agitation mechanism **114** may include an axial agitation mechanism adapted to exert radial forces on the capsule housing **112**, in an axial direction with respect to a longitudinal axis of housing **112**. For example, the axial agitation mechanism may include an electric motor powered by the battery and an urging mechanism, associated with, and driven by, the electric motor, such that the urging mechanism adapted to exert said axial forces, substantially as described in US Patent Number 9,707,150. In some embodiments, the urging mechanism adapted to  
25 exert the axial forces in opposite directions. In some embodiments, the urging mechanism is adapted to deliver at least a portion of the axial forces in a knocking mode.

30 In some embodiments, the forces exerted by intermittently activated vibrating agitation mechanism **114** on capsule housing **112** in the vibration mode of operation include radial forces in a radial direction with respect to the longitudinal axis of the housing and axial forces in an axial direction with respect to the longitudinal axis. In some embodiments, a single agitation mechanism exerts both the radial and the axial forces. In other embodiments, the axial forces are exerted by one agitation mechanism, and the radial forces are exerted by another, separate, agitation mechanism, where both agitation mechanisms form part of intermittently activated vibrating agitation mechanism **114**.

In some embodiments, the intermittently activated vibrating agitation mechanism 114 may include a magnet mounted onto a rotor adapted to exert a magnetic field as well as radial forces on capsule housing 112. For example, such a magnetic vibration agitation mechanism is described in US Patent Application Publication No. 2016/0310357, which is  
5 incorporated by reference for all purposes as if fully set forth herein.

In some embodiments, housing 112 may include first and second members, and vibrating agitation mechanism 114 may include a mechanism adapted to effect a vibration by moving the first member of the housing in the opposite direction relative to the second member of the housing, substantially as described in US Patent Number 9,078,799, which is  
10 incorporated by reference for all purposes as if fully set forth herein.

In some embodiments, housing 112 may include a vibration agitation mechanism 114 which makes use of a pendulum to cause vibration in the vicinity of the capsule, for example as described in CN Patent Application Number 105997466 filed on June 16, 2016, which is incorporated by reference for all purposes as if fully set forth herein.

15 In some embodiments, or at some times, control element 116 is adapted to control vibration agitation mechanism 114, and specifically to set at least one vibration parameter of vibration agitation mechanism 114, so as to promote delivery of the flowable ingestible medicament into an environment surrounding device 100 and/or absorption of the ingestible medicament into the bloodstream of the user.

20 For example, delivery of the flowable ingestible medicament into an environment surrounding device 100 may be promoted by controlling one or more characteristics of the vibrating agitation mechanism 114 such that conduit 126 is open for relatively long durations, facilitating rapid delivery of the flowable medicament into the gastrointestinal tract.

25 As another example, absorption of the ingestible medicament may be promoted by the vibration promoting emulsification of the ingestible medicament. As yet another example, absorption of the ingestible medicament may be promoted by the vibration causing a hydrophobic phase of the ingestible medicament to form smaller bubbles, thereby increasing the surface area of the hydrophobic phase for absorption thereof. In another  
30 example, absorption of the ingestible medicament may be promoted by the vibration causing greater exposure of the ingestible medicament to the environment.

In some embodiments, or at some times, control element 116 may be adapted to control vibrating agitation mechanism 114 so that the capsule applies forces to an

environment thereof, such that within the gastrointestinal tract, a mechanical stimulation of the wall of the gastrointestinal tract is effected.

In some such embodiments, the at least one vibration parameter includes at least one of a vibration frequency, a cumulative vibration duration, a number of vibration cycles per time unit, a duration of a vibration duration within a vibration cycle, a duration of a repose  
5 duration within a vibration cycle, a total duration of a single vibration cycle, and a net force exerted by said housing on said environment, as explained in further detail hereinbelow.

In some embodiments, control element 116 is adapted to control a timing or activation delay of the vibration mode of operation of the vibration agitation mechanism 114  
10 such that the vibration mode of operation at least partially transpires within a region of the gastrointestinal tract in which the flowable ingestible medicament is absorbable by the body of the user, and at which it is desirable for the flowable ingestible medicament to be delivered into the gastrointestinal tract.

In some embodiments, control element 116 is adapted to control a timing or  
15 activation delay of the vibration mode of operation of the vibration agitation mechanism 114 such that the vibration mode of operation at least partially transpires within an estimated absorption time period of the flowable ingestible medicament 102 within the gastrointestinal tract of the user.

In some embodiments, control element 116 is adapted to control a timing or  
20 activation delay of the vibration mode of operation of the vibration agitation mechanism 114 such that the vibration mode of operation at least partially transpires within an actual absorption time period of the flowable ingestible medicament 102 within the gastrointestinal tract of the user.

In the vibrating mode of operation, intermittently activated vibrating agitation  
25 mechanism 114 is adapted to have a plurality of vibration cycles, where each cycle includes a vibration duration followed by a repose duration. Forces are exerted by the vibrating agitation mechanism 114 on capsule housing 112 only during the vibration duration, and as such, capsule housing 112 only exerts forces on an environment thereof during the vibration duration.

30 In some embodiments, the number of vibration cycles per hour is in the range of 20 to 400, 40 to 400, 60 to 400, 80 to 400, 40 to 380, 60 to 380, 80 to 380, 40 to 360, 60 to 360, 80 to 360, 100 to 360, 100 to 330, 100 to 300, 100 to 280, 100 to 250, 100 to 220, 100 to 200, 120 to 300, 120 to 280, 120 to 250, 120 to 220, 120 to 200, 150 to 300, 150 to 280, 150 to 250, 150 to 220, 150 to 200, 170 to 300, 170 to 250, 170 to 220, or 170 to 200.

In some embodiments, the repose duration is greater than the vibration duration.

In some embodiments, the vibration duration is in the range of 0.1 second to 10 seconds, 1 second to 10 seconds, 1 second to 9 seconds, 2 seconds to 9 seconds, 3 seconds to 9 seconds, 3 seconds to 8 seconds, 3 seconds to 7 seconds, 3 seconds to 6 seconds, 4  
5 seconds to 6 seconds, or 5 seconds to 6 seconds.

In some embodiments, the repose duration is in the range of 1 second to 180 seconds, 3 seconds to 180 seconds, 5 seconds to 180 seconds, 5 seconds to 150 seconds, 5 seconds to 120 seconds, 8 seconds to 100 seconds, 8 seconds to 30 seconds, 10 seconds to 80 seconds, 10 seconds to 70 seconds, 10 seconds to 60 seconds, 10 seconds to 50 seconds,  
10 10 seconds to 40 seconds, 10 seconds to 30 seconds, 10 seconds to 20 seconds, or 15 seconds to 20 seconds.

In some embodiments, the total duration of one vibration cycle is in the range of 1.1 seconds to 200 seconds, 5 seconds to 200 seconds, 10 seconds to 200 seconds, 10 seconds to 150 seconds, 10 seconds to 100 seconds, 10 seconds to 80 seconds, 10 seconds to 50  
15 seconds, 10 seconds to 40 seconds, 10 seconds to 30 seconds, 15 seconds to 50 seconds, 15 seconds to 40 seconds, 15 seconds to 30 seconds, or 15 seconds to 25 seconds.

In some embodiments, the cumulative duration of the vibrating mode of operation, or the cumulative duration during which vibration cycles are occurring, is in the range of 1 hour to 12 hours, 2 hours to 10 hours, 2 hours to 8 hours, 2 hours to 6 hours, 2 hours to 4  
20 hours, or 2 hours to 3 hours. It will be appreciated that the cumulative duration of vibration cycles may be dependent on properties of power source **118**.

It will be appreciated by persons skilled in the art that the vibration mode of operation may be intermittent, or interrupted, such that vibrating agitation mechanism **114** is operative in the vibration mode for a first duration, for example 30 minutes, then does have  
25 any vibration cycles for a second duration, for example 1 hour, and then is operative in the vibration mode and has vibration cycles for a third duration, for example two hours. The cumulative duration relates to the sum of all durations during which vibrating agitation mechanism **114** was operative in the vibration mode and included vibration cycles, including the vibration duration and the repose duration of the vibration cycle.

30 In some embodiments, vibrating agitation mechanism **114** is configured to exert forces on the capsule housing **112**, such that a net force exerted by the capsule housing **112** on the environment thereof is preferably in the range of 50 grams force (gf) to 600gf, 50gf to 550gf, 100gf to 550gf, 100gf to 500gf, 150gf to 500gf, 200gf to 500gf, or 200gf to 450gf.

In some embodiments, vibrating agitation mechanism **114** is configured to exert said forces on capsule housing **112** to attain a capsule housing **112** vibrational frequency within a range of 10Hz to 650Hz, 15Hz to 600Hz, 20Hz to 550Hz, 30Hz to 550Hz, 50Hz to 500Hz, 70Hz to 500Hz, 100Hz to 500Hz, 130Hz to 500Hz, or 150Hz to 500Hz.

5           It will be appreciated that the exact specifications of the capsule, such as the specific frequency and force ranges applicable to a specific capsule, are dependent on the specifications of the power source **118** and of the vibrating agitation mechanism **114**.

          It will be further appreciated that a specific capsule may be controlled by the control element **116** such that different vibrational frequencies may be attained and/or different net  
10       forces may be exerted, by the capsule in different vibration cycles of the capsule. Due to the natural distinction between users, use of multiple different parameters in different vibration cycles of a single capsule would allow the capsule to successfully treat multiple users, even if the personal optimal treatment for those users is not the same, as there is a higher chance that in at least some of the vibration cycles the activation parameters of the capsule would  
15       reach, or be close to, the optimal parameters for each specific user.

          Control element **116** is adapted to control the operation of intermittently activated vibrating agitation mechanism **114**. Such control may include control of any one or more of the force applied by the vibrating agitation mechanism **114**, the vibrational frequency reached, the times in which vibrating agitation mechanism **114** operates in the vibration  
20       mode of operation, the vibration duration of each vibration cycle, the repose duration of each vibration cycle, the vibration cycle duration, and cumulative vibration duration of the vibrating agitation mechanisms.

          In some embodiments, control element **116** is adapted to receive information relating to the desired vibration protocol from control unit **140**, prior to ingestion of device **100** and  
25       capsule **110** or to activation of the capsule, or during the device's and capsule's traversal of the user's GI tract. For example, the information may be remotely transmitted from control unit **140** to control element **116**, for example using a short range wireless communication method. In some embodiments, the information is transmitted as a list of vibration parameters for effecting the vibration protocol. In some embodiments, the information is  
30       transmitted as executable code for effecting the first vibration protocol.

          In some embodiments, the information includes a desired number of vibration cycles, a desired vibration duration in each vibration cycle, a desired repose duration in each vibration cycle, a desired cumulative vibration duration, and the like.

In some embodiments, the flowable ingestible medicament is absorbable or at least partially absorbable in the stomach of the user. In some embodiments, the flowable ingestible medicament is absorbable or at least partially absorbable in the small intestine of the user.

5 In some embodiments, the flowable ingestible medicament has a viscosity in the range of 100 Pa·s to 1000 Pa·s.

In some embodiments, the flowable ingestible medicament is suitable for treatment of one or more symptom or disease, selected from the group consisting of: Parkinsonism; Parkinson's Disease; progressive supranuclear palsy; corticobasal degeneration; multiple  
10 system atrophy; Parkinson-plus syndromes (also known as disorders of multiple system degeneration); any neurodegenerative disease in which the subject exhibits at least one (and typically at least two or three) of the classical features of Parkinson's disease: tremor, postural instability, and akinesia or bradykinesia; any neurodegenerative disease in which the subject positively responds to a dopaminergic treatment; any neurodegenerative disease in  
15 which the particular subject positively responds to an anticholinergic treatment; Constipation; Crohn's disease; Gastroparesis; irritable bowel syndrome (IBS); diarrhea or loose bowel movements; colitis; Hirschsprung's disease; Dyspepsia; and dysphagia.

In some embodiments, the flowable ingestible medicament comprises or includes an ingestible medicament selected from the group consisting of: levodopa; at least one  
20 dopaminergic agent; at least one catecholamine precursor; a dopamine precursor; at least one dopamine precursor agent; (L)-3,4-dihydroxyphenylalanine; N-methyl-N-(2-propynyl)-2-methyl-1-phenylethyl-2-amine; tyrosine hydroxylase; apomorphine; at least one anticholinergic agent; at least one agent selected to antagonize at least one cholinergic receptor; benzhexol; orphenadrine; at least one selective allosteric potentiator of  
25 metabotropic glutamate receptor 4 (mGluR4); N-phenyl-7-(hydroxylimino)cyclopropa[b]chromen-1a-carboxamide; at least one osmotic agent; magnesium citrate; magnesium hydroxide; polyethylene glycol; sodium phosphate; MiraLAX®; at least one contraction stimulating agent; bisacodyl; senna; Correctol; Ducodyl; Dulcolax; Senexon; Senokot; at least one stool softening agent; docusate sodium;  
30 Colace; Linaclotide; Lactulose; lubiprostone; plecanatide; prucaltride; loperamide; and bismuth subsalicylate.

Reference is now made to Figure 2, which is a planar sectional illustration of a device 200 for delivering a flowable ingestible medicament **202** into the gastrointestinal tract of a user according to another embodiment of the present invention, the device

including a medicament reservoir **224** and a valve, to Figure 3, which is a partial perspective sectional illustration of device **200**, to Figures 4A and 4B, which are partial planar sectional illustrations of device **200**, where medicament reservoir **224** is full, and the valve is in closed and open operative orientations, respectively, and to Figure 5, which is a partial  
5 planar sectional illustrations of device **200**, where medicament reservoir **124** is empty, and the valve is in a closed operative orientation.

As seen, device **200**, which is arranged along a longitudinal axis, includes a vibrating ingestible capsule **210** including a housing **212**, substantially as described hereinabove with respect to Figure 1. It will be appreciated that capsule **210** includes at least  
10 a vibrating agitation mechanism, a control element, and a power source, as described hereinabove with respect to Figure 1, even though these components are not explicitly shown in Figures 2A to 4B.

A medicament delivery compartment **220**, here illustrated as having the shape of a convex dome is formed by a medicament compartment housing **221** which defines a hollow  
15 **222**. A portal **223** is formed in medicament compartment housing **221**. Medicament reservoir **224** is disposed within hollow **222**, and is biased toward capsule **210** by a reservoir biasing mechanism. The reservoir biasing mechanism includes a spring **225a** anchored at one end thereof to medicament compartment housing **221** and terminating, at an opposing end, in a biasing plate **225b** which engages an exterior surface of medicament reservoir **224**  
20 and applies pressure thereto. The medicament reservoir **224** is flexible and collapsible, and may be formed of any suitable material such as silicone rubber, natural rubber, polyethylene, and PVC.

A conduit **226**, which may be a flexible and/or resilient conduit, extends from medicament reservoir **224** to portal **223**, and terminates with portal **223**, such that fluid can  
25 flow from medicament reservoir **224**, via conduit **226** and portal **223**, out of the device **200** and into an environment surrounding the device. In some embodiments, the end of conduit **226** disposed within portal **223** also seals the portal, so as to prevent material from the environment entering device **200**. In other embodiments, the end of conduit **226** may be surrounded by a seal sealing the portal.

A valve **227** disposed within hollow **222** includes a weight **228** attached to a compression spring **229**, which functions as a valve biasing mechanism. The spring **229** is anchored, at an end distal to weight **228**, to a rigid anchoring shelf **230** extending from medicament compartment housing **221** or from housing **212** of vibrating ingestible capsule  
30 **210**.

Biassing spring 229 and weight 228 are constructed such that, when vibrating ingestible capsule 210 is in an inoperative mode, or is in an operative mode but not vibrating, biassing spring 229 biases weight 228 against conduit 226, thus pinching the conduit closed, as illustrated clearly in Figure 4A. This is the closed operative orientation of valve 227. When valve 227 is in the closed operative orientation, no fluid can flow through conduit 226, and pressure applied by the reservoir biasing mechanism to medicament reservoir 224 is at an equilibrium with forces resisting such pressure by the content of the medicament reservoir and conduit.

However, when vibrating ingestible capsule 210 is in the vibrating mode of operation, vibration of the vibrating ingestible capsule 210 is applied also to biassing spring 229, via anchoring shelf 230. As discussed hereinabove, the vibrations of the capsule 210 are periodic, and cause the spring to periodically contract and extend. Contraction of the spring 229 results in weight 228 being withdrawn, or moved away, from conduit 226, thus enabling the conduit 226 to recover its nominal diameter and fluid to flow through the conduit 226, as illustrated in Figure 4B. This is the open operative orientation of valve 227. When valve 227 is in the open operative orientation, pressure applied by the reservoir biasing mechanism to medicament reservoir 224 causes medicament 202 to flow from reservoir 224, via conduit 226 and portal 223, into the environment surrounding device 200.

In use, when capsule 210 is in the vibrating mode of operation, valve 227 periodically transitions between the closed operative orientation and the open operative orientation, and vice versa. During such vibration times, and when the valve is in the open operative orientation, flowable ingestible medicament 202 is delivered from reservoir 224 to the environment surrounding device 200. Because of the periodic opening and closing of valve 227, such delivery occurs in bursts, or quanta, until the medicament reservoir is empty and all the flowable medicament has been delivered, as illustrated in Figure 5.

The volume of medicament delivered in each such burst, is dependent on the pressure applied by the reservoir biasing mechanism, the recovery time of conduit 226, the diameter of the conduit, and the duration that valve 227 is in the open operative orientation. The duration that valve 227 is in the open operative orientation is based on the frequency of vibrations exerted by vibrating ingestible capsule 210, as well as on the mass of weight 228, the length and spring constant of biassing spring 229, and the rigidity of anchoring shelf 230. In some embodiments, the valve 227 functions as a gear reducer, such that the frequency at which the valve transitions between the open and closed configurations is lower than the frequency of vibration of the capsule 210.

Medicament compartment housing **221** of medicament delivery compartment **220** is attached to housing **212** of vibrating ingestible capsule **210**. In the illustrated embodiment, housing **212** of vibrating ingestible capsule **210** includes a first attachment mechanism in the form of a circumferential slot **250** and a circumferential protrusion **252** disposed adjacent a longitudinal end **254** of capsule housing **212**. Medicament compartment housing **221** includes a second, corresponding attachment mechanism in the form of a circumferential slot **260** and a circumferential protrusion **262** disposed adjacent an end **264** of medicament compartment housing **221**. Circumferential slot **260** corresponds in dimensions to circumferential protrusion **252** of capsule **210**, and circumferential protrusion **262** corresponds in dimensions to circumferential slot **250** of capsule **210**.

In the illustrated embodiment, medicament compartment housing **220** is fixedly attached to vibrating ingestible capsule **210** by snap fit engagement of slot **260** with protrusion **252** and snap fit engagement of protrusion **262** with slot **250**. However, any type of attachment between medicament compartment housing **221** and vibrating ingestible capsule **210** is considered within the scope of the present invention, including threaded engagement, engagement by soldering, engagement by adhesive, and the like.

Reference is now made to Figure 6, which is a schematic diagram of a device **300** for delivering a flowable ingestible medicament **302** into the gastrointestinal tract of a user according to yet another embodiment of the present invention

As seen, device **300**, which is arranged along a longitudinal axis, includes a vibrating ingestible capsule **310** including a housing **312**, formed of a first housing portion and a second housing portion which define a single hollow, and a vibrating agitation mechanism **314**, substantially as described hereinabove with respect to Figure 1. It will be appreciated that capsule **310** also includes a control element, and a power source, as described hereinabove with respect to Figure 1, even though these components are not explicitly shown in Figure 6.

Vibrating ingestible capsule **310** also functions as a medicament delivery compartment, such that a portal **323** is formed in the second housing portion of housing **312**. A medicament reservoir **324** is disposed within a hollow of capsule **310**, and is biased toward a shelf **320** extending radially inwardly from housing **312** by a reservoir biasing mechanism. The reservoir biasing mechanism includes a spring **325a** anchored at one end thereof to a longitudinal end of housing **312** and terminating, at an opposing end, in a biasing plate **325b** which engages an exterior surface of medicament reservoir **324** and applies pressure thereto. The medicament reservoir **324** is flexible and collapsible, and may

be formed of any suitable material such as silicone rubber, natural rubber, polyethylene, and PVC.

A conduit **326**, which may be a flexible and/or resilient conduit, extends from medicament reservoir **324** to portal **323**, and terminates with portal **323**, such that fluid can  
5 flow from medicament reservoir **324**, via conduit **326** and portal **323**, out of the device **300** and into an environment surrounding the device. In some embodiments, the end of conduit **326** disposed within portal **323** also seals the portal, so as to prevent material from the environment entering device **300**. In other embodiments, the end of conduit **326** may be surrounded by a seal sealing the portal.

10 Vibrating agitation mechanism **314** is attached to a biasing spring **329**, which is anchored to housing **312**. Vibrating agitation mechanism **312** and compression spring **329** form a valve, which functions in the manner described above with respect to valve **227** of Figures 2 to 5, which functions as a valve biasing mechanism. The spring **229** is anchored, at an end distal to weight **228**, to a rigid anchoring shelf **230** extending from medicament  
15 compartment housing **221** or from housing **212** of vibrating ingestible capsule **210**.

As such, in a closed operative orientation of the valve, biasing spring **329** biases vibrating agitation mechanism **314** against conduit **326**, thus pinching the conduit closed. In this closed operative orientation, no fluid can flow through conduit **326**, and pressure applied by the reservoir biasing mechanism to medicament reservoir **324** is at an  
20 equilibrium with forces resisting such pressure by the content of the medicament reservoir and conduit.

However, when vibrating agitation mechanism **314** is in the vibrating mode of operation, biasing spring **329** periodically contracts and extends, resulting in vibration agitation mechanism **314** being periodically withdrawn, or moved away, from conduit **326**,  
25 thus transitioning the valve to an open operative orientation, enabling conduit **326** to recover its nominal diameter and allowing fluid to flow through conduit **326**. When the valve is in the open operative orientation, pressure applied by the reservoir biasing mechanism to medicament reservoir **324** causes medicament **302** to flow from reservoir **324**, via conduit **326** and portal **323**, into the environment surrounding device **300**.

30 The delivery of the flowable medicament into the environment is as described hereinabove with respect to Figures 2 to 5.

Reference is now additionally made to Figure 7, which is a schematic flowchart of a method for delivering a flowable ingestible medicament into the gastrointestinal tract of user according to the present invention. The method may be based on the use of a device

including a vibrating ingestible capsule and a flowable ingestible medicament, as described hereinabove with reference to Figures 1 to 6.

As seen at step **400**, a device, such as device **100**, **200**, or **300** described hereinabove, including a vibrating ingestible capsule and a medicament delivery compartment, is provided to a user.

In some embodiments, at step **402**, the vibrating ingestible capsule and the medicament delivery compartment are attached to each other. In some embodiments, step **402** may take place in a factory, prior to providing the device to the user at step **400**. In other embodiments, the device may be provided to the user as two separate pieces, namely the ingestible vibrating capsule and the medicament delivery compartment, and the user carries out step **402** following receipt of the device at step **400**. In some embodiments, in which the device is constructed as a unitary structure, for example as illustrated in Figure 6, step **402** may be obviated.

In some embodiments, the attaching at step **402** includes fixedly attaching the medicament delivery compartment to the vibrating ingestible capsule.

In some embodiments, the attaching at step **402** includes removably attaching the medicament delivery compartment to the vibrating ingestible capsule.

In some embodiments, the attaching at step **402** includes attaching the medicament delivery compartment to the vibrating ingestible capsule by one or more of snap fit engagement, threaded engagement, adhering, soldering, or any other suitable mechanism of attachment.

In some embodiments, the attaching at step **402** includes mutually attaching a first attachment mechanism on the vibrating ingestible capsule with a corresponding attachment mechanism on the medicament delivery compartment, for example as described with respect to figures 2 to 5.

In some embodiments, the device is provided to the user having the flowable ingestible medicament disposed within the medicament reservoir and within the medicament delivery compartment.

In other embodiments, at step **404**, the flowable ingestible medicament is inserted into medicament delivery compartment. Step **404** may include filling of the medicament reservoir with the flowable ingestible medicament and/or inserting the medicament reservoir into the medicament delivery compartment or into the device.

In some embodiments, step **404** takes place prior to attaching the ingestible vibrating capsule with the medicament delivery compartment, either in a factory or by the user. The

flowable ingestible medicament inserted at step **404** may be any suitable type of flowable ingestible medicament, as described in detail hereinabove.

Regardless of when the medicament reservoir is inserted into the device, the medicament reservoir is placed under pressure within the device, as explained hereinabove.

5           At step **406**, the device, including the vibrating ingestible capsule, the medicament delivery compartment, and the flowable ingestible medicament, is ingested by the user, and begins to travel through the gastrointestinal tract of the user.

          At step **408**, which occurs following the user ingesting the device at step **406**, the vibrating ingestible capsule is controlled such that the vibration mode of operation (e.g.,  
10       when the vibration mode is initiated, a duration of the vibration mode, etc.) at least partially transpire within an area of the gastrointestinal tract at which the flowable ingestible medicament should be delivered, or within an absorption time period of the flowable ingestible medicament within the gastrointestinal tract of the user.

          The absorption time period may be an estimated absorption time period, as defined  
15       herein, and/or an actual absorption time period as defined herein.

          In some embodiment, step **408** may include controlling a timing of the vibration mode of operation such that the vibration mode at least partially transpires when the capsule is in a region of the gastrointestinal tract in which the flowable ingestible medicament is typically absorbed into the bloodstream. The region of the gastrointestinal tract may include  
20       one or more of the stomach of the user, the duodenum of the user, the small intestine of the user, the large intestine of the user, or the colon of the user.

          For example, when the flowable ingestible medicament is levadopa, which is typically absorbed into the bloodstream through the stomach walls and/or the small intestine walls, the vibration mode at least partially transpires within a time period in which the  
25       device traverses, or is expected to traverse, the stomach and small intestine.

          In some embodiments, step **408** includes setting at least one vibration parameter of the vibrating ingestible capsule of the device so as to promote delivery of flowable ingestible medicament into the gastrointestinal tract of the user or absorption of the ingestible medicament into the bloodstream of the user. In some such embodiments, the at  
30       least one vibration parameter set at step **408** includes at least one of a vibration frequency, a cumulative vibration duration, a number of vibration cycles per time unit, a duration of a vibration duration within a vibration cycle, a duration of a repose duration within a vibration cycle, a total duration of a single vibration cycle, and a net force exerted by said housing on said environment.

In some embodiments, the controlling at step **408** includes controlling the vibration agitation mechanism such that the vibrating mode of operation includes a plurality of cycles, each of the cycles including a vibration duration followed by a repose duration, wherein the housing exerts the vibrations during the vibration duration.

5 In some embodiments, the repose duration is greater than the vibration duration.

In some embodiments, the vibration duration is in the range of 0.1 second to 10 seconds, 1 second to 10 seconds, 1 second to 9 seconds, 2 seconds to 9 seconds, 3 seconds to 9 seconds, 3 seconds to 8 seconds, 3 seconds to 7 seconds, 3 seconds to 6 seconds, 4 seconds to 6 seconds, or 5 seconds to 6 seconds.

10 In some embodiments, the repose duration is in the range of 1 second to 180 seconds, 3 seconds to 180 seconds, 5 seconds to 180 seconds, 5 seconds to 150 seconds, 5 seconds to 120 seconds, 8 seconds to 100 seconds, 8 seconds to 30 seconds, 10 seconds to 80 seconds, 10 seconds to 70 seconds, 10 seconds to 60 seconds, 10 seconds to 50 seconds, 10 seconds to 40 seconds, 10 seconds to 30 seconds, 10 seconds to 20 seconds, or 15  
15 seconds to 20 seconds.

In some embodiments, a duration of each of the plurality of cycles is in the range of 1.1 seconds to 200 seconds, 5 seconds to 200 seconds, 10 seconds to 200 seconds, 10 seconds to 150 seconds, 10 seconds to 100 seconds, 10 seconds to 80 seconds, 10 seconds to 50 seconds, 10 seconds to 40 seconds, 10 seconds to 30 seconds, 15 seconds to 50 seconds,  
20 15 seconds to 40 seconds, 15 seconds to 30 seconds, or 15 seconds to 25 seconds.

In some embodiments, the controlling at step **408** includes controlling the vibrating agitation mechanism such that a cumulative duration of the vibrating mode of operation is in the range of 1 hour to 12 hours, 2 hours to 10 hours, 2 hours to 8 hours, 2 hours to 6 hours, 2 hours to 4 hours, or 2 hours to 3 hours.

25 In some embodiments, the controlling at step **408** includes controlling the vibrating agitation mechanism to exert forces on the housing of the vibrating ingestible capsule, such that a net force exerted by the housing on the environment thereof is preferably in the range of 50 grams force (gf) to 600gf, 50gf to 550gf, 100gf to 550gf, 100gf to 500gf, 150gf to 500gf, 200gf to 500gf, or 200gf to 450gf.

30 In some embodiments, the controlling at step **408** includes controlling the vibrating agitation mechanism to exert the forces on the housing to attain a housing vibrational frequency within a range of 10Hz to 650Hz, 15Hz to 600Hz, 20Hz to 550Hz, 30Hz to 550Hz, 50Hz to 500Hz, 70Hz to 500Hz, 100Hz to 500Hz, 130Hz to 500Hz, or 150Hz to 500Hz.

In some embodiments, and as described in further detail herein, the method may include a further step **412** of transitioning the capsule (from an inoperative state) to an operative state.

5 The capsule may be pre-programmed with a vibration protocol. This protocol may include, by way of example, a particular or pre-determined activation time following ingestion, in which the capsule is transitioned from an inoperative state to an operative state. In such embodiments, the step **412** may be omitted from the method.

10 Alternatively or additionally, the capsule may receive an activation input in an active fashion (e.g., from an external controller via RF) or in a passive fashion (e.g., a signal from a sensor to the on-board controller), as described in detail hereinabove. It will be appreciated that step **412**, in which the vibrating ingestible capsule is transitioned from the inoperative state to the operative state, may be performed prior to ingestion of the device by the user in step **406**, or following such ingestion, for example in the case of external control via RF.

15 Substantially as described hereinabove, step **412** may be carried out, and the vibrating ingestible capsule may be activated, prior to the user ingesting the capsule at step **406**, for example by a signal from the control unit or by the user carrying out an activation motion. In other embodiments, the activation input, and the transitioning of the capsule from being inoperative to being operative, occurs at the time of ingestion or immediately thereafter, for example by sensors sensing a change in the environment of the capsule due to its ingestion, as described at length hereinabove. In yet other embodiments, the transitioning of the capsule at step **412** may include the capsule receiving an activation input which is provided remotely when the capsule is already in the body of the user, for example by remote communication from control module **140**.

25 In some embodiments, a control element of the vibrating ingestible capsule may optionally receive a desired vibration protocol for the user, at an optional step **414**. In some embodiments, the programming of the desired vibration protocol at step **414** occurs at the time of manufacturing of the vibrating ingestible capsule or of the device, for example by pre-programming the protocol into the control element. In other embodiments, providing the desired vibration protocol for the user at step **414** may be effected by a control unit, such as control unit **140** of Figure 1, as described in detail hereinabove with respect to Figure 1.

Some embodiments of the invention are provided hereinbelow:

1. A device for delivering a flowable ingestible medicament into the gastrointestinal tract of a user, the device including:

a housing including a first housing portion and a second housing portion, the second housing portion having a portal formed therein;

a vibrating agitation mechanism disposed within the housing and adapted such that, in a vibration mode of operation, the housing exerts vibrations on an environment  
5 surrounding the device;

a power supply disposed within the housing and adapted to power the vibrating agitation mechanism; and

a control element adapted to activate the vibrating agitation mechanism to be operative in the vibration mode of operation; the

10 a flexible and collapsible medicament reservoir dimensioned to contain the flowable ingestible medicament;

a reservoir biasing mechanism adapted to apply pressure to the flexible and collapsible medicament reservoir;

a conduit extending from the medicament reservoir to the portal, and sealing the  
15 portal; and

a valve including a weight and a valve biasing mechanism adapted, in a closed operative orientation, to bias the weight against the conduit so as to block flow through the conduit, and in an open operative orientation, to remove the weight from the conduit so as to allow fluid to flow through the conduit,

20 wherein the valve is functionally associated with at least one of the housing and the vibrating agitation mechanism, such that when the vibrating agitation mechanism is in the vibration mode of operation, at least some of the vibrations exerted by the vibrating agitation mechanism or by the housing are applied to the valve biasing mechanism and periodically transition the valve between the closed operative orientation and the open  
25 operative orientation.

2. The device of embodiment 1, wherein, when the vibrating agitation mechanism is in the vibration mode of operation and the valve is in the open operative orientation, pressure applied by the reservoir biasing mechanism to the reservoir causes the flowable ingestible medicament to flow from the reservoir, via the conduit and the portal, to an environment  
30 surrounding the device.

3. The device of embodiment 1 or embodiment 2, wherein at least one vibration parameter of the vibrating agitation mechanism is set so as to promote transitioning of the valve between the closed operative orientation and the open operative orientation.

4. The device of any one of embodiments 1 to 3, wherein at least one vibration parameter of the vibrating agitation mechanism is set so as to promote absorption of the ingestible medicament into the bloodstream of the user.
5. The device of any one of embodiments 1 to 4, wherein at least one valve parameter of the valve is set such that the valve functions as a gear reducer, opening and closing at a frequency smaller than a frequency of the vibrating agitation mechanism.
6. The device of embodiment 5, wherein the at least one valve parameter includes a mass of the weight, a length of the valve biasing mechanism, and a spring constant of the valve biasing mechanism.
7. The device of any one of embodiments 3 to 6, wherein the at least one vibration parameter includes at least one of a vibration frequency, a cumulative vibration duration, a number of vibration cycles per time unit, a duration of a vibration duration within a vibration cycle, a duration of a repose duration within a vibration cycle, a total duration of a single vibration cycle, and a net force exerted by the housing on the environment.
8. The device of any one of embodiments 1 to 7, wherein:  
the first housing portion is a sealed housing portion accommodating the vibrating agitation mechanism, the power supply, and the control element;  
the second housing portion accommodates the flexible and collapsible medicament reservoir, the reservoir biasing mechanism, the conduit, and the valve;  
the first housing portion and the second housing portion are separate elements, which are attached to each other to form the housing; and  
the valve is functionally associated with the first housing portion such that when the vibrating agitation mechanism is in the vibration mode of operation, at least some of the vibrations exerted by the first housing portion are applied to the valve biasing mechanism and periodically transition the valve between the closed operative orientation and the open operative orientation.
9. The device of embodiment 8, wherein the first housing portion includes an attachment mechanism and the second housing portion includes a corresponding attachment mechanism, for mutual attachment of the first and second housing portions.
10. The device of embodiment 8 or embodiment 9, wherein the second housing portion is fixedly attached to the first housing portion.

11. The device of any one of embodiments 8 to 10, wherein the second housing portion is attached to the first housing portion by snap fit engagement.
12. The device of any one of embodiments 8 to 10, wherein the second housing portion is attached to the first housing portion by threaded engagement.
- 5 13. The device of any one of embodiments 8 to 10, wherein the second housing portion is attached to the first housing portion by adhering.
14. The device of any one of embodiments 8 to 10, wherein the second housing portion is attached to the first housing portion by soldering.
15. The device of any one of embodiments 1 to 7, wherein the first and second housing  
10 portions form a single housing element including the portal and defining a single hollow, the single hollow accommodating the vibrating agitation mechanism, the power supply, the control element, the flexible and collapsible medicament reservoir, the reservoir biasing mechanism, and the flexible and resilient conduit.
16. The device of any one of embodiments 1 to 15, wherein a hollow of the second  
15 housing portion has a volume in the range of  $200\text{mm}^3$  to  $3000\text{mm}^3$ ,  $200\text{mm}^3$  to  $800\text{mm}^3$ ,  $100\text{mm}^3$  to  $600\text{mm}^3$ ,  $400\text{mm}^3$  to  $1000\text{mm}^3$ ,  $700\text{mm}^3$  to  $1500\text{mm}^3$ , or  $1400\text{mm}^3$  to  $3000\text{mm}^3$ .
17. The device of any one of embodiments 1 to 16, wherein the flexible and collapsible medicament reservoir has a maximal volume in the range of 0.5ml to 15ml.
- 20 18. The device of any one of embodiments 1 to 17, wherein the flexible and collapsible medicament reservoir has a Young's modulus smaller than 1 GPa.
19. The device of any one of embodiments 1 to 18, wherein the flexible and collapsible medicament reservoir is formed of a material selected from the group consisting of: silicone rubber, natural rubber, Polyethylene, and PVC
- 25 20. The device of any one of embodiments 1 to 19, wherein the reservoir biasing mechanism includes a reservoir spring terminating in a pressure applying surface, the pressure applying surface engaging an exterior surface of the medicament reservoir.
21. The device of embodiment 20, wherein the reservoir spring is anchored to the second housing portion.

22. The device of any one of embodiments 1 to 21, wherein the reservoir biasing mechanism has a spring constant in the range of 1 N/m to 200 N/m.
23. The device of any one of embodiments 1 to 22, wherein the conduit is integrally formed with the medicament reservoir.
- 5 24. The device of any one of embodiments 1 to 22, wherein the conduit is formed of a different material than the medicament reservoir.
25. The device of any one of embodiments 1 to 24, wherein a recovery time of the conduit is at most 0.1 seconds.
26. The device of any one of embodiments 1 to 25, wherein the vibrating agitation  
10 mechanism has a frequency  $f$ , and a recovery time of the conduit is at most equal to  $1/f$ .
27. The device of any one of embodiments 1 to 25, wherein the valve biasing mechanism has a frequency  $f_v$  of moving from the open operative orientation to the closed operative orientation and back to the open operative orientation, and a recovery time of the conduit is at most equal to  $1/f_v$ .
- 15 28. The device of any one of embodiments 1 to 27, wherein the conduit has at least one of:  
a diameter in the range of 0.01mm to 0.9mm; and  
a length in the range of 3mm to 25mm.
29. The device of any one of embodiments 1 to 28, wherein the conduit is at least one of,  
20 and optionally both of, flexible and resilient.
30. The device of any one of embodiments 1 to 29, wherein the valve biasing mechanism is anchored to the first housing portion.
31. The device of any one of embodiments 1 to 29, wherein the valve biasing mechanism is anchored to the second housing portion.
- 25 32. The device of any one of embodiments 1 to 31, wherein the valve biasing mechanism has a spring constant in the range of 0.1 N/m to 5 N/m.
33. The device of any one of embodiments 1 to 32 wherein the weight has a mass in the range of 0.1 grams to 2 grams.

34. The device of any one of embodiments 1 to 33, wherein the weight includes the vibrating agitation mechanism.

35. The device of any one of embodiments 1 to 34, wherein the vibrations exerted by the vibrating agitation mechanism are transferred, through an anchoring point of the valve  
5 biasing mechanism, to the valve biasing mechanism, thereby causing rocking of the valve biasing mechanism resulting in the periodic transitioning of the valve between the closed operative orientation and the open operative orientation.

36. The device of any one of embodiments 1 to 35, wherein the control element is adapted to control a timing or activation delay of the vibration mode of operation such that  
10 the vibration mode of operation at least partially transpires within a region of the gastrointestinal tract in which the flowable ingestible medicament is absorbable by the body of the user.

37. The device of any one of embodiments 1 to 36, wherein the control element is adapted to control a timing or activation delay of the vibrating mode of operation such that  
15 the vibration mode of operation at least partially transpires during at least one of an estimated absorption time period and an actual absorption time period of the flowable ingestible medicament released from the reservoir, via the conduit and the portal, into the gastrointestinal tract of the user.

38. The device of any one of embodiments 1 to 37, wherein the control element is  
20 adapted to activate the vibration agitation mechanism to be operative in the vibration mode of operation in response to receipt of an activation input.

39. The device of embodiment 38, further including at least one sensor adapted to provide the activation input to the control element.

40. The device of embodiment 39, wherein the at least one sensor is disposed within the  
25 first housing portion.

41. The device of embodiment 39 or embodiment 40, wherein the at least one sensor includes an illumination sensor, adapted to provide an input indicating transition of the device from an illuminated environment to a dark environment.

42. The device of any one of embodiments 39 to 41, wherein the at least one sensor  
30 includes a pressure sensor, adapted to provide an input indicating pressure applied to the device, which pressure is indicative of the device moving through a pharynx of the user.

43. The device of any one of embodiments 39 to 42, wherein the at least one sensor includes a temperature sensor, adapted to provide an input indicating transition of the device from an area with ambient temperature to an area with a human body temperature.
44. The device of any one of embodiments 39 to 43, wherein the at least one sensor  
5 includes an accelerometer, adapted to provide an input in response to a detected activation motion carried out with the device.
45. The device of any one of embodiments 39 to 44, wherein the at least one sensor includes a moisture sensor, adapted to provide an input indicating transition of the device from a dry environment to a humid environment.
- 10 46. The device of embodiment 38, functionally associated with a control unit remote from the device, and wherein the control element is adapted to receive the activation input from the control unit.
47. The device of any one of embodiments 38 to 46, wherein the control element is adapted to receive the activation input following ingesting of the device.
- 15 48. The device of any one of embodiments 38 to 46, wherein the control element is adapted to receive the activation input prior to ingesting of the device.
49. The device of any one of embodiments 38 to 48, wherein the control element is adapted to receive the activation input by receiving a vibration protocol to be used by the control element to control operation of the vibrating agitation mechanism.
- 20 50. The device of any one of embodiments 1 to 49, wherein the vibrating agitation mechanism includes at least a radial agitation mechanism adapted, in the vibration mode of operation, to exert radial forces on the housing, in a radial direction with respect to a or the longitudinal axis of the housing, thereby to cause the vibrations exerted by the housing.
51. The device of any one of embodiments 1 to 49, wherein the vibrating agitation  
25 mechanism includes at least an axial agitation mechanism adapted, in the vibration mode of operation, to exert axial forces on the housing, in an axial direction with respect to a or the longitudinal axis of the housing, thereby to cause the vibrations exerted by the housing.
52. The device of any one of embodiments 1 to 49, wherein the vibration agitation  
30 mechanism includes a radial agitation mechanism adapted, in the vibration mode of operation, to exert radial forces on the housing, in a radial direction with respect to a or the

longitudinal axis of the housing, and a separate axial agitation mechanism adapted, in the vibration mode of operation, to exert axial forces on the housing, in an axial direction with respect to a or the longitudinal axis of the housing.

53. The device of any one of embodiments 1 to 49, wherein the vibration agitation  
5 mechanism includes a single agitation mechanism adapted, in the vibration mode of operation, to exert radial forces on the housing in a radial direction with respect to a or the longitudinal axis of the housing, and to exert axial forces on the housing, in an axial direction with respect to the longitudinal axis of the housing.

54. The device of any one of embodiments 1 to 53, wherein the control element is  
10 adapted to control the vibrating agitation mechanism such that the vibrating mode of operation includes a plurality of cycles, each of the cycles including a vibration duration followed by a repose duration, wherein the housing exerts the vibrations during the vibration duration.

55. The device of embodiment 54, wherein the repose duration is greater than the  
15 vibration duration.

56. The device of embodiment 54 or embodiment 55, wherein the vibration duration is in the range of 0.1 second to 10 seconds, 1 second to 10 seconds, 1 second to 9 seconds, 2 seconds to 9 seconds, 3 seconds to 9 seconds, 3 seconds to 8 seconds, 3 seconds to 7 seconds, 3 seconds to 6 seconds, 4 seconds to 6 seconds, or 5 seconds to 6 seconds.

20 57. The device of any one of embodiments 54 to 56, wherein the repose duration is in the range of 1 second to 180 seconds, 3 seconds to 180 seconds, 5 seconds to 180 seconds, 5 seconds to 150 seconds, 5 seconds to 120 seconds, 8 seconds to 100 seconds, 8 seconds to 30 seconds, 10 seconds to 80 seconds, 10 seconds to 70 seconds, 10 seconds to 60 seconds, 10 seconds to 50 seconds, 10 seconds to 40 seconds, 10 seconds to 30 seconds, 10 seconds  
25 to 20 seconds, or 15 seconds to 20 seconds.

58. The device of any one of embodiments 54 to 57, wherein a duration of each of the plurality of cycles is in the range of 1.1 seconds to 200 seconds, 5 seconds to 200 seconds, 10 seconds to 200 seconds, 10 seconds to 150 seconds, 10 seconds to 100 seconds, 10 seconds to 80 seconds, 10 seconds to 50 seconds, 10 seconds to 40 seconds, 10 seconds to  
30 30 seconds, 15 seconds to 50 seconds, 15 seconds to 40 seconds, 15 seconds to 30 seconds, or 15 seconds to 25 seconds.

59. The device of any one of embodiments 1 to 58, wherein the control element is adapted to control the vibrating agitation mechanism such that a cumulative duration of the vibrating mode of operation is in the range of 1 hour to 12 hours, 2 hours to 10 hours, 2 hours to 8 hours, 2 hours to 6 hours, 2 hours to 4 hours, or 2 hours to 3 hours.
- 5 60. The device of any one of embodiments 1 to 59, wherein the vibrating agitation mechanism is configured to exert forces on the housing, such that a net force exerted by the housing on the environment thereof is preferably in the range of 50 grams force (gf) to 600gf, 50gf to 550gf, 100gf to 550gf, 100gf to 500gf, 150gf to 500gf, 200gf to 500gf, or 200gf to 450gf.
- 10 61. The device of any one of embodiments 1 to 60, wherein the vibrating agitation mechanism is configured to exert the forces on the housing to attain a housing vibrational frequency within a range of 10Hz to 650Hz, 15Hz to 600Hz, 20Hz to 550Hz, 30Hz to 550Hz, 50Hz to 500Hz, 70Hz to 500Hz, 100Hz to 500Hz, 130Hz to 500Hz, or 150Hz to 500Hz.
- 15 62. The device of any one of embodiments 1 to 61, further including the flowable ingestible medicament disposed within the medicament reservoir.
63. The device of any one of embodiments 1 to 62, wherein the flowable ingestible medicament has a viscosity in the range of 100 Pa·s to 1000 Pa·s.
64. The device of embodiment 62 or embodiment 63, wherein the flowable ingestible  
20 medicament is absorbable in the stomach of the user.
65. The device of any one of embodiments 62 to 64, wherein the flowable ingestible medicament is absorbable in the small intestine of the user.
66. The device of any one of embodiments 62 to 65, wherein the flowable ingestible medicament is suitable for treatment of one or more symptom or disease, selected from the  
25 group consisting of: Parkinsonism; Parkinson's Disease; progressive supranuclear palsy; corticobasal degeneration; multiple system atrophy; Parkinson-plus syndromes; any neurodegenerative disease in which the subject exhibits at least one, at least two, or at least three of the classical features of Parkinson's disease: tremor, postural instability, and akinesia or bradykinesia; any neurodegenerative disease in which the subject positively  
30 responds to a dopaminergic treatment; any neurodegenerative disease in which the particular subject positively responds to an anticholinergic treatment; Constipation; Crohn's disease;

Gastroparesis; irritable bowel syndrome (IBS); diarrhea or loose bowel movements; colitis; Hirschsprung's disease; Dyspepsia; and dysphagia.

67. The device of any one of embodiments 62 to 66, wherein the flowable ingestible medicament includes or includes an ingestible medicament selected from the group consisting of: Levodopa; at least one dopaminergic agent; at least one catecholamine precursor; a dopamine precursor; at least one dopamine precursor agent; (L)-3,4-dihydroxyphenylalanine; N-methyl-N-(2-propynyl)-2-methyl-1-phenylethyl-2-amine; tyrosine hydroxylase; apomorphine; at least one anticholinergic agent; at least one agent selected to antagonize at least one cholinergic receptor; benzhexol; orphenadrine; at least one selective allosteric potentiator of metabotropic glutamate receptor 4 (mGluR4); N-phenyl-7-(hydroxylimino)cyclopropa[b]chromen-1a-carboxamide; at least one osmotic agent; magnesium citrate; magnesium hydroxide; polyethylene glycol; sodium phosphate; MiraLAX®; at least one contraction stimulating agent; bisacodyl; senna; Correctol; Ducodyl; Dulcolax; Senexon; Senokot; at least one stool softening agent; docusate sodium; Colace; Linaclotide; Lactulose; Lubiprostone; Plecanatide; Prucaltride; Loperamide; and bismuth subsalicylate.

68. A method of delivering an ingestible medicament into a gastrointestinal tract of a user, the method including:

providing to the user the device according to any one of embodiments 62 to 67, for ingestion by the user;

following the user ingesting the device, the vibrating agitation mechanism such that the vibration mode of operation at least partially transpires within a region of the gastrointestinal tract in which the flowable ingestible medicament is absorbable by the body of the user, thereby to cause the periodic transitioning of the valve between the closed operative orientation and the open operative orientation, and delivery of the flowable ingestible medicament from the reservoir, via the conduit and the portal, into the environment surrounding the device.

69. The method of embodiment 68, wherein the controlling the vibrating agitation mechanism further includes controlling the vibrating agitation mechanism such that the vibration mode of operation at least partially transpires within at least one of an estimated absorption time period and an actual absorption time period of the ingestible medicament within the gastrointestinal tract of the user.

70. A medicament delivery compartment, adapted to be attached to a vibrating ingestible capsule having a first housing portion and adapted to operate in a vibrating mode of operation, for delivery of a flowable ingestible medicament into the gastrointestinal tract of a user, the medicament delivery compartment including:

- 5 a second housing portion adapted to be attached to the first housing portion of the vibrating ingestible capsule, and having a portal formed therein;
  - a flexible and collapsible medicament reservoir dimensioned to contain the flowable ingestible medicament;
  - a reservoir biasing mechanism adapted to apply pressure to the flexible and
  - 10 collapsible medicament reservoir;
  - a conduit extending from the medicament reservoir to the portal, and sealing the portal; and
  - a valve including a weight and a valve biasing mechanism adapted, in a closed operative orientation, to bias the weight against the flexible and resilient conduit so as to
  - 15 block flow through the conduit, and in an open operative orientation to remove the weight from the flexible and resilient conduit so as to allow fluid to flow through the conduit.

71. The medicament delivery compartment of embodiment 70, wherein the valve is configured to be in the open operative orientation and to enable flow through the conduit when the vibrating ingestible capsule is in the vibration mode of operation.

- 20 72. The medicament delivery compartment of embodiment 71, wherein at least one valve parameter of the valve is set such that the valve functions as a gear reducer, opening and closing at a frequency smaller than a frequency of vibration of the vibrating ingestible capsule.

- 73. The medicament delivery compartment of embodiment 72, wherein the at least one
- 25 valve parameter includes a mass of the weight, a length of the valve biasing mechanism, and a spring constant of the valve biasing mechanism.

- 74. The medicament delivery compartment of any one of embodiments 70 to 73, wherein the second housing portion includes an attachment mechanism for mutual
- attachment to a corresponding attachment mechanism of the first housing portion of the
- 30 vibrating ingestible capsule.

75. The medicament delivery compartment of any one of embodiments 70 to 74, wherein the second housing portion is adapted to be fixedly attached to the first housing

portion.

76. The medicament delivery compartment of any one of embodiments 70 to 75, wherein the second housing portion is adapted to be attached to the first housing portion by snap fit engagement.

5 77. The medicament delivery compartment of any one of embodiments 70 to 75, wherein the second housing portion is adapted to be attached to the first housing portion by threaded engagement.

78. The medicament delivery compartment of any one of embodiments 70 to 75, wherein the second housing portion is adapted to be attached to the first housing portion by  
10 adhering.

79. The medicament delivery compartment of any one of embodiments 70 to 75, wherein the second housing portion is adapted to be attached to the first housing portion by soldering.

80. The medicament delivery compartment of any one of embodiments 70 to 79,  
15 wherein a hollow formed in the first housing portion has a volume in the range of  $200\text{mm}^3$  to  $3000\text{mm}^3$ ,  $200\text{mm}^3$  to  $800\text{mm}^3$ ,  $100\text{mm}^3$  to  $600\text{mm}^3$ ,  $400\text{mm}^3$  to  $1000\text{mm}^3$ ,  $700\text{mm}^3$  to  $1500\text{mm}^3$ , or  $1400\text{mm}^3$  to  $3000\text{mm}^3$ .

81. The medicament delivery compartment of any one of embodiments 70 to 80, wherein the flexible and collapsible medicament reservoir has a maximal volume in the  
20 range of  $1\text{mm}^3$  to  $600\text{mm}^3$ ,  $1\text{mm}^3$  to  $10\text{mm}^3$ ,  $5\text{mm}^3$  to  $20\text{mm}^3$ ,  $15\text{mm}^3$  to  $50\text{mm}^3$ ,  $30\text{mm}^3$  to  $200\text{mm}^3$ ,  $100\text{mm}^3$  to  $400\text{mm}^3$ , or  $300\text{mm}^3$  to  $600\text{mm}^3$ .

82. The medicament delivery compartment of any one of embodiments 70 to 81, wherein the flexible and collapsible medicament reservoir has a Young's modulus smaller than 1 GPa.

25 83. The medicament delivery compartment of any one of embodiments 70 to 82, wherein the flexible and collapsible medicament reservoir is formed of a material selected from the group consisting of: silicone rubber, natural rubber, Polyethylene, and PVC.

84. The medicament delivery compartment of any one of embodiments 70 to 83, wherein the reservoir biasing mechanism includes a reservoir spring terminating in a

pressure applying surface, the pressure applying surface engaging an exterior surface of the medicament reservoir.

85. The medicament delivery compartment of embodiment 84, wherein the reservoir spring is anchored to the second housing portion.

5 86. The medicament delivery compartment of any one of embodiments 70 to 85, wherein the reservoir biasing mechanism has a spring constant in the range of 1 N/m to 200 N/m.

87. The medicament delivery compartment of any one of embodiments 70 to 86, wherein the conduit is integrally formed with the medicament reservoir.

10 88. The medicament delivery compartment of any one of embodiments 70 to 86, wherein the conduit is formed of a different material than the medicament reservoir.

89. The medicament delivery compartment of any one of embodiments 70 to 88, wherein a recovery time of the conduit is at most 0.1 seconds.

90. The medicament delivery compartment of any one of embodiments 70 to 89,  
15 wherein the vibrating ingestible capsule is adapted to vibrate at a frequency  $f$ , and a recovery time of the conduit is at most equal to  $1/f$ .

91. The medicament delivery compartment of any one of embodiments 70 to 89, wherein the valve biasing mechanism has a frequency  $f_v$  of moving between the closed operative orientation and the open operative orientation, and a recovery time of the conduit  
20 is at most equal to  $1/f_v$ .

92. The medicament delivery compartment of any one of embodiments 70 to 91, wherein the conduit has at least one, and optionally both, of:

a diameter in the range of 0.01mm to 0.9mm; and

a length in the range of 3mm to 25mm.

25 93. The medicament delivery compartment of any one of embodiments 70 to 92, wherein the conduit is at least one of, and optionally both of, flexible and resilient.

94. The medicament delivery compartment of any one of embodiments 70 to 93, wherein the valve biasing mechanism is adapted to be anchored to the vibrating ingestible capsule.

95. The medicament delivery compartment of any one of embodiments 70 to 93, wherein the valve biasing mechanism is anchored to the second housing portion.
96. The medicament delivery compartment of any one of embodiments 70 to 95, wherein the valve biasing mechanism has a spring constant in the range of 0.1 N/m to 5  
5 N/m.
97. The medicament delivery compartment of any one of embodiments 70 to 96, wherein the weight has a mass in the range of 0.1 grams to 2 grams.
98. The medicament delivery compartment of any one of embodiments 70 to 97, further including the flowable ingestible medicament disposed within the medicament reservoir.
- 10 99. The medicament delivery compartment of any one of embodiments 70 to 98, wherein the flowable ingestible medicament has a viscosity in the range of 100 Pa·s to 1000 Pa·s.
100. The medicament delivery compartment of embodiment 98 or embodiment 99, wherein the flowable ingestible medicament is absorbable in the stomach of the user.
- 15 101. The medicament delivery compartment of any one of embodiments 98 to 100, wherein the flowable ingestible medicament is absorbable in the small intestine of the user.
102. The medicament delivery compartment of any one of embodiments 98 to 101, wherein the flowable ingestible medicament is suitable for treatment of one or more symptom or disease, selected from the group listed in embodiment 66.
- 20 103. The medicament delivery compartment of any one of embodiments 98 to 102, wherein the flowable ingestible medicament includes or includes an ingestible medicament selected from the group listed in embodiment 67.
104. A vibrating ingestible capsule adapted to be attached to a medicament delivery compartment for delivering a flowable ingestible medicament disposed within the  
25 medicament delivery compartment into the gastrointestinal tract of a user, the vibrating ingestible capsule including:
- a housing including an attachment mechanism adapted for mutual attachment to a corresponding attachment mechanism of the medicament delivery compartment;

a vibrating agitation mechanism disposed within the housing and adapted such that, in a vibration mode of operation, the housing exerts vibrations on an environment surrounding the vibrating ingestible capsule;

5 a power supply disposed within the housing and adapted to power the vibrating agitation mechanism; and

a control element adapted to activate the vibrating agitation mechanism to be operative in the vibration mode of operation,

10 wherein at least one vibration parameter of the vibrating agitation mechanism is set so as to promote at least one of delivery of the flowable ingestible medicament from the medicament delivery compartment into an environment surrounding the medicament delivery compartment and absorption of the flowable ingestible medicament into the bloodstream of the user.

105. The vibrating ingestible capsule of embodiment 104, wherein the at least one vibration parameter includes at least one of a vibration frequency, a cumulative vibration  
15 duration, a number of vibration cycles per time unit, a duration of a vibration duration within a vibration cycle, a duration of a repose duration within a vibration cycle, a total duration of a single vibration cycle, and a net force exerted by the housing on the environment.

106. The vibrating ingestible capsule of embodiment 104 or embodiment 105, wherein  
20 the control element is adapted to control a timing or activation delay of the vibration mode of operation such that the vibration mode of operation at least partially transpires within a region of the gastrointestinal tract in which the flowable ingestible medicament is absorbable by the body of the user.

107. The vibrating ingestible capsule of any one of embodiments 105 to 106, wherein the  
25 control element is adapted to control a timing or activation delay of the vibration mode of operation such that the vibration mode of operation at least partially transpires within at least one of an estimated absorption time period and an actual absorption time period of the flowable ingestible medicament within the gastrointestinal tract of the user.

108. The vibrating ingestible capsule of any one of embodiments 104 to 107, wherein the  
30 control element is adapted to activate the vibration agitation mechanism to be operative in the vibration mode of operation in response to receipt of an activation input.

109. The vibrating ingestible capsule of embodiment 108, further including at least one sensor adapted to provide the activation input to the control element.

110. The vibrating ingestible capsule of embodiment 109, wherein the at least one sensor includes an illumination sensor, adapted to provide an input indicating transition of the vibrating ingestible capsule from an illuminated environment to a dark environment.

111. The vibrating ingestible capsule of any one of embodiments 109 to 110, wherein the at least one sensor includes a pressure sensor, adapted to provide an input indicating pressure applied to the vibrating ingestible capsule, which pressure is indicative of the vibrating ingestible capsule moving through a pharynx of the user.

112. The vibrating ingestible capsule of any one of embodiments 109 to 111, wherein the at least one sensor includes a temperature sensor, adapted to provide an input indicating transition of the vibrating ingestible capsule from an area with ambient temperature to an area with a human body temperature.

113. The vibrating ingestible capsule of any one of embodiments 109 to 112, wherein the at least one sensor includes an accelerometer, adapted to provide an input in response to a detected activation motion carried out with the vibrating ingestible capsule.

114. The vibrating ingestible capsule of any one of embodiments 109 to 113, wherein the at least one sensor includes a moisture sensor, adapted to provide an input indicating transition of the vibrating ingestible capsule from a dry environment to a humid environment.

115. The vibrating ingestible capsule of any one of embodiments 108 to 114, functionally associated with a control unit remote from the vibrating ingestible capsule, and wherein the control element is adapted to receive the activation input from the control unit.

116. The vibrating ingestible capsule of any one of embodiments 108 to 115, wherein the control element is adapted to receive the activation input following ingesting of the vibrating ingestible capsule.

117. The vibrating ingestible capsule of any one of embodiments 108 to 115, wherein the control element is adapted to receive the activation input prior to ingesting of the vibrating ingestible capsule.

118. The vibrating ingestible capsule of any one of embodiments 108 to 117, wherein the

control element is adapted to receive the activation input by receiving a vibration protocol to be used by the control element to control operation of the vibrating agitation mechanism.

119. The vibrating ingestible capsule of any one of embodiments 104 to 118, wherein the vibrating agitation mechanism includes at least a radial agitation mechanism adapted, in the vibration mode of operation, to exert radial forces on the housing, in a radial direction with respect to a or the longitudinal axis of the housing, thereby to cause the vibrations exerted by the housing.

120. The vibrating ingestible capsule of any one of embodiments 104 to 118, wherein the vibrating agitation mechanism includes at least an axial agitation mechanism adapted, in the vibration mode of operation, to exert axial forces on the housing, in an axial direction with respect to a or the longitudinal axis of the housing, thereby to cause the vibrations exerted by the housing.

121. The vibrating ingestible capsule of any one of embodiments 104 to 118, wherein the vibration agitation mechanism includes a radial agitation mechanism adapted, in the vibration mode of operation, to exert radial forces on the housing, in a radial direction with respect to a or the longitudinal axis of the housing, and a separate axial agitation mechanism adapted, in the vibration mode of operation, to exert axial forces on the housing, in an axial direction with respect to a or the longitudinal axis of the housing.

122. The vibrating ingestible capsule of any one of embodiments 104 to 118, wherein the vibration agitation mechanism includes a single agitation mechanism adapted, in the vibration mode of operation, to exert radial forces on the housing in a radial direction with respect to a or the longitudinal axis of the housing, and to exert axial forces on the housing, in an axial direction with respect to the longitudinal axis of the housing.

123. The vibrating ingestible capsule of any one of embodiments 104 to 122, wherein the control element is adapted to control the vibrating agitation mechanism such that the vibrating mode of operation includes a plurality of cycles, each of the cycles including a vibration duration followed by a repose duration, wherein the housing exerts the vibrations during the vibration duration.

124. The vibrating ingestible capsule of embodiment 123, wherein the repose duration is greater than the vibration duration.

125. The vibrating ingestible capsule of embodiment 123 or embodiment 124, wherein the vibration duration is in the range of 0.1 second to 10 seconds, 1 second to 10 seconds, 1 second to 9 seconds, 2 seconds to 9 seconds, 3 seconds to 9 seconds, 3 seconds to 8 seconds, 3 seconds to 7 seconds, 3 seconds to 6 seconds, 4 seconds to 6 seconds, or 5 seconds to 6 seconds.

126. The vibrating ingestible capsule of any one of embodiments 123 to 125, wherein the repose duration is in the range of 1 second to 180 seconds, 3 seconds to 180 seconds, 5 seconds to 180 seconds, 5 seconds to 150 seconds, 5 seconds to 120 seconds, 8 seconds to 100 seconds, 8 seconds to 30 seconds, 10 seconds to 80 seconds, 10 seconds to 70 seconds, 10 seconds to 60 seconds, 10 seconds to 50 seconds, 10 seconds to 40 seconds, 10 seconds to 30 seconds, 10 seconds to 20 seconds, or 15 seconds to 20 seconds.

127. The vibrating ingestible capsule of any one of embodiments 123 to 126, wherein a duration of each of the plurality of cycles is in the range of 1.1 seconds to 200 seconds, 5 seconds to 200 seconds, 10 seconds to 200 seconds, 10 seconds to 150 seconds, 10 seconds to 100 seconds, 10 seconds to 80 seconds, 10 seconds to 50 seconds, 10 seconds to 40 seconds, 10 seconds to 30 seconds, 15 seconds to 50 seconds, 15 seconds to 40 seconds, 15 seconds to 30 seconds, or 15 seconds to 25 seconds.

128. The vibrating ingestible capsule of any one of embodiments 104 to 127, wherein the control element is adapted to control the vibrating agitation mechanism such that a cumulative duration of the vibrating mode of operation is in the range of 1 hour to 12 hours, 2 hours to 10 hours, 2 hours to 8 hours, 2 hours to 6 hours, 2 hours to 4 hours, or 2 hours to 3 hours.

129. The vibrating ingestible capsule of any one of embodiments 104 to 128, wherein the vibrating agitation mechanism is configured to exert forces on the housing of the vibrating ingestible capsule, such that a net force exerted by the housing on the environment thereof is in the range of 50 grams force (gf) to 600gf, 50gf to 550gf, 100gf to 550gf, 100gf to 500gf, 150gf to 500gf, 200gf to 500gf, or 200gf to 450gf.

130. The vibrating ingestible capsule of any one of embodiments 104 to 129, wherein the vibrating agitation mechanism is configured to exert the forces on the housing to attain a housing vibrational frequency within a range of 10Hz to 650Hz, 15Hz to 600Hz, 20Hz to 550Hz, 30Hz to 550Hz, 50Hz to 500Hz, 70Hz to 500Hz, 100Hz to 500Hz, 130Hz to 500Hz, or 150Hz to 500Hz.

131. The vibrating ingestible capsule of any one of embodiments 104 to 130, wherein the housing is adapted to be fixedly attached to a second housing of the medicament delivery compartment.

132. The vibrating ingestible capsule of any one of embodiments 104 to 131, wherein the housing is adapted to be attached to the medicament delivery compartment by snap fit engagement.

133. The vibrating ingestible capsule of any one of embodiments 104 to 131, wherein the housing is adapted to be attached to the medicament delivery compartment by threaded engagement.

134. The vibrating ingestible capsule of any one of embodiments 104 to 131, wherein the housing is adapted to be attached to the medicament delivery compartment by adhering.

135. The vibrating ingestible capsule of any one of embodiments 104 to 131, wherein the housing is adapted to be attached to the medicament delivery compartment by soldering.

136. A method for delivering a flowable ingestible medicament into the gastrointestinal tract of a user, the method including:

providing an ingestible device including:

a housing including a first housing portion and a second housing portion, the second housing portion having a portal formed therein;

a vibrating agitation mechanism disposed within the housing and adapted such that, in a vibration mode of operation, the housing exerts vibrations on an environment surrounding the ingestible device;

a power supply disposed within the housing and adapted to power the vibrating agitation mechanism;

a control element adapted to activate the vibrating agitation mechanism to be operative in the vibration mode of operation; the

a flexible and collapsible medicament reservoir having the flowable ingestible medicament disposed therein;

a reservoir biasing mechanism applying pressure to the flexible and collapsible medicament reservoir;

a conduit extending from the medicament reservoir to the portal, and sealing the portal; and

a valve including a weight and valve biasing mechanism adapted, in a closed operative orientation, to bias the weight against the conduit so as to block flow through the conduit, and in an open operative orientation to remove the weight from the conduit so as to allow fluid to flow through the conduit, the valve being  
5 functionally associated with at least one of the housing and the vibrating agitation mechanism,

ingesting the ingestible device by the user; and  
following the user ingesting the device, controlling the vibrating agitation mechanism such that in the vibration mode of operation, at least some of the vibrations  
10 exerted by the vibrating agitation mechanism or by the housing are applied to the valve biasing mechanism and periodically transition the valve between the closed operative orientation and the open operative orientation,

wherein, during the controlling, when the vibrating agitation mechanism is in the vibration mode of operation and the valve is in the open operative orientation, pressure  
15 applied by the reservoir biasing mechanism to the reservoir causes the flowable ingestible medicament to flow from the reservoir, via the conduit and the portal, to an environment surrounding the assembly.

137. The method of embodiment 136, wherein the providing includes providing the ingestible device wherein the first housing portion and the second housing portion include a  
20 single housing including the portal and defining a single hollow, the single hollow accommodating the vibrating agitation mechanism, the power supply, the control element, the flexible and collapsible medicament reservoir, the reservoir biasing mechanism, and the conduit.

138. The method of embodiment 137, wherein the weight includes the vibrating agitation  
25 mechanism.

139. A method for delivering a flowable ingestible medicament into the gastrointestinal tract of a user, the method including:

providing a vibrating ingestible capsule including:

a housing;

30 a vibrating agitation mechanism disposed within the housing and adapted such that, in a vibration mode of operation, the housing exerts vibrations on an environment surrounding the vibrating ingestible capsule;

a power supply disposed within the housing and adapted to power the vibrating agitation mechanism; and

a control element adapted to activate the vibrating agitation mechanism to be operative in the vibration mode of operation; and

5 forming an ingestible device by attaching to the vibrating ingestible capsule a medicament delivery compartment, the medicament delivery compartment including:

a second housing portion having a portal formed therein;

a flexible and collapsible medicament reservoir having the flowable ingestible medicament disposed therein;

10 a reservoir biasing mechanism applying pressure to the flexible and collapsible medicament reservoir;

a conduit extending from the medicament reservoir to the portal, and sealing the portal; and

15 a valve including a weight and valve biasing mechanism adapted, in a closed operative orientation, to bias the weight against the conduit so as to block flow through the conduit, and in an open operative orientation to remove the weight from the conduit so as to allow fluid to flow through the conduit, the valve being functionally associated with at least one of the housing and the vibrating agitation mechanism;

20 ingesting the ingestible device by the user; and

following the user ingesting the device, controlling the vibrating agitation mechanism such that in the vibration mode of operation, at least some of the vibrations exerted by the vibrating agitation mechanism or by the housing are applied to the valve biasing mechanism and periodically transition the valve between the closed operative  
25 orientation and the open operative orientation,

wherein, during the controlling, when the vibrating agitation mechanism is in the vibration mode of operation and the valve is in the open operative orientation, pressure applied by the reservoir biasing mechanism to the reservoir causes the flowable ingestible medicament to flow from the reservoir, via the conduit and the portal, to an environment  
30 surrounding the device.

140. The method of embodiment 139, further including, prior to the attaching, filling the medicament reservoir with the flowable ingestible medicament.

141. The method of any one of embodiments 136 to 140, wherein the controlling the vibrating agitation mechanism includes setting at least one vibration parameter of the vibrating agitation mechanism so as to promote transitioning of the valve between the closed operative orientation and the open operative orientation.

- 5 142. The method of any one of embodiments 136 to 141, wherein the controlling the vibrating agitation mechanism includes setting at least one vibration parameter of the vibrating agitation mechanism so as to promote absorption of the ingestible medicament into the bloodstream of the user.

- 10 143. The method of embodiment 141 or embodiment 142, wherein the setting the at least one vibration parameter includes setting at least one of a vibration frequency, a cumulative vibration duration, a number of vibration cycles per time unit, a duration of a vibration duration within a vibration cycle, a duration of a repose duration within a vibration cycle, a total duration of a single vibration cycle, and a net force exerted by the housing on the environment.

- 15 144. The method of any one of embodiments 139 to 143, wherein the housing of the vibrating ingestible capsule includes an attachment mechanism, the second housing portion includes a corresponding attachment mechanism, and the attaching includes mutually attaching the housing of the vibrating ingestible capsule to the second housing portion.

- 20 145. The method of any one of embodiments 139 to 144, wherein the attaching includes fixedly attaching the second housing portion to the housing of the vibrating ingestible capsule.

146. The method of any one of embodiments 139 to 144, wherein the attaching includes attaching the second housing portion to the housing of the vibrating ingestible capsule by snap fit engagement.

- 25 147. The method of any one of embodiments 139 to 144, wherein the attaching includes attaching the second housing portion to the housing of the vibrating ingestible capsule by threaded engagement.

- 30 148. The method of any one of embodiments 139 to 144, wherein the attaching includes attaching the second housing portion to the housing of the vibrating ingestible capsule by adhering.

149. The method of any one of embodiments 139 to 144, wherein the attaching includes attaching the second housing portion to the housing of the vibrating ingestible capsule by soldering.

5 150. The method of any one of embodiments 136 to 149, wherein the controlling includes controlling a timing or activation delay of the vibration mode of operation such that the vibration mode of operation at least partially transpires within a region of the gastrointestinal tract in which the flowable ingestible medicament is absorbable by the body of the user.

10 151. The method of any one of embodiments 136 to 150, wherein the controlling includes controlling a timing or activation delay of the vibration mode of operation such that the vibration mode of operation at least partially transpires within at least one of an estimated absorption time period and an actual absorption time period of the flowable ingestible medicament released from reservoir within the gastrointestinal tract of the user.

15 152. The method of any one of embodiments 136 to 151, further including, prior to the controlling, at the control element receiving an activation input, wherein the controlling includes activating the vibration agitation mechanism to be operative in the vibration mode of operation following the receiving the activation input.

153. The method of embodiment 152, wherein the receiving the activation input includes receiving the activation input from at least one sensor.

20 154. The method of embodiment 153, wherein the receiving the activation input includes receiving, from an illumination sensor, an input indicating transition of the device from an illuminated environment to a dark environment.

25 155. The method of any one of embodiments 153 to 154, wherein the receiving the activation input includes receiving, from a pressure sensor, an input indicating pressure applied to the device, which pressure is indicative of the device moving through a pharynx of the user.

30 156. The method of any one of embodiments 153 to 155, wherein the receiving the activation input includes receiving, from a temperature sensor, an input indicating transition of the device from an area with ambient temperature to an area with a human body temperature.

157. The method of any one of embodiments 153 to 156, wherein the receiving the

activation input includes receiving, from an accelerometer, an input in response to a detected activation motion carried out with the device.

158. The method of any one of embodiments 153 to 157, wherein the receiving the activation input includes receiving, from a moisture sensor, an input indicating transition of  
5 the device from a dry environment to a humid environment.

159. The method of any one of embodiments 152 to 158, wherein the receiving the activation input includes receiving the activation input from a control unit remote from the device and functionally associated with the control element.

160. The method of any one of embodiments 152 to 159, wherein the receiving the activation input occurs following the ingesting of the device.  
10

161. The method of any one of embodiments 152 to 160, wherein the receiving the activation input occurs prior to the ingesting of the device.

162. The method of any one of embodiments 152 to 161, wherein the receiving the activation input includes receiving a vibration protocol to be used by the control element for  
15 the controlling operation of the vibrating agitation mechanism.

163. The method of any one of embodiments 136 to 162, wherein the controlling the vibrating agitation mechanism includes controlling the vibration agitation mechanism such that the vibrating mode of operation includes a plurality of cycles, each of the cycles including a vibration duration followed by a repose duration, wherein the housing exerts the vibrations during the vibration duration.  
20

164. The method of embodiment 163, wherein the repose duration is greater than the vibration duration.

165. The method of embodiment 163 or embodiment 164, wherein the vibration duration is in the range of 0.1 second to 10 seconds, 1 second to 10 seconds, 1 second to 9 seconds, 2  
25 seconds to 9 seconds, 3 seconds to 9 seconds, 3 seconds to 8 seconds, 3 seconds to 7 seconds, 3 seconds to 6 seconds, 4 seconds to 6 seconds, or 5 seconds to 6 seconds.

166. The method of any one of embodiments 163 to 165, wherein the repose duration is in the range of 1 second to 180 seconds, 3 seconds to 180 seconds, 5 seconds to 180 seconds, 5 seconds to 150 seconds, 5 seconds to 120 seconds, 8 seconds to 100 seconds, 8  
30 seconds to 30 seconds, 10 seconds to 80 seconds, 10 seconds to 70 seconds, 10 seconds to

60 seconds, 10 seconds to 50 seconds, 10 seconds to 40 seconds, 10 seconds to 30 seconds, 10 seconds to 20 seconds, or 15 seconds to 20 seconds.

167. The method of any one of embodiments 163 to 166, wherein a duration of each of the plurality of cycles is in the range of 1.1 seconds to 200 seconds, 5 seconds to 200  
5 seconds, 10 seconds to 200 seconds, 10 seconds to 150 seconds, 10 seconds to 100 seconds, 10 seconds to 80 seconds, 10 seconds to 50 seconds, 10 seconds to 40 seconds, 10 seconds to 30 seconds, 15 seconds to 50 seconds, 15 seconds to 40 seconds, 15 seconds to 30 seconds, or 15 seconds to 25 seconds.

168. The method of any one of embodiments 136 to 167, wherein the controlling includes  
10 controlling the vibrating agitation mechanism such that a cumulative duration of the vibrating mode of operation is in the range of 1 hour to 12 hours, 2 hours to 10 hours, 2 hours to 8 hours, 2 hours to 6 hours, 2 hours to 4 hours, or 2 hours to 3 hours.

169. The method of any one of embodiments 136 to 168, wherein the controlling including controlling the vibrating agitation mechanism to exert forces on the housing, such  
15 that a net force exerted by the housing on the environment thereof is in the range of 50 grams force (gf) to 600gf, 50gf to 550gf, 100gf to 550gf, 100gf to 500gf, 150gf to 500gf, 200gf to 500gf, or 200gf to 450gf.

170. The method of any one of embodiments 136 to 169, wherein the controlling including controlling the vibrating agitation mechanism to exert the forces on the housing to  
20 attain a housing vibrational frequency within a range of 10Hz to 650Hz, 15Hz to 600Hz, 20Hz to 550Hz, 30Hz to 550Hz, 50Hz to 500Hz, 70Hz to 500Hz, 100Hz to 500Hz, 130Hz to 500Hz, or 150Hz to 500Hz.

171. The method of any one of embodiments 136 to 170, wherein the flowable ingestible medicament has a viscosity in the range of 100 Pa·s to 1000 Pa·s.

25 172. The method of any one of embodiments 136 to 171, wherein the flowable ingestible medicament is absorbable in the stomach of the user.

173. The method of any one of embodiments 136 to 172, wherein the flowable ingestible medicament is absorbable in the small intestine of the user.

174. The method of any one of embodiments 136 to 173, the flowable ingestible  
30 medicament being is suitable for treatment of one or more symptom or disease, selected from the group listed in embodiment 66.

175. The method of any one of embodiments 136 to 174, wherein the flowable ingestible medicament includes or includes an ingestible medicament selected from the group listed in embodiment 67.

5 It will be appreciated that certain features of the invention, which are, for clarity, described in the context of separate embodiments, may also be provided in combination in a single embodiment. Conversely, various features of the invention, which are, for brevity, described in the context of a single embodiment, may also be provided separately or in any suitable sub-combination.

10 Although the invention has been described in conjunction with specific embodiments thereof, it is evident that many alternatives, modifications and variations will be apparent to those skilled in the art. Accordingly, it is intended to embrace all such alternatives, modifications and variations that fall within the spirit and broad scope of the appended claims. All publications, patents and patent applications mentioned in this specification are herein incorporated in their entirety by reference into the specification, to  
15 the same extent as if each individual publication, patent or patent application was specifically and individually indicated to be incorporated herein by reference. In addition, citation or identification of any reference in this application shall not be construed as an admission that such reference is available as prior art to the present invention.

## WHAT IS CLAIMED IS:

1. A device for delivering a flowable ingestible medicament into the gastrointestinal tract of a user, the device comprising:

a housing including a first housing portion and a second housing portion, said second housing portion having a portal formed therein;

a vibrating agitation mechanism disposed within said housing and adapted such that, in a vibration mode of operation, said housing exerts vibrations on an environment surrounding the device;

a power supply disposed within said housing and adapted to power said vibrating agitation mechanism; and

a control element adapted to activate said vibrating agitation mechanism to be operative in said vibration mode of operation;

a flexible and collapsible medicament reservoir dimensioned to contain the flowable ingestible medicament;

a reservoir biasing mechanism adapted to apply pressure to said flexible and collapsible medicament reservoir;

a conduit extending from said medicament reservoir to said portal, and sealing said portal; and

a valve including a weight and a valve biasing mechanism adapted, in a closed operative orientation, to bias said weight against said conduit so as to block flow through said conduit, and in an open operative orientation to remove the weight from said conduit so as to allow fluid to flow through said conduit,

wherein said valve is functionally associated with at least one of said housing and said vibrating agitation mechanism, such that when said vibrating agitation mechanism is in said vibration mode of operation, at least some of said vibrations exerted by said vibrating agitation mechanism or by said housing are applied to said valve biasing mechanism and periodically transition said valve between said closed operative orientation and said open operative orientation.

2. The device of claim 1, wherein, when said vibrating agitation mechanism is in said vibration mode of operation and said valve is in said open operative orientation, pressure applied by said reservoir biasing mechanism to said reservoir causes the flowable ingestible

medicament to flow from said reservoir, via said conduit and said portal, to an environment surrounding said device.

3. The device of claim 1 or claim 2, wherein at least one vibration parameter of said vibrating agitation mechanism is set so as to promote transitioning of said valve between said closed operative orientation and said open operative orientation.

4. The device of any one of claims 1 to 3, wherein at least one vibration parameter of said vibrating agitation mechanism is set so as to promote absorption of the ingestible medicament into the bloodstream of the user.

5. The device of any one of claim 1 to 4, wherein at least one valve parameter of said valve is set such that said valve functions as a gear reducer, opening and closing at a frequency smaller than a frequency of said vibrating agitation mechanism.

6. The device of claim 5, wherein said at least one valve parameter includes a mass of said weight, a length of said valve biasing mechanism, and a spring constant of said valve biasing mechanism.

7. The device of any one of claims 1 to 6, wherein:

said first housing portion is a sealed housing portion accommodating said vibrating agitation mechanism, said power supply, and said control element;

said second housing portion accommodates said flexible and collapsible medicament reservoir, said reservoir biasing mechanism, said conduit, and said valve;

said first housing portion and said second housing portion are separate elements, which are attached to each other to form said housing; and

said valve is functionally associated with said first housing portion such that when said vibrating agitation mechanism is in said vibration mode of operation, at least some of the vibrations exerted by said first housing portion are applied to said valve biasing mechanism and periodically transition said valve between said closed operative orientation and said open operative orientation.

8. The device of claim 7, wherein said first housing portion includes an attachment mechanism and said second housing portion includes a corresponding attachment mechanism, for mutual attachment of said first and second housing portions.
9. The device of any one of claims 1 to 6, wherein said first and second housing portions form a single housing element including said portal and defining a single hollow, said single hollow accommodating said vibrating agitation mechanism, said power supply, said control element, said flexible and collapsible medicament reservoir, said reservoir biasing mechanism, and said conduit.
10. The device of any one of claims 1 to 9, wherein a hollow of said second housing portion has a volume in the range of  $200\text{mm}^3$  to  $3000\text{mm}^3$ ,  $200\text{mm}^3$  to  $800\text{mm}^3$ ,  $100\text{mm}^3$  to  $600\text{mm}^3$ ,  $400\text{mm}^3$  to  $1000\text{mm}^3$ ,  $700\text{mm}^3$  to  $1500\text{mm}^3$ , or  $1400\text{mm}^3$  to  $3000\text{mm}^3$ .
11. The device of any one of claims 1 to 10, wherein said flexible and collapsible medicament reservoir has at least one of:
- a maximal volume in the range of 0.5ml to 15ml; and
  - a Young's modulus smaller than 1 GPa.
12. The device of any one of claims 1 to 11, wherein said reservoir biasing mechanism comprises a reservoir spring terminating in a pressure applying surface, said pressure applying surface engaging an exterior surface of said medicament reservoir, said reservoir spring being anchored to said hollow compartment housing.
13. The device of any one of claims 1 to 12, wherein said reservoir biasing mechanism has a spring constant in the range of 1 N/m to 200 N/m.
14. The device of any one of claims 1 to 13, wherein said conduit is at least one, and optionally both, of flexible and resilient.
15. The device of any one of claims 1 to 14, wherein a recovery time of said conduit is at most 0.1 seconds.

16. The device of any one of claims 1 to 15, wherein said vibrating agitation mechanism has a frequency  $f$ , and a recovery time of said conduit is at most equal to  $1/f$ .
17. The device of any one of claims 1 to 15, wherein said valve biasing mechanism has a frequency  $f_v$  of moving from said open operative orientation to said closed operative orientation and back to said open operative orientation, and a recovery time of said conduit is at most equal to  $1/f_v$ .
18. The device of any one of claims 1 to 17, wherein said conduit has at least one of:  
a diameter in the range of 0.01mm to 0.9mm; and  
a length in the range of 3mm to 25mm.
19. The device of any one of claims 1 to 18, wherein said valve biasing mechanism has a spring constant in the range of 0.1 N/m to 5 N/m.
20. The device of any one of claims 1 to 19 wherein said weight has a mass in the range of 0.1 grams to 2 grams.
21. The device of any one of claims 1 to 20, wherein said weight includes said vibrating agitation mechanism.
22. The device of any one of claims 1 to 21, wherein said vibrations exerted by said vibrating agitation mechanism are transferred, through an anchoring point of said valve biasing mechanism, to said valve biasing mechanism, thereby causing rocking of said valve biasing mechanism resulting in said periodic transitioning of said valve between said closed operative orientation and said open operative orientation.
23. The device of any one of claims 1 to 22, wherein said control element is adapted to control at least one of:  
a timing or activation delay of said vibration mode of operation such that said vibration mode of operation at least partially transpires within a region of the gastrointestinal tract in which the flowable ingestible medicament is absorbable by the body of the user; and  
a timing or activation delay of said vibrating mode of operation such that said vibration mode of operation at least partially transpires during at least one of an estimated

absorption time period and an actual absorption time period of the flowable ingestible medicament released from said reservoir, via said conduit and said portal, into the gastrointestinal tract of the user.

24. The device of any one of claims 1 to 23, wherein said vibrating agitation mechanism comprises at least a radial agitation mechanism adapted, in said vibration mode of operation, to exert radial forces on said housing, in a radial direction with respect to a or said longitudinal axis of said housing, thereby to cause said vibrations exerted by said housing.

25. The device of any one of claims 1 to 24, wherein said vibrating agitation mechanism comprises at least an axial agitation mechanism adapted, in said vibration mode of operation, to exert axial forces on said housing, in an axial direction with respect to a or said longitudinal axis of said housing, thereby to cause said vibrations exerted by said housing.

26. The device of any one of claims 1 to 25, further comprising said flowable ingestible medicament disposed within said medicament reservoir.

27. The device of any one of claims 1 to 26, wherein said flowable ingestible medicament has a viscosity in the range of 100 Pa·s to 1000 Pa·s.

28. A medicament delivery compartment, adapted to be attached to a vibrating ingestible capsule having a first housing portion and adapted to operate in a vibrating mode of operation, for delivery of a flowable ingestible medicament into the gastrointestinal tract of a user, the medicament delivery compartment including:

- a second housing portion adapted to be attached to said first housing portion of said vibrating ingestible capsule, and having a portal formed therein;

- a flexible and collapsible medicament reservoir dimensioned to contain the flowable ingestible medicament;

- a reservoir biasing mechanism adapted to apply pressure to said flexible and collapsible medicament reservoir;

- a conduit extending from said medicament reservoir to said portal, and sealing said portal; and

- a valve including a weight and a valve biasing mechanism adapted, in a closed operative orientation, to bias said weight against said conduit so as to block flow through

said conduit, and in an open operative orientation to remove the weight from said conduit so as to allow fluid to flow through said conduit.

29. The medicament delivery compartment of claim 28, wherein said valve is configured to be in said open operative orientation and to enable flow through said conduit when the vibrating ingestible capsule is in the vibration mode of operation.

30. A vibrating ingestible capsule adapted to be attached to a medicament delivery compartment for delivering a flowable ingestible medicament disposed within the medicament delivery compartment into the gastrointestinal tract of a user, the vibrating ingestible capsule including:


- a housing including an attachment mechanism adapted for mutual attachment to a corresponding attachment mechanism of the medicament delivery compartment;

- a vibrating agitation mechanism disposed within said housing and adapted such that, in a vibration mode of operation, said housing exerts vibrations on an environment surrounding the vibrating ingestible capsule;

- a power supply disposed within said housing and adapted to power said vibrating agitation mechanism; and

- a control element adapted to activate said vibrating agitation mechanism to be operative in said vibration mode of operation,

wherein at least one vibration parameter of said vibrating agitation mechanism is set so as to promote at least one of delivery of the flowable ingestible medicament from the medicament delivery compartment into an environment surrounding the medicament delivery compartment and absorption of the flowable ingestible medicament into the bloodstream of the user.






FIG. 3







FIG. 4A










FIG. 6

Figure 7

