



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : C11D 3/39, 3/00	A2	(11) International Publication Number: WO 98/20101 (43) International Publication Date: 14 May 1998 (14.05.98)
(21) International Application Number: PCT/US97/20213 (22) International Filing Date: 7 November 1997 (07.11.97) (30) Priority Data: 08/745,164 7 November 1996 (07.11.96) US (71) Applicant: S.C. JOHNSON & SON, INC. [US/US]; 1525 Howe Street, Racine, WI 53403 (US). (72) Inventors: MISHRA, Bijaya, K.; Chandrakat Bindha, Balasore, Orissa, 756131 (IN). FRIBERG, Stig, E.; Outer Main Street, Potsdam, NY 13676 (US). (74) Agents: BOZEK, Laura, L. et al.; S.C. Johnson & Son, Inc., Patent Section, 1525 Howe Street, Racine, WI 53403 (US).		(81) Designated States: AU, CA, CN, JP, NZ, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>Without international search report and to be republished upon receipt of that report.</i>
(54) Title: TUNGSTEN CONTAINING HARD SURFACE BLEACHING COMPOSITION (57) Abstract Disclosed herein are bleaching systems that contain a peroxide and an activator. The activator is a tungsten containing compound, preferably sodium tungstate or tungstosilicic acid. When such bleaching systems are applied in an aqueous alkaline environment they can bleach mold, fungus, and the like.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakistan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

TUNGSTEN CONTAINING HARD SURFACE BLEACHING COMPOSITION

5

Technical Field

The present invention relates to cleaning compositions that contain peroxide.
10 These compositions can be used to remove organic and other stains from various hard surfaces and textiles.

15

Background Art

Peroxides are known bleaching agents. They can be supplied as hydrogen peroxide itself, or by using a hydrogen peroxide "generator" such as a perborate, a percarbonate, a peroxyurea compound, persilic acid and hydrogen peroxide adducts of
20 pyrophosphates, citrates, sodium sulfate and sodium silicate. Such generators readily release hydrogen peroxide in aqueous solution.

However, such peroxides achieve only moderate bleaching when used by themselves in an aqueous environment. Better results have been achieved when they are used with activators. See e.g. U.S. patents 3,398,096, 4,119,557 and 5,460,747.
25 The disclosure of these patents, and of all other publications referred to herein, are incorporated by reference as if fully set forth herein.

Unfortunately, such activators present their own problems. Some activators are susceptible to storage instability. Others are expensive to produce or are highly toxic. Others provide only minor improvements in bleaching effectiveness.

30 In unrelated work, it has been determined that a tungstate can catalyze the oxidation of secondary amines with hydrogen peroxide (H. Mitsui, J. Chem Soc.

Chem. Comm. 874 (1984)), and that an in acid environment certain tungsten containing compounds used with peroxides can help process pulp (U.S. patent 4,427,490).

5 However, hard surfaces stains in buildings and on materials to be used for manufacturing are often caused by mold/fungus, and such stains can be resistant to bleaching by acidic cleaners. Similarly, stains on non-woven and woven textiles can be resistant to bleaching by conventional cleaning compositions. Moreover, peroxides can have stability problems during storage, and especially in alkaline environments.

10 Thus, a need exists for improved activators for use in alkaline peroxide bleaching systems.

Disclosure Of Invention

15 In one aspect, the invention provides a bleaching system having a peroxide and a tungsten containing activator. The system operates best at an alkaline pH, preferably at between pH 8.0 and pH 10.99.

20 Preferred bases to be used with these systems are alkali metal hydroxides, alkali metal carbonates, alkali metal borates, alkali metal phosphates, alkali metal citrates, organo carboxylated citrates, ammonia, and alkali metal salts of polyacrylic acid. Alternatively, the tungsten containing activator can itself be a weak base (e.g. sodium tungstate).

25 In one form, the peroxide is selected from the group consisting of hydrogen peroxide, percarbonates, perborates, and hydrogen peroxide adducts of pyrophosphates, citrates, sodium sulfate, urea and sodium silicate, and mixtures thereof. The activator is preferably selected from the group consisting of sodium tungstate (e.g. provided in the dihydrate form: $\text{Na}_2\text{WO}_4 \cdot 2\text{H}_2\text{O}$) and tungstosilicic acid

(a/k/a silicotungstic acid: $H_4[SiO_4(W_3O_9)_4]$). However, other tungsten containing compounds are alternatives (e.g. where the tungsten is at a plus six oxidation state).

A surfactant such as an anionic surfactant or a non-ionic surfactant can also be used with such bleaching systems, as can the usual chelating agents (e.g. EDTA), dyes,
5 and fragrances.

In the preferred "bleaching system" the activator and the peroxide are separately stored prior to use. In one container there can be an alkaline stabilized solution of hydrogen peroxide, and in another container the activator can be stored prior to use. Alternatively, the activator can be stored in one container in an alkaline
10 solution, and hydrogen peroxide can be stored in a separate container (as standard, mildly acidic hydrogen peroxide). Where the peroxide generator and activator are both solids they can be stored together.

In yet another form, the invention provides a method of bleaching an organic stain (e.g. fungus/mold) that is present on a surface. One applies the above bleaching
15 system to the stain in a solution that has a pH that is above 7.0 (preferably between 8.0 and 10.99). The activator reacts with the hydrogen peroxide to generate singlet oxygen in the solution, which in turn bleaches the stain.

In addition to other cleaning applications, the bleaching system can be used to bleach paper pulp products and textiles (including fabrics and carpeting), such as those
20 containing cotton and/or artificial fibers such as nylon and polyester.

The peroxide and the activator are preferably mixed in a molar ratio from 20:1 to 1:2, with the most preferred embodiments having at least an excess of the peroxide. When water is pre-added (e.g. when the activator and peroxide are separately stored as liquids), it is preferred to use deionized water to avoid the inclusion of stray
25 transition metal ions. The activator can be 0.1%-10% of the system (by weight),

preferably 1%-3%. Even more activator can be added, but this may undesirably raise the cost of the bleach.

Preferred surfactants are non-ionic surfactants such as the Neodols from Shell Chemical. However, a wide variety of other surfactants should also be useful.

5 Surfactants that may be employed in the present invention include anionic, nonionic and amphoteric surfactants, and mixtures thereof. Suitable anionic surfactants include alpha olefin sulfonates, the alkyl aryl sulfonic acids and their alkali metal and alkaline earth metal salts such as sodium dodecyl benzene sulfonate, magnesium dodecyl benzene sulfonate, disodium dodecyl benzene disulfonate and the
10 like, as well as the alkali metal salts of fatty alcohol esters of sulfuric and sulfonic acids, the alkali salts of alkyl aryl (sulfothioic acid) esters, alkyl thiosulfuric acid and soaps such as coco or tallow, etc. Other anionics include sodium dodecyl benzene sulfonate available under the tradename Nacconal 40-G from Stepan Company, Northfield, Illinois, and sodium lauryl sulfate also from the Stepan Company.

15 Nonionic surfactants include the ethylene oxide esters of alkyl phenols such as (nonylphenoxy) polyoxyethylene ether, the ethylene oxides esters of fatty alcohols such as tridecyl alcohol polyoxyethylene ether, the propylene oxide ethers of fatty alcohols, the ethylene oxide ethers of alkyl mercaptans such as dodecyl mercaptan polyoxyethylene thioester, the ethylene oxide esters of acids such as the lauric ester of
20 methoxy polyethylene glycol, the ethylene oxide ethers of fatty acid amides, the condensation products of ethylene oxide with partial fatty acid esters of sorbitol such as the lauric ester of sorbitan polyethylene glycol ether, and other similar materials.

 Amphoteric surfactants include the fatty imidazolines, such as 2-coco-1 hydroxyethyl-1 carboxymethyl-1hydroxyimidazoline and similar compounds made by
25 reacting monocarboxylic fatty acids having chain lengths of 10 to 24 carbon atoms with 2-hydroxy ethyl ethylene diamine and with monohalo monocarboxylic fatty acids.

An additional class of surfactants are amine oxides which demonstrate cationic surfactant properties in acidic pH and nonionic surfactant properties in alkaline pH. Example amine oxides include alkyl dimethyl amine oxide, dihydroxyethyl cocamine oxide, tallowamidopropylamine oxide and lauramine oxide.

5 The invention can bleach out a wide variety of organic stains on a wide variety of surfaces (e.g. plumbing fixtures, floors, walls, countertops). However, as noted below, the bleaching systems of the invention are particularly effective in bleaching mold/fungus caused discolorations on ceramic tile and plastic.

10 The objects of the present invention therefore include providing a bleaching system of the above kind:

- (a) having desirable stability characteristics;
- (b) having excellent stain removal capability; and
- (c) which is relatively inexpensive to produce.

15 These and still other objects and advantages of the present invention (e.g. methods for using such bleaching systems) will be apparent from the description which follows. The following description is merely of the preferred embodiments. Thus, the claims should be looked to in order to understand the full scope of the invention.

20 Best Modes For Carrying Out The Invention

Tile Experiments

25

Solution A is .1 g tungstosilicic acid and 9.9 g deionized H₂O.

Solution B is 10 g of 6% H₂O₂ and .5 g of 2.5 M NaOH.

Solution C is 6% H₂O₂.

Solution D is .1 g of sodium tungstate and 9.9 g of deionized water.

30 Experiment 1

10 g of Solution A was mixed with 6 g of Solution B. A 1 ml sample of the resulting mixture (approximately pH 8.5) was placed onto a mold stained ceramic tile (stained by spraying on an *aspergillus niger* spore suspension). The stained (medium brown) tile color was bleached white within two minutes.

5 Experiment 2

10 g of Solution A was mixed with 6 g of Solution B. A 1 ml sample of the mixture (approximately pH 8.5) was applied to a mold stained plastic shower curtain, where the mold had been naturally grown. The surface was bleached completely (to the eye) within five minutes of application.

10 Experiments 3/4

10 g of Solution C was mixed with 10 g of Solution D. The resulting solution was pH 8.0. The above mixture was then applied to the same types of stained tiles and plastic as in Experiments 1 and 2. The tiles and curtain were bleached completely within less than two minutes.

15 It should be appreciated that the above experiments merely describe preferred forms of the invention. Other forms of the invention are also possible. For example, surfactants, fragrance, dyes and other conventional additives can be included. Also, suitable thickener compositions can be incorporated.

20

Industrial Applicability

25 The bleaching systems of the present invention can be used in connection with cleaning tiles, countertops, and the like prior to sale (at a factory or at an industrial plant). It may also have utility as a hard surface cleaner in certain building applications. Also, the systems can be used to bleach textile or paper products.

Claims

5 We claim:

1. A bleaching system, comprising:
a peroxide; and
10 an activator containing tungsten;
wherein the bleaching system, when used, has a pH above 7.0.
2. The bleaching system of claim 1, further comprising a base selected
from the group consisting of alkali metal hydroxide, alkali metal carbonate, alkali metal
15 borate, alkali metal phosphate, alkali metal citrate, organo carboxylated citrate,
ammonia, and alkali metal salt of polyacrylic acid.
3. The bleaching system of claim 1, wherein the peroxide is selected from
the group consisting of hydrogen peroxide, percarbonates, perborates, hydrogen
20 peroxide adducts of pyrophosphates, citrates, sodium sulfate, urea and sodium silicate,
and mixtures thereof.
4. The bleaching system of claim 3, wherein the peroxide is hydrogen
peroxide.
25
5. The bleaching system of claim 1, wherein the activator is selected from the
group consisting of sodium tungstate and tungstosilicic acid.
6. The bleaching system of claim 5, further comprising a surfactant.

7. The bleaching system of claim 5, wherein the activator and peroxide are stored in separate containers.

5 8. A method of bleaching an organic stain that is present on a solid surface, comprising:

applying the bleaching system of claim 1 to the stain in an aqueous solution that has a pH above 7.0.

10

9. The method of claim 8, wherein the pH of the aqueous solution is between pH 8.0 and 10.99.

10. Bleached paper that has been produced by the method of claim 8.

15

11. Bleached textile fabric that has been produced by the method of claim 8.