




(86) Date de dépôt PCT/PCT Filing Date: 2020/12/27
 (87) Date publication PCT/PCT Publication Date: 2021/08/05
 (45) Date de délivrance/Issue Date: 2023/02/21
 (85) Entrée phase nationale/National Entry: 2022/07/19
 (86) N° demande PCT/PCT Application No.: IL 2020/051334
 (87) N° publication PCT/PCT Publication No.: 2021/152570
 (30) Priorité/Priority: 2020/02/02 (IL272406)

(51) Cl.Int./Int.Cl. *A61B 42/50* (2016.01),
A61B 42/00 (2016.01), *A61B 42/10* (2016.01),
A61B 42/40 (2016.01), *B65G 47/00* (2006.01),
B65G 47/90 (2006.01)
 (72) Inventeur/Inventor:
 SHALOM AVSHALOM, SHLOMO MATAN, IL
 (73) Propriétaire/Owner:
 IGIN SMART HYGIENE PTE. LTD, SG
 (74) Agent: INTEGRAL IP

(54) Titre : APPAREIL PERMETTANT DE METTRE EN PLACE UN GANT SUR LA PAUME D'UNE MAIN
 (54) Title: APPARATUS FOR PUTTING A GLOVE ON A PALM HAND



(57) **Abrégé/Abstract:**

A gloving apparatus that has a glove-opening device and a glove-lifting-and-positioning device. The glove-lifting-and-positioning device includes a linear actuator with a moveable rod that is ended with an inserting pin, a rotating actuator that is designed to rotate the glove-lifting-and-positioning device, and a lifting arm with a lifting actuator that are designed to lift up and lower down the glove-lifting-and-positioning device. The glove-lifting-and-positioning device is designed to insert the inserting pin into a matching hole at a glove holder to which a glove is attached and to insert the opening of the glove over grasping pins of the glove-opening device. The glove-opening device can stretch open the glove opening and when an air pump creates sub-pressure then the glove inflates to a size suitable for a hand to be inserted.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau

(43) International Publication Date
05 August 2021 (05.08.2021)



(10) International Publication Number
WO 2021/152570 A1

(51) International Patent Classification:

A61B 42/50 (2016.01) *A61B 42/10* (2016.01)
A61B 42/00 (2016.01) *B65G 47/90* (2006.01)
A61B 42/40 (2016.01) *B65G 47/00* (2006.01)

ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO,
NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW,
SA, SC, SD, SE, SG, SK, SL, ST, SV, SY, TH, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, WS, ZA, ZM, ZW.

(21) International Application Number:

PCT/IL2020/051334

(22) International Filing Date:

27 December 2020 (27.12.2020)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

272406 02 February 2020 (02.02.2020) IL

(72) Inventor; and

(71) Applicant: AVSHALOM, Shlomo Matan Shalom
[IL/IL]; 177 Emek Hazeitim, 9903454 Beit Shemesh (IL).

(74) Agent: DAHAN, Meir; P.O.Box 174, 1794000 Adi (IL).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, IT, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD,

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*):

ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report (Art. 21(3))*

(54) Title: APPARATUS FOR PUTTING A GLOVE ON A PALM HAND




FIG. 8

(57) Abstract: A gloving apparatus that has a glove-opening device and a glove-lifting-and-positioning device. The glove-lifting-and-positioning device includes a linear actuator with a moveable rod that is ended with an inserting pin, a rotating actuator that is designed to rotate the glove-lifting-and-positioning device, and a lifting arm with a lifting actuator that are designed to lift up and lower down the glove-lifting-and-positioning device. The glove-lifting-and-positioning device is designed to insert the inserting pin into a matching hole at a glove holder to which a glove is attached and to insert the opening of the glove over grasping pins of the glove-opening device. The glove-opening device can stretch open the glove opening and when an air pump creates sub-pressure then the glove inflates to a size suitable for a hand to be inserted.



WO 2021/152570 A1

1

Apparatus for Putting a Glove on a Palm Hand

Description

TECHNICAL FIELD

The present invention refers to a gloving apparatus for putting a sterile glove on a palm hand.

BACKGROUND ART

It is customary and sometimes necessary to use sterile gloves in operating theaters to perform medical surgeries, laboratories, and in various other places in which a sterile environment must be maintained. The user, for instance a surgeon preparing for surgery, usually scrubs and disinfects his or her hands with soap and a disinfectant and then puts on a pair of sterile gloves. While putting the gloves on his or her hands, the user touches the gloves, potentially contaminating the exterior of the glove. Touching the exterior of the gloves, even after scrubbing and disinfecting, may contaminate them with bacteria. The present invention describes a system that offers a solution to this problem.

LIST OF DRAWINGS

The intention of the drawings attached to the application is not to limit the scope of the invention and its application. The drawings are intended only to illustrate the invention and they constitute only one of its many possible implementations.

FIG. 1 presents a glove (100) with its opening (103) and the circumferential part (104) of the opening (103).

FIGS 2 and 3 depict the gloving apparatus (1) that includes the casing (2), the glove-opening device (3), the glove-lifting-and-positioning device (4), the air
5 pump (5), and the replaceable glove cartridge (7).

FIGS 4 and 5 depict the glove-lifting-and-positioning device (4) when the moveable rod (411) is facing downwards on the way to collect a glove from the replaceable cartridge (7).

FIGS 6 and 7 depict the glove-lifting-and-positioning device (4) when the
10 inserting pin is inserted in the matching hole of the glove holder.

FIGS 8 and 9 depict the glove-lifting-and-positioning device (4) in diagonal state and that holds a glove on the way to wear the glove on the glove-opening device (3).

FIGS 10 and 11 depict the glove-lifting-and-positioning device (4) in
15 horizontal state and that holds a glove and wears the glove on the glove-opening device (3).

FIGS 12 and 13 depict the glove-lifting-and-positioning device (4) that wears the glove on the glove-opening device (3).

FIG. 14 depicts the glove (100) when inserted on the grasping pins and inflated
20 and ready to receive the user's hand.

FIG. 15 depicts the glove-lifting-and-positioning device (4) when the movable rod (411) is in “up” position.

FIG. 16 depicts the glove-lifting-and-positioning device (4) when the movable rod (411) is in “down” position.

FIGS 17 and 18 depict the glove-lifting-and-positioning device (4) in diagonal position.

5 FIG. 19 depicts the adjustment piece (48) in two states relative to the moveable rod (411).

FIGS 20 and 21 depict the inserting pin (42) when inserted in the glove holder.

FIGS 22 and 23 depict the inserting pin (42) before and after being inserted into the glove holder (6).

10 FIGS 24A – 24E depict several states of the moveable rod (411) and the glove holder (6).

FIG. 25 depicts the glove holder (6).

FIG. 26 depicts the glove holder (6) with a glove (100).

FIGS 27 and 28 depict the glove-opening device (3) wherein the grasping pins
15 (36) are concentrated in the center of the polygonal circumferential frame (31).

FIG. 29 depicts the glove-opening device (3) in partially opened position.

FIG. 30 depicts the glove-opening device (3) in an open position.

FIGS 31 – 33 depict the adjuster (8) in several states.

FIG. 34 is a partial cross section view of the replaceable cartridge (7) with the
20 follower (92) and the spring (93).

FIG. 35 depicts an empty replaceable cartridge (7).

FIG. 36 is a top view of the replaceable cartridge (7).

FIG. 37 is a top frame of the cartridge that includes the stoppers (75).

THE INVENTION

The main objective of the present invention is to provide a gloving apparatus (1) that is designed to help users to put gloves on their hands. The gloving apparatus (1) comprises the following main parts: a casing (2), a glove-opening device (3), a glove-lifting-and-positioning device (4), and an air pump (5).

The gloving apparatus (1) may contain a replaceable glove cartridge (7) that is designed to contain gloves (100). The gloves may be placed in the replaceable glove cartridge, one on top of the other. The replaceable glove cartridge may be a fixed as permanent part of the gloving apparatus that is refilled whenever the gloves run out, or alternatively, the entire replaceable cartridge may be replaced with a new replaceable glove cartridge, thus serving as a kind of disposable glove cartridge. In cases in which the sterility of the gloves must be maintained, the disposable, replaceable glove cartridge setup is more appropriate and recommended.

The glove-lifting-and-positioning device (4) is designed to lift a glove, possible from a replaceable glove cartridge, one glove at a time, and to position the glove opening (103) over the glove-opening device (3).

The gloving apparatus (1), as depicted in the drawings and as explained above, includes the casing (2), the glove-lifting-and-positioning device (4), the glove-opening device (3), and the air pump (5). The casing (2) is partially depicted in the drawings and it contains the above-mentioned parts of the gloving apparatus (1). The casing (2) may also contain the replaceable glove cartridge (7).

The glove-lifting-and-positioning device (4) includes:

- (a) A base (43) with a linear actuator (41) that is equipped with a moveable rod (411). When operating the linear actuator the moveable rod is designed to move forth and back.
- 5 (b) A rotating actuator (44) that is designed to rotate the glove-lifting-and-positioning device (4). By operating the rotating actuator it is possible to rotate the glove-lifting-and-positioning device and to change the direction to which the moveable rod is facing.
- (c) A lifting arm (45) with a lifting actuator (46) that is designed to lift up and
10 lower down the glove-lifting-and-positioning device (4). The drawings depict for example two lifting arms. By controlling the lifting actuator the position of the glove-lifting-and-positioning device is changed.
- (d) The base also includes releasing rods (47). The moveable rod (411) is ended with an inserting pin (42) and the moveable rod (411) includes an adjustment
15 piece (48) with adjustment rods (49).

The glove-lifting-and-positioning device (4) is designed to descend and reaches a glove holder (6) to which a glove (100) is attached and then to "pick up" the glove by the movable rod (411) due to the fact that the inserting pin (42)
20 penetrated into a matching hole (61) in the glove holder (6) and locked it to the movable rod. At this stage the glove-lifting-and-positioning device (4) lifts the glove upward and forwards and presents the glove to the glove-opening device.

Some explanations about the gloves: The gloving apparatus (1) may include the replaceable glove cartridge (7) that includes several gloves (100). Each glove (100) is attached to a glove holder (6). The glove holder may be made of a flexible plastic that include several holding rods (62) that each of them is
5 ended with a holding clip (63) to which the circumferential part (104) of the opening (103) of the glove (100) is attached and a matching hole (61) that match to the inserting pin (42) of the glove-lifting-and-positioning device (4). In this way, the inserting pin (42) is inserted into the matching hole (61), lock the glove holder (6) to it and take the glove holder with the glove to the glove-
10 opening device (3). In order to center the inserting pin (42) directly to the matching hole (61) the movable rod (411) includes the adjustment piece (48) with the adjustment rods (49) that centering the inserting pin (42) straight to the matching hole (61) by embracing and surrounding the glove holder (6).

15 When the opening of the glove is inserted over the grasping pins (36) while they are in a closed position and these grasping pins (36) move to an open position then the glove is disconnected from the glove holder (6). At this stage, the glove-lifting-and-positioning device (4) is move back to bring another glove on demand. The glove-lifting-and-positioning device (4) get rid from the
20 glove holder (6), which is now without a glove, by pulling back the movable rod (411) so that the glove holder (6) clashes with the releasing rods (47) that are connected to the base (43) causing the glove holder (6) to exit the inserting pin (42) and to fall down preferably to a trash can.

The drawings illustrate the glove-opening device (3) with a six-sided frame, although the invention may be implemented with a frame with more or less sides. The outer end (33) of each spreading rod (32) is attached to the polygonal circumferential frame (31) via an axial joint (34). The inner end (35) of each spreading rod (32) is equipped with a grasping pin (36). The glove-opening device (3) also includes a mechanism that changes the joint angle between the spreading rods (32) and the polygonal circumferential frame (31). The gloving apparatus (1) may include an adjuster (8) that covers the hole inside the polygonal circumferential frame (31) and that is designed to be closed when the apparatus (1) is not in used, and vice versa.

Method of operation of the gloving apparatus (1): The glove-lifting-and-positioning device (4) descends and picks up a glove (100) as described above. The glove-lifting-and-positioning device (4) then brings the opening of the glove over the grasping pins (36). Then the glove-opening device (3) goes from closed to open position, in other words, to a position in which the glove opening is stretched into the shape of the polygonal circumferential frame, and the glove, in fact, is sealing the opening of the glove-opening device. The air pump (5) then creates sub-pressure within the casing (2), causing the glove to inflate. The user can now insert his or her hand into the inflated glove which, as a result of its slight inward motion, is released from the grasping pins, remaining on the user's hand. A sensor that identifies full insertion of the hand into the glove or a pressing or touching switch may control the release of the

glove from the grasping pins. In addition, the gloving apparatus is equipped with several activators that activate each of the above mentioned apparatus parts, as well as sensors that enable it to operate automatically.

- 5 Figure 1 presents a glove (100) with its opening (103) and the circumferential part (104) of the opening (103). Figures 2 and 3 depict the gloving apparatus (1) that includes the casing (2), the glove-opening device (3), the glove-lifting-and-positioning device (4), the air pump (5), and the replaceable glove cartridge (7). Figures 4 and 5 depict the glove-lifting-and-positioning device
- 10 (4) when the moveable rod (411) is facing downwards on the way to collect a glove from the replaceable cartridge (7). Figures 6 and 7 depict the glove-lifting-and-positioning device (4) when the inserting pin is inserted in the matching hole of the glove holder. Figures 8 and 9 depict the glove-lifting-and-positioning device (4) in diagonal state and that holds a glove on the way to
- 15 wear the glove on the glove-opening device (3). Figures 10 and 11 depict the glove-lifting-and-positioning device (4) in horizontal state and that holds a glove and wears the glove on the glove-opening device (3). Figures 12 and 13 depict the glove-lifting-and-positioning device (4) that wears the glove on the glove-opening device (3).
- 20 Figure 14 depicts the glove (100) when inserted on the grasping pins and inflated and ready to receive the user's hand. Figure 15 depicts the glove-lifting-and-positioning device (4) when the movable rod (411) is in "up" position and Figure 16 depicts the glove-lifting-and-positioning device (4)

when the movable rod (411) is in “down” position. Figures 17 and 18 depict the glove-lifting-and-positioning device (4) in diagonal position. Figure 19 depicts the adjustment piece (48) in two states relative to the moveable rod (411). Figures 20 and 21 depict the inserting pin (42) when being inserted into the glove holder (6). Figures 22 and 23 depict the inserting pin (42) before and after being inserted into the glove holder (6). Figures 24A – 24E depict several states of the moveable rod (411) and the glove holder (6). Figure 25 depicts the glove holder (6). Figure 26 depicts the glove holder (6) with a glove (100).

Figures 27 and 28 depict the glove-opening device (3) wherein the grasping pins (36) are concentrated in the center of the polygonal circumferential frame (31), i.e. in a closed position. Figure 29 depicts the glove-opening device (3) in partially opened position, i.e. the spreading rods (32) are rotated slightly so that their inner ends (35) are closer to the sides of the polygonal circumferential frame (31). Figure 30 depicts the glove-opening device (3) in an open position, i.e. when the spreading rods (32) are parallel and adjacent to the sides of the polygonal circumferential frame (31) and the grasping pins (36) are positioned in the angles between said sides of the polygonal circumferential frame. Figures 31 – 33 depict the adjuster (8) in several states.

The replaceable cartridge (7) and the glove holder (6) of the gloving apparatus (1) are described in the drawings and explained above, and hereinafter we will describe them with more details. It is preferably that the gloving apparatus (1) will include a replaceable cartridge (7) of gloves (100) and it is even more

preferably that the gloving apparatus will includes several replaceable cartridges (7), as explained hereinafter.

The gloving apparatus (1) includes a cartridge mechanism (90) that includes a
5 cartridge housing (91), a follower (92) and a spring (93). The follower (92)
may include a pushing rod (921) that equipped with a pushing plate (922) in its
upper end and with a pulling plate (923) in its bottom end, as depicted for
example in Figure 34. One end of the spring (93), preferably a type of constant-
force spring, is attached to the bottom of the cartridge housing (91) and the
10 other end of the spring is attached to the pulling plate (923), in such a way that
the spring exerts pressure on the follower (92) to move upward through the
cartridge housing and push up the holders (6) with the gloves (100), resembling
the manner as a rifle cartridge / magazine works.

15 The cartridge mechanism (90) may include several cartridge housings (91) and
with relevant parts such as the followers and the springs, and an activator that
rotates the cartridge mechanism for aligning the relevant replaceable cartridge
with the inserting pin (42). Figures 2 and 3 depict the gloving apparatus with
the cartridge mechanism (90) that is designed to contain several replaceable
20 cartridges (7).

The user can insert into each cartridge housing (91) a replaceable cartridge (7)
through the upper opening of the cartridge housing and by that to push and

press down the follower (92), and then to lock the replaceable cartridge to the housing. The spring (93) which is now in a tense state activates upward power on the follower (92) as explained above. Whenever a glove holder (6) is pulled out of the cartridge (7), the follower (92) raises slightly upward, the same as a
5 rifle cartridge operation principle. When that replaceable cartridge is run out then the cartridge mechanism rotates a bit and aligns another cartridge to the inserting pin and when all the cartridges run out the user can replace them all.

The replaceable glove cartridge (7) is designed to contain several glove holders
10 (6), one on top of the other, while a glove (100) is attached to each one of them. The replaceable cartridge (7) comprises a closed peripheral wall (71) with an upper opening (72) through which the glove holders (6) can be pulled out from the replaceable cartridge and a lower opening (73) through which the follower (92) can penetrate and push upwards the glove holders (6).

15

The replaceable cartridge (7) includes at least three inner corners (74) that serve as a guide for the glove holders (6) when they are inside the cartridge. In this way, the gloves holders (6) are positioned inside the cartridge in a way that the end of each holding rod (62) is positioned in each inner corner (74), so,
20 when the glove holder includes three legs, means three holding rods then the cartridge should include at least three inner corners, and so forth.

Along two or more of the inner corners (74), or all of them, there is a stopper (75) that is deigned to stop the upward movement of the glove holders (6). The stoppers (75) may be corresponds with the end (64) of the holding rod (62). For example, the stopper (75) may comprises two horizontal protrusions (751) with a gap (752) between them that correspond with the end (64) of the holding rod (62) that comprises two horizontal pieces (641) with a vertical piece (642) between them. In this way, the two horizontal protrusions (751) of the stopper (75) prevent the two horizontal pieces (641) from moving upward while the vertical piece (642) of the glove holder (6) is positioned inside the gap (752) and by that the upper glove holder (6) in the cartridge is located properly in the place to meet the inserting pin (42). The glove holder (6) may be made of a flexible material so that when the inserting pin (42) penetrates through the matching hole (61) of the glove holder (6), locks it and pulls it up, the holding rods (62) bend and the glove holder is able to be pulled out from the cartridge. Figure 35 depicts an empty cartridge (7), Figure 4 depicts it with glove holders (6), Figure 36 is a top view of the cartridge (7) and Figure 37 is a top frame of the cartridge that includes the stoppers (75).

As explained above and will explained hereinafter the glove holder (6) comprises a base (60) and at least three holding rods (62). The base (60) comprises a matching hole (61) with several horizontal slots (611) that match with the inserting pin (42). The inserting pin (42) comprises a rounded mushroom tip (421) and a polygonal stem (422). The rounded mushroom tip

(421) enables the inserting pin (42) to easily penetrate through the matching hole (61) and to prevent it to be pulled out easily. It is possible to design the base in a way that the area (612) around the matching hole and between the will inclines towards the hole to allow easier penetration of the inserting pin and to prevent the pin to exit easily from the hole. The polygonal stem (422) is positions inside the matching hole (61) while surrounding by the ends of the horizontal slots (611) that prevents a rotary movement of the glove holder (6) around the inserting pin (42). The end (64) of each one of the at least three holding rods (62) comprises a holding clip (63) to which the circumferential part (104) of the opening (103) of the glove (100) is attached, and two horizontal pieces (641) with a vertical piece (642) between them. When the glove holders (6) are positioned inside the cartridge, one on top of the other, then the vertical piece (642) of each glove holder is situated between the two horizontal pieces (641) of the glove holder above it, and by that the glove holders are arranged in a stable and orderly manner one on top of the other inside the cartridge.

Claims

What is claimed is:

1. A gloving apparatus that comprises a casing, a glove-opening device, a glove-lifting-and-positioning device, and an air pump;

wherein the glove-lifting-and-positioning device includes a base with a linear actuator that is equipped with a moveable rod, a rotating actuator that is designed to rotate the glove-lifting-and-positioning device, and a lifting arm with a lifting actuator that are designed to lift up and lower down the glove-lifting-and-positioning device;

wherein said base includes a releasing rods;

wherein the glove-opening device comprises a polygonal circumferential frame and several spreading rods; wherein an outer end of each spreading rod is attached to the polygonal circumferential frame via an axial joint; and wherein an inner end of each spreading rod is equipped with a grasping pin;

wherein the glove-lifting-and-positioning device is designed to move up and down and back and forth and to insert the movable rod into a matching hole at a glove holder to which a glove is attached and to lift the glove holder with the glove and insert an opening of the glove over said grasping pins;

wherein the glove-opening device is designed to move from closed position when the spreading rods are perpendicular to sides of said polygonal circumferential frame and grasping pins are concentrated in the center of the polygonal circumferential frame to open position when said grasping pins are de-concentrated, causing the glove opening to stretch open and assume the shape of the polygonal circumferential frame;

wherein the air pump is designed to create sub-pressure in the casing, causing the glove to expand to a size and shape suitable for a hand to be inserted into the inflated glove.

2. The gloving apparatus of claim 1 that further includes said glove holder wherein the glove holder is connected to said movable rod; wherein the glove holder comprises a base that includes said matching hole that corresponds with the movable rod, and at least three holding rods, wherein an end of each of the holding rods includes a holding clip to which a circumferential part of said opening of said glove is attached.

3. The gloving apparatus of claim 1 that further includes a replaceable glove cartridge that contains glove holders with gloves that comprises a closed peripheral wall and at least two stoppers;

wherein said closed peripheral wall includes at least three inner corners that are designed to serve as a guide for the glove holders, an upper opening through which the glove holders is designed to be pulled out, and a lower opening through which a follower is designed to penetrate and pushes upwards the glove holders;

wherein the stoppers are situated along at least two of the at least three inner corners and wherein said stoppers are designed to stop an upward movement of the glove holders when they are pushed upwardly by the follower; and

wherein each of said stopper corresponds with an end of a respective one of the holding rods of each one of said glove holders.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

7/36




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG 13




FIG 14




FIG 15




FIG 16




FIG 17




FIG 18

19/36




FIG 19

20/36




FIG 20

21/36




FIG 21




FIG 22




FIG 23




FIG 24A




FIG 24B




FIG 24C




FIG 24D




FIG 24E




FIG 25

25/36




FIG 26




FIG 27

27/36




FIG 28

28/36




FIG 29

29/36




FIG 30




FIG 31

31/36




FIG 32




FIG 33




FIG 34

34/36




FIG 35

35/36




FIG 36

36/36




FIG 37

