



US010907812B1

(12) **United States Patent**  
**Webb et al.**

(10) **Patent No.:** **US 10,907,812 B1**  
(45) **Date of Patent:** **\*Feb. 2, 2021**

- (54) **ROTATING LIGHT TOWER ASSEMBLY**
- (71) Applicant: **BOSS LTG, INC.**, Baton Rouge, LA (US)
- (72) Inventors: **George Webb**, Baton Rouge, LA (US); **Todd Chambers**, Baton Rouge, LA (US)
- (73) Assignee: **BOSS LTG, INC.**, Baton Rouge, LA (US)
- (\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.  
  
This patent is subject to a terminal disclaimer.
- (21) Appl. No.: **16/552,082**
- (22) Filed: **Aug. 27, 2019**

**Related U.S. Application Data**

- (63) Continuation-in-part of application No. 15/481,222, filed on Apr. 6, 2017, now Pat. No. 10,393,324.
- (60) Provisional application No. 62/320,057, filed on Apr. 8, 2016.

- (51) **Int. Cl.**  
**F21V 21/26** (2006.01)  
**F21V 25/00** (2006.01)  
**F21V 21/22** (2006.01)  
**F21V 21/15** (2006.01)

- (52) **U.S. Cl.**  
CPC ..... **F21V 21/26** (2013.01); **F21V 21/15** (2013.01); **F21V 21/22** (2013.01); **F21V 25/00** (2013.01)

- (58) **Field of Classification Search**  
CPC ..... F21V 21/26; F21V 21/15; F21V 21/22; F21V 25/00  
See application file for complete search history.

(56) **References Cited**  
**U.S. PATENT DOCUMENTS**

3,874,683	A *	4/1975	Lawson	.....	B62B 13/18
					280/10
9,437,109	B1 *	9/2016	Stafford	.....	F21L 4/02
10,393,324	B1 *	8/2019	Chambers	.....	F21L 4/08
2001/0030683	A1 *	10/2001	Howell	.....	A61B 90/50
					348/61
2010/0232148	A1 *	9/2010	Sharpley	.....	B62D 63/08
					362/183
2016/0258601	A1 *	9/2016	Gowanlock	.....	F21V 21/22
2016/0309566	A1 *	10/2016	Fletcher	.....	B62D 49/08

\* cited by examiner


*Primary Examiner* — Mary Ellen Bowman

(74) *Attorney, Agent, or Firm* — Roy Kiesel Ford Doody & North, APLC

(57) **ABSTRACT**

A light tower assembly configured to rotate a light section from a first to a second position. In various embodiments, the light tower assembly comprises (a) a primary boom extending vertically from a base, (b) a light array boom supporting a light section on a frame rotatively mounted to the primary boom wherein the light array boom rotates around an axis of rotation, (c) a mounting assembly rotatively mounting the light array boom to the primary boom, and (d) a linear actuator assembly connected to the primary boom and the light array boom being configured to rotate the light array boom in one direction when the linear actuator extends and configured to rotate the light array boom in an opposite direction when the linear actuator assembly retracts.

**17 Claims, 11 Drawing Sheets**







Fig 1

Fig 2






Fig 3




Fig 4

Fig 5




Fig 6





Fig 7






Fig 8

Fig 9




Fig 10





Fig 11






Fig 13




Fig 14





Fig 15






Fig 17




Fig 18





Fig 19



1

**ROTATING LIGHT TOWER ASSEMBLY****CROSS REFERENCE TO RELATED APPLICATION**

This application claims the benefit of U.S. patent application Ser. No. 15/481,222, filed Apr. 6, 2017 issuing as patent Ser. No. 10/393,324 on Aug. 27, 2019, which in turn claims the benefit of U.S. Provisional Application No. 62/320,057, filed Apr. 8, 2016, each of which are hereby incorporated by reference in its entirety.

**BACKGROUND OF THE INVENTION****Field of Invention**

Various embodiments relate to light towers or mobile lighting apparatus supporting a light array for the illumination of focal or desired locations

**Prior Art**

Light towers, mobile or stationary, used to support light assemblies for illumination purposes are well known in the prior art, but generally include a base, a boom, and a light section. Mobile light towers are deployed proximate the location to be illuminated and positioned to direct the light assembly towards the location desired to be illuminated. Safety concerns require that some mobile light towers be lowered to a mobile or storage configuration before the base is moved or repositioned. Thus, some mobile light towers must be lowered to a mobile configuration, the base repositioned, and the light tower subsequently erected again over the new location. However, it may be desired to illuminate a second location relatively adjacent to the first without having to lower, move and erect the mobile light tower. Regarding stationary light towers, similar desires exists to illuminate a second location relatively adjacent to the first. Methods exist for rotating the light section. However, these are often structurally limiting. Therefore, there is a need in the art to develop a method and apparatus to rotate a light array without repositioning the base or rotating the light tower. Further, there is a need in the art to apply such a method and apparatus to preexisting light towers.

**SUMMARY OF THE INVENTION**

The present disclosure pertains to a light tower assembly configured to rotate a light section from a first position to a second position. In various embodiments, the light tower assembly includes (a) a primary boom extending vertically from a base; (b) a light array boom supporting a light section on a frame rotatively mounted to the primary boom wherein the light array boom rotates around an axis of rotation; (c) a mounting assembly rotatively mounting the light array boom to the primary boom; and (d) a linear actuator assembly connected to the primary boom and the light array boom being configured to rotate the light array boom in one direction when the linear actuator extends and configured to rotate the light array boom in an opposite direction when the linear actuator assembly retracts. In various embodiments, the light tower assembly further comprises and (e) a means of producing power and transferring power to operate the light tower assembly.

**BRIEF DESCRIPTION OF THE DRAWINGS**

FIG. 1 is a view of the prior art showing a light section mounted to a primary boom, which is extending vertically from a base.

2

FIG. 2 a view of one of various embodiments of the light tower assembly of the claimed invention showing the light section, with the plurality of lights removed to illustrate the parts, rotatively mounted to the primary boom via the light array boom.

FIG. 3 is an exploded view of the light tower assembly of FIG. 2, illustrating the mounting assembly.

FIG. 4 is an exploded view of the linear actuator assembly of FIG. 2.

FIG. 5 is a view of the linear actuator assembly of FIG. 4 in a neutral configuration.

FIG. 6 is a view of the linear actuator assembly of FIG. 4 in an extended configuration.

FIG. 7 is a view of the linear actuator assembly of FIG. 4 in a retracted configuration.

FIG. 8 is an exploded view of another embodiment of the linear actuator assembly.

FIG. 9 is a view the linear actuator assembly of FIG. 8 in a neutral configuration.

FIG. 10 is a view of the linear actuator assembly of FIG. 8 in an extended configuration.

FIG. 11 is a view of the linear actuator assembly of FIG. 8 in a retracted configuration.

FIG. 12 is an exploded view of another embodiment of the linear actuator assembly.

FIG. 13 is a view of the linear actuator assembly of FIG. 12 in a neutral configuration.

FIG. 14 is a view of the linear actuator assembly of FIG. 12 in an extended configuration.

FIG. 15 is a view of the linear actuator assembly of FIG. 12 in a retracted configuration.

FIG. 16 is an exploded view of another embodiment of the linear actuator assembly.

FIG. 17 is a view of the linear actuator assembly of FIG. 16 in a neutral configuration.

FIG. 18 is a view of the linear actuator assembly of FIG. 16 in an extended configuration.

FIG. 19 is a view of the linear actuator assembly of FIG. 16 in a retracted configuration.

**DETAILED DESCRIPTION OF THE DRAWINGS**

FIG. 1 is a view of a prior art light tower assembly 1. The primary boom 10 is extending substantially vertically from a base 5. A light section 30 having a fixture 31 and a plurality of lights 32 is mounted to the primary boom 10. As disclosed in U.S. patent Ser. No. 10/393,324, which is hereinafter incorporated by reference, light tower assembly may further include, but not necessarily shown in FIG. 1, (i) a tower post pivotally mounting the primary boom 10 to the base 5, (ii) a pivot controller affixed to the base 5 and operatively attached to the primary boom 10, the pivot controller when activated causing the primary boom 10 to be raised to a vertical position, (iii) a pivot winch or hydraulic pivot cylinder operatively responsive to the pivot controller to pivot the primary boom 10, (iv) a safety means to control the movement of the primary boom 10 as it is pivoted into a vertical position, (v) an extension boom 11 extendably and retractably connecting the primary boom 10 to the base 5, (vi) a telescoping controller affixed to the base 5 and operatively attached to the extension boom 11, the telescoping controller when activated causes the extension boom 11 to extend from the primary boom 10 relative to the base 5, (vii) a telescoping winch or telescoping hydraulic cylinder operatively responsive to the telescoping controller to extend the extension boom 11, and (viii) a power assembly 1000 operatively connected to the plurality of lights 32, the

3

power assembly including a power supply **1001**, an electrical connection box **1002**, and a power cable **1003** operatively connected to the plurality of lights **32**, the pivot winch or hydraulic pivot cylinder, and the telescoping winch or telescoping hydraulic cylinder.

FIG. 2 is a view of one of various embodiments of the light tower assembly of the claimed invention. The primary boom **10** is extending substantially vertically from a base **5**, not shown. A light array boom **100** having a frame **110** is rotatively mounted to the primary boom **10** wherein the light array boom **100** rotates around an axis of rotation **101**. A mounting assembly **20** rotatively mounts the light array boom **100** to the primary boom **10**. A light section **30** is removably connected to the light array boom **100**. For purposes of clarity to illustrate the invention, the plurality of lights **32** have been removed from the figure.

A linear actuator assembly **7** is connected to the primary boom **10** and operatively connected to the light array boom **100**. The linear actuator assembly **7** is configured to rotate the light array boom **100** in one direction when the linear actuator assembly **7** extends. The linear actuator assembly **7** is also configured to rotate the light array boom **100** in an opposite direction when the linear actuator assembly **7** retracts. In addition to being operatively connected to the plurality of lights **32**, power assembly **1000** is further operatively connected to the linear actuator assembly. However, for purposes of clarity to illustrate the invention, power assembly **1000** and more specifically power cable **1003** has been removed from the figure.

FIG. 3 is an exploded view of the light tower assembly **1** show in FIG. 2, including the primary boom **10**, the light array boom **100**, the mounting assembly **20**, and the linear actuator assembly **7**. In various embodiments, the light array boom **100** is rotatively mounted to the primary boom **10** wherein the light array boom **100** rotates around the axis of rotation **101**. In various embodiments, the axis of rotation **101** is the geometric longitudinal axis of the frame **110** of the light array boom **100**. In various embodiments, the light array boom **100** further comprises a longitudinal axle **120** connected to the frame **110** that is collinear with the axis of rotation **101** of the frame **110**.

In various embodiments, the mounting assembly **20** rotatively mounts the light array boom **100** to the primary boom **10**. In various embodiments, the mounting assembly **20** comprises a first mounting plate **21** removably connected to the primary boom **10** at a first end of the first mounting plate **21**. In various embodiments, the mounting assembly **20** comprises a second mounting plate **26** removably connected to the primary boom **10** at a first end of the second mounting plate **26**.

In various embodiments, the light array boom **100** is rotatively mounted to rotate around an axis of rotation **101**, the weight of the light array boom **100** resting on a second end of the first mounting plate **21**. In various embodiments, a bore passes through the second end of the first mounting plate **21**. In various embodiments, the mounting assembly **20** further comprises a first flange bushing **22** having an axle bore passing through a top and a bottom, the bottom of the first flange bushing **22** positioned concentric with the bore of the first mounting plate **21**. In various embodiments, the first mounting assembly **20** further comprises a thrust washer **24**, also having an axle bore, and being positioned concentric with the first flange bushing **22** and concentric with the bore of the first mounting plate **22** wherein the first flange bushing **22** is between thrust washer **24** and the first mounting plate **21**. In various embodiments, the light array boom **100** is rotatively mounted to rotate around an axis of rotation **101**,

4

the weight of the light array boom **100** being supported by the thrust washer **24**. In various embodiments, the frame **110** of the light array boom **100** rotatively mounted to rotate around an axis of rotation **101**. In various embodiments, thrust washer is a thrust bearing.

In various embodiments, the longitudinal axle **120** passes through the axle bore of the thrust washer **24**. In various embodiments, the longitudinal axle **120** passes through the axle bore of the first flange bushing **22**. In various embodiments, the longitudinal axle **120** passes through the bore of the first mounting plate **21**. In various embodiments, a first shaft collar **23** secures frame **110** to the first mounting plate **21**.

In various embodiments, the light array boom **100** is rotatively supported to rotate around an axis of rotation **101**, the weight of the light array boom **100** stabilized by the second end of the second mounting plate **26**. In various embodiments, a bore passes through the second end of the second mounting plate **26**. In various embodiments, the mounting assembly **20** further comprises a second flange bushing **27** having an axle bore passing through a top and a bottom, the bottom of the second flange bushing **27** positioned within the bore of the second mounting plate **26**.

In various embodiments, the longitudinal axle **120** passes through the bore of the second mounting plate **26**. In various embodiments, the longitudinal axle **120** passes through the axle bore of the second flange bushing **27**. In various embodiments, a second shaft collar **28** secures frame **110** to the second flange bushing **27**.

It should be understood from the prior art that several methods exist to connect a primary boom **10** to a light section **30**. In various embodiments, primary boom **10** further comprises a first and second mounting bracket **12**, **13** to removably connect the first ends of the first and second mounting plates **21**, **26**. In various embodiments, light array boom **100** further comprises first and second mounting brackets **112**, **113** to removably connect the light section **30** to the light array boom **100**. In various embodiments, brackets **12**, **13** and brackets **112**, **113** are similar such that the same light section **30** may be removably connected to both the primary boom **10** and the light array boom **100**. In various embodiments, brackets **12**, **13** and brackets **112**, **113** are not similar such that the light section **30** may be removably connected to the light array boom **100**.

The linear actuator assembly **7** controllably transfers linear motion into rotational motion. In various embodiments, a power assembly **1000** is operatively connected to the linear actuator assembly **7** to power the extension and retraction of the linear actuator assembly **7**. In various embodiments of the invention, linear actuator assembly **7** has a predetermined operating range of degrees through which it may rotate, or a range of rotation.

It should be understood that the range of rotation is limited by at least two factors. The first limit to the range of rotation is the configuration of a linear actuator assembly to rotate. Various linear actuator assemblies **7**, **1007**, **2007**, **3007** can achieve various ranges of rotation. For example, the linear actuator assembly **7** may bind if configured to go beyond a certain threshold. However, the linear actuator assembly **3007** may not be limited by such a threshold. The second limit to the range of rotation is the configuration of the light array boom **100** and light section **30** with respect to the primary boom **10**. In a various embodiments, light array boom **100** is rotatively mounted to the side of the primary boom **10**, wherein dimensions of light array boom **100** or light section **30** may prevent the light array boom **100** or the light section **30** from freely rotating 360 degrees. In a

various embodiments, the light array boom **100** is rotatively mounted onto the top of the primary boom **10**, wherein dimension of the light array boom or the light assembly does not prevent the light array boom from freely rotating 360 degrees.

In various embodiments, the linear actuator assembly **7**, **1007**, **2007**, **3007** has a neutral configuration wherein the light array boom **100** may rotate in an equal number of degrees in either direction. In various embodiments, the linear actuator assembly **7**, **1007**, **2007**, **3007** has an extended configuration wherein the light array boom **100** has rotated to a maximum positive degree of rotation from a neutral configuration. In various embodiments, the linear actuator assembly **7**, **1007**, **2007**, **3007** has a retracted configuration wherein the light array boom **100** has rotated to a maximum negative degree of rotation from a neutral configuration. In various embodiments, linear actuator assembly **7**, **1007**, **2007**, **3007** has a plurality of configurations between the extended and retracted configuration. In various embodiments, light array boom **100** may be rotated to a plurality of degrees between a maximum positive degree of rotation to a maximum negative degree of rotation.

The linear actuator assembly **7** controllably transfers linear motion into rotational motion. Various methods of transferring linear motion into rotational motion are well known in the prior art. Various embodiments are disclosed to transfer linear motion into rotational motion. It should be understood that these disclosures are not exhaustive, but representative of art in transferring linear motion to rotational motion. Further, embodiments disclosed present a configuration wherein the linear actuator assembly **7**, **1007**, **2007**, **3007** is located at the top of the primary boom **10** when in an operating position. It should be understood that the linear actuator assembly **7**, **1007**, **2007**, **3007** can be located at any stationary position, stationary meaning with respect to the rotational motion of the light array boom **100**. Further, embodiments disclosed present a configuration wherein the linear actuator assembly **30** acts on the top of the light array boom **100**. It should be understood that the linear actuator assembly **30** can act on any portion of the light array boom **100**. Further, embodiments disclosed position the light array boom **100** adjacent and parallel to the primary boom **10**. It should be understood that the light array boom **100** can be positioned adjacent but not parallel to the primary boom **10**. It should also be understood that the light array boom can be positioned adjacent and collinear to the primary boom **10**.

FIG. **4** is an exploded view of one embodiment of the linear actuator assembly **7**. FIG. **5** is a view of linear actuator assembly **7** in a neutral configuration. The linear actuator assembly **7** comprises a linear actuator **200** having a first end **210** connected **250** to the primary boom **10** (not shown) via stand **500** and having a second end **220** extendable and retractable with respect to the first end **210** of the linear actuator **200** and operatively connected to the light array boom **100**. The first end **210** of the linear actuator **200** may be rotatively connected **250** to the primary boom **10** to allow rotation of the first end **210** of the linear actuator **200** to enable linear to rotational motion. The linear actuator assembly **7** further comprises a slotted link **400** operatively connecting the linear actuator **200** to the light array boom **100**. The slotted link has an anchor point **450** rotatively connected to the primary boom **10** (not shown) via stand **500**. The slotted link also has a swivel point **420** rotatively connected to the second end **220** of the linear actuator **200**. The slotted link **400** also has a slotted section **430** slidably and operatively connected to the light array boom **100**. The linear actuator assembly **7** of further comprises a cam **300**

operatively connecting the longitudinal axle **120** (not shown) of the light array boom **100** to the slotted section **430** of the slotted link **400**.

FIG. **6** is a view of the linear actuator assembly **7** in an extended configuration. When linear actuator **200** extends, slotted link **400** rotates around the swivel point **420** and anchor point **450** in a first direction causing the slotted link **400** to rotate cam **300** and light array boom **100** in the first direction. The first end **210** of the linear actuator **200** rotates relative to the primary boom **10** thereby preventing binding on the slotted link **400** during extension.

FIG. **7** is a view of the linear actuator assembly **7** in a retracted configuration. When linear actuator **200** retracts, slotted link **400** rotates around the swivel point **420** and the anchor point **450** in a second direction causing the slotted link **400** to rotate cam **300** and light array boom **100** in the second direction. The first end **210** of the linear actuator **200** rotates relative to the primary boom **10** thereby preventing binding on the slotted link **400** during retraction.

FIG. **8** is an exploded view of one embodiment of the linear actuator assembly **1007**. FIG. **9** is a view of linear actuator assembly **1007** in a neutral configuration. The linear actuator assembly **1007** comprises a linear actuator **1200** having a first end **1210** connected to the primary boom **10** (not shown) via stand **1500** and having a second end **1220** extendable and retractable with respect to the first end **1210** of the linear actuator **1200** and operatively connected to the light array boom **100**. The linear actuator assembly **1007** further comprises a slotted **1400** link operatively connecting the linear actuator **1200** to the light array boom **100**. The slotted link **1400** has an anchor point **1450** rotatively connected to the primary boom **10** (not shown) via stand **1500**. The slotted link **1400** also has at least one slotted section **1420**, **1430** slidably connected to the second end **1220** of the linear actuator **1200** and slidably and operatively connected to the light array boom **100**. The linear actuator assembly **1007** of further comprises a cam **1300** operatively connecting the longitudinal axle **120** (not shown) of the light array boom **100** to the at least one slotted section **1420**, **1430** of the slotted link **1400**.

FIG. **10** is a view of the linear actuator assembly **1007** in an extended configuration. When linear actuator **1200** extends, slotted link **1400** slides relative to the second end **1220** of the linear actuator **1200** and rotates around the anchor point **1450** and the second end **1220** of the linear actuator **1200** in a first direction causing the slotted link **1400** to rotate cam **1300** and light array boom **100** in the first direction.

FIG. **11** is a view of the linear actuator assembly **1007** of FIG. **8** in a retracted configuration. When linear actuator **1200** retracts, slotted link **1400** slides relative to the second end **1220** of the linear actuator **1200** and rotates around the anchor point **1450** and the second end **1220** of the linear actuator **1200** in a second direction causing the slotted link **1400** to rotate cam **1300** and light array boom **100** in the second direction.

FIG. **12** is an exploded view of one embodiment of the linear actuator assembly **2007**. FIG. **13** is a view of the linear actuator assembly **2007** in a neutral configuration. The linear actuator assembly **2007** comprises a linear actuator **2200** having a first end **2210** connected to the primary boom **10** (not shown) via stand **2500** and having a second end **2220** extendable and retractable with respect to the first end **2210** of the linear actuator **2200** and operatively connected to the light array boom **100**. The linear actuator assembly **2007** further comprises a slotted link **2400** operatively connecting the linear actuator **2200** to the light array boom **100**. The

slotted link has a swivel point **2420** rotatively connected to the second end **2220** of the linear actuator **2200**. The slotted link **2400** also has at least one slotted section **2430**, **2450** slidably connected to the primary boom **10** (not shown) via stand **2500** and slidably and operatively connected to the light array boom **100**. The linear actuator assembly **2007** further comprises a cam **2300** operatively connecting the longitudinal axle **120** (not shown) of the light array boom **100** to the at least one slotted section **2430**, **2450** of the slotted link **2400**.

FIG. **14** is a view of the linear actuator assembly **2007** in an extended configuration. When linear actuator **2200** extends, slotted link **2400** slides relative to the primary boom **10** and rotates relative to the swivel point **2420** and the primary boom **10** in a first direction causing slotted link **2400** to rotate cam **2300** and light array boom **100** in the first direction.

FIG. **15** is a view of the linear actuator assembly **2007** in a retracted configuration. When linear actuator **2200** retracts, slotted link **2400** slides relative to the primary boom **10** and rotates relative to the swivel point **2420** and the primary boom **10** in a second direction causing slotted link **2400** to rotate cam **2300** and light array boom **100** in the second direction.

FIG. **16** is an exploded view of one embodiment of the linear actuator assembly **3007**. FIG. **17** is a view of the linear actuator assembly **3007** in a neutral configuration. The linear actuator assembly **3007** comprises a linear actuator **3200** having a first end **3210** connected to the primary boom **10** (not shown) via stand **1500** and having a second end **3220** extendable and retractable on the first end **3210** of the linear actuator **3200** operatively connected to the light array boom **100**. The second end **3220** of the linear actuator assembly **3007** further comprises a rack **3230** operatively connected to the light array boom **100**. The linear actuator assembly **3007** further comprises a pinion **3300** operatively connecting the rack to the longitudinal axle **120** (not shown) of the light array boom **100**.

FIG. **14** is a view of the linear actuator assembly **3007** in an extended configuration. When linear actuator **3200** extends, the rack **3230** rotates the pinion **3300** and the light array boom **100** in a first direction.

FIG. **15** is a view of the linear actuator assembly **3007** in a retracted configuration. When linear actuator **3200** retracts, the rack **3230** rotates the pinion **3300** and the light array boom **100** in a second direction.

In various embodiments, the linear actuator assembly **1007**, **2007**, **3007**, **4007** includes a stand **500**, **1500**, **2500**, **3500**. In various embodiments, stand **500**, **1500**, **2500**, **3500** connects **520**, **1520**, **2520**, **3520** the first end of the linear actuator to the primary boom **10**. In various embodiments, stand **500**, **1500** rotatively connects **540**, **1540** the anchor point **450**, **1450** of the slotted link **400**, **1400** to the primary boom **10**. In various embodiments, stand **2500** slidably connects the slotted section **2450** of the slotted link **2400** to the primary boom **10**. In various embodiments, longitudinal axle **120** passes through stand **500**, **1500**, **2500**, **3500**.

We claim:

1. A light tower assembly including:

- (a) a primary boom pivotally mounted to a base;
- (b) a light array rotatively mounted to said primary boom opposite the base wherein said light array rotates around an axis of rotation;
- (c) a mounting assembly rotatively mounting said light array to said primary boom;
- (d) a linear actuator assembly mounted to said primary boom and operatively connected to said light array to

rotate said light array in one direction when said linear actuator assembly extends and configured to rotate said light array in an opposite direction when said linear actuator assembly retracts; and

- (e) a power assembly operatively connected to the linear actuator assembly to power said extension and retraction of said linear actuator assembly.

2. The apparatus of claim **1** wherein said mounting assembly comprises a first mounting plate connected to said primary boom, and a thrust washer positioned on said first mounting plate to rotatively support said light array around said axis of rotation.

3. The apparatus of claim **2** wherein said mounting assembly further comprising a second mounting plate connected to said primary boom and configured to stabilize said light array with respect to said primary boom.

4. The apparatus of claim **2** wherein said light array further comprises a longitudinal axle connected to the frame that is collinear with said axis of rotation of the light array, and extends through said thrust washer of said first mounting assembly.

5. The apparatus of claim **4** wherein said mounting assembly further comprises a flange bushing passing through a bore in said first mounting plate, said flange bushing configured to rotatively support the thrust washer and to stabilize the longitudinal axle with respect to the primary boom.

6. The apparatus of claim **5** wherein said mounting assembly further comprise a shaft collar configured to prevent said longitudinal axle from sliding relative to the first mounting plate.

7. The apparatus of claim **1** wherein said linear actuator assembly further comprises a stand connecting said linear actuator assembly to said primary boom.

8. The apparatus of claim **1** wherein said linear actuator assembly comprises a linear actuator having a first end connected to said primary boom, and a second end extendable and retractable with respect to said first end of said linear actuator, and operatively connected to said light array; a slotted link operatively connecting said linear actuator to the light array and having an anchor point rotatively connected to said primary boom, a swivel point rotatively connected to said second end of said linear actuator, and a slotted section slidably and operatively connected to said light array; and a cam operatively connecting said light array to said slotted link; wherein when said linear actuator extends, said slotted link rotates around said swivel point and anchor point in a first direction causing said slotted link to rotate said cam and said light array in said first direction; and wherein when said linear actuator retracts, said slotted link rotates around said anchor point in a second direction causing said slotted link to rotate said cam and said light array in said second direction, wherein said first end of said linear actuator rotates relative to said primary boom thereby preventing binding on said slotted link during extension and retraction.

9. The apparatus of claim **1** wherein the linear actuator assembly comprises a linear actuator having a first end connected to the primary boom, and a second end extendable and retractable on the first end of the linear actuator and operatively connected to the light array; a slotted link operatively connecting the linear actuator to the light array and having an anchor point rotatively connected to the primary boom, and at least one slotted section slidably connected to the second end of the linear actuator, and slidably and operatively connected to the light array; and a cam operatively connecting the light array to the slotted link;

wherein when linear actuator extends, slotted link slides relative to the second end of the linear actuator and rotates around the anchor point in a first direction, causing slotted link to rotate cam and light array in the first direction; and wherein when linear actuator retracts, slotted link slides 5 relative to the second end of the linear actuator and rotates around the anchor point in a second direction causing slotted link to rotate cam and light array in the second direction.

10. The apparatus of claim 1 wherein the linear actuator assembly comprises a linear actuator having a first end connected to the primary boom, and a second end extendable and retractable on the first end of the linear actuator and operatively connected to the light array; a slotted link operatively connecting the linear actuator to the light array and having a swivel point rotatively connected to the second 15 end of the linear actuator, and at least one slotted section slidably connected to the primary boom, and slidably and operatively connected to the light array; and a cam operatively connecting the light array to the slotted link; wherein when linear actuator extends, slotted link rotates relative to 20 the swivel point and slides relative to the primary boom in a first direction causing slotted link to rotate cam and light array in the first direction; and wherein when linear actuator retracts, slotted link slides and rotates relative to the anchor point connected to the primary boom in a second direction 25 causing slotted link to rotate cam and light array in the second direction.

11. The apparatus of claim 1 wherein the linear actuator assembly comprises a linear actuator having a first end connected to the primary boom, and a second end extendable 30 and retractable on the first end of the linear actuator and having a rack operatively connected to the light array; and a pinion operatively connecting the rack to the light array boom wherein when linear actuator extends, the Rack rotates the pinion and the light array in a first direction; and 35 wherein when linear actuator retracts, the rack rotates the pinion and the light array in a second direction.

12. The apparatus of claim 1 wherein said primary boom is connected to a base boom, wherein said base boom is connected to said base, and said primary boom may be 40 raised relative to said base boom.

13. The apparatus of claim 1 wherein said primary boom is pivotally connected to said base and configured to have an operating position extending vertically from said base, and a storage position substantially perpendicular to said oper- 45 ating position.

14. The apparatus of claim 1 wherein said base is a portable frame.

15. The apparatus of claim 1 further including:
- (a) a tower post pivotally mounting the primary boom to the base;
  - (b) a pivot controller affixed to the base and operatively attached to the primary boom, the pivot controller when activated causing the primary boom to be raised to a vertical position;
  - (c) a safety means to control the movement of the primary boom as it is pivoted into a vertical position;
  - (d) an extension boom extendably and retractably connecting the primary boom to the base; and
  - (e) a telescoping controller affixed to the base and operatively attached to the extension boom, the telescoping controller when activated causes the extension boom to extend the primary boom relative to the base.

16. A tower array assembly including:
- (a) a primary boom pivotally mounted to a base;
  - (b) an array mounted on to said primary boom wherein said array rotates around an axis of rotation; and
  - (c) a linear actuator mounted to said primary boom and operatively configured to rotate said array boom in one direction when said linear actuator extends and operatively configured to rotate said array boom in an opposite direction when said linear actuator retracts.

17. A light tower assembly including:
- (a) a primary boom having a first and second end, the first end secured to a base;
  - (b) a light array having an axis, wherein said light array is rotativity mounted to the second end of the primary boom;
  - (c) a mounting assembly mounting the axis to the second end of the primary boom such that the axis is substantially vertical and the light assembly rotates across a plane of rotation that is substantially horizontal;
  - (d) a linear actuator mounted to said primary boom and operatively configured to rotate said light array in one direction across the substantially horizontal plane of rotation when said linear actuator extends and operatively configured to rotate said light array in an opposite direction across the substantially horizontal plane of rotation when said linear actuator retracts; and
  - (e) a power assembly operatively connected to the linear actuator and light array to power said extension and retraction of said linear actuator and to power said light array.

\* \* \* \* \*