



US010568620B2

(12) **United States Patent**
Smith et al.

(10) **Patent No.:** **US 10,568,620 B2**
(45) **Date of Patent:** ***Feb. 25, 2020**

(54) **ADJUSTABLE COMPRESSION STAPLE AND METHOD FOR STAPLING WITH ADJUSTABLE COMPRESSION**

(52) **U.S. Cl.**
CPC *A61B 17/0644* (2013.01); *A61B 17/064* (2013.01); *F16B 15/0015* (2013.01)

(71) Applicant: **Ethicon LLC**, Guaynabo, PR (US)

(58) **Field of Classification Search**
CPC A61B 17/0644; A61B 17/064; F16B 15/0015
See application file for complete search history.

(72) Inventors: **Kevin W. Smith**, Coral Cables, FL (US); **Matthew A. Palmer**, Miami, FL (US); **Korey Kline**, Miami, FL (US); **Derek Dee Deville**, Coral Gables, FL (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,278,091 A 7/1981 Borzone
4,532,927 A 8/1985 Miksza, Jr.
(Continued)

(73) Assignee: **Ethicon LLC**, Guaynabo, PR (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 88 days.

This patent is subject to a terminal disclaimer.

FOREIGN PATENT DOCUMENTS

EP 0852128 B1 7/1998
EP 1179994 B1 2/2002
(Continued)

(21) Appl. No.: **15/614,666**

OTHER PUBLICATIONS

(22) Filed: **Jun. 6, 2017**

European Search Report of Patent App. EP 16185670 dated Nov. 23, 2016.

(65) **Prior Publication Data**

US 2017/0265862 A1 Sep. 21, 2017

(Continued)

Related U.S. Application Data

Primary Examiner — Shaun L David
Assistant Examiner — Christina C Lauer
(74) *Attorney, Agent, or Firm* — Gregory L. Mayback; Rebecca A. Tie; Ethicon LLC


(62) Division of application No. 14/164,748, filed on Jan. 27, 2014, now Pat. No. 9,700,306, which is a division of application No. 13/222,758, filed on Aug. 31, 2011, now Pat. No. 8,679,156, which is a division of application No. 11/971,998, filed on Jan. 10, 2008,
(Continued)

(57) **ABSTRACT**

A substantially U-shaped staple has a bridge, legs, and an internally disposed compression device with a bias portion having a compression surface movably disposed between the legs and a compression resistor connected to the bridge and to the compression surface and is formed to resist movement of the compression surface towards the bridge with a force.

(51) **Int. Cl.**
A61B 17/064 (2006.01)
F16B 15/00 (2006.01)

20 Claims, 19 Drawing Sheets



Related U.S. Application Data

now Pat. No. 8,679,154, said application No. 14/164,748 is a division of application No. 11/971,998, filed on Jan. 10, 2008, now Pat. No. 8,679,154.

(60) Provisional application No. 60/880,146, filed on Jan. 12, 2007.

2006/0100646	A1	5/2006	Hart et al.
2006/0155288	A1	7/2006	Little et al.
2006/0167480	A1	7/2006	Loshakove et al.
2006/0282084	A1	12/2006	Blier et al.
2006/0291981	A1	12/2006	Viola et al.
2007/0010854	A1	1/2007	Cummins
2007/0213747	A1	9/2007	Monassevitch et al.

FOREIGN PATENT DOCUMENTS

EP	1728473	A1	12/2006
JP	1967001089	B2	1/1967
JP	2006334412		12/2006
JP	2014064924		4/2014

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,887,601	A	12/1989	Richards	
5,222,961	A	6/1993	Nakao et al.	
5,393,184	A *	2/1995	Beeuwkes, III F16B 15/0015 174/159
5,715,987	A	2/1998	Kelley et al.	
6,015,417	A	1/2000	Reynolds, Jr.	
6,171,320	B1	1/2001	Monassevitch	
6,261,303	B1	7/2001	Mayenberger et al.	
6,402,765	B1	6/2002	Monassevitch et al.	
6,802,848	B2	10/2004	Anderson	
6,896,684	B2	6/2005	Monassevitch et al.	
7,108,709	B2	9/2006	Cummins	
7,794,475	B2	9/2010	Hess et al.	
8,679,154	B2 *	3/2014	Smith A61B 17/064 606/219
8,679,156	B2 *	3/2014	Smith A61B 17/064 606/219
9,700,306	B2 *	7/2017	Smith A61B 17/064
2003/0069603	A1	4/2003	Little et al.	
2005/0216056	A1	9/2005	Valdevit et al.	

OTHER PUBLICATIONS

Extended European Search Report for European Application No. 08 72 7577 dated Jan. 28, 2011.
 International Search Report of PCT/US08/50829 dated Aug. 1, 2008.
 Notice of Rejection of the Japanese Patent Office for Application No. 2009-545698 dated Oct. 4, 2011.
 Office Action of Japanese Patent App. No. 2015-192457 dated Aug. 19, 2016.
 Search Report of Chinese Patent App. No. 201510248868.8 dated Sep. 19, 2016.
 Office Action from Japanese Patent Application No. 2017-113125 dated Apr. 24, 2018.

* cited by examiner




FIG. 1
Prior Art




FIG. 2






FIG. 3




40

FIG. 4



50 ↗

FIG. 5



60

FIG. 6




FIG. 7

70




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 11A




FIG. 12






FIG. 13




140

FIG. 14



150

FIG. 15



160

FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20

ADJUSTABLE COMPRESSION STAPLE AND METHOD FOR STAPLING WITH ADJUSTABLE COMPRESSION

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application:

is a divisional of U.S. patent application Ser. No. 14/164,748, filed on Jan. 27, 2014, which:

is a divisional of U.S. patent application Ser. No. 13/222,758, filed on Aug. 31, 2011, now U.S. Pat. No. 8,679,156, issued on Mar. 25, 2014, which:

is a divisional of U.S. patent application Ser. No. 11/971,998, filed on Jan. 10, 2008, now U.S. Pat. No. 8,679,154, issued on Mar. 25, 2014, which: claims the benefit, under 35 U.S.C. § 119, of U.S. Provisional Patent Application No. 60/880,146, filed on Jan. 12, 2007; and

is a divisional of U.S. patent application Ser. No. 11/971,998, filed on Jan. 10, 2008, now U.S. Pat. No. 8,679,154, issued on Mar. 25, 2014, which:

claims the benefit, under 35 U.S.C. § 119, of U.S. Provisional Patent Application No. 60/880,146, filed on Jan. 12, 2007,

the complete disclosures of which are hereby incorporated by reference herein in their entireties.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

n/a

FIELD OF THE INVENTION

The present invention lies in the field of staple fastening, in particular, staples and instruments capable of applying a single or a plurality of staples to a material and processes therefor. More particularly, the present invention relates to a staple capable of placing a load-bearing force against the material being stapled and improvements in processes for stapling material. The device can be used, particularly, in the medical field for stapling tissue during surgical procedures, whether open, endoscopic, or laparoscopic.

BACKGROUND OF THE INVENTION

Conventional staples are, typically, U-shaped and require a staple cartridge and anvil to fasten the staple onto a material. The U-shape of the staple can be considered relatively square-cornered because of the sharp angle at which the legs extend from the bridge. On activation of a stapling device, the staple legs are advanced forward so that they penetrate a material on both sides of a slit or opening. As a staple former is advanced further, the legs of the staple bend around the anvil causing the tips of the legs to advance along an arcuate path toward each other so that the staple ultimately assumes a generally rectangular shape, thereby compressing the material that has been trapped between the staple legs, which is tissue in surgical applications. This compression of the material is the mechanism by which a closure is effected. Depending on the length of the incision or opening, a series of staples will be delivered along its length, which can ensure a blood tight closure in surgical procedures.

Because the staple has two legs that pierce the material, they are well suited for fastening two or more layers of

material together when used with the opposing anvil. Whether used in an office or during a surgical procedure, most staples **1** have similar shapes—a bridge **2** connecting two relatively parallel legs **4**, which legs are disposed approximately orthogonal to the bridge **2**, which, depending on the material of the staple, results in a square-cornered U-shape. In surgical stapling devices, it is beneficial to start the legs **4** in a slight outward orientation to assist retention of the staples within the cartridge. The staple illustrated in FIG. **1** is representative of conventional surgical staples. Such staples are compressed against an anvil to bend the tips of the legs **4** inward. For purposes sufficient in surgery, the final stapled configuration has a stapling range from a “least” acceptable orientation to a “greatest” acceptable orientation. The “least” acceptable staple range is a position where the tangent defined by the tip of each leg **4** is at a negative angle to a line parallel to the bridge **2** and touching the lower portions of both legs **4**. The “greatest” acceptable staple range is a position where the legs **4** are bent into a shape similar to the letter “B.”

The staple **1** of FIG. **1** is shown in an orientation where the tips of the legs **4** are bent slightly by an anvil on the way towards a final stapled form. (This slightly bent orientation is also present with respect to the staples illustrated hereafter.) The legs **4** of such slightly bent staples have three different portions:

a connecting portion **6** (at which the legs **4** are connected to the bridge **2**);

an intermediate portion **8** (at which the staple is bent; of course it is also possible for the connection portion **6** to be bent for various fastening purposes); and

a piercing portion **10** (for projecting through the material to be fastened; this portion, too, is bent when fastening).

Many stapling devices exist to deploy such staples. Some surgical stapling instruments are described in U.S. Pat. No. 5,465,895 to Knodel et al., and U.S. Pat. Nos. 6,644,532 and 6,250,532 to Green et al. When the staple **1** is bent for fastening, the polygon formed by the interior sides of the bent staple **1** defines an envelope or a central region **14**. The material to be fastened by the staple **1** resides in and is compressed within the central region **14** when stapling occurs. When the final staple orientation is B-shaped, there can be two regions in which the tissue is held and compressed.

One common feature associated with conventional staples is that there is no controllable way of adjusting the compressive force that is applied by the staple to the material being stapled. While items such as paper and cardboard can withstand a wide range of stapler compressive force without breaking or puncturing, living tissue, such as the tissue to be fastened in a surgical procedure, has a limited range of compressive force and cannot withstand force greater than an upper limit within that range without causing tissue damage. In fact, the range of optimal stapling force for a given surgical stapling procedure is relatively small and varies substantially with the type of tissue being stapled.

While it may be true that the distance between the bending point of the legs and the bridge (see, e.g., span **12** in FIG. **1**) can be increased to impart less force on material within the staple, this characteristic does not apply when living tissue having varying degrees of hardness, composition, and flexibility is the material being stapled. Even if the staple leg bending distance **12** is increased, if more or less or harder or softer tissue than expected is actually captured within the staple, the force applied to the captured tissue will not be controlled and will not be optimal for that tissue.

When one, two, or more layers of tissue are being stapled, it is desirable for the tissue to be at a desired compressive state so that a desirous medical change can occur, but not to be at an undesired compressive state sufficient to cause tissue necrosis. Because there is no way to precisely control the tissue that is being placed within the staple, it is not possible to ensure that the tissue is stapled within an optimal tissue compression range, referred to as an OTC range. Therefore, ruling out of tissue necrosis is difficult or not possible. Further, tissue presented within one staple may not be the same tissue that is presented within an adjacent staple or is within another staple that is fired during the same stapling procedure. Thus, while one or a few of a set of staples could actually fasten within the OTC range, it is quite possible for many other staples in the same stapling procedure to fasten outside the OTC range.

What is needed, therefore, is an improved staple and improved methods of stapling that allow automatic control of the staple compression force imparted upon the material being stapled so that compression of the material remains within a desired OTC range. While prior art surgical stapling instruments have utility, and may be successfully employed in many medical procedures, it is desirable to enhance their operation with the ability to deliver a staple that can automatically tailor the compression force delivered to the tissue without external mechanics or operations.

BRIEF SUMMARY OF THE INVENTION

It is accordingly an object of the invention to provide an adjustable compression staple and methods for stapling with adjustable compression that overcome the hereinafore-mentioned disadvantages of the heretofore-known devices and methods of this general type and that automatically tailors the compression force delivered to the tissue.

When tissue is stapled, liquid is forced out of the tissue. The OTC range of the tissue is a compression range in which liquid is removed from the tissue (i.e., desiccates the tissue) without damaging or necrosing the tissue. As the liquid from the tissue exits the tissue due to compression exerted upon the tissue by the staple, however, the compressive force that is being imposed upon the tissue naturally reduces—because less mass is between the opposing staple portions. In some instances, this reduction can allow the imparted tissue compression to exit the OTC range. Staples according to the present invention each have a self-adjusting, pre-tensioned compression device that keeps compression force on the interposed tissue within the OTC compression range even after being desiccated.

The prior art staple of FIG. 1 has a stapling range that is illustrated in FIG. 17. For purposes sufficient in surgery, the final stapled configuration of the OTC staples of the present invention has a stapling range that is illustrated, for example, in FIGS. 18 to 20. A “least” acceptable staple range is a position where the tangent T defined by the tip of each leg 4 is at a negative angle α to a line L parallel to the bridge 2. This orientation is illustrated with the left half of the staple in FIG. 17 merely for reasons of clarity. See also FIGS. 18 to 20. A “greatest” acceptable staple range is a position where the legs 4 are bent 180 degrees into a shape similar to the letter “B” (see the exemplary orientation illustrated in the right-half of FIG. 17) but, in comparison to the prior art staple range of FIG. 17, as described below in detail, the tips of the legs 4 of the staples according to the invention reach only up to a compressing portion and not further than this compressing portion as shown in FIG. 20, for example. In

such an orientation, the stapled tips of the legs do not interfere with the OTC device present in the staples according to the invention.

The OTC devices for staples according to the invention take many forms. The OTC device can be integral with the legs of the staple and project into a central area or can be attached to the staple to project into the central area. The OTC device can be sinusoidal in shape with a compressing portion at the end of the OTC device or can be have multiple cycles of bends between the bridge of the staple with the compressing portion at the end of the OTC device. The bending portion can be single or double, the double bends being in cycle, out of cycle, mirror-symmetrical, to name a few. The bends can be double-sinusoidal as shown in FIGS. 8, 9, and 11. The OTC device can be contained entirely between the two legs of the staple or can encircle one or both of the legs and, thereby, use the legs as a guide, for example, a sliding guide. The leg encirclement by the OTC device can be single or multiple. Travel of the OTC device can be limited, for example, by a star washer. The OTC device can be a compression spring(s) and a plate(s), with the plate encircling the legs and sliding thereon. The OTC device can be a compressible material secured on the legs. This material can be in the shape of a plate or a pillow.

With the foregoing and other objects in view, there is provided, in accordance with the invention, a substantially U-shaped staple having a bridge, legs, and an internally disposed compression device having a bias portion with a compression surface movably disposed between the legs and a compression resistor connected to the bridge and to the compression surface and is formed to resist movement of the compression surface towards the bridge with a force.

In accordance with another feature of the invention, the bridge is substantially rod-shaped with ends and the base end of each of the legs is integral with a respective one of the ends.

In accordance with a further feature of the invention, the bridge and legs define a bridge-leg plane and the legs extend from the bridge at an angle of between 80 and 100 degrees in the bridge-leg plane.

In accordance with an additional feature of the invention, the compression surface defines two orifices and each of the legs extends through one of the two orifices.

In accordance with yet another feature of the invention, the compression resistor defines at least one orifice pair, the compression surface defines two orifices, and each of the legs extends through one of the two orifices and one of the at least one orifice pair.

In accordance with yet a further feature of the invention, the compression resistor defines a plurality of orifice pairs, the compression surface defines two orifices, and each of the legs extends through one of the two orifices and one of each of the orifice pairs.

In accordance with yet an added feature of the invention, the bridge and the legs define a compression axis and the compression surface is movably disposed between the legs along the compression axis.

In accordance with yet an additional feature of the invention, the compression device is connected to the bridge.

In accordance with again another feature of the invention, the compression resistor connects the bridge to the compression surface.

In accordance with again a further feature of the invention, the bridge, the legs, the compression resistor, and the compression surface are integral.

In accordance with again an added feature of the invention, the compression resistor is at least partly disposed between the legs.

In accordance with again an additional feature of the invention, the compression resistor is disposed between the bridge and the compression surface.

In accordance with still another feature of the invention, the force is a pre-defined opposing force.

In accordance with still a further feature of the invention, the force is a substantially constant force.

In accordance with still an added feature of the invention, the force is a linearly increasing force.

In accordance with still an additional feature of the invention, the compression resistor has an anti-compressive spring constant imparting a substantially constant anti-compressive force over a pre-defined compression range.

In accordance with another feature of the invention, the staple and the compression device are of a biocompatible material.

In accordance with a further feature of the invention, the compression surface and the legs define a central compression region in which is to be disposed a material to be compressed between the compression surface and stapling points when distal ends of the staple legs are deformed. When the distal ends are deformed in a staple closing direction into the central compression region, the bias portion resists movement of the compression surface in the staple closing direction with a pre-defined, substantially constant force.

In accordance with an added feature of the invention, the compression surface and the bias portion are shaped to impart a pre-defined, substantially constant bias force upon material disposed between the compression surface and stapling points when the stapling points are deformed.

In accordance with a concomitant feature of the invention, when stapling points are deformed toward one another, material disposed between the compression surface and the stapling points is compressed between the stapling points and the compression surface. The compression resistor maintains a substantially constant compressive force on the material within a pre-defined range independent of a degree of compression between stapling points and the compression surface.

Although the invention is illustrated and described herein as embodied in an adjustable compression staple and method for stapling with adjustable compression, it is, nevertheless, not intended to be limited to the details shown because various modifications and structural changes may be made therein without departing from the spirit of the invention and within the scope and range of equivalents of the claims. Additionally, well-known elements of exemplary embodiments of the invention will not be described in detail or will be omitted so as not to obscure the relevant details of the invention.

Other features that are considered as characteristic for the invention are set forth in the appended claims. As required, detailed embodiments of the present invention are disclosed herein; however, it is to be understood that the disclosed embodiments are merely exemplary of the invention, which can be embodied in various forms. Therefore, specific structural and functional details disclosed herein are not to be interpreted as limiting, but merely as a basis for the claims and as a representative basis for teaching one of ordinary skill in the art to variously employ the present invention in virtually any appropriately detailed structure. Further, the terms and phrases used herein are not intended to be limiting; but rather, to provide an understandable description

of the invention. While the specification concludes with claims defining the features of the invention that are regarded as novel, it is believed that the invention will be better understood from a consideration of the following description in conjunction with the drawing figures. The figures of the drawings are not drawn to scale.

Before the present invention is disclosed and described, it is to be understood that the terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting. The terms "a" or "an", as used herein, are defined as one or more than one. The term "plurality," as used herein, is defined as two or more than two. The term "another," as used herein, is defined as at least a second or more. The terms "including" and/or "having," as used herein, are defined as comprising (i.e., open language). The term "coupled," as used herein, is defined as connected, although not necessarily directly, and not necessarily mechanically.

As used herein, the term "about" or "approximately" applies to all numeric values, whether or not explicitly indicated. These terms generally refer to a range of numbers that one of skill in the art would consider equivalent to the recited values (i.e., having the same function or result). In many instances these terms may include numbers that are rounded to the nearest significant figure.

BRIEF DESCRIPTION OF THE DRAWINGS

Advantages of the embodiments of the present invention will be apparent from the following detailed description of the preferred embodiments thereof, which description should be considered in conjunction with the accompanying drawings in which:

FIG. 1 is a perspective view from above a side of an exemplary prior art surgical staple;

FIG. 2 is a perspective view from above a side of a first exemplary embodiment of an OTC staple according to the invention;

FIG. 3 is a perspective view from above a side of a second exemplary embodiment of an OTC staple according to the invention;

FIG. 4 is a perspective view from above a side of a third exemplary embodiment of an OTC staple according to the invention;

FIG. 5 is a perspective view from above a side of a fourth exemplary embodiment of an OTC staple according to the invention;

FIG. 6 is a perspective view from above a side of a fifth exemplary embodiment of an OTC staple according to the invention;

FIG. 7 is a perspective view from above a side of a sixth exemplary embodiment of an OTC staple according to the invention;

FIG. 8 is a perspective view from above a side of a seventh exemplary embodiment of an OTC staple according to the invention;

FIG. 9 is a perspective view from above a side of an eighth exemplary embodiment of an OTC staple according to the invention;

FIG. 10 is a perspective view from above a side of a ninth exemplary embodiment of an OTC staple according to the invention;

FIG. 11 is a perspective view from above a side of a tenth exemplary embodiment of an OTC staple according to the invention;

FIG. 11A is a fragmentary, enlarged perspective view from below a side of the OTC staple of FIG. 11;

7

FIG. 12 is a perspective view from above a side of an eleventh exemplary embodiment of an OTC staple according to the invention;

FIG. 13 is a perspective view from above a side of a twelfth exemplary embodiment of an OTC staple according to the invention;

FIG. 14 is a perspective view from above a side of a thirteenth exemplary embodiment of an OTC staple according to the invention;

FIG. 15 is a perspective view from above a side of a fourteenth exemplary embodiment of an OTC staple according to the invention;

FIG. 16 is a perspective view from above a side of a fifteenth exemplary embodiment of an OTC staple according to the invention;

FIG. 17 is a side elevational view of the prior art surgical staple of FIG. 1 with the staple tips illustrating an exemplary range of stapling;

FIG. 18 is a side elevational view of the staple of FIG. 6 with the staple tips in a first intermediate position of an exemplary stapling range;

FIG. 19 is a side elevational view of the staple of FIG. 6 with the staple tips in a second intermediate position of an exemplary stapling range; and

FIG. 20 is a side elevational view of the staple of FIG. 6 with the staple tips in a third intermediate position of an exemplary stapling range.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Herein various embodiment of the present invention are described. In many of the different embodiments, features are similar. Therefore, to avoid redundancy, repetitive description of these similar features may not be made in some circumstances. It shall be understood, however, that description of a first-appearing feature applies to the later described similar feature and each respective description, therefore, is to be incorporated therein without such repetition.

Referring now to the figures of the drawings in detail and first, particularly to FIG. 2 thereof, there is shown a first exemplary embodiment of an automatic optimal tissue compression (OTC) staple 20 according to the invention. In this first embodiment, the bridge 21 has a center bridge portion 22 and an extension 23 that substantially increases the overall length of the bridge 21—as compared to the bridge 2 of the staple 1 of FIG. 1. As the upper bridge portion 22 transitions into the extension 23, it curves into and within the central region 24 of the staple 20. This extension 23 can be in any shape or of any material so long as it delivers a pre-set compressive force to the tissue at a compressing portion 25, and as long as it allows for absorption (within the area between the compressing portion 25 and the upper bridge portion 22) of forces greater than this pre-set force. Therefore, the shape can be trapezoidal, triangular, sinusoidal, or any other configuration. An exemplary embodiment of relatively sinusoidal curves is shown in FIG. 2. These curves traverse two periods in the illustrated embodiment, however, the number of wave periods can be varied (smaller or larger). The extension 23 has two mirror-symmetrical portions each starting from the upper bridge portion 22 and ending at respective ends of the compressing portion 25. Further, it is noted that neither the extension 23 nor the compressing portion 25 directly contacts the legs 26 in this exemplary configuration.

8

In the embodiment of FIG. 2, the extension 26 and the compressing portion 29 are integral with the upper bridge portion 22 and a base end 27 of the legs 26. The legs 26 are shown as relatively circular in cross-section. The bridge 21 and all of the compressing components 22, 23, 25 can also be circular in cross-section. Alternatively, as shown in FIG. 2, any portion of the extension 23 and/or the compressing portion 25 can have different cross-sectional shapes, such as ovalar, rectangular, or polygonal. In the embodiment shown, the cross-section of the extension 23 after the first curve away from the upper bridge portion 22 is shaped in a “racetrack” form (two relatively straight sides with two curved ends connecting each end of the sides). The upper bridge portion 22 can also have a different cross-sectional shape. The extension 23 and compressing portion 25 are, in this embodiment, even in cross-sectional area. Different portions of these parts can, however, have varying cross-sectional areas (i.e., varying thicknesses) as desired.

When the upper bridge 22, the extension 23, and the compressing portion 25 are shaped to deliver the pre-set compressive force to the tissue in a substantially longitudinal direction 28 of an unbent section of the leg portions 26 and to absorb forces greater than this pre-set force, the overall effect is to create an OTC device having a given spring coefficient. In other words, the OTC device maintains the preset compressive force within the stapled area even after tissue changes states, such as expanding due to swelling and/or contracting during desiccation. Variation of the cross-section of any portion of the upper bridge 22, the extension 23, and the compressing portion 25 will allow for different OTC spring coefficients and, therefore, allows for adjustment of the compressive and reactive force constants of the OTC device within the staple 20. Variation of the material making up all of the staple 20 or any of its portions also permits adjustment of the OTC force.

FIG. 3 illustrates a second exemplary embodiment of the OTC staple 30 according to the invention. In this variation, as compared to the embodiment of FIG. 2, the OTC portion is not integral with the bridge 31 and the legs 32. Instead, the OTC device 33 is separate therefrom and is connected to these staple portions. Specifically, the OTC device 33 has a compressing portion 34 that directly contacts the tissue being compressed and an extension 36 for providing the load-bearing force when tissue is compressed within the central region 37 of the staple 30. The OTC device 33 also has a connecting portion 35 for attaching the OTC device 33 to the bridge 31. The extension 36 connects the upper and lower portions 34, 35 of the OTC device 33. The extension 33 and the compressing portion 34 are, in this embodiment, different in cross-sectional area. Here, the cross-sectional area of the compressing portion 34 is wider than the extension 36. Any portions of the extension 33 or the compressing portion 34 can be varied to have same or varying cross-sectional areas (i.e., varying thicknesses).

Connection of the OTC device 33 to the staple, for example, at the bridge 31, can occur by any fastening measure. One exemplary connection method is spot welding, which is indicated in FIG. 3 by reference numeral 38. Other exemplary methods of attaching suitable materials together include soldering and brazing. The type or types of material of the staple portions 31, 32 and the OTC device 33 will direct a preferable attachment method. In the case of attaching two materials together that are not suited to be welded, soldered or brazed, other attachment methods can be used such as crimping and adhesive bonding. Features can be added to one or both of the two components to facilitate the crimp or bond. These features could be con-

figured to have the components snap together. In the case of dissimilar materials, for example, if the staple material is stainless steel and the OTC device **33** is of nickel titanium alloy, then preferred attachment measures include crimping, adhesive bonding, or snapping.

In this second embodiment, the OTC device **33** behaves similar to the OTC portions of the embodiment of FIG. 2 and can be shaped with the same variations of cross-section and other spatial characteristics and can be formed with the same variations in material composition. Variation of any attribute of the OTC device **33** allows for adjustment of the compressive and reactive force constants thereof on the compressed tissue. The extension **36** can be any shape or material so long as it delivers a pre-set compressive force to the tissue at the compressing portion **34** and as long as it allows for absorption of forces greater than this pre-set force. An exemplary embodiment selected for this exemplary OTC device **33** is a relatively sinusoidal set of curves traversing less than two periods. The extension **36** has two mirror-symmetrical portions each starting from the bridge **31** and ending at respective ends of the compressing portion **34**. In this exemplary embodiment, neither the extension **36** nor the compressing portion **34** directly contacts the legs **32**. Most of the cross-section of the OTC device **33** has a racetrack form. Like the embodiment of FIG. 2, the cross-section can be varied in any desired way to deliver the pre-set compressive force to the tissue and to absorb forces greater than this pre-set force.

FIG. 4 illustrates a third exemplary embodiment of the OTC staple **40** according to the invention. In this variation, as compared to the embodiments of FIGS. 2 and 3, the OTC portion **43** is not symmetrical with respect to the bridge **41** or the legs **42**. Also, like the embodiment of FIG. 3, the OTC portion is not integral with either the bridge **41** or the legs **42**. The OTC device **43** is a separate part from the bridge **41** and the legs **42** and is fixedly connected to the bridge **41** at a connection location (for example, with a spot weld **48**; other fixation/connection processes can be used). In particular, a connecting portion **45** of the OTC device **43** fixedly secures the OTC device **43** to the bridge **41**. An extension **46** of the OTC device **43** provides the load-bearing force when tissue is compressed within the central region **47** of the staple **40** and a compressing portion **44** directly contacts the tissue being compressed.

Notably different from the embodiments of FIGS. 2 and 3 is the compressing portion **44**. Here, the width of the compressing portion **44** (defined along the line between the two legs **42** of the staple **40**) is greater than the separation distance of the two legs **42**. The compressing portion **44** is provided with orifices **49** having a shape substantially corresponding to the cross-sectional shape of the upper portion of the staple legs **42** but slightly larger. The legs **42** pass through and slidably rest within these orifices **49**. In such a configuration, movement of the OTC device **43** out of the bridge-legs plane is substantially prevented. Because the orifices **49** are shaped to be slightly larger than the cross-section of the legs **42**, the extension **46** acts as a compression spring in the bridge-legs plane as the compressing portion **44** moves up and down along the upper portion of the legs **42** (up being defined as the direction towards the bridge **41** from the piercing tips of the legs **42**). Thus, the OTC device **43** of the third embodiment behaves different from the OTC devices of FIGS. 2 and 3 because of the form-locking and sliding connection between the connecting portion **44** and the legs **42**. A form-locking connection is one that connects two elements together due to the shape of the elements

themselves, as opposed to a force-locking connection, which locks the elements together by force external to the elements.

Like the previous embodiments, the OTC device **43** can be shaped with variations in cross-section and other spatial characteristics and can be formed with a variety of material compositions. The extension **46** and compressing portion **44** are, in this embodiment, different in cross-sectional area. Here, the cross-sectional area of the compressing portion **44** is wider than the extension **46**. Any portions of the extension **46** or the compressing portion **44** can be varied to have same or varying cross-sectional areas (i.e., varying thicknesses). The extension **46** can be any shape or material so long as it delivers the pre-set compressive force to the tissue at the compressing portion **44** and as long as it allows for absorption of forces greater than this pre-set force. An exemplary embodiment selected for this OTC device **43** is a relatively sinusoidal curve traversing approximately one sinusoidal period. Virtually all of the cross-section of the OTC device **43** has a racetrack form, but can be changed as desired to other shapes (e.g., circular, ovalar, polygonal, etc.). As described above, variation of any attribute of the OTC device **43** allows for adjustment of the compressive and reactive force constants thereof on the compressed tissue in the central region **47**.

FIG. 5 illustrates a fourth exemplary embodiment of the OTC staple **50** according to the invention. This variation has some of the features of the above embodiments. In this variant, like the embodiment of FIG. 2, the OTC portion is symmetrical with respect to the bridge **51** and the legs **52** and the OTC device **53** is integral with the bridge **51**. Like the embodiment of FIG. 4, the compressing portion **54** has a width greater than the separation distance of the two legs **52** and has ports **55** with a shape substantially corresponding to the cross-sectional shape of the upper portion of the legs **52**, but slightly larger. The legs **52** pass through these ports **55**. In this configuration, movement of the OTC device **53** out of the bridge-legs plane is substantially prevented. The extension **56** of the OTC device **53** traverses from the bridge **51** to the compressing portion **54**. Because the ports **55** are shaped to be slightly larger than the cross-section of the legs **52**, the extension **56** acts as a compression spring in the bridge-legs plane as the compressing portion **54** moves up and down along the upper portion of the legs **52**. It is the extension **56** that provides the load-bearing force when tissue is compressed within the central region **57** of the staple **50**. Because of the form-locking and sliding connection between the compressing portion **54** and the legs **52**, the OTC device **53** of the fourth embodiment behaves similar to the OTC devices of FIG. 4.

Here, the OTC device **53** is integral with the legs **52**, the bridge **51**, and the compressing portion **54**. Because the two sides of the bridge **51** are not integral, they can separate from one another when the staple **50** is subjected to a twisting force. If desired, to substantially prevent such separation, the central portions of the bridge **51** can be fixedly connected to one another at a connection location (for example, with a spot weld **58**; other connection processes can be used as well).

Like the previous embodiments, the OTC device **53** can be shaped with variations in cross-section and other spatial characteristics and can be formed with a variety of material compositions. Any portions of the extension **56** or the compressing portion **54** can be varied to have the same or varying cross-sectional areas (i.e., varying thicknesses). The extension **56** and compressing portion **54** are, in this embodiment, different in cross-sectional areas. Here, the

11

cross-sectional area of the upper majority of the extension **56** is narrower than the lower portion of the extension **56** and the cross-section of the lower portion of the extension **56** gradually increases in width until it is equal to the cross-section of the compressing portion **54**.

The extension **56** can be any shape or material so long as it delivers the pre-set compressive force to the tissue at the compressing portion **54** and as long as it allows for absorption of forces greater than this pre-set force. An exemplary embodiment selected for this OTC device **53** is a relatively sinusoidal curve traversing more than one sinusoidal period. Again, only for illustrative purposes, the cross-section of the OTC device **53** has a racetrack shape, but can be changed as desired to other shapes (e.g., circular, ovular, polygonal, etc.). As described above, variation of any attribute of the OTC device **53** allows for adjustment of the compressive and reactive force constants thereof on the compressed tissue in the central region **57**.

FIG. **6** illustrates a fifth exemplary embodiment of the OTC staple **60** according to the invention. This variation has some of the features of the above embodiments. In this variant, like the embodiment of FIG. **3**, the OTC portion is symmetrical with respect to the bridge **61** and the legs **62** and the OTC device **63** is a separate part from the bridge **61** and legs **62** of the staple **60**. Like the embodiment of FIGS. **4** and **5**, the compressing portion **64** has a width greater than the separation distance of the two legs **62** and has ports **65** with a shape substantially corresponding to the cross-sectional shape of the upper portion of the legs **62**, but slightly larger. The legs **62** pass through these ports **65**. In this configuration, movement of the OTC device **63** out of the bridge-legs plane is substantially prevented. The extension **66** of the OTC device **63** traverses from the bridge **61** to the compressing portion **64**. Because the ports **65** are shaped to be slightly larger than the cross-section of the legs **62**, the extension **66** acts as a compression spring in the bridge-legs plane as the compressing portion **64** moves up and down along the upper portion of the legs **62**. It is the extension **66** that provides the load-bearing force when tissue is compressed within the central region **67** of the staple **60**. Because of the form-locking and sliding connection between the compressing portion **64** and the legs **62**, the OTC device **63** of the fifth embodiment behaves similar to the OTC devices of FIGS. **4** and **5**.

Connection of the OTC device **63** to the staple **60**, for example, at the bridge **61**, can occur by any fastening measure. One exemplary connection method is spot welding, which is indicated in FIG. **6** by reference numeral **68**. The type or types of material of the staple portions **61**, **62** and the OTC device **63** will direct a preferable attachment method. In the case of attaching two materials together that are not suited to be welded, soldered or brazed, other attachment methods can be used such as crimping and adhesive bonding. Features can be added to one or both of the two components to facilitate the crimp or bond. These features could be configured to have the components snap together. In the case of dissimilar materials, for example, if the staple material is stainless steel and the OTC device **63** is of nickel titanium alloy, then preferred attachment measures include crimping, adhesive bonding, or snapping.

Like the previous embodiments, the OTC device **63** can be shaped with variations in cross-section and other spatial characteristics and can be formed with a variety of material compositions. Any portions of the extension **66** or the compressing portion **64** can be varied to have the same or different cross-sectional areas (i.e., varying thicknesses). The extension **66** and compressing portion **64** are, in this

12

embodiment, different in cross-sectional areas. Here, the cross-sectional area of most of the extension **66** is narrower than the lowermost portion of the extension **66** and the cross-section of this lowermost portion of the extension **66** gradually increases in width until it is equal to the cross-section of the compressing portion **64**, which is substantially wider.

The extension **66** can be any shape or material so long as it delivers the pre-set compressive force to the tissue at the compressing portion **64** and as long as it allows for absorption of forces greater than this pre-set force. An exemplary embodiment selected for this OTC device **63** is a relatively sinusoidal curve traversing more than one sinusoidal period. Again, only for illustrative purposes, the cross-section of the OTC device **63** has a racetrack shape, but can be changed as desired to other shapes (e.g., circular, ovular, polygonal, etc.). As described above, variation of any attribute of the OTC device **63** allows for adjustment of the compressive and reactive force constants thereof on the compressed tissue in the central region **67**.

FIG. **7** illustrates a sixth exemplary embodiment of the OTC staple **70** according to the invention. This variation has some of the features of the above embodiments. In this variant, like the embodiment of FIG. **3**, the OTC portion is symmetrical with respect to the bridge **71** and the legs **72** and the OTC device **73** is a separate part from the bridge **71** and legs **72** of the staple **70**. Like the embodiment of FIGS. **4** to **6**, the compressing portion **74** has a width greater than the separation distance of the two legs **72** and has ports **75** with a shape substantially corresponding to the cross-sectional shape of the upper portion of the legs **72**, but slightly larger. The legs **72** pass through these ports **75**. In this configuration, movement of the OTC device **73** out of the bridge-legs plane is substantially prevented. The extension **76** of the OTC device **73** traverses from the bridge **71** to the compressing portion **74**. Because the ports **75** are shaped to be slightly larger than the cross-section of the legs **72**, the extension **76** acts as a compression spring in the bridge-legs plane as the compressing portion **74** moves up and down along the upper portion of the legs **72**. It is the extension **76** that provides the load-bearing force when tissue is compressed within the central region **77** of the staple **70**. Because of the form-locking and sliding connection between the compressing portion **74** and the legs **72**, the OTC device **73** of the sixth embodiment behaves similar to the OTC devices of FIGS. **4** to **6**.

Connection of the OTC device **73** to the staple **70**, for example, at the bridge **71**, can occur by any fastening measure. One exemplary connection method is spot welding, which is indicated in FIG. **7** by reference numeral **78**. The type or types of material of the staple portions **71**, **72** and the OTC device **73** will direct a preferable attachment method. In the case of attaching two materials together that are not suited to be welded, soldered or brazed, other attachment methods can be used such as crimping and adhesive bonding. Features can be added to one or both of the two components to facilitate the crimp or bond. These features could be configured to have the components snap together. In the case of dissimilar materials, for example, if the staple material is stainless steel and the OTC device **73** is of nickel titanium alloy, then preferred attachment measures include crimping, adhesive bonding, or snapping.

It is noted that the extensions (i.e., springs) in each of FIGS. **2**, **3**, **5**, and **6** are in the same plane, which can be the bridge-legs plane (as shown) or out of that plane. In com-

parison to these embodiments, the extension **76** has the springs residing in different planes (i.e., one next to the other).

Like the previous embodiments, the OTC device **73** can be shaped with variations in cross-section and other spatial characteristics and can be formed with a variety of material compositions. Any portions of the extension **76** or the compressing portion **74** can be varied to have the same or varying cross-sectional areas (i.e., varying thicknesses). The extension **76** and the compressing portion **74** are, in this embodiment, different in cross-sectional areas. Here, the cross-sectional area of most of the extension **76** is narrower than the lowermost portion of the extension **76** and the cross-section of this lowermost portion of the extension **76** gradually increases in width until it is equal to the cross-section of the compressing portion **74**, which is substantially wider.

The extension **76** can be any shape or material so long as it delivers the pre-set compressive force to the tissue at the compressing portion **74** and as long as it allows for absorption of forces greater than this pre-set force. An exemplary embodiment selected for this OTC device **73** is a relatively sinusoidal curve traversing more than one sinusoidal period. Again, only for illustrative purposes, the cross-section of the OTC device **73** has a racetrack shape, but can be changed as desired to other shapes (e.g., circular, ovular, polygonal, etc.). As described above, variation of any attribute of the OTC device **73** allows for adjustment of the compressive and reactive force constants thereof on the compressed tissue in the central region **77**.

FIG. **8** illustrates a seventh exemplary embodiment of the OTC staple **80** according to the invention. This variation has some of the features of the above embodiments. In this variant, like the embodiment of FIG. **3**, the OTC portion is symmetrical with respect to the bridge **81** and the legs **82**, and the OTC device **83** is a separate part from the bridge **81** and legs **82** of the staple **80**. Like the embodiment of FIGS. **4** to **7**, the compressing portion **84** has a width greater than the separation distance of the two legs **82** and has ports **85** with a shape substantially corresponding to the cross-sectional shape of the upper portion of the legs **82**, but slightly larger. The legs **82** pass through these ports **85**. In this configuration, movement of the OTC device **83** out of the bridge-legs plane is substantially prevented. The extension **86** of the OTC device **83** traverses from the bridge **81** to the compressing portion **84**. Because the ports **85** are shaped to be slightly larger than the cross-section of the legs **82**, the extension **86** acts as a compression spring in the bridge-legs plane as the compressing portion **84** moves up and down along the upper portion of the legs **82**. It is the extension **86** that provides the load-bearing force when tissue is compressed within the central region **87** of the staple **80**. Because of the form-locking and sliding connection between the compressing portion **84** and the legs **82**, the OTC device **83** of the seventh embodiment behaves similar to the OTC devices of FIGS. **4** to **7**.

Like the previous embodiments, the OTC device **83** can be shaped with variations in cross-section and other spatial characteristics and can be formed with a variety of material compositions. Any portions of the extension **86** or the compressing portion **84** can be varied to have the same or varying cross-sectional areas (i.e., varying thicknesses). The extension **86** and the compressing portion **84** are, in this embodiment, different in cross-sectional areas. Here, the cross-sectional area of most of the extension **86** is smaller and narrower than the lowermost portion of the extension **86** and the cross-section of this lowermost portion gradually

increases in width until it is equal to the cross-section of the compressing portion **84**, which is substantially wider. Also, the cross-sectional area of this extension **86** is smaller than previous embodiments (but it need not be).

The extension **86** can be any shape or material so long as it delivers the pre-set compressive force to the tissue at the compressing portion **84** and as long as it allows for absorption of forces greater than this pre-set force. An exemplary embodiment selected for this OTC device **83** is a relatively sinusoidal curve traversing a more than two periods and also having a second "interior" curve that traverses sinusoidal periods. In this embodiment, the OTC device **83** has an uppermost portion that is, in contrast to the embodiments of FIGS. **3**, **6**, and **7** a single bar extending along a majority of the bridge **81**.

Connection of the OTC device **83** to the staple **80**, for example, at the bridge **81**, can occur by any fastening measure. One exemplary connection method is spot welding, which is indicated in FIG. **8** by reference numeral **88**. Because there is contact over most of the bridge **81**, the OTC device **83** can be welded over the entire length thereof. The type or types of material of the staple portions **81**, **82** and the OTC device **83** will direct a preferable attachment method. In the case of attaching two materials together that are not suited to be welded, soldered or brazed, other attachment methods can be used such as crimping and adhesive bonding. Features can be added to one or both of the two components to facilitate the crimp or bond. These features could be configured to have the components snap together. In the case of dissimilar materials, for example, if the staple material is stainless steel and the OTC device **83** is of nickel titanium alloy, then preferred attachment measures include crimping, adhesive bonding, or snapping.

Only for illustrative purposes, the cross-section of the OTC device **83** has a racetrack shape, but can be changed as desired to other shapes (e.g., circular, ovular, polygonal, etc.). As described above, variation of any attribute of the OTC device **83** allows for adjustment of the compressive and reactive force constants thereof on the compressed tissue in the central region **87**.

FIG. **9** illustrates an eighth exemplary embodiment of the OTC staple **90** according to the invention. This variation has some of the features of the above embodiments. In this variant, like the embodiment of FIG. **3**, the OTC portion is symmetrical with respect to the bridge **91** and the legs **92**, and the OTC device **93** is a separate part from the bridge **91** and legs **92** of the staple **90**. Like the embodiment of FIGS. **4** to **8**, the compressing portion **94** has a width greater than the separation distance of the two legs **92** and has ports **95** with a shape substantially corresponding to the cross-sectional shape of the upper portion of the legs **92**, but slightly larger. The legs **92** pass through these ports **95**. In this configuration, movement of the OTC device **93** out of the bridge-legs plane is substantially prevented. The extension **96** of the OTC device **93** traverses from the bridge **91** to the compressing portion **94**. Because the ports **95** are shaped to be slightly larger than the cross-section of the legs **92**, the extension **96** acts as a compression spring in the bridge-legs plane as the compressing portion **94** moves up and down along the upper portion of the legs **92**. It is the extension **96** that provides the load-bearing force when tissue is compressed within the central region **97** of the staple **90**. Because of the form-locking and sliding connection between the compressing portion **94** and the legs **92**, the OTC device **93** of the eighth embodiment behaves similar to the OTC devices of FIGS. **4** to **8**.

Like the previous embodiments, the OTC device **93** can be shaped with variations in cross-section and other spatial characteristics and can be formed with a variety of material compositions. Any portion(s) of the extension **96** or the compressing portion **94** can be varied to have the same or varying cross-sectional areas (i.e., varying thicknesses). The extension **96** and the compressing portion **94** are, in this embodiment, different in cross-sectional areas. Here, the cross-sectional area of most of the extension **96** is smaller and narrower than the lowermost portion of the extension **96** and the cross-section of this lowermost portion gradually increases in width until it is equal to the cross-section of the compressing portion **94**, which is substantially wider. Also, the cross-sectional area of this extension **96** is smaller than previous embodiments (but need not be). With such a relatively smaller cross-sectional shape, the curves of the extension **96** might tend to deform or move out of the bridge-legs plane, which tendency can increase or decrease depending upon the material of the extension **96**. To prevent such deformation and/or movement, a plurality of guiding tabs **99** are disposed at one or more of the outside ends of each periodic curve adjacent the legs **92**. These guiding tabs **99** are shaped in a similar manner to the ends of the compressing portion **94**, in that they have ports with a cross-sectional shape substantially corresponding to the cross-sectional shape of the upper portion of the legs **92** but slightly larger. The embodiment illustrated in FIG. **9** provides each guiding tab **99** with two relatively parallel plates each having one of the two ports through which the respective leg **92** is disposed. Like the lower portion of the extension **96**, the cross-sectional area of the extension gradually increases in width until it is equal to the larger cross-section of the plate of the guiding tab **99**. Another alternative of the guiding tab **99** is to have only a single plate with a single port. In such an embodiment (assuming the material was the same as a dual-plate embodiment), the curves of the extension **96** would be slightly stiffer because of the absence of the exterior curve of the guiding tab **99**.

The extension **96** can be any shape or material so long as it delivers the pre-set compressive force to the tissue at the compressing portion **94** and as long as it allows for absorption of forces greater than this pre-set force. An exemplary embodiment selected for this OTC device **93** is a relatively sinusoidal curve having a second interior curve that traverses a few sinusoidal periods and, in this embodiment, has an uppermost portion that is, like the embodiment of FIG. **8**, a single bar extending along a majority of the bridge **91**. Connection of the OTC device **93** to the staple **90**, for example, at the bridge **91**, can occur by any fastening measure. One exemplary connection method is spot welding, which is indicated in FIG. **9** by reference numeral **98**. Alternatively, the weld can be over the entire span contacting the bridge **91**. The type or types of material of the staple portions **91**, **92** and the OTC device **93** will direct a preferable attachment method. In the case of attaching two materials together that are not suited to be welded, soldered or brazed, other attachment methods can be used such as crimping and adhesive bonding. Features can be added to one or both of the two components to facilitate the crimp or bond. These features could be configured to have the components snap together. In the case of dissimilar materials, for example, if the staple material is stainless steel and the OTC device **93** is of nickel titanium alloy, then preferred attachment measures include crimping, adhesive bonding, or snapping.

Again, only for illustrative purposes, the cross-section of the OTC device **93** has a racetrack shape, but can be changed

as desired to other shapes (e.g., circular, ovular, polygonal, etc.). As described above, variation of any attribute of the OTC device **93** allows for adjustment of the compressive and reactive force constants thereof on the compressed tissue in the central region **97**.

FIG. **10** illustrates a ninth exemplary embodiment of the OTC staple **100** according to the invention. This variation has some of the features of the above embodiments. In this variant, like the embodiment of FIG. **3**, the OTC portion is symmetrical with respect to the bridge **101** and the legs **102**, and the OTC device **103** is a separate part from the bridge **101** and legs **102** of the staple **100**. The compressing portion **104**, however, is unlike all of the previous embodiments. Here, the compressing portion **104** is formed from two compressing plates, each of these plates being attached to a respective lower end of two halves of the OTC device **103**. The shape of the compressing portion **104** need not be a plate. It can be cylindrical, for example. Like previous embodiments, the lowermost end of the extension **106** gradually increases in cross-section until it is equal to the compressing portion **104**. Each compressing plate, then, extends towards a respective one of the legs **102** and defines a respective port **105** for receiving therein the leg **102**. The port **105** has a shape substantially corresponding to the cross-sectional shape of the upper portion of the legs **102**, but is slightly larger. The legs **102** pass through each port **105** to form the OTC device **103**. In this configuration, movement of the OTC device **103** out of the bridge-legs plane is substantially prevented. The extension **106** of the OTC device **103** traverses from the bridge **101** to the plates of the compressing portion **104**. Because the ports **105** are shaped to be slightly larger than the cross-section of the legs **102**, the extension **106** acts as a compression spring in the bridge-legs plane as the compressing portion **104** moves up and down along the upper portion of the legs **102**. It is the extension **106** that provides the load-bearing force when tissue is compressed within the central region **107** of the staple **100**.

In this embodiment, as compared to previous OTC device embodiments, the two sides of the OTC device **103** move independent from one another. Thus, if tissue varies in any characteristic within the central portion **107** (e.g., hardness, thickness, density), the optimal tissue compression force can be delivered independently and differently for each of the two differing tissue segments contacting the respective one of the sides of the OTC device **103**.

Connection of the OTC device **103** to the staple **100**, for example, at the bridge **101**, can occur by any fastening measure. One exemplary connection method is spot welding, which is indicated in FIG. **10** by reference numeral **108**. As the upper portion contacts almost all of the bridge **101**, the weld **108**, instead, can span any amount of the bridge **101**. The type or types of material of the staple portions **101**, **102** and the OTC device **103** will direct a preferable attachment method. In the case of attaching two materials together that are not suited to be welded, soldered or brazed, other attachment methods can be used such as crimping and adhesive bonding. Features can be added to one or both of the two components to facilitate the crimp or bond. These features could be configured to have the components snap together. In the case of dissimilar materials, for example, if the staple material is stainless steel and the OTC device **103** is of nickel titanium alloy, then preferred attachment measures include crimping, adhesive bonding, or snapping.

Like the previous embodiments, the OTC device **103** can be shaped with variations in cross-section and other spatial characteristics and can be formed with a variety of material

compositions. Any portions of the extension **106** or the compressing portion **104** can be varied to have the same or varying cross-sectional areas (i.e., varying thicknesses). The extension **106** and the plates of the compressing portion **104** are, in this embodiment, different in cross-sectional areas. Here, the cross-sectional area of most of the extension **106** is smaller and narrower than the lowermost portion of the extension **86** and the cross-section of this lowermost portion gradually increases in width until it is equal to the cross-section of the respective plate of the compressing portion **104**, which is substantially wider.

The extension **106** can be any shape or material so long as it delivers the pre-set compressive force to the tissue at the compressing portion **104** and as long as it allows for absorption of forces greater than this pre-set force. An exemplary embodiment selected for this OTC device **103** is a relatively sinusoidal curve having almost two sinusoidal periods and, in this embodiment, has an uppermost portion that is (like the embodiments of FIGS. **8** and **9**) a single bar extending along a majority of the bridge **101**. For illustrative purposes, the cross-section of the OTC device **103** has an ovular shape, but can be changed as desired to other shapes (e.g., circular, racetrack, polygonal, etc.). As described above, variation of any attribute of the OTC device **103** allows for adjustment of the compressive and reactive force constants thereof on the compressed tissue in the central region **107**.

FIGS. **11** and **11A** illustrate a tenth exemplary embodiment of the OTC staple **110** according to the invention. This variation has some of the features of the above embodiments. In this variant, like the embodiment of FIG. **3**, the OTC portion is symmetrical with respect to the bridge **111** and the legs **112**, and the OTC device **113** is a separate part from the bridge **111** and legs **112** of the staple **110**. The compressing portion **114** is like the embodiment of FIG. **10**—it is formed from two compressing plates, each of these plates being attached to a respective lower end of two halves of the OTC device **113**. The lowermost end of the extension **116** gradually increases in cross-section until it is equal in area to the compressing portion **114**. Each compressing plate, then, extends towards a respective one of the legs **112** and defines a respective port **115** for receiving therein one of the legs **112**. In FIG. **11**, the ports **115** cannot be seen because of the presence of one-way washers **119** (described below), but the port **115** is visible in FIG. **11A**.

As set forth above, each port **115** has a shape substantially corresponding to the cross-sectional shape of the upper portion of the legs **112** but is slightly larger. The legs **112** pass through each port **115** to form the OTC device **113**. Because the ports **115** are shaped to be slightly larger than the cross-section of the legs **112**, the extension **116** acts as a compression spring in the bridge-legs plane as the compressing portion **114** moves up and down along the upper portion of the legs **112**. In this configuration, movement of the OTC device **113** out of the bridge-legs plane is substantially prevented. It is the extension **116** that provides the load-bearing force when tissue is compressed within the central region **117** of the staple **110**. In this embodiment (like the embodiment of FIG. **10**), the two sides of the OTC device **113** move independent from one another. Thus, if tissue varies in any characteristic within the central portion **117** (e.g., hardness, thickness, density), the optimal tissue compression force can be delivered independently and differently for each of the two differing tissue segments contacting the two plates of the compressing portion **114**.

Introduced for the first time in this embodiment are one-way devices **119** (one exemplary embodiment being a

star washer that is illustrated in FIGS. **11** and **11A**) disposed on the leg **112** between the bridge **111** and the compressing portion **114**. These devices **119** are shaped to freely move on the leg **112** upwards towards the bridge **111** but not to move in the opposite direction. Thus, as tissue is being compressed within the central region **117** as the distal ends of the legs **112** are curved in the stapling action, the tissue presses against the compressing portion **114** and moves the compressing portion **114** up towards the bridge **111**. Once the stapling force is removed from the staple **110** (after stapling is complete), the tissue will most likely not press the washers **119** any further without any additionally supplied outside force. Thus, the washers **119** limit further movement of the compressing portion **114** from the then-current location of the washers **119** towards the first bend of the legs **112**. These washers also add some friction when the first stapling movement occurs, which friction may be used to add to and make up the compression coefficients of the OTC device **113**. If the stapled tissue swells, it is possible for the washers **119** to be moved if the force is sufficient. After such swelling ends and desiccation of the tissue occurs, the compressing portions **114** will be limited in further compression by these washers **119**.

Like the previous embodiments, the OTC device **113** can be shaped with variations in cross-section and other spatial characteristics and can be formed with a variety of material compositions. Any portions of the extension **116** or the compressing portion **114** can be varied to have the same or varying cross-sectional areas (i.e., varying thicknesses). The extension **116** and the plates of the compressing portion **114** are, in this embodiment, different in cross-sectional areas. Here, the cross-sectional area of most of the extension **116** is smaller and narrower than the lowermost portion of the extension **116** and the cross-section of this lowermost portion gradually increases in width until it is equal to the cross-section of the respective plate of the compressing portion **114**, which is substantially wider.

The extension **116** can be any shape or material so long as it delivers the pre-set compressive force to the tissue at the compressing portion **114** and as long as it allows for absorption of forces greater than this pre-set force. An exemplary embodiment selected for this OTC device **113** is a relatively sinusoidal curve traversing more than two sinusoidal periods and having a second “interior” curve. In this embodiment, the OTC device **113** has an uppermost portion that is (like the embodiments of FIGS. **8** to **10**) a single bar extending along a majority of the bridge **111**. Connection of the OTC device **113** to the staple **110**, for example, at the bridge **111**, can occur by any fastening measure. One exemplary connection method is spot welding, which is indicated in FIG. **11** by reference numeral **118**. This process can be changed if desired. The type or types of material of the staple portions **111**, **112** and the OTC device **113** will direct a preferable attachment method. In the case of attaching two materials together that are not suited to be welded, soldered or brazed, other attachment methods can be used such as crimping and adhesive bonding. Features can be added to one or both of the two components to facilitate the crimp or bond. These features could be configured to have the components snap together. In the case of dissimilar materials, for example, if the staple material is stainless steel and the OTC device **113** is of nickel titanium alloy, then preferred attachment measures include crimping, adhesive bonding, or snapping.

For illustrative purposes, the cross-section of the OTC device **113** has a racetrack shape, but can be changed as desired to other shapes (e.g., circular, ovular, polygonal, etc.). As described above, variation of any attribute of the

OTC device **113** allows for adjustment of the compressive and reactive force constants thereof on the compressed tissue in the central region **117**.

FIG. **12** illustrates an eleventh exemplary embodiment of the OTC staple **120** according to the invention. This variation is significantly different from the above embodiments. The OTC device **123** is, as above, a separate part from the bridge **121** and legs **122** of the staple **120**. Here, however, the compressing portion **124** is a C-beam having ports **125** that permit passage of a respective one of the legs **122** therethrough. Each port **125** has a shape substantially corresponding to the cross-sectional shape of the upper portion of the legs **122** but is slightly larger. The legs **122** pass through each port **125** to form the OTC device **123**. In this configuration, movement of the OTC device **123** out of the bridge-legs plane is substantially prevented.

The C-beam shape is useful for a variety of reasons. First, the C-shape provides a central cavity in which a distal end of a compression device **126** can be held or fastened. Next, the C-shape also increases resistance to bending forces as compared to a simple rectangular plate, as is known in construction. Finally, orienting the open portion of the “C” away from the tissue presents a flat compressing plate to the tissue to be compressed. With such a shape, the tissue can be compressed evenly, with no singular pressure points. Of course, the C-shape is not the only possible cross-sectional shape. The compressing portion **124** can be a rectangular plate, an I-beam, an L-beam, or any other desired shape.

The compression device **126** can take any form (see, e.g., FIG. **13**). The exemplary embodiment of FIG. **12** illustrates the compression device **126** as a conically expanding compression spring. Connection of the spring **126** and compressing portion **124** to the staple **120**, for example, at the bridge **121**, can occur by any fastening measure. The illustrated exemplary proximal connection method is a ring of the spring material wrapping around the bridge **121**. This proximal end is secured at the center of the bridge **121** and held in place there by placing protuberances **128** on the bridge **121**. These protuberances prevent lateral movement of the proximal ring towards either of the two legs **122**. Of course, this ring can be welded or fastened to the bridge **121** by any fastening process. The distal end of the spring is a relatively circular coil lying in the same plane as the interior cavity of the C-beam and having an outer diameter just slightly less than the interior diameter of the C-shaped cavity of the compressing portion **124**. Thus, the ends of the C-shape can be used to retain the distal end of the spring **126** within the cavity. Of course, other fastening measures can be used to secure the spring distal ends to the compressing portion **124**.

It is the spring **126** that provides the load-bearing force when tissue is compressed within the central region **127** of the staple **120**. Like the previous embodiments, the OTC device **123** can be shaped with variations in cross-section, winding, and other spatial characteristics and can be formed with a variety of material compositions. Any portions of the spring **126** or the compressing portion **124** can be varied. In particular, the spring **126** can be any shape or material so long as it delivers the pre-set compressive force to the tissue through the compressing portion **124** and as long as it allows for absorption of forces greater than this pre-set force. As described above, variation of any attribute of the OTC device **123** allows for adjustment of the compressive and reactive force constants thereof on the compressed tissue in the central region **127**.

FIG. **13** illustrates a twelfth exemplary embodiment of the OTC staple **130** according to the invention. This variation is similar to the embodiment of FIG. **12**. The OTC device **133**

is, as above, a separate part from the bridge **131** and legs **132** of the staple **130** and the compressing portion **134** is a C-beam having ports **135** that permit passage of a respective one of the legs **132** therethrough. Each port **135** has a shape substantially corresponding to the cross-sectional shape of the upper portion of the legs **132** but is slightly larger. The legs **132** pass through each port **135** to form the OTC device **133**. In this configuration, movement of the OTC device **133** out of the bridge-legs plane is substantially prevented.

The C-beam shape has the same benefits as described in the eleventh embodiment of FIG. **12**. Like that embodiment, the C-shape is not required; the compressing portion **134** can be a rectangular plate, an I-beam, an L-beam, or any other desired shape.

The compression device **136** can take any form. In the exemplary embodiment of FIG. **13**, the compression device **136** is a pair of compression springs **136**. Connection of these springs **136** and the compressing portion **134** to the staple **130**, for example, at the bridge **131**, can occur by any fastening measure. The illustrated exemplary proximal connection method is a narrowing of the spring diameter to be equal or less than the diameter of the legs **132** at the connection point to the bridge **131**. Thus, the springs **136** can be held by the force imparted on the legs **132** by press-fitting the narrower spring rings onto a desired location on the legs **132**. Alternatively and/or additionally, the almost ninety degree bend at the legs-bridge intersection forms a stop preventing further upward movement of the distal ends of each spring **136**. Of course, the upper ring(s) can be fastened to the staple **130** by any measure, such as welding, crimping, etc.

Like the embodiment of FIG. **12**, the distal end of the springs **136** in FIG. **13** is formed by a relatively circular coil lying in the same plane as the interior cavity of the C-beam and having an outer diameter just slightly less than the interior diameter of the C-shaped cavity of the compressing portion **134**. Thus, the ends of the C-shape can be used to retain the distal end of the spring **136** within the cavity. The coils can be welded to the C-beam, for example. Of course, other fastening measures and coil configurations can be used to secure the distal ends of the springs **136** to the compressing portion **134**.

It is the springs **136** that provide the load-bearing force when tissue is compressed within the central region **137** of the staple **130**. Like the previous embodiments, the OTC device **133** can be shaped with variations in cross-section and other spatial characteristics and can be formed with a variety of material compositions. Any portions of the springs **136** or the compressing portion **134** can be varied. In particular, the spring **136** can be any shape or material so long as it delivers the pre-set compressive force to the tissue through the compressing portion **134** and as long as it allows for absorption of forces greater than this pre-set force. As described above, variation of any attribute of the OTC device **133** allows for adjustment of the compressive and reactive force constants thereof on the compressed tissue in the central region **137**.

The spring **136** shown in FIG. **12** floats between the legs **132** and does not touch either leg **132**. In contrast, the springs **135** of FIG. **13** wrap around the legs throughout the entire length. This orientation presents the possibility of resistance (i.e., friction) imparted upon the springs **136** by the legs **132** when the springs **136** are compressed. This resistance may be desirable depending upon the desired OTC device compression coefficient. If resistance is to be reduced, then sleeves **138** can be inserted onto the legs **132** such that they “lubricate” or reduce resistance of spring

compression. These sleeves **138** can be made of polytetrafluoroethylene (PTFE), for example.

FIG. **14** illustrates a thirteenth exemplary embodiment of the OTC staple **140** according to the invention. This variation is similar to the embodiments of FIGS. **12** and **13**. The OTC device **143** is, as above, a separate part from the bridge **141** and legs **142** of the staple **140** and the compressing portion **144** is a C-beam having non-illustrated ports that permit passage of a respective one of the legs **142** therethrough (in the view of FIG. **14**, the ports are blocked from view by the C-beam). Each port has a shape substantially corresponding to the cross-sectional shape of the upper portion of the legs **142** but is slightly larger. The legs **142** pass through each port to form the OTC device **143**. In this configuration, movement of the OTC device **143** out of the bridge-legs plane is substantially prevented.

The C-beam shape has the same benefits as described in the eleventh embodiment of FIG. **12**. Like that embodiment, the C-shape is not required; the compressing portion **144** can be a rectangular plate, an I-beam, an L-beam, or any other desired shape.

The compression device **146** can take any form. The exemplary embodiment of FIG. **14** is a pair of compression springs **146**. Like the single spring **136** shown in FIG. **12**, the compression springs **146** of this embodiment float between the legs **142** and do not touch either leg **142**. Connection of these springs **146** to the staple **140**, for example, at the bridge **141**, can occur by any fastening measure. The illustrated exemplary proximal connection method is a second C-beam disposed against the bridge **141** and connected thereto by any fastening measure, such as spot welds **148**, for example. With such a connection configuration, each of the springs **146** can be formed with a relatively circular coil lying in the same plane as the interior cavity of each C-beam and having an outer diameter just slightly less than the interior diameter of the respective C-shaped cavity of the compressing portion **144**. Thus, the ends of the C-shape can be used to retain the distal end of the spring **146** within the cavity. These end coils can be press-fit or slid into the C-beam cavity for connection thereto. Alternatively and/or additionally, these lower and upper loops can be fastened to the beams by welding, crimping, etc. The respective interior cavities of the two C-beams can be of different or of equal size.

It is the springs **146** that provide the load-bearing force when tissue is compressed within the central region **147** of the staple **140**. Like the previous embodiments, the OTC device **143** can be shaped with variations in cross-section, winding, and other spatial characteristics and can be formed with a variety of material compositions. Any portions of the springs **146** or the compressing portion **144** can be varied. In particular, the spring **146** can be any shape or winding or of any material so long as it delivers the pre-set compressive force to the tissue through the compressing portion **144** and as long as it allows for absorption of forces greater than this pre-set force. As described above, variation of any attribute of the OTC device **143** allows for adjustment of the compressive and reactive force constants thereof on the compressed tissue in the central region **147**.

FIG. **15** illustrates a fourteenth exemplary embodiment of the OTC staple **150** according to the invention. The OTC device **153** is, as above, a separate part from the bridge **151** and legs **152** of the staple **150**. Here, however, this variation differs from the previous embodiments because the OTC device **153** is a cushion made of a compressible material. Examples of such material include, but are not limited to, closed cell polyethylene foam, expanded polytetrafluoroeth-

ylene (PTFE), silicone rubber, silicone rubber foam, urethane, and electro-spun thermoplastic elastomers. This cushion **153** defines two channels **154** for receiving therethrough a respective one of the legs **152**. Because the staple legs **152** taper inwards slightly in a direction from the intermediate portion **155** of the staple **150** to the ends of the bridge **151** (although this taper is not a requirement), the cross-sectional area of the channels **154** are larger than the cross-section of a portion of the legs **152** disposed inside the channels **154**. By passing the legs **152** through each channel **154**, the OTC device **153** is formed.

It is this pillow **153** that provides the load-bearing force when tissue is compressed within the central region **157** of the staple **150**. Like the previous embodiments, the OTC device **153** can be shaped with variations in cross-section and other spatial characteristics and can be formed with a variety of material compositions. The exemplary embodiment illustrated in FIG. **15** is a pillow having a racetrack cross-sectional shape in the transverse direction. However, the pillow can be circular, ovular, rectangular, and polygonal in its outer transverse shape.

Any portion of the pillow **153** can be varied so long as it delivers the pre-set compressive force to the tissue at the distal end of the pillow **153** and as long as it allows for absorption of forces greater than this pre-set force. As described above, variation of any attribute of the OTC device **153** allows for adjustment of the compressive and reactive force constants thereof on the compressed tissue in the central region **157**.

FIG. **16** illustrates a fifteenth exemplary embodiment of the OTC staple **160** according to the invention. This variation is different from the previous embodiments. The OTC device **163** is, as above, a separate part from the bridge **161** and legs **162** of the staple **160**. The OTC device is a plate **163** made of a semi-compressible material having properties that will be described in detail below. Examples of such a material include, but are not limited to, polyurethane and silicone rubber. The plate **163** defines two channels **164** for receiving therethrough a respective one of the legs **162**. Because the legs **162** taper inwards slightly in the bridge-legs plane in a direction from the intermediate portion **165** of the staple **160** to the ends of the bridge **161** (although this taper is not a requirement), the cross-sectional area of each of the channels **164** in the bridge-legs plane is larger than the cross-section of the legs **162** that are to be disposed inside the channels **164**. This larger area is defined by a hole that is longer in the bridge-legs plane than in the plane orthogonal thereto along the axis of the leg **162**. In the exemplary embodiment shown in FIG. **16**, the cross-sectional shape of the channels **164** are ovular or racetrack shaped. By passing the legs **162** through each channel **164**, the OTC device **163** is formed.

It is noted that the staple **160** shown in FIG. **16** is different from the prior art staple of FIG. **1**. Specifically, the connecting portion **166** of the legs **162** tapers in width outwardly in the direction beginning from the intermediate portion towards the bridge **161** in a plane that is orthogonal to the bridge-legs plane. Because the channels **164** have a fixed width in the plane of the widening (which plane is orthogonal to the bridge-legs plane), and due to the fact that the fixed width is close in size to the lower-most portion of the connecting portion **166** (nearest to the intermediate portion **165**), the plate **163** will not be able to move upwards towards the bridge **161** unless the material of the plate **163** is semi-compressible. Knowledge about the material's ability to compress and the resistance it provides to upward movement as the plate **163** progresses upward along the outwards

taper of the leg widening can be used to set or adjust the compressive and reactive force constants thereof on the compressed tissue in the central region 167. Any portion of the plate 163 and of the upper leg taper can be varied so long as the OTC system (plate 163 and taper of the legs 162) 5 delivers the pre-set compressive force to the tissue at the distal end of the plate 163 and as long as it allows for absorption of forces greater than this pre-set force.

The OTC device of this embodiment can be shaped with variations in cross-section, taper, and other spatial characteristics and can be formed with a variety of material compositions. The exemplary embodiment illustrated in FIG. 16 is a plate 163 having a racetrack cross-sectional shape in the transverse direction. However, the pillow can be circular, ovular, rectangular, and polygonal in its outer transverse shape, for example. 15

The OTC staple according to the invention is applied in the same manner as a conventional staple, that is:

the staple is loaded into a staple cartridge;
material to be stapled with the staple is placed between the staple cartridge and an anvil; and
the anvil and staple are brought together to press the lower portion of the legs against the anvil and bend the lower portions inward to capture the material in the central region and compress it between the bent portions and the compressing portion of the staple. 25

Because the material to be stapled has a length less than the distance between the bent lower portions and the bridge, the captured material partially compresses the OTC device inside the staple to, thereby, effect the optimal tissue compression feature. When the staple and material are released from the staple cartridge and anvil, the OTC device is imparting a pre-set compressive force against the compressed material. Significantly, the OTC device is able to move while the material is going through its compression and expansion cycle(s) until it finally reaches a steady state size. Even after reaching the steady state, the OTC device imparts the desired compressive force (within an acceptable minimum range) so that the material is not permanently damaged due to over-compression. 35

For example, if the material is human tissue, when tissue is stapled, liquid is forced out of the tissue. During the desiccation period, the tissue compresses further and further. The OTC device compensates by enlarging to follow the tissue compression. At some point in time, the tissue begins to swell (due to the puncturing and compressing forces imparted thereon). During the swelling period, the OTC device compensates by reducing to follow the tissue swelling. 40

The foregoing description and accompanying drawings illustrate the principles, preferred embodiments and modes of operation of the invention. However, the invention should not be construed as being limited to the particular embodiments discussed above. Additional variations of the embodiments discussed above will be appreciated by those skilled in the art. 50

Therefore, the above-described embodiments should be regarded as illustrative rather than restrictive. Accordingly, it should be appreciated that variations to those embodiments can be made by those skilled in the art without departing from the scope of the invention as defined by the following claims. 60

What is claimed is:

1. A compression-self-adjusting staple, comprising:
a substantially U-shaped staple that imparts a compressive force on material to which the staple is applied, and having: 65

a bridge;
two legs extending from the bridge at an angle thereto;
and

a compression device:
at least partly disposed between the legs; and
having a bias portion with:
a compression surface movably disposed between the legs; and
a compression resistor
formed into a plurality of bends that resist movement of the compression surface towards the bridge with a pre-set force that opposes the compressive force, wherein the compression resistor absorbs compressive forces that are greater than the pre-set opposing force, thereby regulating an amount of compressive force being imparted on the material. 10

2. The staple according to claim 1, wherein each of the legs have: 20

a base end integral with the bridge; and
a deformable distal end defining a stapling point shaped to pierce material to be stapled.

3. The staple according to claim 1, wherein:
due to the pre-set force, stapling of tissue occurs within an optimal tissue compression range upon application of a stapling force; and 25

after stapling, the compression resistor maintains the pre-set force within the optimal tissue compression range.

4. The staple according to claim 1, wherein the compression resistor is disposed between the bridge and the compression surface.

5. The staple according to claim 1, wherein the compression resistor is formed to resist movement of the compression surface towards the bridge with a constant force.

6. The staple according to claim 1, wherein the compression resistor is formed to resist movement of the compression surface towards the bridge with a linearly increasing force. 35

7. The staple according to claim 1, wherein the compression resistor has an anti-compressive spring constant imparting a constant anti-compressive force over an optimal tissue compression range.

8. The staple according to claim 1, wherein the compression resistor is sinusoidal.

9. The staple according to claim 1, wherein the compression surface is at a distance from the bridge.

10. The staple according to claim 1, wherein the compression surface is parallel to the bridge.

11. A compression-self-adjusting staple, comprising:
a substantially U-shaped staple that imparts a compressive force on material to which the staple is applied, and having: 40

legs;
a bridge connecting the legs; and
an internally disposed compression device having a bias portion with:
a compression surface movably disposed between the legs; and
a compression resistor 45

formed into a plurality of bends that resist movement of the compression surface towards the bridge with a pre-set force that opposes the compressive force, wherein the compression resistor absorbs compressive forces that are greater than the pre-set opposing force, thereby 50

25

regulating an amount of compressive force being imparted on the material.

12. The staple according to claim 11, wherein the compression surface and the legs define a central compression region in which material is disposed and compressed between the compression surface and stapling points when distal ends of the legs are deformed.

13. The staple according to claim 12, wherein the compression resistor maintains the force during expansion and contraction of the material.

14. The staple according to claim 12, wherein:

when the distal ends are deformed in a staple closing direction into the central compression region, the bias portion resists movement of the compression surface in the staple closing direction with a pre-set, substantially constant force.

15. The staple according to claim 12, wherein the compression surface and the bias portion are shaped to impart a pre-defined, substantially constant force upon material disposed between the compression surface and the stapling points when the distal ends of the legs are deformed.

26

16. The staple according to claim 12, wherein: when the distal ends of the legs are deformed toward one another, material disposed between the compression surface and the stapling points is compressed between the stapling points and the compression surface; and the compression resistor maintains a substantially constant compressive force on the material within a pre-defined range independent of a degree of compression between the stapling points and the compression surface.

17. The staple according to claim 11, wherein the compression resistor is at least partly disposed between the legs.

18. The staple according to claim 11, wherein the compression resistor is disposed between the bridge and the compression surface.

19. The staple according to claim 11, wherein the force comprises one of a pre-set opposing force, a substantially constant force, and a linearly increasing force.

20. The staple according to claim 11, wherein the compression resistor has an anti-compressive spring constant imparting a substantially constant anti-compressive force over a pre-defined compression range.

* * * * *