



(12) **United States Patent**  
**Bullock et al.**

(10) **Patent No.:** **US 11,659,965 B2**  
(45) **Date of Patent:** **May 30, 2023**

(54) **BULK REFILL PROTECTION SENSOR FOR DISPENSING SYSTEM**

(56) **References Cited**

(71) Applicant: **GOJO Industries, Inc.**, Akron, OH (US)  
(72) Inventors: **Mark Bullock**, Wooster, OH (US); **Scott Proper**, Stow, OH (US)  
(73) Assignee: **GOJO Industries, Inc.**, Akron, OH (US)  
(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 80 days.

U.S. PATENT DOCUMENTS

3,581,998 A	6/1971	Roche
3,963,063 A	6/1976	Pascarella
4,090,525 A	5/1978	Potter
4,173,858 A	11/1979	Cassia
4,313,477 A	2/1982	Sebalos
4,322,019 A	3/1982	Smith
4,615,362 A	10/1986	Hartman et al.
4,682,734 A	7/1987	Proctor et al.
4,807,675 A	2/1989	Sharp
5,018,558 A	5/1991	Sharp
5,088,530 A	2/1992	Harp
5,226,566 A	7/1993	Brandenburg
5,390,713 A	2/1995	Fiech

(Continued)

(21) Appl. No.: **17/371,591**

(22) Filed: **Jul. 9, 2021**

(65) **Prior Publication Data**

US 2021/0330137 A1 Oct. 28, 2021

**Related U.S. Application Data**

(63) Continuation of application No. 15/211,582, filed on Jul. 15, 2016, now Pat. No. 11,058,261.

(60) Provisional application No. 62/192,835, filed on Jul. 15, 2015.

(51) **Int. Cl.**  
**A47K 5/12** (2006.01)  
**B05B 12/08** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **A47K 5/1217** (2013.01); **A47K 5/1211** (2013.01); **B05B 12/08** (2013.01)

(58) **Field of Classification Search**  
CPC ..... G05D 9/00; G05D 7/0617; B67D 2001/1263; B67D 2001/1261; B67D 2001/1259; B67D 1/0871; G06K 19/07798; A47K 5/1217; A47K 5/1211; B05B 12/08

See application file for complete search history.

FOREIGN PATENT DOCUMENTS

DE	29707536 U1	10/1998
DE	19948462 A1	9/2000

*Primary Examiner* — Vishal Pancholi


*Assistant Examiner* — Robert K Nichols, II

(74) *Attorney, Agent, or Firm* — Calfee, Halter & Griswold LLP

(57) **ABSTRACT**

An exemplary dispensing system includes a dispenser, an actuator, a sensor, and a controller. The dispenser includes a container for holding liquid, a liquid pump, an air pump, an outlet nozzle, and a foaming media. The actuator causes the dispenser to dispense liquid or foam. The sensor generates an input signal indicative of a status of the container. The controller receives the input signal, generates at least one output signal, and prevents the dispenser from dispensing liquid or foam if a breach is detected in the container.

**20 Claims, 3 Drawing Sheets**



(56)

References Cited

U.S. PATENT DOCUMENTS

5,392,827 A	2/1995	Yasso et al.	9,437,103 B2	9/2016	Ophardt	
5,474,112 A	12/1995	Carola	9,681,779 B2	6/2017	Babikian et al.	
5,540,362 A	7/1996	Azuma et al.	9,681,780 B2	6/2017	Ciavarella et al.	
5,586,586 A	12/1996	Fiech	9,913,562 B2	3/2018	Wegelin et al.	
5,632,414 A	5/1997	Merriweather	10,034,584 B2	7/2018	Ciavarella et al.	
5,829,681 A	11/1998	Hamel et al.	10,189,698 B2	1/2019	Proper et al.	
6,000,626 A	12/1999	Futo et al.	10,358,335 B2	7/2019	Proper et al.	
6,142,342 A	11/2000	Lewis	10,716,436 B2	7/2020	Ciavarella et al.	
6,345,738 B1	2/2002	Brozell et al.	11,122,939 B2	9/2021	Ciavarella et al.	
6,371,386 B1	4/2002	Hoy	2002/0185500 A1	12/2002	Muderlak et al.	
6,467,651 B1	10/2002	Muderlak et al.	2004/0011807 A1*	1/2004	Knepler .....	B67D 1/1247 222/129.1
6,651,851 B2	11/2003	Muderlak et al.	2004/0050876 A1	3/2004	Muderlak et al.	
6,749,135 B2	6/2004	Groblebe et al.	2005/0205612 A1	9/2005	Muderlak et al.	
6,929,150 B2	8/2005	Muderlak et al.	2005/0218161 A1	10/2005	Muderlak et al.	
7,228,874 B2	6/2007	Bolderheij et al.	2006/0011655 A1	1/2006	Ophardt	
7,364,053 B2	4/2008	Ophardt	2007/0084521 A1	4/2007	Rhodenbaugh et al.	
7,455,197 B2	11/2008	Ophardt	2007/0204925 A1	9/2007	Bolderheij et al.	
7,527,174 B2	5/2009	Meehan et al.	2008/0185399 A1	8/2008	Yang et al.	
7,533,787 B2	5/2009	Muderlak et al.	2009/0084813 A1	4/2009	Chen	
7,611,317 B2	11/2009	Muderlak et al.	2009/0101671 A1	4/2009	Cittadino et al.	
7,647,653 B1	1/2010	Catania	2011/0127291 A1	6/2011	Tramontina et al.	
7,753,087 B2	7/2010	Rhodenbaugh et al.	2011/0131714 A1	6/2011	Remijn et al.	
7,798,370 B2	9/2010	Ciavarella et al.	2011/0215115 A1	9/2011	Proper	
7,815,074 B2	10/2010	Ciavarella et al.	2012/0048420 A1	3/2012	Martin	
7,950,548 B2	5/2011	Ciavarella et al.	2013/0075420 A1	3/2013	Tramontina et al.	
8,051,507 B2	11/2011	Lin	2014/0124540 A1	5/2014	Ciavarella et al.	
8,100,299 B2	1/2012	Phelps et al.	2014/0253336 A1	9/2014	Ophardt	
8,251,110 B2	8/2012	Bassett et al.	2014/0263421 A1	9/2014	Urban et al.	
8,256,472 B2	9/2012	De Vries et al.	2014/0263430 A1	9/2014	Muderlak et al.	
8,261,950 B2	9/2012	Cittadino et al.	2015/0083748 A1	3/2015	Mchale et al.	
8,371,474 B2	2/2013	Tramontina et al.	2015/0223646 A1	8/2015	Wegelin et al.	
8,579,157 B2	11/2013	Bem et al.	2015/0230668 A1	8/2015	Shakkour et al.	
8,800,815 B1	8/2014	Butler et al.	2016/0184851 A1	6/2016	McNulty et al.	
8,863,992 B2	10/2014	Wing et al.	2016/0316975 A1	11/2016	Ophardt	
8,893,928 B2	11/2014	Proper	2017/0112329 A1	4/2017	Babikian	
8,950,628 B2	2/2015	Muderlak et al.	2017/0190565 A1	7/2017	Proper et al.	
			2018/0078958 A1	3/2018	Ophardt et al.	

\* cited by examiner




Fig. 1




Fig. 2




FIG. 3

1

**BULK REFILL PROTECTION SENSOR FOR DISPENSING SYSTEM**

## RELATED APPLICATIONS

This application is a continuation of U.S. Ser. No. 15/211, 582, which will issue as U.S. Pat. No. 11,058,261 on Jul. 13, 2021 and is titled BULK REFILL PROTECTION SENSOR FOR DISPENSING SYSTEM, and which is incorporated herein by reference in its entirety. This application also claims priority to and the benefits of U.S. Provisional Application Ser. No. 62/192,835, filed on Jul. 15, 2015 and titled BULK REFILL PROTECTION SENSOR FOR DISPENSING SYSTEM, and which is also incorporated herein by reference in its entirety.

## TECHNICAL FIELD

The present invention relates generally to liquid dispenser systems, such as liquid soap and sanitizer dispensers and bulk refill units.

## BACKGROUND OF THE INVENTION

Liquid dispensing systems, such as liquid soap and sanitizer dispensers, provide a user with a predetermined amount of liquid or foam upon actuation of the dispenser. Liquid dispensing systems typically have a container for holding dispensable liquid. The container is typically sealed to prevent contaminants from entering the dispensing system, thereby maintaining the system in a sanitary condition. To maintain the sanitary condition of the system, empty containers are disposed of and new containers are installed in the dispenser. The system may become contaminated, however, if the seal of the container is breached, for example, to refill the container with liquid rather than installing a new, sealed, container. In some refillable systems, bulk refill units are used to fill one or more refillable sensors. However, such systems may be prone to growing bacteria in either the bulk refill or the refillable dispenser if the bulk refill is not maintained in a sanitary condition, which may occur if someone attempts to refill the sealed bulk refill.

## SUMMARY

Exemplary embodiments of liquid dispensing systems are disclosed herein.

In one exemplary embodiment, a dispensing system includes a container for holding fluid, a fluid pump for pumping fluid from the container, and an outlet nozzle. An actuator is included that causes the dispenser to dispense fluid. A sensor monitors the integrity of the container. A controller receives a signal from the sensor and generates at least one output signal. The at least one output signal includes a breach signal that is indicative of a breach in the integrity of the container.

In another exemplary embodiment, a dispensing system includes a dispenser having a refill unit and a housing with a receptacle for receiving the refill unit. The refill unit includes a container for holding fluid. An actuator causes the dispenser to dispense fluid from the container. The dispensing system also includes a sensor and a controller. The sensor generates an input signal indicative of the integrity of the container of the refill unit. The controller receives the signal from the sensor and generates at least one output signal indicating whether or not the integrity of the container has been breached.

2

An exemplary method for controlling a dispensing system comprises receiving an instruction to dispense fluid, receiving an input signal from a sensor for monitoring the integrity of a container, dispensing fluid if the input signal from the sensor indicates that the container has not been breached, and not dispensing fluid if the input signal from the sensor indicates that the container has been breached.

## BRIEF DESCRIPTION OF THE DRAWINGS

These and other features and advantages of the present invention will become better understood with regard to the following description and accompanying drawings in which:

FIG. 1 is a schematic diagram of an exemplary dispensing system;

FIG. 2 is a block diagram illustrating the steps of an exemplary method for controlling a dispensing system; and

FIG. 3 is a schematic diagram of an exemplary bulk refill unit for a dispensing system.

## DETAILED DESCRIPTION

“Circuit communication” as used herein indicates a communicative relationship between devices. Direct electrical, electromagnetic and optical connections and indirect electrical, electromagnetic and optical connections are examples of circuit communication. Two devices are in circuit communication if a signal from one is received by the other, regardless of whether the signal is modified by some other device. For example, two devices separated by one or more of the following—amplifiers, filters, transformers, optoisolators, digital or analog buffers, analog integrators, other electronic circuitry, fiber optic transceivers or satellites—are in circuit communication if a signal from one is communicated to the other, even though the signal is modified by the intermediate device(s). As another example, an electromagnetic sensor is in circuit communication with a signal if it receives electromagnetic radiation from the signal. As a final example, two devices not directly connected to each other, but both interfacing with a third device, such as, for example, a CPU, are in circuit communication.

Also, voltages and values representing digitized voltages are considered to be equivalent for the purposes of this application, and thus the term “voltage” as used herein refers to either a signal, or a value in a processor representing a signal, or a value in a processor determined from a value representing a signal.

“Signal,” as used herein includes, but is not limited to one or more electrical signals, analog or digital signals, one or more computer instructions, a bit or bit stream, or the like.

“Logic,” synonymous with “circuit” includes, but is not limited to hardware, firmware, software and/or combinations of each to perform a function(s) or an action(s). For example, based on a desired application or needs, logic may include a software controlled microprocessor or microcontroller, discrete logic, such as an application specific integrated circuit (ASIC) or other programmed logic device. Logic may also be fully embodied as software. The circuits identified and described herein may have many different configurations to perform the desired functions.

Values identified in the detailed description are exemplary and they are determined as needed for a particular system. Accordingly, the inventive concepts disclosed and claimed herein are not limited to the particular values or ranges of values used to describe the embodiments disclosed herein.

FIG. 1 illustrates an exemplary embodiment of a foam dispensing system 100. The foam dispensing system 100

includes a housing **102**, a container **110**, a foam pump **120** comprising a liquid pump **130** and an air pump **132**, a liquid pump actuator **140**, an air pump actuator **144**, a controller **150**, and a sensor **152**. Although a foam dispensing system is shown and describe, the system may be a liquid dispensing system that dispenses liquid in the form of a liquid, i.e. without adding air to create a foam. The foam dispensing system **100** may be a wall-mounted system, a counter-mounted system, an un-mounted portable system movable from place to place, or any other kind of dispenser system. As used herein, actuator or actuating members or mechanism includes one or more parts that cause the dispensing system **100** to move liquid, air or foam.

The container **110** forms a liquid reservoir that contains a supply of dispensable liquid **112**. In various embodiments, the contained liquid could be for example a soap, sanitizer, a cleanser, a disinfectant, a foamable liquid, or some other dispensable liquid. The container **110** may advantageously be refillable, replaceable or both refillable and replaceable. In the exemplary dispensing system **100**, the container **110** is a non-collapsible container and can be made of thin plastic. A non-collapsing container usually includes a vent (not shown) to vent the container. In other embodiments, the container **110** may be a collapsible container made of a thinner plastic than its non-collapsible counterpart, or a flexible bag-like material.

An optional housing **102** of the dispensing system **100** may contain all components of the system, or may enclose only some components of the system **100**. For example, the container **110** may be outside of the housing **102** so that it is exposed to ambient light and is visible to the user. In some other embodiments, multiple housings may enclose various combinations of components of the system **100**. The container **110** may be located separate from the dispenser housing **102**, and may, for example, rest on the floor.

In various embodiments, the dispensing system **100** includes a disposable refill unit **101** that includes the container **110**. In some embodiments, the refill unit **110** includes the foam pump **120**. Although the embodiments disclosed herein show and describe a foam pump, other embodiments include liquid pumps without the air pumps or foam cartridge. In the event the liquid stored in the container **110** of the installed disposable refill unit **101** runs out, or the installed refill unit **101** otherwise has a failure, the installed refill unit **101** may be removed from the dispenser **100**. The empty or failed disposable refill unit **101** may then be replaced with a new disposable refill unit **101**. The refill unit **110** may be secured within the dispenser **100** by any means, such as, for example, a quarter turn connection, a threaded connection, a flange and fastener connection, a clamped connection, or any other reusable connection.

The liquid pump **130** and air pump **132** of the foam pump **120** are shown in FIG. 1 as separate pumps, with the liquid pump **130** being inside a pump housing **121** while the air pump **132** is disposed outside the pump housing **121**. The concept of having a foam pump that has a liquid pump portion separable from an air pump portion may be referred to as a "split pump". In a split pump configuration, one of the liquid pump **130** and air pump **132** may be included in the refill unit **101** while the other pump is attached to the housing **102** of the dispensing system **100**.

The foam pump **120** combines foamable liquid **112** from the container **110** and air from the atmosphere in a premix chamber **122**. The liquid pump **130** pumps foamable liquid **112** from the container **110** through a liquid inlet **114** into the premix chamber **122**. Simultaneously, the air pump **132** pumps air through an air inlet **134** into the premix chamber

**122**. The air and liquid mixture in the premix chamber **122** flows through the foaming media **124** disposed in the outlet nozzle **126** to be dispensed as rich foam through an aperture **104** in a bottom plate **103** of the housing **102**. Foaming media **124** may include screens, porous members, sponges, baffles, or the like.

The liquid pump actuator **140** includes an actuation member **142** that engages and actuates the liquid pump **130**. The air pump actuator **144** includes an actuation member **146** that engages and actuates the air pump **132**. In various embodiments, a single actuator may be used to actuate both the liquid pump **130** and air pump **132**. Electronic actuators may additionally include a sensor (not shown) to provide for a hands-free dispenser system with touchless operation

Liquid pump **130**, air pump **132**, and liquid and air actuators **140**, **144** are generically illustrated because there are many different kinds of these components which may be employed in dispensing system **100**. The liquid pump **130** may be any kind of pump, such as, for example, a diaphragm pump, a piston pump, a peristaltic pump, or the like. The air pump **132** may be any type of air pump, such as a rotary pump, a piston pump, a fan pump, a turbine pump, a pancake pump, a diaphragm pump, or the like. The actuators **140**, **144** of the dispensing **100** may be any type of actuator, such as a manual lever, a manual pull bar, a manual push bar, a manual rotatable crank, an electrically activated actuator or other means for actuating liquid pump **130** and air pump **132**.

The controller **150** may be any kind of electronic component, such as a processor, configured to receive an input signal from the sensor **152**. In some embodiments, the controller **150** generates at least one output signal. In the illustrated embodiment, the output signal is sent to the actuators **140**, **144**. In other embodiments, an output signal (not shown) may be sent to a valve (not shown), an electromechanical latch, or other means of preventing the dispenser from actuating or dispensing liquid or foam. The controller **150**, sensor **152**, and actuators **140**, **144** are shown hard wired with input signal wires **154** and output signal wires **156**, though these components may be connected by any means of transmitting a signal, such as, for example, by one or more busses, printed circuits, Wi-Fi, Bluetooth, NFC, or other means of wireless communication. The controller **150** is shown in FIG. 1 inside of the housing **102**, but the controller **150** may be disposed remotely from the foam pump **120** and container **110**. The controller **150** and sensor **152** may be battery powered or may be wired into the electrical system of a building.

The sensor **152** senses one or more parameters associated with the integrity of the container **110**. The integrity of the container **110** is breached if the container **110** is opened, cut, ruptured, etc. so that fluid may be added to the container **110**. In an exemplary embodiment, the sensor **152** is a photodiode that measures the amount of light transmitted through a light transmitting portion **116** of the container **110**. In some embodiments, the container **110**, other than the light transmitting portion **116**, is opaque to prevent the transmission of light. If the container **110** is cut, ruptured, or breached in some way an increase in light will be detected by the sensor **152**. Though the sensor **152** is shown attached to a side of the container **110**, in other embodiments the sensor **152** may be inserted inside the container (not shown) so that no window **116** is necessary and the sensor is able to view the interior of the container **110** directly. In still other embodiments, a light pipe may be used between the container **110** and the sensor **152** so that the sensor **152** can be placed in a location that is remote from the container **110**. The light

pipe may interface with the container **110** at the wall of the container **110** through a window **116**, or in a coupling of the container (not shown) or otherwise so that the sensor **152** may detect an increase in light level. The light detected by the sensor **152** may be ambient light or may be generated by a light source (not shown) configured to shine on the exterior of the container **110**. This configuration allows a breach in the container **110** to be detected when there is not enough ambient light to detect a breach.

During operation of the dispensing system **100**, the controller **150** determines if the container **110** has been breached before dispensing any foam to the user. Breaches are detected as described above by the sensor **152**. The sensor **152** transmits a signal to the controller **150**. When no breach in the container **110** is detected by the sensor **152**, the controller **150** allows foam to be dispensed from the dispensing system **100**. In some embodiments, when a breach in the container **100** is detected, the controller **150** prevents the dispensing system **100** from dispensing foam by any means, such as, for example, closing a liquid valve (not shown) disposed before or after the liquid pump **130**, preventing the actuators **140**, **144** from actuating either by physically preventing actuation or not powering electrical actuators, or the like. Additionally, the controller **150** may illuminate an LED (not shown) on the exterior of the dispenser system **100** to notify a user that the container **110** has been breached and the system is potentially in an unsanitary condition. The controller **150** may even transmit a notification signal over a computer network to inform a remote user or administrator of a breach in the container **110**.

In some embodiments, the controller **150** monitors the sensor **152** to detect an increase in light above a set threshold. The threshold allows some light to pass into the container **110** without indicating a breach. In addition, the sensor **152** may be set to detect certain light wavelengths that are associated with a breach. In an embodiment including a light source, the light source may be set to transmit the wavelengths of light that the sensor **152** is set to detect. In some embodiments, a lens may be used to concentrate light from within the container **110** on the sensor **152**.

FIG. 2 illustrates an exemplary embodiment of a simple methodology **200** for preventing contamination of a dispenser system due to a breach in a container. The methodology begins with receiving an instruction to dispense fluid at block **202**. An input signal is received from a sensor at block **204**. At block **206** a determination is made as to whether there was a breach in the integrity of the container. If there has been a breach the system does nothing at block **208** and no fluid is dispensed. If there has not been a breach in the integrity of the container, fluid is dispensed at block **210**.

FIG. 3 illustrates an exemplary embodiment of a bulk refill system **300**. The bulk refill system **300** includes a bulk refill container **310**, an outlet **312**, a valve **314**, a nozzle **316**, sensor **320** and a refill controller **324**. In some embodiments, the system includes one or more dispenser **380**. The dispenser **380** includes a dispenser controller **382**. In some exemplary embodiments, the dispenser includes an inlet port **390**, an inlet valve **391** and a dispenser controller **382**.

Bulk refill container **310** forms a liquid reservoir that contains a supply of dispensable liquid. In various embodiments, the contained liquid could be for example a soap, sanitizer, a cleanser, a disinfectant, a foamable liquid, or some other dispensable liquid. The container may include a vent (not shown) to vent the container.

Refill controller **342** includes a processor **350** and memory **352**. In some embodiments, refill controller **324**

includes a transceiver **354** for communicating with a dispenser controller **382** and/or a central station (not shown).

Refill controller **324** is configured to receive an input signal from the sensor **320**. Refill controller **320** is also configured to provide an output signal to actuate valve **314**. Valve **314** may be any type of valve capable of operating in response to a signal from refill controller **324**, such as, for example, a solenoid valve, and eclectically operated ball valve, or the like.

The refill controller **324**, sensor **320**, and valve **314** are shown hard wired however, these components may be connected by any means of transmitting a signal, such as, for example, by one or more busses, printed circuits, Wi-Fi, Bluetooth, NFC, or other means of wireless communication. Refill controller **324** and sensor **320** may be battery powered or may be wired into the electrical system of a building.

The sensor **320** senses one or more parameters associated with the integrity of the container **310**. The integrity of the container **310** is breached if the container **310** is opened, cut, ruptured, etc. so that fluid may be added to the container **310**. In some embodiment sensor **320** continuously monitors the integrity of bulk refill container **310**. In some embodiment, the monitoring is intermittent. In some embodiments, monitoring of the container is based on another condition, such as for example, motion, vibration, noise, shock, or the like.

In an exemplary embodiment, the sensor **320** is a photodiode that measures the amount of light transmitted through a light transmitting portion **321** of the container **310**. In some embodiments, the bulk refill container **310**, other than the light transmitting portion **321**, is opaque to prevent the transmission of light. If the bulk refill container **310** is cut, ruptured, or breached in some way an increase in light will be detected by the sensor **321**. Though the sensor **320** is shown attached to a side of the bulk refill container **310**, in other embodiments the sensor **321** may be inserted inside the container (not shown) so that no window **321** is necessary and the sensor is able to view the interior of the container **310** directly. In still other embodiments, a light pipe may be used between the bulk refill container **310** and the sensor **321** so that the sensor **321** can be placed in a location that is remote from the bulk refill container **310**. The light pipe may interface with the bulk refill container **310** at the wall of the container **310** through a window **321**, or in a coupling of the container (not shown) or otherwise so that the sensor **321** may detect an increase in light level. The light detected by the sensor **320** may be ambient light or may be generated by a light source (not shown) configured to shine on the exterior of the bulk refill container **321**. This configuration allows a breach in the bulk refill container **310** to be detected when there is not enough ambient light to detect a breach. Sensor **320**, the controller for valve **314**, memory **352**, transceiver **354** are in circuit communication with one another.

During operation of the bulk refill system **300**, the refill controller **324** determines if the bulk refill container **310** has been breached before transmitting a signal that causes valve **314** to open. In some embodiments, additional requirements are included before valve **314** is caused to open, such as to, for example, insuring that outlet nozzle **316** is inserted in an inlet **390** of a dispenser system. Breaches are detected as described above by the sensor **321**. The sensor **321** transmits a signal to the controller **324**. When no breach in the container **310** is detected by the sensor **321**, the controller **324** allows liquid to be dispensed from the bulk refill system **300**. Additionally, the controller **324** may illuminate an LED (not shown) to notify a user that the container **310** has been breached and the system is potentially in an unsanitary condition. The controller **324** may even transmit a notifica-

tion signal over a computer network to inform a remote user or administrator of a breach in the container 310.

In some embodiments, the controller 324 monitors the sensor 320 to detect an increase in light above a set threshold. The threshold allows some light to pass into the container 310 without indicating a breach. In addition, the sensor 321 may be set to detect certain light wavelengths that are associated with a breach. In an embodiment including a light source, the light source may be set to transmit the wavelengths of light that the sensor 320 is set to detect. In some embodiments, a lens may be used to concentrate light from within the container 310 on the sensor 321.

In some embodiments bulk refill system 300 includes one or more dispensers 380. Dispensers 380 include a valve 391, outlet nozzle 390 and dispenser controller 382. Dispenser controller 382 includes a processor 384, memory 388 and in some embodiments, transceiver 394. Processor 384, controller for valve 391, memory 388, transceiver 386 are in circuit communication with one another.

In some embodiments, refill controller 324 transmits a signal 392 to dispenser controller 382. In some embodiments, signal 392 is a signal indicating that there has been no breach in the integrity of container 310. In some embodiments, signal 392 includes an information indicative of the identity of the bulk refill container 310. In some embodiments, if there has not been a breach in container 310, dispenser controller 382 will send a signal to open valve 391 and allow fluid to flow in from outlet nozzle 316 of bulk refill container 310.

While the present invention has been illustrated by the description of embodiments thereof, and while the embodiments have been described in considerable detail, it is not the intention of the applicants to restrict or in any way limit the scope of the appended claims to such detail. Additional advantages and modifications will readily appear to those skilled in the art. Moreover, elements described with one embodiment may be readily adapted for use with other embodiments. Therefore, the invention, in its broader aspects, is not limited to the specific details, the representative apparatus and illustrative examples shown and described. Accordingly, departures may be made from such details without departing from the spirit or scope of the applicants' general inventive concept.

What is claimed is:

1. A bulk refill system comprising:
  - a refill container for holding a liquid to be dispensed; wherein the refill container is opaque;
  - wherein the refill container is sealed from the outside environment;
  - a sensor for sensing an increase in light in the container;
  - a refill controller configured to receive one or more signals from the sensor indicative of an increase in light; and
  - wherein the refill controller transmits a signal to allow an electronically controllable valve to open if the refill controller has not received one or more signals indicative of an increase in light.
2. The bulk refill system of claim 1, wherein the electronically controllable valve is located on the refill container.
3. The bulk refill system of claim 2, further comprising a soap or sanitizer dispenser and wherein the electronically controllable valve is located on a soap or sanitizer dispenser and the refill controller transmits the signal to a dispenser controller which controls the electronically controllable valve.
4. The bulk refill system of claim 2, further comprising a second electronically controllable valve wherein the second

electronically controllable valve is on one of the refill container and a soap or sanitizer dispenser.

5. The bulk refill system of claim 2 wherein the sensor is located proximate a translucent window on the refill container.

6. The bulk refill system of claim 2 wherein the sensor is located at least partially within the refill container.

7. The bulk refill system of claim 2 further comprising a light pipe for directing light from inside the refill container to the light sensor.

8. The bulk refill system of claim 2 further comprising an indicator for indicating that the refill container has been breached.

9. The bulk refill system of claim 8 wherein the indicator is a light emitting diode.

10. The bulk refill system of claim 2 further comprising circuitry for transmitting a signal to a remote computer that the refill container has been breached.

11. The bulk refill system of claim 10 wherein the circuitry for transmitting a signal is wireless communication circuitry.

12. A bulk refill system comprising:

- a refill container for holding a liquid to be dispensed; wherein the refill container is sealed from the outside environment;

- a sensor for sensing the container has been breached, wherein the sensor senses one of an increase in light being let into the container, vibration, noise, or shock;
- a refill controller configured to receive one or more signals from the sensor indicative of a breach of the container;

- refill communication circuitry; and

- an outlet port on the refill container;

- one or more soap or sanitizer dispensers configured to be refilled by the refill container;

- the one or more soap or sanitizer dispensers having an inlet port configured to mate with the outlet port on the refill container;

- a dispenser controller;

- dispenser communication circuitry for communicating with the refill communication circuitry; and

- an electronically controllable valve;

- wherein the refill controller transmits a signal to the dispenser controller indicative of whether the refill container has been breached; and

- wherein the dispenser controller allows the electronically controllable valve to open if the refill controller has not received one or more signals indicative of a breach.

13. The bulk refill system of claim 12, further comprising a second electronically controllable valve wherein the second electronically controllable valve is on the refill container.

14. The bulk refill system of claim 12 wherein the refill container is opaque and the sensor senses an increase in light within the refill container.

15. The bulk refill system of claim 12 wherein the sensor is located at least partially within the refill container.

16. The bulk refill system of claim 12 wherein the refill communication circuitry and the dispenser communication circuitry are wireless communications circuitry.

17. A method for controlling fluid flow to a dispensing system comprising:

- providing a refill container having

- a sensor for sensing a breach of the refill container;

- a refill controller for receiving one or more signals from the sensor;

refill container communications circuitry for communicating one or more signals; and  
 an outlet nozzle;  
 providing a soap or sanitizer dispenser having  
 an inlet port for connecting to the outlet nozzle;  
 a dispenser container;  
 a conduit between the inlet port and the dispenser  
 container;  
 an electronically controllable valve in the conduit  
 between the inlet port and the dispenser container;  
 a dispenser controller;  
 dispenser communications circuitry for receiving the  
 one or more signals;  
 connecting the outlet nozzle to the inlet port;  
 receiving a signal from the refill communications cir-  
 cuitry by the dispenser communications circuitry;  
 causing the electronically controlled valve to open if  
 the signal is indicative of the refill container not

having been breached and not causing the electroni-  
 cally controlled valve to open if the signal is indica-  
 tive of the refill container having been breached.

**18.** The method of claim **17** wherein the refill communi-  
 cations circuitry and the dispenser communications circuitry  
 comprises wireless communication circuitry.

**19.** The method of claim **17** further comprising transmit-  
 ting a notification signal of a breach to a central computer to  
 notify of a breach of the integrity of the refill container.

**20.** The method of claim **17** further comprising a refill  
 container valve and wherein the refill container valve is  
 controllable by the refill controller and wherein the refill  
 container valve is opened if no breach of the integrity of the  
 refill container is detected and is not opened if a breach of  
 the integrity of the refill container is detected.

\* \* \* \* \*