



(22) **Date de dépôt/Filing Date:** 2008/05/23

(41) **Mise à la disp. pub./Open to Public Insp.:** 2008/11/25

(45) **Date de délivrance/Issue Date:** 2015/06/30

(30) **Priorité/Priority:** 2007/05/25 (EP EP07010505)

(51) **Cl.Int./Int.Cl.** *F03D 1/06* (2006.01),
F03D 3/06 (2006.01), *B64C 11/32* (2006.01),
F04D 29/36 (2006.01), *F04D 29/56* (2006.01)


(72) **Inventeur/Inventor:**
MUNCH, JESPER, DE

(73) **Propriétaire/Owner:**
SIEMENS AKTIENGESELLSCHAFT, DE

(74) **Agent:** SMART & BIGGAR

(54) **Titre : DISPOSITIF POUR LE REGLAGE DU PAS D'UNE PALE DE ROTOR D'UNE EOLIENNE**

(54) **Title: DEVICE FOR THE ADJUSTMENT OF THE PITCH OF A ROTOR BLADE OF A WIND TURBINE**



(57) **Abrégé/Abstract:**

A device is provided for the adjustment of the pitch of a rotor blade of a wind turbine comprising a pitch actuator acting on an adjusting plane for the adjustment of the pitch and a fixing device to which the pitch actuator is attached, the fixing device comprises a first and a second bearing shaft allowing a pendulum motion of the pitch actuator wherein both the first and the second bearing shaft are arranged respectively under a certain tilt angle relatively to the adjusting plane which tilt angle is respectively substantially different from 0° or 90°.



54106-144

Abstract

A device is provided for the adjustment of the pitch of a rotor blade of a wind turbine comprising a pitch actuator acting on an adjusting plane for the adjustment of the pitch
5 and a fixing device to which the pitch actuator is attached, the fixing device comprises a first and a second bearing shaft allowing a pendulum motion of the pitch actuator wherein both the first and the second bearing shaft are arranged respectively under a certain tilt angle relatively to the
10 adjusting plane which tilt angle is respectively substantially different from 0° or 90° .

54106-144

1

Device for the adjustment of the pitch of a rotor blade of a wind turbine.

FIELD OF INVENTION

The invention relates to a device for the adjustment of the pitch of a rotor blade of a wind turbine.

BACKGROUND

A wind turbine comprises two, three or more rotor blades arranged at a hub. A rotor blade is as a rule adjustable relatively to the hub wherein the so called pitch of the rotor blade is adjusted. With the adjustment of the pitch of the rotor blades e.g. the operation of the wind turbine can be influenced and controlled.

In US 4 352 629, DE 27 15 584 A1, US 4 363 241, US 4 431 375 and 4 545 728 wind turbines are disclosed each comprising a pitch mechanisms wherein subject to the impact of the wind to the rotor blades and thus to the respective pitch mechanism the pitch of a rotor blade of the wind turbine is altered in particular to avoid an overspeed of the rotor.

For the adjustment of the pitch of a rotor blade in some wind turbines a hydraulic pitch cylinder is used.

In US 6 327 957 B1 a wind turbine is disclosed comprising a wind turbine rotor with oppositely disposed flexible blades attached to the hub of a drive shaft by a flexible spar. The blades are pitched to a stall position by a collective pitch mechanism in the absence of proper operating conditions. The pitch mechanism is used to change the pitch of the blades collectively. The pitch mechanism comprises a pitch beam extending transversely of the axis of the drive shaft and having a shaft portion that reciprocates within the hollow portion of the drive shaft. Opposite ends of the pitch beam are coupled to respective blade root-ribs by linkages. Movement of the pitch beam inwardly of the drive shaft is provided by a hydraulic cylinder pitch actuator on a pitch yoke attached to the hub. Opposite movement of the pitch

54106-144

2

beam, outwardly of the drive shaft, is provided by a strong compression spring at the innermost end of the shaft portion of the pitch beam. To pitch the blades to the run position, the hydraulic cylinder of the pitch actuator is charged from a hydraulic fluid supply to move the pitch beam inwardly of the drive shaft, so that wind in the downwind direction drives the rotor. To pitch the blades to the stall position, the hydraulic pressure in the cylinder is released, and the strong compression spring drives the pitch beam outwardly of the drive shaft. A thin mechanical tube guides the shaft portion of the pitch beam inside the drive shaft and positions the powerful coil spring against the end of the shaft portion of the pitch beam to permit pre-loading of the blade pitch system. In a shut-down mode, the blades are held in the stalled position by the spring force.

In another wind turbine the hydraulic pitch cylinder comprises a piston rod movable in a tube of the hydraulic pitch cylinder and acts on an adjusting plane e.g. in form of a rotatable plate connected with the rotor blade. E.g. the piston rod is connected to the rotatable plate and the hydraulic pitch cylinder tube is fastened at a support which is fastened at the hub. Thus when the piston rod is hydraulically moved along the hydraulic pitch cylinder tube the pitch of the corresponding rotor blade is adjusted.

As a rule the support of the hydraulic pitch cylinder comprises two cylindrical bearings which define a first bearing shaft. The first bearing shaft is arranged perpendicularly relatively to the adjusting plane or the rotatable plate. Thus the hydraulic pitch cylinder can pivot around the first bearing shaft during the adjustment of the pitch. This is necessary since the linear movement of the piston rod is converted in a circular movement of the rotatable plate. Often there is a small additional pivoting around a second bearing shaft. The second bearing shaft is perpendicular to the first bearing shaft, substantially perpendicular to the hydraulic pitch cylinder and parallel to the adjusting plane or the rotatable plate. The two bearings

54106-144

3

assigned to the second bearing shaft are also cylindrical bearings. Because of the only small pivoting around the second bearing shaft there is a high risk of so called standstill marks in the bearings of the second bearing shaft caused by loads on the bearings without any rotation of the bearings. Thus there is a high risk of a deadlock preventing a pivoting of the hydraulic pitch cylinder around the second bearing shaft.

SUMMARY

It is therefore an object of some embodiments of the present invention to provide a device as initially mentioned in such a way, that the pivoting of the pitch actuator is preferably not hindered.

This object may be achieved by a device for the adjustment of the pitch of a rotor blade of a wind turbine comprising a pitch actuator in form of hydraulic pitch cylinder or an electric pitch actuator acting on an adjusting plane for the adjustment of the pitch and a fixing device to which the pitch actuator is attached, and which is provided for an attachment to a hub of a wind turbine, the fixing device comprises a first and a second bearing shaft allowing a pendulum motion of the pitch actuator relatively to the fixing device wherein both the first and the second bearing shaft are arranged respectively under a certain tilt angle relatively to the adjusting plane which tilt angle is respectively substantially different from 0° or 90° . By tilting the first and the second bearing shaft relatively to the adjusting plane the angular or circular rotation is divided on both bearing shafts. Thus an angular or circular rotation around substantially only one bearing shaft, the first or the second bearing shaft, during the adjustment of the pitch can be avoided. Thereby also the occurrence of standstill marks in bearings can be avoided and the pivoting of the pitch actuator around the first and the second bearing shaft is not hindered. The fixing device has thereby the operation of a pendulum bearing support of the pitch actuator.

54106-144

4

According to an embodiment of the invention the first and the second bearing shaft are arranged substantially perpendicularly relatively to each other.

According to another embodiment of the invention the first and the second bearing shaft are arranged substantially in a common plane.

According to a variant of the invention the first and/or the second bearing shaft are arranged substantially under a tilt angle within the range of $+10^\circ$ to $+80^\circ$ or -10° to -80° relatively to the adjusting plane. Thus the tilt angle of each bearing shaft can be chosen as desired or required. Depending on the chosen tilt angles for the first and the second bearing shaft relatively to the adjusting plane the angular or circular rotation can be divided on the bearing shafts.

In a further development of the invention the first bearing shaft is arranged substantially under a -45° tilt angle relatively to the adjusting plane and the second bearing shaft is arranged substantially under a $+45^\circ$ tilt angle relatively to the adjusting plane. In this case the angular or the circular rotation is divided equally on both bearing shafts.

Preferably at least two bearings are assigned to the first bearing shaft wherein the two bearings of the first bearing shaft are attached to a first ring-like element of the fixing device. The first ring-like element is a kind of support ring for the pitch actuator comprising two projecting parts facing each other. At each projecting part a bearing is arranged.

According to a further development of the invention at least two bearings are assigned to the second bearing shaft wherein the two bearings of the second bearing shaft are attached to a third ring-like element of the fixing device connected respectively to a bearing part of the bearings of the first bearing shaft.

54106-144

5

According to an embodiment of the invention at least one bearing is a plain bearing. Preferably all bearings assigned to the first or second bearing shaft are plain bearings which can support both axial and radial loads from the hydraulic pitch cylinder.

As a rule the fixing device comprises one or more fixing means e.g. in form of flanges comprising clearance holes for fastening the fixing device and thus the pitch actuator at the hub.

10 According to one aspect of the present invention, there is provided device for the adjustment of the pitch of a rotor blade of a wind turbine comprising a pitch actuator acting on an adjusting plane for the adjustment of the pitch and a fixing device to which the pitch actuator is attached, and which is
15 provided for an attachment to a hub of the wind turbine, the fixing device comprises a first and a second bearing shaft allowing a pendulum motion of the pitch actuator relatively to the fixing device wherein both the first and the second bearing shaft are arranged respectively under a first tilt angle
20 relatively to the adjusting plane which tilt angle is respectively substantially different from 0° or 90° .

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will in the following be explained in more detail with reference to the schematic drawings, where

25 FIG 1 shows a device for the adjustment of the pitch of a rotor blade of a wind turbine in a perspective view,

54106-144

5a

FIG 2 shows partially a sectional view of the device of FIG 1,

FIG 3, 4 shows the device of FIG 1 attached to a hub in two different operation positions,

5 FIG 5 shows tilt angles of bearing shafts of the device,

FIG 6 shows a cramp,

FIG 7 shows a spreader and

FIG 8 shows schematically a tube having a projection.

DETAILED DESCRIPTION

10 FIG 1 shows a device D for the adjustment of the pitch of a rotor blade of a wind turbine comprising a pitch actuator in form of a hydraulic pitch cylinder 1 and a fixing device 2.

The hydraulic pitch cylinder 1 comprises a tube 3, a piston rod 4 with a flange 5 at its free end and in a common way
15 connectors 6 as well as conduits 7 for feeding and draining off hydraulic fluid. The piston rod 4 is hydraulically movable relatively to the tube 3. In case of the present embodiment of the invention the tube 3 is substantially a cylindrical tube wherein the cylindrical tube 3 comprises two

54106-144

6

grooves 8, 9 on its outside in a certain applicable distance from each other. FIG 2 shows the arrangement of the grooves 8, 9 relatively to each other. The groove 8 is a receptacle for a first stop ring 10 and the groove 9 is a receptacle for a second stop ring 11. In case of the present embodiment both stop rings 10 and 11 are made of a metal and are appropriately arranged in the respective groove 8, 9. Thus there is substantially no free space between a stop ring and a wall of a groove and thus substantially no movement of a stop ring within a groove. The stop rings 10 and 11 project above the tube 3 and are stoppers for parts of the fixing device 2.

The fixing device 2 comprises a first ring-like element 20 and a second ring-like element 21. The first ring-like element 20 is arranged at the tube 3 in particular around the tube 3 wherein the tube 3 is slightly pressed into the first ring-like element 20 comparable with a slight press fit. The first ring-like element 20 is thereby a kind of support ring having a side 22 with a L-shaped flute 23. The dimensions of the L-shaped flute 23 are such that the part of the stop ring 10 projecting above the tube 3 is appropriately arranged in the flute 23. Thus the first ring-like element 20 is supported towards the stop ring 10 operating as a stopper for the first ring-like element 20. Additionally the first ring-like element 20 comprises in the side 22 around its perimeter several screw holes 24. The screw holes 24 are substantially parallel to a longitudinal axis L of the tube 3.

The second ring-like element 21 is a kind of fixing ring, holding ring or holding mechanism and is also arranged at the tube 3 in particular around the tube 3. The second ring-like element 21 comprises several clearance holes or through borings 25 around its perimeter and a side 26 having a L-shaped flute 27. The clearance holes or through borings 25 are substantially parallel to the longitudinal axis L of the tube 3. The dimensions of the L-shaped flute 27 are such that the part of the stop ring 11 projecting above the tube 3 is

54106-144

7

appropriately arranged in the flute 27. Thus the second ring-like element 21 is supported towards the stop ring 11 operating as a stopper for the second ring-like element 21. Thereby the side 22 of the first ring-like element 20 and the side 26 of the second ring-like element 21 face each other.

After the attachment of the first ring-like element 20 and the second ring-like element 21 around the tube 3 what is by the way done e.g. before the conductors 6 and conduits 7 are mounted several screws or bolts 28 with snap rings 29 are used which press the first 20 and the second 21 ring-like element in such a way towards the respective stop ring 10, 11 that the fixing device 2 and the tube 3 are substantially non-relocatable relatively to each other. Thereby each bolt 28 is arranged in a through boring 25 of the second ring-like element 21 and screwed in one screw hole 24 of the first ring-like element 20. By tightening the bolts 28 the first ring-like element 20 is pressed towards the stop ring 10 and the second ring-like element 21 is pressed towards the stop ring 11.

The first ring-like element 20 comprises additionally two projecting parts 30, 31 facing each other. At each projecting part 30, 31 a bearing 32, 33 is arranged. Thus the hydraulic pitch cylinder 1 can be pivoted around a first bearing shaft A or a first axis A. In case of the present embodiment the bearings 32 and 33 are plain bearings. The bearing part 32a of the bearing 32 and the bearing part 33a of the bearing 33 are attached to a third ring-like element 34. The third ring-like element 34 substantially surrounds the first ring-like element 20 wherein the space between the first ring-like element 20 and the third ring-like element 34 is such that the hydraulic pitch cylinder 1 can pivot in a sufficient way around the bearing shaft A.

Attached to the third ring-like element 34 are two further bearings 35, 36 allowing the hydraulic pitch cylinder 1 to be pivoted around a second bearing shaft B or a second axis B

54106-144

8

which is substantially perpendicular to the first bearing shaft A. In case of the present embodiment of the invention the bearings 35, 36 are also plain bearings.

At the static parts 37 of the bearings 35, 36 are attached fixing means in form of flanges 38. Each flange 38 comprises a clearance hole or through boring 39. By means of the flanges 38 and not shown screws or bolts the device D comprising the fixing device 2 and the hydraulic pitch cylinder 1 can be attached in particular screwed at a hub 40 of a wind turbine as can be seen from FIG 3 and FIG 4.

In case of the present embodiment of the invention the flange 5 of the piston rod 4 of the hydraulic pitch cylinder 1 is connected to a moving part 41 of the hub 40 in form of a rotatable plate 41 defining an adjusting plane P. The rotatable plate 41 is connected to a rotor blade of a wind turbine. The other end of the hydraulic pitch cylinder 1 is arranged through an opening of the hub 40 and is arranged in a housing 42. The device D is in such a way arranged or fastened at the hub 40 by means of the flanges 38 and not shown screws or bolts that the first bearing shaft A and the second bearing shaft B are arranged respectively under a certain tilt angle α relatively to the adjusting plane P and the rotatable plate 41 respectively. This situation is explicitly shown in FIG 5. As can be seen from FIG 5 the device D is compared with the known, initially mentioned arrangement of the bearing shafts tilted about approximately 45° relatively to the adjusting plane P and the rotatable plate 41 respectively. Thus the angular or circular rotation during the adjustment of the pitch is divided substantially equally on both bearing shafts A and B. In this manner the load can be divided on the bearings substantially equally. As can further be seen from FIG 5 in case of the present embodiment of the invention the first and the second bearing shaft A, B are arranged substantially perpendicularly relatively to each other and are arranged substantially in a common plane.

54106-144

9

FIG 3 shows a first operating position of the hydraulic pitch cylinder 1 in particular of the piston rod 4 in which the pitch of the rotor blade is minimal. When the piston rod 4 is adjusted relatively to the tube 3 the pitch can be adjusted respectively. Thereby the hydraulic pitch cylinder 1 pivots around the bearing shafts A and B. Thus the fixing device 2 is a kind of pendulum bearing support of the hydraulic pitch cylinder 1 attachable to a hub of a wind turbine. In FIG 4 the maximum pitch is shown.

According to another embodiment of the device D the attachment of the device D per se at the hub 40 can be unchanged compared with the known and initially mentioned arrangement what means that the device D is not tilted relatively to the adjusting plane P and the rotatable plate 41 respectively. In this case the construction of the fixing device 2 in particular the arrangement of the bearings 32, 33 and 35, 36 at the fixing device 2 must be respectively adapted to receive tilted bearing shafts A and B relatively to the adjusting plane P and the rotatable plate 41 respectively to divide the angular or circular rotation during the adjustment of the pitch substantially equally on both bearing shafts A and B.

Furthermore the tilt angel of the first bearing shaft A needs not to be -45° and the tilt angle of the second bearing shaft B needs not to be $+45^{\circ}$ relatively to the adjusting plane P and the rotatable plate 41 respectively. In fact the tilt angle of the first bearing shaft A can be chosen in the range of $+10^{\circ}$ to $+80^{\circ}$ or in the range of -10° and -80° . Also the tilt angle of the second bearing shaft B can be chosen in the range of $+10^{\circ}$ to $+80^{\circ}$ or in the range of -10° and -80° . As a rule the tilt angles of the first and the second bearing shafts A, B are chosen such that the angular or circular rotation and/or the loads of the hydraulic pitch cylinder 1 are divided preferably substantially equally onto all bearings 32, 33, 35, 36.

54106-144

10

By the way the first and the second bearing shaft need not to be arranged substantially perpendicularly to each other or substantially in a common plane.

According to an alternative embodiment of the device D the first ring-like element 20 and the second ring-like element 21 can be pressed towards the respective stop ring 10, 11 by at least one cramp 50 e.g. as shown in FIG 6. As a rule several cramps 50 are used. In this case the first ring-like element 20 and the second ring-like element 21 can have instead of the clearance holes, through borings or screw holes one or more slots around their perimeter in the sides 51, 52 which receive respectively at least one end of a cramp 50. Thus the cramps 50 e.g. made of an elastic material press the first ring-like element 20 and the second ring-like element 21 towards the respective stop ring 10, 11.

According to a further embodiment of the device D the stop ring 10 can be arranged at the side 51 of the first ring-like element 20 and the stop ring 11 can be arranged at the side 52 of the second ring-like element 21 in respective not shown grooves. In this case at least one spreader 60 e.g. as shown in FIG 7 is used between the side 22 of the first ring-like element 20 and the side 26 of the second ring-like element 21. The spreader of FIG 7 comprises two screws 61, 62 and a retainer 63 with screw threads 64. By turning the retainer 63 in a certain direction the screws 61, 62 move out of the retainer 63. With such spreaders 60 the first ring-like element 20 can be pressed towards its stop ring and the second ring-like element 21 can be pressed towards its stop ring.

By the way a stopper needs not to be a stop ring. The stopper can also be a projection e.g. a ring-like projection 70 on the outside of the tube 3 as schematically shown in FIG 8. Thereby both stoppers can be a stop ring, both stoppers can

54106-144

11

be a projection or one stopper can be a stop ring and the other stopper can be a projection.

Furthermore the pitch actuator needs not to be a hydraulic pitch cylinder. The pitch actuator can also be an electric pitch actuator.

In addition in particular the contours of the outside of the tube and the inside of the first ring-like element and of the second ring-like element need not to be substantially roundly. It is also possible that the contours comprise edges or other forms as long as they fit.

Preferably a device D according to some embodiments of the invention is assigned to each rotor blade of a wind turbine.

The device D needs thereby not to be connected to a plate 41. The device D can also be connected to another element connected to a rotor blade of a wind turbine.

Unlike as described before the device D can also be attached or fastened at a rotor blade of a wind turbine. In this case the flange 5 is attached e.g. to a fixed plate or another fixed element of a hub defining an adjusting plane. If the device D is operated the piston rod 4 moves out of the tube 3 wherein the rotor blade is pivoted relatively to the hub.

By the way each rotor blade is pivoted in a common way relatively to the hub.

The described embodiments of the inventions are only examples. In particular hybrids of the embodiments are without any qualification within the scope of the invention.

Some embodiments of the invention refer also to a wind turbine comprising a hub, at least one rotor blade and a described device for the adjustment of the pitch of the rotor blade.

54106-144

12

CLAIMS:

1. Device for the adjustment of the pitch of a rotor blade of a wind turbine comprising

5 - a pitch actuator acting on an adjusting plane for the adjustment of the pitch and

 - a fixing device to which the pitch actuator is attached, and which is provided for an attachment to a hub of the wind turbine,

10 the fixing device comprises a first and a second bearing shaft allowing a pendulum motion of the pitch actuator relatively to the fixing device wherein both the first and the second bearing shaft are arranged respectively under a first tilt angle relatively to the adjusting plane which tilt angle is respectively substantially different from 0° or 90°.

15 2. Device according to claim 1, wherein the pitch actuator is a hydraulic pitch cylinder.

3. Device according to claim 1, wherein the pitch actuator is an electric pitch actuator.

4. Device according to any one of claims 1 to 3, wherein
20 the first and the second bearing shaft are arranged substantially perpendicularly relatively to each other.

5. Device according to any one of claims 1 to 4, wherein the first and the second bearing shaft are arranged substantially in a common plane.

54106-144

13

6. Device according to any one of claims 1 to 5, wherein the first and/or the second bearing shaft are arranged substantially under a tilt angle within the range of $+10^{\circ}$ to $+80^{\circ}$ or -10° to -80° relatively to the adjusting plane.
- 5 7. Device according to any one of claims 1 to 6, wherein the first bearing shaft is arranged substantially under a -45° tilt angle relatively to the adjusting plane and wherein the second bearing shaft is arranged substantially under a $+45^{\circ}$ tilt angle relatively to the adjusting plane.
- 10 8. Device according to any one of claims 1 to 7, wherein at least two bearings are assigned to the first bearing shaft wherein the two bearings of the first bearing shaft are attached to a first ring-like element of the fixing device.
9. Device according to any one of claims 1 to 8, wherein
15 at least two bearings are assigned to the second bearing shaft wherein the two bearings of the second bearing shaft are attached to a third ring-like element of the fixing device connected respectively to a bearing part of the bearings of the first bearing shaft.
- 20 10. Device according to claim 8 or 9, wherein at least one bearing is a plain bearing.
11. Device according to any one of claims 1 to 10, wherein the fixing device comprises at least one fixing means.

200710133

1/4

FIG 1





FIG 2



200710133

2/4

FIG 3






FIG 4



200710133

3/4

FIG 5



200710133

4/4

FIG 6



FIG 7




FIG 8

