




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : B01D 21/30	A1	(11) International Publication Number: WO 91/19554 (43) International Publication Date: 26 December 1991 (26.12.91)
(21) International Application Number: PCT/US91/04193 (22) International Filing Date: 12 June 1991 (12.06.91) (30) Priority data: 538,301 14 June 1990 (14.06.90) US (71) Applicant: BAXTER INTERNATIONAL INC. [US/US]; One Baxter Parkway, Deerfield, IL 60015 (US). (72) Inventors: HWANG, Yean, Yow ; 832 Huntington Dr., Apt. #16, Arcadia, CA 91007 (US). RITCHEY, Brian ; 609 Ximeno Avenue, Apt. #1, Long Beach, CA 90814 (US). SCHOENDORFER, Donald, W. ; 1842 Whites- tone Terrace, Santa Ana, CA 92705 (US).		(74) Agents: PRICE, Bradford, R., L. et al.; One Baxter Park- way, Deerfield, IL 60015 (US). (81) Designated States: AT (European patent), BE (European patent), CA, CH (European patent), DE (European pa- tent), DK (European patent), ES (European patent), FR (European patent), GB (European patent), GR (Euro- pean patent), IT (European patent), JP, LU (European patent), NL (European patent), SE (European patent). Published <i>With international search report.</i>

(54) Title: AUTOMATED BLOOD COMPONENT SEPARATION PROCEDURE AND APPARATUS PROMOTING DIFFERENT FUNCTIONAL CHARACTERISTICS IN MULTIPLE BLOOD COMPONENTS

**(57) Abstract**

Method and apparatus are provided for machine separation of blood into blood components, wherein a preselected fluid such as anticoagulant is added to at least two different locations (16, 112) through the fluid flow path of the set (10), in order to promote the different functional characteristics in different blood components. The method results in reduced incidence of citrate reaction in the blood donor and increased platelet yield in platelet rich plasma (60) collected during the procedure.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MG	Madagascar
AU	Australia	FI	Finland	ML	Mali
BB	Barbados	FR	France	MN	Mongolia
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinea	NL	Netherlands
BJ	Benin	GR	Greece	NO	Norway
BR	Brazil	HU	Hungary	PL	Poland
CA	Canada	IT	Italy	RO	Romania
CF	Central African Republic	JP	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SN	Senegal
CI	Côte d'Ivoire	LI	Liechtenstein	SU	Soviet Union
CM	Cameroon	LK	Sri Lanka	TD	Chad
CS	Czechoslovakia	LU	Luxembourg	TG	Togo
DE	Germany	MC	Monaco	US	United States of America
DK	Denmark				

-1-

AUTOMATED BLOOD COMPONENT SEPARATION
PROCEDURE AND APPARATUS PROMOTING DIFFERENT
FUNCTIONAL CHARACTERISTICS IN MULTIPLE BLOOD COMPONENTS

5

Filed concurrently herewith is United States Patent Application Serial No. 07/538,306, entitled "Method and Apparatus for Administration of Anticoagulant to Red Cell Suspension Output of a Blood Separator", Donald W. Schoendorfer inventor, assigned to the
10 assignee of the present invention.

FIELD OF THE INVENTION

15 The present invention relates generally to automated blood component separation and more particularly relates to promoting different functional characteristics in different blood components, such as increased platelet yield for platelet collection and resistance to clotting in packed red blood cell suspensions.

20

BACKGROUND OF THE INVENTION

There today exist a number of automated donor hemapheresis systems for the separation of blood, including whole blood, into
25 components or fractions. The systems are designed: to collect one or more components, such as plasma, white cells, platelets and red cells, for further use or for disposal; to return certain components to the donor, who may be a patient; and/or to treat a component, for subsequent return to a donor. One such system is the
30 Autopheresis-C® system sold by Baxter Healthcare Corporation of Deerfield, Illinois, a wholly owned subsidiary of the assignee of the present invention. That system utilizes a microprocessor-

- 2 -

controlled instrument including automated processing programs, in conjunction with a disposable set. The Autopheresis-C® device may, when a disposable plasmapheresis set is installed therein, be used to collect plasma from whole blood drawn from a donor. A rotating
5 membrane in a separation chamber of the disposable may in fact be wetted by an anticoagulant priming operation before blood is withdrawn from the donor, as shown in U.S. Patent Application Serial No. 07/106,089, filed October 7, 1987, entitled "Method for Wetting a Plasmapheresis Filter with Anticoagulant", and corresponding PCT
10 International Application Publication No. W089/03229.

For the collection of platelets and plasma, the Autopheresis-C® system uses a single, two stage set as disclosed in U.S. Patent No. 4,851,126, entitled "Apparatus and Methods for Generating Platelet Concentrate". The set may include a rotating membrane separation
15 chamber as set forth in U.S. Patent Application Serial No. 73,378 and in corresponding Canadian Patent No. 1,261,765, as well as a centrifuge separator as set forth in U.S. Patent Nos. 4,776,964 and 4,911,833 entitled "Closed Hemapheresis System and Method" and in International PCT Publication No. W088/05332 entitled "Continuous
20 Centrifugation System and Method for Directly Deriving Intermediate Density Material from a Suspension". If an anticoagulant source is preattached to the set, a biologically closed system, as medically defined, can be created.

The two stage system enables the collection of blood from a
25 donor for separation into platelet-rich plasma and packed red cells. The red cell suspension is returned to the donor by means of the same needle used to withdraw the whole blood. The platelet-rich plasma is collected in a container. The machine and set are disconnected from the donor. The collected platelet-rich plasma is
30 then separated into plasma and platelet concentrate, utilizing the second stage of the biologically closed set.

- 3 -

Another automated closed system for separating blood fractions is the CS-3000® cell separator sold by Baxter Healthcare Corporation. Still another system is the Model 50 separator sold by Haemonetics Corp. of Braintree, Massachusetts.

5 During withdrawal of blood and its subsequent treatment/separation, anticoagulant must be added in order to prevent clotting of the blood within the disposable tubing and separation set during the separation or collection of the blood. The conventional method of administering anticoagulant during
10 automated apheresis procedures is to add anticoagulant during the step of withdrawal of the whole blood from a donor's vein. Anticoagulant from an anticoagulant container is administered through tubing to a location just downstream from the phlebotomy needle at a tubing junction, where the anticoagulant tubing line
15 merges with the unanticoagulated whole blood tubing line, adjacent the phlebotomy needle in the donor.

There are at least four separate reasons for the addition of anticoagulant to the donor's blood during an extracorporeal blood procedure. The first reason is to prevent the blood from clotting
20 as it travels through the various tubes to the blood separator of the disposable set. The second reason is to prevent the blood from clotting as it is being separated. All separators require some exposure of blood to fluid shear stresses and these shear stresses can induce coagulation or agglomeration. The third reason is to
25 prevent the separated cells from coagulation as they are being pumped through reinfusion filters and back to the donor. The fourth reason is to provide enough nutrients and sufficient pH buffering to permit storage of the separated blood component for the required duration of time.

30

- 4 -

The demand for anticoagulant in each of the four general steps identified above depends on the particular automated apheresis procedure. Some systems may induce significantly more shear stress during blood separation than other systems and therefore the upper
5 limit demand for anticoagulant would be set by the separation step. Also, the separation technology used may have different stages wherein each separation stage may have its own, different demand level for the amount of anticoagulant in the blood. For example, if
10 an intermediate stage separation such as platelet-rich plasma is collected first and then a secondary stage separation is utilized to separate the platelet-rich plasma (PRP) into plasma and platelet concentrate, there may be different requirements for anticoagulant at these two stages.

Alternatively, if the separated blood product is platelets for
15 example and if the requirement is to store the platelets for five days, this relatively lengthy platelet storage period can often require more anticoagulant than any other stage in the blood withdrawal and separation procedure.

The addition of different amounts of anticoagulant to different
20 blood components in manual (non-automated) blood collection is identified in "Platelet Concentrates from Acidified Plasma: A Method of Preparation Without the Use of Additives", Wanda S. Chappell. As best understood, the procedure explained therein utilized different aliquots of anticoagulant in different blood
25 component containers to better optimize the amount of anticoagulant in a collected blood component.

Generally, the prior art has dealt with the issue of anticoagulant demand in automated procedures by adding to the whole
30 blood, almost immediately upon its withdrawal from the donor, enough anticoagulant to meet the highest anticoagulant demand level during the entire withdrawal, separation, return and storage procedure. The anticoagulant is added adjacent the phlebotomy needle. The anticoagulant mixes with the whole blood upon being withdrawn from

- 5 -

the donor. The prior art systems have been directed to adding as much anticoagulant as necessary to prevent clotting, with attention being paid to an upper limit dosage of anticoagulant, beyond which a so-called "citrate reaction" may occur in the donor upon return of an anticoagulated blood component to the donor. For example, with same blood separation systems, anticoagulant ratios of up to one part of anticoagulant to eight parts anticoagulated whole blood are used. In plasma collection procedures using the Autopheresis-C® device, typically six percent anticoagulant is used, but users have the ability to alter this percentage from four percent to eight percent. For platelet collection procedures with the Autopheresis-C® device, anticoagulant levels of six percent to eight percent are utilized. By the nature of some of these apheresis systems, it would be difficult to separate the four anticoagulant demand stages outlined above and have different amounts added depending on the individual stage.

For example, in the Haemonetics Model 50 Device, there are no intermediate stages in the separation process. If the goal is to make platelet concentrate, the platelet concentrate is derived directly from the whole blood, not from an intermediate component such as platelet-rich plasma for example. In other systems, such as the CS-3000® device there are intermediate stages. For example, if plateletpheresis is the objective, platelet-rich plasma is initially separated from whole blood. Then platelet-rich plasma is separated into platelet concentrate. In the CS-3000® device, this is done utilizing separate blood component containers within a closed system, within a centrifuge bowl. The Autopheresis-C® device, in conjunction with a disposable set, separates these components in completely separate stages, but in a single closed system. The platelet-rich plasma is harvested from the donor's blood and the donor is subsequently disconnected. In the next stage, the collected platelet-rich plasma is converted to platelet concentrate and platelet-poor plasma and these become two products of the procedure.

- 6 -

There has been, up until now, no automated blood component separation equipment and procedure for optimizing anticoagulant use during different steps of the automated apheresis procedure. Until now, there has been no recognition of the desirability of reducing the amount of anticoagulant added to whole blood before the separation step. There has been no automated procedure for optimizing the functional characteristics of different blood components in an automated procedure by adding aliquots of anticoagulant or other fluid at different stages in the apheresis procedure.

SUMMARY OF THE INVENTION

According to the present invention, means are provided for adding one or more preselected fluids to a total of two or more blood components in a blood separation procedure, in order to enhance the functional characteristics of the multiple blood components.

According to the present invention, means are provided for adding a single additive such as anticoagulant at different stages of an automated blood component separation procedure. We have discovered that by adding a single preselected fluid, such as anticoagulant, at different stages of an automated blood separation procedure, different functional characteristics of different blood components may be optimized. (For the purpose of this document, whole blood or blood itself is considered to be a blood component.) While it is known to be desirable to add anticoagulant to whole blood in excess of the amount needed for preventing red cell clotting, in order to provide necessary nutrients and pH buffering for platelet concentrate subsequently separated from the whole blood, we have now discovered that, contrary to known teachings, the platelet yield obtained from blood actually increases with decreasing anticoagulant levels in the whole blood.

- 7 -

According to the present invention, during the automated procedure, an appropriate amount of anticoagulant is added to the whole blood adjacent the phlebotomy needle in order to prevent coagulation and activation of the blood as the blood travels to the separation chamber of the disposable set and during separation of the blood into final or intermediate fractions, such as platelet-rich plasma (PRP). The sufficiently anticoagulated, packed red cells exiting the separator may be returned to the donor. Then, in accordance with the invention, another aliquot of anticoagulant is subsequently added to the PRP to promote storage, after separation of the PRP from the whole blood.

The reduction of anticoagulant in whole blood and the subsequent addition of anticoagulant to the PRP tends to greatly reduce the frequency of "citrate reaction" in donors because of reduced anticoagulant in components returned to the donor.

In accordance with the present invention a method is provided for promoting different functional characteristics in blood components during an automated blood component separation procedure, including providing a preferably microprocessor-controlled separation instrument and disposable set; installing the set, which includes tubing defining flow path means and a separator; and adding a preselected fluid at least at two different steps of the procedure, for at least two separate blood components. In the preferred embodiments the preselected fluid is an anticoagulant. The invention is directed to the method of adding anticoagulant to whole blood at a location in the set upstream of the separator and adding anticoagulant to a first blood fraction resulting from the separation step or steps. In accordance with the invention, the first fraction may be platelet-rich plasma or other blood component. The invention is further directed to machine systems for performing these methods.

- 8 -

BRIEF DESCRIPTION OF THE DRAWING

Fig. 1 is a plan view of a tubing/separator set for use in producing platelet concentrate;

5 Fig. 2 is a front elevational view of a microprocessor-controlled, automated blood component separation instrument illustrating a first stage of the set of Fig. 1 installed in the instrument;

10 Fig. 3 is a front elevational view illustrating the instrument with a second stage of the set of Fig. 1 installed in the instrument;

Fig. 4 is a schematic/fluid flow diagram of the blood withdrawal and separation cycle of the first stage portion of the set installed in the instrument as shown in Fig. 2;

15 Fig. 5 is a schematic/fluid flow diagram of the separation and reinfusion cycle of the first stage portion of the set as shown in Fig. 2;

Fig. 6 is a schematic/fluid flow diagram of the first stage portion of the set, illustrating introduction of a second aliquot of anticoagulant into the PRP; and

20 Fig. 7 is a schematic/fluid flow diagram of another first stage set portion for introducing a subsequent aliquot of anticoagulant into the PRP.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

25

Referring now to the drawings, particularly to Fig. 1, there is illustrated a separation set, generally designated 10, such as described in aforementioned U.S. Patent No. 4,851,126. The set 10 includes tubing 11 and separators 46, 62 defining flow path means.
30 The set 10 may be applied to a microprocessor controlled hemapheresis instrument, such as the instrument H illustrated in Figures 2 and 3, in a manner to effect collection of whole blood from a donor through a single needle; separation of the whole blood

- 9 -

into packed blood cells and platelet-rich plasma (PRP); reinfusion of the packed blood cells to the donor, (or alternatively, transfer of some of the packed red cells to a red blood cell collection container); and subsequent separation of platelets from the platelet-rich plasma to provide platelet concentrate and cell depleted, platelet-poor plasma (PPP). While in the preferred embodiments the set 10 is described in conjunction with a single needle with its attendant features and advantages, it will be appreciated that the invention is also applicable to two-needle systems.

Set 10 is provided with a single phlebotomy needle 12 for alternately receiving whole blood from a donor and reinfusing one or more blood fractions such as packed red cells back into the donor. The needle 12 communicates with a blood line 14. An anticoagulant line 16 has an anticoagulant spike 18 at one end for reception in an anticoagulant supply container 20, illustrated in Fig. 2. At the opposite end, anticoagulant line 16 joins blood line 14 in a Y-connection 13 closely adjacent the single phlebotomy needle 12.

The set 10 also includes a reservoir 22. The reservoir 22 is divided into a pair of side-by-side compartments 24, 26. Ports 28 and 30 are provided at the lower ends of the compartments 24, 26, respectively. Mesh screen/filter tubes 32, 34 are disposed in compartments 24, 26, respectively, in communication with respective inlet ports 36 and 38 at the upper end of the reservoir 22. The blood line 14 branches, at a Y-connection 40, into branch a line 42 connecting the blood line 14 with the port 28 of compartment 24, and a branch line 44 which connects the blood line 14 with the port 38 of compartment 26. The set 10 additionally includes a separator 46 for separating platelet-rich plasma and packed red cells from anticoagulated whole blood. A separator of this type is described and illustrated in above-identified PCT International Publication WO 88/05332, as well as in U.S. Patent No. 4,776,964, Schoendorfer et al., entitled "Closed Hemapheresis System and Methods". For

- 10 -

present purposes, separator 46 has a whole blood inlet port 48, a packed cell outlet port 50 and a PRP outlet port 52. The line 54 connects the lower whole blood outlet port 30 of the reservoir compartment 26 with the inlet port 48 of separator 46. A line 56 connects the packed cell outlet 50 of the separator 46 with the inlet port 36 for supplying packed cells to the compartment 24 of the reservoir 22. Tubing 58 connects between the platelet-rich plasma outlet port 52 of the separator 46 and a platelet-rich plasma (PRP) collection container 60.

The foregoing described portion of the set 10 is, for convenience hereafter, identified as the first stage set portion, identified as "A" in Fig. 1, whereas the remaining portion of the set 10 is identified as the second stage set portion, identified as "B" in Figure 1. The unit labelled "B'" (B prime) in Figure 1 illustrates an alternate embodiment having a second, return needle to the donor. It will be appreciated from this description that the first and second stage portions A, B form an integral or unitary set 10 which is packaged and sold for one-time use with the instrument H disclosed in Figures 2 and 3 hereof.

The second stage portion of set 10 also includes in use the PRP container 60 which serves as the platelet-rich plasma supply from which platelets are concentrated upon installation of the second stage portion B on instrument H, as described hereinafter. The second stage portion also includes a separator 62 of the rotary filter membrane type, such as described and illustrated in previously identified Canadian Patent No. 1,261,765. For present purposes, the separator chamber 62 filters the platelet-rich plasma received from the container 60 to provide platelet concentrate and depleted or platelet-poor plasma filtrate (PPP). The separator 62 has a platelet-rich plasma inlet port 64, a platelet-poor or cell depleted plasma outlet port 66 and a platelet concentrate outlet port 68. The container 60 has a PRP outlet port 70 in communication with the inlet port 64 of the separator 62 via tubing 72. A

- 11 -

platelet-poor plasma collection container 74 communicates with the outlet port 66 of the separator 62 via tubing 76. Finally, the platelet concentrate outlet port 68 of the separator 62 communicates with a platelet concentrate collection container 78 via tubing 80.

5 As an alternative, the platelet-rich plasma tubing 72 may be connected to the lower tangential port 68 of the separator 62 and the platelet concentrate tubing 80 may be connected to the upper tangential port 64 of the separator 62. The separator will operate to provide platelet concentrate using this alternate connection.
10 However, the illustrated embodiment is preferred because it facilitates ready removal of the final aliquot of blood product from the separator 62 at the end of the procedure.

As indicated previously, the set 10 is disposable and preferably each of the first and second stage portions are separately provided
15 in discrete flexible plastic containers or pouches indicated by the dashed lines designated A and B, respectively, in Figure 1. Thus, when the first stage portion is used in conjunction with the instrument illustrated in Figures 2 and 3, as hereinafter described, the second tubing portion may be retained in its plastic container
20 or pouch B and disposed on an available hook on the instrument until the first stage portion is removed from the instrument and the second stage portion is applied thereto. It will be understood, however, that the first and second stage portions of the set 10 are integrally connected one to the other and comprise a single closed
25 blood collection, reinfusion and separation system. Accordingly, while the first and second stage portions A, B may be provided in discrete pouches, they are interconnected and their provision in discrete pouches is for convenience of use only as will be apparent from this description.

30 Turning now to Figures 2 and 3, and especially Figures 4 and 5, the relevant operating components of the hemapheresis instrument H will now be described. The instrument is provided with various pumps, detectors, clamps, and the like, under control of a

- 12 -

microprocessor, for cooperation with the set 10 when applied to the instrument. As illustrated in Figures 2, 4 and 5, there are provided pumps P1, P2, P3 and P4 on the front face of instrument H. These pumps are preferably of the peristaltic type and cooperate
5 with the various tubings 11 of the set to flow blood in the desired directions between the various elements of the set. Also, a series of clamps are provided which receive various tubing segments of the set 10. The clamps are movable between open or closed positions and thus operate to open or close the lumens of the tubing segments
10 disposed in the clamps. For present purposes, only clamps C1, C2, C4 and C5 need be identified. The face of the instrument also contains a pressure transducer 82, a hemoglobin detector 84, an air detector 86, sensors (not shown) for determining the levels of liquid in reservoir 22, and a mount or lower holder 88 for the
15 separators 46 and 62 of the harness set 10. The face of instrument H also includes a motor cup 90 for mounting motor magnets which, in turn, drive the separator rotors. Thus, separators 46 and 62 may be installed sequentially on lower mount 88 with their upper ends in the motor cup, whereby magnetic connection is effected between the
20 magnetic drive motor and the rotor of the installed separator.

In accordance with the method of separating blood into constituent parts the first stage portion of set 10 is applied to the instrument face, while the second stage portion is preferably retained in its pouch B and hung from an available hook on the
25 instrument. Under control of the microprocessor, instrument H operates the pumps, clamps, detectors and the like in conjunction with the first stage portion of set 10 to separate platelet-rich plasma from whole blood and reinfuse packed red cells into the donor. During this separation procedure, anticoagulant is metered
30 into whole blood being withdrawn from the donor. After the PRP has been collected, the phlebotomy needle is removed from the donor and additional anticoagulant is delivered to the PRP. The first stage portion is then removed from the instrument, separated from the

- 13 -

second stage portion and discarded. The second stage portion of the set is then installed in the instrument H as shown in Fig. 3 to generate platelet concentrate from the platelet-rich plasma. The procedure of ultimately providing platelet concentrate will now be described in detail, including the known procedure steps such as disclosed in U.S. Patent No. 4,851,126 as well as the new method steps and apparatus for addition of anticoagulant.

Referring to Figures 2 and 4, the various tubings 11 of the first stage portion A are applied to instrument H as follows: blood line 14 is disposed in blood pump P1; lines 42 and 44 are disposed in clamps C5 and C2, respectively; line 54 is applied to pump P3 and line 56 is applied to pump P4. The reservoir 22 is mounted on the face of the instrument, by means not shown, and the separator 46 is disposed on the mount 88 with its upper end disposed in the motor cup 90 such that the drive rotor of separator 46 is coupled magnetically to the drive motor of the instrument. Platelet-rich plasma line 58 is disposed in hemoglobin detector 84 and clamp C1 and platelet-rich plasma container 60 is hung from a weight scale on a lower part of the instrument.

Divert line 104, which extends from the PRP line 58 to the compartment 26 at port 39 (Figure 4), is mounted in clamp C4. Alternatively, but not important for the purpose of the present invention, as seen in Figures 1 and 2 the divert line 104 may instead join the branch line 44 at Y-connector 41, for return to the compartment 26 at port 38.

Anticoagulant line 16 is disposed in anticoagulant pump P2 and is connected at one end to a supply of anticoagulant, i.e., supply container 20, for supplying anticoagulant via line 16 to blood line 14 adjacent the needle 12. The blood line 14 also extends through the air detector 86. The second stage portion is retained in its individual pouch B which is hung from an available hook on the instrument in an out-of-the-way location.

- 14 -

In operation, various procedures are followed under control of the microprocessor for performing certain instrument functions which need not be described herein. Referring to Figure 4, after set-up and following venepuncture performed on the donor and after priming of the separator and reservoir, the instrument, in conjunction with the first stage portion A, is ready to alternately collect whole blood from the donor and reinfuse packed red cells into the donor while whole blood is simultaneously and continuously supplied to the separation device to produce platelet-rich plasma and packed cells.

5 Thus, clamp C2 is opened, clamp C5 is closed and pumps P1, P2, P3 and P4 are actuated. Whole blood therefore flows through the needle 12 and blood line 14, through open clamp C2, and into whole blood compartment 26 via branch line 44 and inlet port 38 of reservoir 22.

Anticoagulant, such as known anticoagulant citrate dextrose solution Formula A (ACDA), is added to the whole blood by pump P2 via line 16 at its Y-connection with blood line 14. This known anticoagulant includes dextrose (hydrous), sodium citrate (hydrous) and citric acid (anhydrous). Other anticoagulants can also be used in accordance with medical guidelines for various anticoagulant formulations.

10 15 20

Closed clamp C5 prevents flow of anticoagulated blood into reinfusion line 42. Pump P3 pumps whole blood from compartment 26 through outlet port 30 via line 54 into separator 46 via inlet port 48. Red cells are pumped from separator 46 through outlet 50 via line 56 by pump P4 into reservoir compartment 24 through inlet port 36. Platelet-rich plasma flows from separator 46 via line 58 through hemoglobin detector 84 and open clamp C1 into collection container 60. Divert clamp C4 is closed. Thus, during collection anticoagulated whole blood is supplied to compartment 26 and separator 46 while packed cells are supplied to compartment 24 and platelet-rich plasma is supplied to container 60.

25 30

- 15 -

The system provides for the alternate collection of whole blood from the donor and reinfusion of packed cells or platelet-depleted plasma into the donor while separator 46 simultaneously and continuously receives anticoagulated whole blood for separation into the platelet-rich plasma and packed cells. To accomplish this, sensors, not shown, on the instrument face detect the level of fluids in the compartments 24, 26 of the reservoir 22. When the compartments are full, the microprocessor, in response to the detected signals, causes instrument H to change from its blood collection cycle to its reinfusion cycle.

Referring now to Figure 5, in the reinfusion cycle, clamp C2 is closed and clamp C5 is opened and the anticoagulant pump P2 is stopped. Pump P1 is reversed to pump packed cells from compartment 24 of reservoir 22 into the donor through needle 12. Pumps P3 and P4, however, continue to operate to respectively provide anticoagulated whole blood from the compartment 26 of reservoir 22 to separator 46 and to supply packed cells from separator 46 to compartment 24 of reservoir 22. When the packed cells and the supply of whole blood are substantially depleted from compartments 24 and 26, respectively, these low liquid levels are sensed. At that time, the microprocessor causes instrument H to change from its reinfusion cycle back to its blood collection cycle. Thus, clamp C2 is opened, clamp C5 is closed, pump P2 is started, and pump P1 is reversed to again begin the draw cycle illustrated in Figure 4, with anticoagulated whole blood flowing to the whole blood compartment 26, which has been substantially depleted of whole blood during the reinfusion cycle illustrated in Figure 5. It will be appreciated that during the alternate collection and reinfusion cycles, whole blood is continuously pumped from reservoir compartment 26 to separator 46 by pump P3 whereby separation is effected continuously. Thus, platelet-rich plasma (PRP) flows continuously from separator 46, while anticoagulated whole blood is continuously supplying separator 46.

- 16 -

In the preferred embodiments, PRP collection terminates when a preselected weight of PRP has been reached utilizing a weight scale 43. The preselected weight value may be selected by the operator for donor-specific reasons such as donor weight, donor age, etc.

5 When the preselected PRP weight value in the container 60 is reached, the instrument automatically transfers to a final return mode including purging the tubing 11 of all but a small amount of packed cells (e.g. about 10 mls). Then, the instrument automatically notifies the instrument operator to disconnect the
10 donor. The operator uses a hemostat 100 or other known clamp to close the tubing segment 102 that is disposed between the phlebotomy needle 12 and the connector 13 which joins anticoagulant supply line 16 and the blood line 14. The operator may then remove the phlebotomy needle from the donor's vein. The donor may rest and
15 then leave. The hemostat 100 is illustrated schematically in Figures 5 and 6.

Next, the operator activates an advance button 105 on the instrument H that notifies the microprocessor control in the instrument that the donor has been disconnected. The microprocessor
20 control then automatically advances the procedure into the new PRP - anticoagulant addition cycle illustrated in Figure 6, so as to deliver an additional amount of anticoagulant to the PRP in the container 60. This cycle is controlled by the microprocessor in the instrument. As seen in Figure 6, pumps P1, P2 and P3 are
25 activated. Pumps P1 and P2 pump at a speed of about 15 mls per minute, at most about 250 mls totally, of anticoagulant through line 16 into blood line 14 and, as in the draw cycle illustrated in Figure 4, clamp C2 is open and clamp C5 is closed so that pump P1
30 pumps anticoagulant from source 20 through branch line 44 into compartment 26 through the port 38. Input pump P3 pumps the anticoagulant from the compartment 26 into the separator 46 through tubing line 54 along with significant residual red cells in the tubing and reservoir. Pump P3 may operate at a speed of about 15

- 17 -

mls per minute, for example. Preferably output pump P4 is not operated. Therefore, additional packed cells accumulate within the separator 46. The rotor within the centrifugal separator 46, which normally operates in the range of approximately 2400 to 3600 rpm
5 during the separation procedure, here operates at a speed of approximately 2000 rpm.

As the anticoagulant mixed with the residual blood cells enter by line 54 into the separator 46, where additional red cells reside, the centrifugal force within the separator separates the
10 anticoagulant from these cells in the same manner that the separator operates to separate PRP from the donor's whole blood during the above-described separation procedure. The separated anticoagulant exits the separator 46 through port 52 and line 58, which is disposed within the hemoglobin detector 84.

15 The system has been stopped for a time period in order to enable the operator to disconnect the donor from the instrument and set. Thus, the efficiency of the separator 46 will initially be less than optimal when the PRP-anticoagulant addition cycle illustrated in Fig. 6 begins. Therefore, it is likely that the first aliquot of
20 anticoagulant flowing through line 58 during the PRP-anticoagulant addition step will have an unacceptably high concentration of red cells. If so, the hemoglobin detector 84, through the microprocessor control, will close the platelet line clamp C1 and open the divert clamp C4, thereby diverting the packed
25 cell/anticoagulant mix through divert tubing line 104 back into the reservoir compartment 26 via port 39, for subsequent recirculation into the separator 46 through the tubing line 54. As previously mentioned and as shown in Fig. 2, the divert line may alternatively join branch line 44 to reach compartment 26 via port 38.

30 After a short time period (approximately 30 seconds) the separator 46 will be operating with sufficient efficiency so as to meet the low hemoglobin standard set by the detector 84. Upon sensing the lower hemoglobin content, the detector 84 will instruct

- 18 -

the microprocessor to close clamp C4 and open clamp C1, thereby delivering the desired additional aliquot of anticoagulant to the platelet-rich plasma previously collected in the collection container 60.

5 By not operating the pump P4, the packed cells tend to remain in the separator, thereby lessening the volume of anticoagulant and therefore the time required to perform the PRP-anticoagulant addition step shown in Figure 6. The centrifugal separator itself has a low blood volume of about 15 mls. If the final tubing purge
10 performed immediately prior to donor disconnect leaves more than the desired volume of red cells in the set 10, this may result in higher pressure within the separator 46 than is desirable for the selected efficiency range of the separator during the PRP-anticoagulant addition step. If the pressure is higher than about 320 mmHg, the
15 pump P4 may be activated at a slow pumping rate, such as at a rate of 15 mls per minute, thereby returning some of the packed cells from the separator 46 into the reservoir compartment 24, through port 36, until the device pressure is released.

By means of the just described PRP-anticoagulant addition
20 procedure, the PRP receives the necessary nutrients and pH buffering for PRP storage, at least equivalent to that performed by prior art procedures where all anticoagulant is added to the whole blood during the draw cycle from the donor. In addition, this system permits the reduction of the amount of anticoagulant added to the
25 whole blood, with two very significant results: (1) increased platelet yield and (2) reduced chance of a citrate response in the donor.

First, it has been discovered that the decreased anticoagulant concentration in the whole blood being separated in the separator
30 during both the draw and reinfusion cycles illustrated in Figures 4 and 5 results in greater platelet yield, a highly desirable goal. Typically, with the Autopheresis-C® instrument operators have utilized eight or six percent anticoagulant level in the whole

- 19 -

blood. With the new, PRP-anticoagulant addition procedure, the anticoagulant added to the whole blood during the draw/separation cycle may be reduced, for example to a level of approximately 4 percent anticoagulant.

5 In this specification the anticoagulant levels indicate the percent anticoagulant by volume for anticoagulant-added whole blood. Stated differently, an 8% level means 8 parts anticoagulant to 92 parts whole blood, or 8 parts anticoagulant in 100 parts anticoagulated whole blood. This is the standard system for
10 comparing anticoagulant levels in the medical community. Furthermore, while anticoagulant levels in separated blood fractions vary, comparisons have typically been made by looking at the anticoagulant level in the whole blood to be separated.

15 The level of anticoagulant added to blood components by the instrument A can be precisely controlled by the use in the instrument of the pump calibration system disclosed in U.S. Patent No. 4,769,001, assigned to the assignee of the present invention.

20 Tables I and II illustrate the improvement in platelet yield in the separated PRP achieved by lowering the anticoagulant level supplied to the whole blood during the draw/separation cycle of Figure 4, made possible by the later, PRP-anticoagulant addition cycle.

25

30

- 20a -

TABLE I
8% ACDA Anticoagulant

Donor	PRP Efficiency Total <u>Collected (%)</u>	Precount Platelet		Platelet Concentration In Collected PRP (/ul)
		Concentration In Donor's Anticoagulated <u>Whole Blood (/ul)</u>		
1	45	198200	507600	
2	50	251400	686000	
3	41	207667	540667	
4	40	299333	697667	
5	46	273000	703286	
6	43	182200	465000	
7	37	306800	628200	
8	36	228250	660250	
9	39	238000	510000	
10	37	202500	596500	
11	48	233000	645000	
12	45	178000	406000	
13	45	298750	798500	
14	41	324800	798600	

N = Total Donors

x = Mean PRP Efficiency

SD = Standard Deviation

SUBSTITUTE SHEET

N	14	14	14
x	42	244421	617376
SD	4	48947	119197
15			
16			
17			
18			
N			
x			
SD			

N = Total Donors
x = Mean PRP Efficiency
SD = Standard Deviation

- 20c -

6% ACDA Anticoagulant

Donor	PRP Efficiency Total <u>Collected (%)</u>	Precount Platelet		Platelet Concentration In Collected PRP (/ul)
		Concentration In Donor's Anticoagulated Whole Blood (/ul)		
1	46	220040	584400	
2	50	271750	828750	
3	55	211250	655250	
4	33	428000	1095000	
5	49	280000	744000	
6	69	163000	550000	
7	33	330000	671000	
8	39	314000	899000	
9	46	252000	665000	
10	45	214000	665000	
11	48	233667	714667	
12	49	189500	502000	
13	45	328000	929500	
14	51	316750	919750	

N = Total Donors

x = Mean PRP Efficiency

SD = Standard Deviation

SUBSTITUTE SHEET

- 20d -

N	14	14	14
x	47	267997	744523
SD	9	70576	168231
15	48	191000	594500
16	53	363333	787000
17	49	197000	566333
18	38	238000	531000
N	4	4	4
x	47	247333	619708
SD	6	80104	114514

N = Total Donors
 x = Mean PRP Efficiency
 SD = Standard Deviation

- 20e -

4% ACDA Anticoagulant

Donor	PRP Efficiency Total	Precount Platelet		Platelet Concentration In Collected PRP (/ul)
		Concentration In Donor's Anticoagulated Whole Blood (/ul)	Concentration In Collected PRP (/ul)	
1	49	244000	704672	
2	52	285500	972931	
3	51	237333	709256	
4	43	441500	1121648	
5	43	284000	652000	
6	57	222000	468000	
7	40	367000	853889	
8				
9	58	282000	855000	
10	44	217500	723188	
11				
12	44	206500	516712	
13	45	318000	951500	
14	49	362000	1034000	

N = Total Donors
 x = Mean PRP Efficiency
 SD = Standard Deviation

SUBSTITUTE SHEET

- 20f -

N	12	12	12
x	48	288944	796900
SD	6	71794	202818
15	58	161500	617922
16	56	226500	621272
17	45	180000	566871
18	65	238000	773471
N	4	4	4
x	56	201500	644884
SD	8	36604	89266

N = Total Donors
 x = Mean PRP Efficiency
 SD = Standard Deviation

- 21 -

TABLE II

		<u>% Change in Yield Over 8%</u>	
	<u>Donor</u>	<u>At 6%</u>	<u>At 4%</u>
5	1	15	39
	2	21	42
	3	21	31
	4	57	61
	5	6	-7
10	6	18	1
	7	7	36
	8	36	--
	9	30	68
	10	11	21
15	11	11	--
	12	24	27
	13	16	19
	14	15	29
	Average	21	31
		<u>% Change in Yield Over 6%</u>	
	<u>Donor</u>		<u>At 4%</u>
20	15	--	3
	16	--	8
	17	--	0
	18	--	46
25	Average	--	14

Referring to Table I, PRP efficiency is a relevant parameter to show improvement in platelet yield. To calculate PRP efficiency, the volume of platelet rich plasma collected is multiplied by the platelet concentration in that platelet rich plasma, the product forming the numerator. The denominator used in determining PRP efficiency is the product of the platelet concentration in the donor's anticoagulated whole blood (the precount) times the volume of blood that was processed in the procedure.

- 22 -

In the fourteen donors 1 through 14, mean PRP efficiency improved from 42 to 47 to 48 percent at anticoagulant levels of 8 percent, 6 percent, and 4 percent respectively.

Donors 15 through 18 were run at anticoagulant levels of 6 percent and 4 percent resulting in a mean PRP efficiency of 47 percent and 56 percent respectively.

The data could be presented without platelet concentration in both precount and PRP, illustrating only the effect of the anticoagulant concentration on PRP efficiency. However, this would overlook the benefit of less anticoagulant diluting the blood less, thereby allowing the system to start with a higher precount.

Table II is a summary illustrating the percentage change in platelet yield at different anticoagulant levels. Platelet yield is the platelet count in the PRP. Yield comparisons are made utilizing constant volume of PRP. When collecting platelets, it is desirable to maximize platelet yield.

We have found that by lowering the whole blood anticoagulant level from 8 percent to 6 percent, there is an increase in platelet yield of approximately 21 percent. Approximately half of the 21 percent increase is due to less fluid volume because of less anticoagulant and about half of the 21 percent increase is due to other factors, currently unexplained, which may be occurring within the separator because of the reduced anticoagulant level. Similarly, a reduction from 8 percent to 4 percent anticoagulant in the withdrawn whole blood results in an approximately 31 percent improvement in platelet yield, approximately half of which results from the reduced fluid volume. The other half of the improvement is caused by other reasons.

The second significant beneficial effect of lowering the anticoagulant level in the whole blood is that it greatly reduces the likelihood of an adverse citrate reaction in the donor. Citrate reaction is a known condition that occurs when the amount of anticoagulant returned to the donor becomes too high. This value

- 23 -

differs from donor to donor. The problem is exacerbated during a platelet collection procedure, as opposed to plasma collection, for the following reasons.

Anticoagulant is soluble in plasma. In any manual or automated
5 plasma collection procedure, i.e. a procedure wherein it is desirable to have the platelets remain with the packed cells (plasma collection) as opposed to remaining with the plasma (for e.g. platelet collection), the hematocrit (i.e. the packed cell concentration) is typically higher than with a platelet collection
10 procedure such as has been set forth above. Typically, with the Autopheresis-C® system, an expected hematocrit value for packed cells returned to the donor in a plasma collection procedure is about 70. However, in a platelet collection procedure as described above, the resulting hematocrit value for the packed cells is
15 typically less, on the order of about 55 for a typical donor.

Stated differently, the percentage that comprises plasma of the entire packed cell suspension returned to the donor in the platelet collection procedure is more than the percentage of plasma in the packed cell suspension returned to the donor in a plasma collection
20 procedure. Thus, because anti-coagulant is plasma-soluble, for a given amount of anticoagulant added to the whole blood, the amount of anticoagulant in the packed cell suspension returned to the donor in a platelet collection procedure is higher than in a plasma collection procedure.

This alone is a significant reason for why adverse, citrate reactions are more likely to occur in platelet collection procedures than in plasma collection procedures. The problem becomes more egregious in platelet collection operations performed by prior art
25 methods because of the typically higher anticoagulant levels in the whole blood which were sought in order to obtain a higher
30 anticoagulant level in the platelet-rich plasma, the goal being to meet previously described storage condition requirements for the platelet concentrate.

- 24 -

The new, PRP-anticoagulant addition step set forth herein satisfies the storage requirements for collected platelets as achieved by the prior art, while providing the additional benefits of increased platelet yield and reduced incidence of citrate
5 reaction in the donor.

These benefits are achieved with the new method described above, (1) even though most blood separation procedures generate stress on the platelets so that the platelets exiting the separation chamber are partially activated, thereby requiring sufficient anticoagulant
10 to eliminate clotting which otherwise occurs; and (2) even though in platelet collection procedures, such as the procedure described above, significant numbers of platelets, partially activated, are returned with the red cells to the donor.

Thus, the PRP-anticoagulant addition step permits adding about 4
15 percent or less anticoagulant to the donor's whole blood, which is just enough to sufficiently anticoagulate the system and yet enjoy the high performance and platelet yield resulting from such a low anticoagulant level. The subsequent addition of anticoagulant to the PRP permits adequate storage of the platelet concentrate product
20 after separation from the plasma.

While Figure 6 and the accompanying description set forth a preferred embodiment for adding anticoagulant to the collected PRP as the PRP-anticoagulant addition method, in particular by routing anticoagulant through the separation chamber 46, it will be
25 appreciated that other means can be provided for accomplishing the addition of anticoagulant to the collected PRP. For example, a less preferred, alternate embodiment is set forth in phantom line in Fig. 6. In the alternate embodiment, a Y-connector 114 is disposed in the anticoagulant line 16 downstream of pump P2. Another
30 Y-connector 116 is disposed in the PRP outlet line 58 downstream of the hemoglobin connector 84. A tubing segment 118 is disposed between the two Y-connectors. An associated hardware clamp 120 selectively closes and opens the tubing segment 118, for the

- 25 -

selective addition of anticoagulant to the container 60 through the tubing segment 118. This sort of configuration, while providing a more direct routing of anticoagulant to the container 60, results in a change to the disposable which is otherwise not needed as well as the addition of an extra clamp in the hardware. In addition, such a configuration does not take advantage of separating the small aliquot of remaining blood in the reservoir 22, unlike the preferred procedure as set forth in Figure 6, wherein the anticoagulant in the PRP-anticoagulant addition procedure runs through the separation chamber 46.

Still further improvements are obtained by means of the blood processing system illustrated in Figure 7. Here, like numbers are used for like components compared to the previous embodiment. In Figure 7 there is shown a set 106 that is utilized with the microprocessor-controlled instrument H.

The set 106 includes the separator 46, reservoir 22, PRP collection container 60, phlebotomy needle 12 and tubing 11 as set forth in the embodiment of Figures 1 through 6. A Y-connection 108 is disposed in the anticoagulant tubing 16 between the anticoagulant supply 20 and the pump P2. A Y-connection 110 is provided in tubing line 56 between the separator outlet port 50 and the output pump P4. Secondary anticoagulant line 112 communicates between anticoagulant line 16 and line 56 via Y connectors 108 and 110. The instrument H includes an additional pump P5, which serves as a secondary anticoagulant pump.

Set 106 is installed in the instrument H as set forth previously. Additionally, tubing line 112 is installed in the secondary anticoagulant pump P5. Operation of the set 106 during a blood separation procedure is best understood by reference to Figures 4 and 5 as well as Figure 7. Primary anticoagulant pump P2 is a discontinuous pump in that it operates only during the draw cycle illustrated in Figure 4. In contrast, the secondary anticoagulant pump is a so-called continuous pump in that it

- 26 -

operates, under microprocessor control, during both the draw and separation cycle illustrated in Figure 4 and the reinfusion and separation cycle illustrated in Figure 5. During both draw and reinfusion, the secondary anticoagulant pump P5 meters anticoagulant by pumping it from the supply source 20 through tubing 112 into the tubing line 56. Anticoagulant entering the tubing line 56 from the tubing line 112 is pumped by pump P4 into compartment 24 of the reinfusion reservoir 22, along with packed cells exiting the separator 46.

10 The secondary anticoagulant line 112 and pump P5 facilitate still another step in promoting different functional characteristics in the blood fractions being separated during an automated blood component separation procedure. Compared to the previous embodiment illustrated in Figure 6, the separation system and method
15 illustrated in Figure 7 permits a still further lowering of the amount of anticoagulant which must be added to the whole blood at connection 13 when the blood is withdrawn from the donor, thereby facilitating even greater platelet yields in the separator 46. Here, the anticoagulant level in the whole blood may be lowered to
20 an amount which would be insufficient to prevent clotting in the packed cells exiting the separator 46 through tubing 56, but for the secondary anticoagulant tubing 112 and pump P5.

PRP collection procedures were conducted at a 3 percent anticoagulant level in the whole blood previously withdrawn from the donor. It is believed that reduction of the anticoagulant level to
25 even this low level results in still further improvement in platelet yield when compared to the 4 percent anticoagulant level for example, which is itself an improvement resulting from the PRP-anticoagulant addition step illustrated in Figure 6. The anticoagulant level of 3
30 percent appears to be acceptable for whole blood withdrawal during the separation procedure, in order to prevent clotting.

However, this level is insufficient for the returned packed cells exiting the separator 46. This added demand for anticoagulant may be due to the presence of white cells in the packed cells or may

- 27 -

be due to the above described platelet activation occurring during the separation step in the separator 46. As noted previously, a significant number of platelets are returned with the packed cells, even during PRP collection procedure. The addition of secondary
5 anticoagulant through tubing line 112 prevents such clotting. Anticoagulant is preferably added through tubing line 112 at a level sufficient to bring the anticoagulant ratio up to about four to six percent in the returned packed cells. Thus, the primary anti-coagulant pump P2 may in a preferred embodiment supply anticoagulant
10 at a 3 percent or less level (perhaps even down to zero). The secondary anticoagulant pump P5 could supply anticoagulant at a 1 percent or more level, providing just sufficient anticoagulant to prevent clots from forming in the reinfusion circuit, but not enough anticoagulant to produce citrate toxicity in the donor.

15 The addition of anticoagulant to the packed cells illustrated in Figure 7 permits the lower anticoagulant levels in blood entering the separator, for even greater platelet yield. The secondary anticoagulant addition disclosed herein and best illustrated in Figure 7 may be employed with or without the PRP-anticoagulant
20 addition procedure for desired PRP collection, separation and storage requirements that is disclosed herein and illustrated in Figure 6.

While the testing for the lower acceptable limit of anticoagulant added to whole blood in an automated blood separation
25 procedure has not yet been performed for various reasons, including questions of human efficacy and different regulatory requirements, it may be that the anticoagulant level added to the whole blood removed from the donor may be reduced to zero. Such a reduction may in fact continue to increase platelet yields from the separator 46.
30 Because clotting typically takes several minutes, the residence time of whole blood from the needle 112 through the reservoir 22 and separator 46 may be short enough so that the first addition of anticoagulant may in fact be made through the tubing line 112 downstream of the separator, eliminating any need for anticoagulant

- 28 -

addition at the Y-connection 13. If anticoagulant added to just-removed whole blood by pump P2 were further reduced from three percent, it is expected that the amount of anticoagulant added to the just-separated packed cells by pump P5 would need to be increased.

The ability to reduce anticoagulant levels in the whole blood and packed cells may be further facilitated by means of an improved phlebotomy needle design disclosed in the concurrently filed application of Ritchey et al entitled "Blood Component Needle Assembly for Reduced Coagulation Response" U.S.S.N. 7/538,812, assigned to the assignee of the present invention. The improved needle design resists clotting in and adjacent to the needle better than prior art needle designs.

In order to provide a complete description, a review of the second stage of the set 10, 106 will now be provided.

After the donor has been disconnected from the set 10, 106 and after the anticoagulant addition procedure set forth in Figure 6, if utilized, the first stage portion of the set 10 is removed from the instrument H by the operator.

The platelet-rich plasma line 58 is then heat-sealed just above the inlet port to container 60. The first stage portion may then be cut away above the seal and discarded. The second stage portion B, including container 60 with the platelet-rich plasma therein, is then applied to instrument H, as illustrated in Figure 3. It will be appreciated that in the preferred embodiment, the same particular instrument H may be used to generate PPP and platelet concentrate with set portion B as is used to generate the PRP using set portion A, although it will be recognized that this separate operation to produce the platelet concentrate may be performed on a separate instrument. Alternatively, a machine may be utilized in which set portions A and B are installed at the same time, and for example in which two needles are used (B^1), for continuous draw and continuous reinfusion to the donor.

- 29 -

The container 60, the platelet-poor plasma container 74 and the platelet concentrate container 78 are hung from hooks conveniently disposed along the underside of the instrument. Separator 62 is disposed on mounting 88 and its upper end is disposed in mounting
5 cup 90 for magnetic coupling with the drive motor of the instrument. Tubing 72 interconnecting the platelet-rich plasma container 60 and the separator 62 is disposed in pump P1 and the ultrasonic air detector 86. Tubing 76 is disposed in pump P3, while tubing 80 is disposed in the hemoglobin detector 84 and clamp C1.

10 To produce platelet concentrate, the microprocessor controls the instrument to actuate pump P1 to pump platelet-rich plasma from container 60 into separator 62. The rotary membrane filter of separator 62 causes the platelet-rich plasma to separate into platelet-poor plasma and platelet concentrate. The platelet-poor
15 plasma is pumped by the pump P3 from the separator 62 via line 76 for collection in the container 74. The desired platelet concentrate flows from the separator 62 via line 80 through the hemoglobin detector 84 into platelet concentrate container 78.

The instrument is programmed such that it knows the weight of
20 the platelet-rich plasma collected in the container 60 during the first stage. Additionally, the operator may input the instrument with the desired quantity of platelet concentrate. The pumps are controlled by the microprocessor such that the desired quantity of product is provided in the platelet concentrate collection container
25 78. The end of the procedure is determined when the ultrasonic air detector 86 senses air in the tube 72, thereby terminating the end of the platelet concentration cycle using the second stage of the set 10, 106. If the final weight of the platelet concentrate suspension is low, the instrument can pump platelet-poor plasma from
30 container 74 back through the device 62 and into the platelet concentrate container 78. If the final weight of the platelet concentrate suspension is high, the instrument can pump more platelet concentrate from container 78 back through separator 62

- 30 -

into the platelet-rich plasma container 60 and then reprocess the fluid in container 60 using the procedure set forth above.

Significantly, the platelets separated by separation device 62 require no incubation period or resuspension procedure to produce
5 infusible platelets. This greatly reduces labor and improves the quality of the product.

In accordance with the present disclosure, it will be appreciated that improved apparatus and methods have been provided for adding anticoagulant at different stages of an automated blood
10 component separation procedure, in order to achieve desired nutrients and pH buffering in the platelet concentrate; to lower the amount of anticoagulant added to whole blood in order to avoid citrate toxicity to the donor; to lower anticoagulant in the blood, thereby achieving greater platelet yield; to lower anticoagulant
15 levels in packed cells returned to the donor, thereby offsetting the otherwise higher anticoagulant requirements of a platelet collection procedure, as opposed to a plasma collection procedure; and, in the set illustrated in Figure 7, to permit still further lowering of the anticoagulant level in the whole blood for both improved donor
20 reaction and improved platelet yield, at anticoagulant levels which, but for the set 106 and the accompanying method, would be insufficient to prevent clotting in the packed cells. It is believed that by adding anticoagulant to packed cells soon after their exit from the separator, it may in fact be possible to reduce
25 the anticoagulant level in whole blood entering the separator to zero, which it is believed should lead to further improvements in platelet yield.

While the above disclosure has been intended to describe the preferred embodiments, it will be understood that the present
30 invention is not limited to same, but is instead intended to include various further modifications included within the spirit and scope of the appended claims.

- 31 -

What is claimed is:

1. A method for promoting different functional characteristics in different blood components during an automated blood component separation procedure, the steps comprising:
 - (a) providing an automated instrument for blood component separation;
 - (b) providing a set including a blood component separator and means defining a flow path;
 - 10 (c) installing the set in the instrument;
 - (d) separating, in the separator, the blood introduced into the set, into two or more components;
 - (e) adding quantities of the same preselected fluid to at least two different blood components through the fluid flow path
 - 15 of the set, to promote said different functional characteristics in different blood components.
2. The method as in claim 2, the steps further comprising;
adding the preselected fluid to a third blood component,
20 separate from said first and second component fluid addition steps.
3. The method in accordance with claim 1, the steps further comprising at least one of (a) returning at least part of the second component to the donor; and (b) transferring at least part of the
25 second component to a storage container.
4. The method in accordance with claim 1, wherein said first blood component is whole blood and said first component fluid addition
30 step is made by adding the preselected fluid to the whole blood in the flow path means upstream of the separator.

- 32 -

5. A system including an automated, blood component separation instrument and a set installed in said instrument, said set including a blood component separator and flow path means, wherein said instrument is programmed for conducting the blood separation and preselected fluid addition steps in accordance with Claim 1.

6. A method for promoting different functional characteristics in different blood components during an automated blood component separation procedure, the steps comprising:

- 10 (a) providing an automated instrument for blood component separation;
- (b) providing a set including a blood component separator and means defining a flow path;
- (c) installing the set in the instrument;
- 15 (d) separating, in the separator, the blood introduced into the set, into two or more components;
- (e) adding anticoagulant to at least two different blood components, through the fluid flow path of the set, to promote the different functional characteristics in different blood components.
- 20

7. The method in accordance with claim 6, said anticoagulant addition step comprising;

- 25 (a) adding anticoagulant to whole blood at a location in the defined flow path upstream of the separator; and
- (b) adding anticoagulant to platelet rich plasma separated out of the whole blood by the separator.

8. The method in accordance with claim 6, said anticoagulant addition step comprising adding anticoagulant to platelet-rich plasma separated out of whole blood by the separator.

30

- 33 -

9. A method for promoting different functional characteristics in different blood components during an automated blood component separation procedure, the steps comprising:

5 (a) providing an automated instrument for blood component separation;

(b) providing a set including a blood component separator and means defining a flow path;

(c) installing the set in the instrument;

10 (d) separating, in the separator, the blood introduced into the set, into two or more components, one of which is platelet-rich plasma;

(e) adding anticoagulant to platelet-rich plasma separated out of whole blood by the separator.

15 10. The method in accordance with claim 9, including promoting storage of the PRP by said addition of anticoagulant thereto.

20 11. The method in accordance with claim 9, wherein said PRP anticoagulant addition step permits the level of anticoagulant in whole blood to be lower than the level would be without said PRP-anticoagulant addition step, thereby promoting greater platelet yield in the platelet component output of the separator.

25 12. The method in accordance with claim 11 wherein greater platelet yield in the platelet rich plasma component output of the separator is promoted by said PRP-anticoagulant addition step.

13. A method for increasing platelet yield in an automated blood component separation procedure, the steps comprising:

30 (a) providing an automated instrument for blood component separation;

(b) providing a set including a blood component separator and means defining a flow path;

- 34 -

(c) installing the set in the instrument;

(d) separating, in the separator, the blood introduced into the set, into two or more components;

5 (e) adding anticoagulant to whole blood at a location in the defined flow path upstream of the separator, at a level less than about eight percent; and

(f) adding additional anticoagulant to a collected, separated platelet component at a location in the flow path downstream of the separator.

10

14. A method for promoting different functional characteristics in different blood components during an automated blood component separation procedure, the steps comprising:

15 (a) providing a microprocessor-controlled blood separation system including:

(i) whole blood access means, including flow path means between a source of whole blood and a reservoir,

(ii) a reservoir,

(iii) a blood component separator,

20 (iv) a reservoir flow path means communicating between the reservoir and the separator,

(v) first fraction flow path means extending downstream from the separator,

25 (vi) red cell flow path means communicating between the separator and a reservoir,

(vii) a plurality of pumps to move the blood and blood fractions through the various flow path means;

(b) pumping whole blood from the whole blood access means to the reservoir;

30 (c) pumping blood from the reservoir to the separator;

(d) transferring the first fraction out of the separator, through the first fraction flow path means;

- 35 -

(e) transferring red cells from the separator to the reservoir through the red cell flow path means;

(f) pumping anticoagulant from an anticoagulant source into whole blood in the access means flow path upstream of the reservoir; and

(g) subsequent to withdrawing a preselected amount of first fraction from the whole blood, pumping anticoagulant from the anticoagulant source through the flow path means into the separated first fraction.

10

15. The method in accordance with claim 14, wherein the step of pumping anticoagulant to the separated first fraction includes pumping the anticoagulant through the access means, into the reservoir.

15

16. The method in accordance with claim 15, wherein the step of pumping anticoagulant to the separated first fraction includes pumping the resulting reservoir contents into the separator, said method further including transferring anticoagulant out of the separator to the separated first fraction and transferring additional red cells from the separator to the reservoir.

20

17. The method in accordance with claim 14, the steps further comprising:

(a) providing a hemoglobin detector in the first fraction flow path means;

(b) utilizing the hemoglobin detector to determine whether the first fraction is sufficiently free of red cells;

(c) diverting back to the reservoir any first fraction which is not sufficiently free of red cells in accordance with a pre-set standard.

30

- 36 -

18. A method for increasing platelet yield in an automated blood component separation procedure, the steps comprising:

- 5 (a) providing an automated instrument for blood component separation;
- (b) providing a set including a blood component separator and means defining a flow path;
- (c) installing the set in the instrument;
- (d) separating, in the separator, the blood introduced into
10 the set, into two or more components; and
- (e) adding anticoagulant to at least one separated component at a location in the flow path downstream of the separator.

19. A method for promoting different functional characteristics in
15 different blood components during an automated blood component separation procedure, the steps comprising:

- (a) providing an automated instrument for blood component separation;
- (b) providing a set including a blood component separator
20 and means defining a flow path;
- (c) installing the set in the instrument;
- (d) separating, in the separator, the blood introduced into the set, into two or more component;
- (e) adding anticoagulant to whole blood upstream of the
25 separator;
- (f) adding a second fluid to a separator- created blood component, to enhance the functional characteristics thereof.

20. An automated instrument for practicing the method of claim 1
30 including:

- (a) means for receiving the set;
- (b) pump means for adding quantities of the preselected fluid to at least two different blood components; and

- 37 -

(c) microprocessor control means for automatically governing said pump means for the addition of the preselected fluid to the at least two different blood components.

- 5 21. Apparatus, comprising an automated blood component separation machine in combination with a disposable, single use blood separation set mounted on the machine, for conducting the blood separation and anticoagulant addition steps of Claim 6.

10

15

20

25

30





FIG. 1

SUBSTITUTE SHEET



SUBSTITUTE SHEET






FIG. 3

4/7

FIG. 4


SUBSTITUTE SHEET

5/7

FIG. 5

SUBSTITUTE SHEET


FIG. 6



SUBSTITUTE SHEET

7/7

FIG. 7



SUBSTITUTE SHEET

INTERNATIONAL SEARCH REPORT

International Application No. **PCT/US91/04193**

I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all) ⁶		
According to International Patent Classification (IPC) or to both National Classification and IPC		
IPC(5): B01D 21/30		
US CL.: 210/739		
II. FIELDS SEARCHED		
Minimum Documentation Searched ⁷		
Classification System	Classification Symbols	
US	210/85,96.1,143,206,257.1,321.67,321.68,739,767,782,805 604/4,5,6	
Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in the Fields Searched ⁸		
III. DOCUMENTS CONSIDERED TO BE RELEVANT ⁹		
Category [*]	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³
Y	US, A, 4,806,247 (SCHOENDORFER) 21 February 1989 See entire document.	1-13,18-21
Y	US, A, 4,708,714 (LARSSON) 24 November 1987 See entire document.	1-21
Y	US, A, 4,851,126 (SCHOENDORFER) 25 July 1989	1-21
A	US, A, 4,776,964 (SCHOENDORFER) 11 October 1988	1-21
<p>[*] Special categories of cited documents: ¹⁰</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"&" document member of the same patent family</p>		
IV. CERTIFICATION		
Date of the Actual Completion of the International Search		Date of Mailing of this International Search Report
22 JULY 1991		09 AUG 1991
International Searching Authority		Signature of Authorized Officer
ISA/US		<i>W. Gary Jones</i> W. GARY JONES