




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5 : H04N 7/12		A1	(11) International Publication Number: WO 91/19393 (43) International Publication Date: 12 December 1991 (12.12.91)
(21) International Application Number: PCT/US91/03734			(74) Agents: MELLER, Michael, N. et al.; M.N. Meller & Associates, P.O. Box 2198, Grand Central Station, New York, NY 10163 (US).
(22) International Filing Date: 29 May 1991 (29.05.91)			
(30) Priority data: 9012326.6 1 June 1990 (01.06.90) GB			(81) Designated States: AT (European patent), AU, BB, BE (European patent), BF (OAPI patent), BG, BJ (OAPI patent), BR, CA, CF (OAPI patent), CG (OAPI patent), CH (European patent), CI (OAPI patent), CM (OAPI patent), DE (European patent), DK (European patent), ES (European patent), FI, FR (European patent), GA (OAPI patent), GB (European patent), GN (OAPI patent), GR (European patent), HU, IT (European patent), JP, KP, KR, LK, LU (European patent), MC, MG, ML (OAPI patent), MN, MR (OAPI patent), MW, NL (European patent), NO, PL, RO, SD, SE (European patent), SN (OAPI patent), SU, TD (OAPI patent), TG (OAPI patent), US.
(71) Applicant (for all designated States except US): THOMSON CONSUMER ELECTRONICS, INC. [US/US]; 600 North Sherman Drive, Indianapolis, IN 46201 (US).			
(72) Inventors; and			
(75) Inventors/Applicants (for US only) : CHRISTOPHER, Todd, J. [US/US]; 1402 S. Kitley Avenue, Indianapolis, IN 46203 (US). HORLANDER, Karl, Francis [US/US]; 1226 North Dequincy, Indianapolis, IN 46201 (US). SAEGER, Timothy, William [US/US]; 8318 Nashau Drive, Indianapolis, IN 46260 (US).			
			Published With international search report.

(54) Title: TWO STAGE INTERPOLATION SYSTEM



(57) Abstract

A two stage interpolation system provides greater bandwidth for signals compressed and expanded by interpolation, such as video signals displayed in a zoom or enlarged mode. A finite impulse response filter (391) generates from a first signal of digital samples a second signal of digital samples representing signal points between the samples of the first signal. The first signal is delayed. The second signal and the delayed first signal are interleaved by a multiplexer (393) to produce a third signal of digital values having a sample density twice that of the first signal. A compensated variable interpolator (394) derives from the third signal a fourth signal of digital samples in which the frequency content of information represented by the first signal has been changed. In the case of enlarging the picture represented by a video signal, the video signal can be truncated in a FIFO line memory (395), prior to being delayed and processed by the finite impulse response filter (391). The compensated variable interpolator (394) can be controlled to provide selected ratios of compression or expansion.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MG	Madagascar
AU	Australia	FI	Finland	ML	Mali
BB	Barbados	FR	France	MN	Mongolia
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinea	NL	Netherlands
BJ	Benin	GR	Greece	NO	Norway
BR	Brazil	HU	Hungary	PL	Poland
CA	Canada	IT	Italy	RO	Romania
CF	Central African Republic	JP	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SN	Senegal
CI	Côte d'Ivoire	LI	Liechtenstein	SU	Soviet Union
CM	Cameroon	LK	Sri Lanka	TD	Chad
CS	Czechoslovakia	LU	Luxembourg	TG	Togo
DE	Germany	MC	Monaco	US	United States of America

TWO STAGE INTERPOLATION SYSTEM

The invention relates to the field of televisions, for example those televisions having a wide display format ratio screen, which must interpolate video data to implement various display formats.

5 Most televisions today have a format display ratio, horizontal width to vertical height, of 4:3. A wide format display ratio corresponds more closely to the display format ratio of movies, for example 16:9. The invention is applicable to both direct view televisions and projection televisions.

10 Televisions having a format display ratio of 4:3, often referred to as 4 X 3, are limited in the ways that single and multiple video signal sources can be displayed. Television signal transmissions of commercial broadcasters, except for experimental material, are broadcast with a 4 X 3 format display ratio. Many viewers find the 15 4 X 3 display format less pleasing than the wider format display ratio associated with the movies. Televisions with a wide format display ratio provide not only a more pleasing display, but are capable of displaying wide display format signal sources in a corresponding wide display format. Movies "look" like movies, not 20 cropped or distorted versions thereof. The video source need not be cropped, either when converted from film to video, for example with a telecine device, or by processors in the television.

25 Televisions with a wide display format ratio are also suited to a wide variety of displays for both conventional and wide display format signals, as well as combinations thereof in multiple picture displays. However, the use of a wide display ratio screen entails numerous problems. Changing the display format ratios of multiple signal sources, developing consistent timing signals from asynchronous but simultaneously displayed sources, switching 30 between multiple sources to generate multiple picture displays, and providing high resolution pictures from compressed data signals are general categories of such problems. Such problems are solved in a wide screen television according to this invention. A wide screen television according to various inventive arrangements is capable of 35 providing high resolution, single and multiple picture displays, from

single and multiple sources having similar or different format ratios, and with selectable display format ratios.

Televisions with a wide display format ratio can be implemented in television systems displaying video signals both at 5 basic or standard horizontal scanning rates and multiples thereof, as well as by both interlaced and noninterlaced scanning. Standard NTSC video signals, for example, are displayed by interlacing the successive fields of each video frame, each field being generated by a raster scanning operation at a basic or standard horizontal 10 scanning rate of approximately 15,734 Hz. The basic scanning rate for video signals is variously referred to as f_H , $1f_H$, and $1H$. The actual frequency of a $1f_H$ signal will vary according to different video standards. In accordance with efforts to improve the picture 15 quality of television apparatus, systems have been developed for displaying video signals progressively, in a noninterlaced fashion. Progressive scanning requires that each displayed frame must be scanned in the same time period allotted for scanning one of the two fields of the interlaced format. Flicker free AA-BB displays require that each field be scanned twice, consecutively. In each case, the 20 horizontal scanning frequency must be twice that of the standard horizontal frequency. The scanning rate for such progressively scanned or flicker free displays is variously referred to as $2f_H$ and $2H$. A $2f_H$ scanning frequency according to standards in the United States, for example, is approximately 31,468 Hz.

25 The wide screen television according to various inventive arrangements can expand and compress video in the horizontal direction by using adaptive interpolator filters. In the case of a format display of side by side pictures of comparable size, for example, one of the video signals must be compressed and the other 30 must be enlarged. In the case of a zoom feature, one of the signals is first truncated, and then expanded. The interpolators for the luminance components of the main and auxiliary signals may be skew correction filters, of the kind described in U.S. Patent No. 4,694,414- Christopher. A four point interpolator as described 35 therein, for example, comprises a two point linear interpolator and an associated filter and multiplier connected in cascade to provide

amplitude and phase compensation. In total, four adjacent data samples are used to calculate each interpolated point. The input signal is applied to the two-point linear interpolator. The delay imparted to the input is proportional to the value of a delay control signal (K). The amplitude and phase errors of the delayed signal are minimized by the application of a correction signal obtained by an additional filter and multiplier connected in cascade. This correction signal provides peaking which equalizes the frequency response of the two point linear interpolation filter for all values of (K). The original four point interpolator is optimized for use with signals having a pass band of .25 fs, where fs is the data sample rate.

Alternatively, and in accordance with inventive arrangements, both channels can use what is termed a two stage interpolative process. The frequency response of the original variable interpolation filter can be improved by using such a two stage process. This process is hereinafter referred to as a two stage interpolator. A two stage interpolator according to an inventive arrangement comprises a $2n+4$ tap finite impulse response (FIR) filter with fixed coefficients and a four point variable interpolator. The FIR filter output is located midway between the input pixel samples. The output of the FIR filter is then combined by interleaving with the original data samples, which are delayed, to create an effective $2fs$ sample rate. This is a valid assumption for frequencies in the pass band of the FIR filter. The result is that the effective pass band of the original four point interpolator is significantly increased.

The compensated variable interpolation filter of the prior art provides accurately interpolated samples as long as the frequency components of the signal are no greater than approximately one fourth the sample rate, .25 fs. The two-stage approach can be used for signals having frequency components substantially greater than .25 fs. In accordance with inventive arrangements, a finite impulse response filter generates from a first signal of digital samples a second signal of digital samples representing signal points between the samples of the first signal. The first signal may be, for

example, a video signal defined by a data stream of pixel values. The first signal is delayed, but otherwise substantially unmodified. The second signal and the delayed first signal are interleaved, for example by a multiplexer, to produce a third signal of digital values

5 having a sample density twice that of the first signal. A compensated variable interpolator derives from the third signal a fourth signal of digital samples in which the frequency content of information represented by the first signal has been changed. The frequency content can be compressed or expanded. The first signal

10 can have frequency components as high as approximately 40% of the sampling rate for the first signal without significant reduction of bandwidth in the fourth signal, even when expanded. In the case of enlarging the picture represented by a video signal, the video signal can be truncated, for example in a FIFO line memory, prior to being

15 delayed and processed by the finite impulse response filter. The compensated variable interpolator can be controlled, for example by a microprocessor or hardware equivalent, to provide selected ratios of compression or expansion.

FIGURES 1(a)-1(i) are useful for explaining different display
20 formats of a wide screen television.

FIGURE 2 is a block diagram of a wide screen television in accordance with aspects of this invention and adapted for operation at $2f_H$ horizontal scanning.

FIGURES 3 is a block diagram of the wide screen processor
25 shown in FIGURE 2.

FIGURE 4 is a block diagram showing further details of the wide screen processor shown in FIGURE 3.

FIGURE 5 is a block diagram of the picture-in-picture processor shown in FIGURE 4.

30 FIGURE 6 is a block diagram of the gate array shown in FIGURE 4 and illustrating the main, auxiliary and output signal paths.

FIGURES 7 and 8 are timing diagrams useful for explaining the generation of the display format shown in FIGURE 1(d), using fully
35 cropped signals.

FIGURE 9 is a block diagram showing the main signal path of FIGURE 6 in more detail.

FIGURE 10 is a block diagram showing the auxiliary signal path of FIGURE 6 in more detail.

5 FIGURE 11 is a block diagram of the the timing and control section of the picture-in-picture processor of FIGURE 5.

FIGURE 12 is a block diagram of a circuit for generating the internal $2f_H$ signal in the $1f_H$ to $2f_H$ conversion.

10 FIGURE 13 is a combination block and circuit diagram for the deflection circuit shown in FIGURE 2.

FIGURE 14 is a block diagram of the RGB interface shown in FIGURE 2.

15 FIGURES 15 and 16 are pixel diagrams useful for explaining the operation of two-stage variable interpolation filters, as may be used to implement the interpolators of FIGURES 6, 9 and 10.

FIGURE 17 is a block diagram of a two stage compensated variable interpolation filter.

20 FIGURE 18 is a block diagram of a two stage compensated variable interpolation filter configured for implementing a zoom feature.

FIGURE 19 is a block diagram of a circuit for implementing an eight tap, two stage interpolation filter.

25 The various parts of FIGURE 1 illustrate some, but not all of the various combinations of single and multiple picture display formats which can be implemented according to different inventive arrangements. Those selected for illustration are intended to facilitate the description of particular circuits comprising wide screen televisions according to the inventive arrangements. The inventive arrangements are in some cases directed to the display formats themselves, apart from specific underlying circuitry. For purposes of convenience in illustration and discussion herein, a conventional display format ratio of width to height for a video source or signal is generally deemed to be 4 X 3, whereas a wide screen display format ratio of width to height for a video source or 30 signal is generally deemed to be 16 X 9. The inventive arrangements are not limited by these definitions.

FIGURE 1(a) illustrates a television, direct view or projection, having a conventional format display ratio of 4 X 3. When a 16 X 9 format display ratio picture is transmitted, as a 4 X 3 format display ratio signal, black bars appear at the top and at the bottom.

5 This is commonly referred to as letterbox format. In this instance, the viewed picture is rather small with respect to the entire available display area. Alternatively, the 16 X 9 format display ratio source is converted prior to transmission, so that it will fill the vertical extent of a viewing surface of 4 X 3 format display.

10 However, much information will be cropped from the left and/or right sides. As a further alternative, the letterbox picture can be expanded vertically but not horizontally, whereby the resulting picture will evidence distortion by vertical elongation. None of the three alternatives is particularly appealing.

15 FIGURE 1(b) shows a 16 X 9 screen. A 16 X 9 format display ratio video source would be fully displayed, without cropping and without distortion. A 16 X 9 format display ratio letterbox picture, which is itself in a 4 X 3 format display ratio signal, can be progressively scanned by line doubling or line addition, so as to

20 provide a larger display with sufficient vertical resolution. A wide screen television in accordance with this invention can display such a 16 X 9 format display ratio signal whether the main source, the auxiliary source or an external RGB source.

25 FIGURE 1(c) illustrates a 16 X 9 format display ratio main signal in which a 4 X 3 format display ratio inset picture is displayed. If both the main and auxiliary video signals are 16 X 9 format display ratio sources, the inset picture can also have a 16 X 9 format display ratio. The inset picture can be displayed in many different positions.

30 FIGURE 1(d) illustrates a display format, wherein the main and auxiliary video signals are displayed with the same size picture. Each display area has a format display ratio of 8 X 9, which is of course different from both 16 X 9 and 4 X 3. In order to show a 4 X 3 format display ratio source in such a display area, without 35 horizontal or vertical distortion, the signal must be cropped on the left and/or right sides. More of the picture can be shown, with less

cropping, if some aspect ratio distortion by horizontal squeezing of the picture is tolerated. Horizontal squeezing results in vertical elongation of objects in the picture. The wide screen television according to this invention can provide any mix of cropping and 5 aspect ratio distortion from maximum cropping with no aspect ratio distortion to no cropping with maximum aspect ratio distortion.

10 Data sampling limitations in the auxiliary video signal processing path complicate the generation of a high resolution picture which is as large in size as the display from the main video signal. Various methods can be developed for overcoming these complications.

15 FIGURE 1(e) is a display format wherein a 4 X 3 format display ratio picture is displayed in the center of a 16 X 9 format display ratio screen. Dark bars are evident on the right and left sides.

20 FIGURE 1(f) illustrates a display format wherein one large 4 X 3 format display ratio picture and three smaller 4 X 3 format display ratio pictures are displayed simultaneously. A smaller picture outside the perimeter of the large picture is sometimes referred to as a POP, that is a picture-outside-picture, rather than a PIP, a picture-in-picture. The terms PIP or picture-in-picture are used herein for both display formats. In those circumstances where the wide screen television is provided with two tuners, either both internal or one internal and one external, for example in a video 25 cassette recorder, two of the displayed pictures can display movement in real time in accordance with the source. The remaining pictures can be displayed in freeze frame format. It will be appreciated that the addition of further tuners and additional auxiliary signal processing paths can provide for more than two 30 moving pictures. It will also be appreciated that the large picture on the one hand, and the three small pictures on the other hand, can be switched in position, as shown in FIGURE 1(g).

35 FIGURE 1(h) illustrates an alternative wherein the 4 X 3 format display ratio picture is centered, and six smaller 4 X 3 format display ratio pictures are displayed in vertical columns on either side. As in the previously described format, a wide screen

television provided with two tuners can provide two moving pictures. The remaining eleven pictures will be in freeze frame format.

FIGURE 1(i) shows a display format having a grid of twelve 5 4 X 3 format display ratio pictures. Such a display format is particularly appropriate for a channel selection guide, wherein each picture is at least a freeze frame from a different channel. As before, the number of moving pictures will depend upon the number of available tuners and signal processing paths.

10 The various formats shown in FIGURE 1 are illustrative, and not limiting, and can be implemented by wide screen televisions shown in the remaining drawings and described in detail below.

An overall block diagram for a wide screen television in accordance with inventive arrangements, and adapted to operate 15 with $2f_H$ horizontal scanning, is shown in FIGURE 2 and generally designated 10. The television 10 generally comprises a video signals input section 20, a chassis or TV microprocessor 216, a wide screen processor 30, a $1f_H$ to $2f_H$ converter 40, a deflection circuit 50, an RGB interface 60, a YUV to RGB converter 240, kine 20 drivers 242, direct view or projection tubes 244 and a power supply 70. The grouping of various circuits into different functional blocks is made for purposes of convenience in description, and is not intended as limiting the physical position of such circuits relative to one another.

25 The video signals input section 20 is adapted for receiving a plurality of composite video signals from different video sources. The video signals may be selectively switched for display as main and auxiliary video signals. An RF switch 204 has two antenna inputs ANT1 and ANT 2. These represent inputs for both off-air 30 antenna reception and cable reception. The RF switch 204 controls which antenna input is supplied to a first tuner 206 and to a second tuner 208. The output of first tuner 206 is an input to a one-chip 202, which performs a number of functions related to tuning, horizontal and vertical deflection and video controls. The particular 35 one-chip shown is industry designated type TA7730. The baseband video signal VIDEO OUT developed in the one-chip and resulting from

the signal from first tuner 206 is an input to both video switch 200 and the TV1 input of wide screen processor 30. Other baseband video inputs to video switch 200 are designated AUX1 and AUX 2. These might be used for video cameras, laser disc players, video 5 tape players, video games and the like. The output of the video switch 200, which is controlled by the chassis or TV microprocessor 216 is designated SWITCHED VIDEO. The SWITCHED VIDEO is another input to wide screen processor 30.

With further reference to FIGURE 3, a switch SW1 wide screen 10 processor selects between the TV1 and SWITCHED VIDEO signals as a SEL COMP OUT video signal which is an input to a Y/C decoder 210. The Y/C decoder 210 may be implemented as an adaptive line comb filter. Two further video sources S1 and S2 are also inputs to the Y/C decoder 210. Each of S1 and S2 represent different S-VHS 15 sources, and each consists of separate luminance and chrominance signals. A switch, which may be incorporated as part of the Y/C decoder, as in some adaptive line comb filters, or which may be implemented as a separate switch, is responsive to the TV microprocessor 216 for selecting one pair of luminance and 20 chrominance signals as outputs designated Y_M and C_IN respectively. The selected pair of luminance and chrominance signals is thereafter considered the main signal and is processed along a main signal path. Signal designations including _M or _MN refer to the main signal path. The chrominance signal C_IN is 25 redirected by the wide screen processor back to the one-chip, for developing color difference signals U_M and V_M. In this regard, U is an equivalent designation for (R-Y) and V is an equivalent designation for (B-Y). The Y_M, U_M, and V_M signals are converted to digital form in the wide screen processor for further signal 30 processing.

The second tuner 208, functionally defined as part of the wide screen processor 30, develops a baseband video signal TV2. A switch SW2 selects between the TV2 and SWITCHED VIDEO signals as an input to a Y/C decoder 220. The Y/C decoder 220 may be 35 implemented as an adaptive line comb filter. Switches SW3 and SW4 select between the luminance and chrominance outputs of Y/C

decoder 220 and the luminance and chrominance signals of an external video source, designated Y_EXT and C_EXT respectively. The Y_EXT and C_EXT signals correspond to the S-VHS input S1. The Y/C decoder 220 and switches SW3 and SW4 may be combined, as in some adaptive line comb filters. The output of switches SW3 and SW4 is thereafter considered the auxiliary signal and is processed along an auxiliary signal path. The selected luminance output is designated Y_A. Signal designations including _A, _AX and _AUX refer to the auxiliary signal path. The selected chrominance is converted to color difference signals U_A and V_A. The Y_A, U_A and V_A signals are converted to digital form for further signal processing. The arrangement of video signal source switching in the main and auxiliary signal paths maximizes flexibility in managing the source selection for the different parts of the different picture display formats.

A composite synchronizing signal COMP SYNC, corresponding to Y_M is provided by the wide screen processor to a sync separator 212. The horizontal and vertical synchronizing components H and V respectively are inputs to a vertical countdown circuit 214. The vertical countdown circuit develops a VERTICAL RESET signal which is directed into the wide screen processor 30. The wide screen processor generates an internal vertical reset output signal INT VERT RST OUT directed to the RGB interface 60. A switch in the RGB interface 60 selects between the internal vertical reset output signal and the vertical synchronizing component of the external RGB source. The output of this switch is a selected vertical synchronizing component SEL_VERT_SYNC directed to the deflection circuit 50. Horizontal and vertical synchronizing signals of the auxiliary video signal are developed by sync separator 250 in the wide screen processor.

The $1f_H$ to $2f_H$ converter 40 is responsible for converting interlaced video signals to progressively scanned noninterlaced signals, for example one wherein each horizontal line is displayed twice, or an additional set of horizontal lines is generated by interpolating adjacent horizontal lines of the same field. In some instances, the use of a previous line or the use of an interpolated

line will depend upon the level of movement which is detected between adjacent fields or frames. The converter circuit 40 operates in conjunction with a video RAM 420. The video RAM may be used to store one or more fields of a frame, to enable the 5 progressive display. The converted video data as Y_{2f_H} , U_{2f_H} and V_{2f_H} signals is supplied to the RGB interface 60.

The RGB interface 60, shown in more detail in FIGURE 14, enables selection of the converted video data or external RGB video data for display by the video signals input section. The external RGB 10 signal is deemed to be a wide format display ratio signal adapted for $2f_H$ scanning. The vertical synchronizing component of the main signal is supplied to the RGB interface by the wide screen processor as INT VERT RST OUT, enabling a selected vertical sync (f_{vm} or f_{vext}) to be available to the deflection circuit 50. Operation of the wide 15 screen television enables user selection of an external RGB signal, by generating an internal/external control signal INT/EXT. However, the selection of an external RGB signal input, in the absence of such a signal, can result in vertical collapse of the raster, and damage to the cathode ray tube or projection tubes. Accordingly, the RGB 20 interface circuit detects an external synchronizing signal, in order to override the selection of a non-existent external RGB input. The WSP microprocessor 340 also supplies color and tint controls for the external RGB signal.

The wide screen processor 30 comprises a picture in picture 25 processor 320 for special signal processing of the auxiliary video signal. The term picture-in-picture is sometimes abbreviated as PIP or pix-in-pix. A gate array 300 combines the main and auxiliary video signal data in a wide variety of display formats, as shown by the examples of FIGURES 1(b) through 1(i). The picture-in-picture 30 circuit 320 and gate array 300 are under the control of a wide screen microprocessor (WSP μ P) 340. Microprocessor 340 is responsive to the TV microprocessor 216 over a serial bus. The serial bus includes four signal lines, for data, clock signals, enable signals and reset signals. The wide screen processor 30 also 35 generates a composite vertical blanking/reset signal, as a three level sandcastle signal. Alternatively, the vertical blanking and

reset signals can be generated as separate signals. A composite blanking signal is supplied by the video signal input section to the RGB interface.

The deflection circuit 50, shown in more detail in FIGURE 13, 5 receives a vertical reset signal from the wide screen processor, a selected $2f_H$ horizontal synchronizing signal from the RGB interface 60 and additional control signals from the wide screen processor. These additional control signals relate to horizontal phasing, 10 vertical size adjustment and east-west pin adjustment. The deflection circuit 50 supplies $2f_H$ flyback pulses to the wide screen processor 30, the $1f_H$ to $2f_H$ converter 40 and the YUV to RGB converter 240.

Operating voltages for the entire wide screen television are 15 generated by a power supply 70 which can be energized by an AC mains supply.

The wide screen processor 30 is shown in more detail in FIGURE 3. The principal components of the wide screen processor are a gate array 300, a picture-in-picture circuit 301, analog to digital and digital to analog converters, the second tuner 208, a 20 wide screen processor microprocessor 340 and a wide screen output encoder 227. Further details of the wide screen processor, which are in common with both the $1f_H$ and the $2f_H$ chassis, for example the PIP circuit, are shown in FIGURE 4. A picture-in-picture processor 320, which forms a significant part of the PIP circuit 25 301, is shown in more detail in FIGURE 5. The gate array 300 is shown in more detail in FIGURE 6. A number of the components shown in FIGURE 3, forming parts of the main and auxiliary signal paths, have already been described in detail.

The second tuner 208 has associated therewith an IF stage 224 30 and an audio stage 226. The second tuner 208 also operates in conjunction with the WSP μ P 340. The WSP μ P 340 comprises an input output I/O section 340A and an analog output section 340B. The I/O section 340A provides tint and color control signals, the INT/EXT signal for selecting the external RGB video source and 35 control signals for the switches SW1 through SW6. The I/O section also monitors the EXT SYNC DET signal from the RGB interface to

protect the deflection circuit and cathode ray tube(s). The analog output section 340B provides control signals for vertical size, east-west adjust and horizontal phase, through respective interface circuits 254, 256 and 258.

5 The gate array 300 is responsible for combining video information from the main and auxiliary signal paths to implement a composite wide screen display, for example one of those shown in the different parts of FIGURE 1. Clock information for the gate array is provided by phase locked loop 374, which operates in conjunction
10 with low pass filter 376. The main video signal is supplied to the wide screen processor in analog form, and Y U V format, as signals designated Y_M, U_M and V_M. These main signals are converted from analog to digital form by analog to digital converters 342 and 346, shown in more detail in FIGURE 4.

15 The color component signals are referred to by the generic designations U and V, which may be assigned to either R-Y or B-Y signals, or I and Q signals. The sampled luminance bandwidth is limited to 8 MHz because the system clock rate is $1024f_H$, which is approximately 16 MHz. A single analog to digital converter and an
20 analog switch can be used to sample the color component data because the U and V signals are limited to 500 KHz, or 1.5 MHz for wide I. The select line UV_MUX for the analog switch, or multiplexer 344, is an 8 MHz signal derived by dividing the system clock by 2. A one clock wide start of line SOL pulse synchronously resets this
25 signal to zero at the beginning of each horizontal video line. The UV_MUX line then toggles in state each clock cycle through the horizontal line. Since the line length is an even number of clock cycles, the state of the UV_MUX, once initialized, will consistently toggle 0, 1, 0, 1, . . . , without interruption. The Y and UV data
30 streams out of the analog to digital converters 342 and 346 are shifted because the analog to digital converters each have 1 clock cycle of delay. In order to accommodate for this data shift, the clock gating information from the interpolator control 349 of main signal processing path 304 must be similarly delayed. Were the
35 clock gating information not delayed, the UV data will not be correctly paired when deleted. This is important because each UV

pair represents one vector. A U element from one vector cannot be paired with a V element from another vector without causing a color shift. Instead, a V sample from a previous pair will be deleted along with the current U sample. This method of UV multiplexing is 5 referred to as 2:1:1, as there are two luminance samples for every pair of color component (U, V) samples. The Nyquist frequency for both U and V is effectively reduced to one half of the luminance Nyquist frequency. Accordingly, the Nyquist frequency of the output of the analog to digital converter for the luminance component is 8 10 MHz, whereas the Nyquist frequency of the output of the analog to digital converter for the color components is 4 MHz.

The PIP circuit and/or the gate array may also include means for enhancing the resolution of the auxiliary data notwithstanding the data compression. A number of data reduction and data 15 restoration schemes have been developed, including for example paired pixel compression and dithering and dedithering. Moreover, different dithering sequences involving different numbers of bits and different paired pixel compressions involving different numbers of bits are contemplated. One of a number of particular data 20 reduction and restoration schemes can be selected by the WSP μ P 340 in order to maximize resolution of the displayed video for each particular kind of picture display format.

The gate array includes interpolators which operate in conjunction with line memories, which may be implemented as 25 FIFO's 356 and 358. The interpolator and FIFO's are utilized to resample the main signal as desired. An additional interpolator can resample the auxiliary signal. Clock and synchronizing circuits in the gate array control the data manipulation of both the main and auxiliary signals, including the combination thereof into a single 30 output video signal having Y_MX, U_MX and V_MX components. These output components are converted to analog form by digital to analog converters 360, 362 and 364. The analog form signals, designated Y, U and V, are supplied to the $1f_H$ to $2f_H$ converter 40 for conversion 35 to noninterlaced scanning. The Y, U and V signals are also encoded to Y/C format by encoder 227 to define a wide format ratio output signal Y_OUT_EXT/C_OUT_EXT available at panel jacks. Switch SW5

selects a synchronizing signal for the encoder 227 from either the gate array, C_SYNC_MN, or from the PIP circuit, C_SYNC_AUX.

Switch SW6 selects between Y_M and C_SYNC_AUX as synchronizing signal for the wide screen panel output.

5 Portions of the horizontal synchronizing circuit are shown in more detail in FIGURE 12. Phase comparator 228 is part of a phase locked loop including low pass filter 230, voltage controlled oscillator 232, divider 234 and capacitor 236. The voltage controlled oscillator 232 operates at $32f_H$, responsive to a ceramic resonator or the like 238. The output of the voltage controlled oscillator is divided by 32 to provide a proper frequency second input signal to phase comparator 228. The output of the divider 234 is a $1f_H$ REF timing signal. The $32f_H$ REF and $1f_H$ REF timing signals are supplied to a divide by 16 counter 400. A $2f_H$ output is supplied 10 to a pulse width circuit 402. Presetting divider 400 by the $1f_H$ REF signal assures that the divider operates synchronously with the phase locked loop of the video signals input section. Pulse width circuit 402 assures that a $2f_H$ -REF signal will have an adequate pulse width to assure proper operation of the phase comparator 404, 15 for example a type CA1391, which forms part of a second phase locked loop including low pass filter 406 and $2f_H$ voltage controlled oscillator 408. Voltage controlled oscillator 408 generates an internal $2f_H$ timing signal, which is used for driving the progressively scanned display. The other input signal to phase 20 comparator 404 is the $2f_H$ flyback pulses or a timing signal related thereto. The use of the second phase locked loop including phase comparator 404 is useful for assuring that each $2f_H$ scanning period is symmetric within each $1f_H$ period of the input signal. Otherwise, the display may exhibit a raster split, for example, wherein half of 25 the video lines are shifted to the right and half of the video lines are shifted to the left.

The deflection circuit 50 is shown in more detail in FIGURE 13. A circuit 500 is provided for adjusting the vertical size of the raster, in accordance with a desired amount of vertical overscan 30 necessary for implementing different display formats. As illustrated diagrammatically, a constant current source 502

provides a constant quantity of current I_{RAMP} which charges a vertical ramp capacitor 504. A transistor 506 is coupled in parallel with the vertical ramp capacitor, and periodically discharges the capacitor responsive to the vertical reset signal. In the absence of 5 any adjustment, current I_{RAMP} provides the maximum available vertical size for the raster. This might correspond to the extent of vertical overscan needed to fill the wide screen display by an expanded 4 X 3 format display ratio signal source, as shown in FIGURE 1(a). To the extent that less vertical raster size is required, 10 an adjustable current source 508 diverts a variable amount of current I_{ADJ} from I_{RAMP} , so that vertical ramp capacitor 504 charges more slowly and to a smaller peak value. Variable current source 508 is responsive to a vertical size adjust signal, for example in analog form, generated by a vertical size control circuit. Vertical 15 size adjustment 500 is independent of a manual vertical size adjustment 510, which may be implemented by a potentiometer or back panel adjustment knob. In either event, the vertical deflection coil(s) 512 receive(s) driving current of the proper magnitude. Horizontal deflection is provided by phase adjusting circuit 518, 20 East-West pin correction circuit 514, a $2f_H$ phase locked loop 520 and horizontal output circuit 516.

The RGB interface circuit 60 is shown in more detailed in FIGURE 14. The signal which is to be ultimately displayed will be selected between the output of the $1f_H$ to $2f_H$ converter 40 and an 25 external RGB input. For purposes of the wide screen television described herein, the external RGB input is presumed to be a wide format display ratio, progressively scanned source. The external RGB signals and a composite blanking signal from the video signals input section 20 are inputs to an RGB to Y U V converter 610. The 30 external $2f_H$ composite synchronizing signal for the external RGB signal is an input to external synchronizing signal separator 600. Selection of the vertical synchronizing signal is implemented by switch 608. Selection of the horizontal synchronizing signal is implemented by switch 604. Selection of the video signal is 35 implemented by switch 606. Each of the switches 604, 606 and 608 is responsive to an internal/external control signal generated by the

WSP μ P 340. Selection of internal or external video sources is a user selection. However, if a user inadvertently selects an external RGB source, when no such source is connected or turned on, or if the external source drops out, the vertical raster will collapse, and

5 serious damage to the cathode ray tube(s) can result. Accordingly, an external synchronizing detector 602 checks for the presence of an external synchronizing signal. In the absence of such a signal, a switch override control signal is transmitted to each of switches 604, 606 and 608, to prevent selection of the external RGB source if

10 the signal therefrom is not present. The RGB to YUV converter 610 also receives tint and color control signals from the WSP μ P 340.

A wide screen television in accordance with the inventive arrangements can be implemented with $1f_H$ horizontal scanning instead of $2f_H$ horizontal scanning, although such a circuit is not

15 illustrated. A $1f_H$ circuit would not require the $1f_H$ to $2f_H$ converter and the RGB interface. Accordingly, there would be no provision for displaying an external wide format display ratio RGB signal at a $2f_H$ scanning rate. The wide screen processor and picture-in-picture processor for a $1f_H$ circuit would be very similar. The gate array

20 could be substantially identical, although not all of the inputs and outputs would be utilized. The various resolution enhancement schemes described herein can be generally applied without regard to whether the television operates with $1f_H$ or $2f_H$ scanning.

FIGURE 4 is a block diagram showing further details of the

25 wide screen processor 30 shown in FIGURE 3 which would be the same for both a $1f_H$ and $2f_H$ chassis. The Y_A, U_A and V_A signals are an input to the picture in picture processor 320, which can include a resolution processing circuit 370. The wide screen television according to aspects of this invention can expand and

30 compress video. The special effects embodied by the various composite display formats illustrated in part in FIGURE 1 are generated by the picture-in-picture processor 320, which can receive resolution processed data signals Y_RP, U_RP and V_RP from resolution processing circuit 370. Resolution processing need not be

35 utilized at all times, but during selected display formats. The picture-in-picture processor 320 is shown in more detail in FIGURE

5. The principal components of the picture-in-picture processor are an analog-to-digital converter section 322, an input section 324, a fast switch (FSW) and bus section 326, a timing and control section 328 and a digital-to-analog converter section 330. The timing and 5 control section 328 is shown in more detail in FIGURE 9.

The picture-in-picture processor 320 may be embodied as an improved variation of a basic CPIP chip developed by Thomson Consumer Electronics, Inc. The basic CPIP chip is described more fully in a publication entitled The CTC 140 Picture in Picture (CPIP) 10 Technical Training Manual, available from Thomson Consumer Electronics, Inc., Indianapolis, Indiana. A number of special features or special effects are possible, the following being illustrative. The basic special effect is a large picture having a small picture overlaying a portion thereof as shown in FIGURE 1(c). The large and 15 small pictures can result from the same video signal, from different video signals and can be interchanged or swapped. Generally speaking, the audio signal is switched to always correspond to the big picture. The small picture can be moved to any position on the screen or can step through a number of predetermined positions. A 20 zoom feature increases and decreases the size of the small picture, for example to any one of a number of preset sizes. At some point, for example the display format shown in FIGURE 1(d), the large and small pictures are in fact the same size.

In a single picture mode, for example that shown in FIGURES 25 1(b), 1(e) or 1(f) a user can zoom in on the content of the single picture, for example, in steps from a ratio of 1.0:1 to 5.0:1. While in the zoom mode a user may search or pan through the picture content enabling the screen image to move across different areas of the picture. In either event, either the small picture or the large picture 30 or the zoomed picture can be displayed in freeze frame (still picture format). This function enables a strobe format, wherein the last nine frames of video can be repeated on the screen. The frame repetition rate can be changed from thirty frames per second to zero frames per second.

35 The picture-in-picture processor used in the wide screen television according to another inventive arrangement differs from

the present configuration of the basic CPIP chip itself as described above. If the basic CPIP chip were used with a television having a 16 X 9 screen, and without a video speed up circuit, the inset pictures would exhibit aspect ratio distortion, due to the effective 5 4/3 times horizontal expansion resulting from scanning across the wider 16 X 9 screen. Objects in the picture would be horizontally elongated. If an external speed up circuit were utilized, there would be no aspect ratio distortion, but the picture would not fill the entire screen.

10 Existing picture-in-picture processors based on the basic CPIP chip as used in conventional televisions are operated in a particular fashion having certain undesirable consequences. The incoming video is sampled with a $640f_H$ clock which is locked to the horizontal synchronizing signal of the main video source. In other 15 words, data stored in the video RAM associated with the CPIP chip is not orthogonally sampled with respect to the incoming auxiliary video source. This is a fundamental limitation on the basic CPIP method of field synchronization. The nonorthogonal nature of the input sampling rate results in skew errors of the sampled data. The 20 limitation is a result of the video RAM used with the CPIP chip, which must use the same clock for writing and reading data. When data from the video RAM, such as video RAM 350, is displayed, the skew errors are seen as random jitter along vertical edges of the picture and are generally considered quite objectionable.

25 The picture-in-picture processor 320, according to an inventive arrangement and unlike the basic CPIP chip, is adapted for asymmetrically compressing the video data in one of a plurality of display modes. In this mode of operation, the pictures are compressed 4:1 in the horizontal direction and 3:1 in the vertical 30 direction. This asymmetric mode of compression produces aspect ratio distorted pictures for storage in the video RAM. Objects in the pictures are squeezed horizontally. However, if these pictures are read out normally, as for example in the channel scan mode, for display of a 16 X 9 format display ratio screen, the pictures appear 35 correct. The picture fills the screen and there is no aspect ratio distortion. The asymmetric compression mode according to this

aspect of the invention makes it possible to generate the special display formats on a 16 X 9 screen without external speed up circuitry.

FIGURE 11 is a block diagram of the timing and control section 328 of the picture-in-picture processor, for example a modified version of the CPIP chip described above, which includes a decimation circuit 328C for implementing the asymmetric compression as one of a plurality of selectable display modes. The remaining display modes can provide auxiliary pictures of different sizes. Each of horizontal and vertical decimation circuits comprises a counter which is programmed for a compression factor from a table of values under the control of the WSP μ P 340. The range of values can be 1:1, 2:1, 3:1 and so on. The compression factors can be symmetric or asymmetric, depending upon how the table is set up. Control of the compression ratios can also be implemented by fully programmable, general purpose decimation circuits under the control of the WSP μ P 340.

In full screen PIP modes, the picture-in-picture processor, in conjunction with a free running oscillator 348 will take Y/C input from a decoder, for example an adaptive line comb filter, decode the signal into Y, U, V color components and generate horizontal and vertical sync pulses. These signals are processed in the picture-in-picture processor for the various full screen modes such as zoom, freeze and channel scan. During the channel scan mode, for example, the horizontal and vertical sync present from the video signals input section will have many discontinuities because the signals sampled (different channels) will have non-related sync pulses and will be switched at seemingly random moments in time. Therefore the sample clock (and read/write video RAM clock) is determined by the free running oscillator. For freeze and zoom modes, the sample clock will be locked to incoming video horizontal sync, which in these special cases is the same as the display clock frequency.

Referring again to FIGURE 4, Y, U, V and C_SYNC (composite sync) outputs from the picture-in-picture processor in analog form can be re-encoded into Y/C components by encode circuit 366, which operates in conjunction with a 3.58 MHz oscillator 380. This

Y/C_PIP_ENC signal may be connected to a Y/C switch, not shown, which enables the re-encoded Y/C components to be substituted for the Y/C components of the main signal. From this point on, the PIP encoded Y, U, V and sync signals would be the basis for horizontal 5 and vertical timing in the rest of the chassis. This mode of operation is appropriate for implementing a zoom mode for the PIP, based upon operation of the interpolator and FIFO's in the main signal path.

With further reference to FIGURE 5, the picture-in-picture processor 320 comprises analog to digital converting section 322, input section 324, fast switch FSW and bus control section 326, timing and control section 328 and digital to analog converting section 330. In general, the picture-in-picture processor 320 digitizes the video signal into luminance (Y) and color difference 10 signals (U, V), subsampling and storing the results in a 1 megabit video RAM 350 as explained above. The video RAM 350 associated with the picture-in-picture processor 320 has a memory capacity of 15 1 megabit, which is not large enough to store a full field of video data with 8-bit samples. Increased memory capacity tends to be expensive and can require more complex management circuitry. The 20 smaller number of bits per sample in the auxiliary channel represents a reduction in quantization resolution, or bandwidth, relative to the main signal, which is processed with 8-bit samples throughout. This effective reduction of bandwidth is not usually a 25 problem when the auxiliary displayed picture is relatively small, but can be troublesome if the auxiliary displayed picture is larger, for example the same size as the main displayed picture. Resolution processing circuit 370 can selectively implement one or more schemes for enhancing the quantization resolution or effective 30 bandwidth of the auxiliary video data. A number of data reduction and data restoration schemes have been developed, including for example, paired pixel compression and dithering and dedithering. A dedithering circuit would be operatively disposed downstream of the video RAM 350, for example in the auxiliary signal path of the gate 35 array, as explained in more detail below. Moreover, different dithering and dedithering sequences involving different numbers of

bits and different paired pixel compressions involving different number of bits are contemplated. One of a number of particular data reduction and restoration schemes can be selected by the WSP μ R in order to maximize resolution of the displayed video for each 5 particular kind of picture display format.

The luminance and color difference signals are stored in an 8:1:1 six-bit Y, U, V fashion. In other words, each component is quantized into six-bit samples. There are eight luminance samples for every pair of color difference samples. The picture-in-picture 10 processor 320 is operated in a mode whereby incoming video data is sampled with a $640f_H$ clock rate locked to the incoming auxiliary video synchronizing signal instead. In this mode, data stored in the video RAM is orthogonally sampled. When the data is read out of the picture-in-picture processor video RAM 350, it must also be read 15 using the same $640f_H$ clock locked to the incoming auxiliary video signal in order to maintain the orthogonal relationship. However, even though this data was orthogonally sampled and stored, and can be read out orthogonally, it cannot be displayed orthogonally directly from the video RAM 350, due to the asynchronous nature of the main 20 and auxiliary video sources. The main and auxiliary video sources might be expected to be synchronous only in that instance where they are displaying signals from the same video source.

Further processing is required in order to synchronize the auxiliary channel, that is the output of data from the video RAM 350, 25 to the main channel. With reference again to FIGURE 4, two four bit latches 352A and 352B are used to recombine the 8-bit data blocks from the video RAM 4-bit output port. The four bit latches also reduce the data clock rate from $1280f_H$ to $640f_H$.

Generally, the video display and deflection system is 30 synchronized with the main video signal. The main video signal must be speeded up, as explained above, to fill the wide screen display. The auxiliary video signal must be vertically synchronized with the first video signal and the video display. The auxiliary video signal can be delayed by a fraction of a field period in a field memory, and 35 then expanded in a line memory. Synchronization of the auxiliary video data with main video data is accomplished by utilizing the

video RAM 350 as a field memory and a first in first out (FIFO) line memory device 354 for expanding the signal. The size of FIFO 354 is 2048 X 8. The size of FIFO is related to the minimum line storage capacity thought to be reasonably necessary to avoid read/write 5 pointer collisions. Read/write pointer collisions occur when old data is read out of the FIFO before new data has an opportunity to be written into the FIFO. Read/write pointer collisions also occur when new data overwrites the memory before the old data has an opportunity to be read out of the FIFO.

10 The 8-bit DATA_PIP data blocks from video RAM 350 are written into 2048 x 8 FIFO 354 with the same picture-in-picture processor 640f_H clock which was used to sample the video data, that is, the 640f_H clock which is locked to the auxiliary signal, rather than the main signal. The FIFO 354 is read using the display clock of 15 1024f_H, which is locked to horizontal synchronizing component of the main video channel. The use of a multiple line memory (FIFO) which has independent read and write port clocks enables data which was orthogonally sampled at a first rate to be displayed orthogonally at a second rate. The asynchronous nature of the read 20 and write clocks, however, does require that steps be undertaken to avoid read/write pointer collisions.

The main signal path 304, auxiliary signal path 306 and output signal path 312 of the gate array 300 are shown in block diagram form in FIGURE 6. The gate array also comprises a clocks/sync 25 circuit 320 and a WSP μ P decoder 310. Data and address output lines of the WSP μ P decoder 310, identified as WSP DATA, are supplied to each of the main circuits and paths identified above, as well as to the picture-in-picture processor 320 and resolution processing circuit 370. It will be appreciated that whether or not 30 certain circuits are, or are not, defined as being part of the gate array is largely a matter of convenience for facilitating explanation of the inventive arrangements.

The gate array is responsible for expanding, compressing and cropping video data of the main video channel, as and if necessary, 35 to implement different picture display formats. The luminance component Y_MN is stored in a first in first out (FIFO) line memory

356 for a length of time depending on the nature of the interpolation of the luminance component. The combined chrominance components U/V_MN are stored in FIFO 358. Auxiliary signal luminance and chrominance components Y_PIP, U_PIP and V_PIP are developed by 5 demultiplexer 355. The luminance component undergoes resolution processing, as desired, in circuit 357, and is expanded as necessary by interpolator 359, generating signal Y_AUX as an output.

In some instances, the auxiliary display will be as large as the main signal display, as shown for example in FIGURE 1(d). The 10 memory limitations associated with the picture-in-picture processor and video RAM 350 can provide an insufficient number of data points, or pixels for filling such a large display area. In those circumstances, resolution processing circuit 357 can be used to restore pixels to the auxiliary video signal to replace those lost 15 during data compression, or reduction. The resolution processing may correspond to the resolution processing undertaken by circuit 370 shown in FIGURE 4. As an example, circuit 370 may be a dithering circuit and circuit 357 may be a dedithering circuit.

The auxiliary video input data is sampled at a $640f_H$ rate and 20 stored in video RAM 350. The auxiliary data is read out of video RAM 350 is designated VRAM_OUT. The PIP circuit 301 also has the capability of reducing the auxiliary picture by equal integer factors horizontally and vertically, as well as asymmetrically. With further 25 reference to FIGURE 10, the auxiliary channel data is buffered and synchronized to the main channel digital video by the 4 bit latches 352A and 352B, the auxiliary FIFO 354, timing circuit 369 and synchronization circuit 368. The VRAM_OUT data is sorted into Y (luminance), U, V (color components), and FSW_DAT (fast switch data) by demultiplexer 355. The FSW_DAT indicates which field 30 type was written into the video RAM. The PIP_FSW signal is received directly from the PIP circuit and applied to the output control circuit 321 to determine which field read out of video RAM is to be displayed during the small picture modes.

The auxiliary channel is sampled at $640f_H$ rate while the main 35 channel is sampled at a $1024f_H$ rate. The auxiliary channel FIFO 354 converts the data from the auxiliary channel sample rate to the main

channel clock rate. In this process, the video signal undergoes an 8/5 (1024/640) compression. This is more than the 4/3 compression necessary to correctly display the auxiliary channel signal.

Therefore, the auxiliary channel must be expanded by the 5 interpolator 359 to correctly display a 4 X 3 small picture. The interpolator 359 is controlled by interpolator control circuit 371, which is itself responsive to WSP μ P 340. The amount of interpolator expansion required is 5/6. The expansion factor X is determined as follows:

10
$$X = (640/1024) * (4/3) = 5/6$$

The chrominance components U_PIP and V_PIP are delayed by circuit 367 for a length of time depending on the nature of the interpolation of the luminance component, generating signals U_AUX and V_AUX as outputs. The respective Y, U and V components of the 15 main and auxiliary signals are combined in respective multiplexers 315, 317 and 319 in the output signal path 312, by controlling the read enable signals of the FIFO's 354, 356 and 358. The multiplexers 315, 317 and 319 are responsive to output multiplexer control circuit 321. Output multiplexer control circuit 321 is responsive to 20 the clock signal CLK, the start of line signal SOL, the H_COUNT signal, the vertical blanking reset signal and the output of the fast switch from the picture-in-picture processor and WSP μ P 340. The multiplexed luminance and chrominance components Y_MX, U_MX and V_MX are supplied to respective digital/analog converters 360, 362 25 and 364 respectively. The digital to analog converters are followed by low pass filters 361, 363 and 365 respectively, shown in FIGURE 4. The various functions of the picture-in-picture processor, the gate array and the data reduction circuit are controlled by WSP μ P 340. The WSP μ P 340 is responsive to the TV μ P 216, being 30 connected thereto by a serial bus. The serial bus may be a four wire bus as shown, having lines for data, clock signals, enable signals and reset signals. The WSP μ P 340 communicates with the different circuits of the gate array through a WSP μ P decoder 310.

In one case, it is necessary to compress the 4 X 3 NTSC video 35 by a factor of 4/3 to avoid aspect ratio distortion of the displayed picture. In the other case, the video can be expanded to perform

horizontal zooming operations usually accompanied by vertical zooming. Horizontal zoom operations up to 33% can be accomplished by reducing compressions to less than 4/3. A sample interpolator is used to recalculate the incoming video to a new pixel positions 5 because the luminance video bandwidth, up to 5.5 MHz for S-VHS format, occupies a large percentage of the Nyquist fold over frequency, which is 8 MHz for a $1024f_H$ clock.

As shown in FIGURE 6, the luminance data Y_{MN} is routed through an interpolator 337 in the main signal path 304 which 10 recalculates sample values based on the compression or the expansion of the video. The function of the switches or route selectors 323 and 331 is to reverse the topology of the main signal path 304 with respect to the relative positions of the FIFO 356 and the interpolator 337. In particular, these switches select whether 15 the interpolator 337 precedes the FIFO 356, as required for compression, or whether the FIFO 356 precedes the interpolator 337, as required for expansion. The switches 323 and 331 are responsive to a route control circuit 335, which is itself responsive to the WSP μ P 340. It will be remembered that during small picture modes the 20 auxiliary video signal is compressed for storage in the video RAM 350, and only expansion is necessary for practical purposes. Accordingly, no comparable switching is required in the auxiliary signal path.

The main signal path is shown in more detail in FIGURE 9. The 25 switch 323 is implemented by two multiplexers 325 and 327. Switch 331 is implemented by multiplexer 333. The three multiplexers are responsive to the route control circuit 335, which is itself responsive to the WSP μ P 340. A horizontal timing/synchronization circuit 339 generates timing signals 30 controlling the writing and reading of the FIFOs, as well as latches 347 and 351, and multiplexer 353. The clock signal CLK and start of line signal SOL are generated by the clocks/sync circuit 320. An analog to digital conversion control circuit 369 is responsive to Y_{MN} , the WSP μ P 340 and the most significant bit of UV_{MN} . 35 An interpolator control circuit 349 generates intermediate pixel position values (K), interpolator compensation filter weighting

(C) and clock gating information CGY for the luminance and CGUV for the color components. It is the clock gating information which pauses (decimates) or repeats the FIFO data to allow samples not to be written on some clocks for effecting compression or some samples to be read multiple times for expansion.

It is possible to perform video compressions and expansions through the use of a FIFO. For example, a WR_EN_MN_Y signal enables data to be written into the FIFO 356. Every fourth sample can be inhibited from being written into the FIFO. This constitutes a 4/3 compression. It is the function of the interpolator 337 to recalculate the luminance samples being written into the FIFO so that the data read out of the FIFO is smooth, rather than jagged. Expansions may be performed in exactly the opposite manner as compressions. In the case of compressions the write enable signal has clock gating information attached to it in the form of inhibit pulses. For expanding data, the clock gating information is applied to the read enable signal. This will pause the data as it is being read from the FIFO 356. In this case it is the function of the interpolator 337, which follows the FIFO 356 during this process, to recalculate the sampled data from jagged to smooth. In the expansion case the data must pause while being read from the FIFO 356 and while being clocked into the interpolator 337. This is different from the compression case where the data is continuously clocked through the interpolator 337. For both cases, compression and expansion, the clock gating operations can easily be performed in a synchronous manner, that is, events can occur based on the rising edges of the system clock 1024f_H.

There are a number of advantages in this topology for luminance interpolation. The clock gating operations, namely data decimation and data repetition, may be performed in a synchronous manner. If a switchable video data topology were not used to interchange the positions of the interpolator and FIFO, the read or write clocks would need to be double clocked to pause or repeat the data. The term double clocked means that two data points must be written into the FIFO in a single clock cycle or read from the FIFO during a single clock cycle. The resulting circuitry cannot be made

to operate synchronously with the system clock, since the writing or reading clock frequency must be twice as high as the system clock frequency. Moreover, the switchable topology requires only one interpolator and one FIFO to perform both compressions and

5 expansions. If the video switching arrangement described herein were not used, the double clocking situation can be avoided only by using two FIFO's to accomplish the functionality of both compression and expansion. One FIFO for expansions would need to be placed in front of the interpolator and one FIFO for compressions

10 would need to be placed after the interpolator.

Interpolation of the auxiliary signal takes place in the auxiliary signal path 306. The PIP circuit 301 manipulates a 6 bit Y, U, V, 8:1:1 field memory, video RAM 350, to store incoming video data. The video RAM 350 holds two fields of video data in a plurality of memory locations. Each memory location holds eight bits of data. In each 8-bit location there is one 6-bit Y (luminance) sample (sampled at 640f_H) and 2 other bits. These two other bits hold either fast switch data (FSW_DAT) or part of a U or V sample (sampled at 80f_H). The FSW_DAT values indicate which type of field

15 was written into video RAM. Since there are two fields of data stored in the video RAM 350, and the entire video RAM 350 is read during the display period, both fields are read during the display scan. The PIP circuit 301 will determine which field will be read out of the memory to be displayed through the use of the fast switch

20 data. The PIP circuit always reads the opposite field type that is being written to overcome a motion tear problem. If the field type being read is the opposite type than that being displayed, then the even field stored in the video RAM is inverted by deleting the top line of the field when the field is read out of memory. The result is

25 that the small picture maintains correct interlace without a motion tear.

The clocks/sync circuit 320 generates read, write and enable signals needed for operating FIFOs 354, 356 and 358. The FIFOs for the main and auxiliary channels are enabled for writing data into

35 storage for those portions of each video line which is required for subsequent display. Data is written from one of the main or

auxiliary channels, but not both, as necessary to combine data from each source on the same video line or lines of the display. The FIFO 354 of the auxiliary channel is written synchronously with the auxiliary video signal, but is read out of memory synchronously with the main video signal. The main video signal components are read into the FIFOs 356 and 358 synchronously with the main video signal, and are read out of memory synchronously with the main video. How often the read function is switched back and forth between the main and auxiliary channels is a function of the particular special effect chosen.

Generation of different special effects such as cropped side-by-side pictures are accomplished through manipulating the read and write enable control signals for the line memory FIFOs. The process for this display format is illustrated in FIGURES 7 and 8. In the case of cropped side-by-side displayed pictures, the write enable control signal (WR_EN_AX) for 2048 X 8 FIFO 354 of the auxiliary channel is active for $(1/2) * (5/12) = 5/12$ or approximately 41% of the display active line period (post speed up), or 67% of the auxiliary channel active line period (pre speed up), as shown in FIGURE 7. This corresponds to approximately 33% cropping (approximately 67% active picture) and the interpolator expansion of the signal by 5/6. In the main video channel, shown in the upper part of FIGURE 8, the write enable control signal (WR_EN_MN_Y) for the 910 X 8 FIFOs 356 and 358 is active for $(1/2) * (4/3) = 0.67$ or 67% of the display active line period. This corresponds to approximately 33% cropping and a compression ratio of 4/3 being performed on the main channel video by the 910 x 8 FIFOs.

In each of the FIFOs, the video data is buffered to be read out at a particular point in time. The active region of time where the data may be read out from each FIFO is determined by the display format chosen. In the example of the side-by-side cropped mode shown, the main channel video is being displayed on the left hand half of the display and the auxiliary channel video is displayed on the right hand half of the display. The arbitrary video portions of the waveforms are different for the main and auxiliary channels as illustrated. The read enable control signal (RD_EN_MN) of the main

channel 910 x 8 FIFOs is active for 50% of the display active line period of the display beginning with the start of active video, immediately following the video back porch. The auxiliary channel read enable control signal (RD_EN_AX) is active for the other 50% of the display active line period beginning with the falling edge of the RD_EN_MN signal and ending with the beginning of the main channel video front porch. It may be noted that write enable control signals are synchronous with their respective FIFO input data (main or auxiliary) while the read enable control signals are synchronous with the main channel video.

The display format shown in FIGURE 1(d) is particularly desirable as it enables two nearly full field pictures to be displayed in a side by side format. The display is particularly effective and appropriate for a wide format display ratio display, for example 16 X 9. Most NTSC signals are represented in a 4 X 3 format, which of course corresponds to 12 x 9. Two 4 X 3 format display ratio NTSC pictures may be presented on the same 16 X 9 format display ratio display, either by cropping the pictures by 33% or squeezing the pictures by 33%, and introducing aspect ratio distortion. Depending on user preference, the ratio of picture cropping to aspect ratio distortion may be set anywhere in between the limits of 0% and 33%. As an example, two side by side pictures may be presented as 16.7 % squeezed and 16.7% cropped.

The horizontal display time for a 16 X 9 format display ratio display is the same as a 4 X 3 format display ratio display, because both have 62.5 microsecond nominal line length. Accordingly, an NTSC video signal must be sped up by a factor of 4/3 to preserve a correct aspect ratio, without distortion. The 4/3 factor is calculated as ratio of the two display formats:

$$4/3 = (16/9) / (4/3)$$

Variable interpolators are utilized in accordance with aspects of this invention to speed up the video signals. In the past, FIFOs having different clock rates at the inputs and outputs have been used to perform a similar function. By way of comparison, if two NTSC 4 X 3 format display ratio signals are displayed on a single 4 X 3 format display ratio display, each picture must be distorted or

cropped, or some combination thereof, by 50%. A speed up comparable to that needed for a wide screen application is unnecessary.

The wide screen television according to various inventive arrangements can expand and compress video in the horizontal direction by using adaptive interpolator filters. The interpolators for the luminance components of the main and auxiliary signals may be skew correction filters, of the kind described in U.S. Patent No. 4,694,414- Christopher. A four point interpolator as described therein, for example, comprises a two point linear interpolator and an associated filter and multiplier connected in cascade to provide amplitude and phase compensation. In total, four adjacent data samples are used to calculate each interpolated point. The input signal is applied to the two-point linear interpolator. The delay imparted to the input is proportional to the value of a delay control signal (K). The amplitude and phase errors of the delayed signal are minimized by the application of a correction signal obtained by an additional filter and multiplier connected in cascade. This correction signal provides peaking which equalizes the frequency response of the two point linear interpolation filter for all values of (K). The original four point interpolator is optimized for use with signals having a pass band of $fs/4$, where fs is the data sample rate.

Alternatively, and in accordance with inventive arrangements, both channels can use what is termed a two stage interpolative process. The frequency response of the original variable interpolation filter can be improved by using such a two stage process. This process is hereinafter referred to as a two stage interpolator. A two stage interpolator according to an inventive arrangement comprises a $2n+4$ tap finite impulse response (FIR) filter with fixed coefficients and a four point variable interpolator, as is illustrated by FIGURE 15-16. The FIR filter output is spatially located midway between the input pixel samples, as shown in FIGURE 15. The output of the FIR filter is then combined by interleaving with the original data samples, which are delayed, to create an effective $2fs$ sample rate. This is a valid assumption for frequencies in the pass band of the FIR filter. The result is that the

effective pass band of the original four point interpolator is significantly increased.

The compensated variable interpolation filter of the prior art provides accurately interpolated samples as long as the frequency components of the signal are no greater than approximately one fourth the sample rate, $1/4$ fs. The two-stage approach can be used for signals having frequency components substantially greater than $1/4$ fs, as shown by the block diagram for a two stage interpolator 390 in FIGURE 17. A signal DS_A of digital samples at a sampling rate fs is an input to a finite impulse response (FIR) filter, for example a fixed FIR filter 391. The finite impulse response filter 391 generates from the signal DS_A a second signal DS_B of digital samples which are also at the sampling rate fs, but which are temporally located between the values of the first signal DS_A, for example at the midpoint between each value. Signal DS_A is also an input to a delay circuit 392, which produces a signal DS_C of digital samples, identical to signal DS_A but time delayed by $(N+1)/fs$. The data streams DS_B and DS_C are combined by interleaving in multiplexer 393, resulting in a data stream of values DS_D at twice the sampling rate, 2fs. Data stream DS_D is an input to a compensated variable interpolator 394.

In general terms, the fixed FIR filter is designed to accurately produce sample values corresponding to time locations exactly half-way in between the incoming sample positions. These are then interleaved with delayed but otherwise unmodified samples, producing a data stream with a 2fs sample rate. The FIR filter is most conveniently implemented using an even number of symmetrically weighted taps. An eight-tap filter, for example, having tap weights of:

-1/32, 5/64, -11/64, 5/8, 5/8, -11/64, 5/64, -1/32
will accurately interpolate signals having frequency components up to about 0.4fs. Since the data rate is doubled to 2fs by the interleaving, the signal being processed by the variable interpolator never contains frequency components higher than $1/4$ the sample rate.

An advantage of the two-stage interpolator is to allow accurate interpolations for signals with bandwidths approaching 1/2 the sample rate. Thus, the system is most appropriate for display modes requiring time expansion, such as zoom, where the object is 5 to maintain as much of the original bandwidth as possible. This can be pertinent in a wide screen television, particularly in the auxiliary channel, where the auxiliary signal is initially sampled at a fairly low rate, for example 10 MHz. Preserving as much bandwidth as possible can be important.

10 A two stage interpolator 390' appropriate for a zoom application is shown in block diagram form in FIGURE 18. Components in common with the interpolator 390 shown in FIGURE 17 have the same reference numeral as do the designations of the data streams. The object of the two stage interpolator 390' is to 15 zoom the incoming image horizontally by a factor of m , where m is greater than 2.0. Thus, if the data in and data out signals are occurring at the same sample rate of f_{IN} , there needs to be m output samples generated for every input sample. The signal is stored in a FIFO line memory 395 at f_{IN} rate, and a portion is then read out as 20 data stream DS_A at a reduced rate of f_s . The f_s clock is composed of a subset of f_{IN} clock pulses, and does not have a uniform period.

Data stream DS_B, corresponding to sample values half-way in between the existing samples of data stream DS_A are estimated using the fixed FIR filter 391, and are then interleaved with the 25 delayed samples of data stream DA_C to form the double rate data stream DS_D. Data stream DS_D, having twice the original sample density, is then processed by the variable interpolator 394 to produce a sample value for each f_{IN} period. The accumulator circuit, including latch 398 and summer 399 produces an output which 30 increments by $r = 2/m$ each f_{IN} clock period. The fractional part controls the variable interpolator by supplying the K value from latch 398. The integer carry output (CO) generates the $2f_s$ clock, through latch 397, for reading of the FIFO 395 and shifting data through the FIR filter 391, the delay circuit 392, the multiplexer 35 393 and the interpolator 394. Divider 396 provides the f_s signal from the $2f_s$ signal.

There are several alternative interpolator implementations.

First, the above two stage interpolator can also be constructed using the $2n+4$ FIR filter and a simple linear interpolator without compensation. This is the equivalent of setting the compensation 5 multiplier C, of the four point interpolator, equal to zero. A second alternative is using the original four point interpolator along with a fixed weight linear phase $2n+5$ tap FIR. In order to accomplish this successfully it is first necessary to optimize the original four point interpolator technique.

10 The four point interpolator can be viewed as a variable FIR filter with non-linear phase. It should be recognized that the frequency response of the four point interpolator is highly dependent upon the value K which is chosen. Each particular horizontal compression or expansion can be viewed as being made up of the 15 output of several different FIR filters each having their own unique frequency and phase response. Artifacts in the interpolation become apparent when the collective frequency responses of the interpolator diverge. Thus, the overall pass band of a particular horizontal compression or expansion can be optimized by choosing 20 values of K which produce the most equalized frequency response.

This optimization can be shown by examining the frequency response of a 4 sample to 3 sample data reduction, that is, a 4:3 compression. The criteria that will be used to determine when artifacts become unacceptable is the frequency at which the 25 amplitude curves of the individual interpolations diverge by more than 1 dB. Choosing the initial values of K to be 1, 5/16, and 11/16 leads to a usable pass band of $.3 \times fs$. If the values of K are chosen to be 8/16, 13/16, and 3/16, the useable pass band becomes $.35 \times fs$. This represents a 16.6% improvement. Using this technique, the 30 frequency response of the horizontal interpolator can be equalized.

The values of K and C can be put into a memory block and, dependent upon the speedup required, a counter can index the read pointer to call out the desired memory location and load K and C into the interpolator multipliers. It is very advantageous, for this 35 reason, to encode the value of C into the value of K, such that a single 4-bit or 5-bit word can convey both K and C values. In other

words, C is a function of K, expressed as $C=f(K)$. The control signal sends a value of K to the linear interpolator. The value of K is decoded to yield a value of C for the compensation network multiplier. The FIR coefficients are the multipliers for C in the 5 overall interpolator equations.

This aspect of the invention can be extended generally to $2n$ tap FIR filters used as compensation networks, although it can become increasingly more difficult to use only two linear multipliers for calculating the linear interpolation and the 10 associated compensation network. An alternative to a ten tap FIR filter, for example, is to provide an eight tap fixed FIR filter for taps Z^{-1} to Z^{-6} , with taps Z^0 and Z^{-7} dependent upon either the value of K or C. This is feasible because as K approaches the value of 1/2 from either direction, that is $K=0$ or $K=1$, the frequency response 15 needs added compensation to extend its band pass.

A block diagram for a specific circuit 1150 for implementing an eight tap, two stage filter using a four point interpolator is shown in FIGURE 19. The video luminance signal to be expanded or compressed is an input to a horizontal delay line circuit 1152. The 20 outputs of the delay line $Z^0, Z^{-1}, Z^{-2}, Z^{-3}, Z^{-4}, Z^{-5}, Z^{-6}$ and Z^{-7} are inputs to an eight tap FIR filter 1154. The FIR filter generates at least one set of intermediate samples, designated I, for example between each of the real samples, designated Z. Results can sometimes be improved by using a plurality of FIR filters to 25 generate a plurality of sets of intermediate points, although this significantly increases the complexity of the system. Such additional FIR filters, each of which requires a Z^{-1} delay circuit, are shown by the multiple representations of FIR filter 1154 and Z^{-1} delay circuit 1158. Outputs Z^{-3}, Z^{-4} and Z^{-5} are also inputs to the 30 delay matching circuit 1156. The I₀ output is a direct input to a data selecting circuit 1160, as is a version I-1 thereof delayed by circuit 1158. The outputs $Z^{-(3+n)}, Z^{-(4+n)}$ and $Z^{-(5+n)}$ are also input to data selector circuit 1160. The inputs to data selector circuit 1160 are chosen for being the most symmetric with respect 35 to the delay. The number of such inputs is one more than the number of points of the interpolator of the second stage, in this case, a four

point interpolator 1162. The relative temporal position of the inputs to data selector 1160 is as follows:

$Z-(3+n), I_0, Z-(4+n), I-1, Z-(5+n)$.

Data selector circuit 1160 can be an array of multiplexers, for 5 example, controlled by the MUX_SEL control signal. The selectable sets are indicated diagrammatically and are so arranged that each interpolation of the interpolator 1162 is based on two real points and two intermediate points. The outputs Y_0, Y_1, Y_2 and Y_3 of data selecting circuit 1160 correspond to one of the two selectable sets, 10 and are the inputs to the four point interpolator 1162. Operation of the multiplexer control signal MUX_SEL will be a function of the K values, that is, $MUX_SEL=f(K)$. The MUX_SEL selection depends upon which of the original points the intermediate point falls between. The output Y_{out} of the interpolator 1162, which operates responsive 15 to the K and C control values, is an expanded or compressed video luminance signal.

What is claimed is:

- 1 1. An interpolation system, comprising:
 - 2 a finite impulse response filter for generating from a first
 - 3 signal of digital samples a second signal of digital samples
 - 4 representing signal points between said samples of said first signal;
 - 5 means for delaying said first signal;
 - 6 means for interleaving said second signal and said delayed
 - 7 first signal to produce a third signal of digital values having a
 - 8 sample density twice that of said first signal; and,
 - 9 a compensated variable interpolator for deriving from said
 - 10 third signal a fourth signal of digital samples in which the
 - 11 frequency content of information represented by said first signal
 - 12 has been changed.
- 1 2. The system of claim 1, wherein said first and second
- 2 signals have a first sampling rate and said third and fourth signals
- 3 have a second sampling rate twice that of said first sampling rate.
- 1 3. The system of claim 1, wherein said signal points of said
- 2 second signal are temporally between said samples of said first
- 3 signal.
- 1 4. The system of claim 1, wherein said signal points of said
- 2 second signal are temporally disposed midway between said samples
- 3 of said first signal.
- 1 5. The system of claim 1, further comprising means for
- 2 truncating portions of said first signal prior to generating said
- 3 second signal and delaying said first signal.
- 1 6. The system of claim 5, wherein said first signal is a video
- 2 signal, and said fourth signal represents an enlargement of the
- 3 picture represented by said truncated video signal.

1 7. The system of claim 1, wherein said first signal is a video
2 signal, and said fourth signal represents a compression of the
3 picture represented by said video signal.

1 8. The system of claim 1, wherein said first signal is a video
2 signal, and said fourth signal represents an enlargement of a portion
3 of the picture represented by said video signal.

1 9. The system of claim 1, wherein said compensated variable
2 interpolator controls a ratio of the number of samples per unit time
3 in said fourth signal to the number of samples per unit time in said
4 third signal.

1 10. The system of claim 1, further comprising means for
2 controlling said compensated variable interpolator to provide
3 selected ratios of compression and expansion of information in said
4 first signal.

1 11. The system of claim 9, wherein said ratio is in a range
2 wherein one limit is greater than one and the other limit is less than
3 one

1 12. The system of claim 9, wherein said ratio is a ratio of
2 integers.

1 13. An interpolation system, comprising:
2 means for truncating portions of a video signal of digital
3 samples;
4 a finite impulse response filter for generating from said
5 truncated video signal a second signal of digital samples
6 representing signal points between said samples of said truncated
7 video signal;
8 means for delaying said truncated video signal;
9 means for interleaving said second signal and said delayed
10 video signal to produce a third signal having a sample density twice
11 that of said video signal; and,

12 a compensated variable interpolator for deriving from said
13 third signal a fourth signal of digital samples in which the number
14 of samples per unit time is greater than the number of samples per
15 unit time in said third signal signal, for displaying a portion of said
16 picture in an enlarged scale.

1 14. The system of claim 13, wherein said video signal can
2 have frequency components higher than approximately 25% of a
3 sampling rate of said video signal without significant reduction of
4 bandwidth in said enlarged scale picture.

1 15. The system of claim 13, wherein said video signal can
2 have frequency components as high as approximately 40% of a
3 sampling rate of said video signal without significant reduction of
4 bandwidth in said enlarged scale picture.

1 16. The system of claim 13, wherein said truncating means
2 comprises a FIFO line memory.

1 17. The system of claim 13, further comprising means for
2 controlling said compensated variable interpolator to provide
3 selected ratios of enlargement.

1 18. An interpolation system, comprising:
2 a finite impulse response filter for generating from a first set
3 of digital samples a second set of digital samples representing
4 points between said samples of said first set;
5 means for delaying samples of said first set;
6 means for interleaving samples of said second set and samples
7 of said delayed first set to produce a third set of digital samples
8 having a higher sample density than that of said first set of
9 samples; and,
10 an interpolator for deriving from said third set of samples a
11 fourth set of samples in which the frequency content of information
12 represented by said first set has been changed.

1 19. The system of claim 18, wherein said sample interleaving
2 means selects groups of samples from said third set for processing
3 by said interpolator, each of said groups of said third set including
4 at least one sample from each of said first and second sets.

1 20. The system of claim 18, comprising a plurality of said
2 finite impulse response filters for generating a plurality of sets of
3 said intermediate samples.




FIG. 1(b)




FIG. 1(d)




FIG. 1(e)




FIG. 1(g)




FIG. 1(c)




FIG. 1(f)




FIG. 1(i)





FIG. 1(h)

FIG. 2

2/16






FIG. 3




FIG. 4





FIG. 6



7/16

FIG. 7








FIG. 8



8/16



**FIG. 10**



11/16




FIG. 12

12/16




FIG. 13

13/16






FIG. 14

14/16

STAGE 1 OF TWO STAGE VARIABLE INTERPOLATION FILTER: $n=2$ 

$$P3' = \sum_{i=0}^7 (P_i \cdot a_i) / 128 \quad \text{AND} \quad P4' = \sum_{i=0}^7 (P_{(i+1)} \cdot a_i)$$

WHERE: $a_i = \{ -3, 9, -22, 80, 80, -22, 9, -3 \}$ for $i = 0$ TO 7

FIG. 15**FIG. 16**

$$P3'' = -C(P3 + P4') + (K + C)(P5') + (1 - K + C)(P4) ; \text{ AND,}$$

$$P4'' = -C(P3' + P5) + (K + C)(P4) + (1 - K + C)(P4'')$$

WHERE: $K = \{0, 1/8, 2/8, \dots, 1\}$; AND,
 $C = I(K) = \{0, 1/32, 2/32, 3/32\}$

15/16

FIG. 17




FIG. 18





FIG. 19



INTERNATIONAL SEARCH REPORT

International Application No. PCT/US91/03734

I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all) ⁶

According to International Patent Classification (IPC) or to both National Classification and IPC

IPC(5): H04N 7/12

US. CL: 358/135,136

II. FIELDS SEARCHED

Minimum Documentation Searched ⁷

Classification System	Classification Symbols
U.S.	358/135,136,140,133

Documentation Searched other than Minimum Documentation
to the Extent that such Documents are Included in the Fields Searched ⁸

III. DOCUMENTS CONSIDERED TO BE RELEVANT ⁹

Category ¹⁰	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³
A	US, A, 4,771,331 (BIERLING ET AL.) 13 SEPTEMBER 1988	
A	US, A, 4,829,378 (LEGALL) 09 MAY 1989	
A,P	US, A, 5,019,903 (DOUGALL ET AL.) 28 MAY 1991	

* Special categories of cited documents: ¹⁰

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

IV. CERTIFICATION

Date of the Actual Completion of the International Search

05 AUGUST 1991

International Searching Authority

TSA/US

Date of Mailing of this International Search Report

13 SEP 1991

Signature of Authorized Officer

Nguyen Ngoc-Ho
for JOHN K. PENG NGUYEN NGOC-HO
INTERNATIONAL DIVISION