



(22) Date de dépôt/Filing Date: 2012/01/06

(41) Mise à la disp. pub./Open to Public Insp.: 2012/03/22

(45) Date de délivrance/Issue Date: 2015/03/17

(62) Demande originale/Original Application: 2 763 276

(51) Cl.Int./Int.Cl. *G09G 5/373* (2006.01),
G06F 3/0484 (2013.01), *G06F 3/0488* (2013.01)


(72) Inventeurs/Inventors:
MANDIC, MIRKO, US;
ENS, MICHAEL J., US;
ROGERS, JUSTIN E., US;
RAKOW, MATTHEW A., US;
ROSSI, JACOB S., US;
KIM, JANE T., US;
ROBERTS, SANDRA G., US;
PRAKASH, SIDDHARTHA, US

(73) Propriétaire/Owner:
MICROSOFT CORPORATION, US

(74) Agent: SMART & BIGGAR

(54) Titre : LOGIQUE DE TEMPORISATION ET D'EFFET ZOOM DU POINTEUR D'ENTREE

(54) Title: INPUT POINTER DELAY AND ZOOM LOGIC



(57) Abrégé/Abstract:

Various embodiments enable repetitive gestures, such as multiple serial gestures, to be implemented efficiently so as to enhance the user experience. Other embodiments provide various approaches to zoom operations that consider a particular element's

(57) **Abrégé(suite)/Abstract(continued):**

contextual surroundings in making a zoom decision that is designed to enhance the user experience and provide efficiently-zoomed content given a device's or rendering container's form factor.

51331-1178D1

ABSTRACT

Various embodiments enable repetitive gestures, such as multiple serial gestures, to be implemented efficiently so as to enhance the user experience. Other embodiments provide various approaches to zoom operations that consider a particular element's contextual surroundings in making a zoom decision that is designed to enhance the user experience and provide efficiently-zoomed content given a device's or rendering container's form factor.

-

.

51331-1178D1

INPUT POINTER DELAY AND ZOOM LOGIC

This application is a divisional of Canadian Patent Application No. 2,763,276 filed January 6, 2012.

BACKGROUND

5 **[0001]** When a user provides input to a computing device to zoom in on a particular element, it can be assumed that the user is interested in that particular element. Challenges continue to face those who develop zoom-based technology to provide a desirable user experience.

SUMMARY

10 **[0002]** This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter.

15 **[0003]** Various embodiments enable repetitive gestures, such as multiple serial gestures, to be implemented efficiently so as to enhance the user experience.

20 **[0004]** In at least some embodiments, a first gesture associated with an object is detected. The first gesture is associated with a first action. Responsive to detecting the first gesture, pre-processing associated with the first action is performed in the background. Responsive to detecting a second gesture associated with the object within a pre-defined time period, an action associated with the second gesture is performed. Responsive to the second gesture not being performed within the pre-defined time period, processing associated with the first action is completed.

25 **[0005]** In at least some other embodiments, a first tap associated with an object is detected and a timer is started. Responsive to detecting the first tap, a style that has been defined for an element of which the object is a type is applied. Responsive to detecting a second tap within a time period defined by the timer, an

51331-1178D1S

action associated with a gesture comprising the first and second taps is performed. Responsive to not detecting a second tap within the time period defined by the timer, an action associated with the first tap is performed.

[0006] In yet other embodiments, various approaches to zoom operations

5 consider a particular element's contextual surroundings in making a zoom decision that is designed to enhance the user experience and provide efficiently-zoomed content given a device's or rendering container's form factor.

[0006a] According to one aspect of the present invention, there is provided a method comprising: identifying an object on which to zoom; calculating zoom ratios

10 for an identified object and at least one other object in a display chain associated with the identified object and said at least one other object; identifying a zoom object based, at least in part, on said zoom ratios, said zoom object including said identified object and said at least one other object in the display chain; computing a zoom ratio of the zoom object; and causing zooming of the zoom object using the zoom object's
15 zoom ratio.

[0006b] According to another aspect of the present invention, there is provided one or more computer readable storage media embodying computer readable

instructions which, when executed, implement a method comprising: identifying an object on which to zoom; calculating zoom ratios for an identified object and other
20 objects in a display chain associated with the identified object and the other objects; categorizing the identified object and the other objects within a respective priority category of a plurality of categories; for any priority category that has more than one object, identifying a best object based on a ranking of the more than one object in the priority category; identifying a best object overall from among the priority categories;
25 computing a zoom ratio of the identified best object; and causing zooming of the identified best object using the computed zoom ratio.

[0006c] According to another aspect of the present invention, there is provided a system comprising: one or more processors; one or more computer readable

51331-1178D1S

storage media; computer readable instructions embodied on the one or more computer readable storage media which, when executed under the influence of the one or more processors, implement a method comprising: detecting a first gesture associated with an object, the first gesture being associated with a first action;

5 responsive to detecting the first gesture, performing pre-processing associated with the first action in the background and applying one or more styles that are defined for an object of which the object is a type; responsive to detecting a second gesture associated with the object within a pre-defined time period, performing a zoom operation associated with the second gesture and discarding the pre-processing

10 associated with the first action; and responsive to the second gesture not being performed within the pre-defined time period, completing processing associated with the first action.

[0006d] According to still another aspect of the present invention, there is provided a method comprising: detecting a first gesture associated with an object,

15 the first gesture being associated with a first action; responsive to detecting the first gesture, performing pre-processing associated with the first action in the background and applying one or more styles that are defined for an object of which the object is a type; responsive to detecting the first gesture, performing pre-processing associated with the first action in the background and applying one or more styles that are

20 defined for an object of which the object is a type; responsive to detecting a second gesture associated with the object within a pre-defined time period, performing a zoom operation associated with the second gesture and discarding the pre-processing associated with the first action; and responsive to the second gesture not being performed within the pre-defined time period, completing processing

25 associated with the first action.

[0006e] According to yet another aspect of the present invention, there is provided one or more computer readable storage media having stored thereon computer executable instructions which, when executed under the influence of the one or more processors, implement a method comprising: detecting a first gesture

30 associated with an object, the first gesture being associated with a first action;

51331-1178D1S

responsive to detecting the first gesture, performing pre-processing associated with the first action in the background and applying one or more styles that are defined for an object of which the object is a type; responsive to detecting a second gesture associated with the object within a pre-defined time period, performing a zoom
 5 operation associated with the second gesture and discarding the pre-processing associated with the first action; and responsive to the second gesture not being performed within the pre-defined time period, completing processing associated with the first action.

BRIEF DESCRIPTION OF THE DRAWINGS

10 **[0007]** The detailed description is described with reference to the accompanying figures. In the figures, the left-most digit(s) of a reference number identifies the figure in which the reference number first appears. The use of the same reference numbers in different instances in the description and the figures may indicate similar or identical items.

15 **[0008]** FIG. 1 is an illustration of an environment in an example implementation in accordance with one or more embodiments.

[0009] FIG. 2 is an illustration of a system in an example implementation showing FIG. 1 in greater detail.

20 **[0010]** FIG. 3 is a flow diagram that describes steps of a method in accordance with one or more embodiments.

[0011] FIG. 4 is a flow diagram that describes steps of a method in accordance with one or more embodiments.

[0012] FIG. 5 is a flow diagram that describes steps of a method in accordance with one or more embodiments.

25 **[0013]** FIG. 6 is a flow diagram that describes steps of a method in accordance with one or more embodiments.

51331-1178D1S

[0014] FIG. 7 is a flow diagram that describes steps of a method in accordance with one or more embodiments.

51331-1178D1

[0015] FIG. 8 is an illustration of an example grid in accordance with one or more embodiments.

[0016] FIG. 9 illustrates an example computing device that can be utilized to implement various embodiments described herein.

5

DETAILED DESCRIPTION

Overview

[0017] Various embodiments enable repetitive gestures, such as multiple serial gestures, to be implemented efficiently so as to enhance the user experience.

[0018] In at least some embodiments, a first gesture associated with an object is detected. The first gesture is associated with a first action. Responsive to detecting the first gesture, pre-processing associated with the first action is performed in the background. Responsive to detecting a second gesture associated with the object within a pre-defined time period, an action associated with the second gesture is performed. Responsive to the second gesture not being performed within the pre-defined time period, processing associated with the first action is completed.

[0019] In at least some other embodiments, a first tap associated with an object is detected and a timer is started. Responsive to detecting the first tap, a style that has been defined for an element of which the object is a type is applied. Responsive to detecting a second tap within a time period defined by the timer, an action associated with a gesture comprising the first and second taps is performed. Responsive to not detecting a second tap within the time period defined by the timer, an action associated with the first tap is performed.

[0020] In yet other embodiments, various approaches to zoom operations consider a particular element's contextual surroundings in making a zoom decision that is designed to enhance the user experience and provide efficiently-zoomed content given a device's or rendering container's form factor.

51331-1178D1

[0021] In the following discussion, an example environment is first described that is operable to employ the techniques described herein. Example illustrations of the various embodiments are then described, which may be employed in the example environment, as well as in other environments. Accordingly, the example environment is not limited to performing the described embodiments and the described embodiments are not limited to implementation in the example environment.

Example Operating Environment

[0022] FIG. 1 is an illustration of an environment 100 in an example implementation that is operable to employ the input pointer delay techniques and zoom logic described in this document. The illustrated environment 100 includes an example of a computing device 102 that may be configured in a variety of ways. For example, the computing device 102 may be configured as a traditional computer (e.g., a desktop personal computer, laptop computer, and so on), a mobile station, an entertainment appliance, a set-top box communicatively coupled to a television, a wireless phone, a netbook, a game console, a handheld device, and so forth as further described in relation to FIG. 2. Thus, the computing device 102 may range from full resource devices with substantial memory and processor resources (e.g., personal computers, game consoles) to a low-resource device with limited memory and/or processing resources (e.g., traditional set-top boxes, hand-held game consoles). The computing device 102 also includes software that causes the computing device 102 to perform one or more operations as described below.

[0023] Computing device 102 includes an input pointer delay module 103 configured to enable repetitive gestures, such as multiple serial gestures, to be implemented efficiently so as to enhance the user experience. The input pointer delay module 103 can make use of a timer to measure the time between multiple serial gestural inputs. Given the type and timing of the gestural inputs, actions associated with a first of the gestures and/or one or more of subsequent gestures or combinations thereof can be performed.

51331-1178D1

[0024] Computing device 102 also includes a zoom module 104 that is configured to perform operations as described above and below. The zoom module is configured to perform zoom operations that consider and take into account a particular object or element's contextual surroundings in making a zoom decision that is designed to enhance the user experience and provide efficiently-zoomed content given a device's or rendering container's form factor.

[0025] Computing device 102 also includes a gesture module 105 that recognizes input pointer gestures that can be performed by one or more fingers, and causes operations or actions to be performed that correspond to the gestures. The gestures may be recognized by module 105 in a variety of different ways. For example, the gesture module 105 may be configured to recognize a touch input, such as a finger of a user's hand 106a as proximal to display device 108 of the computing device 102 using touchscreen functionality. Module 105 can be utilized to recognize single-finger gestures and bezel gestures, multiple-finger/same-hand gestures and bezel gestures, and/or multiple-finger/different-hand gestures and bezel gestures. Although the input pointer delay module 103, zoom module 104, and gesture module 105 are depicted as separate modules, the functionality provided by each can be implemented in a single, integrated gesture module. The functionality provided by modules 103, 104 and/or 105 can be implemented by any suitably configured application including, by way of example and not limitation, a web browser.

[0026] The computing device 102 may also be configured to detect and differentiate between a touch input (e.g., provided by one or more fingers of the user's hand 106a) and a stylus input (e.g., provided by a stylus 116). The differentiation may be performed in a variety of ways, such as by detecting an amount of the display device 108 that is contacted by the finger of the user's hand 106a versus an amount of the display device 108 that is contacted by the stylus 116.

[0027] Thus, the gesture module 105 may support a variety of different gesture techniques through recognition and leverage of a division between stylus and touch inputs, as well as different types of touch inputs.

51331-1178D1

[0028] FIG. 2 illustrates an example system 200 showing the input pointer delay module 103, zoom module 104 and gesture module 105 as being implemented in an environment where multiple devices are interconnected through a central computing device. The central computing device may be local to the multiple devices or may be located remotely from the multiple devices. In one embodiment, the central computing device is a “cloud” server farm, which comprises one or more server computers that are connected to the multiple devices through a network or the Internet or other means.

[0029] In one embodiment, this interconnection architecture enables functionality to be delivered across multiple devices to provide a common and seamless experience to the user of the multiple devices. Each of the multiple devices may have different physical requirements and capabilities, and the central computing device uses a platform to enable the delivery of an experience to the device that is both tailored to the device and yet common to all devices. In one embodiment, a “class” of target device is created and experiences are tailored to the generic class of devices. A class of device may be defined by physical features or usage or other common characteristics of the devices. For example, as previously described the computing device 102 may be configured in a variety of different ways, such as for mobile 202, computer 204, and television 206 uses. Each of these configurations has a generally corresponding screen size or form factor and thus the computing device 102 may be configured as one of these device classes in this example system 200. For instance, the computing device 102 may assume the mobile 202 class of device which includes mobile telephones, music players, game devices, and so on. The computing device 102 may also assume a computer 204 class of device that includes personal computers, laptop computers, netbooks, and so on. The television 206 configuration includes configurations of device that involve display in a casual environment, e.g., televisions, set-top boxes, game consoles, and so on. Thus, the techniques described herein may be supported by these various configurations of the computing device 102 and are not limited to the specific examples described in the following sections.

51331-1178D1

[0030] Cloud 208 is illustrated as including a platform 210 for web services 212. The platform 210 abstracts underlying functionality of hardware (e.g., servers) and software resources of the cloud 208 and thus may act as a “cloud operating system.” For example, the platform 210 may abstract resources to connect the
5 computing device 102 with other computing devices. The platform 210 may also serve to abstract scaling of resources to provide a corresponding level of scale to encountered demand for the web services 212 that are implemented via the platform 210. A variety of other examples are also contemplated, such as load balancing of servers in a server farm, protection against malicious parties (e.g., spam, viruses,
10 and other malware), and so on.

[0031] Thus, the cloud 208 is included as a part of the strategy that pertains to software and hardware resources that are made available to the computing device 102 via the Internet or other networks.

[0032] The gesture techniques supported by the input pointer delay module
15 103 and gesture module 105 may be detected using touchscreen functionality in the mobile configuration 202, track pad functionality of the computer 204 configuration, detected by a camera as part of support of a natural user interface (NUI) that does not involve contact with a specific input device, and so on. Further, performance of the operations to detect and recognize the inputs to identify a particular gesture may
20 be distributed throughout the system 200, such as by the computing device 102 and/or the web services 212 supported by the platform 210 of the cloud 208.

[0033] Generally, any of the functions described herein can be implemented using software, firmware, hardware (e.g., fixed logic circuitry), manual processing, or a combination of these implementations. The terms “module,” “functionality,” and
25 “logic” as used herein generally represent software, firmware, hardware, or a combination thereof. In the case of a software implementation, the module, functionality, or logic represents program code that performs specified tasks when executed on or by a processor (e.g., CPU or CPUs). The program code can be stored in one or more computer readable memory devices. The features of the

51331-1178D1

gesture techniques described below are platform-independent, meaning that the techniques may be implemented on a variety of commercial computing platforms having a variety of processors.

[0034] In the discussion that follows, various sections describe various example embodiments. A section entitled “Example Input Pointer Delay Embodiments” describes embodiments in which an input pointer delay can be employed in accordance with one or more embodiments. Following this, a section entitled “Implementation Example” describes an example implementation in accordance with one or more embodiments. Next, a section entitled “Example Zoom Logic” describes zoom logic in accordance with one or more embodiments. Following this, a section entitled “Zoom Logic – Implementation Example” describes one implementation example in accordance with one or more embodiments. Last, a section entitled “Example Device” describes aspects of an example device that can be utilized to implement one or more embodiments.

[0035] Having described example operating environments in which the input pointer delay functionality and zoom logic can be utilized, consider now a discussion of some example embodiments.

Example Input Pointer Delay Embodiments

[0036] In the examples about to be described, two different approaches are described which, in at least some embodiments, may be employed together. The first approach utilizes background pre-processing in connection with receiving multiple serial gestures to mitigate the negative impact, as perceived by the user, of an input pointer delay. The second approach, which may or may not be used in connection with the first approach, is designed to provide concurrent user feedback to a user who is interacting with a resource such as a webpage. Each approach is discussed under its own separate sub-heading, followed by a discussion of an approach that combines both the first and second approaches.

Background Pre-Processing - Example

51331-1178D1

[0037] FIG. 3 is a flow diagram that describes steps in a method accordance with one or more embodiments. The method can be performed in connection with any suitable hardware, software, firmware, or combination thereof. In at least some embodiments, the method can be performed by software in the form of computer readable instructions, embodied on some type of computer-readable storage medium, which can be performed under the influence of one or more processors. Examples of software that can perform the functionality about to be described are the input pointer delay module 103, zoom module 104, and the gesture module 105 described above.

10 **[0038]** Step 300 detects a first gesture associated with an object. The first gesture is associated with a first action that can be performed relative to the object. Any suitable type of gesture can be detected. By way of example and not limitation, the first gesture can comprise a touch gesture, a tap gesture, or any suitable other type of gesture as described above. In addition, any suitable type of first action can
15 be associated with the first gesture. For example, in at least some embodiments, the first action comprises a navigation that can be performed to navigate from one resource, such as a webpage, to another resource, such as a different webpage. Responsive to detecting the first gesture, step 302 performs pre-processing associated with the first action. In one or more embodiments, pre-processing is
20 performed in the background so as to be undetectable by the user. Any suitable type of pre-processing can be performed including, by way of example and not limitation, initiating downloading of one or more resources. For example, assume that the object comprises a hyperlink or some other type of navigable resource. The pre-processing, in this instance, can include downloading one or more resources associated with
25 performing the navigation.

[0039] Step 304 ascertains whether a second gesture is detected within a pre-defined time period. Any suitable pre-defined time period can be utilized. In at least some embodiments, the pre-defined time period is equal to or less than about 300 ms. Further, any suitable type of second gesture can be utilized. By way of example

51331-1178D1

and not limitation, the second gesture can comprise a touch gesture, a tap gesture, or any suitable other type of gesture as described above.

[0040] Responsive to detecting the second gesture associated with the object within a pre-defined time period, step 306 performs an action associated with the
5 second gesture. In at least some embodiments, the action can be associated with the gesture that includes both the first and second gestures. Any suitable type of action can be associated with the second gesture. By way of example and not limitation, such actions can include performing a zoom operation in which the object is zoomed up. In this case, the pre-processing performed by step 302 can be
10 discarded. Zooming can be performed in any suitable way, examples of which are described below.

[0041] Alternately, responsive to the second gesture not being performed within the pre-defined time period, step 308 completes processing associated with the first action. This step can be performed in any suitable way. By way of example
15 and not limitation, completion of the processing can include performing a navigation associated with the object and the resource or resources for which downloading was initiated during pre-processing.

[0042] In at least some embodiments, as will become apparent below, in addition to performing the pre-processing as described above, responsive to
20 detecting the first gesture, one or more styles that are defined for an element of which the object is a type can be applied. Any suitable type of styles can be applied including, by way of example and not limitation, styles that are defined by a CSS pseudo-class. For example, styles associated with the :hover and/or :active pseudo-classes can be applied. As will be appreciated by the skilled artisan, such styles can
25 be used to change an element's display properties such as the size, shape, color of an element, or to change a display background, initiate a position change, provide an animation or transition, and the like. For example, if a hyperlink normally changes colors or is underlined when selected by virtue of a defined style, such style can be applied when the first gesture is detected at step 300.

51331-1178D1

[0043] Having described how background pre-processing can be performed in accordance with one or more embodiments, consider now how concurrent user feedback can be provided in accordance with one or more embodiments.

Concurrent User Feedback - Example

5 **[0044]** FIG. 4 is a flow diagram that describes steps in a method in accordance with one or more embodiments. The method can be performed in connection with any suitable hardware, software, firmware, or combination thereof. In at least some embodiments, the method can be performed by software in the form of computer readable instructions, embodied on some type of computer-readable
10 storage medium, which can be performed under the influence of one or more processors. Examples of software that can perform the functionality about to be described are the input pointer delay module 103, zoom module 104, and the gesture module 105 described above.

[0045] Step 400 detects a first tap associated with an object. Responsive to
15 detecting the first tap, step 402 starts a timer. Responsive to detecting the first tap, step 404 applies a style that has been defined for an element of which the object is of type. Any suitable type of style or styles can be applied including, by way of example and not limitation, styles that are defined by a CSS pseudo-class. For example, styles associated with the :hover and/or :active pseudo-classes can be applied.

20 **[0046]** Step 406 ascertains whether a second tap is detected within a time period defined by the timer. Any suitable time period can be utilized. In at least some embodiments, the time period can be equal to or less than about 300 ms. Responsive to detecting the second tap within the time period defined by the timer, step 408 performs an action associated with a gesture comprising the first and second taps.
25 Any suitable action can be performed. In at least some embodiments, the action associated with the gesture comprising the first and second taps comprises a zoom operation. Some examples of how zoom operations can be performed are described below.

51331-1178D1

[0047] Responsive to not detecting a second tap within the time period defined by the timer, step 410 performs an action associated with the first tap. Any suitable action can be performed. In at least some embodiments, the action associated with the first tap comprises performing a navigation.

5 **[0048]** In at least some embodiments, within the time period defined by the timer, pre-processing associated with performing the action associated with the first tap can be performed. Any suitable type of pre-processing can be performed. In at least some embodiments, pre-processing can include, by way of example and not limitation, initiating downloading of one or more resources. In this instance, the action
10 associated with the first tap can comprise a navigation associated with the downloaded resource or resources.

[0049] Having considered embodiments that employ concurrent user feedback, consider now an approach that utilizes both background pre-processing and concurrent user feedback in accordance with one or more embodiments.

15 Background Pre-Processing and Concurrent User Feedback - Example

[0050] FIG. 5 is a flow diagram that describes steps in a method in accordance with one or more embodiments. The method can be performed in connection with any suitable hardware, software, firmware, or combination thereof. In at least some embodiments, the method can be performed by software in the form of computer
20 readable instructions, embodied on some type of computer-readable storage medium, which can be performed under the influence of one or more processors. Examples of software that can perform the functionality about to be described are the input pointer delay module 103, zoom module 104, and the gesture module 105 described above.

25 **[0051]** Step 500 detects a first gesture associated with an object. The first gesture is associated with a first action that can be performed relative to the object. Any suitable type of gesture can be detected. By way of example and not limitation, the first gesture can comprise a touch gesture, a tap gesture, or any suitable other

51331-1178D1

type of gesture as described above. In addition, any suitable type of first action can be associated with the first gesture. For example, in at least some embodiments, the first action comprises a navigation that can be performed to navigate from one resource, such as a webpage, to another resource, such as a different webpage.

- 5 Responsive to detecting the first gesture, step 502 performs pre-processing associated with the first action in the background. Any suitable type of pre-processing can be performed including, by way of example and not limitation, initiating downloading of one or more resources. For example, assume that the object comprises a hyperlink or some other type of navigable resource. The pre-processing,
- 10 in this instance, can include downloading one or more resources associated with performing the navigation.

- [0052]** Step 504 applies one or more styles that are defined for an element of which the object is a type. Examples of how this can be done are provided above. Step 506 ascertains whether a second gesture is detected within a pre-defined time
- 15 period. Responsive to detecting the second gesture within the predefined time period, step 508 performs an action associated with the second gesture. In at least some embodiments, the action can be associated with a gesture that includes both the first and second gestures. In at least some embodiments, the first and second gestures can comprise a tap gesture. Any suitable type of action can be associated
- 20 with the second gesture. By way of example and not limitation, such action can include performing a zoom operation in which the object is zoomed up. Examples of how this can be done are described below. In this case, the pre-processing performed by step 502 can be discarded.

- [0053]** Alternately, responsive to the second gesture not being performed
- 25 within the pre-defined time period, step 510 completes processing associated with the first action. This step can be performed in any suitable way. By way of example and not limitation, completion of the processing can include performing a navigation associated with the object and the resource or resources for which downloading was initiated during pre-processing.

51331-1178D1

[0054] Having considered some example methods, consider now an implementation example.

Implementation Example

[0055] In one or more embodiments, the functionality described above can be implemented by delaying input pointer events. One way to do this is as follows. When an input is received such as a tap from a gesture, a pinch gesture, a pen tap, a mouse click, input from a natural user interface (NUI) and the like, a timer is set to a predefined time such as, by way of example and not limitation, 300 ms. A double tap caching component is utilized and input messages are re-routed to the double tap caching component. In addition, a preliminary message is sent to a selection component to perform selection-related logic without delay. The functionality performed by the selection-related component can be performed, in the above examples, by the input pointer delay module 103. Selection-related logic can include selecting text that was tapped, un-selecting text that was previously tapped, launching a context menu because already-selected text has been tapped, and the like.

[0056] In one or more embodiments, pseudo-classes such as :active and :hover would already have been applied by normal input processing because a tap is composed of a touch-down and a touch-up, and :active and :hover are applied during touch-down, before a tap is recognized. This also means that the webpage would have seen some events leading up to the tap.

[0057] The double tap caching component examines the previously-sent message and performs the following logic. First, the component ascertains whether the input is caused by a touch with the primary contact (i.e., a touch with one finger). If not, then the input is processed as usual. This allows things such as mouse interactions to continue in an unimpeded manner.

[0058] If, on the other hand, the input is caused by a touch with the primary contact, the logic continues and ascertains whether such is a new contact. If the

51331-1178D1

input is not a new contact, then a corresponding message is appended to an internal deferred messages queue and ignored for the time being. Any information that can only be gathered at the time a message is received is gathered and stored in this queue, e.g., whether the touch came from physical hardware or was simulated. If, on
 5 the other hand, the contact is a new contact the logic continues as described below.

[0059] The logic now ascertains whether the location of the new contact is close enough to a previously-detected tap to be considered a double tap. If not, this is treated the same as a timeout. When a timeout occurs, if the element that was originally tapped still exists, then every input message in the deferred messages
 10 queue is processed immediately, in order, thus completing a delayed tap. An exception is that these messages are hidden from the selection manager because actions associated with the selection manager have already been performed.

[0060] If the location of the new contact is close enough to the previously-detected tap to be considered a double tap, the logic ascertains whether the
 15 originally-tapped element still exists. If the originally-tapped element still exists, a "pointer cancel" event is sent through the document object model (DOM) and :active and :hover are removed to indicate to the webpage that saw the first half of the tap that no more of the tap will be forthcoming. Whether or not the element still exists, the logic continues as described below.

20 **[0061]** Next, any text on the page is unselected which effectively undoes the previous selection. At this point, a double tap zoom operation is performed and all messages in the deferred messages queue are discarded so that the webpage never sees them.

[0062] Having consider example embodiments in which input delay can occur,
 25 consider now a discussion of example zoom logic in accordance with one or more embodiments.

51331-1178D1

Example Zoom Logic

[0063] FIG. 6 is a flow diagram that describes steps in a method in accordance with one or more embodiments. The method can be performed in connection with any suitable hardware, software, firmware, or combination thereof. In at least some
5 embodiments, the method can be performed by software in the form of computer readable instructions, embodied on some type of computer-readable storage medium, which can be performed under the influence of one or more processors. Examples of software that can perform the functionality about to be described are the input pointer delay module 103, zoom module 104, and the gesture module 105
10 described above. The software that performs the method about to be described can be embodied by a web browser or a module or component other than a web browser.

[0064] Step 600 identifies an object on which to zoom. This step can be performed in any suitable way. For example, in at least some embodiments, an object can be identified by receiving a touch gesture associated with the object. Any suitable
15 types gesture can be utilized including, by way of example and not limitation, a tap gesture, a double tap gesture such as that described above, a pinch gesture, a mouse click, a stylus selection, and the like. Alternately or additionally, an object can be identified via an input other than a touch gesture such as, by way of example and not limitation, a natural user interface (NUI) gesture.

[0065] Step 602 calculates zoom ratios for an identified object and at least one other object in a display chain associated with the identified object and other object(s). In one or more embodiments, a display chain can include a hierarchical relationship of objects that appear within other objects. For example, in a webpage, a
20 child object such as an image, may have a parent object that includes text. The parent object, in turn, can have a parent object that might include several paragraphs such as that which would appear in a story. Accordingly, this step calculates zoom ratios for multiple objects that appear within a display chain.

51331-1178D1

[0066] Step 604 identifies a zoom object to zoom based, at least in part, on the zoom ratios calculated in step 602. In one or more embodiments, the zoom object can include the initially-identified object as well as another object or objects that appear in the display chain. By selecting a zoom object that includes multiple
5 different objects in the display chain, the contextual surrounding of the initially-identified object is considered in the zoom operation that is to be performed. Step 606 computes a zoom ratio of the zoom object and step 608 causes zooming of the zoom object using the computed zoom ratio from step 606. This step can be performed by calling a suitably configured application program interface (API) and passing in the
10 relevant information to use in zooming. In at least some embodiments, the zoom operation of step 608 is performed on less than all of the objects in the display chain. Further, as will become apparent below, a zoom operation that uses a category-based prioritization process can be used to select the objects that comprise the zoom object.

15 **[0067]** In this manner, not only is the initially-identified object zoomed, but at least other objects related to the initially-identified object are zoomed. As such, content that may be relevant to the initially-identified object are subject to the zoom operation. Accordingly, such relevant content, in addition to the initially-identified object, can be more easily consumed by a user.

20 **[0068]** But one way in which the above-described functionality can be implemented is described below in a section entitled "Zoom Logic-Implementation Example."

[0069] FIG. 7 is a flow diagram that describes steps in a method in accordance with one or more embodiments. The method can be performed in
25 connection with any suitable hardware, software, firmware, or combination thereof. In at least some embodiments, the method can be performed by software in the form of computer readable instructions, embodied on some type of computer-readable storage medium, which can be performed under the influence of one or more processors. Examples of software that can perform the functionality about to be

51331-1178D1

described are the input pointer delay module 103, zoom module 104, and the gesture module 105 described above. The software that performs the method about to be described can be embodied by a web browser or a module or component other than a web browser.

- 5 **[0070]** Step 700 identifies an object on which to zoom. This step can be performed in any suitable way. For example, in at least some embodiments, an object can be identified by receiving a touch gesture associated with the object. Any suitable types gesture can be utilized including, by way of example and not limitation, a tap gesture, a double tap gesture such as that described above, a pinch gesture, a
10 mouse click, a stylus selection, and the like. Alternately or additionally, an object can be identified via an input other than a touch gesture such as, by way of example and not limitation, a natural user interface (NUI) gesture.

- [0071]** Step 702 calculates zoom ratios for the identified object and other objects in a display chain associated with the identified object and the other objects.
15 Examples of how this can be done are described above and below. Step 704 categorizes the objects within a respective priority category of a plurality of priority categories. Accordingly, the objects are ranked within one of the plurality of categories. In one or more embodiments, the categories can be defined by object width ratios and object height ratios. One example way in which this can be done is
20 described below. For any priority category that has more than one object, step 706 identifies a best object within the priority category that has more than one object. Accordingly, in an event that more than one object is ranked within the same category, a best object within that category is selected. In one or more embodiments, the best object can comprise a plurality of objects that are less than the total number
25 of objects in the display chain. An example of how this can be done is provided below.

[0072] Step 708 identifies a best object overall from among the priority categories. In one or more embodiments, this step can be performed by selecting the best object from a category with the highest priority. One example of how this can be

51331-1178D1

done is provided below. Step 710 computes a zoom ratio of the identified best object. One example of how this can be done is provided below. Step 712 causes zooming of the identified best object using the computed zoom ratio from step 710. This step can be performed by calling a suitably configured application program interface (API) and passing in the relevant information to use in zooming.

[0073] Having considered example methods in accordance with one or more embodiments, consider now an implementation example that employs zoom logic in accordance with one or more embodiments.

Zoom Logic – Implementation Example

[0074] Once an input associated with a zoom operation is received, such as those described above as well as others, zoom logic can be employed which effectively identifies the element or object to focus on, calculates a zoom ratio that is to be used to conduct the zoom operation, and animates the identified element or object into view. Each of these aspects is discussed under its own sub-heading below.

Identify Object or Element to Focus on

[0075] In one or more embodiments, an element or object to focus on can be one of the following: the element or object relative to which the input was received, or one or more of its ancestors in an associated display chain, such as a display tree that has been built prior to rendering. In one or more embodiments, the element or object can include multiple other elements or objects, up to but not including the page on which the elements or objects appear. The element or object to focus on is the one that can desirably fill the associated rendering container, such as an associated application window, device screen and the like, while being maximally zoomed.

[0076] In one or more embodiments, parameters are established and utilized to ascertain how to conduct a particular zoom operation. In at least one embodiment, parameters associated with a zoom ratio are established such that the zoom ratio

51331-1178D1

cannot be greater than 150% or smaller than 100%. In this particular example, a so-called aspirational ratio of 140% is utilized to guide the processing associated with zoom operation.

[0077] Given this, each element or object can be categorized into one of a plurality of priority categories. As but one example, consider FIG. 8 which illustrates a priority grid, generally at 800, that includes a plurality of priority categories designated P1-P9. Individual priority categories are defined based upon width ratios and height ratios as indicated. The categories are defined by what percent zoom would need to be applied in order to fill the rendering container, e.g., application window or device screen, for each axis. In this example, the size of the element or object itself (as indicated by the boxes in dark lines) is utilized to categorize the element or object within a particular category. Alternately, consideration can be given to take into account whether the element is occluded. For example, if a large element is contained in a small element with a scrollbar that allows the user to see the whole element, the effective element size would be the size of the small element with a scrollbar.

[0078] In the illustrated and described example, when the page itself has a default zoom of 100%, in order to avoid favoring elements or objects that are close to the page shape/width, a percentage of 105% is used as the cutoff point between an element that is too wide and just fits.

[0079] In the priority grid, the highest priority category is P1 because an element can be zoomed around 140% to fill the rendering container to achieve the aspirational ratio. Lower priority categories, in order from high to low are: P2, P3, P4, P5, P6, P7, P8, and P9.

25 Calculate Zoom Ratios

[0080] For each element within the display chain (including the element that was selected), a calculation is performed to calculate the element's zoom ratio according to the following logic:

51331-1178D1

- **P1 element:** ratio which ensures that most of the screen or rendering container is fully filled with the element, without any of it getting clipped. This is an area-based calculation, implicitly taking into account both the height and the width of the element, but collapsing them to a single zoom ratio value.
- 5 • **P2, P3, P8 elements:** ratio that ensures that the element fills the window horizontally (as closely to the vertical window edges as possible).
- **P4, P5, P7 elements:** ratio that ensures that the element fills the window vertically (as closely to the horizontal window edges as possible).
- **P6 element:** automatically gets zoomed to an upper bound zoom, e.g., 150%.
- 10 • **P9 element:** 140%

[0081] Note that in one or more embodiments, fixed elements are not treated as special cases. In other words, fixed elements should not be special with respect to zoom level (and should zoom like any other element/entire page). They should, however, be treated as special when it comes to positioning/animation, as described below.

[0082] Once all of the elements within the element's display chain are traversed (including the element that was selected), elements are stack-ranked within each priority category. For example, if there is more than one element in category P1 in the display chain, it is compared with all of the other elements in category P1. The best element within each priority category is the element with the zoom ratio (from the above element zoom ratio calculation) that is closest to 140%. Alternately, rather than finding the best element within each priority category, one can find the best element within the best priority category. For example, as soon as a P2 element is encountered, any P5 elements can be ignored.

[0083] Thus, as noted above, for any given element or object, a calculation is performed to ascertain how much it would take to zoom to the aspirational ratio (to

51331-1178D1

generally fill the rendering container). For example, if horizontally one would need a 200% zoom, and vertically one would need a 200% zoom, then the element or object falls into the P6 category, meaning that it is too small. Thus, the priority categories essentially identify where elements or objects are too small (either horizontally, vertically, or different combinations) and define weightings for each. As noted above, category P1 is the highest priority because here, one can zoom around 140% and have it fill the screen or otherwise achieve the aspirational ratio. As the display chain is traversed and an element's or object's ancestors are considered, the progression leads to larger and larger boxes. The elements/objects or collection of elements/objects are categorized into the grid. For example, if a user clicks on a P6 element or object, a determination is made that the categorization of the element or object is not desirable because it is too small. Accordingly, the next adjacent ancestor in the display chain (i.e., the one that contains the P6 element) is selected and further analyzed to see if, for example, the P6 element or object is within a P2 element. In turn, analysis continues to ascertain whether the P2 element or object is within an element or object that falls within a more desirable category, e.g. a P1 element or object. When an element or object is too big (e.g. within a P9 category), a zoom operation is used that simply zooms on the touched or otherwise selected part of the element.

20 **[0084]** Next, the best element or object overall is selected. The best overall element or object is the best element from the category with the highest priority (where P1 is the highest possible and P9 is the lowest). For example, if the display chain (including the element that was selected) includes elements from categories P6, P1 and P5, the best element overall is the best element from category P1.

25 Effectively, this category prioritization ensures the following prioritization of zoom impact:

1. The best element should fit horizontally after zooming.
2. The best element should fit vertically after zooming.

51331-1178D1

3. The best element should not be cut or clipped horizontally after zooming.
4. The best element should not be cut or clipped vertically after zooming.
5. The chosen zoom factor should be as close to 140% as possible, within the given zoom range (e.g., 100%-150%).

5 **[0085]** Next, the exact zoom ratio for the best overall element is computed.

The exact page zoom ratio depends on which category the best element overall belongs to. For example, in at least some embodiments, the following approach can be used. If the element zoom ratio for the best element overall is greater than 150%, then use 150%. If the element zoom ratio for the best element overall is smaller than 10
150% and greater than 105%, then use the element zoom ratio. If the element zoom ratio for the best element overall is smaller than 105%, do not zoom. For example, if the best element overall is a P1 element that can zoom 135% to fill the screen horizontally and vertically 145%, it will be zoomed 135% so that it does not get cut off vertically.

15 Animate Identified Object or Element into View

[0086] Having performed the above-described processing, a suitably configured application program interface (API) can be used to animate the best element overall into a destination rectangle as follows. The scale ratio is the page zoom ratio calculated above, and the position is calculated according to the following
20 logic, based on the above priority category that the best element overall belongs to:

- P1: Center the element both horizontally and vertically
- P2: Center vertically on the element
- P3: Center vertically on the point tapped or selected
- P4: Center vertically on the element
- 25 • P5: Center horizontally on the point tapped or selected

51331-1178D1

- P6: Center (both horizontally and vertically) the element
- P7: Center horizontally on the point tapped or selected
- P8: Center vertically on the point tapped or selected
- P9: Zoom around the point tapped or selected

5 **[0087]** As an example, consider a web page 802 in which a plurality of elements or objects are displayed, as represented by the boxes which can be images and the lines which can be text. Assume in this example that a user has selected element or object 804 for a zoom operation. Using the above-described methodology, the zoom logic would process element or object 804, its parent object 806 and the
 10 parent object 808 of object 806. Even though the user selected object 804 for zooming, the result of the processing described above could result in objects 804 and 806 or objects 804, 806, and 808 being zoomed on. In this way, contextually relevant material around the user's selection would be zoomed for the user's consumption.

[0088] In this implementation example, there is a special case that pertains to
 15 fixed elements. Fixed elements, because of their fixed nature, can be zoomed but in at least some instances, cannot be fully positioned properly. Consider the notion of a visual view port and a layout view port when zoomed in. The visual view port is smaller than and contained within the layout view port and fixed elements are always fixed to the layout viewport. In these instances, the visual viewport can be moved to
 20 attempt to center a fixed element. Thus, if a fixed element is on the edge of a layout viewport, it cannot be centered along that axis. Thus, when fixed elements are encountered, an attempt will be made to center it, with no guarantees.

[0089] Having described an example implementation, consider now a discussion of an example device that can be utilized to implement the embodiments
 25 described above.

51331-1178D1

Example Device

[0090] FIG. 9 illustrates various components of an example device 900 that can be implemented as any type of portable and/or computer device as described with reference to FIGS. 1 and 2 to implement embodiments of the animation library
5 described herein. Device 900 includes communication devices 902 that enable wired and/or wireless communication of device data 904 (e.g., received data, data that is being received, data scheduled for broadcast, data packets of the data, etc.). The device data 904 or other device content can include configuration settings of the device, media content stored on the device, and/or information associated with a user
10 of the device. Media content stored on device 900 can include any type of audio, video, and/or image data. Device 900 includes one or more data inputs 906 via which any type of data, media content, and/or inputs can be received, such as user-selectable inputs, messages, music, television media content, recorded video content, and any other type of audio, video, and/or image data received from any
15 content and/or data source.

[0091] Device 900 also includes communication interfaces 908 that can be implemented as any one or more of a serial and/or parallel interface, a wireless interface, any type of network interface, a modem, and as any other type of communication interface. The communication interfaces 908 provide a connection
20 and/or communication links between device 900 and a communication network by which other electronic, computing, and communication devices communicate data with device 900.

[0092] Device 900 includes one or more processors 910 (e.g., any of microprocessors, controllers, and the like) which process various computer-
25 executable or readable instructions to control the operation of device 900 and to implement the embodiments described above. Alternatively or in addition, device 900 can be implemented with any one or combination of hardware, firmware, or fixed logic circuitry that is implemented in connection with processing and control circuits which are generally identified at 912. Although not shown, device 900 can include a system

51331-1178D1

bus or data transfer system that couples the various components within the device. A system bus can include any one or combination of different bus structures, such as a memory bus or memory controller, a peripheral bus, a universal serial bus, and/or a processor or local bus that utilizes any of a variety of bus architectures.

5 **[0093]** Device 900 also includes computer-readable media 914, such as one or more memory components, examples of which include random access memory (RAM), non-volatile memory (e.g., any one or more of a read-only memory (ROM), flash memory, EPROM, EEPROM, etc.), and a disk storage device. A disk storage device may be implemented as any type of magnetic or optical storage device, such
10 as a hard disk drive, a recordable and/or rewriteable compact disc (CD), any type of a digital versatile disc (DVD), and the like. Device 900 can also include a mass storage media device 916.

[0094] Computer-readable media 914 provides data storage mechanisms to store the device data 904, as well as various device applications 918 and any other
15 types of information and/or data related to operational aspects of device 900. For example, an operating system 920 can be maintained as a computer application with the computer-readable media 914 and executed on processors 910. The device applications 918 can include a device manager (e.g., a control application, software application, signal processing and control module, code that is native to a particular
20 device, a hardware abstraction layer for a particular device, etc.), as well as other applications that can include, web browsers, image processing applications, communication applications such as instant messaging applications, word processing applications and a variety of other different applications. The device applications 918 also include any system components or modules to implement embodiments of the
25 techniques described herein. In this example, the device applications 918 include an interface application 922 and a gesture-capture driver 924 that are shown as software modules and/or computer applications. The gesture-capture driver 924 is representative of software that is used to provide an interface with a device configured to capture a gesture, such as a touchscreen, track pad, camera, and so
30 on. Alternatively or in addition, the interface application 922 and the gesture-capture

51331-1178D1

driver 924 can be implemented as hardware, software, firmware, or any combination thereof. In addition, computer readable media 914 can include an input pointer delay module 925a, a gesture module 925b, and a zoom module 925c that functions as described above.

5 **[0095]** Device 900 also includes an audio and/or video input-output system 926 that provides audio data to an audio system 928 and/or provides video data to a display system 930. The audio system 928 and/or the display system 930 can include any devices that process, display, and/or otherwise render audio, video, and image data. Video signals and audio signals can be communicated from device 900
10 to an audio device and/or to a display device via an RF (radio frequency) link, S-video link, composite video link, component video link, DVI (digital video interface), analog audio connection, or other similar communication link. In an embodiment, the audio system 928 and/or the display system 930 are implemented as external components to device 900. Alternatively, the audio system 928 and/or the display system 930 are
15 implemented as integrated components of example device 900.

Conclusion

[0096] Various embodiments enable repetitive gestures, such as multiple serial gestures, to be implemented efficiently so as to enhance the user experience. Other embodiments provide various approaches to zoom operations that consider a
20 particular element's contextual surroundings in making a zoom decision that is designed to enhance the user experience and provide efficiently-zoomed content given a device's or rendering container's form factor.

[0097] Although the embodiments have been described in language specific to structural features and/or methodological acts, it is to be understood that the
25 embodiments defined in the appended claims are not necessarily limited to the specific features or acts described. Rather, the specific features and acts are disclosed as example forms of implementing the claimed embodiments.

51331-1178D1S

CLAIMS:

1. A system comprising:
 - one or more processors;
 - one or more computer readable storage media;
- 5 computer readable instructions embodied on the one or more computer readable storage media which, when executed under the influence of the one or more processors, implement a method comprising:
 - detecting a first gesture associated with an object, the first gesture being associated with a first action;
 - 10 responsive to detecting the first gesture, performing pre-processing associated with the first action in the background and applying one or more styles that are defined for an object of which the object is a type;
 - responsive to detecting a second gesture associated with the object within a pre-defined time period, performing a zoom operation associated with the
 - 15 second gesture and discarding the pre-processing associated with the first action; and
 - responsive to the second gesture not being performed within the pre-defined time period, completing processing associated with the first action.
2. The system of claim 1, wherein performing the zoom operation
- 20 comprises:
 - performing the zoom operation on the object and at least one other object in an associated display chain, but less than all objects in the display chain; and

51331-1178D1S

using a category-based prioritization process to select the object and said at least one other object.

3. The system of claim 1, wherein at least one of the first or second gestures comprises a tap gesture.

5 4. A method comprising:

detecting a first gesture associated with an object, the first gesture being associated with a first action;

responsive to detecting the first gesture, performing pre-processing associated with the first action in the background and applying one or more styles
10 that are defined for an object of which the object is a type;

responsive to detecting a second gesture associated with the object within a pre-defined time period, performing a zoom operation associated with the second gesture and discarding the pre-processing associated with the first action; and

15 responsive to the second gesture not being performed within the pre-defined time period, completing processing associated with the first action.

5. The method of claim 4, wherein performing the zoom operation comprises:

performing the zoom operation on the object and at least one other
20 object in an associated display chain, but less than all objects in the display chain; and

using a category-based prioritization process to select the object and said at least one other object.

51331-1178D1S

6. The method of claim 4, wherein at least one of the first or second gestures comprises a tap gesture.

7. One or more computer readable storage media having stored thereon computer executable instructions which, when executed under the influence of the
5 one or more processors, implement a method comprising:

detecting a first gesture associated with an object, the first gesture being associated with a first action;

responsive to detecting the first gesture, performing pre-processing associated with the first action in the background and applying one or more styles
10 that are defined for an object of which the object is a type;

responsive to detecting a second gesture associated with the object within a pre-defined time period, performing a zoom operation associated with the second gesture and discarding the pre-processing associated with the first action;
and

15 responsive to the second gesture not being performed within the pre-defined time period, completing processing associated with the first action.

8. The one or more computer readable storage media of claim 7, wherein performing the zoom operation comprises:

performing the zoom operation on the object and at least one other
20 object in an associated display chain, but less than all objects in the display chain;
and

using a category-based prioritization process to select the object and said at least one other object.

9. The one or more computer readable storage media of claim 7, wherein
25 at least one of the first or second gestures comprises a tap gesture.




Fig. 1

+




Fig. 2

+

+




Fig. 3

+




Fig. 4

+

+




Fig. 5

+




Fig. 6




Fig. 7

+




Fig. 8

+




Fig. 9

