



US 20100261135A1

(19) **United States**(12) **Patent Application Publication**  
**Feine**(10) **Pub. No.: US 2010/0261135 A1**(43) **Pub. Date: Oct. 14, 2010**(54) **DENTAL DELIVERY DEVICE****Publication Classification**(75) Inventor: **James Feine**, Bellaire, TX (US)(51) **Int. Cl.**  
**A61C 19/06** (2006.01)  
**A61C 1/07** (2006.01)

Correspondence Address:


**MARSHALL, GERSTEIN & BORUN LLP**  
**233 SOUTH WACKER DRIVE, 6300 WILLIS**  
**TOWER**  
**CHICAGO, IL 60606-6357 (US)**(52) **U.S. Cl. .... 433/86; 433/215**(73) Assignee: **HU-FRIEDY MFG.CO., INC.,**  
**CHICAGO, IL (US)**(57) **ABSTRACT**(21) Appl. No.: **12/823,835**(22) Filed: **Jun. 25, 2010**

A single use cartridge 10 is disclosed for dispensing a medicament or other substance for dental, medical, or veterinarian applications. A motive fluid can contact the medicament to mix and dispense from reservoir 12, or the motive fluid can act on a plunger 21 to dispense the medicament. A handpiece 15 can sealably connect the cartridge 10 to a source of the motive fluid. The cartridge 10 can be easily replaced to facilitate the use of multiple cartridges with a single handpiece 15. An ultrasonic cleaning element 30 with a channel for fluid flow can be used in a handpiece 25 with a single use medicament cartridge 28 to dispense medicament during ultrasonic dental procedures. A cartridge 72 can contain a mixing element 70 to mix the motive fluid and abrasive particles for tooth surface polishing.




**Related U.S. Application Data**

(62) Division of application No. 11/162,069, filed on Aug. 26, 2005, now Pat. No. 7,766,656.

(60) Provisional application No. 60/604,967, filed on Aug. 27, 2004.



**FIG. 1**






FIG. 5




FIG. 6




FIG. 7

**DENTAL DELIVERY DEVICE****CROSS REFERENCE TO RELATED APPLICATIONS**

**[0001]** This is a divisional of U.S. patent application Ser. No. 11/162,069, filed Aug. 26, 2005, which application claims the benefit of my earlier application U.S. Ser. No. 60/604,967 filed Aug. 27, 2004.

**FIELD OF THE INVENTION**

**[0002]** This invention relates to dental delivery devices, more particularly, to a single use medicament delivery device with a replaceable cartridge. The invention addresses such current issues as infection control, medicament dispensing, dental scaling, polishing, and surface abrading while maintaining ease of use, size, and portability.

**BACKGROUND OF THE INVENTION**

**[0003]** Dental equipment and techniques have evolved over the past decades of use. New concerns such as infection control and sterility of equipment and materials have become increasingly important, both to the patient and to the dental professional. Dental professionals require equipment for dispensing many substances including air, water, medicament, surface abrading materials, impression material, sealants, coatings, anesthetics, fluoride containing gel or solution, etc.

**[0004]** Most dental equipment is required to be sterilized which consumes time and labor. Many different patients may receive treatment from one dental professional in the same day, and there is not usually time to sterilize the equipment between procedures, so the practitioner must have several of the same type of tool ready for use. Different dental equipment may be used during the same procedure. Often, one set of equipment may be used for one type of procedure, whereas a similar set may be used for another. Furthermore, in some offices, there may be several practitioners, each having his or her own preference for types of equipment for particular procedures. Additionally, a medicament can be applied during the procedures which can necessitate a separate medicament dispenser for each differing medicament. Each device requires time, labor, and capital to own, operate, and sterilize.

**[0005]** Dental dispensing devices can require a gas, liquid, or electrical means for operation, which can lead to a complicated supply system. In addition to the expense, having a multitude of supply systems can lead to an unsafe environment due to the close proximity to the patient and dental professional. Some medicaments require mixing with a gas, a liquid, or both, which can require different connections to the office air and water supply creating even more complications.

**[0006]** Some current tooth polishing systems in use that provide baking soda polishing functions are charged with powder in a reservoir in the base unit in an amount for multiple uses or procedures. This powder can absorb moisture from the surroundings and clog the orifices and tubing. Operators of these units can have difficulties in cleaning the powder reservoirs and keeping them dry, and removing, cleaning, and disinfecting their assemblies. Moreover, the base reservoir does not facilitate easy change of the polishing compound for different patients who require a different type or would like a different flavor.

**[0007]** Ultrasonic dental equipment is commonly used in hygienics, periodontal and other dental procedures. This requires additional equipment to be purchased and sterilized

for each patient if a medicament is used with the ultrasonic scaler treatment, in addition to the time wasted by the dental professional setting up and switching equipment.

**SUMMARY OF THE INVENTION**

**[0008]** The present invention is directed to a single-use cartridge for delivering a unit dose of medicament in dental procedures, for example. The medicament can be dispensed from the cartridge using a sterilizable or disposable handpiece and a motive fluid such as air or water. The single-use cartridge can be used to deliver medicament per se, to provide a tooth surface polishing spray of water, air and abradant, or to deliver medicament in an ultrasonic dental procedure.

**[0009]** In one embodiment, the present invention provides a delivery device for medicament. The delivery device includes a cartridge having a reservoir containing a unit dose of medicament. A tip is operably connected at a distal end of the cartridge. A port is provided in the cartridge for removably connecting the cartridge to a source of a motive fluid to displace medicament from the reservoir through a channel in the tip.

**[0010]** In another embodiment, a delivery device for medicament includes a cartridge housing a reservoir containing a unit dose of medicament, and a handpiece with a cavity removably receiving the cartridge. A tip is operably connected at a distal end of the cartridge to project through an opening at a distal end of the handpiece. A source of a first motive fluid is in communication with a first passage in the handpiece, and a first port in the cartridge can connect the first passage to the reservoir for supplying the first motive fluid to displace medicament from the reservoir through a channel in the tip. The tip can be removably connected to the cartridge. The handpiece can be autoclavable. The medicament can be a fluoride gel, for example. The reservoir can further contain a plunger which is drivable by the first motive fluid against the medicament to dispense medicament. In another embodiment, cartridge can have a first port in fluid communication with the medicament in the reservoir. The medicament can be concentrated and the medicament displaced through the channel can be mixed with the first motive fluid.

**[0011]** In another embodiment a source of a second fluid is in communication with a second passage in the handpiece and a second port in the handpiece for connection to the second passage.

**[0012]** In another embodiment, the cartridge can include a second port for supplying the second fluid to the reservoir from the second handpiece port. One of the first and second cartridge ports can be selectively blocked and the other of the first and second cartridge ports can be open. The first and second ports can have different sizes to align the cartridge in the handpiece.

**[0013]** In another embodiment, the single use cartridge can include a flow channel through the cartridge for the second fluid to flow from the second port to the tip separate from the reservoir, and a mixing element can introduce a mixture of the first fluid and medicament from the reservoir into the channel. This first motive fluid can comprise a gas such as air and the second motive fluid can comprise a liquid such as water.

**[0014]** In another embodiment, the mixing element can comprise outer and inner concentric tubes with a flow path for supplying air and medicament from the reservoir to the inner tube or comprise a nozzle.

**[0015]** In another embodiment, the present invention can include an ultrasonic element disposed between the distal end

of the cartridge and the tip with a flow path in the ultrasonic element in fluid communication with the reservoir and the channel in the tip. The ultrasonic element can be powered by a circuit through the cartridge which connects the handpiece to an electrical connection in the ultrasonic element. The cartridge can be essentially free of medicament to provide a flow channel for the first motive fluid to the channel in the tip.

**[0016]** In another embodiment, the invention can include a control unit for modulating the supply of the first motive fluid and can include a conduit for supplying the first motive fluid from the control unit to the first passage in the handpiece. The control unit can further modulate the supply of the first and second fluids and can include a cable. The cable can include first and second conduits for supplying the first and second fluids from the control unit to the first and second passages in the handpiece, respectively. A second embodiment can include a circuit in the cable for supplying power to the handpiece.

**[0017]** In another embodiment, a medicament can be dispensed by connecting the cartridge containing the unit dose of medicament to a source of a motive fluid and supplying the motive fluid to displace the medicament from the reservoir through the channel in the tip onto a dental surface.

**[0018]** In another embodiment, a method of dispensing medicament can further comprise inserting the cartridge having the unit dose of medicament into the handpiece and supplying the first motive fluid to the reservoir to dispense the medicament from the reservoir through the channel in the tip.

**[0019]** In another embodiment, the unit dosage can be concentrated and the can further comprise mixing the medicament with the first fluid wherein the dispensed medicament is diluted.

**[0020]** In another embodiment, a method of dispensing medicament can further comprise a reservoir containing a plunger between the medicament and the first port, where the first fluid can push the plunger to displace the medicament from the reservoir.

**[0021]** In another embodiment, a method of dispensing medicament can comprise the steps of inserting the cartridge containing the unit dosage of medicament into the handpiece, supplying the second fluid through the flow channel to the mixing element, supplying the first fluid to the reservoir to displace medicament and form a first mixture of the first fluid and the medicament, mixing the second fluid with the first mixture to form a second mixture of the medicament and the first and second fluids, and discharging the second mixture from the tip.

**[0022]** In another embodiment, a method of dispensing medicament can comprise the steps of modulating the supply of the first and second fluids to control a rate of the displacement of the medicament.

**[0023]** In another embodiment, a method for ultrasonically scaling teeth can comprise assembling the cartridge to the ultrasonic element and inserting the assembly into the handpiece, powering the ultrasonic element to scale a dental surface, and supplying the first fluid to the reservoir to dispense the medicament through the flow path in the ultrasonic element for discharge adjacent the tip.

**[0024]** In another embodiment, a system for dispensing medicament with single-use cartridges can comprise having an inventory comprising a plurality of like cartridges, each having a reservoir containing a unit dose of medicament, and having a handpiece with a cavity for removably receiving one of the cartridges with a tip operably connected at a distal end

of the cartridge projecting through an opening at a distal end of the handpiece. The handpiece can have a source of a first fluid in communication with a first passage in the handpiece, and a first port in the cartridge for connecting the first passage to the reservoir for supplying the first fluid to displace medicament from the reservoir through a channel in the tip.

**[0025]** In another embodiment, the inventory of cartridges can comprises a plurality of subsets of the cartridges wherein each subset comprises cartridges containing a different medicament from the other subsets. In another embodiment, a method of dispensing medicament can comprise the steps of selecting one of the cartridges from the inventory, inserting the cartridge having the unit dose of medicament into the handpiece, supplying the first fluid to the reservoir to dispense the medicament from the reservoir through the channel in the tip, removing the cartridge from the handpiece, and repeating the selection, insertion, and removal steps with a new cartridge from the inventory. This method can further comprise the step of sterilizing the handpiece prior to the repetition.

#### BRIEF DESCRIPTION OF THE DRAWINGS

**[0026]** FIG. 1 is an exploded sectional view of a two port single use cartridge with a plunger shown in an initial and an advanced position (dashed lines) according to one embodiment of the invention.

**[0027]** FIG. 2 is a perspective view of a handpiece that can be used with the cartridge of FIG. 1, according to one embodiment of the invention.

**[0028]** FIG. 3 is an end view of the handpiece of FIG. 2, as seen along the lines 3-3.

**[0029]** FIG. 4 is a perspective view of the assembled cartridge and handpiece of FIGS. 1-3.

**[0030]** FIG. 5 is an exploded perspective view of a single-use cartridge used in an assembly with an ultrasonic element in a handpiece, according to one embodiment of the invention.

**[0031]** FIG. 6 is a schematic view of a control and fluid/power supply system for the handpiece and cartridge assembly, according to one embodiment of the invention.

**[0032]** FIG. 7 is a perspective view of a two port cartridge with a mixing element and a screw-on tip according to one embodiment of the invention.

#### DETAILED DESCRIPTION

**[0033]** FIGS. 1-4, according to one embodiment, show a single use medicament delivery cartridge 10. The cartridge houses a reservoir 12 which contains medicament, preferably a unit dose for use in dental procedures. The volume of the unit dose can be adjusted depending on the size of the single use cartridge, the type of medicament and dosing requirements, the type of dental procedure, and the like. A proximal end 14 of the cartridge 10 can interlock the handpiece 15, as best seen in FIG. 2. A first cartridge port 16 and a second cartridge port 18 are provided at the proximal end to introduce fluids to the reservoir 12, such as, for example, air and water. In alternative embodiments, there can be a single cartridge port or more than two cartridge ports, depending on the number of different fluids or sources of fluids to be supplied.

**[0034]** In the embodiment illustrated, the cartridge port 16 can be blocked to prevent or inhibit fluid from flowing into the reservoir 12 by an obstruction such as a plug 20, and the port 18 can be open to allow fluid passage. Alternatively, the port 16 can be open and port 18 blocked, if a different motive fluid

is desired for the particular medicament, or both ports **16** and **18** can be open to allow the use of dual motive fluids. The plug **20** can be a plug that is inserted or a plug that is molded into the single use cartridge. The plug **20** can be removable or permanent, e.g. formed as an integral part of the cartridge **10**, or inserted when the cartridge **10** is filled with medicament through one of the ports **16,18** and/or the distal end at the tip attachment nozzle.

**[0035]** If used, a plunger **21** can be disposed in the single use cartridge **10** adjacent the proximal end between the port **18** and the medicament in reservoir **12** to prevent contact between fluid introduced through the port **18** and the medicament. The plunger **21** can sealably contact an inner wall **22** via O-ring seal **23** carried on a groove or channel at an outside diameter of the plunger **21**. Alternatively, the plunger **21** can be a unitary or composite construction with a suitable perimeter seal that can be integral with the plunger. The plunger **21** can be made from a suitably rigid material(s) compatible for use with one side in contact with the motive fluid and the other side in contact with the particular medicament to be dispensed.

**[0036]** A tip **24** can be threadably or otherwise removably connected to the distal end of the single use cartridge **10** for directing the medicament discharge. A flow control orifice **26** can, if desired, be disposed in the cartridge **10** adjacent the tip **24** for limiting the flow of medicament. Orifice **26** can be sized for different tips, different fluid pressures, different types of medicament, different dosage delivery rates, and so on.

**[0037]** Medicament is dispensed by a dental professional or other operating personnel introducing the selected motive fluid such as water or air to one or both of ports **16,18**. In the embodiment shown in FIG. 1 port **18** is open and port **16** is blocked, so the cartridge **20** is connected to the desired motive fluid via port **18**. The motive fluid flows from the port **18** into the reservoir **12** to push the plunger **21**, if present, and displace the medicament into a channel **28** for discharge from the distal end of the tip **24**. FIG. 1 shows movement of the plunger **21** from an initial position adjacent the ports **15,16**, toward the orifice **26** at D (shown in dashed lines) as the medicament is displaced. If the plunger **21** is not used, the motive fluid can also mix with the medicament.

**[0038]** The first and second fluids can be any type of fluid, i.e. liquid or gas. Dental offices typically have office air and water supplies, for example, which can be used as the motive fluid in this invention, but any desired gas, liquid or similar fluid or mixture of fluids can be used. For convenience and clarity, the invention is illustrated herein with air and water as motive fluids by way of example and not limitation.

**[0039]** FIGS. 1-4 show male handpiece ports **16',18'** that extend into the female ports **16,18** in the proximal end **14** of the cartridge **10**, but the ports **16,18** can be male and ports **16',18'** female, or one of the ports **16,18** could be female and the other male and the corresponding ports **16',18'** would be male and female. Moreover, the ports are not limited to male and female ports, and can be any connective means known to those skilled in the art. The alignment of cartridge ports **16,18** and handpiece ports **16',18'** can facilitate an interlocking registration between the cartridge **10** and handpiece **15** to ensure the cartridge **10** is positioned and aligned appropriately in the handpiece **15** so that the desired motive fluids are supplied to the appropriate ports **16,18**. The registration can alternatively or additionally be effected by using ports of different sizes, e.g. relatively larger ports **16,16'** for water and relatively

smaller ports **18,18'** for air, or by asymmetric positioning of the ports, e.g. axially aligned ports **16,16'** for water and offset ports **18,18'** for air. Similarly, a registration pin(s) and corresponding slot(s) can be used between the handpiece and the cartridge for alignment purposes.

**[0040]** The cartridge ports **16,18** can also be selectively blocked or open so as to allow the desired motive fluid into the reservoir and/or to push the plunger, as may be required for different medicaments or procedures. By configuring the cartridge ports **16,18** for the particular medicament, e.g. in conjunction with a standardized controller (see below) and handpiece, the cartridge can automatically provide for the use of the appropriate motive fluid without requiring the operator to manually select the fluid. By blocking one of the ports **16, 18**, the motive fluid can be selected to match the requirements of the medicament. For example where a medicament is to be mixed with water, the air port can be blocked; or where air is the desired motive fluid for the appropriate dispensing rate, the water port can be blocked.

**[0041]** A source of a first fluid is connected to a first port **16'** in the handpiece **15**, and a source of a second fluid to a second port **18'**. These ports can connect to the fluid supply through channels formed in a proximal end of the handpiece **15**, e.g. by extending supply tubing or other conduit from an attachment cable through the proximal end of the handpiece to terminate at the respective ports **16',18'**. In one embodiment the termini of the supply tubing can conveniently be formed into the ports **16',18'**.

**[0042]** Connecting the single use cartridge **10** and the handpiece **15** can connect or be effected by engaging the male handpiece port **16'** to female cartridge port **16**, and the male handpiece port **18'** to cartridge port **18**, at the proximal end **14** of the cartridge **10**. The cartridge ports **16,18** can form a fluid-tight seal to the handpiece ports **16',18'** by an O-ring seal, friction seal, or other conventional sealing means.

**[0043]** The distal view of the handpiece **15** in FIG. 3 shows an opening **29** at the distal end that allows the tip **24** to project from the distal end of the handpiece **15**. The opening **29** can include a peripheral lip **33** to facilitate retention of the cartridge **10** in the handpiece.

**[0044]** Page 10 of 31 **15**, and can have a profile matching that of the distal end of the cartridge **15** to hold it tightly in place and inhibit lateral movement during administration of the medicament by the dental practitioner. Alternatively, the handpiece **15** can have a hinged body (not shown) that surrounds the single use cartridge with an aperture for exposing the tip.

**[0045]** Handpiece **15** in FIG. 2 is shown as having a cavity for receiving the cartridge **10** (see FIG. 4), but the cartridge **10** can be used independently of the handpiece **15**. For use without a handpiece, the user can hold the single use cartridge **10** itself, and the source(s) of motive fluid can be removably attached directly to one or both of the ports **16,18** on the cartridge using connective means known in the art, such as, for example, a slip fit, threaded connection, or the like.

**[0046]** The distal end of the handpiece **15** can have a peripheral lip **33** adjacent the opening **29** for engaging the distal end of the cartridge **10**, e.g. at an edge of the outer profile. The lip **33** can help retain the cartridge **10** connected to the handpiece **15** (see FIG. 4) through an overlap or friction fit with the distal end of the cartridge **10**, or another connective means known in the art to prevent the cartridge **10** from separating from and/or moving with respect to the handpiece **15** in use. The ports **16,18** and **16',18'** can provide a similar



retention function at the proximal end of the cartridge **10**. One or both the proximal and distal ends of the cartridge **10** or preferably the handpiece **15** can provide spring biasing in a conventional manner to facilitate insertion and removal of the cartridge **10** to and from the handpiece **15**.

**[0047]** In use, the dental professional or other operating personnel can receive a supply of a plurality of cartridges **10** each filled with a unit dose of medicament sufficient for a single use. An inventory of cartridges with different medicaments or different dosages for different procedures can also be maintained on hand. Each cartridge **10** can be individually packaged with or without tip **24** and sterilized, e.g. by radiation, gas (ethylene oxide) permeation, or the like. The handpiece **15** can be sterilized by autoclaving, or provided as a disposable, pre-sterilized single use device. One of the cartridges **15** containing the appropriate medicament for the intended procedure can be selected from the inventor, assembled into the handpiece **15**, and connected to a suitable source of air and/or water. The dental practitioner can then introduce air and/or water into the reservoir **12** of cartridge **10**. The fluid acts directly on the medicament and optionally mixes with the medicament, or against the plunger **21**, displacing medicament or a fluid and medicament mixture through channel **28** in the tip **24** to the dental surface or tissue of the patient. After the procedure is completed or the medicament exhausted, the spent cartridge **10** can be removed from the handpiece **15** for disposal or return to the supplier for refilling, the handpiece **15** autoclaved or otherwise sterilized, or replaced with another handpiece **15**, and a new cartridge **10** installed for the next application procedure or patient. The handpiece **15** can be constructed of a material suitable for use in an autoclave or other sterilization equipment if it is not disposable.

**[0048]** The tip **24** can be removable, so one can use a disposable tip **24**, autoclave or otherwise sterilize the tip **24** for re-use, use different types or sizes of tips **24** for different procedures or application requirements, or change the tip **24** during the procedure, or the like. The tip **24** can also be built integrally into the cartridge **10** and/or supplied with the cartridge **10**, either separate or pre-assembled to the cartridge **10**. The single use cartridge **10** can be manufactured of any material or materials that are suitable for use in containing medicament.

**[0049]** The medicament can be placed in the reservoir during manufacture of the cartridge or later. The medicament can conveniently be injected into the ports **16,18** or the tip connection nozzle. Alternatively, where the plunger **21** is used, the plunger **21** can be positioned distally adjacent to the tip **24**, the tip **24** immersed in the medicament, and the plunger **21** retracted to draw in the medicament through the tip **24** by temporarily connecting one or both of ports **16, 18** to a vacuum source.

**[0050]** The cartridge **10** can be transparent or translucent so that the volume of remaining medicament can be determined visually. The reservoir can contain a single medicament, or a mixture of medicaments, such as, for example, dental preparations, polishing compounds, bleaching or whitening agents, cleansers, anesthetics, analgesics, antiseptics, dyes, adhesives, solvents, astringents, sealants, fluoridation agents, impression materials, combinations thereof, or the like. Medical, veterinarian and other medicaments can also be dispensed in the cartridge **10**, it being understood that dental use is merely exemplary for illustrative purposes and can have the advantage that dental practitioner offices are typically

provided with instrument air and water supplies that can be readily used as the motive fluid. The medicament can be in any suitable form, such as, for example, liquid, solution, emulsion, dispersion, gel, paste, slurry, foam, powder, or the like.

**[0051]** The cartridge **10** can be for a single use. The single use cartridge **10** can be replaced quickly during a dental procedure or after the procedure. If the tip **24** is removable, different styles and sizes of tips can be interchangeably used with the cartridge **10**. The ease of cartridge replacement can allow for multiple cartridge changes during a procedure for a single treatment modality as well as mixed treatment modalities such as using more than one medicament sequentially, for example dispensing fluoride gel from one cartridge followed by tooth surface sealing using another cartridge, or the like. For use of different cartridges with the same patient, it may not be necessary to sterilize the handpiece, and thus the same handpiece could be used for the different procedures.

**[0052]** The cartridge can be supplied in a sealed, sterile package. The sealed package can inhibit moisture from entering the reservoir, and can optionally include a desiccant. The single use cartridge **10** can have a disposable cap to seal the openings (at ports **16,18**, at the tip **24** or corresponding attachment point) before use, or the openings can be sealed with foil or other protective covering or membrane that can be punctured before use or by insertion of the cartridge **10** into the handpiece **15**, e.g. with the male ports **16',18'** piercing a covering over the female ports **16,18**. A removable cap on the entry and exit ports of the single use cartridge **10** can retain the medicament in the reservoir **12** before use. The packaging of the cartridge **10** can have a complementary geometry to seal the entry and exit ports of the cartridge to seal the medicament in the reservoir **12** before use.

**[0053]** By providing the plunger **21** or other impermeable membrane between the medicament and the ports **16,18**, medicament can be dispensed without the addition and/or mixing of motive fluid. Instead, the plunger **21** is moved longitudinally as shown in FIG. 1 or expanded by the entry of the fluid to displace medicament from the reservoir **12**. Some medicaments can be of a two part or three part mixture, etc. The single use cartridge **10** can dispense multipart medicaments with or without mixing with motive fluid, for example, by partitioning the reservoir **12** into compartments for each medicament part and independently supplying motive fluid to each compartment to displace the medicaments into the tip **24**, either simultaneously with optional mixing in the tip **24** and/or sequentially.

**[0054]** Alternatively, a plurality of stackable cartridges, each containing different medicaments can be used, where the stack has an overall length corresponding to the length of the cavity in the handpiece. The proximal cartridge can have a proximal end that selectively registers with the handpiece and a distal end that selectively registers with the proximal end of the distal cartridge to pass medicament and/or fluid into the distal cartridge; and the distal cartridge can have a distal end with a tip. In this manner a medicament in a first stackable cartridge can react with another medicament in another cartridge to form an active medicament to be dispensed. As one non-limiting example, the proximal cartridge can be plunger operated to discharge a relatively stable medicament directly into the reservoir of the distal cartridge where it reacts with the relatively stable medicament in the reservoir of the distal cartridge and thereby forms an unstable reaction product that is dispensed from the tip of the distal cartridge.

The cartridge stack elements can be stored pre-measured until ready for use, and the registration indicia at the ends of the cartridge stack elements can prevent improper assembly in the handpiece.

[0055] In FIG. 5, according to one embodiment, an assembly of a single use medicament cartridge 35 and an ultrasonic vibratory element 30 can be used in a handpiece 25. The ultrasonic element 30 can be piezoelectric, magnetostrictive, ferroelectric, or any other type of ultrasonic element known in the art. The ultrasonic element can also be a piezoelectric ceramic element or any other piezoelectric element known in the art.

[0056] The single use cartridge 35 in this embodiment is sized lengthwise to fit into the handpiece 25 when assembled with the ultrasonic element 30. In this manner, the same handpiece 25 can be used, if desired, in both ultrasonic and non-ultrasonic applications. The cartridge used in the non-ultrasonic application can have a length that equals the total length of the cartridge 28 and element 30, or a spacer or dummy cartridge (with appropriate flow through passages for the supplied fluid(s)) can be used to make up the required length.

[0057] In FIG. 5, the handpiece port 39 can supply a first motive fluid, the port 27 a second motive or mixing fluid, and handpiece connector 31 can provide an electrical or other power source connection(s) to the cartridge 35. More or fewer ports and/or power connections can be used if desired.

[0058] The single use medicament cartridge 28 can have ports 47,49 for receiving fluid from handpiece ports 27,29, respectively, to allow the user to supply water, air, a combination of water and air (simultaneously or sequentially), or similar motive and/or mixing fluid(s).

[0059] The medicament cartridge contains a circuit 38 through the cartridge 35 for supplying power from the handpiece power connector 31 to an electrical connection 37 with the ultrasonic element 30, which can include a male/female plug-in type connector, for example, with corresponding pins and sockets. The circuit 38 can include a fluid impervious sheath surrounding the wiring, which can also be coated, or in another embodiment a conduit can be positioned or molded into the cartridge to allow the circuit to pass through the cartridge while separating the circuit from the medicament and/or motive fluid(s).

[0060] The ultrasonic element 30 can have a flow path 32 for fluid flow from the reservoir 41 of the single use cartridge 35 to the screw-in tip 36. Although the end of the flow path 32 is shown with a threaded port 34, the tip can be screw-in, snap-in, snap-on, integrally formed on the ultrasonic element, or any other conventional tip connecting means known in the art. The flow path 32 connects to the reservoir 41 of cartridge 35 at a port 42 on the distal end of the cartridge 35. Port 42 can be male as shown, or female.

[0061] In use, the dental professional connects the ultrasonic element 30 to the cartridge 35 which are then inserted as an assembly into the handpiece 25. The dental professional then powers the ultrasonic element 30 to scale a dental surface using techniques and methodology well known in the art, but with the fluid supply and medicament dispensing features of the present invention. A medicament or mixture of medicaments can be dispensed before, during, or after the scaling. For example, an antimicrobial rinse can be applied by supplying air and/or water into the reservoir through a respective port. The fluid can be controllably flowed into the single use cartridge 35 by an on-off and/or adjustable rate controller.

Similarly, the dental professional can install a "dummy" cartridge 35 with no medicament in the reservoir 41 that allows fluid to flow through the cartridge 35 to the ultrasonic element 30, for procedures that do not require medicament but require air, water or other fluid(s) for operation, e.g. water for irrigation and cooling.

[0062] The ultrasonic element 30 can be made of a material that is suitable for use in an autoclave or other means of sterilization. The ultrasonic element 30 and cartridge 35 assembly can be removed as an assembly and a medicament cartridge only can be connected to the handpiece 25. The cartridges can have a port or multiple ports blocked off if they are not needed. The cartridge 35 can also include a plunger disposed adjacent the proximal end between the ports 47,49 and the medicament in reservoir 41 to prevent contact between fluid introduced through the ports 47,49 and the medicament, similar to that shown in FIGS. 1-4. The plunger can have an aperture that allows the circuit 38 to sealably pass through the plunger as the plunger moves to displace medicament.

[0063] In FIG. 6, according to one embodiment, a control unit 48 can connect to a handpiece 46, a cable 58, and have a foot control switch 50 for controlling the supply of motive fluid and/or power. The cable 58 can include one or more fluid supply conduits for air and/or water, for example, and an electrical line or lines for supplying power, if required. Alternatively, there can be more than one cable 58 to the handpiece 46 carrying separate fluid conduits or power lines or any combination thereof, optionally including a sheath or other conventional cable covering, or the cable 58 can comprise an unsheathed conduit or tubing.

[0064] The control unit 48 can be supplied with motive fluids 52, 54, and power 56. The control unit 48 can regulate the flow of air or water using conventional valves (not shown) operated by the foot switch 50 or via settings on the control unit 48, which can be automatic or manual. Power can be regulated by a potentiometer, for example, in either the foot-switch 50 or the control unit 48 such as with an adjustable dial. Fluid and power can include an on-off controller, a modulating or regulating controller, or both. For example, the fluid flow rate or power setting can be set manually or automatically at the control unit 48 and turned on or off via the footswitch 50. The footswitch 50 can also included potentiometer(s) that control the rate of fluid supply, e.g. by means of a valve(s), regulation of the fluid supply pressure, or the like. Further, a programmable logic controller and/or step motor can be used to automatically sequence the fluid(s) and/or power supply for a particular procedure.

[0065] Although FIG. 6 shows a separate control unit 48 by way of illustration for the sake of clarity and convenience, the control unit 48 or any part thereof could be integrated with the handpiece. Furthermore, a separate control unit could be provided for each function of the handpiece.

[0066] In FIG. 7, according to one embodiment, there is shown a cartridge system that can be used for polishing teeth with sodium bicarbonate particles in a spray mixture of air and water. The cartridge 72 can have a mixing element 70 including inner and outer concentric tubes 64,68. After connecting the cartridge 72 to a handpiece 15 (see FIG. 2), water is supplied into port 76 and air is supplied into port 78. Water flows from port 76 into tube 68 and directly to the distal end of the cartridge 72 through the annulus in mixing element 70 around the central tube 64. Air enters through port 78 into the reservoir 66, entraining sodium bicarbonate powder or other

abrasive particles, thence flowing into mixing element **70** via inner tube **64** in the tube **68**, where it is introduced into the annular water stream and the mixture discharged at the distal end of the cartridge **72**.

**[0067]** In use, a dental professional or other operating personnel can insert a single use medicament cartridge **72** into handpiece **15** (FIG. 2). Water and air can be simultaneously supplied to ports **76** and **78**, respectively. The air can flow into the reservoir **66**, form a mixture of air and sodium bicarbonate for pneumatic transport into the mixing element **70** via air tube **64**. The water flows through the tube **68** to the mixing element **70** where a mixture of air, water and abrasive particles can be formed in the tip. The water, air, and sodium bicarbonate mixture can be discharged in a forceful high velocity spray directed using the tip onto a tooth or other dental surface to remove calculus, tartar or other foreign matter, for tooth surface polishing. The powder can be maintained in the reservoir of the cartridge **72** prior to use as a dry, non-clumping, pneumatically conveyable powder. The single-use cartridge in this embodiment thus avoids the prior art problems associated with water absorption by large dispensing reservoirs of powder and the concomitant clumping of the powder and clogging of supply lines.

**[0068]** The tubes **64**, **68** of mixing element **70** can be varied in size to control the mixing rate of the medicament and/or the volume of the discharged mixture. Similarly, the flow rates of the air and water can be varied to adjust the volume or the relative composition of the polishing spray. Alternatively, the mixing element **70** is not limited to concentric tubes, and can be, for example, a mixing nozzle, an eductor, or another suitable mixing element known in the art. Furthermore, tube **68** can be located within or adjacent the cartridge wall and need not be centrally disposed through the cartridge provided that the tube **68** provides a flow channel to supply water to the mixing element **70**.

**[0069]** While the invention has been described with respect to a limited number of embodiments, those skilled in the art will appreciate numerous modifications and variations therefrom. It is intended that the appended claims cover all such modifications and variations as fall within the true spirit and scope of the invention.

**1-12.** (canceled)

**13.** A delivery device for medicament, comprising:

a cartridge housing a reservoir containing a unit dose of medicament;

a handpiece with a cavity removably receiving the cartridge, the handpiece including a retaining lip at a distal end thereof facilitating retention of the cartridge within the cavity;

an ultrasonic element disposed in the handpiece;

an ultrasonic tip in fluid communication with a distal end of the cartridge projecting through an opening at the distal end of the handpiece;

a source of a first motive fluid in fluid communication with a first passage in the handpiece;

a first port in the cartridge for connecting the first passage to the reservoir for supplying the first motive fluid to displace medicament from the reservoir through a channel in the ultrasonic tip;

a source of a second motive fluid in communication with a second passage in the handpiece;

a second port in the handpiece for connection to the second passage;

a flow channel through the cartridge for the second motive fluid from the second port to the tip separate from the reservoir; and

a mixing element for introducing a mixture of the first motive fluid and medicament from the reservoir into the channel.

**14.** The delivery device of claim **13** wherein the first motive fluid comprises a gas and the second motive fluid comprises a liquid.

**15.** The dental delivery device of claim **14** wherein the liquid comprises water and the gas comprises air.

**16.** The dental delivery device of claim **15** wherein the mixing element comprises outer and inner concentric tubes with a flow path for supplying air and medicament from the reservoir to the inner tube.

**17.** The delivery device of claim **15** wherein the mixing element comprises a nozzle.

**18-26.** (canceled)

**27.** The method of dispensing a medicament with the delivery device of claim **13** comprising the steps of:

inserting the cartridge containing the unit dosage of medicament into the handpiece;

supplying the second motive fluid through the flow channel to the mixing element;

supplying the first motive fluid to the reservoir to displace medicament and form a first mixture of the first motive fluid and the medicament;

mixing the second motive fluid with the first mixture to form a second mixture of the medicament and the first and second motive fluids; and

discharging the second mixture from the tip.

**28.** The method of claim **27** further comprising the step of: modulating the supply of the first and second motive fluids to control a rate of the displacement of the medicament.

**29-33.** (canceled)

\* \* \* \* \*