

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(10) International Publication Number

WO 2016/085397 A1

(43) International Publication Date

2 June 2016 (02.06.2016)

WIPO | PCT

(51) International Patent Classification:

E04F 15/02 (2006.01) E04F 15/10 (2006.01)  
E04F 15/04 (2006.01)

HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(21) International Application Number:

PCT/SE2015/051270

(22) International Filing Date:  
25 November 2015 (25.11.2015)

(25) Filing Language:  
English

(26) Publication Language:  
English

(30) Priority Data:  
1451438-4 27 November 2014 (27.11.2014) SE

(71) Applicant: VÄLINGE INNOVATION AB [SE/SE];  
Prästavägen 513, S-263 65 Viken (SE).

(72) Inventor: PERVAN, Darko; Bygatan 30, S-263 61 Viken (SE).

(74) Agent: ENGQUIST, Johan; Floor Iptech AB, Prästavägen 513, S-263 65 Viken (SE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

**Declarations under Rule 4.17:**


— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))

**Published:**

— with international search report (Art. 21(3))

— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

(54) Title: MECHANICAL LOCKING SYSTEM FOR FLOOR PANELS



(57) **Abstract:** Floor panels (1, 1') are shown, which are provided with a mechanical locking system comprising a flexible tongue (10) in a displacement groove (11). The flexible tongue (10) may be formed from the core material (5) of the floor panels and inserted during production into the displacement groove (11). The locking system may be locked with vertical folding.

WO 2016/085397 A1

## MECHANICAL LOCKING SYSTEM FOR FLOOR PANELS

### TECHNICAL FIELD

The disclosure generally relates to the field of mechanical locking systems for floor panels and building panels. The disclosure shows floorboards, locking 5 systems and production methods.

### FIELD OF APPLICATION OF THE INVENTION

Embodiments of the present invention are particularly suitable for use in thin floating floors, which are formed of floor panels which are joined mechanically with a locking system preferably integrated with the floor panel, i.e. mounted 10 at the factory, are made up of one or more upper layers of thermoplastic or thermosetting material or wood veneer, an intermediate core of wood-fibre-based material or plastic material and preferably a lower balancing layer on the rear side of the core. Embodiments of the invention can also be used for joining building panels which preferably contain a board material for instance 15 wall panels, ceilings, furniture components and similar. It may also be used to connect ceramic tiles.

The following description of prior-art technique, problems of known systems and objects and features of embodiments of the invention will therefore, as a non-restrictive example, be aimed above all at this field of application and in 20 particular at floor panels and especially at laminate floors and thin resilient thermoplastic floor panels such as so called luxury vinyl tiles, generally referred to as LVT, formed as rectangular floor panels with long and short edges intended to be mechanically joined to each other on both long and short edges.

25 The long and short edges are mainly used to simplify the description of embodiments of the invention. The panels may be square. Floor panels are generally produced with the surface layer pointing downwards in order to eliminate thickness tolerances of the core material. The major part of the

embodiments is shown with the surface pointing upwards in order to simplify the description.

It should be emphasized that embodiments of the invention can be used in any floor panel on long and/or short edges and it may be combined with all 5 types of known locking system on long or short edges that lock the panels in the horizontal and/or vertical direction.

#### BACKGROUND OF THE INVENTION

Relevant parts of this prior art description are also a part of embodiments of the invention.

10 Several floor panels on the market are installed in a floating manner with mechanical locking systems formed at the long and short edges. These systems comprise locking means, which lock the panels horizontally and vertically. The mechanical locking systems are usually formed by machining of the core of the panel. Alternatively, parts of the locking system can be 15 formed of a separate material, for instance aluminium or plastic material, which is integrated with the floor panel, i.e. joined with the floor panel in connection with the manufacture thereof.

20 Laminate flooring usually comprise a 6-8 millimetre, mm, wood based core, a 0.2 mm thick upper decorative surface layer of laminate and a 0.1 mm thick lower balancing layer of laminate, plastic, paper or like material. A laminate surface comprises melamine-impregnated paper. The most common core material is fibreboard with high density and good stability usually called 25 HDF – High Density Fibreboard. The impregnated paper is laminated to the core with heat and pressure. HDF material is hard and has a low flexibility especially in the vertical direction perpendicular to the fibre orientation.

Recently a new type of powder based laminate floors, generally referred to as 30 WFF floors (Wood Fibre Floors), have been introduced. Impregnated paper is replaced with a dry powder mix comprising wood fibres, melamine particles, aluminium oxide and pigments. The powder is applied on an HDF core and cured under heat and pressure. Generally, high quality HDF is used with a high resin content and low water swelling. Advanced decors may be formed

by means of digital printing. Water based ink may be injected into the upper surface of the powder or injected in several transparent powder layers prior to pressing such that a very wear resistant 3D-print may be obtained. A digital binder and powder printing generally referred to as the "BAP method" may 5 also be used to create advanced 3D-prints. Pigmented powder, or so-called dry ink, may be bonded in several layers with a digitally applied binder pattern comprising blank ink without pigments. The high wear resistance is often used to produce copies of stone and tiles. Such WFF floors may be rather wide and the material cost for the short edge locking system may be rather 10 high.

LVT flooring with a thickness of 3-6 mm usually comprises a transparent wear layer which may be coated with an ultra-violet, UV, cured polyurethane, PU, lacquer and a decorative plastic foil under the transparent foil. The wear layer and the decorative foil are laminated to one or several core layers comprising 15 a mix of thermoplastic material and mineral fillers. The plastic core is generally soft and very flexible.

Wood Plastic Composite floors, generally referred to as WPC floors, are similar to LVT floors. The core comprises thermosetting material mixed with wood fibre fillers and is generally stronger and much more rigid than the 20 mineral based LVT core.

Thermoplastic material such as polyvinyl chloride, PVC, polypropylene, PP, or polyethylene, PE, may be combined with a mix of wood fibres and mineral particles and this may provide a wide variety of floor panels with different densities and flexibilities.

25 Moisture resistant HDF with a high resin content, LVT floors and WPC floors comprise stronger and more flexible core materials than conventional HDF based laminate floors and they are generally produced with a lower thickness.

A minimum thickness in several of the above mentioned floor types are mainly required in order to form the locking system. The panel itself is 30 generally strong and flexible and a thickness of about 3 - 5 mm would in many

applications be sufficient but cannot be used since it is not possible to form strong locking systems in such thin floors.

The above mentioned floor types comprise different core materials with different flexibility, density and strengths. Locking systems must be adapted

5 to such different material properties in order to provide a strong and cost efficient locking function.

#### DEFINITION OF SOME TERMS

In the following text, the visible surface of the installed floor panel is called "front side" or "floor surface", while the opposite side of the floor panel, facing

10 the sub floor, is called "rear side". The edge between the front and rear side is called "joint edge". By "horizontal plane" is meant a plane, which extends parallel to the front side. Immediately juxtaposed upper parts of two adjacent joint edges of two joined floor panels together define a "vertical plane" perpendicular to the horizontal plane. By "vertical locking" is meant locking

15 parallel to the vertical plane. By "horizontal locking" is meant locking parallel to the horizontal plane.

By "up" is meant towards the front side, by "down" towards the rear side, by "inwardly" mainly horizontally towards an inner and centre part of the panel and by "outwardly" mainly horizontally away from the centre part of the panel.

20 RELATED ART AND PROBLEMS THEREOF

For mechanical joining of long edges as well as short edges in the vertical and horizontal direction perpendicular to the edges several methods may be used. One of the most used methods is the angle-snap method. The long edges are installed by angling. The short edges are locked by horizontal snapping. The vertical connection is generally a tongue and a groove and the horizontal connection is a strip with a locking element in on edge that cooperates with a locking groove in the adjacent edge. Snapping is obtained with a flexible strip.

Similar locking systems may also be produced with a rigid strip and they are

30 connected with an angling-angling method where both short and long edges are angled into a locked position.

Advanced so-called “fold down locking systems” with a separate and flexible tongue on the short edges have been introduced where both the long and short edges are locked with a single angling action. A floor panel of this type is presented in WO 2006/043893. It discloses a floor panel with a short edge

5 locking system comprising a locking element cooperating with a locking groove, for horizontal locking, and a flexible bow shaped so called “banana tongue” cooperating with a tongue groove, for locking in a vertical direction. The flexible bow shaped tongue is inserted during production into a displacement groove formed at the edge. The tongue bends horizontally

10 along the edge during connection and makes it possible to install the panels by vertical movement. Long edges are connected with angling and a vertical scissor movement caused by the same angling action connects short edges. Such a locking is generally referred to as “vertical folding”.

Similar floor panels are further described in WO 2007/015669. This document

15 provides a fold down locking system with an improved flexible tongue so called “bristle tongue” comprising a straight outer tongue edge over substantially the whole length of the tongue. An inner part of the tongue comprises bendable protrusions extending horizontally along the tongue edge.

20 WO 2013/151493 describes a locking system having a tongue that is formed of the material of panel edge and is inserted into a groove in order to form a fold down locking system. It is not described how the tongue should be formed in order to obtain sufficient flexibility and how it should be and inserted into a groove in a cost efficient way.

25 The separate flexible tongue is a vital part of the fold down locking system. It would be an advantage if the flexible and separate tongue could be produced and inserted into the edge in a more cost efficient way. It would also be an advantage if the width and thickness of the tongue could be reduced such that a fold down locking system may be formed in very thin floor panels.

SUMMARY OF THE INVENTION AND OBJECTS THEREOF

An objective of embodiments of the present invention is to provide an improved and more cost efficient fold down locking system comprising a flexible tongue for primarily adjacent short edges of thin floor panels.

5 A first specific objective is to provide a separate flexible tongue that is more compact and cost efficient than known tongues and that is suitable for locking thin panels.

10 A second specific objective is to provide a locking system with a flexible and bendable tongue that may be formed as a simple, straight and rod shaped component.

A third specific objective is to provide a cost efficient method to form an advanced flexible tongue from a core material of a floor panel and to insert the tongue after forming into a groove of the panel, preferably in the same production line.

15 The above objects, individually or collectively, of the invention may be achieved by embodiments of the invention.

According to a first aspect of the invention a set of essentially identical floor panels is provided with a mechanical locking system comprising a flexible tongue, which is arranged in a displacement groove at a first edge of a first 20 panel and a tongue groove at a second edge of an adjacent second panel. The flexible tongue is configured to cooperate with the tongue groove for locking of the first and the second edge in a vertical direction. The mechanical locking system further comprises a locking strip at the first or the second edge, provided with a locking element configured to cooperate with a locking groove at the other of the first or second edge for locking in a horizontal direction. The flexible tongue is displaceable in the horizontal direction in the displacement groove. An outer part of the flexible tongue comprises two or more curved edge sections each comprising a sliding surface, which is configured to cooperate with the second edge during locking, and a locking 25 surface that is configured to lock into and/or against the tongue groove. The tongue sections are spaced from each other in a length direction of the 30

flexible tongue that is curved in a locked and in an unlocked position. A first horizontal distance, from an outer upper edge of the first edge to an outer edge of the flexible tongue, and a second horizontal distance, from the outer upper edge of the first edge to an inner edge of the flexible tongue, varies 5 along a length of the flexible tongue. The tongue sections are configured to be pressed inwardly during locking by the second edge such that the curved sections are at least partially straightened and deformed to essentially straight rod shaped sections with a width, which is essentially the same along essentially the entire length of the flexible tongue and to move back towards 10 their initial positions in a final stage of the locking such that the locking surfaces are inserted into the tongue groove.

The curved sections may be straightened and deformed to essentially straight rod shaped sections with a width, which is essentially the same along essentially the entire length of the flexible tongue.

15 The tongue sections may be configured to spring back towards their initial positions in a final stage of the locking such that the locking surfaces are inserted into the tongue groove.

Here and in the following, the wording “second panel edge” will be used interchangeably with the wording “second edge” or “adjacent edge”, unless 20 stated otherwise.

By “essentially straight” is here meant that the curved section has been at least partly straightened towards a straight section. By way of example, the curved section may be straightened to a completely straight section. A first curved section may be straightened towards a straight section by being 25 straightened to a second curved section, wherein the first and second curved sections have a convex or concave outer edge along the length direction of the first and second curved section. During the straightening, an outer edge point of the convex or concave outer edge of the first curved section moves towards the displacement groove, wherein the outer edge point is a point on 30 the first curved section that is farthest away from the displacement groove. Thereby, the outer edge point of the first curved section moves to an outer

edge point of the second curved section that consequently is closer to the displacement groove, wherein the outer edge point now is a point on the second curved section that is farthest away from the displacement groove.

In the final stage of the locking, the tongue sections moves back towards their 5 initial positions. In a first example, the tongue sections partly move back to their initial positions. In a second example, the tongue sections move back completely to their initial positions. In a third example, some tongue sections move back completely to their initial positions and some tongue sections move back partly to their initial positions.

10 The tongue sections may move back towards their initial positions by springing back.

The sliding surface may have a shape that essentially corresponds to a shape of a portion of a lower wall of the tongue groove. Moreover, the locking surface may have a shape that essentially corresponds to a shape of a 15 portion of an upper wall of the tongue groove.

Preferably, the flexible tongue is freely arranged in the displacement groove. Thereby, no part of the flexible tongue is attached to the panel, e.g., by an adhesive or a friction connection.

Alternatively, however, one or more parts of the flexible tongue may be 20 attached to the panel. For example, a first longitudinal end portion and/or a second longitudinal end portion of the flexible tongue may be attached to the displacement groove. The attachment of the tongue may be provided by means of an adhesive, a clip, or by means of inserting it into a slot provided in the panel, such as in the displacement groove.

25 The tongue may be attached to the panel by means of a friction connection. The friction connection may be provided at one or more upper and/or lower parts of the tongue along a length direction of the tongue.

In a first example, the curved edge sections are essentially identical. In a second example, the curved edge sections are different.

The flexible tongue may comprise a plastic material. The plastic material may be a thermoplastic material or a thermosetting plastic material. In particular, the plastic material may be a cross-linked thermoplastic, such as cross-linked PE. By "cross-linked thermoplastic" is here meant that at least a portion of the 5 thermoplastic material comprises cross-links.

The sliding surface may be an inclined surface. The sliding surface may be essentially planar. The sliding surface may be directed upwards. According to one embodiment, the sliding surface forms an angle between 0° and 60° with respect to the vertical plane.

10 The locking surface may be an inclined surface. The locking surface may be essentially planar. The locking surface may be directed downwards. According to one embodiment, the locking surface forms an angle between 0° and 60° with respect to the vertical plane.

15 The width of the flexible tongue may be essentially the same over 90% of the length of the flexible tongue. By "essentially the same" for a measurement is meant within  $\pm 10\%$  of other.

The flexible tongue may comprise tongue sections with cross sections such that the first horizontal distance is essentially the same as the second horizontal distance.

20 A major part of the flexible tongue may comprise cross sections with a horizontal width and a vertical thickness that are essentially the same. By "major part" is meant at least 50% of a length of the tongue. In examples, the major part may be 70%, 80% or 90% of the length of the tongue. In a specific example, the major part may be an entire length of the tongue.

25 The vertical thickness of the flexible tongue may be less than about 1.5 mm.

A curved tongue with a simple cross section and a straight rod shaped geometry in the inner position provides several advantages that may be used to design a very compact flexible tongue suitable for locking of thin floor panels. By a thin floor panel is here meant that a thickness of the panel is

30 between 6 and 10 mm. A very thin floor panel has a thickness below 6 mm, for example 3, 4 or 5 mm.

According to a second aspect of the invention a set of essentially identical floor panels is provided with a mechanical locking system comprising a flexible tongue, which is arranged in a displacement groove at a first edge of a first panel, and a tongue groove at a second edge of an adjacent second panel. The flexible tongue is configured to cooperate with the tongue groove for locking of the first and the second edge in a vertical direction. The flexible tongue comprises a sliding surface and a locking surface. The displacement groove comprises a cavity comprising upper, inner and lower cavity walls and a horizontal opening. The second floor panel comprises a protrusion comprising a sliding edge, which is configured to cooperate with the sliding surface during locking and to press and bend a flexible tongue section into the cavity. The flexible tongue section is configured to move back outwardly such that the locking surface is inserted into the tongue groove.

The tongue sections may move back towards their initial positions by springing back.

The inner cavity wall may be a curved surface or a planar surface. The upper, inner and lower cavity walls may start and end in the displacement groove along a length direction thereof. The upper, inner and lower cavity walls may be continuous upper, inner and lower cavity walls, whereby the walls are smooth and connected to the displacement groove by means of a smooth transition, without any disruptions. The continuous walls may be formed by means of a rotating carving or jumping tool.

The flexible tongue may be straight. Thereby, a simple and cost-effective tongue is provided. Alternatively, however, the tongue may be curved.

The cross-section of the tongue may be constant along its length direction.

In a first example, the tongue section moves back partly to an initial shape of the tongue section. In a second example, the tongue section moves back completely to the initial shape of the tongue section.

The locking system may comprise two or more cavities and protrusions.

The mechanical locking system may comprise a locking strip, at the first or the second edge, provided with a locking element configured to cooperate

with a locking groove at the other of the first or second edge for locking in a horizontal direction.

According to a third aspect of the invention a set of essentially identical floor panels is provided with a mechanical locking system comprising a flexible tongue, which is arranged in a displacement groove at a first edge of a first panel, and a tongue groove at a second edge of an adjacent second panel. The flexible tongue is configured to cooperate with the tongue groove for locking of the first and the second edge in a vertical direction. An outer part of the flexible tongue comprises a protrusion comprising a sliding surface and a locking surface. The displacement groove comprises a cavity comprising upper, inner and lower cavity walls and a horizontal opening. The second floor panel comprises a sliding edge, which is configured to cooperate with the sliding surface during locking and to press and bend a flexible tongue section into the cavity. The flexible tongue section is configured to move back outwardly such that the locking surface is inserted into the tongue groove.

The upper, inner and lower cavity walls may be continuous upper, inner and lower cavity walls.

The tongue sections may move back towards their initial positions by springing back.

20 The locking system may comprise two or more cavities and protrusions.

The mechanical locking system may comprise a locking strip at the first or the second edge, provided with a locking element configured to cooperate with a locking groove at the other of the first or second edge for locking in a horizontal direction.

25 The cavities offer the advantages that the tongue may be formed as a very simple essential straight rod shaped component with a compact geometry suitable for locking of thin floor panels.

According to a fourth aspect of the invention a method for producing a locking system at edges of building panels comprising a core is provided. The

30 method comprises the steps of

- forming a strip at a lower part of a first edge and a locking element at an outer part of the protruding strip.
- forming a tongue from the core at an outer part of the first edge;
- forming an insertion groove at the first edge, wherein said insertion groove is sidewardly open and extends in the horizontal direction;
- displacing the tongue (10) at least partly into the insertion groove with a vertical and horizontal displacement, and
- forming a tongue groove and a locking groove at a second adjacent edge.

10 The tongue is configured to cooperate with the tongue groove for vertical locking and the locking element is configured to cooperate with the locking groove for horizontal locking.

The method may comprise the step of forming the tongue at the outer and lower part of the first edge.

15 The method may comprise the step of forming the tongue with a lower part and an upper part, wherein the lower and the upper part is vertically and horizontally offset in relation to each other.

The method may comprise the step of displacing the tongue with rotating wheels.

20 This production method offers the advantages that the tongue may be formed from the core material of the floor panel and no additional separate material is needed to produce a flexible tongue that always will have a suitable length that corresponds to the short edge of a panel.

According to a fifth aspect of the invention a set of essentially identical floor panels is provided with a mechanical locking system comprising a flexible tongue, which is arranged in a displacement groove at a first edge of a first panel and a tongue groove at a second edge of an adjacent second panel.

25 The flexible tongue is configured to cooperate with the tongue groove for locking of the first and the second edge in a vertical direction, wherein the

mechanical locking system further comprises a locking strip at the first or the second edge provided with a locking element configured to cooperate with a locking groove at the other of the first or second edge for locking in a horizontal direction. The flexible tongue comprises a lower part and an upper part. The lower and the upper part are vertically and horizontally offset in relation to each other and the lower part comprises a lower protrusion extending vertically downwards.

5 The lower part may comprise at least two lower protrusions along its length. The lower part may comprise at least two inner protrusions extending horizontally inwardly and being spaced from each other along the displaceable tongue.

10 A tongue with offset upper and lower parts offers the advantages that protrusions and cavities may be formed on the tongue in a cost efficient way when the tongue is formed in line from the same core material that is used to form the locking system.

15 It is emphasized that all embodiments disclosed above may be partly or completely combined with each other.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The disclosure will in the following be described in connection to exemplary 20 embodiments and in greater detail with reference to the appended exemplary drawings, wherein:

Figs 1a-e illustrate a fold down locking systems according to known principles.

25 Figs 2a-f illustrate embodiments of production methods which may be used to form grooves and cavities.

Figs 3a-f illustrate bending of a flexible tongue according to an embodiment.

30 Figs 4a-f illustrate forming of a flexible tongue from an extruded tongue blank or a sheet material according to an embodiment of the invention.

Figs 5a-f illustrate a locking system comprising cavities and protrusions provided in panels according to an embodiment.

Figs 6a-i illustrate displacement and bending of a rod shaped separate tongue according to an embodiment.

5 Figs 7a-b illustrate a method to separate and insert a flexible tongue into a groove according to an embodiment.

Figs 8a-c illustrate forming and insertion of a flexible tongue comprising protrusions according to an embodiment.

10 Figs 9a-d illustrate alternative methods to insert and bend a flexible tongue according to various embodiments.

Figs 10a-c illustrate forming of a flexible tongue according to an embodiment.

Figs 11a-b illustrate forming of a flexible tongue comprising displaced upper and lower parts according to an embodiment.

15 Figs 12a-e illustrate forming of a flexible tongue comprising displaced upper and lower parts according to various embodiments.

Figs 13a-h illustrate various embodiments in accordance with one aspect of the invention.

20 Figs 14a-d illustrate a method to reinforce a flexible tongue according to an embodiment.

Figs 15a-b illustrate locking systems of furniture components and ceramic tiles according to two embodiments.

Figs 16a-c illustrate forming of a curved flexible tongue according to an embodiment.

25 DESCRIPTION OF EMBODIMENTS OF THE INVENTION

Figures 1a – 1e show flexible tongues 10 and locking of a first 1 and a second 1' panel edge with vertical displacement according to known principles. A flexible bristle tongue 10 comprising a tongue body 20 and flexible protrusions 21 at its inner part as shown in figure 1b, or at its outer part as shown in figure

1c, is displaced inwardly into a displacement groove 11 during locking as shown in figure 1a and outwardly during the final stage of the locking such that the outer parts of the flexible tongue 10 are inserted into a tongue groove 9 and the adjacent edges of the first 1 and the second 1' panel are locked 5 vertically parallel to a vertical plane VP. The panel edges comprise a strip 6 with a locking element 8 in one of the edges that cooperates with a locking groove 14 formed in the adjacent edge and locks the edges in a horizontal direction parallel to the panel surface and perpendicularly to the vertical plane.

10 Figure 1b shows a bristle tongue 10 with a tongue body 20 and flexible protrusions 21 at its inner part. Figure 1c shows a bristle tongue 10 with a tongue body 20 and flexible protrusions 21 at its outer part.

15 The flexible tongue has a length direction L along the edge, a width W extending horizontally perpendicular to the edge, and a tongue thickness TT in the vertical direction. The tongue thickness TT is generally the same as the groove thickness GT of the displacement groove 11. The maximum width W is larger than the groove depth GD of the displacement groove 11.

20 The flexible tongue comprises a complex geometry and is therefore formed as an injected moulded thermoplastic-based component comprising glass fibres that are used to accomplish high strength combined with flexibility. A bending of the protrusions in the length direction of the tongue is an essential feature of such advanced flexible tongues.

25 Figures 1d and 1e show that the flexible tongue 10 is produced and delivered as a tongue blanks 30 comprising for example 8 – 32 tongues. Plastic material is injected into a tool through injection channels 31, generally from one side only in order to reduce production costs. The channel material is removed after the injection forming and may be re-melted and used again.

30 Injection moulding with thermoplastic material comprising glass fibres is a cost efficient method that provides high quality components with very low production tolerances. However, the production method and the geometry of the flexible tongue has several disadvantages that limits the possibilities to

produce cost efficient locking systems comprising a flexible tongues in new type of floor panels and core materials where a fold down installation is desirable.

One disadvantage is that a flexible tongue must have a length  $L$  that 5 corresponds to the width of the panel since it is inserted into a groove formed at the short edge.

Plastic material must flow through a tongue body 20 along the length  $L$  of the tongue 10 and there must be a space  $S$  between the protrusions 21 and the tongue body 20, see Figs. 1d and 1e. This provides certain cost related limits 10 to the geometry of the tongue. For example, the production time and the tool cost may increase considerably if the width  $W$  is lower than 4 mm, the thickness  $TT$  is lower than 1.5 mm and the length exceeds about 300 mm.

Another problem is that it is difficult to form a displacement groove with a 15 groove thickness  $GT$  that is smaller than about 1.5 mm if the groove depth  $GD$  is about 4 mm.

Mechanical locking systems are generally formed with large rotation tools that form grooves and protruding parts parallel to an edge and along the whole edge.

Figures 2a - 2e show embodiments of production methods that may be used 20 to form locking systems and tongues comprising cavities 22 and protrusions 21 arranged perpendicularly to an edge 1 according to an aspect of the invention.

Figure 2a is a top view showing a tool comprising rotating saw blades 40 that are displaced against a panel edge 1 and back again. Alternatively, the panel 25 1 may be displaced against the saw blades 40 and back again. This production method may be used to form cavities 22 or protrusions 21 as shown in figures 2b and 2c, wherein the upper figures illustrate perspective views and the lower figures illustrate top views of the panel edge 1.

Figure 2d shows a side view of a so-called rotating jumping tool head 41 that 30 may be displaced vertically or horizontally against a moving panel edge 1. Thereby, local cavities 22 may be formed.

Figure 2e shows a cost efficient method to form cavities 22 with a rotating carving tool 45. The carving tool 45 comprises teeth 46 which are arranged along an outer edge of the carving tool 45. The tool rotation speed is synchronized with the displacement of the panel 1 and each tooth 46 forms 5 one cavity 22 at a predetermined position and with a predetermined horizontal extension along an edge of a panel 1. It is not necessary to displace the tool vertically. A carving tool 45 may have several sets of teeth 46 and each set may be used to form one cavity. The cavities 22 may have different cross sections depending on the geometry of the teeth 46.

10 Figure 2f shows a top view of a so-called screw cutter 42. This is an advanced production technology that allows high precision and cost efficient forming of protrusions and cavities perpendicular to an edge that is displaced in a high speed against the screw cutter 42. WO 2010/087752 provides a detailed description of the screw cutter principle.

15 Figure 3a shows a flexible tongue 10 according to an embodiment. A width W of the flexible tongue 10 is essentially the same over substantially the whole length L of the flexible tongue 10.

20 Figures 3b and 3c show an enlarged picture of a tongue portion Ts1 shown in figure 3a and a cross section A-A of the flexible tongue 10 inserted in a displacement groove 11 provided in the panel edge 1.

Figure 3b shows the flexible tongue 10 in an unlocked and in a locked position. The unlocked position is illustrated by the upper panel edge 1' which is indicated by an unbroken line while the locked position is illustrated by the lower panel edge 1' which is indicated by a broken line. The flexible tongue 25 10 is inserted in a displacement groove 11 comprising an upper lip 12. A vertical plane VP intersects the upper and outer part of the upper lip 12. The tongue comprises at least two tongue sections Ts1, Ts2, each comprising a sliding surface 15, that during locking cooperates with a sliding edge 17 of the adjacent edge 1', and a locking surface 16 that locks into the tongue groove 30 9. According to the present embodiment, the sliding surface 15 is provided in an upper part of the flexible tongue 10. More specifically, the sliding surface

15 is an outer and upper inclined part of the flexible tongue 10. Moreover, according to the present embodiment, the locking surface 16 is provided in a lower part of the flexible tongue 10. More specifically, the locking surface 16 is an outer and lower inclined part of the flexible tongue 10. The sliding 5 surface 15 is arranged above the locking surface 16. The tongue sections Ts1, Ts2 are spaced from each other in the length direction L of the flexible tongue 10. The tongue is curved in a locked and in an unlocked position such that a first horizontal distance D1 from the vertical plane VP and to the outer part of the flexible tongue 10 and a second horizontal distance D2 from the 10 vertical plane VP to an inner part of the flexible tongue 10 varies along the length L of the tongue.

The shape of the flexible tongue 10 may be further defined by a third horizontal distance D3 from the inner part of the tongue to an inner horizontal line connecting the innermost points of the tongue. The inner line is 15 essentially parallel with a length direction of the flexible tongue 10. The inner line is a straight line if each of the tongue sections Ts1, Ts2,... have the same shape. In a first example, D1 corresponds to D3 along the entire length direction of the flexible tongue 10, thereby providing a constant width W of the flexible tongue 10. In a second example, D1 differs from D3 at least along a 20 portion of the length direction of the flexible tongue 10, thereby providing a varying width W.

It is clear that the illustrated embodiments of the present application are non-limiting with regard to the number of tongue sections. Indeed, there may be one or more tongue sections Ts1, Ts2,..., TsN, where N is an arbitrary integer 25 larger than or equal to one, i.e. N=1, 2, 3, 4,...

Figure 3c shows the flexible tongue 10 in an inner position during locking. According to the present embodiment, the adjacent edge 1' is displaced 30 essentially vertically downwards towards the first panel edge 1 during locking, such that the locking groove 14 provided in the adjacent edge 1' is lowered towards and cooperates with the locking element 8 provided in the first panel edge 1. The flexible tongue 10 is pressed inwardly by the sliding edge 17 of

the adjacent panel 1' and the curved sections Ts1, Ts2 are straightened such that the flexible tongue 10 is formed to an essentially straight rod shaped component with a tongue width W that is essentially the same along the major part of the flexible tongue. In an embodiment, during locking of a tongue 5 section, the distance D3 may change from an unlocked distance to less than 20% of the unlocked distance. It is noted that the sliding surface 15, which protrudes outwardly beyond the vertical plane VP in a locked position as well as in an unlocked position, as illustrated in Fig. 3b, is pressed towards the displacement groove 11 during locking as illustrated in Fig. 3c. Thereby, the 10 sliding surface 15 may be pressed inwardly of the vertical plane VP during locking – partly or entirely.

As shown in Figure 3b the flexible tongue 10 comprises inner protrusions 21a and outer protrusions 21b arranged along a length direction of the tongue at an inner part and an outer part of the tongue, respectively. In Figure 3b it may 15 be seen that the tongue section Ts1 comprising an outer protrusion 21b has been straightened to an essentially straight section.

Figure 3d shows an embodiment according to which the panels comprise short edges 1, 1' and long edges 4. A scissor movement of the adjacent short edge 1' caused by the angling of the long edge 4 of the panel will gradually 20 press the tongue sections inwardly along the panel edge and deform the flexible tongue 10 towards an essentially straight component. For example, at least one tongue section of the flexible tongue 10, which has a convex or concave outer edge along the length direction of the tongue section, may become straightened so that an outer edge point of the convex or concave 25 outer edge moves towards the displacement groove 11, wherein the outer edge point is a point on the tongue section farthest away from the displacement groove 11. In Figure 3b the outer edge point is located in a centre portion of the convex tongue section Ts1 along its length direction where a distance XM to the inner wall of the displacement groove 11 is maximal. It is noted that in a concave tongue section Ts0, as shown in Figure 30 3b, the outer edge point may be located in an edge portion of the concave tongue section along its length direction where a distance to the inner wall of

the displacement groove 11 is maximal. By way of example, the outer edge point may move towards the displacement groove 11 at least by a distance corresponding to 20-60% of a maximal width of the tongue 10, preferably 40-50%. In particular, the flexible tongue 10 may be straightened to an 5 essentially straight component, for example a straight component along its entire length. Preferably, the outer parts of the flexible tongue 10 and the tongue groove 9 are configured such that an inner part of the edge 1a and a first tongue portion Ts1 is located close to its final locked position, as shown in figure 3e, when an outer part of the edge 1b and a second tongue portion 10 Ts2, preferably a tongue portion that is most distant to the first tongue portion Ts1, is located in its inner position as shown in figure 3f. The edge sections Ts1, Ts2 will gradually move into the tongue groove 9 during the vertical folding and locking resistance and separation forces, that may press the short edges away from each other due to the bending of the tongue, will be 15 reduced. This facilitates an easy locking.

The flexible tongue 10 may comprise friction connections 23, preferably located at an upper and/or a lower part of tongue. The friction connections 23 may be elongated. The required flexibility is mainly obtained by a curved tongue body 20 of the tongue that during locking bends mainly horizontally 20 and inwardly into the displacement groove 11.

The flexible tongue 10 may comprise tongue portions with cross sections wherein the first horizontal distance D1 is essentially the same as the second horizontal distance D2 such that the tongue width W may be about 2 times the width of the sliding surface 15 that protrudes beyond the vertical plane 25 VP. The flexible tongue 10 may be formed with a very compact cross section such that the tongue width W is essentially the same as the tongue thickness TT.

The described embodiment offers several advantages. The straight inner position makes it possible to form displacement grooves with a very small 30 depth. The simple geometry of the tongue allows a cost efficient production since plastic material may float easily during the injection moulding and this

makes it possible to decrease the tongue width W and the tongue thickness TT and to increase the tongue length L. It is possible to produce an injection-moulded tongue with a thickness TT that is less than 1.5 mm, for example with a thickness of about 1.0 – 1.5 mm and with a width W of about 1.5 – 3 mm. It is also possible to produce extremely thin flexible tongues with a tongue thickness TT of 0.5 – 1.0 mm. Such tongues may be used to lock very thin floor panels, for example LVT or WPC floor panels with a thickness of about 3 mm.

A stiffness of the flexible tongue may be specified by a transverse spring constant. According to a non-limiting example, the transverse spring constant of the flexible tongue is between 5-50 N/mm per 100 mm length of the tongue. According to another non-limiting example, the transverse spring constant is between 15-25 N/mm per 100 mm length of the tongue. The transverse spring constant of the flexible tongue may be tested by standard methods known to a person skilled in the art.

Figure 4a illustrates a top view and a cross-sectional view of a tongue blank 30 according to an embodiment. Figures 4a – 4b show that the flexible tongue 10 may be formed from a tongue blank 30 that is an extruded plastic or metal component comprising an identical cross section along the whole length of the tongue blank. In particular, the tongue blank 30 has a constant width along its length direction. A punching wheel 43 may form curved parts of the flexible tongue 10. The curved parts are formed by removing material from the tongue blank 30. According to the present embodiment, material is removed from an inner part and from an outer part of the tongue blank 30 in such a way that a width of the resulting flexible tongue 10 becomes essentially constant along a length direction of the flexible tongue 10. The flexible tongue 10 may have friction connections 23 protruding vertically upward or downward. This is illustrated in the top view of the flexible tongue 10 according to the embodiment in Figure 4b.

According to an alternative embodiment, material may be removed from an inner part and/or from an outer part of the tongue blank 30 in such a way that

the width of the resulting flexible tongue 10 becomes non-constant along the length direction of the flexible tongue 10. Examples of flexible tongues 10 having non-constant widths will be described further below in relation to the embodiments in Figures 9b, 9c and 12c.

5 According to alternative embodiments, the curved parts of the flexible tongue 10 may be formed by other means, such as cutting, carving, punching or milling, or any combination of these means.

The tongue blank 30 and/or the flexible tongue 10 may be formed by means of injection moulding, extrusion, 3D printing by forming successive layers, or  
10 pultrusion with a reinforcement material.

Generally, the tongue blank 30 and/or the flexible tongue 10 may comprise at least one material chosen from the group consisting of a plastic, such as a thermoplastic or a thermosetting plastic, a WPC, a metal, or a panel material, such as a panel core material or material from at least one layer of a panel.

15 The material may further comprise a reinforcement material. Thereby, the material may become more rigid. For example, the reinforcement material may comprise fibres or resins, such as thermosetting resins. Alternatively, or additionally, the material may comprise a cross-linked material, such as a plastic with cross-linked polymers.

20 The thermoplastic may comprise PVC, PE, PP, CPVC, or similar materials. In non-limiting examples the polyethylene may be a low-density PE, a linear low-density PE, a medium-density PE or a high-density PE. In particular, the thermoplastic may be a cross-linked thermoplastic, such as cross-linked polyethylene, also called PEX or XLPE. Moreover, the thermoplastic may be  
25 a reinforced thermoplastic. The reinforced thermoplastic may comprise a reinforcement material, such as fibres. The fibres may comprise at least one of glass fibres, carbon fibres, aramid fibres, wood fibres, basalt fibres, non-woven fibres, or textile fibres. Alternatively, the fibres may comprise metal fibres, such as magnetic metal fibres, e.g. iron or a magnetic alloy. Thereby,  
30 the fibres may be separated from the plastic more easily during recycling. The

fibres may have a specific orientation. For example, the fibres may be oriented along a length direction of the flexible tongue 10. Alternatively, the fibres may be randomly oriented. The fibres may be randomly distributed in the flexible tongue 10. Alternatively, the fibres may be arranged in the form of 5 a mat-shaped layer in the flexible tongue 10, such as a fabric, for example in a centre portion of the flexible tongue 10.

Thus, the flexible tongue 10 preferably comprises a low-creep material that does not creep or deform to any considerable extent over time. Thereby, the locking function does not deteriorate over time, for example after 1 month, 1 10 year, or 10 years. The reinforced and the cross-linked materials described above may both counteract creeping. Figures 4d-4f show that tongues blanks 30 may be formed from a sheet shaped material 50. The sheet shaped material 50, which is illustrated in Figure 4d in the case of a single-layer sheet, may be a thermoplastic material, preferably comprising mineral or 15 wood fillers. Preferably at least three layers are laminated or fused together. Glass fibres or any other fibres described above may be used to reinforce the sheet shaped material. The sheet shaped material may also comprise thermosetting resins preferably mixed with wood fibres. Figure 4f shows a sheet shaped material 50 comprising at least three layers. The upper 51a and 20 the lower 51c layers comprise thermoplastic material and the middle layer 51b is a reinforcement layer comprising fibres, for example glass fibres. The middle layer 51b is a mat-shaped layer comprising fibres. It is clear, however, that other materials described above may be used for the layers 51a-c. For example, the upper 51a and the lower 51c layers may comprise a 25 thermosetting plastic and/or the middle layer 51b may comprise randomly distributed fibres. According to the embodiment in Figure 4e, the flexible tongue 10 comprises at least three layers of materials with different material properties. The layers and reinforcement layers may be joined to each other by means of heating and/or pressing. Hot embossed rollers may be used to 30 form straight 52a or curved 52b sheet grooves in the sheet shaped material 50 that after separation form outer and/or inner parts of a flexible tongue 10. The grooves may also be formed with rotating cutting or carving tools. A

punching tool 43, or punching wheel 43, may also be used to form the flexible tongues 10. All these production methods may be combined. Flexible tongues 10 may also be formed with conventional 3D-printing methods. In relation to Figures 4d-f, three layers have been chosen for illustrative purposes only and 5 it is clear that any number of layers may be chosen, for example 1, 2, 3, 4, 5, 6 or 7 layers. Additionally, there may be a plurality of reinforcement layers. For example, there may be a centre layer sandwiched between inner surfaces of a first and a second reinforcement layer, and an upper and lower layer arranged on outer surfaces of the first and second reinforcement layer, 10 respectively.

Figure 5a shows that the flexible tongue 10 may be formed as a straight rod shaped component. Figure 5b shows that cavities 22a, 22b may be formed at the inner part of the displacement groove 11 of a first panel 1 and that protrusions 21 may be formed in the adjacent second panel 1'. The cavities 15 22a, 22b and the protrusions 21 are formed along portions of the side edges of the panels 1, 1' in their length direction. Each cavity comprises a continuous upper 26, inner 27, and lower 28 cavity wall and a horizontal cavity opening 29 towards the vertical plane VP. The cavity walls are preferably continuous along the edge since they are preferably formed with a 20 rotating carving or jumping tool. At least a portion of the inner cavity wall 27 is curved. Each protrusion 21 comprises an upper horizontal wall and an outer wall. According to the present embodiment, the outer wall is inclined. According to an alternative embodiment, however, the outer wall may be 25 vertical and the protrusion may also comprise a lower horizontal wall that is essentially parallel with the upper wall. The cavities 22a, 22b may have the same vertical extension as the displacement groove 11. Alternatively, the cavities 22a, 22b may have a larger vertical extension than the displacement groove 11. This provides a more cost efficient production since larger and more efficient jumping tools or saw blades may be used and production 30 tolerances may be increased without negative effects on the locking function. According to an alternative embodiment, the cavities 22a, 22b may have a smaller vertical extension than the displacement groove 11.

Figure 5c – 5f show that the protrusions 21 and the cavities 22 are located along the panel edges and adjacent to each other such that a protrusion 21 may displace and bend a part of a tongue section Ts1 into the cavity 22.

Figure 5d shows a cross section A-A comprising a cavity 22a that has about 5 the same vertical extension or cavity thickness Ct as the thickness GT of the displacement groove 11. Figure 5e shows an alternative embodiment of the cross-section A-A wherein a cavity 22b has a larger cavity thickness than the displacement groove 11 and is offset vertically below the upper or lower parts of the displacement groove. The displaceable tongue 10 may have an outer 10 portion with a larger outer tongue thickness TTa than a tongue thickness TTb of an inner portion. An advantage is that the inner part of the tongue may be displaced into a cavity even if the vertical position of the forming tool is not aligned with the upper part of the displacement groove 11. According to an alternative embodiment, the cavity 22b may have a smaller cavity thickness 15 than the displacement groove 11. Figure 5f shows a cross section B-B where no cavity and protrusion are formed and where essentially no displacement of the flexible tongue 10 in the displacement groove 11 takes place. This part of the edge is used as a support for the inward bending of the tongue section Ts1.

20 Figures 6a – 6i show in detail the displacement of a flexible rod shaped tongue 10 according to figures 5a – 5f. Figure 6a shows a top view of a first 1 and a second 1' edge section at horizontal planes HP 1 and HP 1' according to figures 6b and 6c. Here, the tongue is essentially straight. Figures 6d – f show the flexible tongue 10 in a bended inner position wherein parts of the 25 flexible tongue 10 has been pressed into the cavities 22 by means of the protrusions 21. Figures 6g – 6i show the flexible tongue 10 in an outer and locked position wherein the tongue groove 9 and the displacement groove 11 are vertically aligned so that the outer parts of the flexible tongue 10 has been inserted into the tongue groove 9. According to the present embodiment, the 30 flexible tongue 10 is essentially straight in the outer and locked position. According to an alternative embodiment (not shown), however, at least a

portion of the flexible tongue 10 may be bended in the outer and locked position. For example, the flexible tongue 10 may be bended in sections.

Figures 7a and 7b show a method to form a tongue, preferably a flexible tongue 10, from an edge part of a panel 1 and to insert the tongue into a groove, preferably a displacement groove 11, preferably in the same production line that is used to form the locking system. The flexible tongue 10 is in this embodiment formed at an outer part of the strip 6. Pressing wheels 44a, 44b and 44c may be used to separate the tongue 10 from the edge 1 and displace the tongue vertically and horizontally into the groove 11. It is preferred that a part P1 of the tongue is connected to the edge 1 when another part P2 is inserted and fixed into the groove 11. The tongue 10 may also be released from the edge 1 and displaced with the wheels 44a, 44b, preferably at the same speed as the panel edge 1, and inserted into the displacement groove 11 with wheels 44c or some pressing units. Upper and lower support units may be used to align and position the tongue into the groove. The tongue may be used in a locking system as described in figures 5a - 5f.

Such production method offers several advantages. Tongue blanks are not needed and the tongue 10 will always have an appropriate length that corresponds to the panel edge. A wide variety of core materials have been introduced on the market, such as HDF, high density water resistant HDF comprising an increased resin content, thermoplastic material mixed with mineral or wood fibre fillers, so called LVT or WPC material, foamed thermoplastic material etc. Any of the above-mentioned materials may be used for forming the flexible tongue 10 according to the embodiment in Figs. 7a-b. Thermoplastic floor materials are often reinforced with glass fibres in order to decrease thermal shrinking and expansion. Glass fibres 47 may be located in the part of the core 6 where the flexible tongue 10 is formed and may contribute to increase the strength and spring properties of the flexible tongue 10. Such materials have a sufficient flexibility and may provide a strong and flexible tongue body. Engineered wood floorings have generally a

separate material such as plywood on the short side and this separate material may also be used to form the flexible tongue. Thermoplastic floor materials are often reinforced with glass fibres in order to decrease thermal shrinking and expansion. Such glass fibre layers are positioned in the middle 5 parts of the core 6. Glass fibres 47 may be positioned in the part of the core 6, preferably the lower part, where the flexible tongue 10 is formed and may contribute to increase the strength and spring properties of the flexible tongue 10.

Figures 8a - 8c show that rather complex curved tongues 10 may be formed 10 with screw cutters, jumping tool heads or punching wheels and that cavities and protrusions formed in the panel edges are not needed to displace a flexible tongue 10 in a displacement groove 11. Figure 8a shows a tongue 10 formed and connected to an outer part of a strip 6. Figure 8b shows the flexible tongue 10 which is released from the strip 6 and figure 8c shows the 15 displaceable tongue 10 inserted into a displacement groove 11.

By a curved tongue is meant that at least a section of the tongue is curved. The curved tongue may comprise any number of curved sections, for example, 3, 4, 5, 6,... The curved sections may be directly connected to each other. Optionally, however, straight sections may connect the curved 20 sections.

Figures 9a - 9d show preferred embodiments of locking systems and the flexible tongues 10. Figure 9a shows a straight rod shaped flexible tongue 10 comprising locking surfaces 16 and sliding surfaces 15 inserted in a displacement groove 11 of an panel edge 1 comprising cavities 22. Figure 9a 25 also shows an adjacent edge 1' comprising protrusions 21. Figure 9b shows that the protrusions on the adjacent edge 1' may be replaced by outwardly extending protrusions 21 formed on the outer part of the flexible tongue 10. Such protrusions 21 are easy to form on a flexible tongue 10 produced by extrusions or produced from a sheet shaped material. Only a cost efficient 30 rotating carving tool may be sufficient to form a high quality locking system. According to the embodiment in Figure 9b, the flexible tongue 10 is insertable

into the cavities 22 of the displacement groove 11 with the protrusions 21 facing away from the cavities 22. Thereby, an outer surface of the panel edge 1', such as the sliding edge 17, may contact the protrusions 21 and displace and bend a part of a tongue section of the flexible tongue 10 inwardly. Figure 5 9c shows that the cavities 22 may be replaced with inner protrusions 21a formed on the inner part of the tongue 10. Thereby, the protrusions 21 on the panel edge 1' may displace and bend a part of a tongue section of the flexible tongue 10 inwardly. The displacement may occur between the inner protrusions 21a where there is a space between the tongue 10 and an inner 10 wall of the displacement groove 11. In this embodiment, the inner wall is a planar surface, but other shapes are equally conceivable. Figure 9d shows that both cavities and protrusions may be replaced with a curved flexible tongue 10 comprising inner protrusions 21a and outer protrusions 21b at the inner and outer parts of the flexible tongue 10, respectively. Thereby, the 15 outer surface of the panel edge 1', such as the sliding edge 17, may contact the protrusions 21 and displace and bend a part of a tongue section of the flexible tongue 10 inwardly towards the inner wall of the displacement groove 11. In this embodiment, the inner wall is a planar surface, but other shapes are equally conceivable.

20 In non-limiting examples, the inner part and/or the outer part of the flexible tongue 10 may be shaped essentially as a part of a sine wave, a part of a saw-tooth wave, have a step-wise constant profile, or have a straight profile.

In all of the embodiments above and in the following, it is clear that each 25 protrusion 21, 21a, 21b may be provided at a lower vertical portion, an upper vertical portion, or a centre portion of the flexible tongue 10.

Figure 10a shows that a curved tongue as shown in figures 8a - 8c may for example be formed with a screw cutter 42 and a jumping tool head 41. Figure 10b shows that a tongue 10 may be formed at an upper part of the edge with jumping tool heads 41. Such an embodiment will save material. Figure 10c 30 shows that the tongue 10 may be formed above the outer part of the strip 6

with a screw cutter 42 and a jumping tool 41. Jumping tools 41 may in all embodiments of the invention be replaced with rotating carving tools 45.

Figure 11a shows a panel 1 comprising a surface layer 2 and a core comprising an upper core layer 5a and a lower core layer 5b. In a non-limiting 5 example, the panel 1 may be an LVT panel. The lower core layer 5b comprises a higher content of thermoplastic material than the upper core layer 5a. A flexible tongue 10 is formed from the lower core layer 5b. This means that the flexible tongue 10 comprises the same material composition as the lower core layer 5b. Figure 11a also shows a flexible tongue 10 that 10 has been inserted into the displacement groove 11.

Figures 11a and 11b shows that a curved flexible tongue 10 may be formed in a cost efficient way with two screw cutters: a first screw cutter 42a and a second screw cutter 42b. The flexible tongue 10 preferably comprises an inner and lower part 10a and an upper and outer part 10b that are displaced 15 vertically and horizontally in relation to each other. The upper part 10b is preferably more distant to the inner part of the displacement groove 11 than the lower part 10a. An outer protrusion 21b is formed at the upper part 10b when a first screw cutter 42a removes material from the tongue and an inner protrusion 21a is formed at the lower part of the tongue 10a when a second screw cutter 42b removes material from the lower part of the tongue 10a. The 20 inner part of the tongue may also be formed as an upper part and the outer part may also be formed as a lower part. Such tongues may for example be used when the tongue is inserted into an edge of the second panel 1' comprising a locking groove 14.

Figures 12a - 12c provide a more detailed description of the locking system 25 shown in figures 11a, 11b. Figure 12a shows an edge section of a panel 1 comprising a part of a locking system formed at one of two adjacent panel edges. A groove 11, a strip 6 with a locking element 8 and a tongue 10 is formed with rotating tools. The tongue is preferably formed at an outer part of 30 the strip 6. The locking system and the tongue 10 comprise an essentially identical and continuous cross section along a length direction of the panel

edge 1. The tongue 10 comprises upper 10b and lower parts 10a displaced vertically and horizontally in relation to each other. The upper part 10b comprises a locking surface 16. The lower part 10a comprises lower protrusions 21c extending downwards. Figure 12b shows that a first screw cutter 42a and a second screw cutter 42b may be used to remove material from the outer and upper parts 10b and inner and lower parts 10a of the tongue 10 such that outer protrusions 21b and inner protrusions 21a are formed. Figure 12c shows a flexible tongue 10 that is released from the strip 6 such that it may be inserted into the displacement groove 11 during production of the locking system. The flexible tongue is characterized in that the inner protrusions 21a are located vertically below the upper part of the tongue 10.

Figure 12d and 12e show that the tongue 10 could be formed with a tongue body 20 that is inclined against a horizontal plane Hp1 in order to facilitate an easy machining in a double-end tenor machine comprising a chain 48 and an upper belt 49. The panel 1 is positioned in the double-end tenor with the surface layer 2 pointing downwards. The horizontal distance D4 from the tongue 10 and to the upper belt 49 may be smaller than a radius R of the jumping tool head 41, the screw cutter tool head 45 or of the screw cutter 42.

Figures 13a - 13h show different embodiments. Figure 13a shows a locking system comprising a flexible tongue 10 on the second panel 1', the fold panel, which comprises a locking groove 14 that cooperates with a locking element 8 formed on a strip 6 of the first panel 1. Figures 13b – 13d show that the flexible tongue 10 may be formed from a core section of the fold panel 1', which may be located at the upper, middle or lower part of the core 5. Figure 13e shows a locking system with a flexible tongue 10 attached to a displacement groove 11 formed at an inner wall of the locking groove 14 on the second fold panel 1'. The tongue 10 may be formed from a core section located at a lower part of the core as shown in figure 13f. Figure 13g shows a locking system comprising a displacement groove 11 formed at an outer part

of the strip 6 of the first panel 1. Figure 13h shows that the tongue 10 may be formed from a core portion located above the strip 6.

Figures 14a - 14d show that a core material 5 may be locally modified such that it becomes more suitable to form a flexible tongue 10. The method may 5 be used to increase the strength and flexibility of any kind of mechanical locking systems, even such systems that are formed as one-piece locking systems without a separate flexible tongue. Figure 14a shows that a resin, for example a thermosetting resin 24, such as for example melamine formaldehyde, urea formaldehyde or phenol formaldehyde resin, may be applied in liquid or dry powder form on for example a melamine formaldehyde 10 impregnated balancing paper 3 or directly on a core material 6. Figure 14b shows that a core material 5, preferably a wood based panel, for example a HDF board or a particle board, may be applied on the impregnated paper 3 with the added resin 24 prior to lamination. Figure 14c shows a floor board 15 after lamination when the surface layers 2 and the balancing layer 3 have been laminated to the core 6. The resins 24 have penetrated into the core 5 and cured during lamination under heat and pressure. Figure 14d shows an edge of a first panel 1 comprising a tongue 10 formed in one piece with the core 5. The tongue 10 is more flexible and comprises a higher resin content 20 than other parts of the core 5. The increased resin content provides a material that is very suitable to form a strong flexible tongue 10 that during production may be inserted into a displacement groove 11.

Figure 15a shows that a flexible tongue 10 and a locking system according to each embodiment of the disclosure may be used to lock furniture components 25 1, 1' perpendicularly to each other. Cavities 22 may be formed in an inclined displacement groove 11 and protrusions may be formed below the tongue groove 9. The flexible tongue may be a curved, rod shaped component as described above, and it may also be formed from a core portion of the panel core.

30 Figure 15b shows that a flexible tongue 10 and a locking system according to each embodiment of the disclosure may also be used to lock ceramic tiles 1,

1'. The strip 6 and the locking element 8 may be formed as a separate plastic or metal part that is attached to an edge of a first tile 1. Cavities 22 and protrusions 21 may also be formed in ceramic material with diamond tools. All embodiments of the disclosed flexible tongue 10 may be used. A second tile 5 1' comprises a tongue groove 9 and a locking groove 14. The flexible tongue 10 is configured to cooperate with the tongue groove 9 as described above for locking of the first and the second edge in a vertical direction. Moreover, the locking element 8 of the separate strip 6 is configured to cooperate with the locking groove 14 for locking in the horizontal direction.

10 All shown locking systems may be adapted such that they may be locked with vertical displacement and/or angling and/ horizontal snapping. They may also be released with upward angling or displacement along the edge. The vertical locking may be combined with a flexible strip 6 and preferably a flexible locking element 8 that is bended during locking. Preferably, the outer part of 15 the strip 6 is bended downwards and the upper part of the locking element 8 is bended or turned horizontally outwardly.

As illustrated schematically in Figs. 16a-c, the curved flexible tongue 10 may be formed by first providing a tongue blank 30, or an essentially straight tongue, and then bend it into a curved flexible tongue of a desired shape by 20 means of deformation. The tongue blank 30 is made of plastic, preferably a thermoplastic material or a thermosetting, with or without reinforcement, as has been described above. However, other materials are equally conceivable. This method is particularly suitable for producing curved flexible tongues 25 having an essentially constant cross-section along the length direction of the tongue. However, the tongue blank 30 may also have a varying cross-section along the length direction of the tongue. Optionally, the tongue blank 30 may comprise inner and/or outer protrusions along its length direction.

As shown in Fig. 16a, the tongue blank 30 is provided on a roll 32 and is fed into a bending device 34 according to a feeding method known to a person 30 skilled in the art. The tongue blank 30 is then arranged in a bent state as shown in Fig. 16b. According to the present embodiment, the tongue blank 30

is arranged in a sequence or matrix of bending elements 50 so that portions of the tongue blank become bent. In Fig. 16b the bending elements 50 are rods, nails or screws that are fixed to a substrate 52 and the tongue blank 30 is arranged in a zig-zag pattern between the bending elements 50.

5 Alternatively, however, the bending elements 50 may be rollers or cylinders. Optionally, the end points of the tongue blank 30 may be fixed, e.g. to the substrate 52. The final shape of the tongue is determined by the pattern of the bending elements 50. The horizontal and/or vertical distances between the bending elements 50 may be constant or, alternatively, varying.

10 The tongue blank 30 is then fixed in the bent state for a period of time. Optionally, heat may be provided to the tongue blank 30 in a heating process before and/or during the bent state by a heating device 60. Thereby, the forming of the curved tongue may be speeded up. Optionally, the tongue blank may also undergo a cooling process after the heating process by means of a cooling device 70. The heating and cooling process may be implemented by means of methods well known to a person skilled in the art. After a critical period of time has elapsed, the tongue blank 30 assumes a bent shape and becomes deformed permanently, or semi-permanently, and becomes a curved tongue element. The deformation may occur due to tensile forces, compression forces, shear, bending or torsion. A permanent deformation may be a plastic, irreversible, deformation. By semi-permanently is here meant that the bent shape provided directly after forming is essentially preserved at least during a minimum amount of time, such as 1 month, 1 year or 10 years. The curved tongue element is finally cut by a cutting device 80

15 into one or more curved flexible tongues 10 having predetermined lengths. A curved flexible tongue 10 resulting from the above process is schematically illustrated in Fig. 16c.

20 It is emphasized that all embodiments disclosed above may be partly or completely combined with each other. In particular, the various choices of

25 materials and reinforcements of the flexible tongue presented in relation to

the embodiment in Figs. 4a-c may also be used in embodiments of the other flexible tongues in the present application – straight or curved.

## CLAIMS

1. A set of essentially identical floor panels (1, 1') provided with a mechanical locking system comprising a flexible tongue (10), which is arranged in a displacement groove (11) at a first edge of a first panel (1), and a tongue groove (9) at a second edge of an adjacent second panel (1'), the flexible tongue (10) is configured to cooperate with the tongue groove (9) for locking of the first and the second edge in a vertical direction, wherein the mechanical locking system further comprises a locking strip (6), at the first or the second edge, provided with a locking element (8) configured to cooperate with a locking groove (14) at the other of the first or second edge for locking in a horizontal direction, characterised in:

that the flexible tongue (10) is displaceable in the horizontal direction in the displacement groove (11),

that an outer part of the flexible tongue (10) comprises two or more curved edge sections (Ts1, Ts2) each comprising a sliding surface (15), which is configured to cooperate with the second edge during locking, and a locking surface (16) that is configured to lock against the tongue groove (9),

that the tongue sections (Ts1, Ts2) are spaced from each other in a length direction (L) of the flexible tongue,

that the flexible tongue (10) is curved in a locked and in an unlocked position, wherein a first horizontal distance (D1), from an outer upper edge of the first edge (1) to an outer edge of the flexible tongue (10), and a second horizontal distance (D2), from the outer upper edge of the first edge (1) to an inner edge of the flexible tongue (10), varies along a length (L) of the flexible tongue (10),

that the tongue sections (Ts1, Ts2) during locking are configured to be pressed inwardly by the second edge such that the curved sections are at least partially straightened and deformed to essentially straight rod shaped sections with a width (W) which is essentially the same along essentially the entire length (L) of the flexible tongue (10), and

that the tongue sections (Ts1, Ts2) are configured to move back towards their initial positions in a final stage of the locking such that the locking surfaces (16) are inserted into the tongue groove (9).

2. The set of floor panels as claimed in claim 1, wherein the curved sections  
5 are straightened and deformed to essentially straight rod shaped sections with a width (W) which is essentially the same along essentially the entire length (L) of the flexible tongue.
3. The set of floor panels as claimed in claim 1 or 2, wherein the width (W) of  
10 the flexible tongue is essentially the same over 90% of the length of the flexible tongue (10).
4. The set of floor panels as claimed in any one of the preceding claims, wherein the flexible tongue (10) comprises tongue sections (Ts1, Ts2) with cross sections such that the first horizontal distance (D1) is essentially the same as the second horizontal distance (D2).
- 15 5. The set of floor panels as claimed in any one of the preceding claims, wherein a major part of the flexible tongue (10) comprises cross sections with a horizontal width W and a vertical thickness TT that is essentially the same.
6. The set of floor panels as claimed in any one of the preceding claims, wherein the vertical thickness TT of the flexible tongue is less than about 1.5  
20 mm.
7. The set of floor panels as claimed in any one of the preceding claims, wherein the flexible tongue (10) is freely arranged in the displacement groove (11).
8. A set of essentially identical floor panels (1, 1') provided with a mechanical  
25 locking system comprising a flexible tongue (10), which is arranged in a displacement groove (11) at a first edge of a first panel (1), and a tongue groove (9) at a second edge of an adjacent second panel (1'), the flexible tongue (10) is configured to cooperate with the tongue groove (9) for locking of the first and the second edge in a vertical direction, characterised in:

that the flexible tongue (10) comprises a sliding surface (15) and a locking surface (16),

that the displacement groove (11) comprises a cavity (22) comprising upper, inner and lower cavity walls (26, 27, 28) and a horizontal opening (29),  
5

that the second floor panel (1') comprises a protrusion (21) comprising a sliding edge (17) which is configured to cooperate with the sliding surface (15) during locking and to press and bend a flexible tongue section (Ts1, Ts2) into the cavity (22), and

10 that the flexible tongue section (Ts1, Ts2) is configured to move back outwardly in a final stage of the locking such that the locking surface (16) is inserted into the tongue groove (9).

9. The set of floor panels (1, 1',) as claimed in claim 8, wherein the locking system comprises two or more cavities (22) and protrusions (21).

15 10. The set of floor panels (1, 1',) as claimed in claim 8 or 9, wherein the mechanical locking system further comprises a locking strip (6), at the first or the second edge, provided with a locking element (8) configured to cooperate with a locking groove (14) at the other of the first or second edge for locking in a horizontal direction.

20 11. A set of essentially identical floor panels (1, 1') provided with a mechanical locking system comprising a flexible tongue (10), which is arranged in a displacement groove (11) at a first edge of a first panel (1), and a tongue groove (9) at a second edge of an adjacent second panel (1'), the flexible tongue (10) is configured to cooperate with the tongue groove (9) for locking of the first and the second edge in a vertical direction, characterised in:

that an outer part of the flexible tongue (10) comprises a protrusion (21) comprising a sliding surface (15) and a locking surface (16),

30 that the displacement groove (11) comprises a cavity (22) comprising upper, inner and lower cavity walls (26, 27, 28) and a horizontal opening (29),

that the second floor panel (1') comprises a sliding edge (17) which is configured to cooperate with the sliding surface (15) during locking and to press and bend a flexible tongue section (Ts1, Ts2) into the cavity (22), and

5 that the flexible tongue section (Ts1, Ts2) is configured to move back outwardly such that the locking surface (16) is inserted into the tongue groove (9).

12. The set of floor panels (1, 1'), as claimed in claim 11, wherein the locking system comprises two or more cavities (22) and protrusions (21).

13. The set of floor panels (1, 1'), as claimed in claim 11 or 12, wherein the 10 mechanical locking system further comprises a locking strip (6), at the first or the second edge, provided with a locking element (8) configured to cooperate with a locking groove (14) at the other of the first or second edge for locking in a horizontal direction.

14. A method for producing a locking system at edges of building panels (1, 1') comprising a core (5), wherein the method comprises:

- forming a strip (6) at a lower part of a first edge (1) and a locking element (8) at an outer part of the strip (6),
- forming a tongue (10) from the core (5) at an outer part of the first edge,
- 20 • forming an insertion groove (11) at the first edge, wherein said insertion groove is sidewardly open and extends in the horizontal direction,
- displacing the tongue (10) at least partly into the insertion groove (11) with a vertical and horizontal displacement, and
- 25 • forming a tongue groove (9) and a locking groove (14) at a second adjacent edge (1'),

wherein the tongue (10) is configured to cooperate with the tongue groove (9) for vertical locking and the locking element (8) is configured to cooperate with the locking groove (14) for horizontal locking.

15. The method as claimed in claim 14, wherein the method comprises the step of forming the tongue (10) at the outer and lower part of the first edge (1).
16. The method as claimed in claim 14 or 15, wherein the method comprises 5 the step of forming the tongue (10) with a lower part (10a) and an upper part (10b), wherein the lower and the upper part is vertically and horizontally offset in relation to each other.
17. The method as claimed in any one of claims 14-16, wherein the method comprises the step of displacing the tongue (10) with rotating wheels.
- 10 18. A set of essentially identical floor panels (1, 1') provided with a mechanical locking system comprising a flexible tongue (10), which is arranged in a displacement groove (11) at a first edge of a first panel (1), and a tongue groove (9) at a second edge of an adjacent second panel (1'), the flexible tongue (10) is configured to cooperate with the tongue groove (9) for 15 locking of the first and the second edge in a vertical direction, wherein the mechanical locking system further comprises a locking strip (6), at the first or the second edge, provided with a locking element (8) configured to cooperate with a locking groove (14) at the other of the first or second edge for locking in a horizontal direction, characterised in
- 20 that the flexible tongue (10) comprises a lower part (10a) and an upper part (10b),  
that the lower and the upper part are vertically and horizontally offset in relation to each other, and  
that the lower part comprises a lower protrusion (21c) extending 25 vertically downwards.
19. The set of floor panels (1, 1') as claimed in claim 18, wherein the lower part (10a) comprises at least two lower protrusions (21c) along its length (L).
20. The set of floor panels (1, 1') as claimed in claim 18 or 19, wherein the lower part (10a) comprises at least two inner protrusions (21a) extending

horizontally inwardly and being spaced from each other along the displaceable tongue (10).

1/16






Fig. 1d




## PRIOR ART






2/16



3/16



4/16



5/16

Fig. 5a




Fig. 5b




Fig. 5c




Fig. 5d




Fig. 5e

Fig. 5f

Fig. 6a




Fig. 6b




Fig. 6c




Fig. 6d





Fig. 6f




Fig. 6g






Fig. 6i



7/16

Fig. 7a





Fig. 7b



8/16

Fig. 8a




Fig. 8b




Fig. 8c




Fig. 9a




Fig. 9b




Fig. 9c





Fig. 9d



10/16

Fig. 10a




Fig. 10b





Fig. 10c



11/16

Fig. 11a




Fig. 11b




Fig. 12a




Fig. 12c




Fig. 12b




Fig. 12e





Fig. 12d



13/16

Fig. 13a




Fig. 13b




Fig. 13c




Fig. 13d




Fig. 13e




Fig. 13f




Fig. 13g





Fig. 13h



14/16

Fig. 14a




Fig. 14b




Fig. 14c





Fig. 14d



15/16

Fig. 15a





Fig. 15b



16/16

Fig. 16a




Fig. 16b




Fig. 16c



**INTERNATIONAL SEARCH REPORT**

International application No.  
PCT/SE2015/051270

**A. CLASSIFICATION OF SUBJECT MATTER**

**IPC: see extra sheet**

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

**IPC: E04F**

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

**SE, DK, FI, NO classes as above**

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

**EPO-Internal, PAJ, WPI data**

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 20070193178 A1 (GROEKE CARSTEN ET AL), 23 August 2007 (2007-08-23); abstract; paragraphs [0010], [0013], [0036], [0042]; figures 2,3,4,5a,5b --	1-7
A	US 20140190112 A1 (PERVAN DARKO ET AL), 10 July 2014 (2014-07-10); abstract; paragraphs [0049]-[0052]; figure 7f -- -----	1-7



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:	
“A” document defining the general state of the art which is not considered to be of particular relevance	“T” later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
“E” earlier application or patent but published on or after the international filing date	“X” document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
“L” document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	“Y” document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
“O” document referring to an oral disclosure, use, exhibition or other means	“&” document member of the same patent family
“P” document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search  
**23-03-2016**

Date of mailing of the international search report  
**24-03-2016**

Name and mailing address of the ISA/SE  
Patent- och registreringsverket  
Box 5055  
S-102 42 STOCKHOLM  
Facsimile No. + 46 8 666 02 86

Authorized officer  
**Örjan Nylund**  
Telephone No. + 46 8 782 28 00

**INTERNATIONAL SEARCH REPORT**

International application No.  
PCT/SE2015/051270

**Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)**

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1.  Claims Nos.: because they relate to subject matter not required to be searched by this Authority, namely:
  
2.  Claims Nos.: because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
  
3.  Claims Nos.: because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

**Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)**

This International Searching Authority found multiple inventions in this international application, as follows:

**The following separate inventions were identified:**

- 1: Claims 1-7 directed to a set of essentially identical floor panels (1, 1') provided with a mechanical locking system for locking in a vertical and horizontal direction comprising a flexible tongue (10).
  
- 2: Claims 8-10 directed to a set of essentially identical floor panels (1, 1') provided with a .../...
  

  1.  As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
  2.  As all searchable claims could be searched without effort justifying additional fees, this Authority did not invite payment of additional fees.
  3.  As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
  
  4.  No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.: **1-7**

**Remark on Protest**

- The additional search fees were accompanied by the applicant's protest and, where applicable, the payment of a protest fee.
- The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.
- No protest accompanied the payment of additional search fees.

**Continuation of:** Box No. III

mechanical locking system comprising a flexible tongue (10) for locking in a vertical direction.

3: Claims 11-13 directed to a set of essentially identical floor panels (1, 1') provided with a mechanical locking system comprising a flexible tongue (10) for locking in a vertical direction.

4: Claims 14-17 directed to a method for producing a locking system at edges of building panels (1, 1') for locking in a vertical and horizontal direction.

5: Claims 18-20 directed to a set of essentially identical floor panels (1, 1') provided with a mechanical locking system locking in a vertical and horizontal direction comprising a flexible tongue (10).

**Continuation of:** second sheet

**International Patent Classification (IPC)**

***E04F 15/02* (2006.01)**

***E04F 15/04* (2006.01)**

***E04F 15/10* (2006.01)**

**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

International application No.  
PCT/SE2015/051270

US	20070193178	A1	23/08/2007	AT	458876	T	15/03/2010
				DE	102006006124	A1	23/08/2007
				DE	502007002892	D1	08/04/2010
				EP	1818478	A1	15/08/2007
				ES	2338813	T3	12/05/2010
				US	7621092	B2	24/11/2009
US	20140190112	A1	10/07/2014	AT	533904	T	15/12/2011
				AU	2006229578	B2	04/08/2011
				BR	PI0612187	A2	26/10/2010
				CA	2600800	A1	05/10/2006
				CA	2824111	A1	05/10/2006
				CN	101581145	B	17/08/2011
				CN	101151430	A	26/03/2008
				CN	100523405	C	05/08/2009
				DE	202006020940	U1	17/02/2011
				DE	202006019869	U1	19/04/2007
				DK	1863984	T3	05/03/2012
				EP	2402527	A2	04/01/2012
				EP	2405075	A2	11/01/2012
				EP	2405074	A2	11/01/2012
				EP	2405073	A2	11/01/2012
				EP	2402528	A2	04/01/2012
				EP	2405078	A2	11/01/2012
				EP	2405077	A2	11/01/2012
				EP	2405076	A2	11/01/2012
				ES	2377435	T3	27/03/2012
				IL	185904	A	31/10/2011
				JP	4927072	B2	09/05/2012
				JP	2008534825	A	28/08/2008
				KR	20080002884	A	04/01/2008
				KR	101253552	B1	11/04/2013
				MX	2007012089	A	11/03/2008
				MY	145742	A	30/03/2012
				NO	20074837	A	13/12/2007
				NZ	561490	A	26/11/2010
				RU	2007139916	A	10/05/2009
				RU	2384679	C2	20/03/2010
				RU	2009145070	A	10/06/2011
				RU	2506382	C2	10/02/2014
				UA	92486	C2	10/11/2010
				US	20140109501	A1	24/04/2014
				US	8677714	B2	25/03/2014

**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

International application No.  
**PCT/SE2015/051270**

US	20150267419	A1	24/09/2015
US	9068360	B2	30/06/2015
US	8707650	B2	29/04/2014
US	20130145708	A1	13/06/2013
US	20120036804	A1	16/02/2012
US	20120031029	A1	09/02/2012
US	20110088345	A1	21/04/2011
US	20080155930	A1	03/07/2008
US	20080066415	A1	20/03/2008
US	20080034708	A1	14/02/2008
US	7634884	B2	22/12/2009
US	7866110	B2	11/01/2011
US	7841144	B2	30/11/2010
US	20060236642	A1	26/10/2006
US	8387327	B2	05/03/2013
US	8079196	B2	20/12/2011
US	8042311	B2	25/10/2011
WO	2006104436	A1	05/10/2006
ZA	200708265	A	26/11/2008