



US 20160241728A1

(19) **United States**

(12) **Patent Application Publication**  
**Naruse**

(10) **Pub. No.: US 2016/0241728 A1**

(43) **Pub. Date: Aug. 18, 2016**

(54) **APPARATUS, METHOD OF CONTROLLING  
THE SAME, AND STORAGE MEDIUM**

(71) Applicant: **CANON KABUSHIKI KAISHA,**  
Tokyo (JP)

(72) Inventor: **Taketomo Naruse,** Yokohama-shi (JP)

(21) Appl. No.: **15/005,208**

(22) Filed: **Jan. 25, 2016**

(30) **Foreign Application Priority Data**

Feb. 13, 2015 (JP) ..... 2015-026970

**Publication Classification**

(51) **Int. Cl.**  
**H04N 1/00** (2006.01)  
**G06F 3/12** (2006.01)


(52) **U.S. Cl.**

CPC ..... **H04N 1/00347** (2013.01); **H04N 1/00893**  
(2013.01); **H04N 1/00899** (2013.01); **G06F**  
**3/1207** (2013.01); **G06F 3/121** (2013.01);  
**G06F 3/1236** (2013.01); **G06F 3/1232**  
(2013.01); **G06F 3/1292** (2013.01); **H04N**  
**2201/0094** (2013.01); **H04N 2201/0072**  
(2013.01); **H04N 2201/006** (2013.01)


(57)

**ABSTRACT**


An apparatus that executes a job, broadcasts a wireless signal prior to establishing a connection by wireless communication with an external apparatus. The wireless signal includes information relating to the apparatus, by which it can be identified whether execution of a job by the apparatus is possible, in a predetermined packet.



**FIG. 1**



**FIG. 2A**



**FIG. 2B**




FIG. 3A




FIG. 3B







FIG. 4



**FIG. 5A**



**FIG. 5B**



**FIG. 5C**




FIG. 6A  
ADVERTISEMENT PACKET




FIG. 6B  
CAPABILITY INFORMATION

MAKER	MODEL NUMBER	COLOR	NUMBER OF INKS	SUPPORTED SHEET SIZES	SUPPORTED SHEET TYPES	DOUBLE-SIDED SUPPORTED
00000001	10101001	11	1001111	00111111	00111111	1

0:MONOCHROME  
1:COLOR

0:BLACK  
1:CYAN  
2:MAGENTA  
3:YELLOW  
4:ORANGE  
5:GREEN  
6:GRAY

0:A2  
1:A3  
2:A4  
3:A5  
4:B4  
5:B3  
6:Legal  
7:Letter

0:NORMAL PAPER  
1:RECYCLED PAPER  
2:PHOTO PAPER  
3:POSTCARD  
4:MATTE PAPER  
5:BOTH SIDES  
6:SEAL PAPER  
7:POSTER BOARD




**FIG. 6C**  
SETTING INFORMATION

616		617		618		619		620		621		622	
FIRST CASSETTE SHEET SIZE	SECOND CASSETTE SHEET SIZE	FIRST CASSETTE SHEET TYPE	SECOND CASSETTE SHEET TYPE	PRIORITY CASSETTE	PRINT MODE	PRINTING SPEED							
00001000	00000100	00001000	00000100	1	0010	101111							

**FIG. 6D**  
ERROR INFORMATION

623		624		625		626	
JOB STATUS	JOB ERROR	RECOVERABLE ERROR	FATAL ERROR				
000100111110011	00000000	01000000	00000				
0:NUMBER OF RECEIVED JOBS 1:NUMBER OF RECEIVED PAGES 2:NUMBER OF USERS IN VICINITY	0:SHEET SIZE MISMATCH 1:SHEET TYPE MISMATCH 2:IMAGE DECODING ERROR 3:PACKET ERROR 4:COLOR MISMATCH 5:IMPOSITION ERROR 6:UNSUPPORTED PROCESSING 7:OTHER	0:CONVEYING UNIT PAPER JAM 1:SHEET FEEDING UNIT PAPER JAM 2:SHEET TRAY FULL 3:DISCHARGING PORT CLOSED 4:COVER OPEN 5:INK OUTAGE 6:INK REMAINING AMOUNT LOW 7:OTHER	0:WASTE INK TANK FULL 1:PRINTING UNIT HIGH TEMPERATURE ERROR 2:INK CIRCULATION ERROR 3:POWER SOURCE ERROR 4:OTHER				



**FIG. 8A**

SEARCH FOR PRINTER MEETING CONDITION

☐ COLOR


☒ A4 SIZE OR GREATER

☒ 15 PPM OR GREATER

**FIG. 8B**

FOUND THE FOLLOWING PRINTERS

▪ PRINTER A	PAPER JAM ERROR	DISTANCE: 10m	
▪ MFP B	GOOD, PAPER = A4	DISTANCE: 30m	<div>CONNECT</div>
▪ PRINTER C	INK LOW, PAPER = A3	DISTANCE: 50m	<div>CONNECT</div>



**FIG. 9**

## APPARATUS, METHOD OF CONTROLLING THE SAME, AND STORAGE MEDIUM

### BACKGROUND OF THE INVENTION

[0001] 1. Field of the Invention

[0002] The present invention relates to a processing technique that processes a job received via a communication unit.

[0003] 2. Description of the Related Art

[0004] In recent years, in the Bluetooth (registered trademark) Core Specification V4.0, a very low power consumption wireless communication standard called Bluetooth Low Energy (hereinafter referred to as BLE) has been established. In BLE, extended operation using a battery such as a button battery is envisioned. In BLE, a new child node notifies its own existence to a parent node by intermittently broadcasting an advertisement packet. A child node can control the timing of advertisement packet broadcasting and the timing of reception of packets from a parent node, and power consumption is significantly reduced by entering a sleep state during other times.

[0005] In a case where a parent node is a mobile terminal such as a smart phone and a child node is an image processing apparatus such as a printer, the mobile terminal becomes a central and the image processing apparatus becomes a peripheral. The image processing apparatus, by an advertising communication scheme, broadcasts advertisement packets intermittently, and the mobile terminal can recognize the existence of the image processing apparatus by acquiring the advertisement packets.

[0006] Here, when the mobile terminal acquires an advertisement packet, it can establish a connection with the image processing apparatus, query the capabilities of the image processing apparatus, and execute a function that the image processing apparatus has. For example, in a case where the image processing apparatus has a print function, and is in a state in which it can execute a job, the mobile terminal can establish a connection with the image processing apparatus, and issue a print job to the image processing apparatus.

[0007] However, even in a state in which the image processing apparatus cannot execute printing, the image processing apparatus cannot broadcast an advertisement packet while the connection is established between the mobile terminal and the image processing apparatus. For this reason, there is a problem in that while a mobile terminal is in communication with an image processing apparatus, a user of another mobile terminal cannot recognize the existence of the image processing apparatus.

### SUMMARY OF THE INVENTION

[0008] The present invention is conceived in view of the foregoing problem, and provides a technique by which it is possible to improve efficiency of usage of a system that implements processing between a plurality of apparatuses.

[0009] According to one aspect of the present invention, there is provided an apparatus that executes a job, the apparatus comprises: a broadcast unit configured to broadcast a wireless signal prior to establishing a connection by wireless communication with an external apparatus, wherein the wireless signal includes information relating to the apparatus, by which it can be identified whether execution of a job by the apparatus is possible, in a predetermined packet.

[0010] Further features of the present invention will become apparent from the following description of exemplary embodiments (with reference to the attached drawings).

### BRIEF DESCRIPTION OF THE DRAWINGS

[0011] FIG. 1 is a view for illustrating a configuration of MFPs and a mobile terminal.

[0012] FIGS. 2A and 2B are perspective views of an MFP.

[0013] FIG. 3A is a block diagram for illustrating a control configuration of the MFP.

[0014] FIG. 3B is a block diagram for illustrating a control configuration of the mobile terminal.

[0015] FIG. 4 is a block diagram for illustrating a detailed configuration of a BLE unit.

[0016] FIGS. 5A to 5C are views for illustrating timing of broadcasting of advertisement packets.

[0017] FIGS. 6A to 6D are views for illustrating a detailed configuration of an advertisement packet.

[0018] FIG. 7 is a view for illustrating a processing sequence between the mobile terminal and the MFP.

[0019] FIGS. 8A and 8B are views for illustrating an example of displaying by a display unit of the MFP.

[0020] FIG. 9 is a view for illustrating a flow for when advertising is performed.

### DESCRIPTION OF THE EMBODIMENTS

[0021] Embodiments of the present invention will be described hereinafter in detail, with reference to the accompanying drawings. Note that the embodiments below do not limit the present invention according to the scope of the claims, and the means for solving in the present invention is not limited to requiring a combination of all features explained in the present embodiment. For identical elements identical reference numerals are given, and detailed explanation therefor is omitted.

#### First Embodiment

[0022] FIG. 1 is a pattern diagram illustrating an image processing apparatus, and a surrounding environment thereof.

[0023] In the present embodiment, explanation is given for a system including the image processing apparatus and a terminal device. Exemplary explanation is given using a Multifunction Printer (MFP) as an example of an image processing apparatus in the present embodiment. An MFP 200 is an MFP of an ink-jet method that has a plurality of functions such as a print function, a scanner function (reading function), a copy function, a fax function, or the like. Note that the print method that the MFP 200 uses is not limited to the ink-jet method, and it is possible to use another print method such as a laser beam method. Also, the image processing apparatus is not limited to this, and may have only a print function, may have only a scanner function, and may comprise other functions.

[0024] The MFP 200 operates as a BLE peripheral which is one short-range wireless communication specification. Also, the MFP 200 can transmit an advertising signal to its periphery without making a network connection with a particular terminal.

[0025] A mobile terminal 30, which is a terminal device, operates as a central which is a BLE central node. The mobile terminal 30, for example, is a terminal that can be carried, and can transmit to the MFP 200 a print job. The mobile terminal

**30** may be an information processing apparatus that handles a file that is a printing target such as a cellular phone, a digital camera, a smart phone or the like, but the mobile terminal **30** is not limited to these. The mobile terminal **30**, if positioned within a signal area **20** which is an effective communication range of the MFP **200**, can receive an advertising signal (an advertisement packet) from the MFP **200**. Accordingly, the mobile terminal **30** is able to receive advertising signals of a plurality of the MFP **200** if within the effective communication ranges of a plurality of the MFP **200** (in the case of FIG. 1, **2** of the MFP **200**). Also, as a characteristic of BLE, because the MFP **200** can receive a signal strength of an advertising signal that the MFP **200** transmitted, a central can identify an approximate distance to a peripheral.

**[0026]** Note that the signal area **20**, which is an effective communication range is a range over which the MFP **200** can communicate, is a communication range in which short-range wireless communication which is of a shorter communication range than that of long-range wireless communication such as Wireless Local Area Network (WLAN) (a shorter communication range than a predetermined distance) is realized. Also, it can be said that the MFP **200** and the mobile terminal **30** function as communication apparatuses, meaning that the apparatuses communicate with each other.

**[0027]** FIGS. 2A and 2B are views for illustrating an outer appearance of the MFP **200**, and in particular, FIG. 2A is a perspective view of the MFP **200**, and FIG. 2B is a top view of the MFP **200**.

**[0028]** An original platen **201** is a transparent base comprised of glass or the like, and is used when an original is placed on it and read by the scanner. An original lid **202** is a lid for making it so that scanning light does not escape to the outside when performing reading by the scanner. A printing sheet insertion port **203** is an insertion port for setting sheets of various sizes as a recording medium. The sheet set in the printing sheet insertion port **203** is conveyed to the printing unit one sheet at a time, a desired print is performed thereon, and it is discharged from a printing sheet discharging port **204**. Also, the MFP **200** comprises a first cassette **209** and a second cassette **210** as other print sheet supply units. For example, if A3 sheets are set in the first cassette **209**, and A4 sheets are set in the second cassette **210**, a user can execute print jobs whose print sizes are A3 and A4 without changing the sheets of the MFP **200**.

**[0029]** On an upper portion of the original lid **202**, an operation display unit **205** and an Near Field Communication (NFC) unit **206** are arranged. The operation display unit **205** has a display unit for displaying images, operation menus or the like, 4-direction keys used for cursor movement on the display unit, buttons, and a console unit for executing other various functions. Also, the operation display unit **205** may be comprised by a touch panel.

**[0030]** The NFC unit **206** is a unit for performing short-range wireless communication, and is in a location at which a terminal with which the short-range wireless communication is performed is actually caused to approach. The NFC unit **206** can perform communication by a terminal having an NFC communication function being caused to approach within a predetermined distance (approximately 10 cm). A WLAN antenna **207** is an antenna for communicating by WLAN. A BT antenna **208** is an antenna for communicating by Bluetooth and BLE.

**[0031]** FIG. 3A is a block diagram for illustrating a control configuration of the MFP **200**.

**[0032]** The MFP **200** comprises a main board **301** for performing main control of the apparatus, a WLAN unit **316** for performing WLAN communication, an NFC unit **317** for performing NFC communication, and a BLE unit **318** for performing Bluetooth communication and BLE communication.

**[0033]** In the main board **301**, a Central Processing Unit (CPU) **302** is a system control unit that controls the MFP **200** on the whole. A Read Only Memory (ROM) **303** stores various programs such as control programs that the CPU **302** executes, an embedded operating system (OS) program, or the like. In the present embodiment, software control such as scheduling, task switching or the like is performed under the management of the embedded OS stored in the ROM **303** for control programs stored in the ROM **303**. A Random Access Memory (RAM) **304** is configured by an SRAM (static RAM) memory or the like, and in addition to storing program control variables, setting values that a user registers, and various data such as management data of the MFP **200**, various work buffer regions are arranged.

**[0034]** A non-volatile memory **305** is configured by a memory such as a flash memory, and holds data that is stored even when a power source is turned off. Specifically, in this data there is user data such as a FAX telephone number, a communication history, network information, or the like, a list of mobile terminals connected to in the past, and setting information of the MFP **200** such as menu items of a print mode, and inkjet printhead correction information or the like. An image memory **306** is configured by a memory such as a DRAM (dynamic RAM), and stores various data such as image data received via each communication unit, image data processed by an encoding/decoding processing unit **312**, or the like.

**[0035]** Note that a memory configuration comprising the various foregoing memories is not limited to this, and it is possible to configure as appropriate the number, characteristics, storage capacities or the like of these in accordance with purpose and objectives.

**[0036]** A data conversion unit **307** performs processing such as analysis of page description language (the PDL) data, or the like, conversion from image data to print data, or the like. A reading control unit **308** optically reads an original in accordance with a reading unit **310** configured by a CIS image sensor (e.g., a contact image sensor) or the like, and outputs image data. Specifically, an original is optically read by the reading unit **310**, various image processing such as binarization processing or halftone processing is applied via an image processing control unit (not shown) to an image signal converted into electronic image data, and high definition image data is outputted.

**[0037]** An operation unit **309** and a display unit **311** correspond to the operation display unit **205** of FIG. 2B. The encoding/decoding processing unit **312** performs various processing such as encoding/decoding processing, resizing processing or the like of image data (the JPEG, PNG, or the like) processed by the MFP **200**. A sheet feeding unit **313** holds sheets for printing, and supplies sheets to a printing unit **315**. Here, the sheet feeding unit **313** collectively refers to a plurality of sheet feeding units such as the printing sheet insertion port **203**, the first cassette **209**, and the second cassette **210** of FIG. 2A. By control from a printing control unit **314**, it is possible to perform sheet feeding from the sheet feeding unit **313** to the printing unit **315**. Also, by the printing

control unit **314**, it is possible to control what sheet feeding unit of the plurality of sheet feeding units to perform sheet feeding from.

[0038] The printing control unit **314** converts image data that is the target of the printing into high definition image data by applying various image processing such as smoothing processing, print density correction processing, and color correction via the image processing control unit (not shown), and outputs to the printing unit **315**. Also, the printing control unit **314** periodically reads various information such as a status of the printing unit **315**, and updates information in the RAM **304**. Specifically, it updates, for example, remaining amounts of ink tanks, print head states, or the like.

[0039] In the MFP **200** there are the WLAN unit **316**, the NFC unit **317** and the BLE unit **318** as communication units for wireless communication, and it is possible to perform wireless communication in accordance with 3 types of communication specifications (WLAN, NFC, and BLE). Specifically, the WLAN unit **316**, the NFC unit **317**, and the BLE unit **318** are units for realizing communication in compliance with WLAN, NFC and BLE specifications respectively. The BLE unit **318** is a unit that used for both classical Bluetooth and BLE. The WLAN unit **316**, the NFC unit **317**, and the BLE unit **318** are communication units for performing data communication with other devices such as mobile terminals. These communication units convert data into packets and perform packet transmission to other devices. Meanwhile, these communication units convert packets from other external devices into data and transmit the data to the CPU **302**.

[0040] The WLAN unit **316**, the NFC unit **317**, and the BLE unit **318** are connected to a system bus **322** via bus cables **319**, **320** and **321** respectively.

[0041] Note that the foregoing various components **303-318** are connected to each other via the system bus **322** which the CPU **302** manages.

[0042] FIG. 3B is a block diagram for illustrating a control configuration of the mobile terminal **30**.

[0043] The mobile terminal **30** comprises a main board **701** for performing main control of the apparatus, a WLAN unit **716** for performing WLAN communication, an NFC unit **717** for performing NFC communication, and a BLE unit **718** for performing classical Bluetooth communication and BLE communication.

[0044] In the main board **701**, a CPU **702** is a system control unit that controls the mobile terminal **30** on the whole. A ROM **703** stores various programs such as control programs that the CPU **702** executes, an embedded operating system (OS) program, or the like. In the present embodiment, software control such as scheduling, task switching or the like is performed under the management of the embedded OS stored in the ROM **703** for control programs stored in the ROM **703**. A RAM **704** is configured by an SRAM (static RAM) memory or the like, and in addition to storing program control variables, setting values that the user registers, and various data such as management data of the mobile terminal **30**, various work buffer regions are arranged.

[0045] A non-volatile memory **705** is configured by a memory such as a flash memory, and holds data that is stored even when a power source is turned off. Specifically in such data there is a communication history, user data such as network information, a list of MFPs connected to in the past, and setting information of the mobile terminal **30** such as menu items of a communication mode or the like. An image memory **706** is configured by a memory such as a DRAM

(Dynamic RAM), and stores various data such as image data received via each communication unit, image data processed by an encoding/decoding processing unit **712**, or the like.

[0046] Note that a memory configuration comprising the various foregoing memories is not limited to this, and it is possible to configure as appropriate the number, characteristics, storage capacities or the like of these in accordance with purpose and objectives.

[0047] A data conversion unit **707** performs processing for data analysis, conversion from image data to job data, or the like.

[0048] An operation unit **709** is configured by a touch panel, keys, buttons or the like for performing operations on the mobile terminal **30**. A display unit **711** is configuring by an LCD, for example. The encoding/decoding processing unit **712** performs various processing such as encoding/decoding processing, resizing processing or the like of image data (the JPEG, PNG, or the like) processed by the mobile terminal **30**.

[0049] In the mobile terminal **30** there are the WLAN unit **716**, the NFC unit **717** and the BLE unit **718** as communication units for wireless communication, and it is possible to perform wireless communication in accordance with 3 types of communication specifications (WLAN, NFC, and BLE). Specifically, the WLAN unit **716**, the NFC unit **717**, and the BLE unit **718** are units for realizing communication in compliance with WLAN, NFC and BLE specifications respectively. The BLE unit **718** is a unit that used for both classical Bluetooth and BLE. The WLAN unit **716**, the NFC unit **717**, and the BLE unit **718** are communication units for performing data communication with other devices such MFPs. These communication units convert data into packets and perform packet transmission to other devices. Meanwhile, these communication units convert packets from other external devices into data and transmit the data to the CPU **702**.

[0050] The WLAN unit **716**, the NFC unit **717**, and the BLE unit **718** are connected to a system bus **722** via bus cables **719**, **720** and **721** respectively.

[0051] Note that the various foregoing components **703-718** are connected to each other via the system bus **722** which the CPU **702** manages.

[0052] FIG. 4 is a block diagram for illustrating a detailed configuration of the BLE unit **318** and the BLE unit **718**. Below explanation is given with the BLE unit **318** as an example.

[0053] Data is transmitted/received between the main board **301** and a microcomputer **403** via the bus cable **321**. By attaching an independent sensor in addition to the bus cable **321** it is possible to transmit/receive data by control other than that of the main board **301**. In the BLE unit **318**, an ADC **402** (Analog-to-Digital Converter) and the microcomputer **403** are connected to the bus cable **321**.

[0054] A sensor **401** is a device for converting a physical amount of a measurement target into an electrical signal. In the present embodiment, as the sensor **401**, there is a monitoring sensor or a motion sensor for identifying that there is a person in the periphery of the MFP **200**, for example, and a temperature sensor for monitoring the temperature of the MFP **200**.

[0055] The ADC **402** is analog/digital conversion circuit that converts an analog signal output from the sensor **401** into a digital signal that the microcomputer **403** can process. The microcomputer **403** is a microprocessor that performs wireless communication processing. In the microcomputer **403**, a

RAM and a flash memory are comprised. A wireless communication circuit 404 is configured by a device such as a wireless communication chip, a crystal oscillator, an inductor, a condenser, or the like, and performs transmission and reception of data by wireless communication. An operation switch 405 is a switch for turning on and turning off the power of the BLE unit 318, and the operation switch 405 sends a broadcasting signal by selecting ON. Note that a power of the BLE unit 318 ordinarily operates in cooperation with a power source of the MFP 200. In a case where a problem occurs in a power supply system of the MFP 200, it is possible to broadcast independently from the operation of the MFP 200 by turning on the operation switch 405 intentionally by a user operation. A battery 406 is a storage battery such as a button battery. A main body power source 408 is a power source supplied from the main board 301. A power source circuit 407 is a circuit for performing processing such as a voltage adjustment for efficiently supplying a power from the battery 406.

[0056] In this way, the MFP 200 has power sources of 2 systems: the battery 406 and the main body power source 408. With this, even if the MFP 200 cannot be activated for some reason, or if the power source of the main board 301 is turned off by a power saving function of the main body of the MFP 200, it is possible to broadcast (i.e., a multi-destination transmission) the advertising signal from the NFC unit 317. Also, in the BLE unit 318 a non-volatile memory 410 is installed, and by moving information such as operation information, setting information or the like that is stored in the RAM 304 of the main board 301, it is possible to perform communication alone using this information as necessary.

[0057] FIGS. 5A to 5C are views for illustrating an advertising signal that the BLE unit 318 broadcasts to its periphery.

[0058] FIG. 5A illustrates a normal advertising signal of the MFP 200. Tx 508 represents a transmission section of the advertising signal, and by causing transmission circuit to operate, a predetermined packet (e.g., an advertisement packet) explained with FIGS. 6A to 6D is transmitted. Rx 509 represents a standby section for waiting for a response from a communication partner (for example, the mobile terminal 30) to the advertising signal. Specifically, in the Rx 509, by turning the power source of a reception circuit on, a state in which reception of a response from a communication partner is possible is switched into. Then, after a predetermined amount of time has elapsed, that is outside of the standby section of the Rx 509, by turning off the power source of the reception circuit, a state in which a response cannot be received is switched to. One channel A 505 is formed by the Tx 508 and the Rx 509, and an advertising time 501 is defined by the Tx 508 and the Rx 509 in the channel A 505. Continuing from the channel A 505, a channel B 506 and a channel C 507 of similar configuration are comprised. Also, Tx and Rx are repeated by the number of the determined channels. For example, in the BLE standard, channels 37, 38 and 39 are allocated for advertisement packet channels, and in the present embodiment, the channel A 505, the channel B 506, and the channel C 507 correspond to these channels.

[0059] An Active section 502 is a section in which transmission and reception is performed by Tx and Rx. A power-saving section 503 is a section in which transmission and reception is not performed by Tx and Rx. The longer the power-saving section 503 is, the more power consumption of the BLE unit 318 can be suppressed. In this way, a predetermined interval from broadcasting the advertising signal until broadcasting the next advertising signal after waiting for a

corresponding response for a predetermined amount of time (i.e., the Active section 502 in FIG. 5A) is called an advertising interval 504. FIG. 5B and FIG. 5C are explained later.

[0060] FIGS. 6A to 6D are views for illustrating a detailed configuration of an advertisement packet.

[0061] The BLE unit 318 performs an initialization process when it enters a power on state, and after that enters an advertising state for transmitting/receiving advertisement packets. When the advertising state is entered, the BLE unit 318 transmits an advertisement packet illustrated in FIG. 6A to the periphery in a settable interval (i.e., predetermined interval). The advertisement packet is configured by a 2 byte header 601, and a payload 602. The header 601 is a region for storing a type of the packet, information of the size of the payload 602, or the like. The payload 602 is a region that can store information of the apparatus transmitting the advertising signal, and a predetermined size is allocated for it. In the payload 602, other than the device name and installation profile information, information relating to the MFP 200 such as the transmission power (a Tx Power 608) is stored. In the present embodiment, it is assumed that identifying information by which it can be identified whether the job execution by the image processing apparatus is possible is included. As the identifying information, there is capability information 605, setting information 606, and error information 607 which are explained later. In the present embodiment, in the payload 602, an MFP name 603, connection-to-MFP information 604, a NEXT Flag 627, and the Tx Power 608 are stored.

[0062] In the payload 602, a name for identifying an MFP is stored in the MFP name 603. Information such as a character string for being able to identify an MFP in an office uniquely, for example, is set as this name. The connection-to-MFP information 604 is information for the mobile terminal 30 to perform a connection to the MFP 200 after having received the advertisement packet. If in compliance with a specification of BLE, a protocol data unit (PDU) described in the BLE 4.0 specification is information for making a connection to the MFP 200. By transmitting/receiving protocol data PDUs, the mobile terminal 30 is able to perform data communication after establishing a connection with the MFP 200. Also, establishing a connection other than one for BLE is possible, and for example, by setting information for connecting to the WLAN unit 316 as information for performing a connection to the MFP 200, the mobile terminal 30 can make a connection with the MFP 200 by WLAN.

[0063] The Tx Power 608 is information indicating a signal strength of Tx. The MFP 200 can identify a propagation loss from information of the Tx Power 608 and the received signal strength of the received packet, and can make an estimation of the distance to the BLE wireless device from this identified propagation loss. For the capability information 605, the setting information 606, and the error information 607 which is state information of the MFP 200, explanation is given later in detail using FIG. 6B, FIG. 6C and FIG. 6D respectively.

[0064] Next, using FIG. 6B, a detailed configuration of the capability information 605 is explained. The capability information 605 is capability information for a job that the MFP 200 can execute. The mobile terminal 30, when it receives an advertisement packet that the image processing apparatus broadcasted, can identify what kind of functions the MFP 200 has without establishing a connection with the MFP 200 by receiving the capability information 605.

[0065] In the present embodiment, as the capability information 605, there is maker information (hereinafter referred



to as a maker **609**), model number information (hereinafter referred to as a model number **610**), color information (hereinafter referred to as a color **611**), and number of inks information (hereinafter referred to as a number of inks **612**). Also, as the capability information **605** there is supported sheet size information (hereinafter referred to as supported sheet sizes **613**), information of supported sheet types (hereinafter referred to as supported sheet types **614**), and information as to whether double-sided printing is possible (hereinafter referred to as double-sided supported **615**).

[0066] In the maker **609**, a maker identification (ID) provided for each maker is stored. In the model number **610**, an ID by which a product model of the MFP **200** can be identified uniquely is stored. In the color **611** a flag indicating whether it is a color printer or a monochrome printer is stored. In the number of inks **612** a bit is allocated for each recording material ink color, and the inks that can be mounted can be represented. That is, it is possible to identify the number of inks. For the supported sheet sizes **613**, a bit is allocated for each sheet size, and it is possible to represent the sheet sizes that can be set. For the supported sheet types **614**, a bit is allocated for each sheet type, and it is possible to represent the sheet types that can be set. In the double-sided supported **615** a flag indicating whether or not double-sided printing is possible is stored. In this way, because it is possible to identify the function of the MFP **200** by the capability information **605**, the mobile terminal **30** can determine whether a job for which execution is scheduled can be executed by that MFP.

[0067] Next, using FIG. 6C, a detailed configuration of the setting information **606** is explained. The setting information **606** is information set currently in the MFP **200**. The mobile terminal **30**, by receiving the setting information **606**, can identify a current setting state of the MFP **200** without establishing a connection with the MFP **200**.

[0068] In the present embodiment, as the setting information **606** there is information of a sheet size of the first cassette (hereinafter referred to as the first cassette sheet size **616**), and information of a sheet size of the second cassette (hereinafter referred to as the second cassette sheet size **617**). Also, as the setting information **606** there is information of a sheet type of the first cassette (hereinafter referred to as the first cassette sheet type **618**), and information of a sheet type of the second cassette (hereinafter referred to as the second cassette sheet type **619**). Furthermore, as the setting information **606** there is information of a priority cassette (hereinafter referred to as a priority cassette **620**), information of a print mode (hereinafter referred to as a print mode **621**), and information of a printing speed (hereinafter referred to as a printing speed **622**).

[0069] In the first cassette sheet size **616** and the second cassette sheet size **617**, setting values indicating the sizes of sheets set in the first cassette and the second cassette are stored. These setting values are similar to the bits allocated in the supported sheet sizes **613**. In the first cassette sheet type **618** and the second cassette sheet type **619**, setting values indicating the sheet types of sheets set in the first cassette and the second cassette are stored. These setting values are similar to the bits allocated in the supported sheet types **614**.

[0070] In the priority cassette **620**, a value indicating the cassette that is used preferentially out of the first cassette and the second cassette is stored. In the case where “1” is stored, the first cassette is used preferentially, and in the case where “2” is stored, the second cassette is used preferentially. For the print mode **621**, a value indicating the default print mode

is stored. In this value, values indicating various print modes such as “beautiful”, “normal”, and “fast” can be set. For the printing speed **622**, the printing speed in the current print settings is stored. For example, in a case where printing is performed in beautiful mode with A4 sheet size and with normal paper, the estimated number of sheets that can be printed in 1 minute is stored. Note that the printing speed itself may be stored.

[0071] In this way, the mobile terminal **30** can identify the current setting information of the MFP **200** and notify the user, and therefore can cue to find an MFP that the user desires. Also, the mobile terminal **30** can identify in advance in a case where the MFP has a desired function but the current settings are different, and notify this. Accordingly, a user can recognize that settings should be changed on the operation unit **709** of the MFP in advance, and the possibility that printing is performed with the wrong settings can be prevented is raised.

[0072] Next, using FIG. 6D, a detailed configuration of the error information **607** is explained. The error information **607** is information of an error that occurred in the MFP **200**. The mobile terminal **30**, by receiving the error information **607**, can identify that an error occurred on the MFP without establishing a connection with the MFP **200**, and can notify the user.

[0073] As the error information **607** there is information of a job status (hereinafter referred to as a job status **623**), information of a job error (hereinafter referred to as a job error **624**), information of a recoverable error (hereinafter referred to as a recoverable error **625**), and information of a fatal error (hereinafter referred to as a fatal error **626**).

[0074] In the job status **623**, information such as a status of a job that the MFP **200** received is stored. For example, the number of received jobs, the number of received pages, and the number of users that exist in the vicinity of the MFP **200** are stored. By identifying the number of received jobs and the number of received pages, the mobile terminal **30** can estimate (identify) approximately what the waiting time will be in a case where a job is transmitted. Also, for the number of users that exist in the vicinity of the MFP **200**, the number of mobile terminals in the vicinity of the MFP **200** can be estimated (identified) by broadcasting an advertisement packet and counting the number of responses thereto. Note that the number of users may be simply the number of mobile terminals that return responses or may be the number of mobile terminals within a predetermined distance.

[0075] In the job error **624**, a value indicating content of an error that occurred when a job is received and executed is stored. In the present embodiment, as the job error, it is possible to identify a sheet size mismatch, a sheet type mismatch, an image decoding error, a packet error, a color mismatch, an imposition error, unsupported processing, or other (errors other than the foregoing). An error often occurs in a case where, for example, the job is incorrect, or setting information of the transmitted job and setting information of the MFP **200** do not match. In other words, often these can be cancelled by re-transmitting an appropriate job from the mobile terminal **30**, or by changing a setting of the MFP **200**. In the present embodiment, the bits allocated for each job error can be notified if a plurality of errors occurred. The mobile terminal **30** can identify a job error of the MFP **200** based on the job error **624** and notify the user, and therefore the user can determine whether to use that MFP after cancelling the error, or whether to use another MFP.

[0076] In the recoverable error 625, a value indicating an error for which maintenance of the MFP 200 by the user is necessary among the errors that occur on the MFP 200 is stored. In the recoverable error 625, a value indicating an error is allocated in each bit similarly to the job error 624. In the present embodiment, as the recoverable error it is possible to identify a conveying unit paper jam, a sheet feeding unit paper jam, sheet tray full, discharging port closed, cover open, an ink outage, ink remaining amount low, and other errors for which maintenance by a user is necessary. By the recoverable error 625, in not only the mobile terminal 30 of the user that transmitted the job, but also in the mobile terminal 30 of users in the periphery, errors can be identified, and therefore it is possible to enhance the maintainability of the MFP 200.

[0077] In the fatal error 626, a value indicating an error for which maintenance of the MFP 200 by a user is difficult among the errors that occur on the MFP 200 is stored. An error for which maintenance is difficult is an error for which it is necessary to contact a service center, for example, and which cannot be caused to be recovered from by an ordinary user. In the present embodiment, as the fatal error, a waste ink tank full, a printing unit high temperature error, a power source error, and other errors for which maintenance is difficult can be identified. The mobile terminal 30 can identify and notify that a fatal error occurred on the MFP 200 based on the fatal error. For example, the MFP can notify to the mobile terminal 30 that is executing a job that it is not a usage target.

[0078] Here, Tx transmits when broadcasting an advertising signal, but in the present embodiment, if an error occurs on the MFP 200, the power source of the reception circuit is kept off, and a response from a communication partner to the advertising signal is not awaited. Specifically, as illustrated in FIG. 5C, the Rx 509 is eliminated in each channel (channel A-channel C), and only a Tx 512, a Tx 513, and a Tx 514 are executed. With this, while configuration is such that the mobile terminal 30 can identify that the MFP 200 cannot execute printing, it is possible to suppress the power consumption of the MFP 200, and realize power saving. That is, it is possible to reduce the power for turning on the power source of the reception circuit. In the present embodiment, if the fatal error 626 is in the error information 607, Rx is not executed. This is because there is no meaning in receiving a response from the mobile terminal 30 in a case where a fatal error occurs even considering from the side of management of the MFP 200. Note that in cases of the job error 624, the recoverable error 625 or the like, and not just the fatal error 626, configuration may be taken so as to not execute Rx because a job cannot be executed until the error is cancelled.

[0079] In this way, the mobile terminal 30 can identify a current state of the MFP 200 by receiving an advertisement packet in which information of the capability information 605, the setting information 606, the error information 607 or the like of the MFP 200 is stored.

[0080] Note that the configurations illustrated in FIGS. 5A to 5C are only examples, and it is possible to store arbitrary data in an advertisement packet and broadcast it outside of the content illustrated in FIGS. 5A to 5C. For example, it is possible to arrange the NEXT Flag 627 illustrated in FIG. 6A. The NEXT Flag 627 represents broadcasting information that could not be fully stored in the advertisement packet of this time in a subsequent advertisement packet. Also, information such as a bit that represents a mode for transmitting an arbitrary

character string, or the like, and not just that of a predetermined format may be arranged.

[0081] FIG. 7 is a view for illustrating a processing sequence between the mobile terminal 30 and the MFP 200 from advertising to job reception to job completion.

[0082] In FIG. 7, the mobile terminal 30 is an initiator that stands by for an advertisement packet from an advertiser in the periphery. Here, the MFP 200 is an advertiser that executes an advertising event of transmitting an advertisement packet in the advertising interval 504. Here, the set of the Tx 508 and the Rx 509 illustrated in FIG. 5A correspond to advertising (step S701-step S703). By the mobile terminal 30 receiving the advertisement packet (FIG. 6A) from the MFP 200, the mobile terminal 30 can identify capabilities and an error state of the MFP 200.

[0083] If one of the MFP 200 that is suitable for executing the job exists, the mobile terminal 30 transmits CONNECT REQ which is a request for transitioning to a connection event for making a network connection (step S704). When the MFP 200 receives CONNECT REQ, it makes preparations to transition to the connection event. By the BLE unit 318 and the BLE unit 718 notifying LE Connection Complete to the main board 301 and the main board 701 respectively, the mobile terminal 30 and the MFP 200 change to master and slave respectively (step S705 and step S706).

[0084] After transitioning to the connection event, the slave MFP 200 establishes a connection with the mobile terminal 30 which is the master. Note that in the BLE standard, the master can form a star-type topology with slaves [1: many].

[0085] The MFP 200, after changing to slave, does not broadcast advertisement packets to the mobile terminal 30. For this reason, mobile terminals in the periphery other than the mobile terminal 30 that established the connection with the MFP 200 cannot identify information regarding the MFP 200 via advertising. In contrast to this, in the present embodiment, the mobile terminal 30, by receiving an advertisement packet, can identify capabilities and an error state of the MFP 200 prior to establishing a connection with the MFP 200. Accordingly, it is possible to suppress the mobile terminal 30 establishing a connection with an MFP 200 that cannot execute the job, and it is possible for other terminal devices to identify via advertising information relating to the MFP 200.

[0086] In the mobile terminal 30, the main board 701 transmits job data of a print job to the BLE unit 718 (step S707). For the job data here, a print job main body in which image data is embedded may be transmitted, and information of a pointer to a print job may be notified. The BLE unit 718 of the mobile terminal 30 transmits job data of a print job to the BLE unit 318 (step S708). Note, in this embodiment, if pointer information (job information) is transmitted, job data of the print job is transmitted to the BLE unit 318 thereafter, but limitation is not made to this. Configuration may be taken such that the print job main body is transmitted by communication means other than BLE, and configuration may be taken such that, for example, it is transmitted using the WLAN unit 316 which can communicate in a wider range than BLE. In the present embodiment, the print job main body or pointer information is transmitted as information relating to the job.

[0087] In the MFP 200, the BLE unit 318 transmits to the main board 301 received job data (step S709). The main board 301 notifies job completion to the BLE unit 318 when it receives the job data (step S710). The timing of notification of job completion may be after the operation of the job com-

pletes, or may be the timing at which the reception of job data ends, or may be the timing at which the pointer to the job is notified. Note that if the pointer to the job is notified, for example, the actual data of the job may be obtained using the WLAN unit 316.

[0088] In the MFP 200, the BLE unit 318 notifies the received job completion to the BLE unit 718 of the mobile terminal 30 (step S711). The BLE unit 718 notifies the received job completion to the main board 701 (step S712).

[0089] After that, the mobile terminal 30 and the MFP 200 respectively return to initiator and advertiser, and the MFP 200 resumes advertising (step S713).

[0090] As explained using the sequence of FIG. 7, when the connection event is transitioned to, the advertiser ceases to be able to broadcast advertisement packets. For this reason, the less the connection event occurs, the more mobile terminals in the periphery other than the mobile terminal 30 that established the connection event with the advertiser can receive advertisement packets from the advertiser. Compared to cases in which information relating to the MFP 200 is received after transitioning to the connection event as is conventional, it is possible to notify information relating to the MFP 200 to the mobile terminal only with an advertisement packet broadcast before the connection event. Accordingly, the MFP 200 and the mobile terminal 30 respectively can suppress electric power consumption due to the establishment of the connection in cases where the print job cannot be executed, and the number of steps for cancellation after connecting can be reduced. Also, if there exists a plurality of the mobile terminal 30 in the effective communication range of the MFP 200, it is possible for all of the mobile terminals 30 in the effective communication range to identify a state of the MFP 200 without establishing a connection with the MFP 200.

[0091] Using FIGS. 8A and 8B, explanation is given of an example of transmitting a job after searching for the MFP 200 from the mobile terminal 30. FIGS. 8A and 8B are an example of display screens displayed in the display unit 311 of the mobile terminal 30.

[0092] The mobile terminal 30, for power consumption reduction, is not put in a state in which it can receive BLE advertisement packets continuously. If a user is trying to print, that is if the user is trying to transmit a print job from the mobile terminal 30, the user activates a predetermined application on the mobile terminal 30. The predetermined application displays an application screen illustrated in FIG. 8A on the display unit 311. This predetermined application has a function of searching for an MFP meeting a desired condition. In the present embodiment, the application screen that the application displays on the mobile terminal 30 has check-boxes for a print mode ("color"), sheet size ("A4 size or greater"), and printing speed ("15 PPM or greater" (the number of sheets that can be printed in one minute)) as conditions for searching for the MFP.

[0093] For example, in the case where a print job is an A4 size and there are a large number of sheets, the user instructs the search after having checked the check-boxes for "A4 size or greater" and printing speed of "15 PPM or greater". With this, the BLE unit 718 of the mobile terminal 30 activates, and a state in which advertisement packets in the periphery can be received is set.

[0094] Then, the mobile terminal 30 identifies the state of the MFP 200 in the periphery based on the capability information 605, the setting information 606, and the error information 607 when it receives an advertisement packet. Then,

as is illustrated in FIG. 8B, a notification screen indicating that MFPs were found is displayed in the display unit 311. Here, the found MFP names, respective statuses, approximate distances from the mobile terminal 30, and a connection button 801 for instructing a connection in a case where the MFP 200 is connected are displayed. In this way, in the present embodiment, the mobile terminal 30 can confirm states of a plurality of the MFP 200 by the advertisement packets.

[0095] The CPU 702 of the mobile terminal 30, as described above, can identify a state of the found MFPs by analyzing the received advertisement packets. The mobile terminal 30 may be configured to cause the display as illustrated in FIG. 8B to change based on the identified results. For example, because the printer A has a paper jam error, it cannot execute a print job even if it is connected to, and so configuration is such that the connection button 801 is not displayed. Note that the connection button 801 may be grayed out, or displayed so that it cannot be selected.

[0096] By pressing the connection button 801, it is possible to execute a print job by transitioning to a sequence from step S704 of FIG. 7. In this way, the mobile terminal 30 that executes the print job can transmit a print job having filtered out the MFPs that satisfy the condition from out of the MFPs in the periphery. Because the connection event is not transitioned to when filtering out the MFPs that satisfy the condition from out of the MFPs in the periphery, the reception of advertisement packets by other mobile terminals is not impeded.

[0097] FIG. 9 is a flowchart for illustrating advertisement packet transmission processing. Note that processing that this flowchart illustrates is realized by the CPU 302 of the MFP 200 reading and executing a program stored in the ROM 303.

[0098] In step S902, the CPU 302 performs preparation for broadcasting an advertisement packet. Here, data necessary for generating the payload 602 is obtained from the main board 301. When the advertisement packet is generated, the CPU 302, in step S903, broadcasts the advertisement packet via the BLE unit 318.

[0099] In step S904, the CPU 302 determines whether or not there is an error in the MFP 200. This error is the job error 624, the recoverable error 625, or the fatal error 626 of FIG. 6D, for example. If the result of the determination is that there is an error (YES in step S904), the CPU 302, in step S905, determines whether or not the error that occurs is an error for which there is a possibility that it will be cancelled by notifying the user. In the case in which the job error 624 or the recoverable error 625 occur, there is a possibility that the user will perform a recovery operation if the content thereof is notified. Accordingly, in the case of these errors, it is determined that the error has a possibility of being cancelled by notification of the user. On the other hand, in the case where the fatal error 626 occurs, it is determined that the error does not have the possibility of being cancelled by notification of the user because the user cannot resolve the error.

[0100] If the result of the determination is that the error has the possibility of being cancelled by notification of the user (YES in step S905), the CPU 302, in step S906, executes the Rx 509 as in FIG. 5A. Meanwhile, if the result of the determination is that the error does not have the possibility of being cancelled by notification of the user (NO in step S905), the CPU 302, in step S907, does not execute the Rx 509 as in FIG. 5C. In other words, the execution of the Rx 509 is prohibited. By controlling in this way, it is possible to suppress the power

consumption by omitting Rx when an error that the user cannot resolve occurs. Also, it is possible to explicitly notify the user that the MFP cannot be used.

[0101] In step S908, the CPU 302 determines whether or not there is data that does not fit in the advertisement packet of this time. If there is data that does not fit in the advertisement packet (YES in step S908), the processing returns to step S902, and the CPU 302 transmits a subsequent advertisement packet using the NEXT Flag 627. Specifically, as is illustrated in FIG. 5B, as the advertisement packet, transmission is divided over Tx 1 (510) and Tx 2 (511) which are consecutive and are associated by the NEXT Flag 627. By configuring in this way, even in the case of additional information, advertising is performed divided over a plurality of times, and the influence on mobile terminals in the periphery is low compared to in the case where the connection event is performed.

[0102] Meanwhile, if the data does not fit in the advertisement packet (NO in step S908), the CPU 302, in step S909, determines whether or not there is an advertising interrupt instruction. If there is no interrupt instruction (NO in step S909), the processing returns to step S903. On the other hand, if there is an interrupt instruction (YES in step S909), processing terminates.

[0103] As explained above, by the first embodiment, the mobile terminal 30, by receiving an advertisement packet, can identify capabilities and an error state of the MFP 200 prior to establishing a connection with the MFP 200. Accordingly, it is possible to suppress the mobile terminal 30 establishing of a connection with one of the MFP 200 that cannot execute the job, and it is possible for other terminal devices to identify via advertising information relating to the MFP 200. With this it is possible to suppress the mobile terminal establishing unnecessary connections to image processing apparatuses, and it is possible to make the time in which the mobile terminal establishes a connection with the image processing apparatus shorter. For this reason, when a plurality of mobile terminal users are using an image processing apparatus, the existence of the image processing apparatus becomes easier to recognize.

#### Second Embodiment

[0104] In the second embodiment, explanation is given for an example in which the power source that drives the BLE unit 318 is switched. When an event such as an error occurs in the MFP 200, there are cases in which the power source cannot be input. At that time, if the BLE unit 318 is operating in the main body power source 408, an advertisement packet cannot be broadcast. In the present embodiment, if an event such as an error occurs and the power source cannot be input, the battery 406 is switched to so that it is possible to broadcast advertisement packets. The BLE unit 318 may be implemented to be able to run for several months by a button battery in order to have very low power consumption. By configuring in this way, even if the power source is not input to the MFP 200, a state of the MFP 200 can be notified to the mobile terminal 30. Also, configuration may be taken such that a battery is driven so as to inactivate the power source of the main board 301 or the main body power source 408 for power saving and not just in cases of errors.

[0105] Here, for the determination to switch to the battery 406, for example when the microcomputer 403 of the BLE unit 318 monitors a state of the MFP 200, the power source is switched from the main body power source 408 to the battery 406 if a predetermined event occurs.

#### Other Embodiments

[0106] In the above described embodiments, as information of the image processing apparatus, it is assumed that capability information, setting information, and error information is included as an advertisement packet, but limitation is not made to this, and it is possible to configure to have one or more of these pieces of information. Also, it is possible to have other information. For example, if advertisement packets only include the capability information, a mobile apparatus can identify an image processing apparatus that does not have a capability for executing a print job.

[0107] Also, in the above described embodiments, explanation was given for an example of a print job as a job that is a processing target, but limitation is not made to this. For example, the MFP 200 may function as a network scanner, an Internet facsimile or the like. For this reason, it is possible to broadcast advertisement packets including information related to these functions (capability information or the like), and to receive various types of jobs such as scan jobs.

[0108] In the above described embodiment, if a particular error occurs, the reception circuit power source is kept off, and a response from a communication partner to an advertising signal is not awaited, but limitation is not made to this. In other words, configuration may be taken such that the reception circuit is on in the standby section even if a particular error occurs.

[0109] Embodiment(s) of the present invention can also be realized by a computer of a system or apparatus that reads out and executes computer executable instructions (e.g., one or more programs) recorded on a storage medium (which may also be referred to more fully as a 'non-transitory computer-readable storage medium') to perform the functions of one or more of the above-described embodiment(s) and/or that includes one or more circuits (e.g., application specific integrated circuit (ASIC)) for performing the functions of one or more of the above-described embodiment(s), and by a method performed by the computer of the system or apparatus by, for example, reading out and executing the computer executable instructions from the storage medium to perform the functions of one or more of the above-described embodiment(s) and/or controlling the one or more circuits to perform the functions of one or more of the above-described embodiment(s). The computer may comprise one or more processors (e.g., central processing unit (CPU), micro processing unit (MPU)) and may include a network of separate computers or separate processors to read out and execute the computer executable instructions. The computer executable instructions may be provided to the computer, for example, from a network or the storage medium. The storage medium may include, for example, one or more of a hard disk, a random-access memory (RAM), a read only memory (ROM), a storage of distributed computing systems, an optical disk (such as a compact disc (CD), digital versatile disc (DVD), or Blu-ray Disc (BD)<sup>TM</sup>), a flash memory device, a memory card, and the like.

[0110] While the present invention has been described with reference to exemplary embodiments, it is to be understood that the invention is not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

[0111] This application claims the benefit of Japanese Patent Application No. 2015-026970, filed Feb. 13, 2015, which is hereby incorporated by reference herein in its entirety.

What is claimed is:

1. An apparatus that executes a job, the apparatus comprising:

a broadcast unit configured to broadcast a wireless signal prior to establishing a connection by wireless communication with an external apparatus, wherein the wireless signal includes information relating to the apparatus, by which it can be identified whether execution of a job by the apparatus is possible, in a predetermined packet.

2. The apparatus according to claim 1, wherein the information relating to the apparatus includes at least one of information relating to a state of the apparatus, and information relating to a capability of the apparatus.

3. The apparatus according to claim 2, wherein the information relating to the capability includes capability information representing a capability of the apparatus.

4. The apparatus according to claim 2, wherein the information relating to the state includes setting information representing a setting state of the apparatus.

5. The apparatus according to claim 2, wherein the information relating to the state includes error information representing an error state of the apparatus.

6. The apparatus according to claim 1, wherein based on a response to the wireless signal a network connection is established with an external apparatus by the wireless communication.

7. The apparatus according to claim 1, further comprising a switching unit configured to switch a receiving unit to a state in which the receiving unit can receive from an external apparatus a response to the wireless signal broadcast by the broadcast unit, wherein

if the apparatus is in an error state, the switching unit does not switch to the state in which the response to the wireless signal can be received from the external apparatus.

8. The apparatus according to claim 7, wherein if there is a possibility that the error state will be cancelled by notifying the error state to an external apparatus, the switching unit switches to the state in which the response to the predetermined packet can be received from the external apparatus.

9. The apparatus according to claim 7, wherein the switching unit, after switching to the state in which the response to the wireless signal can be received from the external apparatus, switches to a state in which the response to the wireless signal cannot be received from the external apparatus after a predetermined amount of time elapses.

10. The apparatus according to claim 1, wherein if a capacity of the information which is broadcasted by the broadcast unit and is relating to the apparatus is larger than a predetermined packet capacity, the information relating to the apparatus is divided and broadcasted.

11. The apparatus according to claim 1, further comprising a control unit configured to, if the apparatus is in a predetermined state, execute the broadcasting by the broad-

cast unit after switching from a power from a main body power source of the apparatus to a power from a storage battery.

12. The apparatus according to claim 1 wherein the wireless signal broadcasted by the broadcast unit includes information of a signal strength by which a distance between the external apparatus and the apparatus can be identified.

13. The apparatus according to claim 1, wherein the wireless communication is in compliance with a BLE standard.

14. An apparatus that executes a job, the apparatus comprising:

a determination unit configured to determine whether an error occurs in the apparatus;

a broadcast unit configured to broadcast a wireless signal prior to establishing a connection by wireless communication with an external apparatus; and

a switching unit configured to switch a receiving unit to a state in which the receiving unit can receive from an external apparatus a response to the wireless signal broadcast by the broadcast unit, wherein

if it is determined by the determination unit that an error occurs, the switching unit does not switch the receiving unit to the state in which the receiving unit can receive from the external apparatus the response to the wireless signal.

15. A method of controlling an apparatus, the method comprising:

executing a job; and

broadcasting a wireless signal prior to establishing a connection by wireless communication with an external apparatus, wherein

the wireless signal includes information relating to the apparatus, by which it can be identified whether execution of a job by the apparatus is possible, in a predetermined packet.

16. A method of controlling an apparatus comprising:

executing a job; and

determining whether an error occurs in the apparatus;

broadcasting a wireless signal prior to establishing a connection by wireless communication with an external apparatus; and

switching a receiving unit to a state in which the receiving unit can receive from an external apparatus a response to the wireless signal, wherein

if it is determined that an error occurs, the receiving unit is not switched to the state in which the receiving unit can receive from the external apparatus the response to the wireless signal.

17. A non-transitory computer-readable storage medium storing a program for causing a computer to function as an apparatus, wherein

the program causes the computer to function as an executing unit configured to execute a job; and

a broadcast unit configured to broadcast a wireless signal, including information relating to the apparatus, by which it can be identified whether execution of a job by the apparatus is possible, in a predetermined packet, prior to establishing a connection by wireless communication with an external apparatus.

\* \* \* \* \*