



(51) International Patent Classification:

A61B 17/00 (2006.01) *A61B 18/12* (2006.01)
A61B 17/32 (2006.01) *A61B 18/14* (2006.01)
A61B 18/00 (2006.01) *A61B 18/18* (2006.01)

(21) International Application Number:

PCT/US2017/027021

(22) International Filing Date:

11 April 2017 (11.04.2017)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

62/320,867 11 April 2016 (11.04.2016) US

(71) Applicant: **BUFFALO FILTER LLC** [US/US]; 5900
 Genesee Street, Lancaster, New York 14086 (US).

(72) Inventors: **PEPE, Gregory**; 26 Clermont Ct., Lancaster,
 New York 14086 (US). **MILLER, Michael J.**; 345 Ter-
 race Blvd., Apt. #2, Depew, New York 14043 (US).
SHVETSOV, Kyrlo; 345 Terrace Blvd., Apt. #1, Depew,
 New York 14043 (US). **BONANO, Samantha**; 174 Cov-
 ent Garden Lane, Williamsville, New York 14221 (US).

(74) Agents: **MENASCO, Timothy W.** et al.; 1600 Bausch &
 Lomb Place, Rochester, New York 14604-2711 (US).


(81) Designated States (unless otherwise indicated, for every
 kind of national protection available): AE, AG, AL, AM,
 AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
 BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM,
 DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
 HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KH, KN,
 KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA,
 MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG,
 NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS,
 RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY,
 TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN,
 ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
 kind of regional protection available): ARIPO (BW, GH,
 GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ,
 TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU,
 TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE,
 DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,
 LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,
 SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
 GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: ELECTROSURGICAL DEVICE WITH VACUUM PORT



(57) Abstract: Presented are a method and apparatus for surgical procedures. An exemplary apparatus includes a body having a longitudinal axis and a connection opening at a first end of the longitudinal axis, the connection opening including an electrical connection to an electrical circuit maintained within the body and an air path extending through the longitudinal axis of the body. The apparatus further includes a tube assembly having a distal end and a mating end along a tube longitudinal axis, the tube assembly having a vacuum inlet circumscribing an electrode extending from the distal end, the vacuum inlet operable for receiving surgical smoke, the vacuum inlet fluidly connected to an air tube extending through the tube longitudinal axis, the mating end operable to be removably affixed to the connection opening thereby connecting the electrode with the electrical connection and the air path with the air tube, and a first button.

ELECTROSURGICAL DEVICE WITH VACUUM PORT

PRIORITY CLAIMS TO PRIOR APPLICATIONS

[0001] This patent application claims priority to pending US Provisional Patent Application No. 62/320,867 filed April 11, 2016, the contents of which are incorporated herein by reference.

TECHNICAL FIELD

[0002] The present invention relates generally to smoke evacuation, and, more specifically, to an electrosurgical device with smoke evacuation during medical procedures.

BACKGROUND OF THE INVENTION

[0003] Surgical smoke and aerosol, or plume, is created in connection with surgery. For example, when laser or electrosurgical energy is delivered to a cell, heat is created. This heat vaporizes the intracellular fluid, which increases the pressure inside the cell and eventually causes the cell membrane to burst. In this example, a plume of smoke containing water vapor is released into the atmosphere of the operating room or doctor's office. At the same time, the heat created may char the protein and other organic matter within the cell, and may cause thermal necrosis in adjacent cells. The charring of cells may also release other harmful contaminants, such as carbonized cell fragments and gaseous hydrocarbons.

SUMMARY OF THE INVENTION

[0004] In view of the foregoing, it is an object of the present disclosure to provide a method and apparatus for surgical procedures.

[0005] A first exemplary embodiment of the present disclosure provides an apparatus for surgical procedures. The apparatus includes a body having a longitudinal axis and a connection opening at a first end of the longitudinal axis, the connection opening including an electrical connection to an electrical circuit maintained within the body and an air path extending through the longitudinal axis of the body. The apparatus further includes a tube assembly having a distal end and a mating end along a tube longitudinal axis, the tube assembly having a vacuum inlet circumscribing an electrode extending from the distal end, the vacuum inlet operable for receiving surgical smoke, the vacuum inlet fluidly connected to an air tube extending through the tube longitudinal axis, the mating end operable to be removably affixed to the connection opening thereby connecting the electrode with the

electrical connection and the air path with the air tube. The apparatus still further includes a first button arranged on an external surface of the body operable for controlling a current flow to the electrode at a first level.

[0006] A second exemplary embodiment of the present disclosure provides an electrosurgical device. The electrosurgical device includes a tubular body having a longitudinal axis and an electrical rod at a first end of the longitudinal axis, the electrical rod operably coupled to an electrical circuit maintained within the body, the body comprises an air path extending through the longitudinal axis. The electrosurgical device further includes a tube assembly having a distal end and a mating end along a tube longitudinal axis, the tube assembly having a vacuum inlet circumscribing an electrode extending from the distal end, the vacuum inlet operable for receiving surgical smoke, the vacuum inlet fluidly connected to an air tube extending through the tube longitudinal axis, the mating end comprising a socket operable to be removably connected to the electrical rod thereby connecting the air path with the air tube. The electrosurgical device still further includes a first button arranged on an external surface of the body operable for controlling a current flow to the electrode at a first level.

[0007] A third exemplary embodiment of the present disclosure provides a method. The method includes providing a body having a longitudinal axis and a connection opening at a first end of the longitudinal axis, the connection opening including an electrical connection to an electrical circuit maintained within the body and an air path extending through the longitudinal axis of the body. The method further includes providing a tube assembly having a distal end and a mating end along a tube longitudinal axis, the tube assembly having a vacuum inlet circumscribing an electrode extending from the distal end, the vacuum inlet operable for receiving surgical smoke, the vacuum inlet fluidly connected to an air tube extending through the tube longitudinal axis, the mating end operable to be removably affixed to the connection opening thereby connecting the electrode with the electrical connection and the air path with the air tube. The method still further includes providing a first button arranged on an external surface of the body operable for controlling a current flow to the electrode at a first level.

[0008] The following will describe embodiments of the present disclosure, but it should be appreciated that the present disclosure is not limited to the described embodiments and various modifications of the disclosure are possible without departing from the basic principle. The scope of the present disclosure is therefore to be determined solely by the appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] FIG. 1 is a perspective view of a first embodiment of the electrosurgical device of the present invention.

[0010] FIG. 2 is a cross-sectional perspective view of the device of FIG. 1.

[0011] FIG. 3 is a perspective view of an alternate embodiment of the electrosurgical device of the present invention.

[0012] FIG. 4 is a cross-sectional perspective view of the electrosurgical device of FIG. 3.

[0013] FIG. 5 is a perspective view of another alternate embodiment of the electrosurgical device of the present invention.

[0014] FIG. 6 is a perspective view of a vacuum tube extension.

[0015] FIG. 7 is a perspective view of another alternate embodiment of the electrosurgical device.

[0016] FIG. 8 is a cross-sectional perspective view of the electrosurgical device.

[0017] FIG. 9 is a front cross-sectional view of the cam locking mechanism of the device of FIG. 7.

[0018] FIG. 10 is a perspective view of the device of FIG. 7 shown in the locked position.

[0019] FIG. 11 is a perspective view of the device of FIG. 7 shown in the unlocked position.

[0020] FIG. 12 is a perspective view of another alternate embodiment of the electrosurgical device.

[0021] FIG. 13 is a cross-sectional perspective view of the device of FIG. 12.

[0022] FIG. 14 is a perspective view of the device of FIG. 12 shown in the locked position.

[0023] FIG. 15 is a perspective view of the device of FIG. 12 shown in the unlocked position.

DETAILED DESCRIPTION

[0024] At the outset, it should be clearly understood that like reference numerals are intended to identify the same structural elements, portions or surfaces consistently throughout the several drawing figures, as such elements, portions or surfaces may be further described or explained by the entire written specification, of which this detailed description is an integral part. Unless otherwise indicated, the drawings are intended to be read (*e.g.*, cross-hatching, arrangement of parts, proportion, debris, etc.) together with the specification, and

are to be considered a portion of the entire written description of this invention. As used in the following description, the terms "horizontal", "vertical", "left", "right", "up" and "down", as well as adjectival and adverbial derivatives thereof, (*e.g.*, "horizontally", "rightwardly", "upwardly", etc.), simply refer to the orientation of the illustrated structure as the particular drawing figure faces the reader. Similarly, the terms "inwardly" and "outwardly" generally refer to the orientation of a surface relative to its axis of elongation, or of rotation, as appropriate.

[0025] Referring now to the drawings, and more particularly to FIG. 1 thereof, this invention provides an electrosurgical pen 20 having a body 23. The body 23 may be ergonomically shaped to be received by a user's hand. The body 23 may be pencil shaped and may have a longitudinal axis 24. At the left hand side of the body 23, a threaded opening 25 may receive interchangeable tube assemblies 27 and 28. In FIG. 1, the shorter tube assembly 27 is attached to the body 23. The longer tube assembly 28 is shown separated from the body 23. The tube assemblies 27, 28 have different lengths which may be suitable depending on the surgical site or the preference of the user. The interchangeable tube assemblies change the overall reach of the electrode 26 and the air suction. Various length extensions may be available for each electrosurgical device 20 and each tube assembly may have a built in electrode 26 or the ability to swap the electrode 26, based on the preference of the user. The tube assemblies 27, 28 may surround an electrode 26. The electrode 26 may have a uninsulated end portion 30 (FIG. 2), insulated portion 31 (FIG. 2), and a mounting portion 32 (FIG. 2). At the end of the tube 28, a threaded portion 33 provides a mating surface for engaging with the threaded opening 25 on the body 23. In this manner the tube assemblies 27, 28 may be interchanged. The distal ends 35, 36 of the vacuum tube assemblies 27, 28 comprise inlets 38, 39 for receiving surgical smoke when using the pen 20.

[0026] The device 20 may be provided with a first button 41 arranged on the external surface 44 of the body 23. The first button 41 may control the current flow to the device at a first level. The device 20 may have a second button 47 for controlling a current flow at a second level to the electrode 26. The current may be provided at different levels depending on the application. For cutting, a higher current level is required, whereas, coagulation requires less current.

[0027] Additional buttons may be added for controlling the vacuum source, a light source or the like.

[0028] There may be many different lengths for the tubing. Also, the tube may be connected in other ways such as by a mechanical lock or an interference fit.

[0029] Turning to FIG. 2, the tube assembly 28 may be removably attached to the body 23 by means of the threaded connection 33. An electrical connection between the printed circuit board and the electrode 26 may be made via a metal rod 56 or strip. The metal rod 56 is electrically connected to the electrode 26 and makes electrical contact with the printed circuit board when the tube assembly 28 is inserted into the end of the body 23. The tube assembly 28 is attached to the body 23 by rotating the tube assembly 28 to engage the threaded connection 33 with the threaded opening 25 at the end of the body 23. As shown, there is an electrode holder 50 that is electrically connected to the printed circuit board to provide power to the electrode 26. The electrode 26 may be received by a metal sleeve connector 53 that is connected to a conductive rod 56. The conductive rod 56 goes into the electrode holder 50 to make the electrical contact with the printed circuit board. The electrode 26 may have an uninsulated end portion 30, an insulated portion 31 and a mounting portion 32 that engages with the metal sleeve connector. The insulated portion 31 may be provided in applications where the user may have a need to remove the electrode 26 and replace it with a different electrode 26.

[0030] The tube assembly 28 has a passageway around the electrode 26 for air to pass into the body 23 where it is in fluid communication with an air channel 60 disposed inside the body 23. The body 23 may be provided with a swivel connection 63. The swivel connection 63 may lead to the vacuum source.

[0031] In an alternate embodiment shown in FIGS. 3-4, an electrosurgical device 120 may utilize a metal contact in order to secure a tube assembly 127 to the body 123 of the electrosurgical device 120. A connecting metal rod 156 (FIG. 4) or strip may span from the electrode 126 in the tube assembly 127 to a blade socket 160 disposed inside the body of the pen 120. The connection between the tube assembly 127 and the body 123 is made by inserting the metal rod 156 into the socket 160. The interface between the electrode 126 and the metal rod 156 may include a metal sleeve connector 162 and a metal rod guide 164. The end 130 of the tube assembly 127 is provided with mating surfaces and one or more alignment guides 163 to provides for correct orientation of the tube assembly 127 with the opening in the body 123. The electrical connection between the electrode 126 and the printed circuit board is made by insertion of the metal rod 156 (which is electrically connected to the electrode 126) into the socket 160 which is electrically connected to the printed circuit board

inside the body 123. A long tube 128 containing an electrode 126 is shown separated from the body 123. The mating surfaces and alignment guides 163 are shown on the right hand side of the tube assembly 128. The tube 28 has a passageway for air that is disposed in fluid communication with an air channel 166 disposed in the body 123 of the electrosurgical device 120. The electrosurgical device 123 may also be provided with a swivel connector 169.

[0032] In another alternate embodiment shown in FIG. 5, an electrosurgical device 220 has a body 223 with an opening 225 on the left hand side. The opening 225 has a locking pin engagement slot 229 formed therein for receiving a locking pin 233 on the end of a tube assembly 228. The tube assembly 228 receives an electrode 226 and engagement of the tube assembly 228 with the body 223 of the electrosurgical device 220 brings the electrode 226 into electrical contact with the printed circuit board inside the body 223 to connect the electrode 226 to the electrical circuit so that it can be activated by cut and coagulate buttons 241 and 247.

[0033] Turning to FIG. 6, in yet another embodiment of the invention, a tube assembly 327 may be provided with a removable air tube extension 330. The extension 330 may be connected to the end of the tube assembly 327 by means of an interference fit. The extension 330 may also be connected to the tube assembly 327 by means of a mechanical lock. The extension may slide back and forth on the tube 327 to reveal or to hide the electrode 326. The tube assembly 327 is connected to the body 323 of the electrosurgical device 320.

[0034] In FIG. 7, another alternate embodiment is shown. As an alternative to the interchangeable tube assemblies, an electrosurgical device 420 includes a telescoping air tube assembly 427 that surrounds an electrode 426. The electrode 426 is mounted on the tube assembly 427 such that movement of the tube assembly also moves the electrode 426 as described below. The tube 427 is received inside the body 423 of the electrosurgical device 420 and may be locked into position by a cam as shown in FIG. 8. The cam may be activated by a twist lock grip 440 disposed at the front of the body 423. The twist lock grip 440 may have ribs 445 disposed thereon to provide for a gripping area for the user.

[0035] The electrosurgical device 420 may include buttons 441 and 447 for cutting and coagulating. And the body 423 may include a swivel connector 463 that leads to a vacuum source.

[0036] Turning to FIG. 8, the tube 427 extends into a channel 450 inside the body 423 and provides an air pathway disposed in fluid communication with an opening inside the swivel 463 that leads to the vacuum source. The electrode 426 may be disposed inside a blade holder 455. The blade holder 455 is electrically conductive and engages with the end of the electrode 426. The blade holder 455 is electrically connected to the printed circuit board inside the body 423 such that the electrode 426 may be energized by the cut and coagulate buttons when the electrode 426 is disposed in the blade holder 455. Rotation of the twist lock grip 440 actuates a cam locking mechanism 460 (FIG. 9) which provides a frictional engagement between the tube 427 and a cam 469 to prevent the tube 427 from sliding relative to the body 423.

[0037] In FIG. 9, the workings of the cam locking mechanism 460 are shown in detail. The cam 469 has an eccentric shape that pivots around a cam lock pivot point 472. Rotation of the cam 469 counterclockwise unlocks the tube 427 (FIG. 11) so that it can be moved relative to the body 423. Rotation of the cam 469 clockwise into the position shown in FIG. 10 causes the cam 469 to engage with the tube 427 to lock it in position. The twist lock grip 440 has a guide pin 470 projecting from an inner surface. The guide pin 470 engages with a slot 473 in the top of the cam 469 such that movement of the twist lock grip 440 from side to side causes rotation of the cam 469 about its pivot point 472. The cam mechanism may be mirrored in the vertical or horizontal direction to provide similar locking properties with actuation in different directions or the cam being on the bottom of the device.

[0038] Turning to FIG. 12, an alternate embodiment for the telescoping tube arrangement of FIGS. 9-10 is shown. Electrosurgical device 520 includes a lever lock 530 that provides for locking and unlocking the tube assembly 527. The lever lock 530 is pivotally attached to the end of the body 523 and pivots about a hinge 524 (FIG. 13). The body 523 may be provided with a swivel 563 at the opposite end that may be connected to the vacuum source. As shown in FIG. 13, the tube 527 is disposed inside a cavity 550 in the body 523 and slides into and out of the cavity 550 to vary the length of the tube 527 extending from the body 523. The electrode 526 may be disposed in the center of the tube 527 in a blade holder 560. The blade holder 560 receives the end of the electrode 526 and makes an electrical connection. The blade holder 560 is constructed of a conductive material and is disposed in electrical communication with the printed circuit board such that insertion of the electrode 526 into the blade holder 560 provides for energizing of the electrode 526 by means of the cut and coagulation buttons 541 and 547. The lever lock 530 pivots about hinge 524. When the lever

530 is pushed downward relative to the body 523, the portion of the lever 530 below the hinge 524 creates interference and engages with the surface of the tube 527 such that the tube 527 is disposed in an unlocked position (FIG. 15). When the lever 530 is raised upward away from the body 523, the portion of the lever 530 below the hinge 524 rotates away from interference with the surface of the tube 527 and the tube 527 may be moved relative to the body 523. The lever mechanism may be present on either side of the device 520 or on the bottom of the device 520. Also, the lever mechanism may be disposed toward the back of the device instead of the front.

[0039] Each of the above embodiments may be provided with the following additional features. The electrode may be disposed in the center of the air channel pathway inside the vacuum tube. The electrode may be disposed in the top or bottom of the air channel pathway inside the vacuum tube. The electrode may be disposed in the wall of the air channel pathway. This arrangement may split the air channel so that half of the electrode is located within the air channel while the other half of the electrode is outside of the air channel. The vacuum tube may have various "cut" angles on its distal end in order to improve performance. The inlet of the vacuum tube may be angled such that inlet is parallel to the line of sight of the user when the device is in use. Also, overmold or rubberized features may be added to the body of the electrosurgical devices to improve grip and comfort. The buttons may have various configurations including different shapes, a rocker switch, different colors or an overmold. The body of the device may be illuminated to help the user see the buttons or other features of the pen. This may be accomplished via an exposed light source or through a clear air tube which would act as a light tube. The light source may be electrically powered or made possible with photoluminescent paint. In addition, the device may include a caddy for extra electrodes or tubes. This holder may attach to the pen, the hose, or may be detached to affix onto somewhere in the surgical theater.

[0040] The present invention contemplates that many changes and modifications may be made. Therefore, while the presently-preferred form of the electrosurgical device has been shown and described, and several modifications and alternatives discussed, persons skilled in this art will readily appreciate that various additional changes and modifications may be made without departing from the spirit of the invention, as defined and differentiated by the following claims.

CLAIMS

1. An apparatus for surgical procedures, the apparatus comprising:

a body having a longitudinal axis and a connection opening at a first end of the longitudinal axis, the connection opening including an electrical connection to an electrical circuit maintained within the body and an air path extending through the longitudinal axis of the body;

a tube assembly having a distal end and a mating end along a tube longitudinal axis, the tube assembly having a vacuum inlet circumscribing an electrode extending from the distal end, the vacuum inlet operable for receiving surgical smoke, the vacuum inlet fluidly connected to an air tube extending through the tube longitudinal axis, the mating end operable to be removably affixed to the connection opening thereby connecting the electrode with the electrical connection and the air path with the air tube; and

a first button arranged on an external surface of the body operable for controlling a current flow to the electrode at a first level.

2. The apparatus according to claim 1, the apparatus further comprising a second button arranged on the external surface of the body operable for controlling the current flow to the electrode at a second level, wherein the second level is greater than the first level.

3. The apparatus according to claim 1, the electrode comprises metal rod or strip for connecting to the electrical connection.

4. The apparatus according to claim 1, wherein the connection opening is one of a threaded connection, a mechanical lock and an interference fit.

5. The apparatus according to claim 1, the body further comprising a swivel connection operably coupled to the air path, the swivel connection operable for connecting to a vacuum source operable for pulling air through the air path and the air tube.

6. The apparatus according to claim 1, wherein the vacuum inlet is angled parallel to a line of sight of a user.
7. The apparatus according to claim 1, the apparatus further comprising a light source operable to illuminate the body and the first button.
8. The apparatus according to claim 1, the apparatus further comprising a rotatable cam located on the connection opening, the rotatable cam operable to pivot to a locked position and an unlocked position, the mating end comprising an engaging surface operable to rotate the cam to the locked position and the unlocked position.
9. The apparatus according to claim 1, the apparatus further comprising a lever pivotally affixed to the body, the lever operable to pivot to and from an interference position engaging the tube assembly and an open position.
10. An electrosurgical device, the electrosurgical device comprising:
 - a tubular body having a longitudinal axis and an electrical rod at a first end of the longitudinal axis, the electrical rod operably coupled to an electrical circuit maintained within the body, the body comprises an air path extending through the longitudinal axis;
 - a tube assembly having a distal end and a mating end along a tube longitudinal axis, the tube assembly having a vacuum inlet circumscribing an electrode extending from the distal end, the vacuum inlet operable for receiving surgical smoke, the vacuum inlet fluidly connected to an air tube extending through the tube longitudinal axis, the mating end comprising a socket operable to be removably connected to the electrical rod thereby connecting the air path with the air tube; and
 - a first button arranged on an external surface of the body operable for controlling a current flow to the electrode at a first level.

11. The electrosurgical device according to claim 10, the tube assembly further comprising at least one alignment guide extending from the mating end operable to interface with corresponding mating surfaces on the tubular body.
12. The electrosurgical device according to claim 10, the body further comprising a swivel connection operably coupled to the air path, the swivel connection operable for connecting to a vacuum source operable for pulling air through the air path and the air tube.
13. The electrosurgical device according to claim 11, wherein the at least one alignment guide and the corresponding mating surfaces provide a correct orientation of the tubular body relative to the tube assembly.
14. The electrosurgical device according to claim 10, the electrosurgical device further comprising a removable air tube extension operable to be slidably coupled to the distal end of the tube assembly.
15. The electrosurgical device according to claim 10, wherein the electrode with the distal end of the tubular assembly is moveably extendable relative the body along the tubular longitudinal axis.
16. A method comprising:
 - (a) providing a body having a longitudinal axis and a connection opening at a first end of the longitudinal axis, the connection opening including an electrical connection to an electrical circuit maintained within the body and an air path extending through the longitudinal axis of the body;
 - (b) providing a tube assembly having a distal end and a mating end along a tube longitudinal axis, the tube assembly having a vacuum inlet circumscribing an electrode extending from the distal end, the vacuum inlet operable for receiving surgical smoke, the vacuum inlet fluidly connected to an air tube extending through the tube longitudinal axis, the

mating end operable to be removably affixed to the connection opening thereby connecting the electrode with the electrical connection and the air path with the air tube; and


(c) providing a first button arranged on an external surface of the body operable for controlling a current flow to the electrode at a first level.


17. The method according to claim 16, the method further comprising providing a second button arranged on the external surface of the body operable for controlling the current flow to the electrode at a second level, wherein the second level is greater than the first level.


18. The method according to claim 16, wherein the connection opening is one of a threaded connection, a mechanical lock and an interference fit.

19. The method according to claim 16, the body further comprising a swivel connection operably coupled to the air path, the swivel connection operable for connecting to a vacuum source operable for pulling air through the air path and the air tube.

20. The method according to claim 16, wherein the vacuum inlet is angled parallel to a line of sight of a user.














FIG. 4















FIG. 9



11/13







Fig. 14

Fig. 15



INTERNATIONAL SEARCH REPORT

International application No.

PCT/US2017/027021

A. CLASSIFICATION OF SUBJECT MATTER

IPC(8) - A61B 17/00; A61B 17/32; A61B 18/00; A61B 18/12; A61B 18/14; A61B 18/18 (2017.01)

CPC - A61B 18/00; A61B 18/14; A61B 18/1402; A61B 2018/00589; A61B 2018/00601; A61B 2218/00; A61B 2218/007; A61B 2218/008 (2017.02)

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

See Search History document

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

USPC - 606/32; 606/34; 606/41; 606/42; 606/45; 606/49; 606/50 (keyword delimited)

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

See Search History document

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 8,057,470 B2 (LEE et al) 15 November 2011 (15.11.2011) entire document	1-6, 10, 12, 15-20
---		---
Y		7-9, 11, 13, 14
Y	US 2014/0081086 A1 (SHVETSOV et al) 20 March 2014 (20.03.2014) entire document	7
Y	US 2013/0261610 A1 (LACONTE et al) 03 October 2013 (03.10.2013) entire document	8
Y	US 2011/0301578 A1 (MUNIZ-MEDINA et al) 08 December 2011 (08.12.2011) entire document	9
Y	US 2015/0335376 A1 (COVIDIEN LP) 26 November 2015 (26.11.2015) entire document	11, 13
Y	US 2011/0190768 A1 (SHVETSOV et al) 04 August 2011 (04.08.2011) entire document	14

☐ Further documents are listed in the continuation of Box C.☐ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

30 May 2017

Date of mailing of the international search report

28 JUN 2017

Name and mailing address of the ISA/US

Mail Stop PCT, Attn: ISA/US, Commissioner for Patents

P.O. Box 1450, Alexandria, VA 22313-1450

Facsimile No. 571-273-8300

Authorized officer

Blaine R. Copenheaver

PCT Helpdesk: 571-272-4300

PCT OSP: 571-272-7774