



US011369489B2

(12) **United States Patent**
Gray et al.

(10) **Patent No.:** **US 11,369,489 B2**
(45) **Date of Patent:** **Jun. 28, 2022**

(54) **DECOUPLED SPACER AND PLATE AND METHOD OF INSTALLING THE SAME**

(71) Applicant: **GLOBUS MEDICAL, INC.**, Audubon, PA (US)

(72) Inventors: **Jason Gray**, East Greenville, PA (US); **Mark Fromhold**, Phoenixville, PA (US); **Brittany Hansen**, Philadelphia, PA (US); **Mark Miccio**, Lynbrook, NY (US); **Morgan Kunkle**, Philadelphia, PA (US); **Matthew Urban**, Mont Clare, PA (US); **Jason Zappacosta**, Philadelphia, PA (US); **Noah Hansell**, King of Prussia, PA (US); **Mark Adams**, Downingtown, PA (US)

(73) Assignee: **Globus Medical, Inc.**, Audubon, PA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 309 days.

(21) Appl. No.: **16/458,467**

(22) Filed: **Jul. 1, 2019**

(65) **Prior Publication Data**

US 2019/0321199 A1 Oct. 24, 2019

Related U.S. Application Data

(63) Continuation of application No. 15/479,438, filed on Apr. 5, 2017, now Pat. No. 10,376,385.

(51) **Int. Cl.**

A61F 2/44 (2006.01)
A61F 2/46 (2006.01)
A61B 17/70 (2006.01)
A61B 17/80 (2006.01)

(52) **U.S. Cl.**

CPC **A61F 2/4611** (2013.01); **A61B 17/7059** (2013.01); **A61B 17/8042** (2013.01); **A61F 2/4455** (2013.01)

(58) **Field of Classification Search**

None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,673,630 A 6/1928 Madge
2,363,405 A 11/1944 Eichelberger
2,596,957 A 5/1952 Olson
4,599,086 A 7/1986 Doty
(Continued)

FOREIGN PATENT DOCUMENTS

FR 2727003 A1 5/1996
JP 2012-508043 A 4/2012
(Continued)

OTHER PUBLICATIONS

Guidance Document: Intervertebral Body Fusion Device, U.S. Dept. of Health and Human Services, Food and Drug Administration (Jun. 12, 2007).


(Continued)

Primary Examiner — Sameh R Boles

(57) **ABSTRACT**

Intervertebral spacer assemblies, systems, and methods thereof. A method of insertion includes inserting an intervertebral spacer and plate together using an insertion tool and, upon removal of the insertion tool, the intervertebral spacer and plate are no longer considered connected/coupled and act as separate components.

18 Claims, 60 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

4,743,256	A	5/1988	Brantigan	6,719,794	B2	4/2004	Gerber
4,955,908	A	9/1990	Frey	6,730,127	B2	5/2004	Michelson
5,002,576	A	3/1991	Fuhrmann	6,740,118	B2	5/2004	Eisermann et al.
5,364,399	A	11/1994	Lowery	6,761,738	B1	7/2004	Boyd
5,397,364	A	3/1995	Kozak	6,761,739	B2	7/2004	Shepard
5,458,641	A	10/1995	Jiminez	6,764,491	B2	7/2004	Frey
5,514,180	A	5/1996	Heggeness	6,767,369	B2	7/2004	Boyer, II
5,549,612	A	8/1996	Yapp et al.	6,776,800	B2	8/2004	Boyer, II
5,609,635	A	3/1997	Michelson	6,793,658	B2	9/2004	LeHuec
5,728,159	A	3/1998	Stroeveer	RE38,614	E	10/2004	Paul
5,741,253	A	4/1998	Michelson	6,805,714	B2	10/2004	Sutcliffe
5,814,084	A	9/1998	Grivas	6,808,585	B2	10/2004	Boyce
5,861,041	A	1/1999	Tienboon	6,827,740	B1	12/2004	Michelson
5,888,223	A	3/1999	Bray, Jr.	6,830,570	B1	12/2004	Frey
5,888,227	A	3/1999	Cottle	6,835,206	B2	12/2004	Jackson
5,899,939	A	5/1999	Boyce	6,849,093	B2	2/2005	Michelson
5,972,368	A	10/1999	Mckay	6,852,126	B2	2/2005	Ahlgren
5,989,289	A	11/1999	Coates	6,855,167	B2	2/2005	Shimp
6,025,538	A	2/2000	Yaccarino, III	6,855,169	B2	2/2005	Boyer, II
6,033,438	A	3/2000	Bianchi	6,887,272	B2	4/2005	Shinomiya
6,045,579	A	4/2000	Hochshuler	6,899,735	B2	5/2005	Coates et al.
6,066,175	A	5/2000	Henderson et al.	6,902,578	B1	6/2005	Anderson
6,096,081	A	8/2000	Grivas	6,929,662	B1	8/2005	Messerli
6,143,033	A	11/2000	Paul	6,972,019	B2	12/2005	Michelson
6,146,421	A	11/2000	Gordon	6,974,480	B2	12/2005	Messerli
6,156,037	A	12/2000	LeHuec et al.	6,986,788	B2	1/2006	Paul
6,174,311	B1	1/2001	Branch	7,001,432	B2	2/2006	Keller et al.
6,200,347	B1	3/2001	Anderson et al.	7,014,659	B2	3/2006	Boyer, II
6,206,922	B1	3/2001	Zdeblick et al.	7,018,412	B2	3/2006	Ferreira
6,206,923	B1	3/2001	Boyd	7,018,413	B2	3/2006	Krüger
6,231,610	B1	5/2001	Geisler	7,022,137	B2	4/2006	Michelson
6,235,059	B1	5/2001	Benezech	7,025,787	B2	4/2006	Bryan et al.
6,245,108	B1	6/2001	Biscup	7,044,968	B1	5/2006	Yaccarino, III et al.
6,258,089	B1	7/2001	Campbell et al.	7,044,972	B2	5/2006	Mathys
6,258,125	B1	7/2001	Paul	7,048,762	B1	5/2006	Sander
6,261,586	B1	7/2001	Mckay	7,048,765	B1	5/2006	Grooms
6,270,528	B1	8/2001	Mckay	7,060,073	B2	6/2006	Frey
6,294,187	B1	9/2001	Boyce	7,060,096	B1	6/2006	Schopf
6,342,074	B1	1/2002	Simpson	7,087,082	B2	8/2006	Paul
6,350,283	B1	2/2002	Michelson	7,087,087	B2	8/2006	Boyer, II
6,364,880	B1	4/2002	Michelson	7,112,222	B2	9/2006	Fraser
6,371,988	B1	4/2002	Pafford	7,115,146	B2	10/2006	Boyer, II
6,379,385	B1	4/2002	Kalas	7,137,997	B2	11/2006	Paul
6,383,186	B1	5/2002	Michelson	7,147,665	B1	12/2006	Bryan et al.
6,398,811	B1	6/2002	Mckay	7,153,325	B2	12/2006	Kim et al.
6,409,765	B1	6/2002	Bianchi	7,163,561	B2	1/2007	Michelson
6,432,106	B1	8/2002	Fraser	7,172,627	B2	2/2007	Fiere
6,432,436	B1	8/2002	Gertzman	7,192,447	B2	3/2007	Rhoda
6,458,158	B1	10/2002	Anderson	7,223,292	B2	5/2007	Messerli
6,468,311	B2	10/2002	Boyd	7,226,482	B2	6/2007	Messerli
6,471,724	B2	10/2002	Zdeblick	7,226,483	B2	6/2007	Gerber
6,482,233	B1	11/2002	Aebi	7,229,477	B2	6/2007	Biscup
6,511,509	B1	1/2003	Ford	7,232,464	B2	6/2007	Mathieu
6,520,993	B2	2/2003	James	7,235,105	B2	6/2007	Jackson
6,540,785	B1	4/2003	Gill et al.	7,238,203	B2	7/2007	Bagga
6,548,080	B1	4/2003	Gertzman	7,276,082	B2	10/2007	Zdeblick et al.
6,554,863	B2	4/2003	Paul	7,300,465	B2	11/2007	Paul
6,558,387	B2	5/2003	Errico	7,309,357	B2	12/2007	Kim
6,558,423	B1	5/2003	Michelson	7,309,359	B2	12/2007	Trieu
6,558,424	B2	5/2003	Thalgott	7,320,708	B1	1/2008	Bernstein
6,562,073	B2	5/2003	Foley	7,323,011	B2	1/2008	Shepard
6,579,318	B2	6/2003	Varga	7,347,873	B2	3/2008	Paul
6,610,065	B1	8/2003	Branch	7,435,262	B2	10/2008	Michelson
6,629,998	B1	10/2003	Lin	7,473,277	B2	1/2009	Boyer, II
6,632,247	B2	10/2003	Boyer, II	7,479,160	B2	1/2009	Branch
6,638,310	B2	10/2003	Lin	7,481,812	B2	1/2009	Frey
6,652,593	B2	11/2003	Boyer, II	7,491,237	B2	2/2009	Randall
6,660,038	B2	12/2003	Boyer, II	7,594,931	B2	9/2009	Louis
6,666,889	B1	12/2003	Commarmond	7,601,173	B2	10/2009	Messerli
6,666,890	B2	12/2003	Michelson	7,618,456	B2	11/2009	Mathieu
6,676,703	B2	1/2004	Biscup	7,618,460	B2	11/2009	Boyd
6,682,563	B2	1/2004	Scharf	7,637,953	B2	12/2009	Branch
6,695,882	B2	2/2004	Bianchi	7,662,184	B2	2/2010	Edwards
6,706,067	B2	3/2004	Shimp	7,662,185	B2	2/2010	Alfaro
6,709,458	B2	3/2004	Michelson	7,726,002	B2	6/2010	Shimp
				7,753,963	B2	7/2010	Boyer, II
				7,771,475	B2	8/2010	Michelson
				7,794,502	B2	9/2010	Michelson
				7,815,682	B1	10/2010	Peterson

(56)

References Cited

U.S. PATENT DOCUMENTS

7,833,271 B2 11/2010 Mitchell
 7,846,207 B2 12/2010 Lechmann
 7,850,731 B2 12/2010 Brittan
 7,862,616 B2 1/2011 Lechmann
 7,875,076 B2 1/2011 Mathieu
 7,879,103 B2 1/2011 Gertzman
 7,918,888 B2 4/2011 Hamada
 7,931,692 B2 4/2011 Sybert
 7,938,857 B2 5/2011 Garcia-bengochea
 7,967,867 B2 6/2011 Barreiro
 7,972,381 B2 7/2011 Michelson
 8,002,833 B2 8/2011 Fabris Monterumici
 8,100,976 B2 1/2012 Bray et al.
 8,105,383 B2 1/2012 Michelson
 8,114,162 B1 2/2012 Bradley
 8,273,127 B2 9/2012 Jones
 8,323,343 B2 12/2012 Michelson
 8,328,872 B2 12/2012 Duffield
 8,343,222 B2 1/2013 Cope
 8,366,776 B2 2/2013 Heinz
 8,435,300 B2 5/2013 Messerli et al.
 8,709,085 B2 4/2014 Lechmann
 8,840,667 B1 9/2014 Tumialan
 8,956,416 B2 2/2015 McCarthy
 9,180,022 B2* 11/2015 Georges A61B 17/7059
 2001/0010021 A1 7/2001 Boyd
 2002/0010511 A1 1/2002 Michelson
 2002/0016595 A1 2/2002 Michelson
 2002/0106393 A1 8/2002 Bianchi
 2002/0138143 A1 9/2002 Grooms
 2003/0045939 A1 3/2003 Casutt
 2003/0105528 A1 6/2003 Shimp et al.
 2003/0125739 A1 7/2003 Bagga et al.
 2003/0167091 A1 9/2003 Scharf
 2004/0078078 A1 4/2004 Shepard
 2004/0143270 A1 7/2004 Zucherman et al.
 2004/0143332 A1 7/2004 Krueger et al.
 2004/0172133 A1 9/2004 Gerber
 2004/0176853 A1 9/2004 Sennett et al.
 2005/0055098 A1 3/2005 Zdeblick et al.
 2005/0065607 A1 3/2005 Gross
 2005/0149192 A1 7/2005 Zucherman et al.
 2005/0149193 A1 7/2005 Zucherman et al.
 2005/0159819 A1 7/2005 McCormack et al.
 2005/0171607 A1 8/2005 Michelson
 2005/0177236 A1 8/2005 Mathieu et al.
 2005/0187625 A1 8/2005 Wolek et al.
 2005/0240267 A1 10/2005 Randall et al.
 2005/0240271 A1 10/2005 Zubok et al.
 2005/0256574 A1 11/2005 Paul et al.
 2006/0085071 A1 4/2006 Lechmann et al.
 2006/0129240 A1 6/2006 Lessar et al.
 2006/0142828 A1 6/2006 Schorr
 2006/0217809 A1 9/2006 Albert et al.
 2006/0241760 A1 10/2006 Randall
 2007/0088441 A1 4/2007 Duggal et al.
 2007/0123987 A1 5/2007 Bernstein
 2007/0135923 A1 6/2007 Peterman et al.
 2007/0162130 A1 7/2007 Rashbaum et al.
 2007/0168032 A1 7/2007 Muhanna et al.
 2007/0225806 A1 9/2007 Squires et al.
 2007/0225812 A1 9/2007 Gill
 2007/0233253 A1 10/2007 Bray et al.
 2007/0250167 A1 10/2007 Bray

2007/0255414 A1 11/2007 Melkent
 2007/0270961 A1 11/2007 Ferguson
 2008/0046090 A1 2/2008 Paul
 2008/0051890 A1 2/2008 Waugh et al.
 2008/0051907 A1 2/2008 Marik
 2008/0125865 A1 5/2008 Abdelgany
 2008/0133013 A1 6/2008 Duggal et al.
 2008/0154379 A1 6/2008 Steiner
 2008/0188940 A1 8/2008 Cohen
 2008/0249569 A1 10/2008 Waugh
 2009/0012529 A1 1/2009 Blain et al.
 2009/0024132 A1 1/2009 Blain et al.
 2009/0076608 A1 3/2009 Gordon et al.
 2009/0099661 A1 4/2009 Bhattacharya
 2009/0101582 A1 4/2009 Liu
 2009/0210062 A1 8/2009 Thalgot et al.
 2010/0057206 A1 3/2010 Duffield
 2010/0145459 A1 6/2010 McDonough
 2010/0145460 A1* 6/2010 McDonough A61B 17/7059
 623/17.16
 2010/0305704 A1 12/2010 Messerli
 2011/0087327 A1 4/2011 Lechmann
 2011/0160864 A1 6/2011 Messerli
 2011/0251689 A1 10/2011 Seifert
 2012/0078373 A1 3/2012 Gamache
 2012/0130495 A1 5/2012 Duffield
 2012/0130496 A1 5/2012 Duffield
 2012/0323330 A1 12/2012 Kuenzi
 2013/0073047 A1 3/2013 Laskowitz
 2013/0211523 A1 8/2013 Southard
 2014/0214166 A1* 7/2014 Theofilos A61F 2/4611
 623/17.16
 2015/0005879 A1 1/2015 Georges et al.
 2015/0025635 A1 1/2015 Laubert
 2016/0058564 A1 3/2016 Zappacosta et al.
 2016/0235448 A1 8/2016 Seex
 2017/0042692 A1 2/2017 Stewart et al.
 2018/0289496 A1 10/2018 Zappacosta et al.

FOREIGN PATENT DOCUMENTS

JP 2017-529910 A 10/2017
 WO 1997023175 A1 7/1997
 WO 1999063914 A1 12/1999
 WO 2005007040 A1 1/2005
 WO 2007098288 A2 8/2007
 WO 2008014258 A2 1/2008
 WO 2011019699 A2 2/2011

OTHER PUBLICATIONS

M. Spruit et al., The in vitro stabilizing effect of polyether-etherketone cages versus a titanium cage of similar design for anterior lumbar interbody fusion, 14(8) Eur. Spine J. 752, 752-758 (2005).
 P. Schleicher et al., Biomechanical comparison of two different concepts for stand alone anterior lumbar interbody fusion, 17(12) Eur. Spine J. 1757, 1757-1765 (2008).
 P.W. Pavlov et al., Anterior lumbar interbody fusion with threaded fusion cages and autologous bone grafts, 9 Eur. Spine J. 224, 224-229 (2000).
 Synthes' SynFix Technique Guide device ("SynFix Technique Guide"), copyright 2006, Synthes Spine.

* cited by examiner





FIG. 1

FIG. 2




FIG. 7




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 9

FIG. 8




FIG. 11

FIG. 10




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 24

FIG. 23




FIG. 25




FIG. 26




FIG. 28




FIG. 27




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 37




FIG. 36




FIG. 38




FIG. 39




FIG. 40




FIG. 41




FIG. 41A




FIG. 41B




FIG. 41D




FIG. 41C




FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 48

FIG. 47




FIG. 50

FIG. 49




FIG. 52




FIG. 51




FIG. 53




FIG. 54




FIG. 55




FIG. 56





FIG. 57




FIG. 58






FIG. 59






FIG. 62




FIG. 63




FIG. 64




FIG. 65




FIG. 66




FIG. 67




FIG. 68




FIG. 70




FIG. 69




FIG. 71




FIG. 72




FIG. 73




FIG. 74




FIG. 75




FIG. 76




FIG. 77




FIG. 78




FIG. 79




FIG. 80




FIG. 81




FIG. 82




FIG. 83




FIG. 84




FIG. 85






FIG. 87

FIG. 88

FIG. 86

FIG. 89








FIG. 98






FIG. 99

FIG. 100

FIG. 101








FIG. 114

FIG. 115

FIG. 116




FIG. 118

FIG. 117




FIG. 122




FIG. 123




FIG. 124




FIG. 125




FIG. 127




FIG. 126




FIG. 128




FIG. 129




FIG. 130

1

**DECOUPLED SPACER AND PLATE AND
METHOD OF INSTALLING THE SAME**

REFERENCE TO RELATED APPLICATIONS

The present application is a continuation application of U.S. Ser. No. 15/479,438, filed Apr. 5, 2017 (published as U.S. Pat. Pub. No. 2018-0289495), which is hereby incorporated by reference in its entirety.

BACKGROUND

Field of the Invention

The present invention relates to bone fixation, and more specifically, to a method of installing an intervertebral spacer and plate.

Description of the Related Art

Various types of spacers can be used in spinal fusion procedures. A standalone spacer is one in which a spacer is attached to a plate. The plate is configured to receive one or more screws that secure the standalone spacer to one or more adjacent vertebrae. The combined spacer/plate structure is typically rigid, thereby reducing the flexibility of the patient at the implant site.

There exists a need for intervertebral spacer and plate assemblies that are inserted as a unit with an insertion tool, but are decoupled from each other when the insertion tool is removed. Further, methods of inserting the assemblies are also needed.

SUMMARY

This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used to limit the scope of the claimed subject matter.

According to one embodiment, a method of installing an intervertebral spacer and plate assembly may include coupling an intervertebral spacer and plate to an insertion tool; delivering the coupled spacer and plate to a surgical site via the insertion tool, wherein the spacer and/or plate are received in an intervertebral disc space; inserting one or more bone screws into the plate to secure the plate to one or more adjacent vertebrae; and removing the insertion tool, such that the spacer is decoupled from the plate at the surgical site.

BRIEF DESCRIPTION OF THE DRAWINGS

Other aspects, features, and advantages of the present invention will become more fully apparent from the following detailed description, the appended claims, and the accompanying drawings in which like reference numerals identify similar or identical elements.

FIG. 1 is a perspective view of a spacer and plate assembly according to a first exemplary embodiment;

FIG. 2 is a perspective view of the spacer shown in FIG. 1;

FIG. 3 is a top plan view of the spacer shown in FIG. 2;

FIG. 4 is a posterior elevational view of the spacer shown in FIG. 2;

2

FIG. 5 is a left lateral side elevational view of the spacer shown in FIG. 2;

FIG. 6 is a right lateral side elevational view of the spacer shown in FIG. 2;

5 FIG. 7 is a perspective view of the plate shown in FIG. 1;

FIG. 8 is a posterior elevational view of the plate shown in FIG. 7;

FIG. 9 is a top plan view of the plate shown in FIG. 7;

10 FIG. 10 is a left lateral side elevational view of the plate shown in FIG. 7;

FIG. 11 is a right lateral side elevational view of the plate shown in FIG. 7;

15 FIG. 12 is a top plan view of the assembly shown in FIG. 1;

FIG. 13 is a posterior elevational view of the assembly shown in FIG. 1;

FIG. 14 is a right lateral side elevational view of the assembly shown in FIG. 1;

20 FIG. 15 is a left lateral side elevational view of the spacer shown in FIG. 1;

FIG. 16 is a perspective view of the assembly components shown in FIG. 1 and an insertion tool for inserting the assembly;

25 FIG. 17 is a perspective view showing the plate of FIG. 7 having been inserted onto the insertion tool;

FIG. 18 is a perspective view showing the spacer and plate assembly of FIG. 1 having been inserted onto the insertion tool;

30 FIG. 19 is a top plan view, in section, of the plate and spacer of the assembly shown in FIG. 1 having been inserted onto the insertion tool;

FIG. 20 is a top plan view of a spacer and plate assembly according to a second exemplary embodiment;

35 FIG. 21 is a posterior elevational view of the assembly shown in FIG. 20;

FIG. 22 is a left lateral side elevational view of the assembly shown in FIG. 20;

40 FIG. 23 is an exploded posterior perspective view of the assembly shown in FIG. 20;

FIG. 24 is an exploded anterior perspective view of the assembly shown in FIG. 20;

FIG. 25 is a top plan view, in section, of the plate of FIG. 20 and an insertion tool for inserting the plate;

45 FIG. 26 is a perspective view of the plate and insertion tool of FIG. 25;

FIG. 27 is a top plan view, in section, of the assembly of FIG. 20 and the insertion tool for inserting the assembly;

50 FIG. 28 is a perspective view of the assembly and insertion tool of FIG. 27;

FIG. 29 is a top plan view, in section, of a spacer block and the spacer and insertion tool of FIG. 27;

FIG. 30 is a perspective view of the spacer block, spacer, and insertion tool of FIG. 29;

55 FIG. 31 is a top plan view of a spacer and plate assembly according to a third exemplary embodiment;

FIG. 32 is a posterior elevational view of the assembly shown in FIG. 31;

60 FIG. 33 is a left lateral side elevational view of the assembly shown in FIG. 31;

FIG. 34 is an exploded anterior perspective view of the assembly shown in FIG. 20;

FIG. 35 is an exploded posterior perspective view of the assembly shown in FIG. 20;

65 FIG. 36 is a top plan view, in section, of the plate of FIG. 31 and an insertion tool for inserting the assembly of FIG. 31;

3

FIG. 37 is a perspective view of the plate and insertion tool of FIG. 36;

FIG. 38 is a top plan view, in section, of the assembly of FIG. 31 and the insertion tool for inserting the assembly;

FIG. 39 is a perspective view of the assembly and insertion tool of FIG. 38;

FIG. 40 is a top plan view, in section, of a spacer block and the spacer and insertion tool of FIG. 38;

FIG. 41 is a perspective view of the spacer block, spacer, and insertion tool of FIG. 40;

FIG. 41A is an anterior perspective view of an alternative plate for use with the spacer shown in FIG. 20;

FIG. 41B is a left perspective view of the plate shown in FIG. 41A;

FIG. 41C is a left side elevational view of the plate shown in FIG. 41A;

FIG. 41D is an anterior side elevational view of the plate shown in FIG. 41A;

FIG. 42 is a top plan view of a spacer and plate assembly according to a fourth exemplary embodiment;

FIG. 43 is a posterior elevational view of the assembly shown in FIG. 42;

FIG. 44 is a left lateral side elevational view of the assembly shown in FIG. 42;

FIG. 45 is an exploded anterior perspective view of the assembly shown in FIG. 42;

FIG. 46 is an exploded posterior perspective view of the assembly shown in FIG. 42;

FIG. 47 is a top plan view, in section, of the plate of FIG. 42 and an insertion tool for inserting the assembly of FIG. 42;

FIG. 48 is a perspective view of the plate and insertion tool of FIG. 47;

FIG. 49 is a top plan view, in section, of the assembly of FIG. 42 and the insertion tool for inserting the assembly;

FIG. 50 is a perspective view of the assembly and insertion tool of FIG. 49;

FIG. 51 is a top plan view, in section, of a spacer block and the spacer and insertion tool of FIG. 49;

FIG. 52 is a perspective view of the spacer block, spacer, and insertion tool of FIG. 51;

FIG. 53 is a top plan view of a spacer and plate assembly according to a fifth exemplary embodiment;

FIG. 54 is a posterior elevational view of the assembly shown in FIG. 53;

FIG. 55 is a left lateral side elevational view of the assembly shown in FIG. 53;

FIG. 56 is an exploded anterior perspective view of the assembly shown in FIG. 53;

FIG. 57 is an exploded posterior perspective view of the assembly shown in FIG. 53;

FIG. 58 is a top plan view, in section, of the assembly of FIG. 53 attached to an insertion tool for inserting the assembly of FIG. 53;

FIG. 59 is a perspective view of the assembly and insertion tool of FIG. 58;

FIG. 60 is a top plan view, in section, of the plate of FIG. 53 and the insertion tool for inserting the plate;

FIG. 61 is a perspective view of the plate and insertion tool of FIG. 60;

FIG. 62 is a top plan view, in section, of a spacer block and the spacer and insertion tool of FIG. 59;

FIG. 63 is a perspective view of the spacer block, spacer, and insertion tool of FIG. 62;

FIG. 64 is a top plan view of a spacer and plate assembly according to a sixth exemplary embodiment;

4

FIG. 65 is a left lateral side elevational view of the assembly shown in FIG. 64;

FIG. 66 is a posterior elevational view of the assembly shown in FIG. 64;

FIG. 67 is an exploded anterior perspective view of the assembly shown in FIG. 64;

FIG. 68 is a perspective view of a spacer and plate assembly according to a seventh exemplary embodiment;

FIG. 69 is a perspective view of a spacer used with the assembly shown in FIG. 68;

FIG. 70 is a perspective view of a plate used with the assembly shown in FIG. 68;

FIG. 71 is a top plan view of the spacer shown in FIG. 69;

FIG. 72 is an anterior elevational view of the spacer shown in FIG. 69;

FIG. 73 is a right side elevational view of the spacer shown in FIG. 69;

FIG. 74 is a left side elevational view of the spacer shown in FIG. 69;

FIG. 75 is an anterior elevational view of the plate shown in FIG. 70;

FIG. 76 is a top plan view of the plate shown in FIG. 70;

FIG. 77 is a right side elevational view of the plate shown in FIG. 70;

FIG. 78 is a left side elevational view of the spacer shown in FIG. 70;

FIG. 79 is a top plan view of the assembly shown in FIG. 68;

FIG. 80 is an anterior elevational view of the assembly shown in FIG. 68;

FIG. 81 is a right side elevational view of the assembly shown in FIG. 68;

FIG. 82 is a left side elevational view of the assembly shown in FIG. 68;

FIG. 83 is a perspective view of a spacer and plate assembly according to an eighth exemplary embodiment;

FIG. 84 is a perspective view of a spacer used with the assembly shown in FIG. 83;

FIG. 85 is a perspective view of a plate used with the assembly shown in FIG. 83;

FIG. 86 is a top plan view of the spacer shown in FIG. 84;

FIG. 87 is an anterior elevational view of the spacer shown in FIG. 84;

FIG. 88 is a right side elevational view of the spacer shown in FIG. 84;

FIG. 89 is a left side elevational view of the spacer shown in FIG. 84;

FIG. 90 is an anterior elevational view of the plate shown in FIG. 85;

FIG. 91 is a posterior elevational view of the plate shown in FIG. 85;

FIG. 92 is a right side elevational view of the plate shown in FIG. 85;

FIG. 93 is a top plan view of the spacer shown in FIG. 85;

FIG. 94 is a top plan view of the assembly shown in FIG. 83;

FIG. 95 is an anterior elevational view of the assembly shown in FIG. 83;

FIG. 96 is a right side elevational view of the assembly shown in FIG. 83;

FIG. 97 is a left side elevational view of the assembly shown in FIG. 83;

FIG. 98 is a side elevational view, in section, of the assembly shown in FIG. 94, taken along lines 98-98 of FIG. 94;

FIG. 99 is a perspective view of a spacer and plate assembly according to a ninth exemplary embodiment;

5

FIG. 100 is a perspective view of a spacer used with the assembly shown in FIG. 99;

FIG. 101 is a perspective view of a plate used with the assembly shown in FIG. 99;

FIG. 102 is a perspective view of the spacer shown in FIG. 100;

FIG. 103 is top plan view of the spacer shown in FIG. 100;

FIG. 104 is an anterior elevational view of the spacer shown in FIG. 100;

FIG. 105 is a posterior elevational view of the spacer shown in FIG. 100;

FIG. 106 is top plan view of the plate shown in FIG. 101;

FIG. 107 is a perspective view of the plate shown in FIG. 101;

FIG. 108 is an anterior elevational view of the plate shown in FIG. 101;

FIG. 109 is a posterior elevational view of the spacer shown in FIG. 101;

FIG. 110 is a top plan view of the assembly shown in FIG. 99;

FIG. 111 is an anterior elevational view of the assembly shown in FIG. 99;

FIG. 112 is a right side elevational view of the assembly shown in FIG. 99;

FIG. 113 is a left side elevational view of the assembly shown in FIG. 99;

FIG. 114 is an anterior elevational view of a spacer and plate assembly according to a tenth exemplary embodiment;

FIG. 115 is a top plan view of the assembly shown in FIG. 114;

FIG. 116 is a right side elevational view of the assembly shown in FIG. 114;

FIG. 117 is a top plan view of a spacer and plate assembly according to an eleventh exemplary embodiment;

FIG. 118 is a top plan view of a spacer and plate assembly according to a twelfth exemplary embodiment;

FIG. 119 is a top plan view of a spacer and plate assembly according to a thirteenth exemplary embodiment;

FIG. 120 is a top plan view of a spacer and plate assembly according to a fourteenth exemplary embodiment;

FIG. 121 is a top plan view of a spacer and plate assembly according to a fifteenth exemplary embodiment;

FIG. 122 is a top plan view of a spacer and plate assembly according to a sixteenth exemplary embodiment;

FIG. 123 is posterior side elevation view of a spacer according to a seventeenth exemplary embodiment;

FIG. 124 is an anterior side elevation view of the spacer shown in FIG. 123;

FIG. 125 is a top plan view of the spacer shown in FIG. 123, with a plate and insertion device;

FIG. 126 is a top plan view of a spacer and plate assembly according to an eighteenth exemplary embodiment;

FIG. 127 is a posterior side elevation view of the assembly shown in FIG. 126;

FIG. 128 is a top plan view of a spacer and plate assembly according to a nineteenth exemplary embodiment;

FIG. 129 is a posterior side elevation view of the plate shown in FIG. 128; and

FIG. 130 is a posterior side elevation view of the spacer shown in FIG. 128.

DETAILED DESCRIPTION

In the drawings, like numerals indicate like elements throughout. Certain terminology is used herein for convenience only and is not to be taken as a limitation on the present invention. The terminology includes the words spe-

6

cifically mentioned, derivatives thereof and words of similar import. The embodiments illustrated below are not intended to be exhaustive or to limit the invention to the precise form disclosed. These embodiments are chosen and described to best explain the principle of the invention and its application and practical use and to enable others skilled in the art to best utilize the invention.

The use of figure numbers and/or figure reference labels in the claims is intended to identify one or more possible embodiments of the claimed subject matter in order to facilitate the interpretation of the claims. Such use is not to be construed as necessarily limiting the scope of those claims to the embodiments shown in the corresponding figures.

It should be understood that the steps of the exemplary methods set forth herein are not necessarily required to be performed in the order described, and the order of the steps of such methods should be understood to be merely exemplary. Likewise, additional steps may be included in such methods, and certain steps may be omitted or combined, in methods consistent with various embodiments of the present invention.

Although the elements in the following method claims, if any, are recited in a particular sequence with corresponding labeling, unless the claim recitations otherwise imply a particular sequence for implementing some or all of those elements, those elements are not necessarily intended to be limited to being implemented in that particular sequence.

In performing spinal fusion procedures, a spacer can be inserted into a disc space. In some embodiments, a stand-alone spacer can be attached to a plate. The plate can receive one or more bone anchors or screws to attach to the plate to one or more adjacent vertebrae. The plate and spacer are often rigidly connected and are not decoupled from one another.

The present application includes spacer and plate assemblies that can be coupled via an insertion instrument upon delivery to a surgical site. In some embodiments, a surgical site can be at or near a disc space, as one skilled in the art will appreciate. The insertion instrument advantageously provides a single tool for delivering both the spacer and plate if desired. Once the spacer and plate are implanted at the surgical site, the insertion instrument can be removed. With the insertion instrument removed, the spacer and plate are considered decoupled from one another. By providing a spacer and plate that are independent and decoupled from one another, a surgeon advantageously has the option to implant both a plate and a spacer, a spacer by itself, or a plate by itself if desired.

The present disclosure provides embodiments of intervertebral spacers and plates that can be used to space and fixedly secure two adjacent vertebrae. According to one embodiment, shown in FIGS. 1-19, an intervertebral spacer and plate assembly 100 ("assembly 100") is provided. In an exemplary embodiment, assembly 100 can be used for cervical repair, although those skilled in the art will recognize that assembly 100 can be sized for thoracic or lumbar repair as well.

Assembly 100 is formed from two separate components, an intervertebral spacer 102 and a plate 104. In some embodiments, spacer 102 and plate 104 are not directly connected to each other, but are instead each separately coupled to an insertion tool 106, shown in FIGS. 16-19.

Referring to FIGS. 1-6, spacer 102 includes a body 108 having a superior surface 110 and an opposing inferior surface 112. Each of superior surface 110 and inferior surface 112 can have a plurality of protrusions or fixation

elements **114** extending outwardly therefrom. While fixation elements **114** are shown as being generally pyramidal in shape, those skilled in the art will recognize that fixation elements **114** can be other shapes, such as ribbed, or other suitable shapes. Fixation elements **114** are used to bite into a grip each of adjacent vertebrae (not shown) between which spacer **102** is inserted.

As shown in FIG. 2, body **102** can have a generally U-shape, with generally parallel lateral sides **116**, **118**, connected to each other by an anterior portion **120**. Lateral side **116** includes a convex arcuate posterior face **117** while lateral side **118** includes a convex arcuate posterior face **119**. The space between lateral sides **116**, **118** can optionally be filled with graft material. The advantage of a U-shaped body is that if a surgeon decides to use the spacer **102** on its own, it can be easily backfilled through the opening of the "U". Referring to FIGS. 2-4, superior surface **110** along lateral side **118** includes a cutout **111** that slopes inferiorly in an anterior-to posterior direction. Similarly, inferior surface **112** along lateral side **116** includes a cutout **113** that slopes superiorly in an anterior-to posterior direction. Cutouts **111**, **113** allow for securing screws (not shown) to be inserted through plate **104**, along cutouts **111**, **113**, respectively, and into adjacent vertebrae (not shown) without engaging spacer **102**.

Lateral side **116** includes a tubular protrusion **122** extending in an anterior-posterior direction. Protrusion **122** has an internally threaded passage **124** that is sized to accept a portion of insertion tool **106** as will be explained in detail below. Passage **124** can have a closed anterior end **125**.

Lateral side **118** includes an open slot **126** that extends in an anterior-posterior direction. An anterior end **128** of slot **126** extends medially inward and is sized to accept a portion of insertion tool **106** as will be explained in detail below.

Referring now to FIGS. 1 and 7-11, plate **104** includes a body **130** having a superior surface **132** and an opposing inferior surface **134**. In some embodiments, the plate **104** is sized and configured to be received within a disc space, while in other embodiments, at least a portion of the plate **104** is sized and configured to be received outside of a disc space. Each of superior surface **132** and inferior surface **134** can have a plurality of stabilizer elements **136** extending outwardly therefrom. In some embodiments, the stabilizer elements **136** can be for torsional stabilization. In an exemplary embodiment, one stabilizer element **136** is located along a central anterior-to-posterior axis, and a second stabilizer element **136** is located proximate to a lateral side of body **130**. While stabilizer elements **136** are shown as being generally ribbed in shape, those skilled in the art will recognize that stabilizer elements **136** can be other shapes, such as pyramidal, or other suitable shapes. Stabilizer elements **136** are used to bite into a grip each of adjacent vertebrae (not shown) between which spacer **102** is inserted.

As shown in FIG. 9, body **130** can have a generally arcuate shape, with generally parallel lateral sides **138**, **140**. Each lateral side **138**, **140** includes an anterior-to-posterior slot **142**, **144**, respectively. Slot **142** includes a superior surface **146** and a generally parallel inferior surface **148**, while slot **144** includes a superior surface **150** and a generally parallel inferior surface **152**. As shown in FIG. 13, when plate **104** is aligned with spacer **102** for insertion, slot **142** is aligned with threaded passage **124** and slot **144** is aligned with open slot **126**.

Body **130** includes a generally concave arcuate anterior face **156** that mates with convex arcuate faces **117**, **119** of spacer **102** when plate **104** is located against spacer **102**, as

shown in FIG. 12. Body **130** also includes a generally convex posterior face **158** that extends generally parallel to anterior face **156**.

Through-holes **160**, **162** extend through body **130** in a posterior-to-anterior direction. Through-holes **160**, **162** are sized to allow a bone or securing screw (not shown) to be inserted therethrough to secure plate **104** to each of a superior vertebra (not shown) and an inferior vertebra (not shown), between which spacer **102** is being inserted. Through-hole **160** extends in a superior-to-inferior direction so that its screw engages and secures to the inferior vertebra, while through-hole **162** extends in an inferior-to-superior direction so that its screw engages and secures the superior vertebra.

A locking screw **164** is disposed between through-holes **160**, **162**. Locking screw **164** has a head **166** with diametrically opposed arcuate cutouts **168**, **170** that are sized to allow the securing screws discussed above to be inserted into through-holes **160**, **162**. During insertion of assembly **100**, locking screw **164** is in a configuration relative to plate **104** as shown in FIG. 8. After the securing screws secure plate **104** to the superior and inferior vertebra, locking screw **164** is rotated, for example, about 90 degrees, so that head **166** extends over the securing screws, preventing the securing screws from inadvertently backing out.

FIGS. 1 and 12-15 show assembly **100**. While plate **104** abuts spacer **102**, plate **104** is not rigidly connected to spacer **102** in any way so that spacer **102** and plate **104** remain separate, independent components. During insertion via an insertion tool, the spacer **102** and plate **104** can both be coupled to the insertion tool. After insertion to a surgical site, the spacer **102** and plate **104** are decoupled from one another.

Referring now to FIGS. 16-19, insertion tool **106** is used to insert spacer **102** and plate **104**. Insertion tool **106** includes a distal end **170** having a first distal finger **172** and a second distal finger **174** that extends generally parallel to first distal finger **174**. A gap **176** between fingers **172**, **174** forms a generally U-shaped cavity **176** that is sized to accept plate **104** therein, as shown in FIG. 17. This gap advantageously provides space for a surgeon to use a tool to insert one or more bone screws or anchors into the plate. First distal finger **172** includes a rod **178** having a threaded end **180** that threads into threaded passage **124** in tubular protrusion **122** on spacer **102**, as shown in FIG. 19. Rod **178** has a proximal end (not shown) that can be rotated by the surgeon to threadingly secure threaded end **180** into threaded passage **124**.

Second distal finger **174** includes a prong **182** that extends generally toward first distal finger **172**. Prong **182** is sized to fit into anterior end **128** of slot **126** on spacer **102**.

While a single insertion tool **106** is shown, those skilled in the art will recognize that multiple insertion tools can be used. For example, a first insertion tool having only first distal finger **172** can be used in conjunction with a second insertion tool having only second distal finger **174**.

According to one embodiment, a method of installing assembly **100**, for example, at the site of two adjacent vertebrae (not shown), may include providing spacer **102**, plate **104**, and insertion tool **106** as a kit, as shown in FIG. 16. Referring to FIG. 17, plate **104** is connected to insertion tool **106** such that distal end **170** of insertion tool **106** extends distally of plate **104** (shown in FIG. 19). Plate **104** is connected to insertion tool **106** by attaching plate **104** to each of first finger **172** and second finger **174**. First finger **172** is inserted into slot **142**, while second finger **174** is inserted into second slot **144**. Plate **104** is slid proximally

onto each of first finger 172 and second finger 174, with plate 104 engaging each of first finger 172 and second finger 174 with an interference fit.

Next, as shown in FIGS. 18 and 19, spacer 102 is attached to distal end 170 of insertion tool 106 by attaching spacer 102 to each of first finger 172 and second finger 174. Sequentially or simultaneously, first finger 172 is connected to spacer 102 by threading threaded end 180 that threads into threaded passage 124 in tubular protrusion 122 on spacer 102 and inserting prong 182 on second finger 174 into slot 126 on spacer 102 and sliding spacer 102 proximally until prong 182 engages anterior end 128 of slot 126, thereby frictionally engaging second finger 174 with spacer 102.

After assembly 100 is attached to insertion tool 106, spacer 102 is inserted between adjacent vertebrae. Gap 176 is sufficiently large between plate 104 and insertion tool 106 to allow securing devices, such as, for example, screws (not shown) to be inserted through through-holes 160, 162, and into inferior vertebra and superior vertebra, respectively, securing plate 104 to the vertebrae. After securing plate 104 to the vertebrae, insertion tool 106 is removed, leaving spacer 102 and plate 104, as separate components, in the patient's spinal column. While the plate 104 and spacer 102 are attached to the insertion tool 106 upon delivery to a surgical site, once the insertion tool 106 is removed, the plate 104 and spacer 102 can be viewed as decoupled or independent from one another.

An alternative embodiment of an intervertebral spacer and plate assembly 200 ("assembly 200") is shown in FIGS. 20-28. In an exemplary embodiment, assembly 200 can be used for lumbar repair, although those skilled in the art will recognize that assembly 200 can be sized for thoracic or cervical repair as well.

Assembly 200 is formed from two separate components, an intervertebral spacer 202 ("spacer 202") and a plate 204 ("plate 204"). In some embodiments, spacer 202 and plate 204 are not connected to each other, but are instead each separately coupled to an insertion tool 206, as shown in FIGS. 25-28.

Referring to FIGS. 20 and 22-24, spacer 202 includes a body 208 having a superior surface 210 and an opposing inferior surface 212. Each of superior surface 210 and inferior surface 212 can have a plurality of protrusions or fixation elements 214 extending outwardly therefrom. While fixation elements 214 are shown as being generally pyramidal in shape, those skilled in the art will recognize that fixation elements 214 can be other shapes, such as ribbed, or other suitable shapes. Fixation elements 214 are used to bite into a grip each of adjacent vertebrae (not shown) between which spacer 202 is inserted.

As shown in FIG. 20, body 202 can have a generally oblong shape, with generally arcuate lateral sides 216, 218, connected to each other by an anterior portion 220 and a posterior portion 222. Lateral side 216 includes an indentation 217 while lateral side 218 includes a similar indentation 219. Indentations 217, 219 reduce the lateral length of posterior portion 222 relative to the remaining lateral length of spacer 202. A space 223 bounded by lateral sides 216, 218, anterior portion 220, and posterior portion 222 can optionally be filled with graft material.

Posterior portion 222 includes a first chamfered face 224 that extends in an inferior direction posteriorly from superior surface 210 and a second chamfered face 226 (shown in FIG. 23) that extends in a superior direction posteriorly from inferior surface 212. Chamfered faces 224, 226 allow for securing screws (not shown) to be inserted through plate

204, along chamfered faces 224, 226, respectively, and into adjacent vertebrae (not shown) without engaging spacer 202.

Posterior portion 222 also includes a smooth, anteriorly directed hole 228 proximate to lateral side 216. Hole 228 is sized to accept a non-threaded portion of insertion tool 206 as will be explained in detail below. Posterior portion 222 also includes a threaded, anteriorly directed hole 229 proximate to lateral side 218. Hole 229 is sized to accept a threaded portion of insertion tool 206 as will be explained in detail below.

Referring now to FIGS. 20-24, plate 204 includes a body 230 having a superior surface 232 and an opposing inferior surface 234. Each of superior surface 232 and inferior surface 234 can have a plurality of stabilizer elements 236 extending outwardly therefrom. In some embodiments, the stabilizer elements 236 can be for torsional stabilization. In an exemplary embodiment, stabilizer elements 236 are located along fingers 238, 240 that extend anteriorly from plate 204. While stabilizer elements 236 are shown as being generally ribbed in shape, those skilled in the art will recognize that stabilizer elements 236 can be other shapes, such as pyramidal, or other suitable shapes. Stabilizer elements 236 are used to bite into a grip each of adjacent vertebrae (not shown) between which spacer 202 is inserted.

As shown in FIG. 20, body 230 can have a generally laterally elongate shape, with generally parallel lateral sides 242, 244. Fingers 238, 240 extend from lateral sides 242, 244, respectively. Fingers 238, 240 are sized to fit into indentations 217, 219 respectively, while a space between fingers 238, 240 is sized to allow posterior portion 222 of spacer 202 to be inserted therein.

Referring to FIG. 21, through-holes 260, 262 extend through body 230 in a posterior-to-anterior direction. Through-holes 260, 262 are located on plate 204 to align with holes 228, 229 when plate 204 and spacer 202 are coupled as shown in FIG. 20. Through-hole 260 can be smooth bored to allow for the passage of the non-threaded portion of insertion tool 206. Through-hole 262 can be smooth bored or threaded to allow for the insertion of the threaded portion of insertion tool 206.

Additional through-holes 264, 266, 268 are provided in plate 204 and are sized to allow a securing screw (not shown) to be inserted therethrough to secure plate 204 to each of a superior vertebra (not shown) and an inferior vertebra (not shown), between which spacer 202 is being inserted. Through-holes 264, 266 each extends in a superior-to-inferior direction so that their respective screw each engages and secures to the inferior vertebra, while through-hole 268 extends in an inferior-to-superior direction so that its screw engages and secures the superior vertebra.

Referring to FIG. 21, locking screws 270, 272, 274 are each disposed adjacent to a respective through-hole 264, 266, 268. Each locking screw 270, 272, 274 has a head 276, 278, 280 with an arcuate cutout 282, 284, 286, respectively, that is sized to allow the securing screws discussed above to be inserted into through-holes 264, 266, 268. During insertion of assembly 200, locking screws 264, 266, 268 are in a configuration relative to plate 204 as shown in FIG. 21. After the securing screws secure plate 204 to the superior and inferior vertebra, locking screws 270, 272, 274 are rotated, for example, about 90 degrees, so that heads 276, 278, 280 each extends over its adjacent securing screws, preventing the securing screws from inadvertently backing out.

FIGS. 20-24, 27, and 28 show assembly 200. While plate 204 is butted up against spacer 202 to form a coupled construct, plate 204 is not connected to spacer 202 so that

spacer 202 and plate 204 remain separate, independent components that can be implanted together or on their own as part of a fusion procedure.

Referring now to FIGS. 25-28, insertion tool 206 is used to insert spacer 202 and plate 204. Insertion tool 206 includes a distal end 282 having a first distal finger 284 and a second distal finger 286 that extends generally parallel to first distal finger 282. First distal finger 282 is a generally smooth bore rod that is sized to pass through through-hole 260 in plate 204 and into hole 228 in spacer 202.

Second distal finger 286 includes a rod 288 having a threaded end 290 that threads into threaded through-hole 262 in plate 204, as shown in FIG. 25, as well as into hole 229 in spacer, as shown in FIG. 27. Rod 288 has a proximal end (not shown) that can be rotated by the surgeon to threadingly secure threaded end 290 into hole 229.

While a single insertion tool 206 is shown, those skilled in the art will recognize that multiple insertion tools can be used. For example, a first insertion tool having only first distal finger 282 can be used in conjunction with a second insertion tool having only second distal finger 286.

According to one embodiment, a method of installing assembly 200, for example, at the site of two adjacent vertebrae (not shown), may include providing spacer 202, plate 204, and insertion tool 206 as a kit, as shown in FIG. 28.

As shown in FIGS. 23 and 24, plate 204 is releasably engaged with spacer 202 in the absence of securing plate 204 to spacer 202 such that plate 204 engages spacer 202 between first finger 238 and second finger 240, as shown in FIG. 20.

Next, insertion tool 206 is inserted through plate 204 and into spacer 202. Such insertion is performed by inserting insertion tool 206 through first through-hole 260 and second through-hole 262 and into holes 228, 230 of spacer 202. This is accomplished by threading threaded finger 286 of insertion tool 206 into plate 204 and into hole 229 in spacer 202, as well as inserting unthreaded finger 282 of insertion tool 206 through plate 204 and into hole 228 in spacer 202.

Next, spacer 202 is implanted between adjacent vertebrae. Insertion tool 206 is removed such that spacer 202 is separate from plate 204. Next, plate 204 is connected to the vertebrae.

Optionally, as shown in FIGS. 25 and 26, insertion tool 206 can be releasably secured to only plate 204. Then, plate 204 can be coupled to spacer 202, after which time insertion tool 206 is then releasably secured to spacer 202.

A situation may arise wherein plate 204 is not required to secure spacer 202 between adjacent vertebrae; the compression of vertebrae toward each other is sufficient to maintain spacer 202 in place. In such a situation, plate 204 can be omitted. It is desired, however, to incorporate a substitute for plate 204 in order to provide desired spacing between plate 202 and insertion tool 206.

To achieve this spacing, as shown in FIGS. 29 and 30, a spacer block 290 is provided. Spacer block 290 has substantially the same anterior-to-posterior width as plate 204, but without fingers 238, 240. Spacer block 290 includes a pair of unthreaded, smooth bore through-holes 292, 294 that align with holes 228, 230 of spacer 202 so that fingers 282, 286 of insertion tool 206 can be inserted therethrough and into hole 228, 230 of spacer 202 for insertion of spacer 202 between adjacent vertebrae (not shown).

An alternative embodiment of an intervertebral spacer and plate assembly 300 ("assembly 300") is shown in FIGS. 31-39. In an exemplary embodiment, assembly 300 can be

used for lumbar repair, although those skilled in the art will recognize that assembly 300 can be sized for thoracic or cervical repair as well.

Assembly 300 is formed from two separate components, an intervertebral spacer 302 ("spacer 302") and a plate 304 ("plate 304"). In some embodiments, spacer 302 and plate 304 are not connected to each other, but are instead each separately coupled to an insertion tool 306, as shown in FIGS. 38 and 39.

Referring to FIGS. 31 and 34-35, spacer 302 is similar to spacer 202, but, instead of a solid posterior portion 222, posterior portion 322 of spacer 302 includes a gap 325 between two medially directed ends 324, 326. Gap 325 allows for spacer 302 to flex after insertion, which may provide enhanced mobility for the patient.

Additionally, spacer 302 includes indentations 317, 319 that are larger than indentations 217, 219 on spacer 202. Similarly, fingers 338, 340 on plate 304 are wider than fingers 238, 240 on plate 204 to accommodate the larger indentations 317, 319.

Other aspects of spacer 302, plate 304, and insertion tool 306 are similar, if not identical, to corresponding aspects of spacer 202, plate 204, and insertion tool 206 as discussed above. Those aspects are identified with element numbers corresponding to spacer 202, plate 204, and insertion tool 206 with respect to spacer 302, plate 304, and insertion tool 306, respectively.

With respect to a spacer block 390 shown in FIGS. 40 and 41, however, spacer block 390 includes fingers 396, 398 that are insertable into indentations 317, 319. Other aspects of spacer block 390 are similar, if not identical, to corresponding aspects of spacer block 290 as discussed above.

Instead of plate 304, an alternative plate 304', shown in FIGS. 41A-41D can be provided. Plate 304' is similar to plate 304, with the addition of a superior extension 393 on the posterior end 394 of plate 304'. Extension 393 increases the overall height of plate 304' and allows plate 304' to be shouldered onto the vertebral body during insertion. As shown in FIG. 41B, extension 393 can be straight. Alternatively, extension 393 can be angled in a posterior direction.

An alternative embodiment of an intervertebral spacer and plate assembly 400 ("assembly 400") is shown in FIGS. 42-50. In an exemplary embodiment, assembly 400 can be used for lumbar repair, although those skilled in the art will recognize that assembly 400 can be sized for thoracic or cervical repair as well.

Assembly 400 is formed from two separate components, an intervertebral spacer 402 ("spacer 402") and a plate 404 ("plate 404"). In some embodiments, spacer 402 and plate 404 are not connected to each other, but are instead each separately coupled to an insertion tool 406, as shown in FIGS. 47 and 48. Upon delivery to a surgical site, the spacer 402 and plate 404 can be decoupled from one another.

Referring to FIGS. 42-47, spacer 402 is similar to spacer 302, but, instead of holes 260, 262 for insertion of insertion tool 306, lateral sides 416, 418 include a recess 460, 462, respectively. Recesses 460, 462 extend anteriorly from indentations 317, 319 toward anterior face 456. Each recess 460, 462 includes a plurality of superior-to-inferior extending slots 464. FIGS. 45 and 46 show two slots 464 in each recess 460, 462, although those skilled in the art will recognize that more or less than two slots 464 can be provided.

Additionally, fingers 338, 340 on plate 404 each include a recess 438, 440, respectively that extend in an anterior-to-posterior direction along the length of each respective finger 338, 340. Each recess 438, 440 includes a plurality of

superior-to-inferior extending slots **464**. FIGS. **45** and **46** show two slots **442** in each recess **438**, **440**, although those skilled in the art will recognize that more or less than two slots **442** can be provided.

Other aspects of spacer **402** and plate **404** are similar, if not identical, to corresponding aspects of spacer **302** and plate **304** as discussed above. Those aspects are identified with element numbers corresponding to spacer **302** and plate **304** with respect to spacer **402** and plate **404**, respectively.

Insertion tool **406** is shown in FIGS. **47-52**. Insertion tool **406** includes a distal end **470** having a first distal finger **472** and a second distal finger **474** that extends generally parallel to first distal finger **474**. A gap between fingers **472**, **474** forms a generally U-shaped cavity **476** that is sized to accept plate **404** therein, as shown in FIGS. **47** and **48**. First distal finger **472** includes a plurality of protrusions **478** that fit into recess **460** and slots **464** on spacer **402** and recess **438** and slots **442** on plate **404**. Similarly, second distal finger **474** includes a plurality of protrusions **480** that fit into recess **462** and slots **464** on spacer **402** and recess **440** and slots **442** on plate **404**.

A proximal end (not shown) of insertion tool **406** can include a pivot connection such that the opening of insertion tool **406** at the proximal end splays first distal finger **472** away from second distal finger **474** to release spacer **402** and plate **404** so that spacer **402** and plate **404** are separated components.

Referring to FIGS. **51** and **52**, spacer block **490** includes slots **492** that receive protrusions **478**, **480** on insertion tool **406**. Other aspects of spacer block **490** are similar, if not identical, to corresponding aspects of spacer block **390** as discussed above.

An alternative embodiment of an intervertebral spacer and plate assembly **500** (“assembly **500**”) is shown in FIGS. **53-63**. In an exemplary embodiment, assembly **500** can be used for lumbar repair, although those skilled in the art will recognize that assembly **500** can be sized for thoracic or cervical repair as well.

Assembly **500** is formed from two separate components, an intervertebral spacer **502** (“spacer **502**”) and a plate **504** (“plate **504**”). In some embodiments, spacer **502** and plate **504** are not connected to each other, but are instead each separately coupled to an insertion tool **506**, as shown in FIGS. **58** and **59**.

Assembly **500** is similar to assembly **400** except that, instead of having gap **325** between two medially directed ends **324**, **326**, spacer **502** has a posterior portion **525** that extends fully between lateral sides **516**, **518**. Lateral sides **516**, **518** include indentations **517**, **519** that do not extend medially as far as indentations **317**, **319** respectively, formed in spacer **402**, as discussed above.

Additionally, referring to FIGS. **62** and **63**, a spacer block **590** includes slots **592** that receive protrusions **478**, **480** on an insertion tool **4506**.

An alternative embodiment of an intervertebral spacer and plate assembly **600** (“assembly **600**”) is shown in FIGS. **64-67**. In an exemplary embodiment, assembly **600** can be used for lumbar repair, although those skilled in the art will recognize that assembly **600** can be sized for thoracic or cervical repair as well.

Assembly **600** is formed from two separate components, an intervertebral spacer **602** (“spacer **602**”) and a plate **604** (“plate **604**”). Plate **704** is shown in detail in FIGS. **75-78**. Plate **602** has a body **610** having a generally arcuate shape, with generally parallel lateral sides **612**, **614**. A posterior portion **616**, **618**, respectively, of each lateral side **612**, **614** includes an anterior-to-posterior recess **620**, **622**, respec-

tively. Each recess **620**, **622** includes a laterally projecting protrusion **624** having sloped superior and inferior sides (only one protrusion **624** is shown in FIG. **65**). Each recess **620**, **622** is in communication with a slot **628**, **630**, respectively that each extends medially. A medial portion **628**, **629** of each lateral side **612**, **614**, respectively, include an oblique cutout **616**, **618**.

Plate **604** includes a body **630** having a generally laterally elongate shape, with generally parallel lateral sides **642**, **644**. Fingers **638**, **640** extend from lateral sides **642**, **644**, respectively. Fingers **638**, **640** are sized to fit into recesses **620**, **622**, respectively, in spacer **602**. As shown in FIG. **65**, finger **638** includes a cutout **646** formed therein. Although not shown, finger **640** includes a corresponding cutout. An anterior end of each finger **638**, **640** includes a medially extending prong **648**, **650** that fits into a slot **628**, **630**, respectively. An anterior face **652** of body **630** also includes two spaced apart tangs **654**, **656**.

Referring to FIG. **66**, through-holes **664**, **666**, **668** are provided in plate **604** and are sized to allow a securing screw (not shown) to be inserted therethrough to secure plate **604** to each of a superior vertebra (not shown) and an inferior vertebra (not shown), between which spacer **602** is being inserted. Through-holes **664**, **666** each extends in a superior-to-inferior direction so that their respective screw each engages and secures to the inferior vertebra, while through-hole **668** extends in an inferior-to-superior direction so that its screw engages and secures the superior vertebra.

Locking screws **670**, **672** are each disposed between respective through-holes **664**, **666**, **668**. Each locking screw **670**, **672** has a head **676** with a pair of arcuate cutouts **682**, **684** that are sized to allow the securing screws discussed above to be inserted into through-holes **664**, **666**, **668**. During insertion of assembly **600**, locking screws **664**, **666**, **668** are in a configuration relative to plate **604** as shown in FIG. **66**. After the securing screws secure plate **604** to the superior and inferior vertebra, locking screws **670**, **672** are rotated, for example, about 90 degrees, so that heads **676**, **678** each extends over its adjacent securing screws, preventing the securing screws from inadvertently backing out. In some embodiments, the locking screws **670**, **672** (upon rotation) can abut a side of the securing screws to prevent inadvertent backing out.

Assembly **600** is fitted together by aligning fingers **638**, **640** and prongs **648**, **650** on plate **604** with recesses **620**, **622** and slots **628**, **630**, respectively, on spacer **602**, which also aligns lateral sides of tangs **654**, **656** with cutout **616**, **618**, respectively. Plate **604** is slid down into spacer **602**, locking fingers **638**, **640** and prongs **648**, **650** into recesses **620**, **622** and slots **628**, **630**, respectively.

Additionally, protrusion **624** slides into cutout **646**. Tangs **654**, **656** engage cutouts **616**, **618**, respectively, stabilizing plate **604** with respect to spacer **602**.

Assembly **600** is inserted between adjacent vertebrae as a unit, and, unlike other embodiments of the present invention, remain as a unit after implantation.

Another alternative embodiment of an intervertebral spacer and plate assembly **700** (“assembly **700**”) is shown in FIGS. **68-82**. In an exemplary embodiment, assembly **700** can be used for cervical repair, although those skilled in the art will recognize that assembly **400** can be sized for thoracic or lumbar repair as well.

Assembly **700** is formed from two separate components, an intervertebral spacer **702** (“spacer **702**”) and a plate **704** (“plate **704**”). In some embodiments, spacer **702** and plate **704** are not connected to each other, but are instead each

separately coupled to an insertion tool similar to insertion tool **406**, shown in FIGS. **47** and **48**.

Referring to FIGS. **72-74**, spacer **702** is similar to spacer **402**, but, instead of having gap **325** between two medially directed ends **324**, **326**, spacer **702** has a posterior portion **725** that extends fully between lateral sides **716**, **718**. Recesses **760**, **762** extend anteriorly from posterior portion **725** toward anterior face **756**. Each recess **760**, **762** includes a plurality of superior-to-inferior extending slots **764**. FIGS. **73** and **74** show two slots **764** in each recess **760**, **762**, respectively, although those skilled in the art will recognize that more or less than two slots **764** can be provided.

Posterior portion **725** includes cutouts **728**, **730** to allow securing screws (not shown) to extend therethrough to secure plate **704** to adjacent vertebrae (not shown). When viewed from a posterior-to-anterior direction, a first cutout **728** is formed in a superior surface **710** and is defined by side walls **732**, **734** and a bottom wall **736**. As shown in FIG. **72**, side walls **732**, **734** and bottom wall **736** extend at oblique angles relative to each other, although those skilled in the art will recognize that side walls **732**, **734** can extend orthogonally to bottom wall **736**.

Similarly, a second cutout **738** is formed in an inferior surface **712** and is defined by side walls **742**, **744** and a top wall **746**. As shown in FIG. **72**, side walls **742**, **744** and top wall **746** extend at oblique angles relative to each other, although those skilled in the art will recognize that side walls **742**, **744** can extend orthogonally to top wall **746**.

Plate **704** is shown in detail in FIGS. **75-78**. Plate **704** has a body **750** having a generally arcuate shape, with generally parallel lateral sides **752**, **754**. Each lateral side **752**, **754** includes an anterior-to-posterior recess **776**, **778**, respectively. Each recess **776**, **778** is in communication with a slot **760**, **762** in spacer **702**.

Plate **704** also includes through-openings **782**, **784** for securing screws (not shown) that are used to secure plate **704** to adjacent vertebrae (not shown). A locking screw **786** can be rotated, for example, about 90 degrees after the securing screws have been inserted to keep the securing screws from backing out after insertion. When plate **704** is aligned with spacer **702** as shown in FIGS. **79-82**, through-opening **782** is aligned with first cutout **728** in spacer **702** and through-opening **784** is aligned with second cutout **730** in spacer **702** so that the securing screws can pass over or under spacer **702** and into their respective vertebrae.

Also, as shown in FIGS. **81** and **82**, when plate **704** is aligned with spacer **702** for insertion, recess **776** is aligned with recess **760** and recess **778** is aligned with recess **762** so that an insertion tool, similar to insertion tool **406**, can extend through plate **704** and grip spacer **702** for insertion.

The insertion procedure for assembly **700** can be similar to that as is described above for assembly **400**. However, instead of insertion tool **406** having protrusions that engage plate **704**, such protrusions can be omitted and assembly **700** can rely on friction between plate **704** and insertion tool **406**, as well as between implant **702** and insertion tool **406**.

An alternative embodiment of an intervertebral spacer and plate assembly **800** ("assembly **800**") is shown in FIGS. **83-98**. In an exemplary embodiment, assembly **800** can be used for cervical repair, although those skilled in the art will recognize that assembly **800** can be sized for thoracic or lumbar repair as well.

Assembly **800** is formed from two separate components, an intervertebral spacer **802** ("spacer **802**") and a plate **804** ("plate **804**"). In some embodiments, spacer **802** and plate **804** are not connected to each other, but instead merely engage each other.

Referring to FIGS. **84** and **86-89**, spacer **802** includes a body **808** having a superior surface **810** and an opposing inferior surface **812**. Each of superior surface **810** and inferior surface **812** can have a plurality of fixation elements **814** extending outwardly therefrom. While fixation elements **814** are shown as being generally pyramidal in shape, those skilled in the art will recognize that fixation elements **814** can be other shapes, such as ribbed, or other suitable shapes. Fixation elements **814** are used to bite into a grip each of adjacent vertebrae (not shown) between which spacer **802** is inserted.

As shown in FIG. **20**, body **802** can have a generally oblong shape, with generally linear lateral sides **816**, **818**, connected to each other by an anterior portion **820** and a posterior portion **822**, with a generally isosceles trapezoid interior space **823** defined therebetween that can optionally be filled with graft material.

Posterior portion **822** includes an arcuate face **824** that extends between lateral sides **816**, **818**. A rounded protrusion **826** extends posteriorly from posterior portion **822**. A pair of insertion tool engagement holes **828**, **829** are each located on opposing sides of protrusion **826**. Holes **828**, **829** can be threaded or unthreaded, and can be through-holes or blind holes. Holes **828**, **829** are sized to accept arms of an insertion tool (not shown) for insertion of assembly **800**.

Referring now to FIGS. **85** and **90-93**, plate **804** includes a body **830** having an anterior surface **832** and an opposing posterior surface **834**. Referring to FIGS. **90** and **91**, plate **804** can have a generally "X" shape, with left and right superior arms **836**, **838**, respectively, and left and right inferior arms **840**, **842**, respectively. Superior arms **836**, **838** include through-openings **844**, **846** that are angled in a superior direction to allow screws (not shown) to be inserted therethrough to secure plate **804** to a superior vertebra (not shown). Similarly, inferior arms **840**, **842** include through-openings **848**, **850** that are angled in an inferior direction to allow securing screws (not shown) to be inserted therethrough to secure plate **804** to an inferior vertebra (not shown).

Referring to FIG. **90**, locking screws **852**, **854**, **856**, **858** are each disposed adjacent to a respective through-opening **844**, **846**, **848**, **850**. Each locking screw **852**, **854**, **856**, **858** has a head **860** with an arcuate cutout **862**, respectively, that is sized to allow the securing screws discussed above to be inserted into through-openings **844**, **846**, **848**, **850**. During insertion of assembly **800**, locking screws **852**, **854**, **856**, **858** are in a configuration relative to plate **804** as shown in FIG. **95**. After the securing screws secure plate **804** to the superior and inferior vertebra, locking screws **852**, **854**, **856**, **858** are rotated, for example, about 90 degrees, so that heads **860** each extends over its adjacent securing screws, preventing the securing screws from inadvertently backing out.

Plate **804** also includes a centrally located posterior recess **870**. As shown in FIG. **90**, recess **870** can be generally oblong in shape, although those skilled in the art will recognize that recess **870** can be other shapes. Recess **870** accepts a prong on an insertion device (not shown) for insertion of assembly **800**.

Referring to FIG. **91**, anterior surface **8732** of plate **804** includes a centrally located concave recess **874** that accepts protrusion **826**, as shown in FIG. **98**. Protrusion **826** rides within recess **874**, forming an articulating joint that allows plate **804** to pivot relative to body **802**, providing some flexibility for the patient after assembly **800** is implanted.

FIGS. **83** and **95-98** show assembly **800**. While plate **804** is butted up against spacer **802** to form a coupled construct, plate **804** is not rigidly connected to spacer **802** so that

spacer **802** and plate **804** remain separate, independent components throughout insertion and after insertion into the patient.

An alternative embodiment of an intervertebral spacer and plate assembly **900** (“assembly **900**”) is shown in FIGS. **99-113**. In an exemplary embodiment, assembly **900** can be used for cervical repair, although those skilled in the art will recognize that assembly **900** can be sized for thoracic or lumbar repair as well.

Assembly **900** is formed from two separate components, an intervertebral spacer **902** and a plate **904**. Spacer **902** and plate **904** are never connected to each other, but instead merely engage each other.

Referring to FIGS. **99** and **102-105**, spacer **902** includes a body **908** having a superior surface **910** and an opposing inferior surface **912**. Each of superior surface **910** and inferior surface **912** can have a plurality of fixation elements **914** extending outwardly therefrom. While fixation elements **914** are shown as being generally pyramidal in shape, those skilled in the art will recognize that fixation elements **914** can be other shapes, such as ribbed, or other suitable shapes. Fixation elements **914** are used to bite into a grip each of adjacent vertebrae (not shown) between which spacer **902** is inserted.

As shown in FIG. **103**, body **902** can have a generally oblong shape, with generally linear lateral sides **916**, **918**, connected to each other by an anterior portion **920** and a posterior portion **922**, with a generally isosceles trapezoid interior space **923** defined therebetween that can optionally be filled with graft material.

Posterior portion **922** includes an arcuate face **924** that extends between lateral sides **916**, **918**. A generally centrally located insertion tool engagement hole **928** extends through posterior portion **922**. Hole **928** can be threaded, as shown in FIG. **100**, or unthreaded. Hole **928** is sized to an insertion tool (not shown) for insertion of assembly **900**.

A pair of plate engagement slots **931**, **932** are each located on opposing sides of hole **928**. Slots **931**, **932** are blind holes and are generally rectangular in shape, with rounded corners. Slots **931**, **932** are sized to accept posterior protrusions from plate **904**, as is discussed below.

Referring now to FIGS. **101** and **106-109**, plate **904** includes a body **930** having an anterior surface **933** and an opposing posterior surface **934**. Referring to FIGS. **108** and **109** and **91** plate can have a generally “rhomboid” shape, with a right superior arm **936** and a left inferior arm **940**. Superior arm **936** includes a through-opening **944** that is angled in a superior direction to allow a screw (not shown) to be inserted therethrough to secure plate **904** to a superior vertebra (not shown). Similarly, inferior arm **940** includes a through-opening **948** that is angled in an inferior direction to allow a securing screw (not shown) to be inserted there-through to secure plate **904** to an inferior vertebra (not shown).

Referring to FIG. **108**, locking screws **952**, **954** are each disposed adjacent to a respective through-opening **944**, **948**. Each locking screw **952**, **954** has a head **960** with an arcuate cutout **962**, respectively, that is sized to allow the securing screws discussed above to be inserted into through-openings **944**, **948**. During insertion of assembly **900**, locking screws **952**, **954** are in a configuration relative to plate **904** as shown in FIG. **108**. After the securing screws secure plate **904** to the superior and inferior vertebra, locking screws **952**, **954** are rotated, for example, about 90 degrees, so that heads **960** each extends over its adjacent securing screws, preventing the securing screws from inadvertently backing out.

Plate **904** also includes a centrally located through-opening **970**. As shown in FIG. **108**, through-opening **970** can be generally circular in shape, although those skilled in the art will recognize that through-opening **970** can be other shapes. Through-opening **970** is unthreaded and allows an insertion device (not shown) to pass therethrough for engagement with hole **928** in spacer **902** for insertion of assembly **900**.

Referring still to FIG. **108**, a posterior surface **972** of plate **904** includes a pair of diametrically opposed slots **974**, **976** that extend at an oblique angle away from through-opening **970**. Slots **974**, **976** accept a prong of an insertion instrument (not shown) during implantation of assembly **900**, allowing the insertion instrument to be placed into slots **974**, **976** so that plate **904** is held rigidly on the insertion instrument without being able to rotate.

Referring now to FIGS. **106**, **107**, and **109**, an anterior surface **980** of plate **904** includes a pair of diametrically opposed protrusions **982**, **984** that are sized and located to fit into plate engagement slots **931**, **932**. A posterior end of locking screws **952**, **954** also extends outwardly from plate engagement slots **931**, **932** as well.

FIGS. **99** and **110-113** show assembly **900**. While plate **904** is butted up against spacer **902** to form a coupled construct, plate **904** is not connected to spacer **902** so that spacer **902** and plate **904** remain separate components throughout insertion and after insertion into the patient.

FIGS. **114-116** show an alternative plate **1004** that can be used with spacer **902** to form an assembly **1000**. Plate **1004** has a generally rectangular shape with a centrally located through-opening **1070**. As shown in FIG. **114**, through-opening **1070** can be generally circular in shape, although those skilled in the art will recognize that through-opening **1070** can be other shapes. Through-opening **1070** is unthreaded and allows an insertion device (not shown) to pass therethrough for engagement with hole **928** in spacer **902** for insertion of assembly **1000**.

Plate **1004** has left and right superior through-openings **1044**, **1046** that are angled in a superior direction to allow screws (not shown) to be inserted therethrough to secure plate **1004** to a superior vertebra (not shown). Similarly, plate **1004** has left and right inferior through-openings **1048**, **1050** that are angled in an inferior direction to allow securing screws (not shown) to be inserted therethrough to secure plate **1004** to an inferior vertebra (not shown).

Locking screws **1052**, **1054**, **1056**, **1058** are each disposed adjacent to a respective through-opening **1044**, **1046**, **1048**, **1050**. Each locking screw **1052**, **1054**, **1056**, **1058** has a head **1060** with an arcuate cutout **1062**, respectively, that is sized to allow the securing screws discussed above to be inserted into through-openings **1044**, **1046**, **1048**, **1050**. During insertion of assembly **1000**, locking screws **1052**, **1054**, **1056**, **1058** are in a configuration relative to plate **1004** as shown in FIG. **114**. After the securing screws secure plate **904** to the superior and inferior vertebra, locking screws **1052**, **1054**, **1056**, **1058** are rotated, for example, about 90 degrees, so that heads **1060** each extends over its adjacent securing screws, preventing the securing screws from inadvertently backing out.

A posterior surface **1072** of plate **1004** also includes a pair of superior and inferior slots **1074**, **1076** on opposing sides of through-opening **1070**. Slots **1074**, **1076** accept a prong of an insertion instrument (not shown) during implantation of assembly **1000**, allowing the insertion instrument to be placed into slots **1074**, **1076** so that plate **1004** is held rigidly on the insertion instrument without being able to rotate.

Referring now to FIG. 117, an alternative embodiment of an intervertebral spacer and plate assembly 1100 (“assembly 1100”) is shown. Assembly 1100 includes a spacer 1102 and a plate 1104.

Plate 1102 has a body 1108 that includes a posterior surface 1110. Posterior surface 1110 includes a central through-opening 1112 that is sized to accept an insertion instrument 1106. Through-opening 1112 is threaded to match threads 1114 on a distal end 1116 of insertion instrument 1106. Posterior surface 1110 also includes a pair of concave recesses 1120, 1122, one on either side of through-opening 1112.

Plate 1104 has a body 1130 that includes an anterior surface 1132 for mating with posterior surface 1110 of spacer 1102. Body 1130 includes a through-opening 1134 that extends posteriorly-to-anteriorly through the center of body 1130. Through-opening 1134 has a larger diameter than through-opening 1112 in spacer 1102 to allow distal end 1116 of insertion instrument 1106 to pass therethrough.

Anterior surface 1132 of body 1130 also includes a pair of convex protrusions 1140, 1142, one on either side of through-opening 1134 that extend into recesses 1120, 1122, respectively, when plate 1104 is butted against spacer 1102, forming a solid construct.

Referring now to FIG. 118, an alternative embodiment of an intervertebral spacer and plate assembly 1200 (“assembly 1200”) is shown. Assembly 1200 includes a spacer 1202 and a plate 1204.

Plate 1202 has a body 1208 that includes a posterior surface 1210. Posterior surface 1210 includes a central recess 1212. Posterior surface 1210 also includes a pair of threaded recesses 1220, 1222, one on either side of central recess 1212.

Plate 1204 includes a body 1230 having an anterior surface 1232. A protrusion 1234 extends anteriorly from anterior surface 1232 and is sized to fit into central recess 1212. Body 1230 also includes a pair of lateral through-holes 1236, 1238 that extend through body 1230 and align with threaded recesses 1220, 1222 when protrusion 1234 is inserted into central recess 1212.

To insert assembly 1200 into a patient, an insertion instrument (not shown) having two prongs is inserted through through-holes 1236, 1238 in plate 1204 and threaded into threaded recesses 1220, 1222 in plate 1200. Assembly 1200 is inserted into plate 1204 is secured to a patient, then the insertion tool is unthreaded from threaded recesses 1220, 1222 and removed from assembly 1200.

Referring now to FIG. 119, an alternative embodiment of an intervertebral spacer and plate assembly 1300 (“assembly 1300”) is shown. Assembly 1300 includes a spacer 1302 and a plate 1304. Spacer 1302 includes a body 1308 having a central void 1309 formed therein. A posterior side 1310 of spacer 1302 includes a pair of through-passages 1312, 1314 into void 1309.

Plate 1304 includes a pair of fingers 1320, 1322, each of which extends into one of through-passages 1312, 1314 and into void 1309. When two prongs of an insertion device (not shown) are inserted into through-passages 1312, 1314, fingers 1320, 1322 splay open, temporarily securing plate 1304 to spacer 1302 for insertion. After insertion, when the insertion device is removed, fingers “un-splay” so that plate 1304 is no longer secured to spacer 1302 and spacer 1302 and plate 1304 are two separate entities.

Referring now to FIG. 119, an alternative embodiment of an intervertebral spacer and plate assembly 1300 (“assembly 1300”) is shown. Assembly 1300 includes a spacer 1302 and a plate 1304. Spacer 1302 includes a body 1308 having a

central void 1309 formed therein. A posterior side 1310 of spacer 1302 includes a pair of through-passages 1312, 1314 into void 1309.

Plate 1304 includes a pair of fingers 1320, 1322, each of which extends into one of through-passages 1312, 1314 and into void 1309. When two prongs of an insertion device (not shown) are inserted into through-passages 1312, 1314, fingers 1320, 1322 splay open, temporarily securing plate 1304 to spacer 1302 for insertion. After insertion, when the insertion device is removed, fingers “un-splay” so that plate 1304 is no longer secured to spacer 1302 and spacer 1302 and plate 1304 are two separate entities.

Referring now to FIG. 120, an alternative embodiment of an intervertebral spacer and plate assembly 1400 (“assembly 1400”) is shown. Assembly 1400 includes a spacer 1402 and a plate 1404. Spacer 1402 includes a body 1408. A posterior side 1410 of spacer 1302 includes a pair of blind passages 1412, 1414 extending into body 1408. Each of blind passages 1412, 1414 widens to a receiving portion 1416, 1418, respectively, in a posterior-to-anterior direction.

Plate 1404 includes a pair of through-passages 1420, 1422 extending parallel to each other in a posterior-to-anterior direction such that, when plate 1404 is aligned with spacer 1402, passage 1420 aligns with passage 1412 and passage 1422 aligns with passage 1414.

An insertion device 1406 includes two parallel hollow prongs 1430, 1432. Each prong 1430, 1432 is split posteriorly into two half portions 1430a, 1430b and 1432a, 1432b, each portion 1430a, 1430b, 1432a, 1432b having a lip.

When prongs 1430, 1432 of insertion device 1406 are inserted through through-passages 1420, 1422 and into blind passages 1412, 1414, respectively, and rods (not shown) are inserted through prongs 1430, 1432, prong half portions 1430a, 1430b and 1432a, 1432b splay apart so that the lips on prongs 1430, 1432 splay open and are retained within receiving portions 1416, 1418, respectively, temporarily securing plate 1404 to spacer 1402 for insertion. After insertion, when the insertion device is removed, fingers “un-splay” so that plate 1404 is no longer secured to spacer 1402 and spacer 1402 and plate 1404 are two separate entities.

Referring now to FIG. 121, an alternative embodiment of an intervertebral spacer and plate assembly 1500 (“assembly 1500”) is shown. Assembly 1500 includes a spacer 1502 and a plate 1504. Spacer 1502 includes a body 1508 having a central void 1509 formed therein. A posterior side 1510 of spacer 1502 includes a pair of through-passages 1512, 1514 into void 1509.

Plate 1504 includes parallel through-passages 1516, 1518 extending parallel to each other in a posterior-to-anterior direction such that, when plate 1504 is aligned with spacer 1502, passage 1516 aligns with passage 1412 and passage 14221518 aligns with passage 1514.

Insertion device 1506 includes a pair of fingers 1520, 1522, each of which extends through one of through-passages 1516, 1518 and one of through-passages 1512, 1514 and into void 1509. Each finger 1520, 1522 includes a laterally extending lip 1524, 1526, respectively.

When two prongs of an insertion device (not shown) are inserted into through-passages 1516, 1518 and 1512, 1514, with the prongs on medial sides of each of fingers 1520, 1522, fingers 1520, 1522 are biased laterally so that lips 1524, 1526 engage the posterior wall of void 1509, temporarily securing plate 1504 to spacer 1502 for insertion. After insertion, when the insertion device 1506 is removed, fingers 1520, 1522 bias back toward each other so that plate 1504

is no longer secured to spacer **1502** and spacer **1502** and plate **1504** are two separate entities.

Referring now to FIG. **122**, an alternative embodiment of an intervertebral spacer and plate assembly **1600** (“assembly **1600**”) is shown. Assembly **1600** includes a spacer **1602** and a plate **1604**. Spacer **1602** includes a body **1608**. A posterior side **1610** of spacer **1602** includes a blind slot **1612** extending into body **1608**. Slot **1612** includes lateral sidewalls **1614**, **1616**.

Plate **1604** includes a tab **1620** sized to fit into slot **1612** with lateral space on either side of tab **1620** to accommodate fingers **1622**, **1624**. Biased fingers **1622**, **1624** are pivotally connected to spacer **1604** with anterior ends **1626**, **1628** having a plurality of laterally extending fingers **1630**. Posterior ends **1632**, **1634** of fingers **1622**, **1624** are engageable by an insertion device (not shown)

During insertion, fingers **1622**, **1624** are against lateral sidewalls **1614**, **1616** of slot **1612** so that plate **1604** is engaged with spacer **1602**. Fingers **1630** compress toward their respective fingers **1622**, **1624**, wedging spacer **1604** into spacer **1602**. After assembly **1600** is inserted, the insertion device is removed, allowing fingers **1622**, **1624** to bias away from sidewalls **1614**, **1616**, respectively, releasing spacer **1602** from plate **1604**.

Referring now to FIGS. **123-125**, an alternative embodiment of an intervertebral spacer and plate assembly **1700** (“assembly **1700**”) is shown. Assembly **1700** includes a spacer **1702** and a plate **1704**. Spacer **1702** includes a body **1708** having a central void **1709** formed therein. A superior surface **1710** of spacer **1702** includes a central slot **1712** extending along a posterior surface **1714** to void **1709**. Similarly, an inferior surface **1720** includes a corresponding slot **1722**.

Referring to FIG. **123**, plate **1704** includes a slot **1730** extending along a top surface **1732** thereof and a slot **1734** extending along a bottom surface **1736** thereof. Plate **1704** includes a pair of screw opening **1740**, **1742** and a centrally located blocking screw **1744**. An alternative embodiment of a plate **1704'**, shown in FIG. **124**, uses multiple blocking screws **1740'**, **1744'**, each for an individual screw opening **1740'**, **1742'**, with locking screws **1744'**, **1746'** disposed laterally away from a center of plate **1740'** to allow plate **1740'** to be thinner than plate **1740** and still be able to secure screws (not shown) in screw openings **1740'**, **1742'**.

FIG. **125** shows in insertion device **1706** gripping both spacer **1702** and either plate **1704** or plate **1704'**. Insertion device **1706** extends through slots **1730**, **1712** and slots **1734**, **1722**, securing spacer **1702** and plate **1704**, **1704'** to securing device **1706**. After insertion, insertion device **1704** is slid posteriorly, decoupling spacer **1702** and plate **1704**, **1704'**.

Referring to FIGS. **126** and **127**, an alternative embodiment of an intervertebral spacer and plate assembly **1800** (“assembly **1800**”) is shown. Assembly **1800** includes a spacer **1802** and a plate **1804**. Spacer **1802** includes a body **1810** having a posterior portion **1812**. Posterior portion **1812** includes a space **1814** that is sized to receive plate **1804**. Plate **1804** can be inserted into space **1814** from a posterior direction or from a superior direction.

Spacer **1802** can include connections for an insertion device (not shown) similar to that disclosed with respect to spacer **102**, described above. Assembly **1800** can be inserted as a unit and then, after insertion, the insertion device is removed and spacer **1802** and plate **1804** remain as separate components in the patient’s spinal column.

Referring to FIGS. **128-130** an alternative embodiment of an intervertebral spacer and plate assembly **1900** (“assembly

1900”) is shown. Assembly **1900** includes a spacer **1902** and a plate **1904** or plate **1904'**. Spacer **1902** includes a body **1910** having a posterior portion **1912**. Posterior portion **1912** includes a threaded opening **1914** that is sized to receive an insertion tool (not shown). Each of plates **1904**, **1904'** include a threaded connection **1920**, **1920'** extending there-through. Threaded connections **1920**, **1920'** accept a threaded insertion device (not shown) that extends through plate **1904**, **1904'** and into threaded opening **1914** in plate **1902**. The threaded connection between the insertion device and spacer **1902** and plate **1904**, **1904'** can be loose to provide for articulation during insertion, similar to the movement of a joystick. Once assembly **1900** is inserted, the insertion device is removed, and spacer **1902** and plate **1904**, **1904'** remain as separate components in the patient’s spinal column.

All of spacers **102-1902** described above can be constructed from biocompatible material, such as, for example, bone, PEEK, titanium, with or without surface treatments, and with varying porosity.

In some embodiments, any of the plates and spacers described above can be accompanied by other surgical implants, including rods and screws. One of skill in the art will appreciate that any of the plates and spacers can be used on multiple levels of the spine.

It will be further understood that various changes in the details, materials, and arrangements of the parts which have been described and illustrated in order to explain the nature of this invention may be made by those skilled in the art without departing from the scope of the invention as expressed in the following claims.

What is claimed is:

1. A surgical method comprising:

- (a) attaching a plate to an insertion tool, the insertion tool comprising a first distal finger and a second distal finger, wherein the first distal finger is threaded;
 - (b) attaching an intervertebral spacer to the insertion tool, wherein the spacer has a U-shaped body with a first lateral portion and a second lateral portion, wherein the first lateral portion includes a tubular protrusion that defines an internally threaded passage, and the first distal finger is threadedly connected to the internally threaded passage of the tubular protrusion;
 - (c) delivering the plate and the intervertebral spacer to a surgical site in a patient via the insertion tool;
 - (d) inserting the intervertebral spacer within a disc space;
 - (e) attaching the plate to one or more vertebral bodies adjacent the disc space; and
- removing the insertion tool such that the intervertebral spacer and the plate are decoupled from each other at the surgical site
- wherein the insertion tool is configured to be inserted through the plate into the spacer.

2. The method according to claim 1, wherein step (a) further comprises sliding the plate onto each of the first finger and the second finger.

3. The method according to claim 1, wherein the first finger is parallel to the second finger.

4. The method according to claim 1, wherein step (b) comprises attaching the intervertebral spacer to each of the first finger and the second finger.

5. The method according to claim 4, wherein step (b) further comprises threadingly inserting the second finger into the intervertebral spacer.

6. The method according to claim 4, wherein the first finger is bore rod configured to pass into the plate and the

23

second finger includes rod having a threaded end configured to thread into the plate and the intervertebral spacer.

7. The method according to claim 6, wherein step (b) further comprises threading the rod of the second finger into a through-hole of the intervertebral spacer.

8. The method according to claim 1, further comprising the step of (g) inserting graft material into the intervertebral spacer.

9. The method according to claim 1, wherein the plate comprises an anterior surface and wherein the intervertebral spacer comprises a posterior surface and wherein step (b) comprises engaging the anterior surface with the posterior surface.

10. A surgical method comprising:

- (a) attaching a plate and an intervertebral spacer to an insertion instrument, wherein the insertion instrument comprises a first distal finger and a second distal finger, and the first distal finger is threaded, and wherein the spacer has a U-shaped body with a first lateral portion and a second lateral portion, the first lateral portion includes a tubular protrusion that defines an internally threaded passage, and the first distal finger is connected to the passage of the tubular protrusion;
- (b) delivering the insertion instrument with the plate and the intervertebral spacer to a surgical site; and
- (c) implanting the plate and the intervertebral spacer at or near the surgical site, wherein the plate and the intervertebral spacer are not attached to one another following implantation

wherein the insertion tool is configured to be inserted through the plate into the spacer.

24

11. The method according to claim 10, wherein step (a) is performed in the absence of securing the plate to the intervertebral spacer.

12. The method according to claim 10, wherein the plate comprises a first through-opening and a second through-opening and wherein step (a) comprises inserting the insertion instrument through the first through-opening and the second through-opening and into the intervertebral spacer.

13. The method according to claim 12, wherein step (a) further comprises threading the insertion instrument into the plate.

14. The method according to claim 12, wherein step (a) further comprises threading the insertion tool into the intervertebral spacer.

15. The method according to claim 10, wherein the second distal finger comprises an unthreaded finger and wherein step (a) comprises inserting the unthreaded finger through the plate and into the intervertebral spacer.

16. The method according to claim 10, further comprising the step of (d) removing the insertion instrument such that the intervertebral spacer is separate from the connecting plate.

17. The method according to claim 16, wherein the intervertebral spacer is inserted between two adjacent vertebrae.

18. The method according to claim 10, wherein the intervertebral spacer is implanted in a disc space between two vertebrae and at least a portion of the plate is implanted outside of the disc space.

* * * * *