



US007815651B2

(12) **United States Patent**
Skakoon et al.

(10) **Patent No.:** **US 7,815,651 B2**
(45) **Date of Patent:** **Oct. 19, 2010**

(54) **DEVICE FOR IMMOBILIZING A PRIMARY INSTRUMENT AND METHOD THEREFOR**

(58) **Field of Classification Search** 600/372-384, 600/386, 393, 188; 606/108, 129, 130; 607/115
See application file for complete search history.

(75) Inventors: **James G. Skakoon**, St. Paul, MN (US); **Robert Wharen**, Ponte Vendra Beach, FL (US); **Matthew S. Solar**, Indialantic, FL (US); **Kari Parmer**, Melbourne, FL (US); **Rudy A. Mazzocchi**, Indian Harbor Beach, FL (US); **John David**, Malabar, FL (US); **Frank Murdock**, Indialantic, FL (US); **David Hatcher**, Palm Bay, FL (US); **Thomas I. Miller**, Palm Bay, FL (US); **Timothy Alan Parmer**, Melbourne, FL, FL (US); **Charles L. Truwit**, Wayzata, MN (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

431,187 A 7/1890 Foster

(Continued)

FOREIGN PATENT DOCUMENTS

DE 3108766 9/1982

(Continued)

OTHER PUBLICATIONS

International Search Report and Written Opinion for PCT/US05/43651 mailed May 8, 2008.

(Continued)

Primary Examiner—Todd E Manahan
Assistant Examiner—Christopher Schubert
(74) *Attorney, Agent, or Firm*—Harness, Dickey & Pierce, PLC

(73) Assignees: **Medtronic, Inc.**, Minneapolis, MN (US); **Mayo Foundation for Medical Education and Research**, Rochester, MN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 575 days.

(21) Appl. No.: **11/768,065**

(22) Filed: **Jun. 25, 2007**

(65) **Prior Publication Data**

US 2007/0250075 A1 Oct. 25, 2007

Related U.S. Application Data

(60) Division of application No. 10/175,668, filed on Jun. 20, 2002, now Pat. No. 7,235,084, which is a continuation of application No. 09/828,451, filed on Apr. 6, 2001, now Pat. No. 7,204,840.

(60) Provisional application No. 60/195,663, filed on Apr. 7, 2000.


(51) **Int. Cl.**
A61B 19/00 (2006.01)

(52) **U.S. Cl.** 606/130

(57) **ABSTRACT**

Devices and methods provide accurate targeting, placement, and/or stabilization of an electrode or other instrument(s) into the brain or other body organ, such as to treat severe tremor or other neurological disorders. Targeting is performed using any form of image-guidance, including real-time MRI, CT, or frameless surgical navigation systems.

18 Claims, 36 Drawing Sheets



U.S. PATENT DOCUMENTS							
438,801	A	10/1890	Delehanty	4,809,694	A	3/1989	Ferrara
873,009	A	12/1907	Baxter	4,824,436	A	4/1989	Wolinsky
1,129,333	A	2/1915	Clarke	4,826,487	A	5/1989	Winter
1,664,210	A	3/1928	Hall	4,869,247	A	9/1989	Howard, III et al.
2,119,649	A	6/1938	Roosen	4,883,053	A	11/1989	Simon
2,135,160	A	11/1938	Beekhuis	4,896,673	A	1/1990	Rose et al.
2,497,820	A	2/1950	Kielland	4,902,129	A	2/1990	Siegmund et al.
2,686,890	A	8/1954	Davis	4,922,924	A	5/1990	Gambale et al.
3,010,347	A	11/1961	Kron	4,955,891	A	9/1990	Carol
3,016,899	A	1/1962	Stenvall	4,957,481	A	9/1990	Gatenby
3,017,887	A	1/1962	Heyer	4,986,280	A	1/1991	Marcus et al.
3,055,370	A	9/1962	McKinney et al.	4,986,281	A	1/1991	Preves et al.
3,055,371	A	9/1962	Kulick et al.	4,989,608	A	2/1991	Ratner
3,115,140	A	12/1963	Volkman	4,991,579	A	2/1991	Allen
3,135,263	A	6/1964	Connelley, Jr.	4,998,938	A	3/1991	Ghajar et al.
3,223,087	A	12/1965	Vladyka et al.	5,006,122	A	4/1991	Wyatt et al.
3,262,452	A	7/1966	Hardy et al.	5,024,236	A	6/1991	Shapiro
3,273,559	A	9/1966	Evans	5,027,818	A	7/1991	Bova et al.
3,282,152	A	11/1966	Myer	5,030,223	A	7/1991	Anderson et al.
3,402,710	A	9/1968	Paleschuck	5,050,608	A	9/1991	Watanabe et al.
3,444,861	A	5/1969	Schulte	5,052,329	A	10/1991	Bennett
3,457,922	A	7/1969	Ray	5,054,497	A	10/1991	Kapp et al.
3,460,537	A	8/1969	Zeis	5,057,084	A	10/1991	Ensminger et al.
3,508,552	A	4/1970	Hainault	5,057,106	A	10/1991	Kasevich et al.
3,672,352	A	6/1972	Summers	5,065,761	A	11/1991	Pell
3,760,811	A	9/1973	Andrew et al.	5,078,140	A	1/1992	Kwoh
3,817,249	A	6/1974	Nicholson	5,078,142	A	1/1992	Siczek et al.
3,893,449	A	7/1975	Lee et al.	5,080,662	A	1/1992	Paul
3,981,079	A	9/1976	Lenczycki	5,087,256	A	2/1992	Taylor et al.
4,013,080	A	3/1977	Froning	5,099,846	A	3/1992	Hardy
4,026,276	A	5/1977	Chubbuck	5,102,402	A	4/1992	Dror et al.
4,040,427	A	8/1977	Winnie	5,116,344	A	5/1992	Sundqvist et al.
4,131,257	A	12/1978	Sterling	5,116,345	A	5/1992	Jewell et al.
4,230,117	A	10/1980	Anichkov et al.	5,120,322	A	6/1992	Davis et al.
4,265,252	A	5/1981	Chubbuck et al.	5,125,888	A	6/1992	Howard et al.
4,312,337	A	1/1982	Donohue	5,142,930	A	9/1992	Allen et al.
4,318,401	A	3/1982	Zimmerman	5,143,086	A	9/1992	Duret et al.
4,328,813	A	5/1982	Ray	5,154,179	A	10/1992	Ratner
4,341,220	A	7/1982	Perry	5,154,723	A	10/1992	Kubota et al.
4,345,606	A	8/1982	Littleford	5,163,430	A	11/1992	Carol
4,350,159	A	9/1982	Gouda	5,166,875	A	11/1992	Machida et al.
4,355,645	A	10/1982	Mitani et al.	5,171,217	A	12/1992	March et al.
4,386,602	A	6/1983	Sheldon et al.	5,174,297	A	12/1992	Daikuzono et al.
4,418,894	A	12/1983	Maillet et al.	5,186,174	A	2/1993	Schlondorff et al.
4,448,195	A	5/1984	LeVeen et al.	5,201,742	A	4/1993	Hasson
4,463,758	A	8/1984	Patil et al.	5,207,223	A	5/1993	Adler
4,475,550	A	10/1984	Bremer et al.	5,207,688	A	5/1993	Carol
4,483,344	A	11/1984	Atkov et al.	5,211,165	A	5/1993	Dumoulin et al.
4,571,750	A	2/1986	Barry	5,221,264	A	6/1993	Wilk et al.
4,572,198	A	2/1986	Codrington	5,222,499	A	6/1993	Allen et al.
4,579,120	A	4/1986	MacGregor	5,230,338	A	7/1993	Allen et al.
4,592,352	A	6/1986	Patil	5,230,623	A	7/1993	Guthrie et al.
4,598,708	A	7/1986	Beranek	5,242,415	A	9/1993	Kantrowitz et al.
4,608,977	A	9/1986	Brown	5,246,448	A	9/1993	Chang
4,617,925	A	10/1986	Laitinen et al.	5,257,998	A	11/1993	Ota et al.
4,618,978	A	10/1986	Cosman	5,263,939	A	11/1993	Worrich
4,629,451	A	12/1986	Winters et al.	5,263,956	A	11/1993	Nobles
4,638,798	A	1/1987	Shelden et al.	5,267,970	A	12/1993	Chin et al.
4,660,563	A	4/1987	Lees	5,269,305	A	12/1993	Corol
4,665,928	A	5/1987	Linial et al.	5,279,309	A	1/1994	Taylor et al.
4,699,616	A	10/1987	Nowak et al.	5,279,575	A	1/1994	Sugarbaker
4,705,436	A	11/1987	Robertson et al.	5,280,427	A	1/1994	Magnusson et al.
4,706,665	A	11/1987	Gouda	5,290,266	A	3/1994	Rohling et al.
4,733,661	A	3/1988	Palestrant	5,291,890	A	3/1994	Cline et al.
4,755,642	A	7/1988	Parks	5,300,080	A	4/1994	Clayman et al.
4,791,934	A	12/1988	Brunnett	5,305,203	A	4/1994	Raab et al.
4,793,355	A	12/1988	Crum et al.	5,306,272	A	4/1994	Cohen et al.
4,798,208	A	1/1989	Faasse, Jr.	5,309,913	A	5/1994	Kormos et al.
4,805,615	A	2/1989	Carol	5,330,485	A	7/1994	Clayman et al.
4,805,634	A	2/1989	Ullrich et al.	5,330,485	A	7/1994	Clayman et al.
4,807,620	A	2/1989	Strul et al.	5,354,283	A	10/1994	Bark et al.
				5,361,763	A	11/1994	Kao et al.
				5,366,446	A	11/1994	Tal et al.
				5,375,588	A	12/1994	Yoon

5,375,596 A	12/1994	Twiss et al.	6,058,323 A	5/2000	Lemelson
5,380,302 A	1/1995	Orth	6,071,288 A	6/2000	Carol et al.
5,383,454 A	1/1995	Bucholz	6,076,008 A	6/2000	Bucholz
5,387,220 A	2/1995	Pisharodi	6,079,681 A	6/2000	Stern et al.
5,394,457 A	2/1995	Leibinger et al.	6,110,182 A	8/2000	Mowlai-Ashtiani
5,405,330 A	4/1995	Zunitch et al.	6,117,143 A	9/2000	Hynes et al.
5,423,832 A	6/1995	Gildenberg	6,120,465 A	9/2000	Guthrie et al.
5,423,848 A	6/1995	Washizuka et al.	6,135,946 A	10/2000	Konen et al.
5,445,166 A	8/1995	Taylor	6,179,826 B1	1/2001	Aebischer et al.
5,452,720 A	9/1995	Smith et al.	6,195,577 B1	2/2001	Truwit et al.
5,464,446 A	11/1995	Dreessen et al.	6,206,890 B1	3/2001	Truwit
5,470,307 A	11/1995	Lindall	6,210,417 B1	4/2001	Baudino et al.
5,474,564 A	12/1995	Clayman et al.	6,231,526 B1	5/2001	Taylor et al.
5,483,961 A	1/1996	Kelly et al.	6,236,875 B1	5/2001	Bucholz et al.
5,494,034 A	2/1996	Schlondorff et al.	6,238,402 B1	5/2001	Sullivan, III et al.
5,494,655 A	2/1996	Rocklage et al.	6,254,532 B1	7/2001	Paolitto et al.
5,515,160 A	5/1996	Schulz et al.	6,257,407 B1	7/2001	Truwit et al.
5,517,990 A	5/1996	Kalfas et al.	6,261,300 B1	7/2001	Carol et al.
5,528,652 A	6/1996	Smith et al.	6,267,769 B1	7/2001	Truwit
5,541,377 A	7/1996	Stuhlmacher	6,267,770 B1	7/2001	Truwit
5,572,905 A	11/1996	Cook, Jr.	6,273,896 B1	8/2001	Franck et al.
5,572,999 A	11/1996	Funda et al.	6,282,437 B1	8/2001	Franck et al.
5,575,798 A	11/1996	Koutrouvelis	6,290,644 B1	9/2001	Green, II et al.
5,618,288 A	4/1997	Calvo et al.	6,298,262 B1	10/2001	Franck et al.
5,622,170 A	4/1997	Schulz	6,315,770 B1	11/2001	de la Torre et al.
5,638,819 A	6/1997	Manwaring et al.	6,321,104 B1	11/2001	Gielen et al.
5,639,276 A	6/1997	Weinstock et al.	6,327,491 B1	12/2001	Franklin et al.
5,643,286 A	7/1997	Warner et al.	6,356,792 B1	3/2002	Errico et al.
5,647,361 A	7/1997	Damadian	6,368,329 B1	4/2002	Truwit
5,649,936 A	7/1997	Real	6,400,992 B1	6/2002	Borgersen et al.
5,658,272 A	8/1997	Hasson	6,457,963 B1	10/2002	Tawara et al.
5,662,600 A	9/1997	Watson et al.	6,482,182 B1	11/2002	Carroll et al.
5,667,514 A	9/1997	Heller	6,488,620 B1	12/2002	Seegermark et al.
5,695,501 A	12/1997	Carol et al.	6,491,699 B1	12/2002	Henderson et al.
5,713,858 A	2/1998	Heruth et al.	6,529,765 B1	3/2003	Franck et al.
5,755,697 A	5/1998	Jones et al.	6,537,232 B1	3/2003	Kucharczyk et al.
5,776,064 A	7/1998	Kalfas et al.	6,546,277 B1	4/2003	Franck et al.
5,776,143 A	7/1998	Adams et al.	6,546,279 B1	4/2003	Bova et al.
5,776,144 A	7/1998	Leysieffer et al.	6,547,795 B2	4/2003	Schneiderman
5,788,713 A	8/1998	Dubach et al.	6,556,857 B1	4/2003	Estes et al.
5,807,033 A	9/1998	Benway	6,609,020 B2	8/2003	Gill et al.
5,809,694 A	9/1998	Postans et al.	6,610,100 B2	8/2003	Phelps et al.
5,810,712 A	9/1998	Dunn	6,632,184 B1	10/2003	Truwit
5,817,106 A	10/1998	Real	6,655,014 B1	12/2003	Babini
5,823,975 A	10/1998	Stark et al.	6,662,035 B2	12/2003	Sochor
5,833,627 A	11/1998	Shmulewitz et al.	6,676,669 B2	1/2004	Charles et al.
5,843,150 A	12/1998	Dreessen et al.	6,706,050 B1	3/2004	Giannadakis
5,851,183 A	12/1998	Bucholz	6,726,678 B1	4/2004	Nelson et al.
5,865,817 A	2/1999	Moening et al.	6,746,471 B2	6/2004	Mortier et al.
5,865,842 A	2/1999	Knuth et al.	6,752,812 B1	6/2004	Truwit
5,871,445 A	2/1999	Bucholz	6,765,122 B1	7/2004	Stout
5,871,487 A	2/1999	Warner et al.	6,773,443 B2	8/2004	Truwit et al.
5,873,822 A	2/1999	Ferre et al.	6,782,288 B2	8/2004	Truwit et al.
5,891,034 A	4/1999	Bucholz	6,802,323 B1	10/2004	Truwit et al.
5,891,157 A	4/1999	Day et al.	6,902,569 B2	6/2005	Parmer et al.
5,927,277 A	7/1999	Baudino et al.	6,913,478 B2	7/2005	Lamirey et al.
5,950,629 A	9/1999	Taylor et al.	6,944,895 B2	9/2005	Truwit
5,954,687 A	9/1999	Baudino	6,960,216 B2	11/2005	Kolb et al.
5,957,933 A	9/1999	Yanof et al.	7,204,840 B2	4/2007	Skakoon et al.
5,957,934 A	9/1999	Rapoport et al.	7,366,561 B2	4/2008	Mills et al.
5,964,705 A	10/1999	Truwit et al.	7,479,146 B2	1/2009	Malinowski
5,980,535 A	11/1999	Barnett et al.	2001/0014771 A1	8/2001	Truwit et al.
5,984,930 A	11/1999	Maciunas et al.	2001/0027271 A1	10/2001	Franck et al.
5,993,463 A	11/1999	Truwit	2001/0037524 A1	11/2001	Truwit
5,997,471 A	12/1999	Gumb et al.	2002/0010479 A1	1/2002	Skakoon et al.
6,006,126 A	12/1999	Cosman	2002/0019641 A1	2/2002	Truwit
6,018,094 A	1/2000	Fox	2002/0022847 A1	2/2002	Ray et al.
6,021,343 A	2/2000	Foley et al.	2002/0052610 A1	5/2002	Skakoon et al.
6,024,729 A	2/2000	Dehdashtian et al.	2002/0077646 A1	6/2002	Truwit et al.
6,030,223 A	2/2000	Sugimori	2002/0156372 A1	10/2002	Skakoon et al.
6,039,725 A	3/2000	Moening et al.	2003/0079287 A1	5/2003	Truwit
6,042,540 A	3/2000	Johnston et al.	2003/0187351 A1	10/2003	Franck et al.
6,044,304 A	3/2000	Baudino	2003/0208122 A1	11/2003	Melkent et al.

2004/0026161	A1	2/2004	Takatsuka et al.
2004/0059260	A1	3/2004	Truwit
2004/0176750	A1	9/2004	Nelson et al.
2004/0243147	A1	12/2004	Lipow
2004/0255991	A1	12/2004	Truwit et al.
2004/0260323	A1	12/2004	Truwit et al.
2004/0267284	A1	12/2004	Parmer et al.
2006/0192319	A1	8/2006	Solar
2006/0195119	A1	8/2006	Mazzocchi et al.
2007/0250078	A1	10/2007	Stuart
2007/0299427	A1	12/2007	Yeung et al.
2008/0004632	A1	1/2008	Sutherland et al.

FOREIGN PATENT DOCUMENTS

DE	3937052	5/1990
DE	19726141	1/1999
DE	29612100	8/1999
DE	19808220	9/1999
DE	19820808	9/1999
DE	19826078	11/1999
EP	0386936	5/1990
EP	0427358	5/1991
EP	0724865	5/1991
EP	0609085	8/1994
EP	0832611	4/1998
EP	0904741	3/1999
GB	2237993	5/1991
GB	2329473	4/1998
GB	2346573	8/2000
WO	WO-8809151	12/1988
WO	WO-9522297	8/1995
WO	WO-9610368	4/1996
WO	WO-9633766	10/1996
WO	WO-9703609	2/1997
WO	WO-9721380	6/1997
WO	WO-9742870	11/1997
WO	WO-9817191	4/1998
WO	WO-9825535	6/1998
WO	WO-9851229	11/1998
WO	WO-0001316	1/2000
WO	WO-0018306	1/2000
WO	WO-0124709	4/2001
WO	WO-0149197	7/2001
WO	WO-0176498	7/2001
WO	WO-2004026161	A2 4/2004

OTHER PUBLICATIONS

"Cross-Hairs Kit", Elekta Instruction for Use Brochure, pp. 2-5.

"CRW™—Tyco Healthcare Radionics", Tyco Product Brochure, pp. 1-7.

"Fathom Remote Introducer", Image-Guided Neurologics, Inc., CNS Hynes Convention Center, 2p., (Oct. 30-Nov. 4, 1999).

"Inomed Competence in Neurophysologic Monitoring", <http://www.inomed.com/english/index.htm>, (observed Mar. 23, 2004), 2 pgs.

"Leksell Stereotactic System", Elekta Product Brochure, pp. 1-6.

"MicroTargeting® Precision Guidance Using Microelectrode Recording", (Aug. 15, 2003), 5 pgs.

"Possible Existence of Common Internalization Mechanisms among Arginine-rich Peptides", Suzuki, T. et al., *Journal of Biological Chemistry*, vol. 277, No. 4 (2002) pp. 2437-2443.

Allison, S., et al., "Microchannel Plate Intensifier Response in Traverse Magnetic Field", *Electronic Letters*, 26, (Jun. 7, 1990), 770-771.

Drake, J.M., et al. "ISG Viewing Wand System", *Neurosurgery*, 34 (6), (Jun. 1994), 1094-1097.

Dyer, P.V., et al., "The ISG Viewing Wand: an Application to Atlanto-Axial Cervical Surgery Using the Le For I Maxillary Osteotomy", *British Journal of Oral and Maxillofacial Surgery*, 33, (1995), 370-374.

Franck Joel, et al., "microTargeting® Platform System incorporating StarFix™ guidance", *microTargeting*, pp. 1-44.

Franck, Joel, et al., "microTargeting® Platform incorporating StarFix™ guidance", *microTargeting*, 3 pgs.

Gehring, W. J., "Homeodomain Proteins", *Annu. Rev. Biochem.*, vol. 63 (1997) pp. 487-526.

Gillies, G., et al., "Magnetic Manipulation Instrumentation for Medical Physics Research", *Review of Scientific Instruments*, 65 (3), Review Article, (Mar. 1994), 533-562.

Grady, M., "Nonlinear Magnetic Stereotaxis: Three-Dimensional, in vivo Remote Magnetic Manipulation of a Small Object in Canine Brain", *Medical Physics*, 17 (3), (May/Jun. 1990), pp. 405-415.

Grady, M., et al., "Initial Experimental Results of a New Stereotaxic Hyperthermia System", *American College of Surgeons: 1998 Clinical Congress: Surgical Forum*, 39, (1998), 507-509.

Grady, M., et al., "Magnetic Stereotaxis System for Neurosurgical Procedures", *Proc. 37th International Instrumentation Symp.*, Sand Diego, CA (May 1991), 665-675.

Grady, M., et al., "Magnetic Stereotaxis: A Technique to Deliver Stereotactic Hyperthermia", *Neurosurgery*, 27 (6), Technical Note, (Dec. 1990), pp. 1010-1016.

Grady, M., et al., "Preliminary Experimental Investigation of in vivo Magnetic Manipulation: Results and Potential Application in Hyperthermia", *medical Physics*, 16 (2), (Mar./Apr. 1989), pp. 263-272.

Hata, N., et al., "Needle Insertion Manipulator for CT-and MR-Guided Stereotactic Neurosurgery", *Interventional MR: Techniques and Clinical Experience*, St. Louis: London: Mosby; Martin Dunitz, F. Jolesz and I. Young, eds., (1998), 99-106.

Hirschberg, H., et al., "Image-Guided Neurosurgery—MR compatible stereotactic equipment", <http://www.medinnova.no/English/P51466ster.html>, (Mar. 29, 2001), 1p.

Hirschberg, Henry, et al., "Image-guided neurosurgery", stereotactic equipment for MR imaging, <http://www.medinnova.no/English/P51466ster.html>, (Observed Mar. 8, 2002), 1 page.

Howard, M., et al., "Magnetic Movement of a Brain Thermoceptor", *Neurosurgery*, 24 (3), (1989), 444-448.

Howard, M., et al., "Magnetic Neurosurgery", *Stereotactic and Functional Neurosurgery*, 66, (1996), 102-107.

Howard, M., et al., "Magnetic Neurosurgery: Image-Guided, Remote-Controlled Movement of Neurosurgical Implants", Ch. 26 in: *Clinical Neurosurgery: Proceedings of the Congress of Neurological Surgeons*, San Francisco, CA, (1995), 382-391.

Howard, M., et al., "Review of Magnetic Neurosurgery Research", *J. Image Guided Surgery*, 1, (Nov. 1995), 295-299.

Lawson, M., et al., "Near Real-Time Bi-planar Fluoroscopic Tracking System for the Video Tumor Fighter", *SPIE*, 1445, (1991), 265-275.

Leggett, W.B., et al. "Surgical Technology—The Viewing Wand: A New System for Three-Dimensional Computed Tomography-Correlated Intraoperative Localization", *Current Surgery*, (Dec. 1991), 674-678.

Malison, R.T., et al., "Computer-Assisted Coregistration of Multislice SPECT and MR Brain Images by Fixed External Fiducials", *Journal of Computer Assisted Tomography*, 17 (6), (1993), pp. 952-960.

Mannervik, M., "Target genes of homeodomain proteins", *BioEssays* vol. 21.4 (Apr. 1999) pp. 267-270.

McNeil, R., et al., "Characteristics of an Improved Magnetic-Implant Guidance System", *IEEE Transactions on Biomedical Engineering*, 42 (8), (Aug. 1995), 802-808.

McNeil, R., et al., "Functional Design Features and Initial Performance Characteristics of a Magnetic-Implant Guidance System for Stereotactic Neurosurgery", *IEEE Transactions on Biomedical Engineering*, 42 (8), (1995), 793-801.

Meeker, D., et al., "Optimal Realization of Arbitrary Forces in a Magnetic Stereotaxis System," *IEEE Transactions on Magnetics*, 32 (2), (Mar. 1996), 320-328.

Molloy, J., et al., "Experimental Determination of the Force Required for Insertion of a ThermoSeed into Deep Brain Tissues", *Annals of Biomedical Engineering*, 18, (1990), 299-313.

Molly, J., et al., "Thermodynamics of Movable Inductively Heated Seeds for the Treatment of Brain Tumors", *Medical Physics*, 18 (4), (1991), 794-803.

- Oliver, L., "Cup-And-Ball Chemopallidectomy Apparatus", (1958), p. 401.
- Patikoglou, G. et al., "Eukaryotic Transcription Factor-DNA Complexes", *Annual Review of Biophysics and Biomolecular Structure* vol. 26 (1997) pp. 289-325.
- Quate, E., et al., "Goniometric Motion Controller for the Superconducting Coil in a Magnetic Stereotaxis System", *IEEE Transactions on Biomedical Engineering*, 38 (9), (Sep. 1991), 899-905.
- Ramos, P., et al., "Electro-Optic Imaging Chain for a Biplanar Fluoroscope for Neurosurgery: Magnetic Field Sensitivity and Contrast Measurements", *Optical Engineering* 32, (7), (1993), 1644-1656.
- Ramos, P., et al., "Low-Dose, Magnetic Field-Immune, Bi-Planar Fluoroscopy for Neurosurgery", *Proc. SPIE*, 1443 (Medical Imaging V: Image Physics), (1991), 160-170.
- Ramos, P., et al., "Microchannel Plate Image Intensifier Electron Dynamics in Magnetic Field", *Electronics Letters*, 27 (18), (Aug. 29, 1991), pp. 1636-1638.
- Ritter, R., et al., "Magnetic Stereotaxis: Computer-Assisted, Image-Guided Remote Movement of Implants in the Brain", Ch. 26 in: *Computer-Integrated Technology and Clinical Applications*, MIT Press, Cambridge, MA., Taylor, R., et al., eds., (1996), 363-369.
- Ritter, R., et al., "Magnetic Sterotaxis: An Application of Magnetic Control Technology to the Needs of Clinical Medicine", *Proc. Of the MAG'95 Industrial Conf. and Exhibition*, Technomic Pub. Co., Lancaster, PA., Allaire, P., ed., (1995), 186-193.
- Sandeman, D.S., et al., "Advances in image-directed neurosurgery: Preliminary experience with the ISG Viewing Wand compared with the Leksell G frame", *British Journal of Neurosurgery*, 8 (199), pp. 529-544.
- Stein, S. et al., "Checklist: Vertebrate homeobox genes", *Mechanisms of Development*, vol. 55, No. 1 (Mar. 1996) pp. 91-108.
- Szikora, I., et al., "Endovascular Treatment of Experimental Aneurysms with Liquid Polymers: The Protective Potential of Stents", *Neurosurgery*, 38, (Feb. 1996), 339-347.
- Vollmer, J. et al., "Homeobox Genes in the Developing Mouse Brain", *Journal of Neurochemistry*, vol. 71, No. 1 (Jul. 1998) pp. 1-19.
- Wolberger, C., "Homeodomain Interactions", *Current Opinion in Structural Biology* vol. 6, No. 1 (Feb. 1996) pp. 62-68.
- Yeh, H.S., et al., "Implantation of intracerebral depth electrodes for monitoring seizures using the Pelorus stereotactic system guided by magnetic resonance imaging", *J. Neurosurg.*, 78 (1993), pp. 138-141.
- Zinreich, S.J., et al., "Frameless Sterotaxic Integration of CT Imaging Data: Accuracy and Initial Applications", *Radiology*, 188 (3), (1993), pp. 735-742.
- Ritter, R., et al., "Stereotaxie Magnetique: Deplacement D'Implants dans le Cerveau, Assistes par Ordinateur et Guides par Imagerie", *Innovation et Technologie en Biologie et Medecine*, 13, (1992), 437-449.
- Supplementary European Search Report mailed Oct. 26, 2009 for EP05852969 filed Dec. 6, 2005 claiming benefit of U.S. Appl. No. 11/005,907, filed Dec. 5, 2004.
- European Office Action mailed Jan. 22, 2010 for European Application No. 05 852 969.4.




FIG. 2




FIG. 4




FIG. 5




FIG. 6B




FIG. 6A




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19A




FIG. 19B




FIG. 20




FIG. 21




FIG. 22




FIG. 24




FIG. 23




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32A




FIG. 32B




FIG. 33A




FIG. 33B




FIG. 33C




FIG. 34A




FIG. 34B




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39

DEVICE FOR IMMOBILIZING A PRIMARY INSTRUMENT AND METHOD THEREFOR

CROSS-REFERENCE TO RELATED APPLICATION

This application is a divisional application of U.S. patent application Ser. No. 10/175,668, filed Jun. 20, 2002, which issues on Jun. 26, 2007 as U.S. Pat. No. 7,235,084, which application is a continuation application of U.S. application Ser. No. 09/828,451, now U.S. Pat. No. 7,204,840, filed Apr. 6, 2001, which patent application claims the benefit of priority, under 35 U.S.C. Section 119(e), to U.S. Provisional Patent Application Ser. No. 60/195,663, filed Apr. 7, 2000, the disclosure of which is incorporated herein by reference in its entirety.

FIELD OF THE INVENTION

This document relates generally to, among other things, surgical placement of a medical instrument deeply into an organ, such as a brain, and specifically, but not by way of limitation, to accurate targeting, placement, and/or acute or chronic stabilization of such an instrument.

BACKGROUND

In placing a medical device or instrument deeply into an organ, such as a brain, it is often advantageous to precisely target, place, and then secure the device for a period of time that may be several days or even indefinitely. Examples of such devices include catheters, needles, and drug and biological agent delivery instruments, as well as electrical mapping, stimulating and/or ablation leads.

Targeting such a device is not always an exact science. The target is not always visible from preoperative images. Even when using image-guided minimally invasive techniques, with such imaging modalities magnetic resonance imaging (MRI), computed tomography (CT), frameless surgical navigation systems, and the like, there is often a need for some tweaking or small adjustment in trajectory to accurately hit the target. A single trajectory approach would mean that the need to move the target slightly laterally would require removing the device and then reintroducing it, sometimes as close as 2 mm away from the original entry site.

One approach to positioning an instrument, such as a deep brain stimulation electrode, uses a conventional stereotactic frame system that is secured to the patient. In this approach, preoperative images of the patient are used to determine the proper trajectory to the target, as measured and aligned relative to the frame. Using accessories mounted to the frame, the electrode is aligned and advanced through a burr hole in the skull to the predetermined target. A base is then inserted into and/or around the burr hole. Various "tool holes" and slots in the base are deformed as the base is slid over the electrode. The tool holes in the base are squeezed together as the base is inserted into the burr hole. When the base is released, it springs back outward against the inside diameter of the burr hole. The stereotactic accessories must then be carefully removed while holding the device in place. This step can be clumsy and inexact. If the electrode moves, it must be repositioned. Before securing the carefully-positioned device to the patient, the equipment used to introduce the device and maintain trajectory must be removed. This action can often dislodge the device requiring the entire placement procedure to be repeated. Even after the stereotactic accessories have been removed, the electrode or other device must be secured.

This procedure may also cause electrode movement. In one example, a silicone rubber cap is fit into place to capture and protect the electrode. Placing the rubber cap may cause further electrode movement.

One disadvantage of this approach is that the instrument positioning is attempted using only a presumed target location, based on the preoperative images, and not an actual determination of the needed trajectory to the target. Another disadvantage is that the stereotactic frame system is both expensive and unwieldy. Yet another disadvantage is that the electrode may move at any one of several times during the procedure and therefore require repositioning. For these and other reasons, the present inventors have recognized that there is a need for improved targeting, placement, and secure stabilization of a deep brain electrode or other medical instrument.

SUMMARY

This document discusses, among other things a device and method for instrument targeting, placement, and/or stabilization. This system may be used with any instrument, but it is particularly useful with a deep brain neurological stimulation electrode to treat severe tremor or other disorders. The system allows any of a number of imaging modalities, including MRI, CT, and frameless surgical navigation. The MRI environment typically provides both real-time brain images and real-time MRI imaging of trajectory-alignment fiducial markings, although preoperative MRI images of the brain could also be used. The frameless surgical navigation typically uses retrospective brain images (e.g., previously-acquired preoperative MRI images of the brain) and real-time imaging recognition of trajectory-alignment fiducial markings (e.g., using light-emitting diodes, reflective globes, etc.). Both environments, therefore, provide image-guided alignment of the instrument's trajectory to the target location. Such techniques provide accurate placement of the electrode or other medical instrument. It also provides acute and/or chronic stabilization of the instrument. The system includes, among other things, an alignment/targeting system, an instrument introducer system, and a stabilizer system. Other aspects of the present system and methods will become apparent upon reading the following detailed description of the invention and viewing the drawings that form a part thereof.

BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings, which are not necessarily drawn to scale, like numerals describe substantially similar components throughout the several views. Like numerals having different letter suffixes represent different instances of substantially similar components. The drawings illustrate generally, by way of example, but not by way of limitation, various embodiments discussed in the present document.

FIG. 1 is a cross-sectional view example of an electrode that has been implanted and secured using the devices and methods discussed herein.

FIG. 2 is a perspective view example of a base and a cap.

FIG. 3 is an exploded perspective view example of an assembly of a base, a stabilizer, and a cap.

FIG. 4 is a perspective view example of a stabilizer.

FIG. 5 is an exploded perspective view example of a base, a stabilizer, and a cap.

FIGS. 6A and 6B provide two perspective view examples of a base and a burr-hole centering device.

FIG. 7 is a perspective view example of a tool for placing the stabilizer, securing the introduced instrument, and removing the cap.

FIG. 8 is a perspective view example of an instrument-securing base and an equipment-supporting base.

FIG. 9 is another perspective view example of an instrument-securing base and an equipment-supporting base.

FIG. 10 is a further perspective view example of an instrument-securing base and an equipment-supporting base.

FIGS. 11 and 12 are perspective view examples of a tower-like instrument alignment and introduction guide assembly, also referred to as a deep brain access device.

FIG. 13 is an exploded perspective view example of portions of a deep brain access device.

FIG. 14 is a perspective view example of adjusting an instrument trajectory using portions of a deep brain access device with MRI, CT, or another imaging modality.

FIG. 15 is a perspective view example of adjusting an instrument trajectory using portions of a deep brain access device with a frameless surgical navigational system.

FIG. 16 is a perspective view example of an MRI-imagable alignment stem.

FIG. 17 is a perspective view example of an adapter for receiving a frameless surgical navigation instrument.

FIG. 18 is a perspective view example of a technique for introducing an instrument along the previously established trajectory using a peel-away sheath and stylet.

FIGS. 19A and 19B provide two perspective view examples of a multilumen insert portion of a deep brain access device.

FIG. 20 is a perspective view example of a hub and stylets.

FIG. 21 is a perspective view example of a single peel-away sheath.

FIG. 22 is a perspective view example of a guide bridge mounted onto a multilumen insert of a deep brain access device.

FIG. 23 is a perspective view example of an offset guide bridge.

FIG. 24 is a perspective view example of a center guide bridge.

FIGS. 25 and 26 are perspective view examples, respectively, of a remote introducer mounted onto a deep brain access device.

FIG. 27 is a perspective view alternate example of an instrument-securing base.

FIG. 28 is a perspective view example of a ball-housing socket on a translational stage.

FIG. 29 is a perspective view example of an alternate remote introducer mounted to a deep brain access device.

FIG. 30 is a cross-sectional view example of an alternate deep brain access device.

FIG. 31 is a perspective view example of a ball and inner sleeve with guide lumens.

FIGS. 32A and 32B provide various perspective and cross-sectional view examples of a peel-away sheath with depth markers, a stylet, and a deep brain access device receiving the sheath and stylet.

FIGS. 33A, 33B and 33C provide various perspective and cross-sectional view examples of an alternate stabilizer.

FIGS. 34A and 34B provide various perspective view examples of another alternate stabilizer and accompanying tool.

FIG. 35 provides various perspective and cross-sectional view examples of a guide alternative to the peel-away sheaths.

FIG. 36 provides a perspective and a cross-sectional view examples of a sheath having rotatable components for allowing side access, which is useful as an alternative to the peel-away sheath.

FIG. 37 is a cross-sectional view example of an alternative deep brain access device, mounted to a skull, and a remote introducer mounted to the deep brain access device.

FIG. 38 is a perspective view example of an alternative deep brain access device providing a pivoting base, an arc-like path, and a ball-and-socket movement for adjusting a trajectory of an instrument being introduced into the brain.

FIG. 39 is a perspective view illustrating an alternate example of a multilumen insert including imaging-recognizable fiducial markings.

DETAILED DESCRIPTION

The following detailed description refers to the accompanying drawings, which form a part of this detailed description and illustrate specific embodiments of the invention. These embodiments are described in sufficient detail to enable those skilled in the art to practice the invention. However, other embodiments may be used, thus structural, logical and electrical changes may be made to this description without departing from the spirit and scope of the invention. The following detailed description is, therefore, not to be taken in a limiting sense, as the scope of the invention is defined only by the appended claims.

One example of trajectory guides for surgical applications is discussed in Truwit et al., International Patent Application No. PCT/US98/10008 (International Publication No. WO 98/51229), which is incorporated herein by reference.

FIG. 1 is a cross-sectional view illustrating an example of a flexible primary medical instrument, such as an implanted deep brain neurostimulator electrode 100. FIG. 1 also illustrates portions of a secondary medical device, such as deep brain access device 102, and portions of a patient's brain in which electrode 100 and access device 102 are used. Electrode 100 includes a distal end 100A and a proximal end 100B. Proximal end 100B emerges from under a skin flap of the patient into which it has been inserted. Access device 102 includes, among other things, a base 104 access plate or ring secured concentrically around and/or in a burr hole 106 in the skull. Base 104 provides an access opening that is approximately the same diameter as a standard burr hole. Electrode 100 extends through burr hole 106 into a target location 108 in the brain, and is held in place by stabilizer 110. Access device 102 also includes a substantially rigid cap 112 that covers burr hole 106, stabilizer 110, and base plate 104, and is overlaid by a tapered low profile flexible (e.g., silicone or other elastomer) conformal cap 114 to soften the profile of the implanted apparatuses under the patient's scalp to more closely match the skull surface 116.

A suitable hole in conformal cap 114 and/or the overlying skin flap permits any upturned proximal portion 100B of electrode 100 to be exposed outside the skin flap, if desired. In this example, conformal cap 114 includes an engaging lip that mates with a lip of cap 112 or base 104. This holds conformal cap 114 in place.

In one example, portions of access device 102 allow attachment by other apparatuses during targeting/alignment, positioning, and/or acutely or chronically securing the implanted instrument. Although designed for use with a trajectory alignment system, stabilizer 110 can be used alone to stabilize catheters, needles, and drug and biological agent delivery instruments, as well as electrodes used for any purpose (e.g.,

5

electrical mapping, stimulation, or ablation) that have been placed using alternate targeting and placement methods and systems.

FIG. 2 is a perspective view of an example base 104. In this example, base 104 is attached to the patient's skull by any suitable fastening device, such as bone screws 200A and 200B. Alternatively, base 104 is secured by threads that screw into burr hole 106. Other examples of attachment to the skull or other portions of the patient's body include adhesive, suction and other techniques. Base 104 includes one or more grooves 202 for receiving the proximal end 100B of electrode 100, or other flexible instrument, which is laterally bent into groove 202 for conformally exiting base 104, so that proximal end 100B of electrode 100 lies generally parallel to the skull surface 116. Proximal end 100B of electrode 100 extends along skull surface 116 for a clinically appropriate distance. Cap 112 covers portions of burr hole 106, and the assembly of base 104 and electrode 100. In this example, base 104 includes recesses 204A-B, such as for receiving respective pry lip extensions 206A-B of cap 112.

FIG. 3 is an exploded view illustrating an example of an assembly of base 104, stabilizer 110, and cap 112. Cap 112 includes a relatively larger top 300 and a relatively smaller, generally cylindrical base 302. Cap 112 includes male finger or female receptacle snap-fits 304 (or other attachment device(s)) that are coupled to respective mating female receptacle or male finger snap-fits 306 of base 104 so that, when assembled, cap 112 is coupled to base 104, within its center opening 307, and covers stabilizer 110. The cylindrical base portion 302 of cap 112 includes at least one opening 308 permitting electrode 100 to exit base 104 via groove 202.

In the example of FIG. 3, stabilizer 110 includes a disk 310 coupled to a cam 312. Cam 312 rotates, with respect to disk 310, about an axis perpendicular to the plane of disk 310, to create and substantially close opening 314 in which electrode 100 is either passed freely (when open) or clamped (when closed) Thus, cam 312 is understood to include any form of clamping device. FIG. 3 illustrates cam 312 in its open position. Stabilizer 110 also includes snap-fits or other fastening features for coupling it to base 104. In the example of FIG. 3, stabilizer 110 can be snapped into base 104 in any rotational orientation. That is, the user can rotate stabilizer 110 a full 360 degrees to choose a specific rotational orientation with respect to base 104, and then snap stabilizer 110 into base 104 at that orientation. Moreover, elongate opening 314 extends radially from the center of the disk-like stabilizer 110 to its outer circumference. Along with the full rotational coupling capability of stabilizer 110, this allows an instrument, such as electrode 100, to be clamped within opening 314 in any location over the full area of opening 307 in base 104. This provides additional precision in placing the electrode 100 or other instrument.

FIG. 4 is a perspective view illustrating a closer view of stabilizer 110 in which cam 312 is in a closed position. FIG. 4 also illustrates coupling features 400A-B for coupling stabilizer 110 to base 104. In this example, one or more recesses 402A-B, or other engaging features, is provided. By using a tool that engages at least one of recesses 402A-B, stabilizer 110 can be placed into base 104 and snap-coupled thereto. Cam 312 also includes one or more recess 404, or other engaging feature. By using a tool that engages recess 404, cam 312 can be moved between open and substantially closed positions. In this example, cam 312 also includes a catch 406 that prevents unwanted accidental movement of cam 312 into the open position when cam 312 is intended to be in the closed position to secure electrode 100 or other medical instrument. In this manner, cam 312 locks into the closed position, and is

6

opened by pressing down on a tool engaging recess 404. This allows catch 406 to slide under disk 310.

FIG. 5 is an exploded view of an alternate embodiment in which stabilizer 110 includes strain relief features 500A-B, either of which may be used to secure a small amount of slack in electrode 100 or other instrument. Also in this example, a plurality of grooves 202 in base 104, and a corresponding plurality of grooves 308 in cap 112, allows electrode 100 to laterally exit base 104.

FIGS. 6A and 6B provide two perspective views of an example base positioner 600 device for centering base 104 around burr hole 106 (of known diameter) in the skull. A distal portion 602 of positioner 600 is appropriately sized to be received into center opening 307 of base 104 and further into burr hole 106. This centers base 104 concentrically around burr hole 106. Bone screws 200A-B are temporarily captured within openings in extension wings 604A-B of positioner 600, such that bone screws 200A-B are aligned to corresponding openings in base 104. Bone screws 200A-B are then loosely secured to the patient's skull, such that base 104 is properly positioned and centered around burr hole 106. Wings 604A-B are scored or otherwise constructed so as to separate when bone screws 200A-B are more securely tightened, thereby releasing bone screws 200A-B so that they can fasten base 104 to the patient's skull. Positioner 600 is then removed, such as by snapping it out of base 104, leaving base 104 securely fastened in the proper position with respect to burr hole 106.

FIG. 7 is a perspective view of an example of a tool 700 for performing procedures with respect to, among other things, base 104, cap 112, and/or stabilizer 110. In this example, tool 700 includes a handle 702, a first engaging arm 704, and a second engaging arm 706. The end of arm 704 is appropriately sized to engage one of recesses 402A-B of disk 310 of stabilizer 110 for placing stabilizer 110 into base 104. The end of arm 706 is appropriately sized to engage recess 404 in cam 312 for moving cam 312 between its open and closed positions. In this example, at least one of ends 704 and 706 is appropriately sized for being inserted into one of recesses 204A-B (see FIG. 2) of base 104, and under one of corresponding extensions 206A-B for prying cap 112 away from base 104.

FIG. 8 is a perspective view of an example of a different base, such as support base 800. In this example, support base 800 provides a ring-like or any other (e.g., cylindrical) suitable platform 802 for supporting other surgical equipment, such as for targeting/alignment of the trajectory of the instrument being introduced, and/or for introducing the instrument after such proper alignment is obtained. In this example, the equipment support base 800 is separate from instrument securing base 104, however, these two bases could alternatively be integrally formed or otherwise joined. In the example of FIG. 8, however, support base 800 is secured directly to the patient's skull over and around securing base 104, using bone screws 804A-C through legs extending downward from platform 802, by using any other appropriate affixation technique.

FIG. 9 is a perspective view of an alternate example of a base 800, secured directly to the patient's skull by four bone screws 804A-D through respective legs extending downward from platform 802. This four-legged example advantageously allows for a smaller incision (e.g., in the direction of the instrument exit slot of base 104) into the patient's skull than the three-legged example of FIG. 8. Because the legs in the example of FIG. 9 are closer together than the legs in the example of FIG. 8, the skin does not have to be laterally spread apart as far to allow placement of the example of FIG.

9. Such a reduced lateral skin-spreading in turn reduces the required length of the incision slit.

FIG. 10 is a perspective view of an alternate example of a support base 800. In this example, support base 800 is secured by any suitable means to instrument-securing base 104, which, in turn, is secured to the patient's skull, such as discussed above. In the example of FIG. 10, legs 1000A-D space platform 802 away from base 104. Each of legs 1000A-D includes one or more snap-fit features 1002 for engaging corresponding mating features on base 104. Tightening screws 1004A-B are each captured by a respective threaded portion of platform 802, and extend downward to press against base 104 when base 104 and platform 802 are snapped together. By adjusting screws 1004A-B, support base 800 is backed away from instrument-securing base 104 so that these two bases are more tightly coupled to each other. This provides added stability to platform 802.

FIGS. 11 and 12 are perspective views of an example of a tower-like instrument alignment and introduction guide assembly, also referred to as a deep brain access device 1100. DBA device 1100 can also be regarded as including base 104, stabilizer 110, cap 112, and support base 800. A tower base 1102 of device 1100 snaps onto and rotates upon the ring-like or other platform 802 of FIGS. 8-10, such as by one or more snap-fitting side blocks 1104. Side blocks 1104 provide added stability to prevent tower base 1102 from rocking from side-to-side on platform ring 802. A curved saddle 1106 is coupled to and seated on a curved portion of tower base 1102, such as by at least one arcuate sliding joint, as illustrated. The curved portions of saddle 1106 and tower base 1102 can be tilted with respect to each other to alter a trajectory angle of an instrument being introduced, and can be secured to fix this aspect of the trajectory angle of the instrument.

An affixation mechanism, such as thumbscrew 1108, passes through an opening in tower base 1102 and engages a portion of platform 802 to prevent further rotation of tower base 1102 with respect to platform 802 once a desired rotational position has been obtained. In this example, a capturing device, such as L-shaped arm 1110, retains thumbscrew 1108 together with tower base 1102.

Another affixation mechanism, such as thumbscrew 1112, passes through a slotted opening (tilt slot) in saddle 1106 and engages a portion of tower base 1102 to prevent further riding of the curved portion of saddle 1106 along the curved portion of tower base 1102 once a desired trajectory angle has been obtained. This example also includes attachment fasteners 1113A-B passing through corresponding slots in saddle 1106 for additionally securing saddle 1106 to tower base 1102. Attachment fasteners 1113A-B include screws passing through respective retainer brackets, each of which includes a curved surface conforming to a curved surface of saddle 1106.

Also in this example, an interior portion of a socket 1114 on saddle 1106 provides a socket portion of a ball-and-socket joint. An affixation mechanism, such as thumbscrew 1116, passes through a threaded opening in socket 1114 to secure the position of a ball housed therein. Socket 1114 also includes fine-tuning thumbscrews 1118A-C, which pass through threaded openings in socket 1114 for further adjusting the exact position of a ball within socket 1114. Socket 1114 further carries a multilumen instrument guide insert assembly 1120. Multilumen insert 1120 includes a tapered sleeve that is releasably coupled, by release tab 1122 and associated structure(s), within a cylindrical opening through the spherical ball housed within socket 1114.

To release the multilumen insert 1120 from the ball, the tab 1122 is pressed inward toward the sleeve. This forces or

wedges a portion of the release tab 1122 against a top portion of the ball and aids in releasing the multilumen insert 1120 from the ball. The top portion of multilumen insert 1120 provides a multilumen guide having a plurality of openings, such as the center opening 1124A and side openings 1124B-E; these openings are also referred to as lumens. Openings 1124B-E are spaced apart from center opening 1124A by a known predetermined distance. Therefore, if electrode 100 is inserted through center opening 1124A, and misses its target location 108 in the brain, it can be inserted into one of the side openings 1124B-E, without readjusting the trajectory, to reach a target at a known distance away from center opening 1124A in the plane of the multilumen insert 1120. In this example, multilumen insert 1120 also includes T-shaped receptacles or recesses 1126A-D for receiving further equipment, as discussed below. In one embodiment, multilumen insert 1120 includes one or more fiducial points (e.g., LEDs, reflective globes, or microcoils), such as for trajectory alignment in a frameless surgical navigation system or in an MRI environment.

FIG. 13 is an exploded perspective view of an example of portions of deep brain access device 1100, including instrument-securing access base 104, support base 800, tower base 1102, saddle 1106, socket 1114A, ball 1300, multilumen insert 1120, and other associated components. As illustrated in FIG. 13, tower base 1102 includes a bottom or groove portion 1302 that engages platform 802, such as using hooked side blocks 1104, and allows tower base 1102 to rotate about the ring-like or other platform 802.

FIG. 13 also illustrates a cylindrical opening 1306 through ball 1300, which is seated in socket 1114A. Multilumen insert 1120 includes a tapered sleeve 1308 or barrel portion that fits snugly within opening 1306. Release 1122 includes a ring portion that fits over the exterior of sleeve 1308. To release multilumen insert 1120 from ball 1300, the tab portion of release 1122 is pressed inward toward sleeve 1308. This forces or wedges a portion of release 1122 against the top portion of ball 1300 and aids in releasing sleeve 1308 of multilumen insert 1120 from ball 1300. The tapered barrel provided by sleeve 1308 of multilumen insert 1120 includes, in one example, a closed end with openings corresponding to lumens 1124A-E of multilumen insert 1120.

FIG. 14 is a perspective view illustrating an example of adjusting an instrument trajectory using portions of deep brain access device 1100 with MRI, CT, PET, or another imaging modality. In FIG. 14, multilumen insert 1120 has been removed, and an imagable reference device, such as alignment stem 1400, has been inserted into the cylindrical passageway of ball 1300 in its place. In this example, alignment stem 1400 includes at least two fiducial points that are recognizable by the imaging modality. The various above-described positioning mechanisms of deep brain access device 1100 are adjusted to make the fiducial points collinear with the target location 108 in the brain. In one example, this may include adjusting the rotation of tower 1102 on platform 802, adjusting the tilt of saddle 1106 with respect to tower 1102, adjusting the spherical position of ball 1300 within socket 1114, and then fine tuning the exact position of ball 1300 using one or more of screws 1118A-C. The imaging modality includes a computer or other processor that provides a display indicating the relative alignment between the trajectory of alignment stem 1400 and target location 108. This display further indicates when the trajectory becomes collinear with target location 108 during the positioning process. The positioning mechanisms provide locking devices that are then locked in, and the alignment stem 1400 is replaced by multilumen insert 1120 for continuing the procedure of intro-

ducing electrode **100** or other instrument along this trajectory to target location **108** in the brain.

FIG. **15** is a perspective view illustrating an example of adjusting an instrument trajectory using portions of deep brain access device **1100** in conjunction with a frameless surgical navigational system. Examples of such systems use LEDs, light reflecting globes, or other spatially-separated fiducial markers to establish a desired instrument trajectory orientation. In the frameless example of FIG. **15**, multilumen insert **1120** remains in place within the cylindrical passageway of ball **1300**. Adapter **1500** is inserted into center lumen **1124A** of multilumen insert **1120**. In this example, adapter **1500** includes a center-bored seat **1502** that snugly receives a portion of frameless navigation reference device instrument. The frameless navigation reference instrument provides spatially-separated fiducial points that are recognized by the frameless imaging modality. These fiducial points are viewed, using the appropriate imaging modality, while the various positioning mechanisms of the deep brain access device are adjusted, to orient the instrument's trajectory toward the desired target location **108** in the brain, then locked in. The frameless navigation instrument is then removed from center-bored seat **1502** of adapter **1500**. Adapter **1500** is then removed from center lumen **1124A** of multilumen insert **1120** for continuing the procedure of introducing electrode **100** or other instrument along this trajectory to brain target location **108**.

FIG. **16** is a perspective view illustrating an example of alignment stem **1400** when separated from deep brain access device **1100**. In this example, alignment stem **1400** is filled with an imagable fluid provided through a one-way valve **1600** at a proximal end of alignment stem **1400**. A distal end of alignment stem **1400** includes a protuberance or other extension **1602**. In this example, extension **1602** is a thin cylindrical container having a distal tip **1604**. Distal tip **1604** is located at the pivot point of ball **1300** when ball **1300** is seated in socket **1114** of saddle **1106**. In this example, imagable fiducial points are provided at proximal valve **1600** and distal tip **1604**. The trajectory is established by adjusting the various positioning mechanisms of deep brain access device **1100** so that these imagable fiducial points are collinear with target location **108** in the brain. In one example, the exact position of target location **108** is obtained using real-time imaging of the brain while the positioning mechanisms of deep brain access device **1100** are being adjusted. In another example, preoperative brain images are used to determine the position of target location **108** while adjusting the various positioning mechanisms of deep brain access device **1100**. FIG. **16** also illustrates a release mechanism **1606**, which includes knob **1608** and ramp **1610**. By imparting a force on knob **1608** toward ball **1300**, ramp **1610** engages the top of ball **1300** to assist in releasing alignment stem **1400** from the cylindrical passageway of ball **1300**. Then, multilumen insert **1120** is reinserted into the cylindrical passageway of ball **1300**, for introducing electrode **100** or other medical instrument(s) through lumen(s) **1124** of multilumen insert **1120**.

FIG. **17** is a perspective view illustrating an example of frameless adapter **1500** when separated from deep brain access device **1100**. In this example, adapter **1500** includes stainless steel pin, having a distal tip **1700**, that is appropriately sized for being inserted into center lumen **1124A** of multilumen insert **1120**. When fully inserted, distal tip **1700** is located the pivot point of ball **1300** when ball **1300** is seated in socket **1114** of saddle **1106**. In this example, a frameless navigation instrument with frameless imagable fiducial points is inserted into center-bored seat **1502** at the proximal

end of adapter **1500**, or onto the outer portion of adapter **1500**, or otherwise coupled to adapter **1500** by any other appropriate coupling technique.

FIG. **18** is a perspective view illustrating an example of a technique for introducing an instrument along the previously established trajectory to target location **108** in the brain. In FIG. **18**, multilumen insert **1120** is used to guide a distal end of a secondary medical instrument, such as an elongate luminal catheter or peel-away sheath, for example, one of sheaths **1800A-C**, toward target location **108**. Before sheath **1800** is inserted into one of lumens **1124A-E** of multilumen insert **1120**, however, a stylet is inserted through a hollow center bore or lumen of sheath **1800**. This prevents coring of brain tissue by the hollow center bore of sheath **1800** and, in one embodiment, provides additional rigidity for performing the insertion and obtaining an accurate path along the established trajectory toward target location **108**.

The example of FIG. **18** illustrates a triple sheath assembly **1802**, with linearly-arranged sheaths **1800A-C**, appropriately spaced apart for being inserted into three linearly-arranged lumens **1124** of multilumen insert **1120**. This example similarly illustrates a triple stylet assembly **1804** in which three linearly-arranged stylets are spaced apart for insertion in the linearly-arranged sheaths **1800A-C**. This triple sheath/stylet illustration is merely an example. The exact number of sheaths **1800** and corresponding stylets being introduced ranges from a single sheath/stylet to the number of available lumens **1124** in multilumen insert **1120**. After sheath assembly **1802** and stylet assembly **1804** has been guided approximately to target location **108**, stylet assembly **1804** is removed and a guide bridge is secured to multilumen insert **1120** for guiding electrode **100** into the center bore of one of sheaths **1800A-C** for positioning electrode **100** at target location **108**. The sheaths **1800A-C** are then removed by pulling apart handles **1806A-B**. In the illustrated example, each sheath **1800** breaks into two pieces as it is being extracted.

FIGS. **19A** and **19B** provide two perspective views of an example of multilumen insert **1120**, which includes the tapered barrel-like sleeve **1308** that is inserted into center hole **1306** of ball **1300**. Lumens **1124A-E** extend from the top of multilumen insert **1120** through the barrel sleeve **1308**. As discussed above, side lumens **1124B-E** are appropriately radially-spaced (e.g., 3 millimeters, center-to-center) from center lumen **1124A** to provide capability for repositioning of electrode **100** by a known amount by simply removing electrode **100** from center lumen **1124A** and reinserting it into a desired one of side lumens **1124B-E**. FIGS. **19A** and **19B** also illustrate receptacles **1126A-D**, opposing pairs of which are used for receiving a guide bridge or other equipment desired to be mounted to the top of multilumen insert **1120**.

FIG. **20** is a perspective view illustrating an alternate example of a stylet assembly **2000**, including a hub **2002** for uniting 1-5 stylets **2004A-C** for insertion into corresponding peel-away or other sheaths inserted through corresponding lumens **1124** of multilumen insert **1120**. In one embodiment, hub **2002** includes a Touhy-Borst adapter, or other suitable adapter for gripping stylets **2004A-C**.

FIG. **21** is a perspective view illustrating an example of a single peel-away sheath **2100** including a distal tip **2102**, a proximal end **2104**, and a center bore or lumen extending therebetween. Handles **2106A-B** are included at proximal end **2104**. Sheath **2100** is peeled away and extracted by pulling apart handles **2106A-B**.

FIG. **22** is a perspective view illustrating an example of a guide lumen selector, such as guide bridge **2200** having tabs or legs that are snap-mounted onto an opposing pair of receptacles **1126A-D** of multilumen insert **1120**. In this example,

guide bridge **2200** includes a cylindrical guide tube **2202** extending upward from a base portion of guide bridge **2200**. Guide tube **2202** includes a center bore hole **2204** for passing electrode **100** or other instrument therethrough. A proximal portion of guide tube **2202** includes a lip **2206** extending outward circumferentially around the perimeter of guide tube **2202**. In one example, the center bore hole **2204** is tapered inward in a direction away from lip **2206**. That is, an inner diameter of bore hole **2204** necks down so the instrument passed therethrough is automatically centered as it approaches the base portion of guide bridge **2200**. In this example, guide bridge **2200** also assists in holding the sheath(s) in place as the electrode is being passed through a sheath to target location **108**. The handle portions of the sheath do not pass through guide tube **2202**, but instead, exit under the sides of guide bridge **2200**. In one example, guide bridge **2200** includes a wedge-like ridge on its underside to assist in splitting the peel-away sheath.

FIGS. **23** and **24** are perspective views illustrating an offset guide bridge **2300** and a center guide bridge **2400**, respectively. Lumens **1124A-E** provide a primary guide device for electrode **100** or other instrument, and the selected one of offset guide bridge **2300** and center guide bridge **2400** provides a secondary guide device for electrode **100** or other instrument. Offset guide bridge **2300** is selected when the instrument being introduced is intended to pass through one of side lumens **1124B-E** in multilumen insert **1120**. In this example, guide tube **2202** is offset from the center of the base of offset guide bridge **2300**, such that its center bore **2204** is aligned with one of side lumens **1124B-E** of multilumen insert **1120**. Alignment with the particular desired side lumen is obtained by appropriately rotating the orientation of offset guide bridge **2300** and snapping tabs **2302A-B** into corresponding opposing pairs of receptacles **1126**. By contrast, in center guide bridge **2400**, guide tube **2202** is centered on the base portion of center guide bridge **2400**, such that its center bore **2204** aligns with center lumen **1124A** of multilumen insert **1120** when center guide bridge **2400** is snapped into opposing pairs of receptacles **1126** of multilumen insert **1120**. In each of the examples of FIGS. **23** and **24**, an outside portion of lip **2206** is threaded for engaging other equipment. Alternatively, other equipment may be mounted onto guide tube **2202** by using a compression fit to a threaded or unthreaded lip **2206**.

FIGS. **25** and **26** are perspective views of deep brain access device **1100**, on which a center guide bridge **2400** is mounted to multilumen insert **1120**. In these examples, an introducer **2500** mechanism is mounted onto guide tube **2202** using a compression fitting to lip **2206**. Introducer **2500** includes a slide **2502** mechanism on which a sliding clamp **2504** rides toward and away from deep brain access device **1100** and, therefore, toward and away from burr hole **106** in the skull or other entry portal. Clamp **2504** holds the electrode **100** or other instrument being introduced. In one example, introducer **2500** is operated remotely by controls **2506A-B** to slide clamp **2504** along slide **2502**, and therefore, to introduce the instrument being held by clamp **2504** into and/or out of the brain along the predetermined trajectory in a controlled manner. One example of an appropriate remote introducer **2500** is the Fathom® Remote Introducer available from Image-Guided Neurologics, Inc. of Melbourne, Fla. U.S.A. Another example of an appropriate remote introducer **2500** is described in Skakoon et al. U.S. patent application Ser. No. 09/827,266 entitled "Medical Device Introducer," filed on Apr. 5, 2001 and assigned to the assignee of the present patent application, the disclosure of which is incorporated herein by reference in its entirety.

FIG. **27** is a perspective view of an alternate example of an instrument-securing base **2700**. In this example, base **2700** is centered around burr hole **106** and secured to the skull using bone screws **2702A-D** extending through openings in leg portions. Base **2700** includes two opposing mating slides **2704A-B** that move toward and away from each other, and that mate and engage each other to clamp electrode **100** or other instrument therebetween. One or more slots **202** are provided for providing a lateral exit for electrode **100**, as discussed above. Other equipment is either attached directly to the skull around base **2700**, or attached indirectly to the skull, though base **2700**, such as by snapping or clamping such equipment to receiving sides **2706A-B**.

FIG. **28** is a perspective view of a ball-housing socket **2800**, used as an alternative to socket **1114**. In this example, socket **2800** rides on a sliding translational stage **2802** on a mount **2804** coupled to saddle **1106** or other portion of deep brain access device **1100**. This example includes a squeeze release **2806** for disengaging mount **2804** from saddle **1106** or other affixation point of deep brain access device **1100**. Alternatively, mount **2804** is affixed to securing base **2700** by a hooked engagement mechanism **2808** that engages an underside of securing base **2700**, or by using any other appropriate coupling technique. Thumbscrew **2810** engages a threaded opening in mount **2804** and also engages and controls translational movement of sliding stage **2802**. Thumbscrew **2812** engages a threaded opening in mount **2804** and secures the position of stage **2802** to prevent unwanted translational movement after its desired position is obtained. Either thumbscrew may be captured to prevent accidental separation from mount **2804**.

FIG. **29** is a perspective view illustrating a remote introducer **2900**, provided as an alternative to introducer **2500**. In this example, introducer **2900** is coupled to a portion of deep brain access device **2901**, such as by using a Touhy-Borst adapter **2902** threaded onto a lip of a guide tube, similar to lip **2206** of guide tube **2202**. In this example, electrode **100** is inserted through a peel-away sheath **2100** (after removing a stylet). Sheath **2100** is secured to a squeeze-release clamp **2904** that slides toward and away from the skull along slide **2906**. In this example, advancement and retraction of clamp **2904** is remotely controlled using controls **2506A-B**.

FIG. **30** is a cross-sectional view illustrating a deep brain access device **3000**, provided as an alternative to deep brain access device **1100**. In this example, base **104** is secured to the skull using bone screws. A pedestal or tower **3002** is secured to base **104** as illustrated or, alternatively, is secured directly to the skull. Tower **3002** includes a socket **3004** housing a ball **3006**. Ball **3006** includes a center opening that receives a rotating inner barrel sleeve **3008**. In this example, sleeve **3008** includes one or more lumens **3010A-C** extending therethrough for passing and guiding instruments, sheaths, stylets, etc. An affixation device, such as thumbscrew **3012**, fixes the position of ball **3006** when the desired trajectory alignment has been obtained, such as by using the MRI, CT, PET, or frameless navigational guidance techniques discussed above. Proximal portions of lumens **3010A-C** include recesses for snapping into place lips on devices inserted therein, such as alignment stem (or frameless adapter) **3014** and/or Luer stem **3016**. A remote introducer may be attached to Luer stem **3016**, as discussed above. Luer stem **3016** may include a wedge **3018**, for assisting in splitting a peel-away sheath inserted through corresponding lumen **3010** before Luer stem **3016** is inserted therein. Luer stem **3016** may also include orientation tabs **3020** to appropriately align the wedge to provide the desired assistance in splitting the peel-away sheath.

13

FIG. 31 is a perspective view illustrating an example of ball 3006 and sleeve 3008, including an illustration of the ball-and-socket movement of ball 3006 and rotational movement of sleeve 3008 within ball 3006. In this example, lumens 3010 include associated transverse grooves 3100 extending laterally in opposite directions from the lumens 3010 to opposing edges of sleeve 3008. Grooves 3100 receive and/or hold peel-away portions of one or more peel-away sheaths inserted into respective lumens 3010.

FIGS. 32A and 32B provide various perspective and side views of portions of deep brain access device 3000 and associated components. In this example, a three prong titanium stylet 3200 assembly is inserted into corresponding lumens of a triple peel-away plastic sheath 3202 assembly. One or more prongs of sheath 3202 includes depth markers 3204. The combined sheath 3202 and stylet 3200 is inserted into corresponding lumens 3010 of guide sleeve 3008 to the desired depth, as indicated by depth markers 3204 on sheath 3202. The proximal portion of sheath 3202 is then separated as illustrated in FIG. 32B and flattened out laterally. Wedge 3206 on a proximal handle portion of stylet 3200 may assist in splitting sheath 3202. This establishes the prongs of sheath 3202 at the desired depth. Stylet 3200 is then removed, and electrode 100 or another instrument is introduced into position through the sheath 3202.

FIGS. 33A, 33B and 33C provide exploded perspective and cross-sectional views of a stabilizer 3300, which can serve as an alternative to stabilizer 110. In this example, stabilizer 3300 includes a substantially rigid ring-like base 3302, a substantially rigid upper plate, 3304, and a soft middle plate 3306 interposed between upper plate 3304 and lower ring 3302. Upper plate 3304 and middle plate 3306 include corresponding openings 3308. A neurostimulating electrode 100 or other instrument is passed through one of these openings 3308. A soft male protuberance around the opening in middle plate 3306 is received within a female receptacle around the opening in upper plate 3304. When upper plate 3304 is clamped down against base 3302, the soft protuberance is squeezed against the electrode 100, holding it securely in place.

FIGS. 34A and 34B are perspective views of a stabilizer 3400, which provides an alternative to stabilizer 110. In this example, stabilizer 3400 is rubber or any other flexible material that tends to return to its original shape. A spreader 3402 is used to open a slot 3406 in stabilizer 3400, which is then inserted into an instrument-securing base-plate fastened to the skull. When electrode 100 or other instrument is properly positioned, the spreader is removed, allowing stabilizer 3400 to return to its original shape with the slot 3406 closed around the electrode 100 to hold it securely in place.

FIG. 35 provides a perspective view and several cross-sectional views illustrating a sheath-substitute guide 3500, which provides an alternative to the peel-away sheaths discussed above. In this example, guide 3500 includes one or more elongate guides 3500A-C that do not have a central bore lumen for guiding an instrument through. Instead, each guide 3500A-C includes a cross-section that is formed for guiding an instrument along its side. In this example, the cross-section is crescent-shaped so as to provide a degree of mating to the outer diameter of electrode 100, stylet 3502, or other instrument that is introduced into the patient along the side of the guide 3500. In one example, guide 3500 is introduced in tandem with removable stylet 3502, which provides additional rigidity to the introduction process. In another example, guide 3500 is introduced without removable stylet 3502. Because guide 3500 does not use a central bore lumen, coring of brain tissue during its introduction may be of less

14

concern. Guide 3500 allows access to the adjacent electrode 100 along its entire length, allowing electrode 100 to be gripped and/or secured very close to the skull (such as using instrument-securing base 104) before guide 3500 is removed. This prevents excessive movement of electrode 100 during extraction of guide 3500, which provides more accurate placement of electrode 100 or other instrument.

FIG. 36 provides a perspective view and a cross-sectional view illustrating a sheath 3600 assembly, which provides another alternative to the peel-away sheaths discussed above. In this example, sheath 3600 assembly includes one or more elongate sheaths 3600A-C. Each elongate sheath 3600 includes an open slot along its length, or a portion thereof. In the illustrated example, each elongate sheath 3600 includes two C-shaped portions 3602A-B that rotate with respect to each other by manipulating a handle portion of the sheath 3600. When the C-shaped portions 3602A-B are rotated into a closed position, they together effectively provide a central lumen 3604 through which electrode 100 or other instrument may be passed. When the C-shaped portions 3602A-B are rotated into an open position, they together effectively provide an open slot along their length, allowing access to electrode 100 or other instrument that has been inserted there-through. This allows electrode 100 to be gripped and/or secured very close to the skull (such as using instrument-securing base 104) before sheath 3600 is removed. This prevents excessive movement of electrode 100 during extraction of sheath 3600, which provides more accurate placement of electrode 100 or other instrument. In this example, stylet(s) may be inserted into the lumen 3604 before sheath 1600 is introduced, to avoid coring of brain tissue.

FIG. 37 is a cross-sectional view illustrating an example of deep brain access device 3000 mounted onto the patient's skull with remote introducer 2500 mounted onto Luer stem 3016, which is snapped into central lumen 3010B. Neurostimulating electrode 100 is held by introducer 2500, and passed through central lumen 3010B to target location 108 of the brain.

FIG. 38 is a cross-sectional view illustrating an alternate example of a deep brain access device 3800. This example illustrates a base 3802, which is centered around burr hole 106 and secured to the skull. A tower 3804 is secured to base 3802 or, alternatively, directly to the skull. Tower 3804 includes mounting legs 3806 and 3808, which are affixed to base 3802 or to the skull. The mounting legs 3806 and 3808 are coupled to a pedestal 3810 by pivot pins 3812 and 3814. Pins 3812 and 3814 are aligned to provide a longitudinal axis about which pedestal 3810 pivots until locked in place by thumbscrew 3816, which engages one of the pins 3812 and 3814. Thus, pedestal 3810 would be capable of pivoting into and out of the drawing of FIG. 38.

In the example of FIG. 38, pedestal 3810 includes an arc 3818 extending between leg extensions 3820A-B that are coupled to pivot pins 3812 and 3814. Arc 3818 is curved, so that a center portion 3822, away from leg extensions 3820A-B, would be more distant from the viewer of FIG. 38 than the portions of arc 3818 that are closer to leg extensions 3820A-B. Arc 3818 includes a slot 3824 extending substantially along its length between leg extensions 3820A-B. A socket 3826 engages and rides along slot 3824, until locked into position by securing thumbscrew 3828 against arc 3818. Socket 3826 houses a ball 3006 that can be adjusted spherically until locked into place by one or more thumbscrews. Ball 3006 includes a center sleeve 3008 having one or more lumens, as discussed above with respect to FIG. 30. In the example of FIG. 38, a Luer stem 3016 is snapped into a center

lumen of sleeve **3008**, and a remote introducer **2500** is mounted onto the Luer stem for guiding electrode **100** to target location **108**.

FIG. **39** is a perspective view illustrating an alternate example of a multilumen insert **1120**. In this example, multilumen insert **1120** includes one or more fiducial markers **3900A-C** (e.g., LEDs, reflective globes, or MRI-imagable microcoils), such as for trajectory alignment in a frameless surgical navigation system or in an MRI environment. This illustration shows three such imagable fiducial markers **3900A-C** defining a plane. Fiducials **3900A-C** are supported on respective arms extending from an attachment extension **3902**, which is coupled by an fastener, such as screw **3904**, to an arm **3906** that extends upward and outward from the planar face plate **3908** of multilumen insert **1120**. This coupling is performed (e.g., using integral alignment guides or, alternatively, performing a calibration adjustment) so that a predetermined known spatial relationship exists between the plane formed by imagable fiducials **3900A-C** and the plane of face plate **3908**, which is orthogonal to the instrument trajectory axis through each of lumens **1124A-E**. Consequently, imaging fiducials **3900A-C** are viewed in conjunction with adjusting the various positioning mechanisms of the deep brain access device to obtain and fix the desired instrument trajectory with respect to the entry portal. Although, in this example, imaging fiducials **3900A-C** are illustrated as being attached and in a known spatial relationship to plate **3908**, imaging fiducials **3900A-C** may alternatively be attached to any other component of the deep brain access device so as to establish a known spatial relationship between the fiducials **3900A-C** and an axial trajectory provided by one or more of lumens **1124A-E**. As another alternative, any component of the deep brain access device includes an adapter for receiving one of several commercially available surgical navigation instruments. Such surgical navigation instruments similarly provide imaging-recognizable fiducials. Such an adapter should be oriented such that the spatial relationship between the surgical navigation instrument and the instrument trajectory is known, thereby allowing imaging of the fiducials to assist in adjusting the trajectory to target location **108**.

The discussed devices and methods may be used in with frameless surgical navigation or with MRI or other imaging. Such techniques permit real-time determination and confirmation of anatomical placement of the instrument for improving targeting and placement accuracy. Other advantages include, among other things, an alignment apparatus that uses a localized coordinate system in which positioning and aligning is based on a coordinate system relative to the patient's skull and the skull entry point rather than a stereotactic frame; real-time imaging that eliminates the need for retrospective imaging and also allows direct confirmation of the anatomical placement; an anatomically determined initial targeting angle (the angle between the body or skull surface and the theoretical target) that is selected based on the patient's actual anatomy; a unique center-of-arc principle using rotation about the nominal trajectory axis, thus simplifying optimization of the first angular adjustment; a locking ball-and-socket arrangement for easy and accurate direct targeting under real-time imaging or frameless surgical navigation; peel-away or alternative sheaths that allow the device to be easily secured into position; access to the base plate assembly so that the electrode can be captured at the surface of the skull immediately after successful placement and before disassembly of the targeting apparatus; and visible (under the imaging method chosen, e.g., under CT or MRI) alignment stems.

Similarly, the stabilization system provides for in situ stabilization immediately upon proper placement, through use of a disk and cam arrangement, thus eliminating inadvertent movement during disassembly of the alignment apparatus, and reducing the likelihood of the electrode moving after implantation; the snap-fit solid cap protects the electrode and its capture mechanism from damage; the stabilization system is substantially sealed to minimize ingress and egress; the base plate is securely attached to the body; a special tool facilitates placement of the base plate correctly into the burr hole, thus assuring adequate clearance for proper assembly of all parts, as well as pre-positioning apparatus for easy attachment; and the electrode is captured by clamping it in a gap between two parts, therefore electrode damage cannot occur because the gap size is limited by a physical stop.

Although the examples primarily discuss targeting, placement, and stabilization of a deep brain electrode, this is just an example of one of the possible procedures that can be done using the body portal type trajectory guide. Numerous other procedures will be accomplished using this device. In addition, the device will give rise to other future surgical procedures.

It is to be understood that the above description is intended to be illustrative, and not restrictive. For example, the above-described embodiments may be used in combination with each other. Many other embodiments will be apparent to those of skill in the art upon reviewing the above description. The scope of the invention should, therefore, be determined with reference to the appended claims, along with the full scope of equivalents to which such claims are entitled. In the appended claims, the terms "including" and "in which" are used as the plain-English equivalents of the respective terms "comprising" and "wherein."

What is claimed is:

1. A device for immobilizing a primary instrument, comprising:
 - a base plate;
 - a stabilizer plate configured to engage the instrument, the stabilizer plate being configured to rest on the base plate and including at least one variable opening surrounded by an integrally formed male protuberance, the male protuberance extending along an axis orthogonal to the stabilizer plate and the stabilizer plate extending transverse to the axis beyond the male protuberance, the male protuberance being sized and shaped to at least partially surround the instrument and allow passage of the instrument when normally relaxed and to immobilize the instrument when compressed inwardly toward the instrument; and
 - an upper plate that is relatively more rigid than the stabilizer plate, the upper plate being configured to rest on the stabilizer plate and comprising a female receptacle formed therein complementary to the normally relaxed size and shape of each male protuberance of the stabilizer plate, yet shaped and sized to compress the at least one variable opening inwardly via the male protuberance upon compression of the upper plate and the stabilizer plate together.
2. The device of claim 1, wherein the base is generally ring-shaped.
3. The device of claim 1, wherein the stabilizer plate and the upper plate each have the same diameter.
4. The device of claim 3, wherein the base plate further comprises a recess formed therein and having a diameter complimentary to the diameter of the upper plate and the stabilizer plate; and

17

wherein the upper plate and the stabilizer plate are each configured to be received within the base plate recess.

5. A device for immobilizing a primary instrument, comprising:

a base;

a stabilizer configured to engage the instrument, the stabilizer being configured to rest on the base and including at least one variable opening sized and shaped to at least partially surround the instrument and allow passage of the instrument when normally relaxed and to immobilize the instrument when compressed inwardly toward the instrument; and

a plate that is relatively more rigid than the stabilizer, the plate being configured to rest on the stabilizer and comprising a feature complementary to the normally relaxed size and shape of each variable opening of the stabilizer, yet shaped and sized to compress the at least one variable opening inwardly upon compression of the plate and the stabilizer together;

wherein the stabilizer includes at least two variable openings, and the plate includes at least two openings corresponding to the variable openings of the stabilizer.

6. The device of claim 5, comprising:

an axially extending male protuberance around each of the at least two variable openings of the stabilizer; and

a receptacle around each of the at least two openings of the plate corresponding to the male protuberance around each of the at least two variable openings of the stabilizer, wherein, upon compression of the plate and the stabilizer together, each male protuberance is configured to compress within the corresponding receptacle to compress each such variable opening inwardly.

7. The device of claim 5, wherein each of the at least two variable openings of the stabilizer is configured to accept at least a portion of the primary instrument therein and grip the primary instrument upon inward compression of each of the at least two variable openings.

8. The device of claim 5, wherein the base is generally ring shaped.

9. The device of claim 5, wherein the stabilizer includes a first diameter and the plate includes a second diameter, the first and second diameters being equal.

10. The device according to claim 9, wherein the base further comprises a recess formed therein and having a diameter complementary to the diameters of the stabilizer and the plate; and

wherein the stabilizer and the plate are each configured to be received within the recess of the base.

18

11. A method, comprising:

providing an immobilizing device with a base, a stabilizer plate configured to rest on the base and an upper plate configured to rest on the stabilizer plate;

5 securing the immobilizing device around an entry portal in a surface;

passing an instrument at least partially through one of at least two variable openings in the stabilizer plate; and inwardly compressing each of the variable openings with the upper plate such that the one of the at least two variable openings is compressed inwardly toward the instrument to immobilize the instrument.

12. The method of claim 11, wherein inwardly compressing the variable opening includes compressing the upper plate and the stabilizer of the immobilizing device together, the upper plate including a receptacle complementary to a normally relaxed size and shape of an axially extending protuberance surrounding each variable opening of the stabilizer, yet shaped and sized to compress each variable opening inwardly through engaging the protuberance upon compression of the upper plate and the stabilizer together.

13. The method of claim 11, comprising attaching the immobilizing device to an adjustable trajectory access device.

14. The method of claim 11, further comprising providing the stabilizer plate and the upper plate in a recess of the base plate, the stabilizer plate and the upper plate each having the same diameter, the recess having a diameter complimentary to the diameter of the stabilizer plate and upper plate.

15. The method of claim 13, comprising guiding the instrument along a trajectory through the entry portal in the surface with the adjustable trajectory access device.

16. A device having at least two openings for immobilizing a primary instrument, comprising:

means for securing the device around an entry portal in a surface; and

means for varying the at least two openings in the device to at least partially surround the instrument when the instrument is positioned in one of the two openings and allow passage of the instrument when the openings are normally relaxed and to immobilize the instrument when the openings are compressed inwardly toward the instrument.

17. The device of claim 16, comprising means for attaching the device to an adjustable trajectory access device.

18. The device of claim 16, comprising means for guiding the instrument along a trajectory through the entry portal in the surface.

* * * * *