



US009308322B2

(12) **United States Patent**  
**Lambert**

(10) **Patent No.:** **US 9,308,322 B2**  
(45) **Date of Patent:** **\*Apr. 12, 2016**

(54) **DEVICES AND METHODS FOR PROTECTING A USER FROM A SHARP TIP OF A MEDICAL NEEDLE**

(71) Applicant: **EMED Technologies Corporation**, El Dorado Hills, CA (US)

(72) Inventor: **Paul Lambert**, El Dorado Hills, CA (US)

(73) Assignee: **EMED Technologies Corporation**, El Dorado Hills, CA (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **13/931,226**

(22) Filed: **Jun. 28, 2013**

(65) **Prior Publication Data**

US 2013/0296804 A1 Nov. 7, 2013

**Related U.S. Application Data**

(63) Continuation-in-part of application No. 12/187,256, filed on Aug. 6, 2008, now Pat. No. 8,500,703.

(60) Provisional application No. 61/130,880, filed on Jun. 2, 2008.

(51) **Int. Cl.**

**A61M 5/32** (2006.01)  
**A61M 5/162** (2006.01)  
**A61M 5/158** (2006.01)

(52) **U.S. Cl.**

CPC ..... **A61M 5/1626** (2013.01); **A61M 5/158** (2013.01); **A61M 5/162** (2013.01); **A61M 5/32** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC ..... A61M 2005/1581; A61M 2005/325; A61M 2005/3256; A61M 5/158; A61M 5/1626; A61M 5/321; A61M 5/3243; A61M 5/3257; A61M 5/3275  
USPC ..... 604/110, 177, 192-198, 263  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,648,400 A 3/1972 Wolfe  
4,280,636 A 7/1981 Lewis

(Continued)

FOREIGN PATENT DOCUMENTS

JP H0966106 A 3/1997

OTHER PUBLICATIONS

LiftLoc Safety Infusion Set, Instructions for Use—Non-Coring Safety Huber Needle, 2004, Specialized Health Products, Inc., 585 West 500 South, Bountiful, Utah 84010, www.shpi.com.

(Continued)


*Primary Examiner* — Imani Hayman

(74) *Attorney, Agent, or Firm* — Laurence A. Greenberg; Werner H. Stemer; Ralph E. Locher

(57) **ABSTRACT**

There are disclosed devices and methods for protecting a user from a sharp tip of a medical needle. In an embodiment, a device includes a central body portion, a medical needle having a sharp tip, a pair of wings in attachment to the central body portion, and a mechanical fastener disposed on at least one of the wings, the mechanical fastener configured to selectively attach the wings together with the medical needle positioned between the wings so as to protect a user from the sharp tip of the medical needle. In another embodiment, a method includes withdrawing a sharp tip of a medical needle from a patient, closing a pair of wings with the medical needle positioned between the wings, and fastening the wings together with the medical needle positioned between the wings so as to protect a user from the sharp tip of the medical needle.

**14 Claims, 35 Drawing Sheets**



(52) **U.S. Cl.**  
 CPC ..... *A61M 5/321* (2013.01); *A61M 5/3243*  
 (2013.01); *A61M 5/3257* (2013.01); *A61M*  
*5/3216* (2013.01); *A61M 5/3275* (2013.01);  
*A61M 2005/1581* (2013.01); *A61M 2005/325*  
 (2013.01); *A61M 2005/3256* (2013.01)

6,585,704 B2 7/2003 Luther et al.  
 6,613,039 B1 9/2003 Namba  
 6,878,136 B2 4/2005 Fleury et al.  
 6,911,020 B2 6/2005 Raines  
 7,291,135 B2 \* 11/2007 Ono ..... 604/263  
 7,578,807 B2 8/2009 Wyss et al.  
 7,803,138 B2 9/2010 Bressler et al.  
 2002/0111581 A1 8/2002 Sasso  
 2005/0107749 A1 5/2005 Smith et al.  
 2006/0064061 A1 3/2006 Solomon et al.  
 2008/0177234 A1 7/2008 Keaton et al.  
 2009/0299302 A1 12/2009 Lambert

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,944,731 A 7/1990 Cole  
 5,092,479 A 3/1992 Wells  
 5,147,319 A 9/1992 Ishikawa et al.  
 5,279,588 A 1/1994 Nicoletti et al.  
 5,342,330 A 8/1994 Kane et al.  
 5,693,022 A \* 12/1997 Haynes ..... 604/192  
 5,823,997 A 10/1998 Thorne  
 5,951,522 A 9/1999 Rosato et al.  
 5,980,488 A 11/1999 Thorne  
 6,500,155 B2 12/2002 Sasso

OTHER PUBLICATIONS

MiniLoc Safety Infusion Set, Instructions for Use—Non-Coring  
 Safety Huber Needle, 2005, Specialized Health Products, Inc., 585  
 West 500 South, Bountiful, Utah 84010, www.shpi.com.  
 SafeStep Huber Needle Set, 2006, The Med-Design Corporation, 585  
 West 500 South, Bountiful, Utah 84010, www.shpi.com.

\* cited by examiner




FIGURE 1  
(PRIOR ART)




FIGURE 2




FIGURE 3




FIGURE 4




FIGURE 5




FIGURE 6




FIGURE 7




FIGURE 8




FIGURE 9




FIGURE 10




FIGURE 11




FIGURE 12




FIGURE 13




FIGURE 14




FIGURE 15




FIGURE 16




FIGURE 17




FIGURE 18




FIGURE 19




FIGURE 20




FIGURE 21




FIGURE 22




FIGURE 23




FIGURE 25




FIGURE 24




FIGURE 26




FIGURE 27




FIGURE 29




FIGURE 28




FIGURE 30




FIGURE 31




FIGURE 32




FIGURE 33




FIGURE 34




FIGURE 35




FIGURE 36






FIGURE 38




FIGURE 39

1

**DEVICES AND METHODS FOR  
PROTECTING A USER FROM A SHARP TIP  
OF A MEDICAL NEEDLE**

CROSS-REFERENCE TO RELATED  
APPLICATIONS

The present application is a continuation-in-part of U.S. patent application Ser. No. 12/187,256, filed on Aug. 8, 2008, now U.S. Pat. No. 8,500,703 which claimed priority from Provisional Patent Application No. 61/130,880, filed on Jun. 2, 2008 and entitled "DEVICES AND METHODS FOR PROTECTING A USER FROM A SHARP TIP OF A MEDICAL NEEDLE", the foregoing applications being incorporated herein, by reference, in their entireties.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a device, system and method for protecting a user from a sharp tip of a medical needle.

2. Description of the Related Art

Generally, Huber needles, subcutaneous needles, and other types of medical needles with sharp tips are inserted by medical workers for medical procedures into patients. These users typically have to carefully maintain the sharp tip during and after removal of the medical needle from the patient until the medical needle is properly disposed of in a biohazard container. As this sharp tip is contaminated with blood or other fluids from the patient, it is considered a significant hazard.

Due to difficulties with the patient, including both physical and mental issues, the carrier portion with the medical needle often is not handled with the degree of care necessary by the user. In contending with various patient issues, a user may become injured by the sharp tip of the needle. FIG. 1 illustrates an example of a device **100** having a sharp tip **102** at the end of a medical needle **104** between a pair of wings **106, 108**. Wings **106, 108** are positioned to allow placement of needle **104** into a patient, and to assist with removal of needle **104** from the patient. However, wings **106, 108** provide little, if any, protection to a user from needle **104** during or after removal from the patient.

Various safety devices have been used as an attempt to ameliorate the danger of the medical needle. However, the currently known safety devices are generally not designed to meet clinical protocols and are difficult to use with other devices. Current devices tend to have a profile which will extend away from a patient's body.

SUMMARY OF THE INVENTION

In an embodiment, there is provided a device for protecting a user from a sharp tip of a medical needle, the device comprising a central body portion in fluid connection with a delivery tube; a medical needle having a first end and a second end in opposition to one another, the first end in fluid connection with the central body portion and the delivery tube, and the second end of the needle extending away from the central body portion to a sharp tip, and a line from the first end to the second end of the medical needle defining a longitudinal axis; a pair of wings having an inner region and an outer region, the inner region of each one of the pair of wings in attachment to the central body portion, the outer region of each one of the pair of wings extending away from the central body portion, the pair of wings disposed in opposition to one another with the medical needle positioned therebetween, and the pair of

2

wings being selectively positionable from a first position to a second position, the first position for placing the medical needle into a patient and delivering a medicinal fluid to a second position, and the second position for removing the medical from the patient; and a mechanical fastener disposed on at least one of the pair of wings, the mechanical fastener configured to selectively attach the pair of wings together with the medical needle positioned therebetween so as to protect a user from the sharp tip of the medical needle.

In another embodiment, there is provided a device for protecting a user from a sharp tip of a medical needle, the device comprising a central body portion in fluid connection with a delivery tube; a medical needle having a first end and a second end in opposition to one another, the first end in fluid connection with the central body portion and the delivery tube, and the second end of the needle extending away from the central body portion to a sharp tip, and a line from the first end to the second end of the medical needle defining a longitudinal axis; and a sleeve slideably disposed in a surrounding configuration to the central body portion, a sliding mechanism formed by the sleeve and the central body portion allowing movement of the sleeve from a first position to a second position, the sleeve in the first position providing the medical needle in a configuration for insertion into a patient and delivery of a medicinal fluid in the patient, and the sleeve in the second position covering the medical needle so as to protect a user from the sharp tip of the medical needle.

In yet another embodiment, there is provided device for protecting a user from a sharp tip of a medical needle, the device comprising a central body portion in fluid connection with a delivery tube; a medical needle having a first end and a second end in opposition to one another, the first end in fluid connection with the central body portion and the delivery tube, and the second end of the needle extending away from the central body portion to a sharp tip, and a line from the first end to the second end of the medical needle defining a longitudinal axis; and a frame member having a polygonal structure extending from the central body portion, the polygonal structure having a first hinged portion, a second hinged portion, a third hinged portion, and a fourth hinged portion, the first hinged portion positioned at the central body portion, the second hinged portion positioned in opposition to the first hinged portion, the third hinged portion and the fourth hinged portion positioned, in opposition to one another, between the first hinged portion and the second hinged portion, the polygonal structure forming an opening at the second hinged portion sized for passage of the medical needle, the polygonal structure selectively positionable from a first position to a second position, the first position configured with the first hinged portion and the second hinged portion in an open configuration, and the third hinged portion and the fourth hinged portion in a closed configuration, with the medical needle extended through the opening for placement into a patient and delivery of a medicinal fluid, and the second position configured with the first hinged portion and the second hinged portion in a closed configuration, and the third hinged portion and the fourth hinged portion in an open configuration, with the polygonal structure surrounding the medical needle so as to protect a user from the sharp tip of the medical needle.

In still another embodiment, there is provided a method of protecting a user from a sharp tip of a medical needle, the method comprising withdrawing a sharp tip of a medical needle from a patient; closing a pair of wings with the medical needle positioned therebetween; and fastening the pair of

wings together with the medical needle positioned therebetween so as to protect a user from the sharp tip of the medical needle.

In another embodiment, there is provided a method of protecting a user from a sharp tip of a medical needle, the method comprising withdrawing a sharp tip of a medical needle from a patient; and sliding a sleeve slideably disposed in a surrounding configuration to a central body portion from a first position providing the medical needle in a configuration for insertion into the patient and delivery of a medicinal fluid in the patient to a second position covering the medical needle so as to protect a user from the sharp tip of the medical needle.

In yet another embodiment, there is provided a method of protecting a user from a sharp tip of a medical needle, the method comprising withdrawing a sharp tip of a medical needle from a patient through an opening formed in a polygonal structure of frame member; and articulating hinges of the polygonal structure to close the frame member surrounding the medical needle so as to protect a user from the sharp tip of the medical needle.

It is to be understood that the scope of the invention is to be determined by the scope of the claims as issued. Nothing in this Summary or the Background is to be construed as requiring a feature set forth herein or that a given embodiment address issues identified in the Background. In this regard, there are other aspects and features of varying embodiments. The will become apparent as the Specification proceeds.

The construction of the invention, however, together with additional objects and advantages thereof will be best understood from the following description of the specific embodiment when read in connection with the accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

For a fuller understanding of the nature of the present invention, reference should be made to the following detailed description, taken in connection with the accompanying drawings in which like reference numerals refer to like elements and in which:

FIG. 1 illustrates a prior art device having a needle associated with subcutaneous fluid administration;

FIG. 2 illustrates an exemplary safety device with a mechanical fastener of an orifice and a pin in wing portions;

FIG. 3 illustrates another safety device with a mechanical fastener of an elongated orifice and a pin in the wing portions;

FIG. 4 illustrates a safety device with a mechanical fastener of a snap button in the wing portions;

FIG. 5 illustrates a safety device with a mechanical fastener of a plurality of elongated orifices and a plurality of pins in the wing portions;

FIG. 6 illustrates a safety device with a mechanical fastener having a circular shape;

FIG. 7 illustrates a safety device with a mechanical fastener having a rectangular shape;

FIG. 8 illustrates a safety device with a mechanical fastener having an elliptical shape;

FIG. 9 illustrates a safety device with a mechanical fastener including a first portion and a second portion in attachment to the wings;

FIG. 10 illustrates a safety device with a mechanical fastener having a lip and a recessed portion configured to engage for attachment with one another, and with a groove sized to house the medical needle;

FIG. 11 illustrates a safety device, similar to the one of FIG. 10, which further includes a handle;

FIG. 12 illustrates a safety device with a mechanical fastener including a hook-and-loop fastening system configured to engage for attachment with one another;

FIG. 13 illustrates a safety device with a hook-and-loop fastening system configured with low profile hook material and low profile loop material;

FIG. 14 illustrates a safety device with a sleeve having a sliding mechanism to selectively cover medical needle;

FIG. 15 illustrates non-DEHP tubing for use with a needle protection device;

FIG. 16 illustrates a section of polypropylene lined tubing with a layer of polypropylene surrounding an inner lumen for use with a needle protection device;

FIGS. 17 and 18 illustrate exemplary embodiments of a frame member with a polygonal structure selectively positionable to cover medical needle;

FIGS. 19-21 illustrate a frame member with a cylindrical shroud within a polygonal structure selectively positionable to cover medical needle;

FIGS. 22-25 illustrate a needle trap at the distal end of a shroud, such as the one shown in FIGS. 19-21;

FIGS. 26 and 27 illustrate a flat spring trap with a low-profile configuration and designed to retain needle subsequent to use;

FIGS. 28 and 29 illustrate a trap having a very small diameter spring, which is similar to the flat spring trap shown in FIGS. 26 and 27;

FIGS. 30-32 illustrate a sliding door trap that includes a door portion and a housing portion;

FIGS. 33-36 illustrate a needle protection device that includes a needle covering spring releasably housed in a recess within a central body portion; and

FIGS. 37-39 illustrate further embodiments of a safety device with a mechanical fastener in accordance with the invention.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring to FIGS. 2-15, there are provided devices for protecting a user from a sharp tip of a medical needle. These safety devices provide protection to eliminate needle stick injuries when using needles associated with subcutaneous fluid administration as well as access to implanted ports.

Subcutaneous sets needles and sets are used to infuse a pharmaceutical product into the subcutaneous tissue. During the insertion and removal, the needle is exposed to users and may cause needle-stick injuries. In addition to subcutaneous needle, Huber needle sets (otherwise known as non-coring needles) are used to infuse a pharmaceutical product into a previously implanted port (which is typically made from titanium). The port has a septum space defined between the titanium port body and an elastic membrane that covers it. Huber needles are inserted through the skin into the port.

Conventional Huber devices can pose difficulty when removing from the patient. A clinician may need to apply a significant amount of force to remove the device. During this process, the needle may free suddenly, as a result of the force applied, and increase the risk of accidental needle stick injury from the exposed needle.

The safety devices described herein include, but are not limited to, subcutaneous needles and Huber needles. The safety devices improve user safety during removal of the needle from the patient. The safety devices described herein may also be applied to other devices that have needles.

A device 200, which is shown in FIG. 2, may include a central body portion 202 in fluid connection with a delivery

tube 204. A medical needle 206 has a first end 208 and a second end 210 in opposition to one another. First end 208 is in fluid connection with central body portion 202 and delivery tube 204. Second end 210 of needle 206 may extend away from central body portion 202 to a sharp tip 212. A line from first end 208 to second end 210 of medical needle defines a longitudinal axis 214.

A pair of wings 216, 218 have an inner region 220 and an outer region 222. Inner region 220 of each one of the pair of wings 216, 218 may be provided in attachment to central body portion 202. Outer region 222 of each one of the pair of wings 216, 218 may extend away from central body portion 202. The pair of wings 216, 218 disposed in opposition to one another with the medical needle positioned therebetween, and the pair of wings 216, 218 being selectively positionable from a first position to a second position. The first position may be generally configured for placing medical needle 206 into a patient and delivering a medicinal fluid. The second position may be configured for removing the medical needle 206 from the patient.

A mechanical fastener 224 may be disposed on at least one of pair of wings 216, 218. Mechanical fastener 224 may be configured to selectively attach the pair of wings 216, 218 together with medical needle 206 positioned in between wings 216, 216. This attachment of the wings 216, 218 protects a user from sharp tip 212 of medical needle 206. In one embodiment, fastener 224 may include portions 224A and 224B.

Optionally, central body portion 202 may include a handle. For example, FIG. 11 illustrates a handle 1126 extending from central body portion 202.

Referring to FIG. 2, mechanical fastener 224 may include one of wings 216, 218 with an orifice 224A and a pin 224B extending from other one of wings 216, 218. Orifice 224A and pin 224B may be configured to engage with one another to selectively attach the pair of wings 216, 218 together with medical needle 218 positioned between wings 216, 216. This attachment of the wings 216, 218 protects a user from sharp tip 212 of medical needle 206.

Orifice 224A has a diameter 226. Pin 224B also has a diameter 228. In one embodiment, diameter 226 of orifice 224A is shorter than the diameter 228 of pin 224B. Looking at FIG. 3, there is shown a device 300 having mechanical fastener 324. In one embodiment, mechanical fastener may include portions 324A and 324B. For example, an orifice 324A is provided with a major axis 330 and a minor axis 332. A pin 324B is provided with a diameter 328. Major axis 330 of orifice 324A is longer than diameter 328 of pin 324B. Minor axis 324B of orifice 324B is shorter than diameter 328 of pin 324B.

In an embodiment, a device 400 (FIG. 4) with mechanical fastener 424 may include a male portion 424A and a female portion 424B. For example, mechanical fastener may be configured as a snap button 424. Male portion 424A of snap button 424 may be mounted to one of wings 216, 218. Female portion 424B of snap button 424B may be mounted to the other one of the wings 216, 218. Male portion 424A and female portion 424B of snap button 424 are configured to engage with one another to selectively attach the pair of wings 216, 218 together with the medical needle 206 positioned between wings 216, 218. This attachment of the wings 216, 218 protects a user from sharp tip 212 of medical needle 206.

Referring now to FIG. 5, and in an embodiment, a device 500 may include mechanical fastener 524 with female portions 524A and a male portions 524B. For example, one of the wings 216, 218 forms a plurality of orifices 524A and the other one of the wings 216, 218 has a plurality of pins 524B.

The plurality of pins 524B and the plurality of orifices 524A may be configured to engage with one another to selectively attach the pair of wings 216, 218 together with medical needle 206 positioned between wings 216, 218. This attachment of the wings 216, 218 protects a user from sharp tip 212 of medical needle 206.

Wings 216, 218 may have various shapes. For example, device 600 has wings 216, 218 with a circular shape (FIG. 6.) Device 700 has wings 216, 218 with a rectangular shape (FIG. 7.) Device 800 has wings 216, 218 with an elliptical shape (FIG. 8).

A device 900, which is shown in FIG. 9, may include a mechanical fastener 924 with a first portion 934 in attachment to one of the wings 216, 218, and a second portion 936 in attachment to the other one of the wings 216, 218. First portion 934 and second portion 936 may be configured to engage with one another to selectively attach the pair of wings 216, 218 together with medical needle 206 positioned between wings 214, 216. This attachment of the wings 216, 218 protects a user from sharp tip 212 of medical needle 206.

In an embodiment, a device 1000 (FIG. 10) may include a mechanical fastener 1024 with one or both of the wings 216, 218 forming a recessed portion 1038 adjacent a perimeter 1040. Mechanical fastener 1024 may also include a lip 1042 extending from at least a portion of perimeter 1040 of one or both of the wings 216, 218. Recessed portion 1038 and lip 1042 may be configured to engage with one another to selectively attach the pair of wings 216, 218 together with medical needle 206 positioned between wings 216, 218. This attachment of the wings 216, 218 protects a user from sharp tip 212 of medical needle 206.

If desired, a device 1000 can include mechanical fasteners in addition to the mechanical fastener 1024. For example, an adhesive and/or hook and loop fastener, or other type of fastener, disclosed herein or otherwise, can be used in addition to the mechanical fastener 1024 of the device 1000. Referring now to FIG. 37, there is shown a device 1000' including the mechanical fastener 1024, as well as additional fasteners, such as mating hook-and-loop fastener portions 1224A and 1224B and/or pins 224B and orifices 224A, as described in connection with FIG. 2. Note that the invention is not intended to be limited only to the embodiments shown herein other variations may be provided without departing from the scope and spirit of the present invention. For example, in addition to the fastener 1024, more or fewer pins and orifices 224A, 224B can be used with or without hook-and-loop fasteners 1224A, 1224B, without departing from the scope of the invention. Alternately, it should be understood that the device 1000' could include the fastener 1024 and the hook-and-loop fasteners 1224A, 1224B, and not the pins and orifices 224A, 224B, if desired. Further, other types of fasteners can be used in addition to the mechanical fastener 1024, such as adhesive and/or snaps 424A and 424B of FIG. 4, in place of, or in addition to, the pins and orifices 224A, 224B and/or the hook-and-loop fastening portions 1224A and 1224B, without departing from the scope of the present invention.

Referring now to FIGS. 10 and 37, in one embodiment, the pair of wings 216, 218 may include rigid material. In another embodiment, the pair of wings 216, 218 may include semi-rigid material. The pair of wings 216, 218 of device 1000, 1000' may be provided in various shapes including, but not limited to, circular shapes and rectangular shapes. See, for example FIGS. 38 and 39, in which other shaped wing designs are shown. Please note that this is not meant to be limiting, as any embodiment of the present invention can be made with differently shaped wings (circles, ellipses, rect-

angles, trapezoids, etc.), including any other shape desired and/or described herein, without departing from the spirit and scope of the present invention. Additionally, as shown in FIGS. 37-39, one or more types of mechanical fastener (such as pin and orifice, hook-and-loop, adhesive and/or snaps) can be used in addition to the lip and recessed portion fastener 1024, if desired.

Device 1000, 1000' may be provided with a groove 1044 in at least one of the wings 216, 218. Groove 1044 may be sized for housing medical needle 206 after the pair of wings 216, 218 are attached to one another. This attachment of the wings 216, 218 protects a user from sharp tip 212 of medical needle 206. In one embodiment, groove 1044 may be formed in a single one of the wings 216, 218. In another embodiment, groove may be formed in both of the wings 216, 218.

A device 1100 (FIG. 11) provides an exemplary embodiment of handle 1126 extending from central body portion 202. Any of the embodiments disclosed herein may include a handle extending away from central body portion 202 in opposition to medical needle 206 and in a direction from second end 210 to first end 208 of medical needle 206.

Looking at FIG. 12, and in an embodiment, mechanical fastener 1200 may include a hook-and-loop fastening system 1224 disposed on the pair of wings 216, 218. Hook-and-loop fastening system 1124 may be configured to engage with one another to selectively attach the pair of wings 216, 218 together with medical needle 206 positioned between wings 216, 218. This attachment of the wings 216, 218 protects a user from sharp tip 212 of medical needle 206.

Hook-and-loop fastening system 1224 may include a hook material 1224A disposed on one of the wings 216, 218. A loop material 1224B may be disposed on the other one of the wings 216, 218. Hook material 1224A and loop material 1224B may be configured to engage with one another to selectively attach the pair of wings 216, 218 together with medical needle 206 positioned between wings 216, 218. This attachment of the wings 216, 218 protects a user from sharp tip 212 of medical needle 206.

Referring to FIG. 13, and in one embodiment, device 1300 may provide hook-and-loop fastening system 1224 with hook material 1224A having a low profile together with loop material 1224B having a low profile.

Referring back to FIG. 12, hook-and-loop fastening system 1224 may also include hook material 1224A and loop material 1224B on each of the pair of wings 216, 218. Hook material 1224A and loop material 1224B may be disposed for engagement with one another on opposed wings 216, 218. This configuration of hook material 1224A and loop material 1224B provides a dual locking configuration.

In an embodiment, hook-and-loop fastening system 1224 may include hook material 1224A on one of the wings 216, 218, loop material 1224B on the other one of the pair of wings 216, 218, and adhesive material 1246 within one or both of hook material 1224A and loop material 1224B. Adhesive material 1246 in hook material 1224A and loop material 1224B may be disposed for engagement with one another to attach the pair of wings 216, 218 together with medical needle 206 positioned between wings 216, 218. This attachment of the wings 216, 218 protects a user from sharp tip 212 of medical needle 206.

In various embodiments, wings 216, 218 may be configured with various materials and in various shapes. For example, wings 216, 218 of device 1200 may include rigid material. Wings 216, 218 of device 1200 may include semi-rigid material. Wings 216, 218 of device 1200 may include soft material. Wings 216, 218 of device 1200 may include gel material. Wings 216, 218 of device 1200 may include cloth.

Wings 216, 218 of device 1200 may include non-woven cloth. In addition, the pair of wings 216, 218 may include a combination of a rigid material, a semi-rigid material, a soft material, a gel material, a cloth material, and a non-woven cloth material. Wings 216, 218 of device 1200 may have one or more shapes, including, for example, a circular shape, a rectangular shape.

In an embodiment, adhesive material 1246 may be dynamically activated. Dynamic bonding agents may include a two component glue-primer and glue each applied to one of the two surfaces to be bonded in which neither component is active until contact with one another. In an alternative example, a "bubble" full of instant glue, which may have a response time of under three seconds, may be configured to burst upon pressing wings 216, 218 together.

Adhesive material 1246 may be incorporated in a gel carrier. A gel carrier is a good way to house a bubble of the instant glue above. Gel or silicone are a very comfortable materials for patients and can overlay hypo-allergenic double-sided adhesive tapes. This may facilitate attachment of the device to the patient's skin.

Referring now to FIG. 14, and in an embodiment, a device 1400 is provided to protect a user from sharp tip of medical needle. Device 1400 may include a central body portion 1402 in fluid connection with a delivery tube 1404.

A medical needle 1406 may be provided with a first end 1408 and a second end 1410 in opposition to one another. First end 1408 may be in fluid connection with central body portion 1402 and delivery tube 1404. Second end 1410 of needle 1406 may extending away from central body portion 1402 to a sharp tip 1412. A line from first end 1408 to second end 1410 of medical needle 1406 defines a longitudinal axis 1414.

A sleeve 1416 may be slideably disposed in a surrounding configuration to central body portion 1402. A sliding mechanism 1418 (e.g., grooves 1418) may formed by sleeve 1416 and central body portion 1402 to allow movement of sleeve 1416 from a first position to a second position.

In the first position, sleeve 1416 may provide medical needle 1416 in a configuration for insertion into a patient and delivery of a medicinal fluid in the patient (i.e., needle 1406 is substantially perpendicular to delivery tube 1404.) In the second position, sleeve 1416 may cover medical needle 1406 so as to protect a user from sharp tip 1412 of medical needle 1406 (i.e., needle 1406 is substantially parallel to delivery tube 1404).

In one embodiment, needle safety devices may be provided non-DEHP tubing 1500 (FIG. 15) or polypropylene lined tubing 1600 (FIG. 16) with a layer 1602 of polypropylene surrounding an inner lumen 1604. Most needle safety devices may be built with a non-DEHP tubing. Polypropylene is a means to minimize chemical interaction (i.e., between the drug and the plastic, thus, minimizing the bleaching effect). Devices may be provided with two tubing material options to minimize chemical interchange with drug. One of these options may include non-DEHP tubing. Another option is polyethylene lined tubing, which provides the least interaction with infused drug.

Referring to FIGS. 17-18, and in an embodiment, a device 1700 is provided for protecting a user from a sharp tip of a medical needle. Device 1700 includes a central body portion 1702 in fluid connection with a delivery tube 1704. A medical needle 1706 has a first end 1708 and a second end 1710 in opposition to one another. First end 1708 may be in fluid connection with central body portion 1702 and delivery tube 1704. Second end 1710 of needle 1706 extends away from

central body portion 1702 to a sharp tip 1712. A line from first end 1708 to second end 1710 of medical needle 1706 defines a longitudinal axis 1714.

Device 1700 includes a frame member 1716 forming a polygonal structure 1718 extending from central body portion 1702. Polygonal structure 1718 has a first hinged portion 1720A, a second hinged portion 1720B, a third hinged portion 1720C, and a fourth hinged portion 1720D. First hinged portion 1720A and second hinged portion 1720C may be positioned at central body portion 1720. First hinged portion 1720A and second hinged portion 1720B may be positioned in opposition to one another. Third hinged portion 1720C and fourth hinged portion 1720D may be positioned in opposition to one another and extend from first hinged portion 1720A and second hinged portion 1720B. Polygonal structure 1718 may form an opening 1722 at second hinged portion 1720B sized for passage of medical needle 1706.

Polygonal structure 1718 may be selectively positionable from a first position to a second position. First position 1718 may be configured with each of first hinged portion 1720A and second hinged portion 1720B in a closed configuration, and third hinged portion 1720C and fourth hinged portion 1720D in a closed configuration. For insertion into patient, 1720A and 1720B are typically in an open position, which allows wings 1730 to serve as the handle and device to insert the needle while third hinged portion 1720C and fourth hinged portion 1720D are in the closed position with layer 1726 laying flat against mechanical fasteners 1724. In this configuration, medical needle 1706 is extended through opening 1722 for placement into a patient and delivery of a medicinal fluid. After insertion, mechanical fastener portions 1732 are laid over base portion 1728 (mechanical fastener portions 1732 and base portion 1728 may have hook-and-loop fastener portions on both sides) to secure the overall device in place. Prior to removal, fastener portions 1732 are removed from base portion 1728, then the clinician's hand (left or right depending on preference) is placed over layer 1726 but not over any other layer and first hinged portion 1720A and second hinged portion 1720B are moved to an open position to allow for the needle to be pulled out thus bringing third hinged portion 1720C and fourth hinged portion 1720D to a closed position. Second position may be configured with first hinged portion 1720A and second hinged portion 1720B in an open configuration, and third hinged portion 1720C and fourth hinged portion 1720D in an open configuration. In this configuration, medical needle 1706 is withdrawn through opening 1722 and polygonal structure 1718 is closed around medical needle 1706. This surrounding configuration of polygonal structure 1718 around medical needle 1706 protects a user from sharp tip 1712.

In an embodiment, one or more mechanical fasteners 1724 may be disposed on frame 1716. Mechanical fastener 1724 may be configured to selectively attach opposed areas of portions 1720C and 1720D to one another with medical needle 1706 positioned between opposed ones of portion 1720A and 1720B, and portion 1720C and 1720D. This surrounding configuration of polygonal structure 1718 around medical needle 1706 protects a user from sharp tip 1712.

In one embodiment, one or more mechanical fasteners 1724 may include a hook-and-loop fastening system. The hook-and-loop fastening system may include a hook material having a low profile as well as a loop material having a low profile. In an embodiment, the hook-and-loop fastening system may include a hook material and a loop material on each of the regions 1724 between third hinged portion 1720C and fourth hinged portion 1720D. The hook material and the loop

material may be disposed to engage with one another so as to provide a dual locking configuration.

Mechanical fastener 1724 may include an adhesive material disposed on one or more of portion 1720C and 1720D. The adhesive material may be configured to engage with another area of portions 1720C and 1720D of polygonal structure 1718 to selectively attach opposed portions 1720C and 1720D of polygonal structure 1718 to one another with medical needle 1706 positioned between opposed portions 1720A, 1720B, 1720C, and 1720D. This surrounding configuration of polygonal structure 1718 around medical needle 1706 protects a user from sharp tip 1712.

In an embodiment, the adhesive material may be dynamically activated. The adhesive material may optionally be incorporated in a gel carrier. In various embodiments, mechanical fastener 1724 may include peelable coverings containing adhesive.

Opposed portions 1720A, 1720B, 1720C, and 1720D of polygonal structure 1718 may be shaped in a variety of shapes, which include, but are not limited to a circular shape, a rectangular shape, and an elliptical shape. Opposed portions 1720A and 1724B as well as 1720C and 1720D of polygonal structure 1718 may include rigid material, semi-rigid material, soft material, gel material, cloth, non-woven cloth, or a combination of these materials.

In an embodiment, an adhesive layer 1726 may extend from central body portion 1702.

Handle 1730 may extend away from central body portion 1702 in opposition to medical needle 1706 and in a direction from first end 1708 to second end 1710 of medical needle 1706. Handle 1730, or any of the handles described hereinabove, facilitates the manipulation of the device during removal. Handle 1730 may be shaped as a tab, a loop, with flaps or wings, or as a detachable clip. Handle 1730 may include rigid material, semi-rigid material, soft material, gel material, cloth, non-woven cloth, or a combination of these materials. Handle 1730 allows the user to remove device 1700 by providing a grab portion to be pulled upwardly. Handle 1730 may include a mechanical fastener 1732 (for example, hook-and-loop material 1732) that mates with base portion 1728. In an embodiment, a mechanical fastener 1732 may extend from base 1728. Handle 1730 and mechanical fastener 1732 may be used to maintain device 1700 in a relatively flat configuration, and are generally not attached to a patient. Mechanical fastener 1732 may be configured to removeably attach to a patient.

Various methods of protecting a user from a sharp tip of a medical needle are provided by the present invention. In one exemplary embodiment, a method of protecting a user from a sharp tip of a medical needle includes withdrawing a sharp tip of a medical needle from a patient. The method further includes closing a pair of wings with the medical needle positioned between the wings. The method also includes fastening the pair of wings together with the medical needle positioned between the wings. This protects a user from the sharp tip of the medical needle.

In another exemplary embodiment, a method of protecting a user from a sharp tip of a medical needle includes withdrawing a sharp tip of a medical needle from a patient. The method also includes sliding a sleeve slideably disposed in a surrounding configuration to a central body portion from a first position providing the medical needle in a configuration for insertion into the patient and delivery of a medicinal fluid in the patient to a second position covering the medical needle. This protects a user from the sharp tip of the medical needle.

In an embodiment, a method of protecting a user from a sharp tip of a medical needle includes withdrawing a sharp tip

of a medical needle from a patient through an opening formed in a polygonal structure of frame member. The method further includes articulating hinges of the polygonal structure to close the frame member surrounding the medical needle. This protects a user from the sharp tip of the medical needle.

Most of the safety devices may be configured with a low profile and small foot print. A small foot-print is particularly useful when the implanted port is a dual port that can only be accessed by two needle sets with a small footprint. Selected materials and a low profile provide enhanced patient comfort, ease of manipulation, ease of fixation, and reduced number of separate pieces to be used when the device is put on the patient.

A misaligned orifice may be provided in device **1700** by providing a non-concentric needle axis through orifice **1722**. Needle **1706** is forced to fit through orifice **1722** during assembly of the device. Once the needle is pulled through orifice **1722**, its axis will force it to its natural position and, thus, it will not be in alignment with orifice **1722**. In one embodiment, the orifice through which the needle goes through on a lower wing can be purposely misaligned (e.g., about twice as much as the needle diameter) so that when the needle is pulled and the double wings take a diamond shape that gradually flattens; the needle will shift out of alignment with the hole.

In an embodiment, a hook-and-loop material **1734** may be positioned on the lower side of wings **1730** and the upper part of frame member **1716**. When the needle is in the patient and the device is flat against the skin, hook-and-loop material **1732** secures the device in its flat position. The loop is the simplest of the three options to be able to pull up the entire polygonal structure. Removal may also be accomplished by pulling on a tab or wings **1730**.

In an embodiment, there may be a shroud **1900** positioned between hinged portions **1720A-1720D**. Shroud **1900** may extend from a low-profile annular ring **1900A** (FIG. 19) to an extended cylinder **1900C** (FIG. 21) so as to cover sharp tip **1712** of needle **1706** when pulled back into a retracted position. As needle **1706** is being removed from a patient, for example, shroud **1900** will form a more elongated cylinder **1900B** (FIG. 20) between hinged portions **1720A-1720D** until shroud **1900** is deployed to cover sharp tip **1712** as extended cylinder **1900C**. In other words, the operation of the movement of the operator pulling handle **1730** upwardly opens the bellows of shroud **1900** as frame **1716** opens to a greater height. This can be used instead of, or in addition to, other protection devices.

A needle trap **2200** may be provided at the end of shroud **1900** or other needle protection devices. Needle trap **2200** has a rounded tip **2202** that has a diameter slightly larger than the diameter of needle **1706**. Flaps **2204** are positioned to abut needle **1706** prior to entrapment within shroud **1900** or another needle protection device. Flaps **2204** are resilient and biased to move toward one another, for example, to a flat position when needle **1706** is removed. Flaps **2204** may be positioned relative to one another such that one overlaps the other preventing needle **1706** from going back through needle trap **2200**.

The material of flaps **2204** can be a number of semi-rigid plastics, which may include, for example, PVC and polypropylene, or metal. If plastic is used, the both body and flaps **2204** can be manufactured by injection molding techniques in a single process. The thickness and angle of flaps **2240** and may be configured to allow bending closer to the inner wall, so that the needle may be positioned through the end of the needle trap **2200** during assembly time. After needle **1706** is

withdrawn into shroud **1900**, the inwardly angled flaps **2204** prevents needle **1706** from going through again.

In another embodiment, and referring to FIGS. 26-29, a flat spring trap **2600** has a low-profile configuration with a loaded position and an activated position to retain needle **1706** subsequent to use. Flat spring trap **2600** may be used in place of needle trap **2200** with shroud **1900**, or trap **2600** may be used with other needle protection devices. For example, a tempered flat wire forming a flat spring **2602** may be bonded at a point **2604** to a surface of trap **2600**. Away from bonded point **2604**, a cover **2606** may be in connection with spring **2602**. Cover **2606** may have a height substantially equal to spring **2602**. Alternatively, cover **2606** may have a different height than spring **2602**. An orifice **2608** is positioned through trap **2600** with a size to accommodate needle **1706**. During assembly of a needle protection device, spring **2602** and cover **2608** are shifted away from orifice **2608** so that needle **1706** is threaded through orifice **2608**. When needle **1706** is withdrawn through orifice **2608**, spring **2602** moves cover **2606** to a position near orifice **2608** so as to prevent needle **1706** from again going through orifice **2608**. FIG. 26 illustrates needle **1706** configured through trap **2600** in a loaded, ready to use position. FIG. 27 illustrates cover **2606** in an activated position with needle **1706** withdrawn from trap **2600**. Trap **2600** is advantageous with a low-profile, an almost flat configuration. For example, spring **2602** may have a thickness of  $\frac{1}{32}$  of an inch. In an embodiment, spring **2602** may be made out of stainless steel. In another embodiment, spring **2602** may be stamped or otherwise configured from a plastic material. In an embodiment, spring **2602** may be completely flat to have a total height in the same amount as the thickness of the wire or other material forming the spring.

In another embodiment, a trap **2600A** includes a very small diameter spring **2602A** rather than a flat spring. Small diameter spring **2602A** may be about  $\frac{1}{16}$  of an inch in diameter. Small diameter spring trap **2602A** may be used in place of needle trap **2200**, or flat spring trap **2600**, with shroud **1900**, or with other needle protection devices. For example, a spring **2602** may be bonded at a point **2604A** to a portion of trap **2600A**. Away from bonded point **2604A**, a cover **2606A** may be in connection with spring **2602A**. An orifice **2608A** is positioned through trap **2600** with a size to accommodate needle **1706**. During assembly of a needle protection device, spring **2602A** and cover **2608A** are shifted away from orifice **2608A** so that needle **1706** is threaded through orifice **2608A**. When needle **1706** is withdrawn through orifice **2608A**, spring **2602A** moves cover **2606A** to a position near orifice **2608A** so as to prevent needle **1706** from again going through orifice **2608A**. FIG. 28 illustrates needle **1706** configured through trap **2600A** in a loaded, ready to use position. FIG. 29 illustrates cover **2606A** in an activated position with needle **1706** withdrawn from trap **2600A**. Trap **2600A** is advantageous with a low-profile, an almost flat configuration. In an embodiment, spring **2602A** may be a cylindrical minute spring at least as small as  $\frac{1}{16}$ " in diameter or smaller such that the diameter of the spring wire is approximately 20-30 thousands of an inch.

In another embodiment, a sliding door trap **3000** includes a door portion **3002** and a housing portion **3004**. An exemplary illustration of sliding door trap **3000** is shown in FIG. 30. One embodiment of door portion **3002** is illustrated in FIG. 31. A cross-sectional view of sliding door trap **3000** is shown in FIG. 30. An opening through door portion **3002** provides an orifice **3006** for a needle. A spring portion **3008** (of door portion **3002** biases against housing portion **3004** so as to move orifice **3006** away from the path of the needle when the needle is removed from orifice **3006**. Door portion **3002** may

13

include plastic material, metal, or other types of material. In an embodiment, door portion **3002** has concentric grooves to form biasing spring **3008** and an off-centered orifice **3006**. During assembly, orifice **3006** is forced into a concentric position by reducing the space between the spiral grooves of spring **3008** to a minimum. When the needle is withdrawn, door portion **3002** realigns back into a pre-configured natural off-centered position and, thus, the needle cannot go back through to inadvertently stick a user.

In another embodiment, a needle protection device **3300** includes a needle covering spring **3302** housed in a recess **3303** within central body portion **202**. A needle **3304** extends from within needle covering spring **3302** and remains uncovered when needle covering spring **3302** remains within recess **3303**. In one embodiment, needle trap **2200** (described hereinabove) or another end portion of spring **3302** may engage an abutment **3506**. To release spring **3302** after a procedure is completed, abutment **3306** may be actuated to allow needle trap **2200** and a portion of spring **3304** to travel toward the end of the needle. Needle trap **2200** may operate as described above or the spring may operate in another matter, such as simply covering the end of the needle. One way to release spring **3304** is to move portions **3306A** and **3306B** of abutment **3306** in connection with wings **216**, **218** apart from one another. FIGS. **33** and **34** illustrate one embodiment of device **3300** with abutment **3306** prior to actuation in a loaded configuration. FIGS. **35** and **36** correspond with illustrate device **3300** after actuation with spring **3302** actuated to cover needle **3304**.

Regarding the polygonal design FIG. **17**, one variation of such is a multi-axis polygon which is covered all around. Imagine two triangular pyramids with their bases attached such that the needle is not visible from any side and thus there is no possibility for any finger to be placed close to the needle at any time during the withdrawal.

Regarding the patient adhesive on the bottom of the polygonal design, such adhesive provides an added level of safety because the clinician places one hand over this layer with the adhesive still on the patient while the needle is being withdrawn from the patient and thus the needle reaches the inside of the “accordion” while the clinicians hands are busy (one with the lower layer and the other with pulling up the top layer—and thus further reducing the possibility of the needle reaching the clinician).

Most safety devices require complex mechanisms to trap the needle. The devices of the present invention provide simpler, easier to manufacture, and yet modifiable, products that satisfy additional clinical requirements beyond safety. These additional requirements include lower profile, flexibility, customizability, patient comfort, and scalability.

Lower profile is critical for patients that wear these devices during prolonged periods of time. Flexibility of the devices is unique as most other safety devices are made from stiff, mechanically complex plastics. The geometry of these designs can be modified to satisfy specific criteria, including the need to use this device with a “dual implanted port,” which may be limited by larger foot-print of other existing devices, and various clinical preferences. Patient comfort is provided in that softer materials are in contact with patient. The ability to use materials that minimize patient allergenic reactions. As discussed above, lower profile and smaller foot-print reduce patient discomfort. Scalability is achieved in that various design features may be used in conjunction with one another as desired.

The present disclosure is provided to allow practice of the invention, after the expiration of any patent granted hereon, by those skilled in the art without undue experimentation, and

14

includes the best mode presently contemplated and the presently preferred embodiment. Nothing in this disclosure is to be taken to limit the scope of the invention, which is susceptible to numerous alterations, equivalents and substitutions without departing from the scope and spirit of the invention.

I claim:

1. A device for protecting a user from a sharp tip of a medical needle, the device comprising:

a central body portion connected with a delivery tube;

the medical needle having a first end and a second end in opposition to one another, the first end in fluid connection with the delivery tube, and the second end of the needle extending away from the central body portion to the sharp tip;

a pair of wings having an inner region and an outer region, the inner region of each one of the pair of wings in attachment to the central body portion, the outer region of each one of the pair of wings extending away from the central body portion, the pair of wings disposed in opposition to one another with the medical needle positioned therebetween, and the pair of wings being selectively positionable from a first position to a second position, the first position for placing the medical needle into a patient and delivering a medicinal fluid, and the second position for removing the medical needle from the patient;

a mechanical fastener disposed on at least one wing of the pair of wings, the mechanical fastener configured to selectively attach the pair of wings together in the second position with the medical needle positioned therebetween so as to protect the user from the sharp tip of the medical needle;

the mechanical fastener including:

a first mechanical fastener including a lip extending along at least a portion of the perimeter of at least one wing of the pair of wings, and a mating portion along a perimeter of at least the other wing of the pair of wings, the mating portion and the lip configured to engage with one another to selectively align the pair of wings together with the medical needle positioned therebetween so as to protect the user from the sharp tip of the medical needle; and

a second mechanical fastener different from said first mechanical fastener.

2. The device in accordance with claim 1, wherein the second mechanical fastener includes one of the wings forming an orifice therein, a pin extending from the other one of the wings, and the pin and the orifice are configured to engage with one another to selectively attach the pair of wings together with the medical needle positioned therebetween so as to protect the user from the sharp tip of the medical needle.

3. The device in accordance with claim 2, wherein the orifice has a diameter, the pin has a diameter, and the diameter of the orifice is smaller than the diameter of the pin.

4. The device in accordance with claim 2, wherein the orifice has a major axis and a minor axis, the pin has a diameter, the major axis of the orifice is longer than the diameter of the pin, and the minor axis of the orifice is shorter than the diameter of the pin.

5. The device in accordance with claim 1, wherein the second mechanical fastener includes a first portion in attachment to one of the wings, a second portion in attachment to the other one of the wings, and the first portion and the second portion are configured to engage with one another to selectively attach the pair of wings together with the medical needle positioned therebetween so as to protect the user from the sharp tip of the medical needle.

15

6. The device in accordance with claim 1, wherein the second mechanical fastener includes a snap button having a male portion and a female portion, the male portion of the snap button mounted to one of the wings, the female portion of the snap button mounted to the other one of the wings, and the male portion and the female portion of the snap button are configured to engage with one another to selectively attach the pair of wings together with the medical needle positioned therebetween so as to protect the user from the sharp tip of the medical needle.

7. The device in accordance with claim 1, wherein the second mechanical fastener includes one of the wings forming a plurality of orifices therein, a plurality of pins extending from the other one of the wings, and the plurality of pins and the plurality of orifices are configured to engage with one another to selectively attach the pair of wings together with the medical needle positioned therebetween so as to protect the user from the sharp tip of the medical needle.

8. The device in accordance with claim 1, wherein the wings have a circular shape.

9. The device in accordance with claim 1, wherein the wings have a rectangular shape.

10. The device in accordance with claim 1, wherein the wings have an elliptical shape.

16

11. The device in accordance with claim 1, wherein the second mechanical fastener includes at least one of the wings having an adhesive material, and the adhesive material is configured to engage with the other one of the wings to attach the pair of wings together with the medical needle positioned therebetween so as to protect the user from the sharp tip of the medical needle.

12. The device in accordance with claim 1, wherein at least one of the wings forms a groove therein with a size for housing the medical needle after the pair of wings are attached to one another.

13. The device in accordance with claim 12, wherein the groove is formed in a single one of the wings.

14. A method of protecting a user from a sharp tip of a medical needle, the method comprising:  
 providing a device according to claim 1;  
 withdrawing the sharp tip of the medical needle from the patient;  
 closing the pair of wings with the medical needle positioned therebetween; and  
 fastening the pair of wings together with the medical needle positioned therebetween so as to protect the user from the sharp tip of the medical needle.

\* \* \* \* \*