

(12) **United States Patent**
Smith

(10) **Patent No.:** **US 10,935,120 B2**
(45) **Date of Patent:** **Mar. 2, 2021**

(54) **AXLE ASSEMBLY HAVING A SPIGOT BEARING ASSEMBLY**

(71) Applicant: **ArvinMeritor Technology, LLC**, Troy, MI (US)

(72) Inventor: **Mark Smith**, Troy, MI (US)

(73) Assignee: **ArvinMeritor Technology, LLC**, Troy, MI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 168 days.

(21) Appl. No.: **16/206,182**

(22) Filed: **Nov. 30, 2018**

(65) **Prior Publication Data**

US 2020/0173531 A1 Jun. 4, 2020

(51) **Int. Cl.**

H02K 7/08 (2006.01)
H02K 7/116 (2006.01)
F16H 48/42 (2012.01)
H02K 11/21 (2016.01)
F16C 19/36 (2006.01)
F16H 57/021 (2012.01)

(Continued)

(52) **U.S. Cl.**

CPC **F16H 48/42** (2013.01); **F16C 19/361** (2013.01); **F16H 57/021** (2013.01); **F16H 57/037** (2013.01); **H02K 5/1732** (2013.01); **H02K 5/20** (2013.01); **H02K 7/083** (2013.01); **H02K 7/116** (2013.01); **H02K 9/19** (2013.01); **H02K 11/21** (2016.01); **H02K 24/00** (2013.01); **F16C 2380/26** (2013.01); **F16H 48/11** (2013.01); **F16H 2048/426** (2013.01); **F16H 2057/02034** (2013.01); **F16H 2057/02052** (2013.01)

(58) **Field of Classification Search**

CPC H02K 7/00-7/20; H02K 5/173-5/1737;

H02K 7/006; H02K 11/21; H02K 5/1732; H02K 5/20; H02K 7/083; H02K 7/116; H02K 9/19; H02K 24/00; H02K 7/08; H02K 7/088; F16H 48/42; F16H 57/021; F16H 57/037; F16H 48/11; F16H 2048/426; F16H 2057/02034; F16H 2057/02052; F16C 19/361; F16C 2380/26; B60K 2001/001

USPC 310/90
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,338,154 A 1/1944 Wilkinson
4,304,152 A 12/1981 Michling
(Continued)

FOREIGN PATENT DOCUMENTS

DE 15 63 051 A1 3/1970
DE 2005047 A1 8/1971
(Continued)

OTHER PUBLICATIONS

Machine Translation, Katsuno, WO-2015129823-A1, Sep. 2015. (Year: 2015).*

(Continued)


Primary Examiner — Thomas Truong

(74) *Attorney, Agent, or Firm* — Brooks Kushman PC

(57) **ABSTRACT**

An axle assembly having a spigot bearing assembly. The spigot bearing assembly may extend between a motor housing and a rotor output flange that may be fixedly mounted to a rotor. The spigot bearing assembly may rotatably support the rotor output flange and may inhibit deflection of the rotor. A spigot bearing biasing member may exert a biasing force on the spigot bearing assembly.

20 Claims, 26 Drawing Sheets



(51) Int. Cl.		2018/0109222 A1	4/2018	Suzuki
F16H 57/037	(2012.01)	2019/0054816 A1	2/2019	Garcia et al.
H02K 5/173	(2006.01)	2019/0054817 A1	2/2019	Garcia et al.
H02K 5/20	(2006.01)	2019/0054818 A1*	2/2019	Garcia B60K 17/02
H02K 9/19	(2006.01)	2020/0204051 A1*	6/2020	An H02K 5/1732
H02K 24/00	(2006.01)			
F16H 48/11	(2012.01)			
F16H 57/02	(2012.01)			

FOREIGN PATENT DOCUMENTS

DE	3036465 A1	5/1982	
DE	4120262 A1	5/1992	
DE	19827756 A1	12/1999	
DE	19915926 A1	3/2000	
DE	19952625 A1	6/2001	
DE	10049197 A1	4/2002	
DE	10226572 A1	1/2004	
DE	102004038882 A1	3/2005	
DE	102010061217 A1	6/2012	
DE	10 2011 007255 A1	10/2012	
DE	102011007253 A1	10/2012	
DE	102011007257 A1	10/2012	
DE	102011007268 A1	10/2012	
EP	0677414 A2	10/1995	
EP	2444265 A1	4/2012	
JP	S57059124 U	4/1982	
JP	2004185207 A	7/1992	
JP	2003019911 A	1/2003	
WO	2013029682 A1	3/2013	
WO	WO-2015129823 A1 *	9/2015 B23Q 1/70
WO	2016132800 A1	8/2016	
WO	2017114423 A1	7/2017	

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,676,667 A	6/1987	Komatsu et al.	
5,603,671 A	2/1997	Schmidt	
6,126,207 A	10/2000	Ives	
6,216,560 B1	4/2001	Takada et al.	
7,316,627 B2	1/2008	Bennett	
7,455,612 B2	11/2008	Teraoka	
7,517,154 B2	4/2009	McKeiman, Jr.	
7,530,912 B2	5/2009	Kramer	
8,858,379 B2	10/2014	Keeney et al.	
9,022,890 B2	5/2015	Smetana et al.	
9,033,107 B2	5/2015	Schneider et al.	
2003/0125150 A1	7/2003	Tanzer	
2005/0124450 A1	6/2005	Gady et al.	
2005/0176543 A1	8/2005	Kirkwood et al.	
2005/0187058 A1	8/2005	Teraoka	
2006/0094552 A1	5/2006	Duncan	
2007/0275816 A1	11/2007	Henderson	
2008/0146396 A1	6/2008	Millar	
2008/0174190 A1	7/2008	Kurata et al.	
2010/0000807 A1	1/2010	Rodriguez et al.	
2010/0180720 A1	7/2010	Kempf et al.	
2011/0290071 A1	12/2011	Giessner	
2012/0238387 A1	9/2012	Stuart	
2013/0005526 A1	1/2013	Matsubara et al.	
2013/0017927 A1	1/2013	Morscheck et al.	
2013/0296094 A1	11/2013	Mack et al.	
2014/0087906 A1*	3/2014	Keeney B60L 15/2009	
		475/150	
2014/0128192 A1	5/2014	Korenaga et al.	
2014/0141918 A1	5/2014	Fukami et al.	
2014/0191604 A1*	7/2014	Hawkins F16C 32/0442	
		310/90.5	
2014/0262675 A1	9/2014	Sugiyama et al.	
2014/0274529 A1	9/2014	Edler et al.	
2015/0151634 A1	6/2015	Smetana	
2015/0330492 A1	11/2015	Lee et al.	
2016/0053880 A1	2/2016	Peura	
2016/0355084 A1	12/2016	Uozumi et al.	
2017/0057349 A1	3/2017	Ogawa et al.	

OTHER PUBLICATIONS

“Spigot, n.” OED Online. Oxford University Press, Jun. 2020. Web. Jul. 12, 2020. (Year: 2020).*

European Extended Search Report dated Mar. 27, 2020 for related European Appin. No. 19211014.6; 8 Pages.

Pedro Garcia, et al., U.S. Appl. No. 15/680,436, filed Aug. 18, 2017.

Pedro Garcia, et al., U.S. Appl. No. 15/680,468, filed Aug. 18, 2017.

Pedro Garcia, et al., U.S. Appl. No. 15/680,559, filed Aug. 18, 2017.

Dhanapal Vittala Raya, et al., U.S. Appl. No. 16/205,586, filed Nov. 30, 2018.

Mark Smith, et al., U.S. Appl. No. 16/205,623, filed Nov. 30, 2018.

Rodrigo Soffner, et al., U.S. Appl. No. 16/205,663, filed Nov. 30, 2018.

Angel Begov, et al., U.S. Appl. No. 16/205,717, filed Nov. 30, 2018.

Mark Smith, et al., U.S. Appl. No. 16/205,771, filed Nov. 30, 2018.

Tao Peng, et al., U.S. Appl. No. 16/205,850, filed Nov. 30, 2018.

United States Patent and Trademark Office, Non-Final Office Action for U.S. Appl. No. 16/205,771, dated Sep. 18, 2019.

* cited by examiner




Fig-1




Fig-3





Fig-4






Fig-6




Fig-7




Fig-8




Fig-9




Fig-10




Fig-12




Fig-13




Fig-14




Fig-15




Fig-16




Fig-17




Fig-18




Fig-19




Fig-20




Fig-21




Fig-22




Fig-23




Fig-24




Fig-25




Fig-26

AXLE ASSEMBLY HAVING A SPIGOT BEARING ASSEMBLY

TECHNICAL FIELD

This disclosure relates to an axle assembly that includes a spigot bearing assembly that may help rotatably support a rotor.

BACKGROUND

An axle assembly having an electric motor module is disclosed in U.S. Pat. No. 8,858,379.

SUMMARY

In at least one embodiment, an axle assembly is provided. The axle assembly may include a differential carrier, a motor cover, a motor housing, a rotor, a rotor output flange, a first rotor bearing assembly, a second rotor bearing assembly, and a spigot bearing assembly. The motor housing may extend between the differential carrier and the motor cover. The rotor may be received in the motor housing and may be rotatable about an axis. The rotor output flange may be fixedly mounted to the rotor. The first and second rotor bearing assemblies may be disposed on the differential carrier and may rotatably support the rotor. The spigot bearing assembly may extend between the motor cover and the rotor output flange. The spigot bearing assembly may rotatably support the rotor output flange to inhibit deflection of the rotor.

In at least one embodiment, an axle assembly is provided. The axle assembly may include a motor housing that may extend from a differential carrier to a motor cover. A rotor that may be rotatable about an axis may be received in the motor housing. A rotor output flange may be fixedly mounted to the rotor and may be at least partially received in the motor cover. First and second rotor bearing assemblies may be disposed on the differential carrier and may rotatably support the rotor. A spigot bearing assembly may extend between the motor cover and the rotor output flange to rotatably support the rotor output flange. A spigot bearing biasing member may exert a biasing force on the spigot bearing assembly to inhibit skidding.

In at least one embodiment, an axle assembly is provided. The axle assembly may include a motor housing that may extend between a differential carrier and a motor cover. A rotor may be received in the motor housing and may be rotatable about an axis. A rotor output flange may be fixedly mounted to the rotor and may be at least partially received in the motor cover. First and second rotor bearing assemblies may rotatably support the rotor on the differential carrier. A spigot bearing assembly may receive and may rotatably support the rotor output flange. A spigot bearing biasing member may exert a biasing force on the spigot bearing assembly and the second rotor bearing assembly.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of an axle assembly.

FIG. 2 is a section view of the axle assembly along section line 2-2 showing a shift collar in a first position.

FIG. 3 is a section view of the axle assembly showing the shift collar in a second position.

FIG. 4 is a section view of the axle assembly showing the shift collar in a third position.

FIG. 5 is a magnified view of a portion of FIG. 2

FIG. 6 is a magnified view of a portion of FIG. 2.

FIGS. 7-20 are exploded views of the axle assembly.

FIG. 21 is a section view of a portion of an electric motor module of the axle assembly along section line 21-21.

FIG. 22 is a magnified section view of an example of a spigot bearing assembly that may be provided with the axle assembly.

FIG. 23 is a schematic representation of the axle system that includes the axle assembly and a control system.

FIG. 24 is a magnified section view of a portion of the axle assembly through a tone ring that is disposed on a planet gear carrier and an associated speed sensor.

FIG. 25 illustrates a planetary gear set that may be provided with a gear reduction module.

FIG. 26 is a magnified view of a portion of FIG. 25.

DETAILED DESCRIPTION

As required, detailed embodiments of the present invention are disclosed herein; however, it is to be understood that the disclosed embodiments are merely exemplary of the invention that may be embodied in various and alternative forms. The figures are not necessarily to scale; some features may be exaggerated or minimized to show details of particular components. Therefore, specific structural and functional details disclosed herein are not to be interpreted as limiting, but merely as a representative basis for teaching one skilled in the art to variously employ the present invention.

Referring to FIG. 1, an example of an axle assembly 10 is shown. The axle assembly 10 may be provided with a motor vehicle like a truck, bus, farm equipment, mining equipment, military transport or weaponry vehicle, or cargo loading equipment for land, air, or marine vessels. The motor vehicle may include a trailer for transporting cargo in one or more embodiments.

Referring to FIGS. 1 and 23, the axle assembly 10 may provide torque to one or more traction wheel assemblies that may include a tire 12 mounted on a wheel 14. The wheel 14 may be mounted to a wheel hub 16 that may be rotatable about a wheel axis 18.

One or more axle assemblies may be provided with the vehicle. As is best shown with reference to FIGS. 1 and 2, the axle assembly 10 may include a housing assembly 20, a drive pinion 22, an electric motor module 24, a gear reduction module 26, a shift mechanism 28, a differential assembly 30, and at least one axle shaft 32.

Housing Assembly

Referring to FIG. 1, the housing assembly 20 may receive various components of the axle assembly 10. In addition, the housing assembly 20 may facilitate mounting of the axle assembly 10 to the vehicle. In at least one configuration, the housing assembly 20 may include an axle housing 40 and a differential carrier 42.

The axle housing 40 may receive and may support the axle shafts 32. In at least one embodiment, the axle housing 40 may include a center portion 50 and at least one arm portion 52.

The center portion 50 may be disposed proximate the center of the axle housing 40. The center portion 50 may define a cavity that may receive the differential assembly 30. As is best shown in FIG. 2, a lower region of the center portion 50 may at least partially define a sump portion that may contain a first lubricant. Splashed lubricant may flow down the sides of the center portion 50 and may flow over various internal components of the axle assembly 10 and

gather in the sump portion. The sump portion may be part of a first lubricant chamber as will be discussed in more detail below.

The center portion **50** may include a carrier mounting surface **56**. The carrier mounting surface **56** may facilitate mounting of the differential carrier **42** to the axle housing **40**. For example, the carrier mounting surface **56** may face toward and may engage the differential carrier **42** and may have a set of holes that may be aligned with corresponding holes on the differential carrier **42**. Each hole may receive a fastener, such as a bolt, that may couple the differential carrier **42** to the axle housing **40**.

Referring to FIG. 1, one or more arm portions **52** may extend from the center portion **50**. For example, two arm portions **52** may extend in opposite directions from the center portion **50** and away from the differential assembly **30**. The arm portions **52** may have substantially similar configurations. For example, the arm portions **52** may each have a hollow configuration or tubular configuration that may extend around and may receive a corresponding axle shaft **32** and may help separate or isolate the axle shaft **32** or a portion thereof from the surrounding environment. An arm portion **52** or a portion thereof may be integrally formed with the center portion **50**. Alternatively, an arm portion **52** may be separate from the center portion **50**. In such a configuration, each arm portion **52** may be attached to the center portion **50** in any suitable manner, such as by welding or with one or more fasteners. An arm portion may rotatably support an associated wheel hub **16**. It is also contemplated that the arm portions **52** may be omitted.

Referring to FIGS. 1 and 2, the differential carrier **42**, which may also be called a carrier housing, may be mounted to the center portion **50** of the axle housing **40**. The differential carrier **42** may support the differential assembly **30** and may facilitate mounting of the electric motor module **24**. As is best shown with reference to FIGS. 2, 7 and 14, the differential carrier **42** may include one or more bearing supports **60**, a mounting flange **62**, and a bearing support wall **64**.

Referring to FIGS. 7 and 14, the bearing support **60** may support a roller bearing assembly that may rotatably support the differential assembly **30**. For example, two bearing supports **60** may be received in the center portion **50** and may be located proximate opposite sides of the differential assembly **30**. The bearing support **60** may be provided in various configurations. For example, a bearing support **60** may include a pair of legs that extend from the differential carrier **42**. A bearing cap may be mounted to the legs and may arch over a roller bearing assembly that may rotatably support the differential assembly **30**. As another example, the bearing support **60** may be received in a roller bearing assembly which in turn may support the differential assembly **30**.

The mounting flange **62** may facilitate mounting of the electric motor module **24**. The mounting flange **62** may be configured as a ring that may extend outward and away from a first axis **70** and may extend around the first axis **70**. The mounting flange **62** may include a set of fastener holes **72**. The fastener holes **72** may be spaced apart from each other and may be threaded in one or more configurations. Each fastener hole **72** may be configured to receive a fastener **74** that may secure the electric motor module **24** to the mounting flange **62** as will be discussed in more detail below. In at least one configuration, the mounting flange **62** may include an abutment surface **76** and a locating ring **78**.

The abutment surface **76** may face toward the electric motor module **24**, or to the right from the perspective shown

in FIG. 3. In at least one configuration, the abutment surface **76** may be disposed substantially perpendicular to the first axis **70**. The abutment surface **76** may be disposed closer to the first axis **70** than the locating ring **78**.

The locating ring **78** may be configured to receive a portion of the electric motor module **24** as will be discussed in more detail below. The locating ring **78** may extend around the first axis **70** and may protrude from the abutment surface **76**. For instance, the locating ring **78** may extend in an axial direction that may extend away from the axle housing **40**. The locating ring **78** may include or define a ring end surface **80** and an inner ring surface **82**.

The ring end surface **80** may be axially offset from the abutment surface **76**. For example, the ring end surface **80** may be disposed further from the axle housing **40** than the abutment surface **76**. In at least one configuration, the ring end surface **80** may be disposed substantially perpendicular to the first axis **70** and may be configured to engage a motor housing of the electric motor module **24** as will be discussed in more detail below.

The inner ring surface **82** may extend from the abutment surface **76** to the ring end surface **80**. For instance, the inner ring surface **82** may extend from the abutment surface **76** to an end of the ring end surface **80**. The inner ring surface **82** may face toward the first axis **70** and may extend around and may receive at least a portion of a coolant jacket of the electric motor module **24** as will be discussed in more detail below.

Referring to FIGS. 2 and 7, the bearing support wall **64** may support bearings that may rotatably support other components of the axle assembly **10**. For example, the bearing support wall **64** may support bearings that may rotatably support the drive pinion **22**, bearings that may rotatably support a rotor of the electric motor module **24**, or both. The bearing support wall **64** may extend in an axial direction away from the axle housing **40** and may extend around the first axis **70**. As such, the bearing support wall **64** may define a hole **90** that may receive the drive pinion **22** and various other components as will be discussed in more detail below. In addition, the bearing support wall **64** may be radially positioned between the first axis **70** and the electric motor module **24**. The bearing support wall **64** may be integrally formed with the differential carrier **42** or may be a separate component that is fastened to the differential carrier **42**.

Referring to FIGS. 5 and 7, the exterior side of the bearing support wall **64** that faces away from the first axis **70** may have a stepped configuration that may generally become narrower as the distance from the axle housing **40** increases. Such a configuration may include a first circumferential surface **100**, a second circumferential surface **102**, and a third circumferential surface **104**.

The first circumferential surface **100** may extend around the first axis **70** and may face away from the first axis **70**. The first circumferential surface **100** may support a first rotor bearing assembly as will be discussed in more detail below.

The second circumferential surface **102** may be axially positioned between the first circumferential surface **100** and the third circumferential surface **104**. The second circumferential surface **102** may have a smaller diameter than the first circumferential surface **100**.

The third circumferential surface **104** may be axially positioned between the second circumferential surface **102** and an end surface **106** of the bearing support wall **64**. The third circumferential surface **104** may have a smaller diameter than the second circumferential surface **102**. The third

5

circumferential surface **104** may support a second rotor bearing assembly as will be discussed in more detail below.

A groove **108** may be provided in the third circumferential surface **104**. The groove **108** may extend toward the first axis **70** and may be axially positioned between the second circumferential surface **102** and the end surface **106**. The groove **108** may receive a retainer, such as a snap ring, as will be discussed in more detail below.

Drive Pinion

Referring to FIG. 2, the drive pinion **22** may provide torque to a ring gear **110** that may be provided with the differential assembly **30**. Moreover, in an axle assembly that includes a gear reduction module **26**, the drive pinion **22** may operatively connect a planetary gear set of the gear reduction module **26** to the differential assembly **30**. The drive pinion **22** may extend along and may be rotatable about the first axis **70** while the ring gear **110** may be rotatable about the wheel axis **18**. In addition, the drive pinion **22** may extend through the hole **90** in the bearing support wall **64** and through a hole in a motor cover as will be discussed in more detail below. In at least one configuration, such as is best shown with reference to FIGS. 2, 9 and 16, the drive pinion **22** may include a gear portion **120** and a shaft portion **122**.

The gear portion **120** may be disposed at or near an end of the shaft portion **122**. The gear portion **120** may have a plurality of teeth that may mate with corresponding teeth on the ring gear **110**. The gear portion **120** may be integrally formed with the shaft portion **122** or may be provided as a separate component that may be fixedly disposed on the shaft portion **122**.

The shaft portion **122** may extend from the gear portion **120** in a direction that extends away from the axle housing **40**. As is best shown with reference to FIGS. 9 and 16, the shaft portion **122** may include a first outer surface **130**, a second outer surface **132**, a third outer surface **134**, a fourth outer surface **136**, a threaded portion **138**, and a spline **140**.

Referring to FIGS. 5, 9 and 16, the first outer surface **130** may extend from the gear portion **120** and may be an outside circumference of a portion of the shaft portion **122**. A first drive pinion bearing **150** may be disposed on the first outer surface **130** and may rotatably support the drive pinion **22**. The first drive pinion bearing **150** may have any suitable configuration. For instance, the first drive pinion bearing **150** may be configured as a roller bearing assembly that may include a plurality of rolling elements **152** that may be disposed between an inner race **154** and an outer race **156**. The inner race **154** may extend around and may be disposed on the first outer surface **130**. The outer race **156** may extend around the rolling elements **152** and may be disposed on the bearing support wall **64** of the differential carrier **42** and may be received in the hole **90** of the bearing support wall **64**.

The second outer surface **132** may be axially positioned between the first outer surface **130** and the third outer surface **134**. The second outer surface **132** may be an outside circumference of a portion of the shaft portion **122** and may have a smaller diameter than the first outer surface **130**. One or more spacer rings **160** may be disposed on the second outer surface **132**. The spacer rings **160** may be disposed between the inner races of the drive pinion bearings to inhibit axial movement of the drive pinion bearings toward each other.

The third outer surface **134** may be axially positioned between the second outer surface **132** and the fourth outer surface **136**. The third outer surface **134** may be an outside circumference of a portion of the shaft portion **122** and may have a smaller diameter than the second outer surface **132**.

6

A second drive pinion bearing **170** may be disposed on the third outer surface **134** and may rotatably support the drive pinion **22**. The second drive pinion bearing **170** may have any suitable configuration. For instance, the second drive pinion bearing **170** may be configured as a roller bearing assembly that may include a plurality of rolling elements **172** that may be disposed between an inner race **174** and an outer race **176**. The inner race **174** may extend around and may be disposed on the third outer surface **134**. The outer race **176** may extend around the rolling elements **172**, may be disposed on the bearing support wall **64** of the differential carrier **42**, and may be received in the hole **90** of the bearing support wall **64**. The inner race **174** of the second drive pinion bearing **170** may have a smaller inside diameter than the inner race **154** of the first drive pinion bearing **150**. The outer race **176** of the second drive pinion bearing **170** may have a smaller outside diameter than the outer race **156** of the first drive pinion bearing **150**.

The fourth outer surface **136** may be axially positioned between the third outer surface **134** and the threaded portion **138**. The fourth outer surface **136** may be an outside circumference of a portion of the shaft portion **122** and may have a smaller diameter than the third outer surface **134**.

A seal support ring **180** may be disposed on the fourth outer surface **136**. The seal support ring **180** may extend around the first axis **70** and may have a hole **182** that may receive the drive pinion **22**. Moreover, the seal support ring **180** may engage and may facilitate sealing against the fourth outer surface **136** to help separate the axle assembly **10** into first and second lubricant chambers as will be discussed in more detail below. The seal support ring **180** may engage the inner race **174** of the second drive pinion bearing **170** and may support one or more seals as will be discussed in more detail below.

The threaded portion **138** may be axially positioned between the fourth outer surface **136** and the spline **140**. The threaded portion **138** may facilitate installation of a preload nut **190**.

The preload nut **190** may be threaded onto the threaded portion **138** and may secure the seal support ring **180** to the drive pinion **22**. The seal support ring **180** may be axially positioned between the inner race **174** of the second drive pinion bearing **170** and the preload nut **190**. The preload nut **190** may apply a preload force on the first and second drive pinion bearings **150**, **170** via the seal support ring **180**. As is best shown in FIG. 5, a portion of the seal support ring **180** may overhang and may extend around the preload nut **190** and may be configured to support a seal as will be discussed in more detail below.

The spline **140** may be disposed between the threaded portion **138** and an end of the shaft portion **122** that may be disposed opposite the gear portion **120**. The spline **140** may include a plurality of teeth. The teeth may be disposed substantially parallel to the first axis **70** and may mate with a corresponding spline on a shift collar of the shift mechanism **28** as will be discussed in more detail below. Alternatively, the teeth of the spline **140** may mate with a corresponding spline of a rotor output flange that may couple the drive pinion **22** to a rotor of the electric motor module **24** when the gear reduction module **26** and shift mechanism **28** are omitted.

Electric Motor Module

Referring to FIG. 2, the electric motor module **24** may be mounted to the differential carrier **42** and may provide torque to the differential assembly **30** via the drive pinion **22**. The electric motor module **24** may be primarily disposed outside the differential carrier **42**. In addition, the electric

motor module **24** may be axially positioned between the axle housing **40** and the gear reduction module **26** and the axle housing **40**. Main components of the electric motor module **24** are best shown with reference to FIGS. **7**, **8**, **11**, **14**, **15** and **18**. In at least one configuration, the electric motor module **24** may include a motor housing **200**, a coolant jacket **202**, a stator **204**, a rotor **206**, a first rotor bearing assembly **208**, a second rotor bearing assembly **210**, a rotor bearing preload module **212**, and a motor cover **214**.

Referring to FIGS. **2**, **7**, **14** and **21**, the motor housing **200** may extend between the differential carrier **42** to the motor cover **214**. For example, the motor housing **200** may extend from the mounting flange **62** of the differential carrier **42** to the motor cover **214**. The motor housing **200** may extend around a first axis **70** to define a motor housing cavity **220**. The motor housing cavity **220** may have a generally cylindrical configuration. The motor housing **200** may extend continuously around and may be spaced apart from the bearing support wall **64** of the differential carrier **42**. In at least one configuration, the motor housing **200** may have an exterior surface **222**, an interior surface **224**, a first end surface **226**, a second end surface **228**, a set of fastener holes **230**, and one or more ports **232**.

The exterior surface **222** may face away from the first axis **70** and may define an exterior or outside surface of the motor housing **200**.

The interior surface **224** may be disposed opposite the exterior surface **222**. The interior surface **224** may be disposed at a substantially constant radial distance from the first axis **70** in one or more configurations.

The first end surface **226** may extend between the exterior surface **222** and the interior surface **224**. The first end surface **226** may be disposed at an end of the motor housing **200** that may face toward the differential carrier **42**. More specifically, the first end surface **226** may be disposed adjacent to the mounting flange **62** of the differential carrier **42**. As is best shown in FIG. **21**, the first end surface **226** may engage the ring end surface **80** of the locating ring **78** of the differential carrier **42**. However, the motor housing **200** and the first end surface **226** may not be received inside the mounting flange **62** of the differential carrier **42**.

The second end surface **228** may be disposed opposite the first end surface **226**. As such, the second end surface **228** may be disposed at an end of the motor housing **200** that may face toward and may engage the motor cover **214**. The second end surface **228** may extend between the exterior surface **222** and the interior surface **224**. In at least one configuration, the second end surface **228** may not be received inside the motor cover **214**.

The set of fastener holes **230** may be arranged around the first axis **70** and may be aligned with the fastener holes **72** of the differential carrier **42**. As such, the fastener holes **230** may be spaced apart from each other and may be disposed substantially parallel to each other and substantially parallel to the first axis **70**. Each fastener hole **230** may be between the first end surface **226** to the second end surface **228**. For example, the fastener holes **230** may extend from the first end surface **226** to the second end surface **228**. Each fastener hole **230** may receive a fastener **74** that may secure the motor housing **200** to the mounting flange **62**, the motor cover **214**, or both. For example, each fastener **74** may extend through the fastener hole **230** and may protrude from the first end surface **226** and the second end surface **228**. Opposing ends of the fastener **74** may be threaded. For example, one threaded end may be received in the fastener hole **72** of the differential carrier **42** and may mate with the threads of the fastener hole **72** of the differential carrier **42**.

Alternatively, the fastener **74** may extend through the fastener hole **72** of the differential carrier **42** and may be received in a nut that may secure the motor housing **200** to the differential carrier **42**. Similarly, an opposing threaded end of a fastener **74** may mate with threads of a fastener hole of the motor cover **214** or may extend through a fastener hole in the motor cover **214** and may be received in a nut that may secure the motor cover **214** to the motor housing **200**.

Referring to FIGS. **7** and **14**, one or more ports **232** may extend through the motor housing **200**. The ports **232** may be configured as a through holes that may extend from the exterior surface **222** to the interior surface **224**. The ports **232** may allow coolant, such as a fluid like water, to flow to and from the coolant jacket **202** as will be described in more detail below.

Referring to FIGS. **8**, **15** and **21**, the coolant jacket **202** may help cool or remove heat from the stator **204**. The coolant jacket **202** may be received in the motor housing cavity **220** and may engage the interior surface **224** of the motor housing **200**. The coolant jacket **202** may extend axially between the differential carrier **42** and the motor cover **214**. In addition, the coolant jacket **202** may extend around the first axis **70** and the stator **204**. In at least one configuration, the coolant jacket **202** may include a first coolant jacket end surface **240**, a second coolant jacket end surface **242**, a plurality of channels **244**, a first groove **246**, a second groove **248**, and a coolant jacket cavity **250**.

The first coolant jacket end surface **240** may be disposed at an end of the coolant jacket **202** and may face toward the differential carrier **42**. More specifically, the first coolant jacket end surface **240** may be disposed outside the motor housing **200** and may be received inside the mounting flange **62** of the differential carrier **42**. For instance, the first coolant jacket end surface **240** may face toward and may contact the abutment surface **76** of the differential carrier **42** and may be received inside the locating ring **78**.

The second coolant jacket end surface **242** may be disposed opposite the first coolant jacket end surface **240**. As such, the second coolant jacket end surface **242** may face toward the motor cover **214**. The second coolant jacket end surface **242** may be disposed outside the motor housing **200** and may be received inside a mounting flange of the motor cover **214**.

The channels **244** may extend around the first axis **70** and may be disposed opposite the coolant jacket cavity **250**. The channels **244** may be configured with an open side that may face away from the first axis **70** and toward the interior surface **224** of the motor housing **200**. The channels **244** may be axially positioned between the first coolant jacket end surface **240** and the second coolant jacket end surface **242**. Coolant may be provided to the coolant jacket **202** via a first port **232** and may exit the coolant jacket **202** via a second port **232**. For instance, coolant may flow from the first port **232** to the channels **244**, receive heat from the stator **204** as the coolant flows through the channels **244**, and exit at the second port **232**. A baffle may be provided with the coolant jacket **202** that may reverse the direction of coolant flow to help route coolant from the first port **232** to the second port **232**.

The first groove **246** may be provided in an exterior surface of the coolant jacket **202** that may face toward the interior surface **224** of the motor housing **200**. The first groove **246** may extend around the first axis **70** and may be axially positioned between the first coolant jacket end surface **240** and the channels **244**. The first groove **246** may receive a first seal **260**. The first seal **260** may seal against the interior surface **224** of the motor housing **200**. The first

seal 260 may have any suitable configuration. For example, the first seal 260 may be configured as an O-ring that may extend continuously around the coolant jacket 202.

The second groove 248 may be provided in the exterior surface of the coolant jacket 202. The second groove 248 may extend around the first axis 70 and may be axially positioned between the second coolant jacket end surface 242 and the channels 244. The second groove 248 may receive a second seal 262. The second seal 262 may seal against the interior surface 224 of the motor housing 200. The second seal 262 may have any suitable configuration. For example, the second seal 262 may be configured as an O-ring that may extend continuously around the coolant jacket 202. The first seal 260 and the second seal 262 may cooperate to inhibit or prevent leakage of coolant between the motor housing 200 and the coolant jacket 202.

The coolant jacket cavity 250 may be defined by the coolant jacket 202. The coolant jacket cavity 250 may be configured as a through hole that may extend from the first coolant jacket end surface 240 to the second coolant jacket end surface 242 and may be disposed opposite the channels 244. The coolant jacket cavity 250 may receive the stator 204.

The stator 204 may be fixedly positioned with respect to the coolant jacket 202. For example, the stator 204 may extend around the first axis 70 and may include stator windings 270 that may be received inside and may be fixedly positioned with respect to the coolant jacket 202, which are best shown in FIGS. 8 and 15.

The motor housing 200, coolant jacket 202, and the stator 204 may be preassembled to provide a subassembly that may be assembled other components. An example of an associated assembly sequence is as follows.

First, the coolant jacket 202 may be provided. The coolant jacket 202 may include the channels, grooves, and other features previously discussed.

Second, the stator windings 270 may be installed on the coolant jacket 202. Installing the stator windings 270 may include positioning the stator windings 270 inside the coolant jacket cavity 250 and against the inside circumference of the coolant jacket 202. The stator windings 270 may then be encapsulated or “potted” using any suitable encapsulation material, such as a polymeric material, epoxy resin, or the like. Encapsulation may help electrically insulate the stator windings 270 and may provide chemical and environmental protection.

Third, one or more seals may be installed on the coolant jacket 202. For instance, the first seal 260 may be installed in the first groove 246 and the second seal 262 may be installed in the second groove 248. The first seal 260 and the second seal 262 may protrude past the outside circumference of the coolant jacket 202 when installed.

Fourth, the coolant jacket 202 along with the stator 204 may be installed in the motor housing cavity 220 of the motor housing 200. The motor housing 200 may be heated to expand or increase the size of the motor housing cavity 220 prior to installation. For instance, heating the motor housing 200 may increase the size or inside diameter of the motor housing cavity 220, which may facilitate installation of the coolant jacket 202 and help avoid displacement of the first and second seals 260, 262 and/or damage to the first and second seals 260, 262. The coolant jacket 202 along with the stator 204, first seal 260, and second seal 262, may be inserted into the motor housing cavity 220 once the motor housing 200 has been heated to a sufficient temperature or for a sufficient period of time to obtain a desired inside diameter.

Fifth the motor housing 200 may be allowed to cool. Cooling the motor housing 200 may reduce the size of the motor housing cavity 220 and may facilitate sealing between the motor housing 200 and the first and second seals 260, 262. Accordingly, the interior surface 224 of the motor housing 200 may engage and may compress against the first and second seals 260, 262. The motor housing 200 may be sufficiently cooled when it reaches ambient temperature or is sufficiently close to ambient temperature.

Sixth, quality checks may be conducted. Such quality checks may include a leak test and a high potential (“hipot”) withstand test.

The leak test may be conducted to determine whether a leak is present between the motor housing 200 and the coolant jacket 202. For example, a pressurized fluid, such as a gas or liquid may be provided via at least one port 232 to the channels 244. The fluid pressure may be monitored to determine whether a leak of a sufficient magnitude is present. For instance, sealing may be acceptable when the fluid pressure is maintained for a predetermined period of time.

The high potential withstand test made be conducted to determine whether the stator windings 270 are adequately insulated. For example, a standard test voltage may be applied to the stator windings 270 and a leakage current that flows through the insulation or encapsulation material may be monitored. Insulation of the stator windings 270 may be acceptable when the leakage current is less than a predetermined value or limit. It is contemplated that the leak test and the high potential withstand test may be conducted concurrently or sequentially. For example, the high potential withstand test may be conducted after the leak test in one or more configurations.

Seventh, the subassembly may be assembled to the differential carrier 42. The subassembly may include the motor housing 200, coolant jacket 202, the stator 204 and the first and second seals 260, 262. The motor housing 200 may be placed into engagement with the locating ring 78 of the mounting flange 62 of the differential carrier 42 such that the first end surface 226 of the motor housing 200 may engage the ring end surface 80 of the locating ring 78. The first coolant jacket end surface 240 may be received inside the locating ring 78 such that the inner ring surface 82 may extend around a portion of the coolant jacket 202 that protrudes from the motor housing 200. Fasteners 74 may be inserted through the fastener holes 230 in the motor housing 200 and into the fastener holes 72 of the mounting flange 62 of the differential carrier 42 and may be secured as previously discussed.

Eighth, the motor cover 214 may be mounted to and secured to the motor housing 200. For example, the motor cover 214 may be placed into engagement with the second end surface 228 of the motor housing 200. The fasteners 74 may facilitate securing of the motor cover 214. For example, the fasteners 74 may extend through corresponding fastener holes in the motor cover 214. The fasteners 74 may be received in nuts 280 that may secure motor cover 214 to the motor housing 200 as is best shown in FIG. 21.

Referring to FIGS. 2, 8 and 15, the rotor 206 may extend around the first axis 70 and may be received inside the stator 204 and the motor housing 200. The rotor 206 may be rotatable about the first axis 70 with respect to the differential carrier 42 and the stator 204. The rotor 206 may be spaced apart from the stator 204 but may be disposed close to the stator 204. The rotor 206 may include magnets or ferromagnetic material that may facilitate the generation of electrical current. The rotor 206 may extend around and may be supported by the bearing support wall 64. The rotor 206

may be operatively connected to the drive pinion 22 with or without a gear reduction module 26. For instance, the rotor 206 may be operatively connected to the drive pinion 22 between the end of the bearing support wall 64 and the motor cover 214, such as with a rotor output flange 290 as will be discussed in more detail below.

Referring to FIGS. 5, 8 and 15, the first rotor bearing assembly 208 may rotatably support the rotor 206. The first rotor bearing assembly 208 may receive the bearing support wall 64 of the differential carrier 42 and may be received inside of the rotor 206. The first rotor bearing assembly 208 may be axially positioned closer to the axle housing 40 than the second rotor bearing assembly 210. The first rotor bearing assembly 208 may have any suitable configuration. For instance, the first rotor bearing assembly 208 may include a plurality of rolling elements 300 that may be disposed between an inner race 302 and an outer race 304. The inner race 302 may extend around and may receive the bearing support wall 64 of the differential carrier 42. For example, the inner race 302 may extend around and may engage the first circumferential surface 100 of the bearing support wall 64. The outer race 304 may extend around the rolling elements 300 and may be disposed on the rotor 206.

The second rotor bearing assembly 210 may be spaced apart from the first rotor bearing assembly 208. The second rotor bearing assembly 210 may be positioned closer to the motor cover 214 than the first rotor bearing assembly 208. The second rotor bearing assembly 210 may have any suitable configuration. For instance, the second rotor bearing assembly 210 may include a plurality of rolling elements 310 that may be disposed between an inner race 312 and an outer race 314. The inner race 312 may extend around and may receive the bearing support wall 64 of the differential carrier 42. For example, the inner race 312 may extend around and may engage the third circumferential surface 104 of the bearing support wall 64. The outer race 314 may extend around the rolling elements 310 and may be disposed on the rotor 206.

The rotor bearing preload module 212 may be axially positioned between the first rotor bearing assembly 208 and the second rotor bearing assembly 210. In addition, the rotor bearing preload module 212 may receive and may extend around the bearing support wall 64. The rotor bearing preload module 212 may exert a preload force on at least one rotor bearing assembly. In addition, the rotor bearing preload module 212 may cooperate with various components to help position the rotor bearing assemblies and inhibit axial movement of the rotor bearing assemblies with respect to the bearing support wall 64. In at least one configuration, the rotor bearing preload module 212 may include a first bearing preload ring 320, a second bearing preload ring 322, and a biasing member 324.

The first bearing preload ring 320 may generally extend around the second circumferential surface 102 of the bearing support wall 64. In addition, the first bearing preload ring 320 may extend from the first rotor bearing assembly 208. For example, the first bearing preload ring 320 may engage the inner race 302 of the first rotor bearing assembly 208 and may be spaced apart from the outer race 304 of the first rotor bearing assembly 208. The first bearing preload ring 320 may be axially movable or movable in an axial direction with respect to the second bearing preload ring 322. In at least one configuration, the first bearing preload ring 320 may include a center portion 330, a first side portion 332, and a second side portion 334.

The center portion 330 may be axially positioned between the first side portion 332 and the second side portion 334.

The center portion 330 may be disposed on the differential carrier 42. For example, the center portion 330 may have a center portion inner surface 340 that may face toward the first axis 70 and may engage the second circumferential surface 102 of the bearing support wall 64. The center portion inner surface 340 may be disposed substantially parallel to the second circumferential surface 102 and may be generally smooth to facilitate sliding axial movement.

The first side portion 332 may extend from the center portion 330 to the first rotor bearing assembly 208. For example, the first side portion 332 may extend from the center portion 330 to the inner race 302 of the first rotor bearing assembly 208. The first side portion 332 may have a first inner surface 342 that may face toward the first axis 70. The first inner surface 342 or a portion thereof may have a larger diameter than the center portion inner surface 340. In addition, the first inner surface 342 or a portion thereof may be spaced apart from the bearing support wall 64 of the differential carrier 42.

The second side portion 334 may be disposed opposite the first side portion 332. The second side portion 334 may extend from the center portion 330 toward the second rotor bearing assembly 210. In addition, the second side portion 334 may extend around part of the second bearing preload ring 322. As such, the second side portion 334 may be spaced apart from the bearing support wall 64 of the differential carrier 42.

The second bearing preload ring 322 may extend around the second circumferential surface 102 and the third circumferential surface 104 of the bearing support wall 64. In addition, the second bearing preload ring 322 may extend from the second rotor bearing assembly 210. For example, the second bearing preload ring 322 may engage the inner race 312 of the second rotor bearing assembly 210 and may be spaced apart from the outer race 314 of the second rotor bearing assembly 210. The second bearing preload ring 322 may be stationary and may not move in an axial direction. In at least one configuration, the second bearing preload ring 322 may include a bearing contact portion 350 and a guide portion 352.

The bearing contact portion 350 may extend from the second rotor bearing assembly 210. For example, the bearing contact portion 350 may engage or contact the inner race 312 of the second rotor bearing assembly 210. In addition, the bearing contact portion 350 may be disposed on the differential carrier 42. For instance, the bearing contact portion 350 may engage the third circumferential surface 104 of the bearing support wall 64. The bearing contact portion 350 may have a smaller diameter than the guide portion 352.

The guide portion 352 may be at least partially received inside the second side portion 334 of the first bearing preload ring 320. In addition, the guide portion 352 may extend around and may engage the second circumferential surface 102 of the bearing support wall 64. The guide portion 352 may extend in an axial direction from the bearing contact portion 350 toward the first rotor bearing assembly 208. As such, the guide portion 352 may extend toward the center portion 330 of the first bearing preload ring 320. The guide portion 352 may be spaced apart from the center portion 330 due to the biasing force exerted by the biasing member 324.

The biasing member 324 may bias the first bearing preload ring 320 in an axial direction with respect to the second bearing preload ring 322. For example, the biasing member 324 may exert a biasing force that may bias the first rotor bearing assembly 208 away from the second rotor bearing assembly 210 away from each other. As is best

shown in FIG. 5, the biasing member 324 may be disposed between the first bearing preload ring 320 and the second bearing preload ring 322. For instance, the biasing member 324 may extend from the second side portion 334 of the first bearing preload ring 320 to the guide portion 352 of the second bearing preload ring 322.

The biasing member 324 may have any suitable configuration. For example, biasing member 324 may extend around a portion of second bearing preload ring 322, such as the guide portion 352. In such a configuration, the biasing member 324 may be a spring like a wave spring or a wave washer that may extend continuously around the first axis 70. Alternatively, the biasing member 324 may not extend continuously around the first axis 70. It is also contemplated that multiple biasing members 324 may be provided. For instance, multiple biasing members 324 such as coil springs may be arranged at various locations around the first axis 70.

Referring to FIGS. 5 and 15, a first retaining member 360 may be positioned on an opposite side of the first rotor bearing assembly 208 from the first bearing preload ring 320. The first retaining member 360 may inhibit axial movement of the outer race 304 of the first rotor bearing assembly 208 toward the axle housing 40. The first retaining member 360 may be fixedly coupled to the rotor 206 in any suitable manner. For example, the first retaining member 360 may be received in a groove in the rotor 206. The first retaining member 360 may have any suitable configuration. For example, the first retaining member 360 may be configured as a protrusion, such as a snap ring, that may extend toward the first axis 70. The first retaining member 360 may be spaced apart from the inner race 302. Accordingly, the biasing force exerted by the biasing member 324 may actuate the inner race 302 with respect to the outer race 304.

A second retaining member 362 may be positioned on an opposite side of the second rotor bearing assembly 210 from the second bearing preload ring 322. The second retaining member 362 may inhibit axial movement of the inner race 312 of the second rotor bearing assembly 210 away from the axle housing 40. The second retaining member 362 may be coupled to the differential carrier 42 in any suitable manner. For example, the second retaining member 362 may be received in a groove 108 in the bearing support wall 64. The second retaining member 362 may have any suitable configuration. For example, the second retaining member 362 may be configured as a protrusion, such as a snap ring, that may extend away from the first axis 70. The second retaining member 362 may be spaced apart from the outer race 314.

Referring to FIGS. 2, 11, 18 and 21, the motor cover 214 may be mounted to the motor housing 200 and may be disposed opposite the axle housing 40. For example, the motor cover 214 may be mounted to the second end surface 228 of the motor housing 200. The motor cover 214 may be spaced apart from and may not engage the differential carrier 42. The motor cover 214 may be provided in various configurations. In at least one configuration, the motor cover 214 may include a first side 370 and a second side 372. The motor cover 214 may also include a motor cover opening 374 in configurations having a gear reduction module 26. Optionally, the motor cover 214 may include or may partially define one or more additional features, such as a locating ring 376, a junction box 378, an outer ring 380, and a resolver slot 382, and a bearing receiving surface 384.

Referring primarily to FIGS. 11, 18 and 21, the first side 370 may face toward the axle housing 40.

The second side 372 may be disposed opposite the first side 370. As such, the second side 372 may face away from the axle housing 40.

The motor cover opening 374 may extend between the first side 370 and the second side 372. The motor cover opening 374 may be a through hole that may extend around the first axis 70.

The locating ring 376 may be configured to receive a portion of the electric motor module 24. The locating ring 376 may have a similar configuration as the locating ring 78 of the differential carrier 42. The locating ring 376 may extend around the first axis 70 and may protrude from an abutment surface 390 toward the axle housing 40. The abutment surface 390 may face toward and may be disposed proximate or engage the second coolant jacket end surface 242 of the coolant jacket 202. The locating ring 376 may have a ring end surface 392 that may be axially offset from the abutment surface 390 and may engage the second end surface 228 of the motor housing 200. The locating ring 376 may extend around and may receive a portion of the coolant jacket 202 that may protrude from the motor housing 200 toward the first side 370 of the motor cover 214. A plurality of fastener holes 394 may be disposed proximate the locating ring 376. The fastener holes 394 may extend into or through the locating ring 376. Each fastener hole 394 may be aligned with a corresponding fastener hole 230 of the motor housing 200 and may receive a corresponding fastener 74 as previously discussed.

Referring to FIGS. 11 and 18, the junction box 378 or portion thereof may be provided with the motor cover 214. The junction box 378 may extend from the second side 372 and may receive components that may facilitate electrical connections to the electric motor module 24. The junction box 378 may be integrally formed with the motor cover 214 or may be provided as a separate component.

The outer ring 380 may extend from the second side 372. The outer ring 380 may extend continuously or discontinuously around the first axis 70. The outer ring 380 may provide multiple functions. For example, the outer ring 380 may act as a locating feature that may facilitate positioning and installation of a shift mechanism housing 900 as is best shown in FIG. 6. The outer ring 380 may also act as a stop that may inhibit axial movement of a planetary ring gear 714 of the gear reduction module 26. The outer ring 380 may also facilitate installation of a seal 400, such as an O-ring, that may extend between the shift mechanism housing 900 and the motor cover 214. For instance, the seal 400 may extend around the outer ring 380 and may be received inside the shift mechanism housing 900.

Referring to FIG. 11, the resolver slot 382 may be disposed between the first side 370 and the second side 372 of the motor cover 214. The resolver slot 382 may be configured as a through hole that may extend to the motor cover opening 374. The resolver slot 382 may receive a portion of a resolver 600 as will be discussed in more detail below.

Referring to FIGS. 6 and 18, the bearing receiving surface 384 may partially define the motor cover opening 374. The bearing receiving surface 384 may extend around the first axis 70 and may extend from or may be disposed adjacent to the first side 370 of the motor cover 214. The bearing receiving surface 384 may be configured to receive and may optionally contact a spigot bearing assembly 410. The spigot bearing assembly 410 may receive the rotor output flange 290 and may help inhibit deflection of the rotor 206 as will be discussed in more detail below. A groove 420 may extend from the bearing receiving surface 384 in a direction that may extend away from the first axis 70. The groove 420 may receive a seal 422, such as an O-ring, that may extend around and may contact the spigot bearing assembly 410.

Other mounting configurations for the spigot bearing assembly **410** will be discussed after discussing the rotor output flange **290** in more detail.

Rotor Output Flange

Referring to FIGS. **5**, **6**, **10** and **17**, the rotor output flange **290** may operatively connect or couple the electric motor module **24** to the gear reduction module **26**. For example, the rotor output flange **290** may couple the rotor **206** to a sun gear **710** of the gear reduction module **26** as will be discussed in more detail below. The rotor output flange **290** may be fixedly coupled to or fixedly mounted to the rotor **206**. As such, the rotor output flange **290** may rotate about the first axis **70** with the rotor **206**. The rotor output flange **290** may be partially disposed inside the bearing support wall **64** of the differential carrier **42** and may be partially disposed inside the motor housing **200** and the motor cover **214** of the electric motor module **24**. In addition, the rotor output flange **290** may extend through the motor cover opening **374** of the motor cover **214**. In at least one configuration, the rotor output flange **290** may include a tubular body **430** and a flange portion **432**.

The tubular body **430** may extend around the first axis **70** and may define a rotor output flange hole **434**. The rotor output flange hole **434** may be a through hole that may extend along and may be centered about the first axis **70**. The drive pinion **22** may extend through the rotor output flange hole **434** and may be spaced apart from the rotor output flange **290**. As is best shown in FIG. **6**, the sun gear **710** of the gear reduction module **26** may be partially received in the rotor output flange hole **434**. In at least one configuration, the tubular body **430** may include a rotor output flange spline **440**, an internal groove **442**, a first seal support surface **444**, a spigot bearing support surface **446**, a first outer groove **448**, a rotary disc support surface **450**, a second outer groove **452**, and a second seal support surface **454**.

The rotor output flange spline **440** may be disposed in the rotor output flange hole **434**. The rotor output flange spline **440** may have teeth that may be arranged around the first axis **70** and may extend toward the first axis **70**. The teeth of the rotor output flange spline **440** may mate with a spline of the sun gear **710** such that the rotor output flange **290** may rotate about the first axis **70** with the sun gear **710** and the rotor **206**.

As is best shown in FIG. **6**, the internal groove **442** may be disposed in the rotor output flange hole **434** and may extend away from the first axis **70**. The internal groove **442** may be axially positioned between a first end of the tubular body **430** that may face toward the axle housing **40** and the sun gear **710**. The internal groove **442** may receive a snap ring **460** or other suitable fastener that may help inhibit axial movement of the sun gear **710** toward the axle housing **40**. Optionally, a spacer **462** such as a washer may be received in the rotor output flange hole **434** and may be axially positioned between the internal groove **442** and the sun gear **710**.

The first seal support surface **444** may extend from the first end of the tubular body **430** to the flange portion **432**. The first seal support surface **444** may be disposed opposite the rotor output flange hole **434** and may be configured to support a seal as will be discussed in more detail below. The bearing support wall **64** may extend around at least a portion of the first seal support surface **444**.

The spigot bearing support surface **446** may be axially positioned between the flange portion **432** and the second end of the tubular body **430**. The spigot bearing support

surface **446** may be configured to support the spigot bearing assembly **410** as will be discussed in more detail below.

Referring to FIGS. **6** and **10**, the first outer groove **448** may be disposed in the spigot bearing support surface **446** or adjacent to the spigot bearing support surface **446**. As such, the first outer groove **448** may be disposed opposite the rotor output flange hole **434**. The first outer groove **448** may extend around the first axis **70** and may extend toward the first axis **70**. The first outer groove **448** may be axially positioned between the spigot bearing assembly **410** and the second end of the tubular body **430**. The first outer groove **448** may receive a fastener **464**, such as a snap ring, that may engage an inner race of the spigot bearing assembly **410** to inhibit axial movement of the inner race.

The rotary disc support surface **450**, which may also be referred to as a resolver rotor support surface, may be disposed opposite the rotor output flange hole **434** and may be axially positioned between the spigot bearing support surface **446** and the second end of the tubular body **430**. In at least one configuration, the rotary disc support surface **450** may have a smaller diameter than the spigot bearing support surface **446**. The rotary disc support surface **450** may support a rotary disc **466**, which may also be referred to as a resolver rotor.

Referring to FIGS. **6** and **11**, the rotary disc **466** may be fixedly disposed on the rotor output flange **290**. As such, the rotary disc **466** may rotate about the first axis **70** with the rotor **206**. The rotary disc **466** may be axially positioned between the spigot bearing assembly **410** and the second end of the rotor output flange **290**. As such, the rotary disc **466** may be received in the rotor output flange hole **434** and may extend around the sun gear **710** of the gear reduction module **26**. As is best shown in FIG. **11**, the rotary disc **466** may have a non-cylindrical outer surface that may face away from the first axis **70** that may include a plurality of protrusions that may extend away from the first axis **70**. The protrusions may be arranged in a repeating pattern around the first axis **70**.

Referring to FIGS. **6** and **10**, the second outer groove **452** may be disposed in the rotary disc support surface **450** or adjacent to the rotary disc support surface **450**. As such, the second outer groove **452** may be disposed opposite the rotor output flange hole **434**. The second outer groove **452** may extend around the first axis **70** and may extend toward the first axis **70**. The second outer groove **452** may be axially positioned between the rotary disc **466** and the second seal support surface **454**. The second outer groove **452** may receive a fastener **468**, such as a snap ring, that may inhibit axial movement of the rotary disc **466**.

The second seal support surface **454** may extend from the second end of the tubular body **430** toward the rotary disc support surface **450**. The second seal support surface **454** may be disposed opposite the rotor output flange hole **434** and may be configured to support a seal as will be discussed in more detail below.

The flange portion **432** may be disposed between the first end and the second end of the tubular body **430**. The flange portion **432** may extend from the tubular body **430** in a direction that extends away from the first axis **70**. The flange portion **432** may be fixedly coupled to the rotor **206**. For instance, the flange portion **432** may include a set of holes that may be arranged around the first axis **70** and that may receive fasteners **470**, such as bolts, that may extend through the holes to couple the flange portion **432** to the rotor **206**. In at least one configuration, the flange portion **432** may include one or more protrusions **480**.

Referring to FIGS. **5** and **17**, the protrusion **480** may extend in an axial direction toward the rotor **206**. In at least

one configuration, the protrusion **480** may be configured as an annular ring that may extend continuously around the first axis **70** and around the first seal support surface **444**. In addition, the protrusion **480** may also extend around the second retaining member **362**. As is best shown in FIG. 5, the protrusion **480** may extend into the rotor **206** and may engage the outer race **314** of the second rotor bearing assembly **210** to inhibit axial movement of the outer race **314** away from the first rotor bearing assembly **208**. The rotor output flange **290** as well as the protrusion **480** may be spaced apart from the inner race **312** of the second rotor bearing assembly **210**.

Spigot Bearing Assembly

Referring to FIGS. 5, 6, 10 and 17, the spigot bearing assembly **410** may receive the rotor output flange **290** and may rotatably support the rotor output flange **290**. The spigot bearing assembly **410** may help inhibit deflection of the rotor **206**, such as deflection with respect to the first axis **70**. As such, the spigot bearing assembly **410** may help align or center the rotor **206** about the first axis **70** and may help improve the stability of the rotor **206** and maintain a desired air gap between the rotor **206** and the stator **204**. As is best shown with reference to FIGS. 5 and 10, the spigot bearing assembly **410** may be received inside the rotor output flange hole **434** of the motor cover **214** and may extend between the motor cover **214** and the rotor output flange **290**. The spigot bearing assembly **410** may also be axially positioned in the electric motor module **24** such that the spigot bearing assembly **410** is received inside of the motor housing **200** and inside of the coolant jacket **202**.

Referring to FIGS. 6 and 10, the spigot bearing assembly **410** may have any suitable configuration. For instance, the spigot bearing assembly **410** may include a plurality of rolling elements **500** that may be disposed between an inner race **502** and an outer race **504**. The inner race **502** may extend around and may engage the spigot bearing support surface **446** of the rotor output flange **290**. The outer race **504** may extend around the rolling elements **500** and may engage the bearing receiving surface **384** of the motor cover **214**.

Referring to FIG. 22, an alternative arrangement for supporting the spigot bearing assembly **410** is shown. This arrangement may include an adapter **510** and a spigot bearing biasing member **512**.

The adapter **510** may be received in the rotor output flange hole **434** of the motor cover **214**. For example, the adapter **510** may be configured as a ring that may extend around the first axis **70** and may receive the spigot bearing assembly **410**. The adapter **510** may also extend around and receive the spigot bearing biasing member **512**. In at least one configuration, the adapter **510** may include a transverse wall **520**, a first flange **522**, and a second flange **524**.

The transverse wall **520** may be radially positioned between the spigot bearing assembly **410** and the motor cover **214**. In addition, the transverse wall **520** may extend generally parallel to the first axis **70**. The transverse wall **520** may include a groove **526**. The groove **526** may be disposed adjacent to the second flange **524**. The groove **526** may extend around the first axis **70** and may extend away from the first axis **70**.

The first flange **522** may extend from a first end of the transverse wall **520** in a direction that extends away from the first axis **70**. The first flange **522** may extend continuously around the first axis **70** in one or more configurations. The first flange **522** may extend from the transverse wall **520** to the motor cover **214**. As such, the first flange **522** may inhibit axial movement of the adapter **510** in a first direction with

respect to the motor cover **214**, or to the right from the perspective shown in FIG. 22.

The second flange **524** may be disposed opposite the first flange **522**. As such, the second flange **524** may extend from a second end of the transverse wall **520**. The second flange **524** may extend toward the first axis **70** and may extend continuously around the first axis **70**. The second flange **524** may inhibit axial movement of the spigot bearing biasing member **512** in the first direction. The second flange **524** may be spaced apart from the spigot bearing assembly **410**.

The spigot bearing biasing member **512** may be at least partially received in the groove **526** of the adapter **510**. The spigot bearing biasing member **512** may extend from the second flange **524** and may be axially positioned such that the spigot bearing biasing member **512** may extend at least partially around the fastener **464**. The spigot bearing biasing member **512** may also be axially positioned between the spigot bearing assembly **410** and a resolver **600** that may detect rotation of the rotor **206** as will be discussed in more detail below.

The spigot bearing biasing member **512** may exert a biasing force on the spigot bearing assembly **410** to inhibit skidding of the spigot bearing assembly **410**. Skidding may include sliding motion of the rolling elements **500** rather than rolling motion of the rolling elements **500** with respect to the inner race **502**, the outer race **504**, or both. Skidding can disrupt lubricant on surfaces of the spigot bearing assembly **410** and result in increased operating temperatures, bearing component damage, and reduced service life. The spigot bearing biasing member **512** may engage the outer race **504** of the spigot bearing assembly **410** and may bias the outer race **504** of the spigot bearing assembly **410** toward the differential carrier **42**, or to the left from the perspective shown in FIG. 22. This biasing force may preload the spigot bearing biasing member **512** to inhibit skidding of the rolling elements **500**. The spigot bearing biasing member **512** may be spaced apart from the inner race **502** of the spigot bearing assembly **410**.

Referring to FIG. 5, the spigot bearing biasing member **512** may also exert a biasing force on the second rotor bearing assembly **210**, which may be axially positioned between the first rotor bearing assembly **208** and the spigot bearing assembly **410**. More specifically, the spigot bearing biasing member **512** may exert a biasing force on the spigot bearing assembly **410**, which in turn may exert a biasing force on the rotor output flange **290**. This biasing force may be transmitted to the outer race **314** of the second rotor bearing assembly **210** via the protrusion **480** of the rotor output flange **290**, which may bias the outer race **314** toward the first rotor bearing assembly **208**.

The spigot bearing biasing member **512** may have any suitable configuration. For instance, the spigot bearing biasing member **512** may be configured as a spring, such as a wave spring or waive washer that may extend around the first axis **70**. Alternatively, the spigot bearing biasing member **512** may not extend around the first axis **70**. As one nonlimiting example, the spigot bearing biasing member **512** may include one or more springs, such as coil springs that may be arranged in an axial direction.

Resolver

Referring to FIGS. 6, 11 and 18, a resolver **600** may be associated with the electric motor module **24**. The resolver **600**, which may also be referred to as a resolver stator, may function as a sensor that may provide a signal indicative of rotation of the rotor **206** or the rotational position of the rotor **206**. For example, the resolver **600** may detect the position of the rotary disc **466**, such as by detecting the presence or

absence of the protrusions of the rotary disc 466 or may detect rotation of the rotary disc 466. The resolver 600 may be of any suitable type. For example, the resolver 600 may be an analog resolver or a digital resolver, such as a rotary encoder.

The resolver 600 may generally be configured as a ring that may extend around the first axis 70. The resolver 600 may also extend around a portion of the rotor output flange 290, and the rotary disc 466 as is best shown in FIG. 6. The resolver 600 or a portion thereof may be received in the rotor output flange hole 434 of the motor cover 214 and may be mounted to the second side 372 of the motor cover 214. As such, the motor cover 214 may be disposed between the resolver 600 and the rotor 206 and the resolver 600 may be accessible from the outside of the electric motor module 24. Such positioning may also isolate the resolver 600 from lubricant in the lubricant chambers of the axle assembly 10 as will be discussed in more detail below. As is best shown in FIGS. 11 and 18, the resolver 600 may include a plurality of elongated slots 602 and an electrical connection or connector 604.

The elongated slots 602 may facilitate mounting of the resolver 600 to the motor cover 214. A fastener 606, such as a screw or bolt, may extend through an associated elongated slot 602 and may secure the resolver 600 to the motor cover 214. The elongated slots 602 may be disposed at a substantially constant radial distance from the first axis 70 and may permit the resolver 600 to be rotated about the first axis 70 when the fasteners 606 are not fully tightened.

The electrical connector 604 may be disposed proximate the outside perimeter or outside circumference of the resolver 600. The electrical connector 604 may extend through the resolver slot 382 in the motor cover 214. The electrical connector 604 may be connected to an electrical power source to provide power to the resolver 600 and may facilitate electronic communication with an axle controller that may control operation of the electric motor module 24.

A resolver cover 608 may extend over the electrical connector 604 to protect the electrical connector 604 and separate the electrical connector 604 from the rotor 206. The resolver cover 608 may be fastened to the first side 370 of the motor cover 214 in any suitable manner, such as with one or more fasteners 610, such as screws.

As is best shown in FIG. 6, the resolver 600 may be axially positioned between the motor cover 214 and a seal carrier plate 620. The seal carrier plate 620 may be spaced apart from the resolver 600. The seal carrier plate 620, which is also shown in FIGS. 11 and 18, may generally be configured as a hollow circular disc that may extend around the first axis 70. As is best shown in FIG. 6, the seal carrier plate 620 may extend further toward the first axis 70 and further away from the first axis 70 than the resolver 600.

Referring to FIGS. 6, 11 and 18, the seal carrier plate 620 may be mounted to the motor cover 214. In at least one configuration, the seal carrier plate 620 may include a seal carrier plate hole 630, an outer surface 632, one or more fastener holes 634, and a seal carrier plate flange 636.

The seal carrier plate hole 630 may extend around the first axis 70. The seal carrier plate hole 630 may receive a portion of the rotor output flange 290 and an inner seal 640. The inner seal 640 may extend around the rotor output flange 290 and may extend from the seal carrier plate 620 to the second seal support surface 454 of the rotor output flange 290. As such, the rotor output flange 290 may separate the inner seal 640 from the sun gear of the gear reduction module 26.

The outer surface 632 may be disposed opposite the seal carrier plate hole 630. As such, the outer surface 632 may face away from the first axis 70.

One or more fastener holes 634 may extend through the seal carrier plate 620. The fastener holes 634 may be configured as through holes that may be positioned between the seal carrier plate hole 630 and the outer surface 632. Each fastener hole 634 may receive a fastener 642, such as a screw or bolt, that may secure the seal carrier plate 620 to the motor cover 214.

The seal carrier plate flange 636 may be disposed between the seal carrier plate hole 630 and the outer surface 632. The seal carrier plate flange 636 may extend toward the motor cover 214. In at least one configuration, the seal carrier plate flange 636 may be configured as a ring that may extend continuously around the first axis 70. The seal carrier plate flange 636 may support an outer seal 644. The outer seal 644 may have any suitable configuration. For example, the outer seal 644 may be configured as an O-ring. The outer seal 644 may extend around the seal carrier plate flange 636 and may extend from the seal carrier plate flange 636 to the motor cover 214 when the seal carrier plate 620 is mounted on the motor cover 214.

Providing a resolver 600 and a seal carrier plate 620 that are accessible from the outside of the electric motor module 24 may simplify assembly as compared to a configuration in which the resolver 600 is positioned on the opposite side of the motor cover 214. In a configuration where the resolver is positioned on the side of the motor cover 214 that faces toward the rotor 206, the resolver would be susceptible to falling into the electric motor module 24 when unfastened. Moreover, if a curable adhesive or sealant was provided between the resolver 600 and the motor cover 214 then the resolver would need to be adjusted to its final rotational position before the adhesive or sealant cures or solidifies. The configuration described above may eliminate such adhesives or sealants and may provide easier access to the resolver 600 and the seal carrier plate 620.

An example of an assembly sequence for the resolver 600 and the seal carrier plate 620 is as follows.

First, the differential carrier 42 may be provided. The differential carrier 42 may be provided with the drive pinion 22 assembled to the differential carrier 42 and rotatably supported on the first and second drive pinion bearings 150, 170.

Second, the electric motor module 24 may be assembled to the differential carrier 42. Assembling the electric motor module 24 to the differential carrier 42 may include mounting the rotor 206 on the bearing support wall 64 of the differential carrier 42 and mounting the subassembly that includes the motor housing 200, the coolant jacket 202, and the stator 204 to the differential carrier 42. The motor cover 214 may also be mounted to the motor housing 200 as previously described. The rotor output flange 290 may be mounted on the rotor 206 before the motor cover 214 is mounted to the motor housing 200. Similarly, the resolver 600 and the resolver cover 608 may be mounted to the motor cover 214 before the motor cover 214 is mounted to the motor housing 200. The drive pinion 22 and the rotor output flange 290 may extend through the motor cover opening 374 and the resolver 600 after the motor cover 214 is installed.

Third, the rotational position of the resolver 600 may be assessed and adjusted if necessary. The rotational position of the resolver 600 with respect to the first axis 70 may not be precisely aligned with the rotational position of the rotor 206 when the motor cover 214 is mounted to the motor housing 200. The rotational position of the resolver 600 may be

assessed in a manner known by those skilled in the art. For example, the rotor **206** may be rotated about the first axis **70**, which may also rotate the rotor output flange **290** and the rotary disc **466**, and the rotational position of the rotor **206** and the rotary disc **466** then may be synchronized with the resolver **600**. The rotor **206** may be rotated manually, such as by turning the rotor output flange **290**, or electrically. The rotational position of the resolver **600** may be adjusted by loosening the fasteners **606** (but not necessarily removing the fasteners **606** from the motor cover **214**) to permit the resolver **600** to be rotated about the first axis **70** and with respect to the fasteners **606** via the elongated slots **602**. Once the resolver **600** is properly aligned, then the fasteners **606** may be tightened to secure the resolver **600** and inhibit rotation of the resolver about the first axis **70**.

Fourth, the seal carrier plate **620** may be mounted to the motor cover **214** after the resolver **600** is secured. The seal carrier plate **620** may be mounted and secured with the fasteners **642** and may include the inner seal **640** and the outer seal **644**.

Gear Reduction Module

Referring to FIG. **2**, the gear reduction module **26**, if provided, may transmit torque from the electric motor module **24** to the differential assembly **30**. As such, the gear reduction module **26** may be operatively connected to the electric motor module **24** and the differential assembly **30**. The gear reduction module **26** may be disposed outside of the differential carrier **42** and may be primarily disposed outside of the electric motor module **24**, thereby providing a modular construction that may be mounted to the electric motor module **24** when gear reduction is desired. Such a configuration may facilitate standardized configurations of the differential carrier **42** and/or the electric motor module **24**.

The gear reduction module **26** may be disposed adjacent to the motor cover **214**. In addition, the gear reduction module **26** may be primarily received or at least partially received in a shift mechanism housing **900** that may be mounted to the motor cover **214** as will be discussed in more detail below.

The gear reduction module **26** may be provided in various configurations, such as planetary gear set configurations and non-planetary gear set configurations. Referring to FIGS. **2**, **12** and **19**, an example of a gear reduction module **26** that has a planetary gear set **700** is shown. In such a configuration, the gear reduction module **26** may include a sun gear **710**, planet gears **712**, a planetary ring gear **714**, and a planet gear carrier **716**. The planetary gear set **700** will primarily be described in the context of an axle assembly that may include an electric motor module **24**; however, it is to be understood that the planetary gear set **700** described below may be provided with axle assemblies that do not have an electric motor module. For example, the planetary gear set **700** may be configured as an interaxle differential unit or may be used to provide gear reduction at a wheel end.

Referring to FIGS. **6**, **12** and **19**, the sun gear **710** may be disposed proximate the center of the planetary gear set **700** and may be rotatable about the first axis **70**. The sun gear **710** may be operatively connectable to the electric motor module **24**. In addition, the sun gear **710** may extend into the motor cover opening **374** of the motor cover **214**. As is best shown primarily with reference to FIGS. **12** and **19**, the sun gear **710** may be a hollow tubular body that may include a first end surface **720**, a second end surface **722**, a sun gear hole **724**, a sun gear spline **726**, a first gear portion **728**, and a second gear portion **730**.

The first end surface **720** may be disposed at an end of the sun gear **710** that may face toward the axle housing **40**. The first end surface **720** may extend into the motor cover opening **374**.

The second end surface **722** may be disposed at an end of the sun gear **710** that may face away from the axle housing **40**. As such, the second end surface **722** may be disposed opposite the first end surface **720**. The second end surface **722** may be disposed outside of the motor cover opening **374** and inside the shift mechanism housing **900**. A thrust bearing **732** may extend from the second end surface **722** to the planet gear carrier **716** to help inhibit axial movement of the sun gear **710** and facilitate rotation of the sun gear **710** with respect to the planet gear carrier **716**.

The sun gear hole **724** may extend from the first end surface **720** to the second end surface **722**. The sun gear hole **724** may extend along and may be centered about the first axis **70**. The drive pinion **22** may extend through the sun gear hole **724** and may be spaced apart from the sun gear **710**.

The sun gear spline **726** may facilitate coupling of the sun gear **710** to a rotor output flange **290**. In at least one configuration, the sun gear spline **726** may be disposed opposite the sun gear hole **724** and may extend from or may be disposed proximate the first end surface **720**. As such, the sun gear spline **726** may be received inside the rotor output flange **290** and may mesh with the rotor output flange spline **440**. It is also contemplated that the sun gear spline **726** may be disposed in the sun gear hole **724** and the rotor output flange **290** may be received inside the sun gear **710**.

The first gear portion **728** may be disposed in the sun gear hole **724**. For example, the first gear portion **728** may be disposed proximate the second end surface **722** of the sun gear **710**. Teeth of the first gear portion **728** may be arranged around the first axis **70** and may extend toward the first axis **70** and may be configured to mesh with teeth of a shift collar **904** as will be discussed in more detail below.

The second gear portion **730** may be disposed opposite the first gear portion **728**. The second gear portion **730** may be disposed proximate the second end surface **722** of the sun gear **710**. The second gear portion **730** may have teeth that may mesh with teeth of the planet gears **712**. The teeth of the second gear portion **730** may be arranged around the first axis **70** and may extend away from the first axis **70**.

The planet gears **712** may be rotatably disposed between the sun gear **710** and the planetary ring gear **714**. Each planet gear **712** may have a hole and a set of teeth. The hole may be a through hole that may extend through the planet gear **712**. The set of teeth may be disposed opposite the hole. The set of teeth may mesh with teeth of the second gear portion **730** of the sun gear **710** and teeth on the planetary ring gear **714**. The teeth may have any suitable configuration. In the configuration shown, the teeth are provided with a helical configuration however, other tooth configurations may be provided. Each planet gear **712** may be configured to rotate about a different planet gear axis of rotation. The planet gear axes of rotation may extend substantially parallel to the first axis **70**.

Referring to FIG. **25**, the planet gears **712** may be grouped into two sets. These sets may be referred to as a first set of planet gears **740** and a second set of planet gears **750**. The first set of planet gears **740** and the second set of planet gears **750** may have individual planet gears that may have the same configuration.

The first set of planet gears **740** may include multiple planet gears that mesh with the sun gear **710** and the planetary ring gear **714**. For example, the first set of planet

gears 740 may have n members, where n is an integer greater than 1. The members of the first set of planet gears 740 may have the same configuration, may be spaced apart from each other, and may be arranged around the first axis 70 in a repeating relationship. For instance, the members of the first set of planet gears 740 may be equidistantly spaced around the first axis 70 with respect to each other. Each member of the first set of planet gears 740 may be arranged around the first axis 70 at an angle α_1 with respect to each other. For instance, if $n=3$, then $\alpha_1=120^\circ$; if $n=4$, then α_1 equals 90° , and so on. The axes of rotation of each member of the first set of planet gears 740, which may also be referred to as a first planet gear axis 742, may be positioned at a substantially constant radial distance from the first axis 70.

Each member of the first set of planet gears 740 may be arranged or positioned between two members of the second set of planet gears 750. In at least one configuration, each member of the first set of planet gears 740 may be positioned closer to one member of the second set of planet gears 750 than all other members of the second set of planet gears 750. This may result in the planet gears appearing to be grouped in pairs that include one member of the first set of planet gears 740 and one member of the second set of planet gears 750.

Each member of the first set of planet gears 740 may be disposed “in-phase” with each other. As such, each member of the first set of planet gears 740 may be provided at a common rotational position or rotational orientation with respect to the planetary ring gear 714. Thus, the members of first set of planet gears 740 may have common meshing relationships with the planetary ring gear 714. For example, each member of the first set of planet gears 740 may be positioned such that a corresponding tooth of the planetary ring gear 714 is received between and is centered between two adjacent teeth of the planet gear. Such positioning is represented in FIG. 25 by triangles that extend from the planetary ring gear 714 toward the first axis 70. A magnified illustration of such positioning is shown in FIG. 26 in which the planetary ring gear tooth that is received between and centered between adjacent teeth of a member of the first set of planet gears 740. In at least one configuration, the planetary ring gear tooth that is received between and centered between adjacent teeth of a member of the first set of planet gears 740 may positioned along a radial line L1 that may extend through the first axis 70 and through a corresponding first planet gear axis 742 about which a member of the first set of planet gears 740 may rotate. The planetary ring gear tooth or a cross section of the planetary ring gear tooth may be centered about the radial line L1. In-phase positioning along with equidistant spacing of the members of the first set of planet gears 740 may help cancel radial vibration excitations.

The second set of planet gears 750 may also include multiple planet gears that mesh with the sun gear 710 and the planetary ring gear 714. For example, the second set of planet gears 750 may have n members, where n is an integer greater than 1. The members of second set of planet gears 750 may have the same configuration, may be spaced apart from each other, and may be arranged around the first axis 70 in a repeating relationship. For instance, the second set of planet gears 750 may be equidistantly spaced around the first axis 70 with respect to each other. Each member of the second set of planet gears 750 may be arranged around the first axis 70 at an angle α_2 with respect to each other. Angle α_1 may equal angle α_2 . The axes of rotation of each member of the second set of planet gears 750 which may also be referred to as a second planet gear axis 752, may be

positioned at a substantially constant radial distance from the first axis 70. In addition, each member of the second set of planet gears 750 may be arranged or positioned between two members of the first set of planet gears 740. In at least one configuration, each member of the first set of planet gears 740 may be positioned closer to one member of the second set of planet gears 750 than all other members of the second set of planet gears 750. Members of the first set of planet gears 740 and members of the second set of planet gears 750 may not mesh with each other.

Each member of the second set of planet gears 750 may be disposed “in-phase” with each other and may be positioned in counterphase with respect to the first set of planet gears 740. For instance, each member of the second set of planet gears 750 may be provided at a common rotational position or rotational orientation with respect to the planetary ring gear 714. Thus, the members of second set of planet gears 750 may have common meshing relationships with the planetary ring gear 714. However, the members of the second set of planet gears 750 may not have common meshing relationships with the first set of planet gears 740. For example, each member of the second set of planet gears 750 may be positioned such that a tooth of each member of the second set of planet gears 750 is received between and is centered between two adjacent teeth of the planetary ring gear 714 when a planetary ring gear tooth is received between and is centered between two adjacent teeth of each member of the first set of planet gears 740. Such positioning is represented in FIG. 25 by triangles that extend from the members of the second set of planet gears 750 away from the first axis 70. A magnified illustration of such positioning is shown in FIG. 26 in which the planet gear tooth of the member of the second set of planet gears 750 that is received between and centered between adjacent teeth of the planetary ring gear 714 is positioned along a radial line L2 that may extend through the first axis 70 and through a corresponding second planet gear axis 752 about which a member of the second set of planet gears 750 may rotate. Counterphase positioning of the second set of planet gears 750 with respect to the first set of planet gears 740 may help cancel rotational vibration excitations. As a result, radial and rotational vibration excitations or torque ripples in the planetary gear set 700 may be substantially or fully cancelled. Moreover, the unequal distribution or angular positioning of the first set of planet gears 740 with respect to the second set of planet gears 750 may facilitate providing a stiffer planet gear carrier 716.

Referring to FIGS. 6, 12 and 19, the planetary ring gear 714 may extend around the first axis 70 and may receive the planet gears 712. The planetary ring gear 714 may include a set of planetary ring gear teeth that may extend toward the first axis 70 and may mesh with teeth on the planet gears 712. The planetary ring gear 714 may be stationary with respect to the first axis 70. For example, the planetary ring gear 714 may be received in and may be fixedly disposed on the shift mechanism housing 900. In at least one configuration, a plurality of pins 760 may be partially received in grooves located along the outside circumference of the planetary ring gear 714 and may be partially received in corresponding grooves in the shift mechanism housing 900 to inhibit rotation of the planetary ring gear 714.

The planet gear carrier 716 may be rotatable about the first axis 70 and may rotatably support the planet gears 712. In at least one configuration, the planet gear carrier 716 may include a planet gear carrier hole 770, a planet gear carrier

ring 772, a planet gear carrier gear portion 774, a first planet gear carrier flange 776, and a second planet gear carrier flange 778.

The planet gear carrier hole 770 may be a through hole that may extend through planet gear carrier 716. The planet gear carrier hole 770 may extend along and may be centered about the first axis 70.

The planet gear carrier ring 772 may at least partially define the planet gear carrier hole 770. The planet gear carrier ring 772 may extend around the first axis 70 and may extend in an axial direction away from the second flange. The planet gear carrier ring 772 may be configured to support a support bearing 780 and a tone ring 782. For example, the planet gear carrier ring 772 may include a bearing mounting surface 784 and a tone ring mounting surface 786.

The bearing mounting surface 784 may face away from the first axis 70 and may extend around the first axis 70. The bearing mounting surface 784 may be axially positioned between the second planet gear carrier flange 778 and a distal end of the planet gear carrier ring 772. An inner race of the support bearing 780 may receive and may be disposed on the bearing mounting surface 784. The support bearing 780 may rotatably support the planet gear carrier 716 on the shift mechanism housing. A fastener 790, such as a snap ring, may be received in a groove in the planet gear carrier ring 772 to inhibit axial movement of the support bearing 780.

The tone ring mounting surface 786 may also face away from the first axis 70 and may extend around the first axis 70. The tone ring mounting surface 786 may extend from the distal end of the planet gear carrier ring 772 or may be disposed between the distal end of the planet gear carrier ring 772 in the bearing mounting surface 784. The tone ring 782 may have a plurality of teeth and may receive and may be disposed on the tone ring mounting surface 786.

The planet gear carrier gear portion 774 may be disposed in the planet gear carrier ring 772 and may extend into the planet gear carrier hole 770. Teeth of the planet gear carrier gear portion 774 may be arranged around the first axis 70 and may extend toward the first axis 70.

The first planet gear carrier flange 776, which may also be referred to as a first flange, may be disposed opposite the planet gear carrier ring 772. The first planet gear carrier flange 776 may extend away from the first axis 70. The first planet gear carrier flange 776 may include a plurality of openings 800 and a set of fastener holes 802.

The openings 800 may facilitate mounting of the planet gears 712 as will be discussed in more detail below. The openings 800 may be configured as through holes.

Referring to FIGS. 6 and 19, a fastener hole 802 may extend to the opening 800. In at least one configuration, the fastener holes 802 may extend along radial lines with respect to the first axis 70.

Referring to FIGS. 6, 12 and 19, the second planet gear carrier flange 778, which may also be referred to as a second flange, may be spaced apart from the first planet gear carrier flange 776. The second planet gear carrier flange 778 may be axially positioned between the first planet gear carrier flange 776 and the planet gear carrier ring 772. The second planet gear carrier flange 778 may extend away from the first axis 70 and may have a similar configuration as the first planet gear carrier flange 776. The second planet gear carrier flange 778 may include a plurality of openings 810 and a set of lubricant holes 812.

The openings 810 in the second planet gear carrier flange 778 may be aligned with a corresponding opening 800 in the

first planet gear carrier flange 776. The openings 800, 810 may facilitate mounting of the planet gears 712 between the first planet gear carrier flange 776 and the second planet gear carrier flange 778.

A lubricant hole 812 may extend through the second planet gear carrier flange 778 to each opening 800. In at least one configuration, the lubricant holes 812 may extend along radial lines with respect to the first axis 70. It is also contemplated that the positioning of some or all of the lubricant holes 812 and the fastener holes 802 may be interchanged between the first planet gear carrier flange 776 and the second planet gear carrier flange 778.

Various components may facilitate mounting of a planet gear 712. These components may include one or more planet pins 820 and one or more of a first roller bearing assembly 822, a second roller bearing assembly 824, a spacer 826, a first washer 828, a second washer 830, and a securing pin 832.

A planet pin 820 may rotatably support each planet gear 712. The planet pin 820 may extend from the first planet gear carrier flange 776 to the second planet gear carrier flange 778. For example, a planet pin 820 may extend into or through the hole in a corresponding planet gear 712 and into or through an opening 800 in the first planet gear carrier flange 776 and an opening 810 in the second planet gear carrier flange 778. As such, the planet pins 820 may not be cantilevered from the planet gear carrier 716. Moreover, the planet pins 820 may be substantially rigid and may not deflect with respect to a corresponding planet gear axis, such as a first planet gear axis 742 or a second planet gear axis 752. In addition, each planet pin 820 may have a securing pin hole 840, an axial bore 842, a first lubricant passage 844, and a second lubricant passage 846 as is best shown in FIG. 6.

The securing pin hole 840 may partially or completely through the planet pin 820. A securing pin 832 may be received in the securing pin hole 840 and may be received in a fastener hole 802 of the first planet gear carrier flange 776 to help inhibit axial movement of a planet pin 820 with respect to the planet gear carrier 716. The securing pins 832 may have any suitable configuration.

The axial bore 842 may extend in an axial direction from an end of the planet pin 820. The axial bore 842 may be a blind hole in one or more embodiments. A plug 852 may be received in an end of the axial bore 842 to help direct lubricant flow as will be discussed in more detail below. The plugs 852 may have any suitable configuration. For instance, the plugs 852 may be configured as set screws.

The first lubricant passage 844 may extend from the axial bore 842 to the spacer 826. As such, the first lubricant passage 844 may be disposed near the center of a planet pin 820.

The second lubricant passage 846 may be spaced apart from the first lubricant passage 844. The second lubricant passage 846 and may extend from the axial bore 842 to a lubricant hole 812 in the second planet gear carrier flange 778. The second lubricant passage 846 may be disposed adjacent to a plug 852.

Referring to FIGS. 6, 12 and 19, the first roller bearing assembly 822 and the second roller bearing assembly 824 may receive a planet pin 820 and may be received inside a corresponding planet gear 712. The first roller bearing assembly 822 and the second roller bearing assembly 824 may rotatably support the planet gear 712.

The spacer 826 may receive a planet pin 820 and may be axially positioned between the first roller bearing assembly 822 and the second roller bearing assembly 824. The spacer

826 may have a larger inside diameter than the outside diameter of the planet pin **820** to allow lubricant to flow inside the spacer **826** to help lubricate the first roller bearing assembly **822** and the second roller bearing assembly **824**.

The first washer **828** and the second washer **830** may receive a planet pin **820**. The first washer **828** may extend from the first planet gear carrier flange **776** to the first roller bearing assembly **822**. The second washer **830** may extend from the second planet gear carrier flange **778** to the second roller bearing assembly **824**. As such, the first washer **828** and the second washer **830** may cooperate to inhibit axial movement of the planet gear **712**, the first roller bearing assembly **822**, the second roller bearing assembly **824**, or combinations thereof.

Shift Mechanism

Referring to FIG. 2, the shift mechanism **28** may be disposed at an end of the axle assembly **10** that may be disposed opposite the axle housing **40**. The shift mechanism **28** may be disposed on the motor cover **214**.

The gear reduction module **26** may cooperate with the shift mechanism **28** to provide a desired gear reduction ratio to change the torque provided from the electric motor module **24** to the differential assembly **30**, and hence to the axle shafts **32** of the axle assembly **10**. For example, the gear reduction module **26** may provide a first drive gear ratio and a second drive gear ratio. The first drive gear ratio, which may be referred to as a low range gear ratio, may provide gear reduction from the electric motor module **24** to the differential assembly **30** and hence to the axle shafts **32**. As a nonlimiting example, the first drive gear ratio may provide a 2:1 gear ratio or more. The first drive gear ratio may provide increased torque to a vehicle traction wheel as compared to the second drive gear ratio.

The second drive gear ratio, which may be referred to as a high range gear ratio, may provide a different gear reduction ratio or lesser gear reduction ratio than the first drive gear ratio. For instance, the second drive gear ratio may provide a 1:1 gear ratio. The second drive gear ratio may facilitate faster vehicle cruising or a cruising gear ratio that may help improve fuel economy.

In addition, a neutral position or neutral drive gear ratio may be provided in which torque may not be provided to the differential assembly **30** by the electric motor module **24**. As such, torque may not be transmitted between the gear reduction module **26** and the drive pinion **22** when a shift collar is in the neutral position.

Referring to FIGS. 2, 13 and 20, the shift mechanism **28** may include a shift mechanism housing **900**, an end plate **902**, a shift collar **904**, and an actuator **906**.

The shift mechanism housing **900** may be disposed on the motor cover **214** and may be mounted to a side of the motor cover **214** that may be disposed opposite the differential carrier **42**. For example, the shift mechanism housing **900** may be mounted to the motor cover **214** with one or more fasteners **910**, such as bolts. The shift mechanism housing **900** may at least partially receive the gear reduction module **26**. In addition, the shift mechanism housing **900** may facilitate mounting of the actuator **906** and may at least partially receive the shift collar **904**. As is best shown in FIG. 6, the shift mechanism housing **900** may rotatably support the planet gear carrier **716** via the support bearing **780**. A retainer **908** may be mounted to the shift mechanism housing **900** to inhibit axial movement of the support bearing **780**. In at least one configuration, the retainer **908** may engage an outer race of the support bearing **780** to inhibit axial movement toward the motor cover **214**.

The end plate **902**, which may also be referred to as an end cap, may be disposed on an end of the shift mechanism housing **900** that may be disposed opposite the axle housing **40**. For example, the end plate **902** may be mounted to the shift mechanism housing **900** with a plurality of fasteners **920**, such as bolts. The end plate **902** may help support the actuator **906**. For example, the end plate **902** may have a support feature **922** that may support a shaft **930** that may support and facilitate axial movement of a shift fork **932** as will be discussed in more detail below. The shaft **930** may also be supported by the shift mechanism housing **900**.

The shift collar **904** may be at least partially received in the shift mechanism housing **900**. For instance, the shift collar **904** may be at least partially received in the shift mechanism housing **900** and may extend through components of the gear reduction module **26**, such as the planet gear carrier **716**. In at least one configuration such as is best shown in FIGS. 13 and 20, the shift collar **904** may include a shift collar hole **940**, a shift collar spline **942**, a shift collar groove **944**, and a shift collar gear **946**.

The shift collar hole **940** may extend through the shift collar **904** and may extend around the first axis **70**. The shift collar hole **940** may receive the shaft portion **122** of the drive pinion **22**.

Referring to FIG. 20, the shift collar spline **942** may be disposed in the shift collar hole **940** and may be axially positioned near a first end of the shift collar **904** that may face toward the differential carrier **42**. The shift collar spline **942** may extend toward the first axis **70** and may mate with the spline **140** of the drive pinion **22**. The mating splines may allow the shift collar **904** to move in an axial direction or along the first axis **70** while inhibiting rotation of the shift collar **904** about the first axis **70** with respect to the drive pinion **22**. Thus, the shift collar **904** may be rotatable about the first axis **70** with the drive pinion **22**.

The shift collar groove **944** may be disposed proximate a second end of the shift collar **904** that may face toward the end plate **902**. The shift collar groove **944** may face away from the first axis **70** and may extend around the first axis **70**. The shift collar groove **944** may receive the shift fork **932**, which may operatively connect the shift collar **904** to the actuator **906**.

The shift collar gear **946** may be disposed between the first end and the second end of the shift collar **904**. The shift collar gear **946** may have teeth that may be arranged around the first axis **70** and that may extend away from the first axis **70**. An annular groove **950** that may extend around the first axis **70** may be provided in the shift collar gear **946**. The annular groove **950** may receive a stop **952** that may limit axial movement of the shift collar **904**. The stop **952** may have any suitable configuration. For instance, the stop **952** may include one or more snap rings.

The shift collar **904** may be movably disposed on the drive pinion **22**. The shift collar **904** may selectively engage a gear ratio. More specifically, the shift collar **904** may move axially or in a direction that extends along the first axis **70** between a first position, a second position, and a third position. These positions are illustrated in FIGS. 2-4.

Referring to FIG. 2 as well as the magnified portion of FIG. 2 shown in FIG. 6, the shift collar **904** is shown in the first position. In the first position, the shift collar **904** may couple the planet gear carrier **716** to the drive pinion **22**. For example, the teeth of the shift collar gear **946** may mesh with the teeth of the planet gear carrier gear portion **774** of the planet gear carrier **716**. As such, torque that is provided by the electric motor module **24** may be transmitted through the rotor output flange **290**, sun gear **710**, planet gears **712**, and

planet gear carrier **716** to the shift collar **904** and from the shift collar **904** to the drive pinion **22**.

Referring to FIG. **3**, the shift collar **904** is shown in a second position or neutral position. The second position may be axially positioned between the first position and the third position. In the second position, the shift collar **904** may not couple the gear reduction module **26** to the drive pinion **22**. For example, the teeth of the shift collar gear **946** may not mesh with the teeth of the sun gear **710** or the planet gear carrier **716**. As such, torque that is provided by the electric motor module **24** may not be transmitted to the shift collar **904** or the drive pinion **22**. The shift collar **904** may be disposed closer to the axle housing **40** when in the second position than when in the first position.

Referring to FIG. **4**, the shift collar **904** is shown in the third position. In the first position, the shift collar **904** may couple the sun gear **710** to the drive pinion **22**. For example, the teeth of the shift collar gear **946** may mesh with the teeth of the second gear portion **730** of the sun gear **710**. As such, torque that is provided by the electric motor module **24** may be transmitted through the rotor output flange **290** and sun gear **710** to the shift collar **904** and from shift collar **904** to the drive pinion **22**. The shift collar **904** may be disposed closer to the axle housing **40** when in the third position than when in the second position.

It is also contemplated that the shift collar may be omitted such that the gear reduction module may provide a single gear ratio rather than multiple gear ratios. For example, the planet gear carrier **716** may be coupled to the drive pinion **22** to provide a low range gear ratio without a high range gear ratio.

The actuator **906** may be disposed on the shift mechanism housing **900**. The actuator **906** may move the shift collar **904** along the first axis **70** between the first, second, and third positions. For example, the actuator **906** may have an output shaft that may be rotatable about an axis. A cam **960** may be mounted to the output shaft and may rotate with the output shaft. The cam **960** may operatively connect the actuator **906** to the shift fork **932**. As such, rotation of the output shaft may actuate the shift fork **932** along the shaft **930**, which in turn may move the shift collar **904** along the first axis **70**. The actuator **906** may be of any suitable type. For example, the actuator **906** may be an electrical, electromechanical, pneumatic or hydraulic actuator.

Lubricant Chambers

Referring to FIG. **4**, the axle assembly **10** may be divided into three main chambers. These chambers may include a first lubricant chamber **1000**, a second lubricant chamber **1002**, and an air chamber **1004**.

The first lubricant chamber **1000** may be primarily defined by the axle housing **40** and the differential carrier **42**. More specifically, the first lubricant chamber **1000** may be disposed between the axle housing **40** and the differential carrier **42** and may be disposed inside a majority of the bearing support wall **64**. As such, the first lubricant chamber **1000** may receive the differential assembly **30**, the gear portion **120** of the drive pinion **22**, part of the shaft portion **122** of the drive pinion **22**, the first drive pinion bearing **150**, and the second drive pinion bearing **170**. In addition, the first lubricant chamber **1000** may receive a first lubricant **1006**. The first lubricant **1006** may be a high shear oil, such as 75W90 gear oil.

The second lubricant chamber **1002** may be primarily defined by the motor cover **214**, rotor output flange **290**, the shift mechanism housing **900**, and the end plate **902**. More specifically, the second lubricant chamber **1002** may be disposed inside a majority of the rotor output flange **290**,

motor cover **214**, and the shift mechanism housing **900**. As such, the second lubricant chamber **1002** may receive the preload nut **190**, part of the shaft portion **122** of the drive pinion **22**, the planetary gear set **700**, and the shift collar **904**. The second lubricant chamber **1002** may receive a second lubricant **1008**. The second lubricant **1008** may be a different type or grade of lubricant than the first lubricant **1006**. For example, the second lubricant **1008** may be Emgard® MTF7000 40W gear oil, which may provide lower frictional loss properties and cost benefits.

The air chamber **1004** may be primarily defined by the electric motor module **24** and the differential carrier **42**. For example, the bearing support wall **64** may cooperate with the motor housing **200** and the motor cover **214** to at least partially define the air chamber **1004**. As such, the air chamber **1004** may be primarily disposed in a radial direction between the bearing support wall **64** and the motor housing **200** and may be primarily disposed between the differential carrier **42** and the motor cover **214** in an axial direction. The air chamber **1004** may receive components such as the coolant jacket **202**, the stator **204**, the rotor **206**, the first rotor bearing assembly **208**, the second rotor bearing assembly **210**, rotor bearing preload module **212**, the spigot bearing assembly **410**, the rotary disc **466**, and the resolver **600**. A vent may be provided in the axle assembly **10** to permit the air chamber **1004** to fluidly communicate with the surrounding environment.

The first lubricant chamber **1000**, the second lubricant chamber **1002**, and the air chamber **1004** may be separated by various sealing components and may not be fluidly connected to each other. Such sealing components may include the seal support ring **180** and the inner seal **640** as previously discussed. In addition, sealing components may include a seal mounting ring **1010**, a first seal **1012**, a second seal **1014**, and a third seal **1016**, which are best shown with reference to FIGS. **5**, **9** and **16**.

The seal mounting ring **1010** may be positioned between the drive pinion **22** and the bearing support wall **64**. As such, the seal mounting ring **1010** may be disposed in the hole **90** that may be defined by the bearing support wall **64**. In addition, the seal mounting ring **1010** may be fixedly positioned with respect to the bearing support wall **64**. For example, the seal mounting ring **1010** may be received in the hole **90** with an interference fit. The seal mounting ring **1010** may extend around and may be spaced apart from the seal support ring **180** and the first seal support surface **444** of the rotor output flange **290**. In at least one configuration, the seal mounting ring **1010** may include a first side **1020**, a second side **1022**, an outer face **1024**, and an inner face **1026**.

The first side **1020** may face toward the second drive pinion bearing **170**. The first side **1020** may be spaced apart from the second drive pinion bearing **170** in one or more embodiments.

The second side **1022** may be disposed opposite the first side **1020**. As such, the second side **1022** may face toward the flange portion **432** of the rotor output flange **290**.

The outer face **1024** may face away from the first axis **70**. The outer face **1024** may extend from the first side **1020** to the second side **1022** and may engage the bearing support wall **64**.

The inner face **1026** may be disposed opposite the outer face **1024**. As such, the inner face **1026** may face toward the first axis **70**. In at least one configuration, the inner face **1026** may have a stepped configuration that may include a first seal mounting surface **1030**, a second seal mounting surface **1032**, a third seal mounting surface **1034**, and an intermediate surface **1036**.

31

The first seal mounting surface **1030** may face toward and may extend around the seal support ring **180**.

The second seal mounting surface **1032** may also face toward and may extend around the seal support ring **180** and may extend around the first axis **70**. The second seal mounting surface **1032** may have a different diameter than the first seal mounting surface **1030**. In the configuration shown, the second seal mounting surface **1032** may have a smaller diameter than the first seal mounting surface **1030**.

The third seal mounting surface **1034** may face toward and may extend around the first seal support surface **444** of the rotor output flange **290**. The third seal mounting surface **1034** may have a different diameter than the first seal mounting surface **1030**. In the configuration shown, the third seal mounting surface **1034** may have a smaller diameter than the first seal mounting surface **1030**.

The intermediate surface **1036** may be axially positioned between the second seal mounting surface **1032** and the third seal mounting surface **1034**. The intermediate surface **1036** or a portion thereof may have a smaller diameter than the second seal mounting surface **1032**, the third seal mounting surface **1034**, or both. Such a configuration may help inhibit axial movement of seals that may be associated with the second seal mounting surface **1032** in the third seal mounting surface **1034**.

The first seal **1012** may extend between the bearing support wall **64** and the drive pinion **22**. For example, the first seal **1012** may extend from the first seal mounting surface **1030** to the seal support ring **180**. The first seal **1012** may extend around the seal support ring **180** and may help separate the first lubricant chamber **1000** from the second lubricant chamber **1002**.

The second seal **1014** may extend between the bearing support wall **64** and the rotor output flange **290**. For example, the second seal **1014** may extend from the second seal mounting surface **1032** to the first seal support surface **444** of the rotor output flange **290**. The second seal **1014** may extend around the rotor output flange **290** and may help separate the air chamber **1004** from the second lubricant chamber **1002**.

The third seal **1016** may be axially positioned between the first seal **1012** and the second seal **1014**. The third seal **1016** may extend between the bearing support wall **64** and the drive pinion **22**. For example, the third seal **1016** may extend from the third seal mounting surface **1034** to the seal support ring **180**. The third seal **1016** may extend around the seal support ring **180** and may help separate the first lubricant chamber **1000** from the second lubricant chamber **1002**. The third seal **1016** may be spaced apart from the first seal **1012** such that a cavity **1040** may be disposed between the first seal **1012** and the third seal **1016**. The cavity **1040** may be fluidly connected to the air chamber **1004**. For instance, the cavity **1040** may be fluidly connected to the air chamber **1004** by at least one vent passage **1042** that may extend through the seal mounting ring **1010**. For example, the vent passage **1042** may extend from the inner face **1026** of the seal mounting ring **1010** to the second side **1022** of the seal mounting ring **1010**. As such, a portion of the vent passage **1042** may extend from the second side **1022** toward the first side **1020** but not to the first side **1020**. In the configuration shown in FIG. 9, four vent passages **1042** shown that may be arranged at 90° intervals from each other; however, it is contemplated that a greater or lesser number of vent passages may be provided.

Referring to FIG. 6, the inner seal **640** may extend between the seal carrier plate **620** and the rotor output flange **290**. For example, the inner seal **640** may be received in the

32

seal carrier plate hole **630** and may extend from the seal carrier plate **620** to the second seal support surface **454** of the rotor output flange **290**. The inner seal **640** may extend around the rotor output flange **290** and may help separate the second lubricant chamber **1002** from the air chamber **1004**. The inner seal **640** may be spaced apart from the seal mounting ring **1010**. As such, various components such as the spigot bearing assembly **410**, the rotary disc **466**, and the resolver **600** may be axially positioned between the second seal **1014** and the inner seal **640**.

Control

Referring to FIG. 23, a schematic representation of an axle system **1100** is shown. The axle system **1100** may include the axle assembly **10** as well as a control system **1102**.

The control system **1102** may include multiple electronic controllers. For example, the control system **1102** may include an axle controller **1110** and a brake controller **1112**. Other electronic controllers may also be provided but are not depicted. One or more controllers may communicate over a Controller Area Network (CAN) bus of a vehicle. Information that is communicated over the CAN bus or through multiple controllers may have latency issues and may be slower than direct communication.

The axle controller **1110** may control operation of the axle assembly **10**. The axle controller **1110** may receive signals from various sensors, such as the resolver **600**, a first speed sensor **1120**, and a second speed sensor **1122**. In addition, the axle controller **1110** may control the actuator **906** and thereby controls movement of the shift collar **904**.

The first speed sensor **1120** may provide a first signal that may be indicative of a rotational speed of a wheel **14**. The first speed sensor **1120** may be located downstream from the gear reduction module **26**. In at least one configuration, the first speed sensor **1120** may be disposed between the differential assembly **30** and a wheel **14**. In such a configuration, the first speed sensor **1120** may detect rotation of a wheel **14**, wheel hub **16**, or axle shaft **32**. For instance, a tone ring **1130** that may have a plurality of teeth may be disposed on the wheel hub **16** and may rotate with the wheel hub **16** about the wheel axis **18**. The first speed sensor **1120** may be disposed near the wheel **14** and may detect rotation of the tone ring **1130**. A first speed sensor **1120** may be associated with each wheel **14**, wheel hub **16**, or axle shaft **32**. Thus, two first speed sensors **1120** are shown in FIG. 23. It is also contemplated that the first speed sensor **1120** may be provided in other locations. For example, the first speed sensor **1120** may detect rotation of the drive pinion **22**.

The first speed sensor **1120** may be directly electrically connected or directly hardwired to the axle controller **1110**. For example, a first conductor **1140** such as a wire may extend from the first speed sensor **1120** to the axle controller **1110**. Accordingly, the first signal from the first speed sensor **1120** may be provided directly from the first speed sensor **1120** to the axle controller **1110** and may not be indirectly routed to the axle controller **1110** via another controller, such as the brake controller **1112**. As such, the axle controller **1110** may receive the first signal faster than if the first signal was indirectly provided and the axle controller **1110** so that the axle controller **1110** may better control shifting of the shift collar **904**.

The second speed sensor **1122** may provide a second signal that may be indicative of a rotational speed of the gear reduction module **26**. The second speed sensor **1122** may be located upstream from the shift collar **904**. In at least one configuration, the second speed sensor **1122** may be disposed between the electric motor module **24** and the shift

collar **904**. In such a configuration, the second speed sensor **1122** may detect rotation of a component of the planetary gear set **700**, such as the planet gear carrier **716**. For instance, the second speed sensor **1122** may be mounted to the shift mechanism housing **900** or extend through a hole in the shift mechanism housing **900** as is best shown in FIG. **24** and may detect rotation of the tone ring **782** that may be disposed on the planet gear carrier **716**. It is also contemplated that the second speed sensor **1122** may be provided in other locations. For example, the second speed sensor **1122** may detect rotation of the sun gear **710**.

The second speed sensor **1122** may be directly electrically connected or directly hardwired to the axle controller **1110**. For example, a second conductor **1142** such as a wire may extend from the second speed sensor **1122** to the axle controller **1110**. Accordingly, the second signal from the second speed sensor **1122** may be provided directly from the second speed sensor **1122** to the axle controller **1110** and may not be indirectly routed to the axle controller **1110** via another controller, such as the brake controller **1112**. As such, the axle controller **1110** may receive the second signal faster than if the second signal was indirectly provided and the axle controller **1110** so that the axle controller **1110** may better control shifting of the shift collar **904**.

A third speed sensor **1150** may be provided with the axle system **1100**. The third speed sensor **1150** may function like the first speed sensor **1120** and may detect rotation of the tone ring **1130**. The third speed sensor **1150** may provide a third signal that may be used by other controllers of the control system **1102**. For instance, the third signal may be provided to the brake controller **1112** to facilitate control of an antilock brake system. The third signal may not be provided to the axle controller **1110** to control shifting of the shift collar **904** due to potential latency issues.

The axle controller **1110** may use the first signal and the second signal to determine when a shift of the shift collar **904** may be executed. For instance, the axle controller **1110** may use the first signal and the second signal to determine when the rotational speed of the shift collar **904** is sufficiently close to the rotational speed of a component of the planetary gear set **700**, such as the sun gear **710** and/or the planet gear carrier **716** to permit the shift collar **904** to be shifted to or from the neutral position. The axle controller **1110** operate the actuator **906** to move the shift collar **904** to a desired position when shifting of the shift collar **904** may be executed and completed.

As an example that starts with the shift collar **904** and the first position or the third position, the axle controller **1110** may determine when the first and second signals are indicative of sufficiently close rotational speeds. The axle controller **1110** may then temporarily relieve or reduced torque on the shift collar **904** by controlling the rotational speed of the rotor **206** or reducing power provided from an electrical power source/inverter **1160** to permit the shift collar **904** to be more easily be actuated from the first position or the third position to the second (neutral) position. The axle controller **1110** may then operate the actuator **906** to move the shift collar **904** to the second position.

The axle controller **1110** may move the shift collar **904** from the second position to either the first position or the third position by controlling the rotational speed of the rotor **206** to synchronize the rotational speed of the shift collar **904** with the sun gear **710** to allow the shift collar **904** to move to the second position to the first position or may synchronize the rotational speed of the shift collar **904** with the planet gear carrier **716** to allow the shift collar **904** to move from the neutral position to the third position

Differential Assembly and Axle Shafts

Referring to FIG. **2**, the differential assembly **30** may be at least partially received in the center portion **50** of the housing assembly **20**. The differential assembly **30** may transmit torque to the wheels **14** and permit the wheels **14** to rotate at different velocities. The differential assembly **30** may be operatively connected to the axle shafts **32** and may permit the axle shafts **32** to rotate at different rotational speeds in a manner known by those skilled in the art. As such, the differential assembly **30** may receive torque via the ring gear **110** and provide torque to the axle shafts **32**.

Referring to FIGS. **1**, **2** and **23**, the axle shafts **32** may transmit torque from the differential assembly **30** to corresponding wheel hubs **16** and wheels **14**. For example, two axle shafts **32** may be provided such that each axle shaft **32** extends through a different arm portion **52** of axle housing **40**. The axle shafts **32** may extend along and may be rotated about the wheel axis **18** by the differential assembly **30**. Each axle shaft **32** may have a first end and a second end. The first end may be operatively connected to the differential assembly **30**. The second end may be disposed opposite the first end and may be operatively connected to a wheel **14**. Optionally, gear reduction may be provided between an axle shaft **32** and a wheel **14**.

While exemplary embodiments are described above, it is not intended that these embodiments describe all possible forms of the invention. Rather, the words used in the specification are words of description rather than limitation, and it is understood that various changes may be made without departing from the spirit and scope of the invention. Additionally, the features of various implementing embodiments may be combined to form further embodiments of the invention.

What is claimed is:

1. An axle assembly comprising:
 - a motor housing that extends between a differential carrier and a motor cover;
 - a rotor that is rotatable about an axis;
 - a rotor output flange that is fixedly mounted to the rotor;
 - a first rotor bearing assembly and a second rotor bearing assembly that are disposed on the differential carrier and rotatably support the rotor; and
 - a spigot bearing assembly that extends between the motor cover and the rotor output flange and rotatably supports the rotor output flange to inhibit deflection of the rotor.
2. The axle assembly of claim **1** wherein the spigot bearing assembly is received inside the motor cover.
3. The axle assembly of claim **1** wherein the spigot bearing assembly engages the motor cover and the rotor output flange and the rotor output flange is received inside the spigot bearing assembly.
4. The axle assembly of claim **1** wherein the motor cover defines a groove that receives a seal that contacts and extends around the spigot bearing assembly.
5. The axle assembly of claim **1** wherein the spigot bearing assembly is received inside the motor housing and inside a coolant jacket that is received inside that motor housing.
6. The axle assembly of claim **1** wherein the rotor output flange extends through the motor cover.
7. An axle assembly comprising:
 - a motor housing that extends from a differential carrier to a motor cover;
 - a rotor that is received in the motor housing and is rotatable about an axis;
 - a rotor output flange that is fixedly mounted to the rotor and is at least partially received in the motor cover;

35

a first rotor bearing assembly and a second rotor bearing assembly that are disposed on the differential carrier and rotatably support the rotor;
 a spigot bearing assembly that extends between the motor cover and the rotor output flange and rotatably supports the rotor output flange; and
 a spigot bearing biasing member that exerts a biasing force on the spigot bearing assembly to inhibit skidding of the spigot bearing assembly.

8. The axle assembly of claim 7 wherein the spigot bearing biasing member engages an outer race of the spigot bearing assembly and biases the spigot bearing assembly toward the differential carrier.

9. The axle assembly of claim 7 wherein the spigot bearing biasing member is a wave spring that is axially positioned between the spigot bearing assembly and a resolver that detects rotation of the rotor.

10. The axle assembly of claim 7 further comprising a snap ring that is mounted to the rotor output flange and that engages an inner race of the spigot bearing assembly to inhibit axial movement of the inner race.

11. The axle assembly of claim 10 wherein the spigot bearing biasing member is axially positioned such that the spigot bearing biasing member extends at least partially around the snap ring.

12. The axle assembly of claim 7 further comprising an adapter that is received in the motor cover and that receives the spigot bearing assembly and the spigot bearing biasing member.

13. The axle assembly of claim 12 wherein the adapter has a transverse wall that is disposed between the spigot bearing assembly and the motor cover and a first flange that extends from the transverse wall to the motor cover to inhibit axial movement of the adapter in a first direction with respect to the motor cover.

14. The axle assembly of claim 13 wherein the adapter has a second flange that extends from the transverse wall, wherein the second flange inhibits axial movement of the spigot bearing biasing member in the first direction.

36

15. The axle assembly of claim 14 wherein the first flange extends away from the axis and the second flange extends toward the axis.

16. The axle assembly of claim 14 wherein the transverse wall has a groove that extends away from the axis and receives the spigot bearing biasing member.

17. An axle assembly comprising:

a motor housing that extends between a differential carrier and a motor cover;

a rotor that is received in the motor housing and is rotatable about an axis;

a rotor output flange that is fixedly mounted to the rotor and is at least partially received in the motor cover;

a first rotor bearing assembly and a second rotor bearing assembly that rotatably support the rotor on the differential carrier;

a spigot bearing assembly that is received in the motor cover and receives and rotatably supports the rotor output flange; and

a spigot bearing biasing member that exerts a biasing force on the spigot bearing assembly and the second rotor bearing assembly.

18. The axle assembly of claim 17 wherein the spigot bearing biasing member exerts the biasing force on an outer race of the spigot bearing assembly.

19. The axle assembly of claim 18 wherein the second rotor bearing assembly is axially positioned between the first rotor bearing assembly and the spigot bearing assembly and the rotor output flange engages the outer race of the second rotor bearing assembly and the spigot bearing biasing member biases the outer race toward the first rotor bearing assembly.

20. The axle assembly of claim 19 wherein the spigot bearing biasing member is spaced apart from an inner race of the spigot bearing assembly and the rotor output flange is spaced apart from the inner race of the second rotor bearing assembly.

* * * * *