



US005993340A

United States Patent [19]

[11] Patent Number: **5,993,340**

Rocca et al.

[45] Date of Patent: **Nov. 30, 1999**

[54] **TIGHTENER FOR A TRANSMISSION BELT**

[75] Inventors: **Carlo Rocca**, Turin, Italy; **Marc Theobald**, Wadgassen, Germany; **Angelo Mennuti**, Nichelino, Italy

[73] Assignee: **Dayco Europe S.P.A.**, Zona Industriale Vallecupa, Italy

5,348,514	9/1994	Foley	474/135
5,399,124	3/1995	Yamamoto et al.	474/135
5,443,424	8/1995	Henderson	474/135
5,462,494	10/1995	Rogalla	474/135
5,599,245	2/1997	Giese	474/135
5,630,767	5/1997	Hirabayashi et al.	474/135
5,795,257	8/1998	Giese et al.	474/135

FOREIGN PATENT DOCUMENTS

19623485 12/1996 Germany .

Primary Examiner—Thomas R. Hannon
Assistant Examiner—Matthew A. Kaness
Attorney, Agent, or Firm—Stevens, Davis, Miller & Mosher, L.L.P.

[21] Appl. No.: **09/013,224**

[22] Filed: **Jan. 26, 1998**

[30] **Foreign Application Priority Data**

Jan. 31, 1997 [IT] Italy TO97A0072

[51] **Int. Cl.⁶** **F16H 7/08**; F16H 7/14; F16H 7/12

[52] **U.S. Cl.** **474/109**; 474/113; 474/133

[58] **Field of Search** 474/101, 115, 474/117, 133, 134, 135, 136, 138, 109, 110, 111, 113, 112

[56] **References Cited**


U.S. PATENT DOCUMENTS


2,490,974	12/1949	Mallory .	
4,596,538	6/1986	Henderson .	
4,938,734	7/1990	Green et al. .	
5,236,396	8/1993	Golovatai-Schmidt et al.	474/135
5,244,438	9/1993	Golovatai-Schmidt	474/117
5,250,009	10/1993	Sidwell et al.	474/117

[57] **ABSTRACT**

Stretcher for a transmission belt comprising a fixed part suitable for being rigidly connected to a support structure, a movable part hinged to the fixed part about a first axis, a pulley carried by the movable part and rotating with respect thereto about a second axis distinct from the first axis and parallel thereto, a spring interposed between the fixed part and the movable part and suitable for loading in use the movable part in the direction tending to keep the pulley in engagement with the relative belt, and a damping element provided with a base wall rigidly fixed to the fixed part and with an annular friction portion extending axially from the base wall and cooperating with a seat produced in the movable part.

9 Claims, 1 Drawing Sheet





TIGHTENER FOR A TRANSMISSION BELT**BACKGROUND OF THE INVENTION**

The invention relates to a stretcher, i.e., belt tightener for a transmission belt and particularly but not exclusively for a belt for transmitting motion from the drive shaft of an internal combustion engine to auxiliary elements driven by the said engine.

Stretchers are known which comprise a fixed part suitable for being rigidly connected to a support structure integral with the engine block, a movable part hinged to the fixed part about a first axis, a pulley carried by the movable part and rotating with respect thereto about a second axis distinct from the first axis and parallel thereto, and a spring interposed between the fixed part and the movable part, which loads the movable part in the direction tending to keep the pulley in engagement with the relative belt.

Variations in belt tension due to the selective actuation of the various accessories and to wear are therefore compensated by consequent variations in the deformation of the spring and corresponding movements of the axis of rotation of the pulley.

Because the belt transmits a pulsating load to the pulley, to limit the oscillations and prevent the occurrence of resonance phenomena, damping means interposed between the fixed part and the movable part are generally provided.

According to a known embodiment, such damping means comprise a pair of friction discs which are integral with the fixed part and the movable part respectively, face to face with each other and axially loaded by a spring so as to cooperate with each other with respective annular friction surfaces preferably having a conical shape.

The known stretchers of the type briefly described have a number of disadvantages.

In particular, the above-mentioned damping means comprise a large number of components and therefore involve long times and high costs for manufacture and assembly.

Furthermore, the dimensions of the known stretchers are large because it is necessary to provide an adequate support of the movable part with respect to the fixed part to withstand the tilting moments (i.e. about an axis at right angles to the axes of rotation) transmitted to the movable part by the pulley, the latter being supported in a projecting manner.

SUMMARY OF THE INVENTION

The object of the invention is to produce a stretcher for belts which enables the disadvantages associated with the known stretchers specified above to be eliminated.

This object is achieved by the invention in that it relates to a stretcher for a transmission belt of the type comprising a fixed part suitable for being rigidly connected to a support structure, a movable part hinged to the said fixed part about a first axis, a pulley carried by the said movable part and rotating with respect thereto about a second axis distinct from the first axis and parallel thereto, flexible means interposed between the said fixed part and the said movable part and suitable for loading in use the said movable part in the direction tending to keep the said pulley in engagement with the relative said belt, and means of damping by friction interposed between the said fixed part and the said movable part, characterized in that the said damping means comprise a damping element provided with a securing portion rigidly fixed to one of the said fixed and movable parts and with an annular friction portion extending axially from the said securing portion and cooperating with a seat produced in another of the said fixed and movable parts.

BRIEF DESCRIPTION OF THE DRAWING

For an improved understanding of the invention a preferred embodiment will now be described below, by way of non-exhaustive example and with reference to the accompanying drawing which shows an axial section thereof.

DETAILED DESCRIPTION OF THE INVENTION

With reference to the illustration, in its entirety **1** denotes a stretcher for a belt **2** with multiple grooves (multi-V) for driving the auxiliary elements (not shown) of an internal combustion engine (not shown).

In known manner the stretcher **1** substantially comprises a fixed part **3** suitable for being rigidly connected to a support structure (not shown), such as a support plate for the auxiliary elements fixed to the engine block, a movable part **4** hinged to the fixed part **3** about a first axis **A**, a pulley **5** carried in projecting manner by the movable part **4** and rotating with respect thereto about a second axis **B** distinct from the first axis **A** and parallel thereto, and a spring **6** interposed between the fixed part **3** and the movable part **4**, which loads the movable part in the direction tending to keep the pulley **5** in engagement with the belt **2**.

More particularly, the fixed part **3** integrally comprises a flange **10** suitable for cooperating axially with the support structure and a tubular pin **11** of axis **A** extending axially in projecting manner from the flange **10**. The flange **10** has a plurality of frontal teeth **12** suitable for engaging respective seats (not shown) of the support structure to anchor the fixed part **3** in the angular direction.

The movable part **4** integrally comprises a hub **13** coaxial to the pin **11** and mounted in rotating manner thereon, an arm **15** extending radially in a projecting manner from the hub **13**, and a tubular portion **16**, of axis **B**, integrally connected to an end of the arm **15** and having the function of supporting the pulley **5**.

The hub **13** of the movable part **4** is substantially bell-shaped and comprises a first portion **18** and a second portion **19** which are axially adjacent and have a larger and smaller diameter respectively.

For a section of its own axial length, the first portion **18** is disposed round the flange **10** and is supported radially thereon by means of a bush **20** which, with the said flange **10**, defines a friction torque of pre-determined coefficient. For the remaining section of its own length the first portion **18** delimits with the pin **11** an annular chamber **21** housing the spring **6**. The latter comprises a strip of steel spiral-wound round the pin **11** and having an internal end **24** secured in known manner to the pin **11** and an external end **25** secured in known manner to the portion **18**.

The second portion **19** is supported radially by the pin **11** with the interposition of a bush **26** which defines with the said pin **11** a friction torque of pre-determined coefficient.

The bush **20** and the bush **26** have respective end, internal and external respectively, flat annular flanges **28**, **29** which cooperate axially with opposite flanks of the spring **6** and are interposed between the latter and, respectively, the flange **10** and the second portion **19** of the hub **13**.

Finally the stretcher **1** comprises a damping element **30** interposed between the pin **11** and the movable part **4**.

The damping element **30** substantially comprises a metallic cupped core **34** having a substantially flat circular base wall **35** rigidly fixed onto a free end **36** of reduced diameter of the pin **11** and a substantially cylindrical lateral wall **37** extending in projecting manner from an external periphery of the base wall **35**.

The damping element **30** also has a coating **38** of plastics material extending over the face of the base wall **35** facing towards the hub **13** and over the entire surface of the lateral wall **37**, so as to form therewith an annular friction crown **39** engaging an annular seat **40**, of complementary form, produced on a front face **41** of the portion **19** of the hub **13**. The material of the coating **38** is selected so as to define with the hub **13** a friction torque of pre-determined coefficient to ensure, in use, adequate oscillation damping properties. The contact between the annular crown **39** and the relative seat **40** conveniently takes place either along the internal and external cylindrical surfaces, or along the annular front surface of the crown **39**.

The core **34** is provided with an axial hole **44**, engaged in forced manner by the end **36** of the pin **11**; the end **36** is thus pressed onto the internal edge of the base wall **35** so as to ensure a "pack" mounting on the pin **11**, i.e. substantially with no axial play, of the group comprising the bush **20**, the spring **6**, the bush **26** and the hub **13**.

The coating **38** is applied to the core **34** by means of over-moulding; for this purpose the core **34** is provided with a plurality of holes **45** surrounding the axial hole **44** and suitable for being engaged by the material of the coating **38**, during the moulding phase, to ensure the anchorage of the said coating **38** to the core **34**.

The operation of the stretcher **1** is per se known and will not therefore be described in detail.

The oscillations of the movable part **4** with respect to the fixed part **3**, in response to the pulsating dynamic variations in pull of the belt **2**, are damped by the action of the bushes **20** and **26** and of the damping element **30**.

According to the invention, this damping element is particularly economical to produce and simple and quick to assemble. Furthermore, in addition to the damping of the oscillations, the engagement between the annular crown **39** and the associated seat **40** also helps radially to support the movable part **4** with respect to the fixed part **3**, and in particular to balance the tilting moment.

Finally, it will be clear that modifications and variants which do not depart from the protective scope of the invention may be introduced to the stretcher **1** described.

For example, the damping element **30** could be rigidly fixed to the hub **13** and be provided with an annular friction portion **39** housed in a seat produced in the pin **11**.

The coating **38** could be made of elastomer material instead of plastics material.

We claim:

1. A stretcher (**1**) for a transmission belt (**2**) comprising:
 - a fixed part (**3**) for being rigidly connected to a support structure,
 - a movable part (**4**) hinged to said fixed part (**3**) about a first axis (A),
 - a pulley (**5**) carried by said movable part and rotating with respect thereto about a second axis (B) distinct from said first axis (A) and parallel thereto,
 - flexible means (**6**), interposed between said fixed part (**3**) and said movable part (**4**), for loading in use said

movable part (**4**) in the direction tending to keep said pulley (**5**) in engagement with the relative said belt (**2**), and

means for damping (**20, 26, 30**) by friction movement of said movable part (**4**) relative to said fixed part (**3**), said means for damping (**20, 26, 30**) interposed between said fixed part (**3**) and said movable part (**4**) and comprising a damping element (**30**) provided with a securing portion (**35**) rigidly fixed to one of said fixed and movable parts (**3, 4**) and with an annular friction portion (**39**) extending axially from said securing portion (**35**) and cooperating with a seat (**40**) produced in another of said fixed and movable parts (**3, 4**),

wherein said securing portion is a substantially flat base wall (**35**) of said damping element (**30**) fixed to an end portion (**36**) of said one of said fixed and movable parts (**3, 4**), and that said seat (**4**) has a form corresponding to said annular friction portion (**39**) and is formed in a front face (**41**) of said another of said fixed and movable parts (**3, 4**).

2. The stretcher according to claim 1, wherein said damping element (**30**) comprises a metallic core (**35**) and a friction coating (**38**) extending at least over said annular friction portion (**39**).

3. The stretcher according to claim 2, wherein said coating (**38**) is of a plastics material.

4. The stretcher according to claim 2, wherein said coating (**38**) is of an elastomer material.

5. The stretcher according to claim 1, wherein said securing portion of said damping element (**30**) is fixed to said fixed part (**3**) of said stretcher (**1**), and said annular friction portion (**39**) is substantially cylindrical in shape and extends in a projecting manner from a periphery of said base wall (**35**), said seat (**40**) being produced in said movable part (**4**) of said stretcher (**1**).

6. The stretcher according to claim 1, wherein said fixed part (**3**) comprises a pin (**11**) defining said first axis (A) and said end portion (**36**) for mounting said damping element (**30**), and said movable part (**4**) comprises a hub (**13**) mounted in rotating manner on said pin (**11**) and defining said front face (**41**) wherein is produced said seat (**40**).

7. The stretcher according to claim 6, wherein said base wall (**35**) of said damping element (**30**) is fixed to said end portion (**36**) of said pin (**11**) by means of a forced connection.

8. The stretcher according to claim 6, wherein said hub (**13**) is supported on said fixed part (**3**) by a pair of bushes (**20, 26**) spaced between said hub and said fixed part in the axial direction, said spring (**6**) being housed in a chamber (**21**) delimited externally by said hub (**13**) and internally by said pin (**11**), and interposed axially between said bushes (**20, 26**).

9. The stretcher according to claim 8, wherein said spring (**6**) is a spiral spring and said bushes (**20, 26**) comprise respective radial flanges (**28, 29**) cooperating axially with said spring (**6**).

* * * * *