

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
22 April 2004 (22.04.2004)

PCT

(10) International Publication Number
WO 2004/034623 A2

(51) International Patent Classification⁷: **H04L**

(21) International Application Number:

PCT/US2003/031295

(22) International Filing Date: 3 October 2003 (03.10.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10/268,824 10 October 2002 (10.10.2002) US

(71) Applicant: **MOTOROLA, INC.** [US/US]; 1303 East Algonquin Road, Schaumburg, IL 60196 (US).

(72) Inventor: **AERRABOTU, Naveen**; 7943 Dada Drive, Gurnee, IL 60031 (US).

(74) Agents: **VAAS, Randall S.** et al.; 600 North US Highway 45, AN475, Libertyville, IL 60048 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: PREFERRED ROAMING LIST AND ROAMING INDICATOR PROVISION AND SYNCHRONIZATION



(57) **Abstract:** A method for synchronizing multiple database that are provided at different times is provided. As a wireless communication device (102) leaves a first region (104) and enters a second region (108), it is provided with a new preferred roaming list information (204) which may no longer be synchronized with a stored functionality extension table. Based upon information included in the new preferred roaming list information, an appropriate functionality extension table (214) that is synchronized to the new preferred roaming list is received.

WO 2004/034623 A2



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

**PREFERRED ROAMING LIST AND ROAMING INDICATOR
PROVISION AND SYNCHRONIZATION**

5 Technical Field

10 The present invention relates generally to a method of providing and synchronizing separate data sets. More specifically, the present invention relates to a method in a wireless communication device synchronizing one data set with another based upon a data parameter.

Background Art

15 It is known to provide a cellular telephone, or a mobile terminal, using the Code Division Multiple Access (“CDMA”) with a table called Preferred Roaming List (“PRL”). Based upon the information contained in the PRL, such as System Identification (“SID”) and Network Identification (“NID”), the mobile determines the most appropriate network to register itself. Depending on the availability of systems 20 and networks in the environment where the mobile is in, the mobile may receive a new PRL appropriate for the current environment of the mobile over the air to replace the existing PRL. Currently, the mobile supports three types of roaming indicators associated with the PRL, which help notify the user the roaming status of the mobile in the current environment. For example, the first type of the indicators may indicate 25 that the mobile is in a home network, i.e., not roaming, by having the roaming indicator light turned off; the second type of the indicators may indicate that the mobile is in a preferred roaming network by having the roaming indicator light turned on; and the third type of the indicators may indicate that the mobile is in a non-preferred roaming network by having the roaming indicator light flashing. As defined 30 in TIA/EIA TSB58b section 8.1, enhanced roaming indicators (“ERI”), supporting more than three types of indicators, may be provided in the mobile to enhance the roaming condition conveyed to the user. However, as the mobile roams and its PRL

is replaced with a new and different PRL, the ERI may not be correctly associated with the new PRL.

Accordingly, there is a need for a method in a wireless communication device for synchronizing two different sets of data, which are acquired by the wireless communication device at separate instances.

Brief Description of Drawings

10 FIG. 1 is an exemplary environment where the method of the present invention may be initiated;

FIG. 2 is an exemplary flow chart of the first embodiment of the present invention in a wireless communication device;

15 FIG. 3 is an exemplary flow chart of the second embodiment of the present invention in a wireless communication device; and

FIG. 4 is an exemplary flow chart of the third embodiment of the present invention in a network.

20 Disclosure of the Invention

The present invention generally relates to a method in a wireless communication device for synchronizing two sets of data that are received at two separate instances.

25 In some applications, a first set of data, for example, a preferred roaming list (“PRL”) or an extended preferred roaming list (“EPRL”) is stored in the wireless communication device, and a second set of data, for example, enhanced roaming indicators (“ERI”), associated with or synchronized to the first set of data is also stored in the wireless communication device.

30 As the wireless communication device roams from one environment to the next, the wireless communication device may receive a new PRL, which may not be synchronized to the current ERI already stored in the device, depending upon the

availability of systems and networks in the new environment. According to one aspect of the invention, the wireless communication device receives an ERI that is synchronized to the new PRL based on a parameter of the new PRL.

FIG. 1 is an exemplary environment where some aspects of the present inventions may be practiced. When a wireless communication device 102 located in a first region 104, which has been operating in a first network 106 provided by Carrier A, leaves the first region and enters a second region 108, it may be necessary for the wireless command device to register and operate in a second network 110 provided by a different carrier, Carrier B.

A home carrier of the wireless communication device may have different contracts with each of the Carriers A and B, which may affect the fee charged to the wireless communication device, for example when the wireless communication device is roaming. To assist in determining the status of the wireless communication device in the network, the wireless communication device may receive a preferred roaming list. In other applications, the mobile device may receive lists or data sets other than a preferred roaming list.

Referring to FIG. 2, there is provided an exemplary flow chart of the first embodiment of the present invention in a wireless communication device. At block 202, this process is initiated when the wireless portable communication device, preferably a portable radiophone, leaves a first region and enters a second region. Upon entering the second region, the wireless communication device receives a preferred roaming list information such as, but not limited to, a preferred roaming list (“PRL”) or an extended preferred roaming list (“EPRL”), at block 204. The wireless communication device, then at block 206, determines if the received preferred roaming list information contains information referring to a functionality extension table such as but not limited to, a roaming indicator and an enhanced roaming indicator, which may compliment the functionality of the received preferred roaming list information. If the received preferred roaming list information does not contain any reference to a functionality extension table, then any functionality extension table previously stored may be deleted in block 208, and the wireless communication resumes its normal operation in block 210. If the received preferred roaming list information contains a reference to a functionality extension table, then the wireless

communication device requests for the functionality extension table information in block 212, and in response to the request, the wireless communication device receives the functionality extension table information that is synchronized to the received preferred roaming list information in block 214. The wireless communication device 5 then updates the stored functionality extension table information in block 216, ends the process in block 210, and resumes its normal operation. After block 216, a third database such as, but not limited to, a call prompt table further complimenting at least one of the preferred roaming list and the functionality extension table, may be received based upon a reference included in the preferred roaming list information or 10 the functionality extension table information. Alternatively, the call prompt table may be included in the preferred roaming list or the functionality extension table.

Referring to FIG. 3, there is provided an exemplary flow chart of another aspect of the invention in a wireless communication device. As shown in the previous example of FIG. 2, this process is initiated when the wireless portable communication 15 device leaves the first region and enters the second region in block 302. Upon entering the second region, the wireless communication device receives functionality extension table information in block 304. Based upon the received functionality extension table information, the wireless communication device requests to receive a corresponding preferred roaming list information in block 306. The wireless 20 communication device then receives the corresponding preferred roaming list information that is synchronized to the received functionality extension table information in block 308, ends the process in block 310, and resumes its normal operation.

In both examples of Fig. 2 and Fig. 3, the synchronization between the 25 preferred roaming list information and the functionality extension table information may be accomplished by maintaining a list of compatible versions or a list of compatible pairs in the network from which the wireless communication device receives the information.

Referring to FIG. 4, there is provided an exemplary flow chart of the third 30 embodiment of the present invention in a network. As shown in block 402, the network maintains a plurality of preferred roaming lists and roaming indicator table, which may be updated periodically. The network also maintains a listing of a

plurality of compatible preferred roaming list and roaming indicator table pairs in block 404. For example, the preferred roaming list version 1 may be compatible with the roaming indicator table version 3 but not with the roaming indicator table version 2; and the preferred roaming list version 2 may be only compatible with the roaming 5 indicator table version 5. As the network detects a wireless communication device leaving the first region and entering the second region, the network transmit one of the preferred roaming list having a version number of the plurality of preferred roaming lists maintained in the network in block 406. Then the network receives the version number and a request for a corresponding roaming indicator table in block 10 408. In addition, the network may receive the capability and status of the wireless communication device to avoid transmitting a roaming indicator table that is compatible with the preferred roaming list but not with the wireless communication device. Based upon the version number received, the network selects the appropriate roaming indicator table that is synchronized with the preferred roaming list having 15 that version number in block 410. The network then transmits the selected roaming indicator table in block 412, and completes the process in block 414.

While the preferred embodiments of the invention have been illustrated and described, it is to be understood that the invention is not so limited. Numerous modifications, changes, variations, substitutions and equivalents will occur to those 20 skilled in the art without departing from the spirit and scope of the present invention as defined by the appended claims.

CLAIMS

1. A method in a wireless communication device, comprising:
 - 5 receiving preferred roaming list information;
 - determining whether the preferred roaming list information includes functionality extension table reference information;
 - 10 requesting functionality extension table information if the preferred roaming list information includes functionality extension table reference information.
- 15 2. The method of Claim 1, receiving the functionality extension table information in response to the request, the functionality extension table information received synchronized with the preferred roaming list information.
3. The method of Claim 2, updating any functionality extension table information stored previously on the wireless communication device with the functionality extension table information received in response to the request.
- 20 4. The method of claim 3, requesting call prompt table information if the preferred roaming list includes call prompt table reference information.
5. The method of claim 4, receiving the call prompt table information in response to the request, the call prompt table information received synchronized with the preferred roaming list information.
- 25 6. The method of claim 3, requesting call prompt table information if the functionality extension table includes call prompt table reference information.
- 30 7. The method of claim 6, receiving the call prompt table information in response to the request, the call prompt table information received synchronized with the functionality extension table.

8. The method of Claim 1, deleting any previously stored functionality extension table information on the wireless communication device if the preferred roaming list information does not include functionality extension table reference information.

5

9. A method in a wireless communication device, comprising:
receiving functionality extension table information from the network;
synchronizing the functionality extension table information with
preferred roaming list information by requesting preferred roaming list
10 information corresponding to the functionality extension table information
received from the network;
receiving preferred roaming list information referencing the
functionality extension table information in response to the request.

15 10. A method in a wireless communication network, comprising:
maintaining an information base correlating compatible versions of
wireless communications device functionality extension table information and
corresponding wireless communication device preferred roaming list
information,

20 the preferred roaming list information including references to the
functionality extension table information;

sending the functionality extension table information to a wireless
communication device;

25 sending the corresponding preferred roaming list information to the
wireless communication device.

11. The method of Claim 10, sending the functionality extension table
information to the wireless communication device in response to a request
from the wireless communication device.

12. The method of Claim 11, sending the functionality extension table information to the wireless communication device after sending the corresponding preferred roaming list information.
- 5 13. The method of Claim 10, sending the preferred roaming list information to the wireless communication device in response to a request from the wireless communication device.
- 10 14. The method of Claim 13, sending the preferred roaming list information to the wireless communication device after sending the corresponding functionality extension table information.
- 15 15. A method in a radiotelephone for synchronizing a preferred roaming list with a roaming indicator table, the preferred roaming list having a list version number, comprising:
 - receiving the preferred roaming list;
 - transmitting the list version number and a request to receive the roaming indicator table corresponding to the list version number; and
 - receiving the roaming indicator table corresponding to the list version number, the roaming indicator table synchronized to the preferred roaming list.

16. A method in a radiotelephone for synchronizing a preferred roaming list with a roaming indicator table, the preferred roaming list having a roaming indicator field and a list version number, comprising:
 - receiving the preferred roaming list;
 - 5 determining if the roaming indicator field meets a predetermined condition;
 - transmitting the list version number and a request to receive the roaming indicator table corresponding to the list version number if the predetermined condition is met; and
- 10 receiving the roaming indicator table corresponding to the list version number, the roaming indicator table synchronized to the preferred roaming list.
17. A method in a radiotelephone for synchronizing a roaming indicator table with a preferred roaming list with the roaming indicator table having a table version number, comprising:
 - receiving the roaming indicator table;
 - 15 transmitting the table version number and a request to receive the preferred roaming list corresponding to the table version number; and
 - 20 receiving the preferred roaming list corresponding to the table version number, the preferred roaming list synchronized to the roaming indicator table.

18. A method in a radiotelephone network for providing a preferred roaming list and a roaming indicator table, comprising:

5 maintaining a plurality of preferred roaming lists and roaming indicator tables;

10 maintaining a listing of a plurality of compatible preferred roaming list and roaming indicator table pairs;

15 transmitting a first preferred roaming list of the plurality of preferred roaming lists having a first list version number;

20 receiving the first list version number of the first preferred roaming list and a request to transmit a first roaming indicator table of the plurality of roaming indicator tables;

25 selecting the first roaming indicator table based upon the first list version number and the listing of compatible preferred roaming list and roaming indicator table pairs; and

30 transmitting the first roaming indicator table, the first roaming indicator table synchronized to the first preferred roaming list.

19. A method in a radiotelephone for replacing a first preferred roaming list and a first roaming indicator table, comprising:

20 receiving a second preferred roaming list having a second list version number;


25 replacing the first preferred roaming list with the second preferred roaming list;

30 transmitting the second list version number and a request to receive a second roaming indicator table corresponding to the second list version number;


35 receiving the second roaming indicator table corresponding to the second list version number, the second roaming indicator table synchronized to the second preferred roaming list.; and

40 replacing the first roaming indicator table with the second roaming indicator table.

1/4

100***FIG. 1***

2/4

***FIG. 2***

3/4





FIG. 3

4/4

400***FIG. 4***