



(12) **United States Patent**
Muthusamy et al.

(10) **Patent No.:** **US 12,081,979 B2**
(45) **Date of Patent:** **Sep. 3, 2024**

(54) **ONE-TIME WIRELESS AUTHENTICATION OF AN INTERNET-OF-THINGS DEVICE**

(71) Applicant: **Visa International Service Association**, San Francisco, CA (US)

(72) Inventors: **Krishnaram Muthusamy**, Austin, TX (US); **Robert Chifamba**, Austin, TX (US)

(73) Assignee: **VISA INTERNATIONAL SERVICE ASSOCIATION**, San Francisco, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 598 days.

(21) Appl. No.: **17/090,385**

(22) Filed: **Nov. 5, 2020**

(65) **Prior Publication Data**

US 2022/0141658 A1 May 5, 2022

(51) **Int. Cl.**
H04W 12/06 (2021.01)
H04L 9/40 (2022.01)

(Continued)

(52) **U.S. Cl.**
CPC **H04W 12/068** (2021.01); **H04L 63/0884** (2013.01); **H04L 63/10** (2013.01); **H04W 12/084** (2021.01); **H04W 12/71** (2021.01)

(58) **Field of Classification Search**
None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,600,915 B1 * 7/2003 Wedeking H04L 67/04 726/28
7,213,143 B1 * 5/2007 Watson H04L 63/0884 713/166

(Continued)

FOREIGN PATENT DOCUMENTS

CN 105472699 B 4/2016
EP 3410675 B1 8/2020

(Continued)

OTHER PUBLICATIONS

Song et al "One-Time Key Authentication Protocol for PMIPv6," Third 2008 International Conference on Convergence and Hybrid Information Technology, IEEE Computer Society pp. 1150-1153 (Year: 2008).*

(Continued)

Primary Examiner — Luu T Pham


Assistant Examiner — James J Wilcox

(74) *Attorney, Agent, or Firm* — Schwabe Williamson & Wyatt, PC

(57) **ABSTRACT**

Authentication of an Internet-of-Things (IoT) device comprises receiving, by a proxy application executing on a mobile device during a registration process, a device identifier associated with the IoT device. The proxy application transmits the device identifier to a router of the wireless network. The proxy application receives the device identifier from the router in response to the router receiving an authorization request with no network password from the IoT device for access to the wireless network, where the router forwards the device identifier to the proxy application. The proxy application prompts the user of the mobile device to enter the password, and transmits the entered network password to the router, such that the router validates the password and grants the IoT device access to the wireless network, the IoT device transmits the IoT device identifier to the router for subsequent network connection without a need for the mobile device.

12 Claims, 8 Drawing Sheets



(56)	References Cited					
U.S. PATENT DOCUMENTS						
2005/0170813	A1*	8/2005	Choi	H04W 12/126	2014/0165165	A1* 6/2014 Story, Jr. H04W 12/0431 726/6
2005/0246243	A1*	11/2005	Adams	G06F 21/10 455/410	2014/0196129	A1* 7/2014 Amin H04L 63/08 726/6
2006/0165060	A1*	7/2006	Dua	G06Q 20/401 705/76	2014/0244834	A1* 8/2014 Guedalia H04W 4/08 709/224
2007/0011452	A1*	1/2007	Marquet	H04L 63/105 713/168	2014/0298405	A1* 10/2014 Qureshi H04L 67/02 726/1
2007/0179794	A1*	8/2007	Fisher	H04L 63/083 726/4	2014/0331295	A1* 11/2014 Kumar H04L 63/0807 726/6
2007/0282201	A1*	12/2007	Kim	G06F 16/9554 707/E17.031	2014/0373170	A1* 12/2014 Brudnicki G06F 21/604 726/27
2008/0301057	A1*	12/2008	Oren	G06Q 20/4012 705/72	2015/0089619	A1* 3/2015 Manza H04L 63/0815 726/8
2009/0013177	A1*	1/2009	Lee	G06F 21/10 713/158	2015/0113172	A1* 4/2015 Johnson H04L 67/75 709/245
2009/0025070	A1*	1/2009	Netanel	H04W 12/08 726/5	2015/0121498	A1* 4/2015 Burch H04L 63/08 726/7
2009/0113536	A1*	4/2009	Zhang	H04L 63/102 726/12	2015/0132984	A1* 5/2015 Kim H04L 63/0838 439/345
2009/0172793	A1*	7/2009	Newstadt	G06F 21/31 726/5	2015/0186642	A1* 7/2015 Cruz Mota G06F 21/554 726/23
2009/0249443	A1*	10/2009	Fitzgerald	H04L 63/10 726/2	2015/0186931	A1* 7/2015 Flake G06Q 30/0247 705/14.46
2009/0249460	A1*	10/2009	Fitzgerald	H04L 63/12 709/206	2015/0230277	A1* 8/2015 O'Meara H04W 76/10 455/411
2009/0253407	A1*	10/2009	Sigmund	H04W 4/16 455/410	2015/0249672	A1* 9/2015 Burns G06F 21/629 726/4
2010/0005516	A1*	1/2010	Alberti	H04L 63/102 726/6	2015/0312250	A1* 10/2015 Redberg H04L 9/30 726/6
2010/0031369	A1*	2/2010	Grummt	H04L 61/30 726/26	2015/0312953	A1* 10/2015 Wang H04L 1/1864 370/312
2010/0100735	A1*	4/2010	Rajan	H04W 12/068 713/168	2015/0350913	A1* 12/2015 Eberwine H04W 12/041 455/411
2010/0192217	A1*	7/2010	Arnold	H04L 63/30 726/13	2015/0365412	A1* 12/2015 Innes H04L 63/12 726/7
2010/0269156	A1*	10/2010	Hohlfeld	H04L 9/321 726/4	2015/0381580	A1* 12/2015 Graham, III H04L 63/20 713/168
2010/0325719	A1*	12/2010	Etchegoyen	H04L 69/40 726/15	2015/0381776	A1* 12/2015 Seed H04L 5/0055 709/203
2011/0040888	A1*	2/2011	Krishnaswamy	H04W 76/14 709/231	2016/0026983	A1* 1/2016 Lindsley G06Q 30/0635 705/26.81
2011/0092185	A1*	4/2011	Garskof	H04L 63/083 455/411	2016/0066183	A1* 3/2016 Conant H04L 63/0853 726/6
2012/0160912	A1*	6/2012	Laracey	H04W 12/069 235/379	2016/0087933	A1* 3/2016 Johnson H04L 41/08 709/245
2012/0179787	A1*	7/2012	Walsh	H04L 63/0281 709/219	2016/0087964	A1* 3/2016 Irving, Jr. H04L 63/12 726/4
2013/0055362	A1*	2/2013	Rathbun	H04L 63/18 726/5	2016/0112434	A1* 4/2016 Chung H04L 63/0807 726/4
2013/0065557	A1*	3/2013	Zhang	H04W 12/04 455/411	2016/0124742	A1* 5/2016 Rangasamy H04L 41/00 717/103
2013/0312091	A1*	3/2013	Merchant	H04L 63/0853 726/20	2016/0127895	A1* 5/2016 Bangole H04W 4/48 380/279
2013/0086657	A1*	4/2013	Srinivasan	H04L 9/3234 726/6	2016/0164840	A1* 6/2016 Robertson H04L 63/10 726/12
2013/0191885	A1*	7/2013	Hubner	H04L 41/5061 709/217	2016/0171479	A1 6/2016 Prakash
2013/0206835	A1*	8/2013	Gazdzinski	G07B 17/00314 235/380	2016/0182228	A1* 6/2016 Smith H04L 9/0841 713/171
2013/0212248	A1*	8/2013	Neafsey	H04W 12/35 709/223	2016/0182518	A1* 6/2016 Smith H04L 63/045 726/3
2013/0339509	A1*	12/2013	Johnson	H04L 41/0803 709/223	2016/0205078	A1* 7/2016 James H04L 9/006 713/171
2014/0040993	A1*	2/2014	Lorenzo	G06F 21/6236 726/4	2016/0205097	A1* 7/2016 Yacoub H04L 61/4511 726/6
2014/0049370	A1*	2/2014	Eberwine	H04L 63/18 340/5.61	2016/0205106	A1* 7/2016 Yacoub H04W 12/041 726/28
2014/0123265	A1	5/2014	Borzycki		2016/0212113	A1* 7/2016 Banerjee H04W 12/06
2014/0143826	A1*	5/2014	Sharp	H04L 63/20 726/1	2016/0212141	A1* 7/2016 Banerjee H04L 63/0846
					2016/0226914	A1* 8/2016 Doddy G06F 21/45
					2016/0234209	A1* 8/2016 Kahol H04L 63/08
					2016/0234628	A1* 8/2016 Rahman H04W 12/50
					2016/0253651	A1* 9/2016 Park G06Q 20/34 705/39
					2016/0259923	A1* 9/2016 Papa H04W 12/35
					2016/0285891	A1* 9/2016 Byers H04L 63/0884

(56)

References Cited

U.S. PATENT DOCUMENTS

2016/0294798	A1*	10/2016	Zarrolì	H04L 63/0861	2018/0232514	A1*	8/2018	Brown	H04L 63/107
2016/0294828	A1*	10/2016	Zakaria	H04L 63/0876	2018/0247064	A1*	8/2018	Aronovich	G06F 16/24552
2016/0315824	A1*	10/2016	Johnson	H04L 63/0281	2018/0247385	A1*	8/2018	Whitfield	H04L 63/102
2016/0323280	A1*	11/2016	Sade	H04L 63/0807	2018/0253544	A1*	9/2018	Ohsumi	H04L 63/0884
2016/0337328	A1*	11/2016	Sallam	H04L 63/08	2018/0255066	A1*	9/2018	Gabriel	H04L 63/0846
2016/0337346	A1*	11/2016	Momchilov	G06F 21/34	2018/0260125	A1*	9/2018	Botes	G06F 16/275
2016/0353489	A1*	12/2016	Blanksby	H04W 76/16	2018/0260876	A1*	9/2018	Graham	H04L 9/32
2016/0364553	A1*	12/2016	Smith	H04L 63/0428	2018/0262388	A1*	9/2018	Johnson	H04L 63/0823
2017/0006009	A1*	1/2017	Hessler	G06F 21/316	2018/0270612	A1*	9/2018	Thoresen	G01S 1/02
2017/0012988	A1*	1/2017	Turgeman	H04W 12/122	2018/0284758	A1*	10/2018	Cella	G06N 3/088
2017/0013549	A1*	1/2017	Ou	H04W 48/16	2018/0287869	A1*	10/2018	Munafò	H04W 12/069
2017/0019387	A1*	1/2017	Ylonen	H04L 63/0435	2018/0293389	A1*	10/2018	Mahaffey	H04L 63/166
2017/0034174	A1*	2/2017	Jägers	H04L 67/01	2018/0309832	A1*	10/2018	Jain	H04L 67/34
2017/0041316	A1*	2/2017	Setchell	H04W 12/50	2018/0316676	A1*	11/2018	Gilpin	H04L 9/0891
2017/0054594	A1*	2/2017	Decenzo	H04L 69/18	2018/0332040	A1*	11/2018	Chou	H04L 63/0853
2017/0063566	A1*	3/2017	Seminario	H04L 67/12	2018/0338241	A1*	11/2018	Li	H04W 4/40
2017/0063843	A1*	3/2017	Vijayasankar	H04L 63/0428	2018/0349482	A1*	12/2018	Oliner	G06F 16/38
2017/0063940	A1*	3/2017	Lapidous	H04L 63/10	2018/0351950	A1*	12/2018	Bao	H04L 63/0884
2017/0086069	A1*	3/2017	Liu	H04L 9/3213	2018/0365309	A1*	12/2018	Oliner	G06F 9/542
2017/0093700	A1*	3/2017	Gilley	H04L 45/44	2019/0012358	A1*	1/2019	Mousseau	G06F 16/27
2017/0093877	A1*	3/2017	Ganda	G06F 21/53	2019/0014085	A1*	1/2019	Soliman	H04L 63/0263
2017/0094509	A1*	3/2017	Mistry	H04W 4/50	2019/0014117	A1*	1/2019	Li	H04L 67/14
2017/0110910	A1*	4/2017	Zeine	H02J 7/00047	2019/0020905	A1*	1/2019	Bennett	H04N 5/917
2017/0124562	A1*	5/2017	Hessler	G06Q 20/386	2019/0025813	A1*	1/2019	Cella	G06F 18/2178
2017/0169234	A1*	6/2017	Camiel	H04L 67/1097	2019/0026445	A1*	1/2019	Ginsberg	H04L 9/0894
2017/0169424	A1*	6/2017	Maddocks	G06Q 20/3821	2019/0026456	A1*	1/2019	Hon	G06F 21/40
2017/0171176	A1*	6/2017	Angaluri	G06F 21/50	2019/0036697	A1*	1/2019	Jerichow	H04L 63/062
2017/0171209	A1*	6/2017	Licklider	G06F 21/31	2019/0036906	A1*	1/2019	Biyani	H04L 63/08
2017/0180208	A1*	6/2017	Smith	H04L 41/5054	2019/0036914	A1*	1/2019	Tzur-David	H04L 9/0861
2017/0180567	A1*	6/2017	Sharma	H04M 15/00	2019/0044976	A1*	2/2019	Smith	H04L 67/12
2017/0187723	A1*	6/2017	Islam	H04L 63/1433	2019/0052630	A1*	2/2019	Lapidous	H04L 63/0853
2017/0208054	A1*	7/2017	Hanay	H04L 63/06	2019/0052659	A1*	2/2019	Weingarten	H04L 41/046
2017/0208057	A1*	7/2017	Wang	H04L 63/083	2019/0095478	A1*	3/2019	Tankersley	G06F 11/3006
2017/0223807	A1*	8/2017	Recker	H02J 7/34	2019/0097902	A1*	3/2019	Hardin	H04L 43/0817
2017/0228182	A1*	8/2017	Novak	H04L 63/08	2019/0104409	A1*	4/2019	Wu	H04L 63/20
2017/0230832	A1*	8/2017	Ophir	H04W 12/06	2019/0109713	A1*	4/2019	Clark	G06F 16/182
2017/0236179	A1*	8/2017	Dreifus	H04M 15/8022	2019/0109714	A1*	4/2019	Clark	H04L 67/565
				705/26.63	2019/0109820	A1*	4/2019	Clark	H04L 9/0861
2017/0237609	A1*	8/2017	Yin	H04L 67/1095	2019/0109821	A1*	4/2019	Clark	H04L 63/0414
				709/222	2019/0109822	A1*	4/2019	Clark	H04L 63/145
2017/0237770	A1*	8/2017	Meriac	H04L 67/12	2019/0109848	A1*	4/2019	Clark	H04L 9/3228
				726/23	2019/0118767	A1*	4/2019	Britt	H04L 67/125
2017/0251026	A1*	8/2017	Straub	H04L 67/02	2019/0121348	A1*	4/2019	Cella	G06N 3/084
2017/0272316	A1*	9/2017	Johnson	H04L 61/301	2019/0124671	A1*	4/2019	Starsinic	H04W 4/60
2017/0272953	A1*	9/2017	Nathan	H04W 12/08	2019/0141526	A1*	5/2019	Bahrami	H04L 63/083
2017/0302669	A1*	10/2017	Chen	H04W 12/08	2019/0141610	A1*	5/2019	Sabella	G06F 9/45533
2017/0330191	A1*	11/2017	Pender	G06Q 20/3221	2019/0149545	A1*	5/2019	Arora	H04W 12/06
2017/0331815	A1*	11/2017	Pawar	H04L 63/0823					726/7
2017/0339561	A1*	11/2017	Wennemyr	H04W 64/00	2019/0158353	A1*	5/2019	Johnson	G06F 16/95
2017/0353859	A1*	12/2017	Idnani	H04W 12/08	2019/0173873	A1*	6/2019	Brown	H04L 63/0823
2017/0359237	A1*	12/2017	Hao	G06F 21/44	2019/0182734	A1*	6/2019	Laliberte	H04W 24/08
2017/0366969	A1*	12/2017	Syed	H04W 12/068	2019/0182895	A1*	6/2019	Di Girolamo	H04L 63/0892
2018/0004933	A1*	1/2018	Nathanson	H04W 12/084	2019/0190920	A1*	6/2019	Connell, II	H04W 12/771
2018/0006883	A1*	1/2018	Melliere	H04L 67/34	2019/0230079	A1*	7/2019	Chung	H04L 63/0884
2018/0013729	A1*	1/2018	Cooper	H04L 63/0428	2019/0236868	A1*	8/2019	Rines	G07C 9/00896
2018/0014988	A1*	1/2018	Diaz-Flores	A61G 5/023	2019/0245856	A1*	8/2019	Irwan	H04L 9/0643
2018/0034682	A1*	2/2018	Gulati	H04L 9/3268	2019/0246276	A1*	8/2019	Lingala	H04W 12/08
2018/0034822	A1*	2/2018	Mistry	H04W 12/37	2019/0253461	A1*	8/2019	Bykampadi	H04L 63/205
2018/0039795	A1*	2/2018	Gulati	H04L 63/0823	2019/0255963	A1*	8/2019	Goei	B60L 53/68
2018/0041341	A1*	2/2018	Gulati	H04L 9/0894	2019/0260762	A1*	8/2019	Fynaardt	H04W 12/06
2018/0054490	A1*	2/2018	Wadhwa	G08G 1/0129	2019/0279212	A1*	9/2019	Brown	G06Q 20/409
2018/0076955	A1*	3/2018	Shields	H04L 63/06	2019/0281455	A1*	9/2019	Luo	H04W 12/08
2018/0083785	A1*	3/2018	Shields	H04W 12/033	2019/0286812	A1*	9/2019	Lounsberry	H04L 9/006
2018/0089693	A1*	3/2018	Martin	H04M 7/0024	2019/0289466	A1*	9/2019	Conant	H04W 12/06
2018/0097639	A1*	4/2018	Gulati	H04L 9/3268	2019/0294765	A1*	9/2019	Fine	G16H 10/60
2018/0115554	A1*	4/2018	Dyon	H04L 63/164	2019/0306251	A1*	10/2019	Talebi Fard	H04W 76/10
2018/0115611	A1*	4/2018	Lear	H04L 41/28	2019/0313468	A1*	10/2019	Talebi Fard	H04W 60/04
2018/0121636	A1*	5/2018	Schiffman	G06F 21/34	2019/0319686	A1*	10/2019	Chen, IV	H04W 24/08
2018/0145956	A1*	5/2018	Anglin	H04L 63/105	2019/0319861	A1*	10/2019	Pan	H04L 9/0637
2018/0146378	A1*	5/2018	Christmas	H04W 4/80	2019/0319916	A1*	10/2019	Venkataramanan	H04L 67/131
2018/0152452	A1*	5/2018	Hu	H04W 12/08					H04L 67/131
2018/0176079	A1*	6/2018	Teo	H04W 52/0219	2019/0324439	A1*	10/2019	Cella	G06F 18/217
2018/0184290	A1*	6/2018	Luo	H04L 63/0442	2019/0324444	A1*	10/2019	Cella	G05B 19/4183
2018/0212768	A1*	7/2018	Kawashima	H04L 63/0876	2019/0334764	A1*	10/2019	Chor	H04L 41/0686
2018/0227842	A1*	8/2018	Chandramouli	H04W 12/065	2019/0334869	A1*	10/2019	Grant	H04L 61/5007
					2019/0339688	A1*	11/2019	Cella	H04L 1/18
					2019/0342289	A1	11/2019	Zhu	
					2019/0342874	A1*	11/2019	Davydov	H04W 72/23
					2019/0351783	A1*	11/2019	Goei	B60L 53/63

(56)

References Cited

OTHER PUBLICATIONS

Rattanalerdnusorn et al "Security Implementation for Authentication in IoT Environments," 2019 IEEE 4th International Conference on Computer and Communication Systems, IEEE, pp. 678-681 (Year: 2019).*

Garg et al "Securing IoT Devices and Securely Connecting the Dots Using REST API and Middleware," IEEE, pp. 1-6 (Year: 2019).*

Guntuku et al "Secure Authentication Scheme for Internet of Things in Cloud," IEEE, pp. 1-7 (Year: 2018).*

Patent Cooperation Treaty: International Search Report and Written Opinion for PCT/US2021/044667 dated Nov. 15, 2021; 10 pages.

European Patent Office: Extended European Search Report issued is EP Application No. 21889773.4, dated Mar. 4, 2024; 12 pages.

* cited by examiner

10




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 6
Continued




FIG. 7

ONE-TIME WIRELESS AUTHENTICATION OF AN INTERNET-OF-THINGS DEVICE

BACKGROUND

Today, the use of Internet-of Things (IoT) devices are proliferating. An IoT device is an electronic computing device that connects wirelessly to a network and has the ability to transmit data over the network. IoT devices are nonstandard computing devices in that they are typically not equipped with a user interface for user interaction and focus instead on machine-to-machine communication. The lack of a user interface can be problematic when the IoT device needs to connect to the wireless network the first time with necessary access credentials (e.g., user name and password), which are typically entered by a user. If the IoT has the requisite size, then the IoT device can be equipped with some type of user interface, such as a small keyboard and/or screen. However, adding a user interface comes at a cost.

Accordingly, it be desirable to provide an improved method and system for wireless authentication of an IoT device.

BRIEF SUMMARY

The exemplary embodiments provide methods and systems for one-time wireless authentication of an Internet-of-Things device. Aspects of exemplary embodiment include receiving, by a proxy application executing on a mobile device during a registration process, a device ID associated with the IoT device. The proxy application transmits the device ID to a router of the wireless network. Subsequent to the registration process, the proxy application receives the device ID from the router in response to the router receiving an authorization request with no network password from the IoT device for access to the wireless network, where the router forwards the device ID to the proxy application. The proxy application prompts the user of the mobile device to enter the password, and transmits the entered network password to the router, such that the router validates the password and grants the IoT device access to the wireless network, the IoT device transmits the IoT device ID to the router for subsequent network connection without a need for the mobile device.

In another embodiment, methods and systems for one-time wireless authentication of an Internet-of-Things device comprises a router receiving a registration request from a proxy application executing on a mobile device, the registration request including a device identifier associated with the IoT device, the device identifier entered into the proxy application by a user of the mobile device, the router further storing the device identifier and enabling a proxy authentication setting. The router receives an authorization request from the IoT device for access to a wireless network, the authorization request comprising at least the device identifier without a network password. The router determines if a proxy authentication setting is enabled, and if so forwards the device identifier to the proxy application. The router receives a message from the proxy application, a message including a network password entered into the proxy application by the user. Responsive to the router validating the network password, the router grants the IoT device access to the wireless network, wherein the IoT device transmits the device identifier to the router for subsequent connection without a need for the mobile device or the proxy application.

According to the method and system disclosed herein, the disclosed embodiments enable easy wireless Internet connectivity for an Internet-of-Things device having no provisions for password entry, thus eliminating the need for keys and user interaction through the Internet-of-Things device. The methods and systems facilitate such Internet-of-Things devices to connect to the Internet of long as the Internet-of-Things devices are pre-configured for proxy authentication using the mobile application in conjunction with software changes in the router.

BRIEF DESCRIPTION OF SEVERAL VIEWS OF THE DRAWINGS

FIG. 1 is a block diagram illustrating a system for enabling a mobile application to provide one-time wireless authentication of an Internet-of-Things device according to a first embodiment.

FIG. 2 is a flow diagram illustrating an overview of a process for one-time wireless authentication of an Internet-of-Things device in accordance with some embodiments.

FIG. 3 is a block diagram illustrating a system for enabling a mobile application to provide one-time wireless authentication of an Internet-of-Things device according to a second embodiment.

FIG. 4 is a flow diagram illustrating the process for one-time wireless authentication of an Internet-of-Things device in accordance with the second embodiment of FIG. 3.

FIG. 5 is a block diagram illustrating a system for enabling a mobile application to provide one-time wireless authentication of an Internet-of-Things device according to a third embodiment.

FIG. 6 is a flow diagram illustrating the process for one-time wireless authentication of an Internet-of-Things device in accordance with the third embodiment of FIG. 5.

FIG. 7 shows an implementation of a computer system that may be applicable to IoT device, the mobile device, the authentication mapping server and/or the router mapper system.

DETAILED DESCRIPTION

The exemplary embodiment relates to a mobile application for one-time wireless authentication of an Internet-of-Things device. The following description is presented to enable one of ordinary skill in the art to make and use the invention and is provided in the context of a patent application and its requirements. Various modifications to the exemplary embodiments and the generic principles and features described herein will be readily apparent. The exemplary embodiments are mainly described in terms of particular methods and systems provided in particular implementations. However, the methods and systems will operate effectively in other implementations. Phrases such as “exemplary embodiment”, “one embodiment” and “another embodiment” may refer to the same or different embodiments. The embodiments will be described with respect to systems and/or devices having certain components. However, the systems and/or devices may include more or less components than those shown, and variations in the arrangement and type of the components may be made without departing from the scope of the invention. The exemplary embodiments will also be described in the context of particular methods having certain steps. However, the method and system operate effectively for other methods having different and/or additional steps and steps in different orders

that are not inconsistent with the exemplary embodiments. Thus, the present invention is not intended to be limited to the embodiments shown, but is to be accorded the widest scope consistent with the principles and features described herein. As used herein, the terms “communication” and “communicate” may refer to the reception, receipt, transmission, transfer, provision, and/or the like of information (e.g., data, signals, messages, instructions, commands, and/or the like). For one unit (e.g., a device, a system, a component of a device or system, combinations thereof, and/or the like) to be in communication with another unit means that the one unit is able to directly or indirectly receive information from and/or send (e.g., transmit) information to the other unit. This may refer to a direct or indirect connection that is wired and/or wireless in nature. Additionally, two units may be in communication with each other even though the information transmitted may be modified, processed, relayed, and/or routed between the first and second unit. For example, a first unit may be in communication with a second unit even though the first unit passively receives information and does not actively send information to the second unit. As another example, a first unit may be in communication with a second unit if at least one intermediary unit (e.g., a third unit located between the first unit and the second unit) processes information received from the first unit and sends the processed information to the second unit. In some non-limiting embodiments, a request or message may refer to a network packet (e.g., a data packet and/or the like) that includes data.

To provide context for the disclosed embodiments, today a wireless router provides and communications over a local or home wireless (Wi-Fi) network and connects to the Internet via a modem. An electronic device needing access to the wireless network needs to send access credentials, such as a network password, to the router. The first time an electronic device connects to the wireless network, a user typically inputs the network password, which is transmitted to the router. The router then sends an authentication request with the access credentials to a credential management system. The credential management system can be local to the router or a remote server. The credential management system receives the authentication request and authenticates the access credentials against previously stored access credentials for the router. The credential management system sends a response to the router either allowing or denying network access, and the router then either grants the device network access or alternatively sends a denial message.

For electronic devices with no provisions for manual entry of access credentials, such as an Internet-of-Things (IoT) device, methods and systems are required to facilitate easy wireless network and Internet connectivity through the router.

According to the disclosed embodiments, a one-time authentication process is provided for an IoT device to use a wireless network without the need for the IoT device to have a user interface for entering access credentials. Instead, a mobile phone of the user, and in particular, an application on the mobile phone, acts as a proxy to provide one-time wireless authentication of the IoT device with a router of a wireless network during first access. Thereafter, if the IoT device becomes disconnected from the network, the IoT device can reconnect to the network by transmitting the device ID of the IoT device to the router for subsequent connection without requiring aid of the mobile device. Several embodiments are herein described that collectively unify the idea of proxy authentication by encapsulating underlying security controls and data distribution.

FIG. 1 is a block diagram illustrating a system for enabling a mobile application to provide one-time wireless authentication of an Internet-of-Things device according to a first embodiment. The system 10 includes a router 12 that provides a network 14 and communicates over the network 14 and the Internet 20. The router 12 is connected to the Internet 20 through a gateway (not shown). In one embodiment, the network is a wireless network, but wired connections (e.g., Ethernet) with the router 12 can also be made. As used herein, a “router” is a networking device forwards data packets between computer networks for example, in the home and small office environment, Internet protocol (IP) routers simply forward IP packets between home/office computing devices and the Internet.

A mobile device 16 is wirelessly connected to the network 14, and an Internet-of-Things (IoT) device 18 requires first time access to the network 14. A “mobile device” may be a device that is operated by a user. Examples of mobile devices 16 may include a mobile phone, a smart phone, a laptop computer, a desktop computer, a server computer, a vehicle such as an automobile, a thin-client device, a tablet PC, etc. Additionally, mobile devices may be any type of wearable technology device, such as a watch, earpiece, glasses, etc. The mobile device 16 may include one or more processors capable of processing user input. The mobile device 16 may also include one or more input sensors for receiving user input. As is known in the art, there are a variety of input sensors capable of detecting user input, such as accelerometers, cameras, microphones, etc. The user input obtained by the input sensors may be from a variety of data input types, including, but not limited to, audio data, visual data, or biometric data. The mobile device may comprise any electronic device that may be operated by a user, which may also provide remote communication capabilities to a network. Examples of remote communication capabilities include using a mobile phone (wireless) network, wireless data network (e.g., 3G, 4G, 5G or similar networks), Wi-Fi, Wi-Max, or any other communication medium that may provide access to a network such as the Internet or a private network.

As used herein, an Internet of things (IoT) device describes an electronic device—“a thing”—that is embedded with sensors, software, and other technologies for the purpose of connecting and exchanging data with other devices and systems over the Internet or other network.

The router 12 may communicate with a credential management system 22, which maintains an access credentials database 25. When the router 12 receives an authentication request from a device, e.g., the IoT device 18, for network access, the router 12 may forward the authentication request to the credential management system 22 to authenticate the requesting device.

The IoT device 18 is associated with a device identifier (ID) 34, and the proxy application 24 is associated with an application (app) ID 32. The IDs 34 and 32 may include any distinctive set of alphanumeric characters (numbers, graphics, symbols letters or other information) that can be used to identify a device or a program. For example, the device ID 34 may comprise a serial number, partial serial number, a key and the like, or a combination thereof, associated with the IoT device 18.

In one embodiment, the router 12, the IoT device 18, and the mobile device 16 are configured to receive and transmit messages over the network 14 using the Internet protocol suite otherwise known as Transmission Control Protocol (TCP) and the Internet Protocol (IP) or TCP/IP.

According to the disclosed embodiments, since a user cannot enter the access credentials for the network 14 on the IoT device 18 due to its lack of a user interface, the system 10 further includes a mobile application, referred to herein as a proxy application (proxy app) 24 that acts a proxy for the IoT device 18 during the first network authentication attempt with the router 12, and a proxy authentication setting 28 for the router 12. In embodiments, the authentication mapping server 326 maintains a mapping between the IoT device 18 and the proxy application 24.

According to embodiments, the system 10 associates the proxy app 24 with the app ID 32. The app ID 32 may be a special purpose software key, a mobile phone number associated with the mobile device 16, a partial phone number, a software key, and the like, or a combination thereof. When associated with the proxy application 24, the app ID 32 may be used by the system 10 to determine the mobile device 16 on which the proxy application 24 is installed.

FIG. 2 is a flow diagram illustrating an overview of a process for one-time wireless authentication of an Internet-of-Things device in accordance with some embodiments. As an overview, the process occurs between the router 12 and the proxy application 24 executing on the mobile device 16 of the user. The process assumes that access credentials, such as a password, for the wireless network 14 have been sent from the router 12 to the credential management system 22 and stored in access credentials database 25. The process further assumes the user has installed the proxy application 24 on the user's mobile device 16 in order to configure the IoT device 18 for a one-time proxy authentication to the wireless network 14.

The one-time wireless authentication process includes a registration phase in which the proxy application 24 is opened and receives the device ID 34 associated with the IoT device 18 that is entered by a user (block 200). This step may be initiated in response to a user who wants to set up the IoT device 18 and presses a "registration button" displayed by proxy application 24 to register the IoT device 18. Thereafter, the proxy application 24 displays a field into which the user may enter the device ID 34. The device ID 34 may comprise a serial number or other identifier of the IoT device 18. The user may find the device ID 34 on the IoT device 18 itself or in documentation provided with the IoT device 18.

The proxy application 24 transmits the device ID to the router 12 in a registration request (block 201). The router 12 receives the registration request, stores the device ID 34 in the credential management system 22, and enables the proxy authentication setting 28 (block 202). In one embodiment, the credential management system 22 may comprise part of a local backend system for the router 12. In another embodiment, the credential management system 22 may be a remote site on the Internet 20. The proxy authentication setting can be stored by the router 12 or by the credential management system 22.

In one embodiment, the registration phase may include the proxy application 24 associating the device ID 34 with the app ID 32 of the proxy application 24. In one embodiment, a mapping of the device ID 34 to the app ID 32 may be registered as an ID pair with the router 12 or another system (e.g., an authentication mapper server 326 shown in FIG. 3). In one embodiment, the proxy application 24 sends both the device ID 34 and the app ID 32 as an ID pair in the registration request sent to the router 12 in block 201. The router 12 may then store the mapping of the ID pair in the credential management system 22 or forward the ID pair to another system in block 202.

Subsequent to the registration process, the router 12 receives, an authorization request from the IoT device 18 over the network 14, wherein the authorization request comprises at least the device ID 34 without a network password (block 204). In one embodiment, when the IoT device 18 is first turned on, the IoT device 18 may be configured to determine automatically which one of a plurality of detected wireless networks to request access. This may be done by selecting the network 14 having the highest signal strength based on the assumption that the physically closest router 12 would have the best signal, as is typically the case in a local network environment. If the IoT device 18 fails to receive a reply to the authorization request within a predetermined time threshold, the IoT device 18 may send an authentication request to a router of another network having the next highest signal strength and so on until the IoT device finds the router with proxy authentication enabled.

The router 12 then determines if the proxy authentication setting 28 is enabled, and if so, forwards the device ID 34 to the proxy application 24 (block 206). If the proxy authentication setting 28 is not enabled, the process ends with the router sending a denial message to the IoT device 18. The proxy application 24 receives the device ID 34 from the router 12, and optionally validates the device ID (block 208). In response to the proxy application 24 validating the device ID 34 (e.g., by checking an internal setting, table or database), the proxy application 24 prompts the user to enter the network password and receives the entered network password (block 210). The proxy application 24 then transmits the entered network password in a message to the router 12 (block 212).

The router 12 receives a message including the entered network password and validates the entered network password (block 214). In one embodiment, the router 12 validates the entered network password by sending a validation request to the credential management system 22, which validates the network password if a match is found for the password in the access credentials database 25. In one embodiment, the credential management system 22 may be part of a backend system for the router.

Responsive to validating the entered network password, the router 12 sends a success message to the IoT device 18 granting access to the wireless network, wherein the IoT device 18 transmits the device ID 34 to the router 12 for subsequent connection without a need for the network password, the mobile device 16, or the proxy application 24 (block 216). That is, the IoT device 18 typically stays connected to the wireless network 14, but if the IoT device 18 becomes disconnected, the IoT device 18 resends the device ID 34 to the router 12. The router 12 looks up the device ID 34 and if found reestablishes the network connection, all without any input from the user or the mobile device 16.

FIG. 3 is a block diagram illustrating a system for enabling a mobile application to provide one-time wireless authentication of an Internet-of-Things device according to a second embodiment, where like components from FIG. 1 have like reference numerals.

The system 300 is similar to the system 10 of FIG. 1, except provides additional security by separating functionality of the proxy application into two separate applications (apps), referred to herein as proxy app A 324A and proxy app B 324B, installed on mobile device 16. In this embodiment, proxy app A 324A is associated with an app A ID 32A and proxy app B 324B is associated with an app B ID 32B. Both

the app A ID 32A and the app B ID 32B may include the unique mobile phone number of the mobile device 16 in which the apps are installed.

According to one embodiment, for additional security the proxy system 300 further includes an authentication mapper server 326 in communication with the router 312 over the Internet 20, which is configured to communicate request and responses for proxy app A 324A and proxy app B 324B so that proxy app A 324A and proxy app B 324B do not communicate with one another directly. The term “server” may refer to one or more computing devices, such as processors, storage devices, and/or similar computer components, that communicate with client devices and/or other computing devices over a network, such as the Internet or private networks and, in some examples, facilitate communication among other servers and/or client devices. For example, the server computer can be a large mainframe, a minicomputer cluster, or a group of servers functioning as a unit. In one example, the server computer may be a database server coupled to a Web server, and may include or be coupled to a database.

In one embodiment, the authentication mapper server 326 communicate with proxy app A 324A and proxy app B 324B though, for example, a Representational state transfer (REST) application programming interface (API) or REST API.

This second embodiment provides additional security by establishing distributed controls and distributed ownership on the data. For example, the authentication mapper server 326 may have control over network authentication and may be provided and/or run by a manufacturer of the router 312. Any subsequent need of decoupling or disabling a IoT device 18 from proxy authentication may require the manufacturer of the IoT device 18 to update the authentication mapper server 326 through the router manufacture.

In one embodiment, proxy app A 324A is configured to receive from the router 312 the device ID 34 of the IoT device 18 during the request for network authorization, and determine if that specific IoT device has been enabled for proxy authentication by forwarding the device ID 34 to the authentication mapper server 326 to validate the device ID. Proxy app B 324B is configured to respond to a validation message from the authentication mapper server 326 by displaying a popup screen prompting the user to enter the network password and to send the entered network password to the router 312 for validation through the authentication mapper server 326 and proxy app A 324A, as explained below.

Technically proxy app A 324A and proxy app B 324B have different functionalities, but in an alternative embodiment can be combined into one proxy application on the mobile device 16, as in FIG. 1. Also multiple IoT devices can use the dual proxy applications or the single proxy application in the mobile device 16 for this initial setup.

FIG. 4 is a flow diagram illustrating the process for one-time wireless authentication of an Internet-of-Things device in accordance with the second embodiment of FIG. 3. The one-time wireless authentication process includes a registration phase that assumes once proxy app A 324A and proxy app B 324B are started the first time on the mobile device 16, proxy app A 324A and proxy app B 324B register the respective app A ID 32A and the app B ID 32B as an application pair with the authentication mapper server 326. The authentication mapping server 326 may store the registration of the app A ID 32A and the app B ID 32B as an application ID pair in the mapping database 302.

Referring both to FIGS. 3 and 4, during the registration phase proxy app A 324A displays a user interface in which to receive the device ID 34 associated with the IoT device 18 entered by a user (block 400). This step may be initiated in response to a user desiring to set up the IoT device 18 and pressing a “registration button” on proxy app A 324A or proxy app B 324B to register the IoT device 18. Thereafter, the proxy app A 324A displays a field into which the user may enter the device ID 34. Proxy app A 324A receives the device ID 34 and transmits both the app A ID 32A and device ID 34 as an ID pair in a registration request to the router 312 (block 401).

The router 312 receives the registration request, i) enables the proxy authentication setting 28, ii) stores at least the device ID 34, and iii) forwards the ID pair to the authentication mapper server 326 in a registration request (block 402). Once the authentication mapper server 326 receives the ID pair, the authentication mapper server 326 uses the app A ID 32A to find the record 304 having a matching app A ID 32A in the mapping database 302, and stores/associates the device ID 34 with the application ID pair in record 304. In an alternative embodiment, proxy app B 324B may be used instead of proxy app A 324A in the above registration process.

Subsequent to the registration process, the router 312 receives, an authorization request from the IoT device 18 over the network 14, wherein the authorization request comprises at least the device ID 34 without a network password (block 404). As an example, the authorization request may include DeviceID: “tdrgsthawu2n4n5j9aj415n2v97 cm3bc78h3vn678” for instance.

The router 312 then determines if the proxy authentication setting 28 is enabled, and if so, forwards the device ID 34 to the proxy app A 324A (block 406). In one embodiment, the router 312 receives and forwards the authorization request over the network 14 using the Internet protocol suite otherwise known as Transmission Control Protocol (TCP) and the Internet Protocol (IP).

Proxy app A 324A receives the device ID 34 from the router 312, and forwards the device ID 34 in a validation request to the authentication mapper server 326 for validation (block 408). In response, proxy app B 324B receives a validation response from the authentication mapper server 326 in response to the validation request of proxy app A 324A (block 410A). In embodiments, the authentication mapper server 326 upon receiving the validation request, first uses the device ID 34 to search the mapping database 302 to find the mapping record 304 having a matching device ID 34, and once found, the authentication mapper server 326 sends the validation response to the proxy app B 324B listed in the matching mapping record 304 via the preconfigured REST API.

For example the authentication mapper server 326 may store the preconfigured REST API as:
 (https://www.appa.appid/{info}) APP A—
 deviceKey:“tdrgsthawu2n4n5j9aj415n2v97
 cm3bc78h3vn678---->APP B
 (https://www.appb.appId/{Info}),

where the preconfigured REST API informs the authentication mapper server 326 to call https://www.appb.appId/{Info} registered by app B, for any incoming requests from App A corresponding to deviceKey: “tdrgsthawu2n4n5j9aj415n2v97 cm3bc78h3vn678.

In response to receiving the response from the authentication mapper server 326 validating the device ID 34, proxy app B 324B prompts the user to enter the network password

and receives the entered network password (block 410B). Proxy app B 324B then transmits the entered network password in a message to the authentication mapper server 326 for forwarding to proxy app A 324A via the preconfigured REST API (block 412A). Proxy app A 324A then transmits the entered network password in a message to the router 12 (block 412B).

The router 312 receives a message including the entered network password and validates the entered network password (block 414). In one embodiment, the router 312 validates the entered network password by sending a validation request to the credential management system 22, which does so if a match is found for the password in the access credentials database 24. In one embodiment, the credential management system 22 may be part of a backend system for the router 312.

Responsive to validating the entered network password, the router 312 sends a success message to the IoT device 18 granting access to the wireless network, wherein the IoT device 18 transmits the device ID 34 to the router 312 for subsequent connection without a need for the network password, the mobile device 16 or the proxy applications 324A and 324B (block 416).

FIG. 5 is a block diagram illustrating a system for enabling a mobile application to provide one-time wireless authentication of an Internet-of-Things device according to a third embodiment, where like components from FIG. 3 have like reference numerals. The system 500 is similar to the system 300 of FIG. 3, except in addition to using the two separate proxy applications, proxy app A 324A and proxy app B 324B, system 500 further includes a router mapper system 502. In this embodiment, proxy app A 324A is associated with an app A ID 32A and proxy app B 324B is associated with an app B ID 32B, where both the app A ID 32A and the app B ID 32B may include the unique mobile phone number of the mobile device 16 in which the apps are installed.

The third embodiment enables the manufacturer of the router 512 and the manufacturer of the IoT device 18 to share responsibility for the proxy authentication. For example, the manufacturer of the router 512 may control the router mapper system 504, while the manufacturer of the IoT device 18 may control the authentication mapper server 326. During the proxy authentication process, input from both the router mapper system 504 and the authentication mapper server 326 is required, as described with respect to FIG. 6.

FIG. 6 is a flow diagram illustrating the process for one-time wireless authentication of an Internet-of-Things device in accordance with the third embodiment of FIG. 5. The one-time wireless authentication process includes a registration phase that assumes once proxy app A 324A and proxy app B 324B are started the first time on the mobile device 16 that: i) a mapping between the app A ID 32A and the network password (PW) is registered with the router mapper system 504; and ii) the app B ID 32B is registered with the authentication mapper server 326. This pre-mapping process safeguards the router 512 from having to receive authentication request from proxy apps on connected mobile devices other than from authorized proxy app A 324A and proxy app B 324B on mobile device 16 by checking any such request against the router DB 506 and the mapping DB 302.

Referring both to FIGS. 5 and 6, during the registration phase proxy app A 324A displays a user interface in which to receive the device ID 34 associated with the IoT device 18 entered by a user (block 600). Proxy app A 324A receives

the device ID 34 and transmits both the app A ID 32A and device ID 34 as an ID pair in a registration request to the router 312 (block 601).

The router 312 upon receiving the registration request: i) enables the proxy authentication setting 28, ii) stores at least the device ID 34, and iii) forwards the device ID pair to the router mapper system 504 in one registration request, and iv) forwards the app B ID 32B and the device ID 34 to the authentication mapper server 326 in another registration request (block 602).

As shown in FIG. 5, the router mapper system 504 may store the device ID 34 in a record 508 of router database 506 associating app A ID 32A and the network password. Similarly, the authentication mapper server 326 may store the device ID 34 in a record 304 of mapping database 302 containing the app B ID 32B.

Subsequent to the registration process, the router 312 receives, an authorization request from the IoT device 18 over the network 14, wherein the authorization request comprises at least the device ID 34 without a network password (block 604). As an example, the authorization request may include DeviceID: "tdrgsthawu2n4n5j9aj415n2v97 cm3bc78h3vn678" for instance.

The router 312 then determines if the proxy authentication setting 28 is enabled, and if so, forwards the device ID 34 to the router mapper system 504 (block 606).

The router mapper system 504 receives the device ID 34 and uses the device ID 34 to find, and send a notification message to, the proxy app A 324A mapped to the device ID 34 by the app A ID 32A (block 608). In one embodiment, the notification message is sent using the preconfigured REST API. For example the router mapper system 504 may store the preconfigured REST API as:

```
(https://www.appa.appid/{info}) APP A—
deviceKey:"tdrgsthawu2n4n5j9aj415n2v97
cm3bc78h3vn678---->Mobile device
APP A (https://www.appa.appId/{Info}),
where the preconfigured REST API in the router mapper
system 504 informs the authentication mapper server 326 to
call https://www.appa.appId/{Info} registered by app A, for
any incoming requests from the router 512 corresponding to
deviceKey: "tdrgsthawu2n4n5j9aj415n2v97
cm3bc78h3vn678.
```

In response, proxy app A 324A receives the notification message from the router mapper system 504 and forwards the notification message through the router-Internet to the authentication mapper server 326 (block 610). In response, proxy app B 324B receives a validation response from the authentication mapper server 326 in response to notification message from proxy app A 324A (block 612). That is, the authentication mapper server 326 first uses the device ID 34 received from proxy app A 324A to search the mapping database 302 to find the mapping record 304 having a matching device ID, and once the matching mapping record 304 is found, the authentication mapper server 326 sends the validation response to the proxy app B 324B mapped to the device ID in mapping record 304 via the preconfigured REST API.

For example the authentication mapper server 326 may store the preconfigured REST API as:

```
(https://www.appa.appid/{info}) APP A—
deviceKey:"tdrgsthawu2n4n5j9aj415n2v97
cm3bc78h3vn678---->APP B
(https://www.appb.appId/{Info}),
where the preconfigured REST API informs the authentica-
tion mapper server 326 to call https://www.appb.appId/
```

{Info} registered by app B, for any incoming requests from App A corresponding to deviceKey: "tdrgsthawu2n4n5j9aj415n2v97 cm3bc78h3vn678.

In response to receiving the response from the authentication mapper server **326** validating the device ID **34**, the proxy app B **324B** prompts the user to enter the network password and receives the entered network password (block **614**). Proxy app B **324B** then transmits the entered network password in a message to the authentication mapper server **326** for forwarding to proxy app A **324A** via the preconfigured REST API (block **616**). Proxy app A **324A** then transmits the entered network password in a message to the router mapper system **504** using the REST API (block **618**).

The router mapper system **504** receives a message including the entered network password and upon finding a matching network password, transmits the network password to the router **512** (block **620**). The router **512** receives a message including the entered network password and validates the network password (block **622**). In one embodiment, the router **512** validates the entered network password by sending a validation request to the credential management system **22**, which does so if a match is found for the password in the access credentials database **24**.

Responsive to validating the entered network password, the router **512** sends a success message to the IoT device **18** granting access to the wireless network, wherein the IoT device **18** transmits the IoT device ID to the router **512** for subsequent connection without a need for the network password, the mobile device **16** or the proxy applications **324A** and **324B** (block **624**).

Methods and systems for one-time wireless authentication of an IoT device have been described. Methods and systems facilitate easy wireless Internet connectivity for an IoT device when there is no available means for manual entry of passwords from the IoT device, thus eliminating the need for keys and user interaction through the IoT device **18**. The methods and systems facilitate IoT devices having no provisions for password entry to connect to the Internet of long as the IoT devices are pre-configured for proxy authentication using one or more mobile application and in addition to software changes in the router.

FIG. 7 shows an implementation of a computer system **700** that may be applicable to IoT device **18**, the mobile device **16**, the authentication mapping server **26** and/or the router mapper system **504**. According to an embodiment. The computer system **700** can include a microprocessor(s) **703** and memory **702**. In an embodiment, the microprocessor(s) **703** and memory **702** can be connected by an interconnect **701** (e.g., bus and system core logic). In addition, the microprocessor **703** can be coupled to cache memory **709**. In an embodiment, the interconnect **701** can connect the microprocessor(s) **703** and the memory **702** to input/output (I/O) device(s) **705** via I/O controller(s) **707**. I/O devices **705** can include a display device and/or peripheral devices, such as mice, keyboards, modems, network interfaces, printers, scanners, video cameras and other devices known in the art. In an embodiment, (e.g., when the data processing system is a server system) some of the I/O devices (**705**), such as printers, scanners, mice, and/or keyboards, can be optional.

In an embodiment, the interconnect **701** can include one or more buses connected to one another through various bridges, controllers and/or adapters. In one embodiment, the I/O controllers **707** can include a USB (Universal Serial Bus) adapter for controlling USB peripherals, and/or an IEEE-1394 bus adapter for controlling IEEE-1394 peripherals.

In an embodiment, the memory **702** can include one or more of: ROM (Read Only Memory), volatile RAM (Random Access Memory), and non-volatile memory, such as hard drive, flash memory, etc. Volatile RAM is typically implemented as dynamic RAM (DRAM) which requires power continually in order to refresh or maintain the data in the memory. Non-volatile memory is typically a magnetic hard drive, a magnetic optical drive, an optical drive (e.g., a DV D RAM), or other type of memory system which maintains data even after power is removed from the system. The non-volatile memory may also be a random access memory.

The non-volatile memory can be a local device coupled directly to the rest of the components in the data processing system. A non-volatile memory that is remote from the system, such as a network storage device coupled to the data processing system through a network interface such as a modem or Ethernet interface, can also be used.

In this description, some functions and operations are described as being performed by or caused by software code to simplify description. However, such expressions are also used to specify that the functions result from execution of the code/instructions by a processor, such as a microprocessor.

Alternatively, or in combination, the functions and operations as described here can be implemented using special purpose circuitry, with or without software instructions, such as using Application-Specific Integrated Circuit (ASIC) or Field-Programmable Gate Array (FPGA). Embodiments can be implemented using hardwired circuitry without software instructions, or in combination with software instructions. Thus, the techniques are limited neither to any specific combination of hardware circuitry and software, nor to any particular source for the instructions executed by the data processing system.

While one embodiment can be implemented in fully functioning computers and computer systems, various embodiments are capable of being distributed as a computing product in a variety of forms and are capable of being applied regardless of the particular type of machine or computer-readable media used to actually effect the distribution.

At least some aspects disclosed can be embodied, at least in part, in software. That is, the techniques may be carried out in a computer system or other data processing system in response to its processor, such as a microprocessor, executing sequences of instructions contained in a memory, such as ROM, volatile RAM, non-volatile memory, cache or a remote storage device.

Routines executed to implement the embodiments may be implemented as part of an operating system or a specific application, component, program, object, module or sequence of instructions referred to as "computer programs." The computer programs typically include one or more instructions set at various times in various memory and storage devices in a computer, and that, when read and executed by one or more processors in a computer, cause the computer to perform operations necessary to execute elements involving the various aspects.

Although specific embodiments have been described above, these embodiments are not intended to limit the scope of the present disclosure, even where only a single embodiment is described with respect to a particular feature. Examples of features provided in the disclosure are intended to be illustrative rather than restrictive unless stated otherwise. The above description is intended to cover such

alternatives, modifications, and equivalents as would be apparent to a person skilled in the art having the benefit of the present disclosure.

Methods and systems for one-time wireless authentication of an Internet-of-Things device has been disclosed. The present invention has been described in accordance with the embodiments shown, and there could be variations to the embodiments, and any variations would be within the spirit and scope of the present invention. Accordingly, many modifications may be made by one of ordinary skill in the art without departing from the spirit and scope of the appended claims.

We claim:

1. A computer-implemented method for enabling wireless connectivity through a router of a wireless network for an Internet-of-Things (IoT) device, comprising:

displaying to a user, by a proxy application executing on a mobile device, an option for the user to begin a one-time network authentication for the IoT device that lacks a user interface and is not yet configured to access the router;

responsive to the user accepting the option, initiating, by the proxy application, a registration process and receiving a device identifier associated with the IoT device entered into the proxy application by the user of the mobile device, wherein the device identifier comprises at least one of a serial number, a partial serial number, or a key, and wherein functionality of the proxy application is separated into an application pair including a first proxy application and a second proxy application, wherein the first proxy application or the second proxy application associates the device identifier with an application identifier used to identify the first proxy application or the second proxy application;

transmitting, by the proxy application, the device identifier to the router as part of the registration process, resulting in the router storing the device identifier in a credential management system and enabling a proxy authentication setting for the router;

subsequent to the registration process, receiving by the proxy application, the device identifier from the router in response to the router receiving an authorization request from the IoT device for a first-time access to the wireless network, the authorization request comprising the device identifier with no network password, and the router forwarding the device identifier to the proxy application after determining that the router has proxy authentication enabled based on the device identifier and the proxy authentication setting;

prompting, by the proxy application, the user of the mobile device to enter the network password, and transmitting the network password in a message to the router, such that in response the router validates the network password and grants the IoT device access to the wireless network; and

wherein responsive to the IoT device becoming disconnected from the first-time access to the wireless network, the IoT device resends the device identifier to the router for a second-time access to the wireless network, and wherein in response, the router looks up the device identifier in the credential management system, and if found reestablishes access to the wireless network for the IoT device without a need for another network authentication through the mobile device or the proxy application.

2. The computer-implemented method of claim 1, wherein the registration process further comprises: register-

ing, by the first proxy application, a mapping of the device identifier to the application identifier as an identifier pair with the router.

3. The computer-implemented method of claim 2, wherein the registration process further comprises: sending, by the first proxy application, the identifier pair to the router such that the router stores the identifier pair in a credential management system or forwards the identifier pair to an authentication mapper server.

4. The computer-implemented method of claim 2, wherein during the registration process, the identifier pair is registered with an authentication mapper server.

5. The computer-implemented method of claim 4, further comprising: configuring the authentication mapper server to communicate requests and responses for the first proxy application and the second proxy application.

6. The computer-implemented method of claim 5, further comprising: configuring the first proxy application to receive from the router the device identifier of the IoT device and determine if the IoT device has been enabled for proxy authentication by forwarding the device identifier to the authentication mapper server to validate the device identifier.

7. The computer-implemented method of claim 5, further comprising: configuring the second proxy application to prompt the user of the mobile device to enter the network password in response to receiving a validation message from the authentication mapper server, and transmit the network password in the message to the router through the authentication mapper server and the first proxy application.

8. The computer-implemented method of claim 7, further comprising:

registering a mapping between the first application identifier and the network password with a router mapper system; and

registering the second application identifier with an authentication mapper server.

9. The computer-implemented method of claim 1, further comprising: associating the first proxy application with a first application identifier and the second proxy application with a second application identifier, wherein the first application identifier and the second application identifier include a mobile phone number of the mobile device.

10. The computer-implemented method of claim 1, wherein receiving, by the proxy application, the device identifier associated with the IoT device further comprises: automatically determining, by the IoT device, which one of a plurality of detected wireless networks to request access to by selecting the wireless network having a highest signal strength.

11. A system for enabling wireless connectivity through a router of a wireless network, comprising:

the router;

an Internet-of-Things (IoT) device requiring first-time access to the wireless network, the IoT device lacking a user interface and is not yet configured to access the router, the IoT device associated with a device identifier; and

a proxy application executing on a mobile device of a user, the proxy application to act a proxy for the IoT device during a first network authentication attempt with the router, wherein functionality of the proxy application is separated into an application pair including a first proxy application and a second proxy application, the proxy application configured to:

display to a user an option for the user to begin a one-time network authentication for the IoT device;

15

responsive to the user accepting the option, initiate a registration process and receive during a registration process, the device identifier associated with the IoT device, the device identifier entered into the proxy application by the user of the mobile device, wherein the device identifier comprises at least one of a serial number, a partial serial number, or a key, and wherein the first proxy application or the second proxy application associates the device identifier with an application identifier used to identify the first proxy application or the second proxy application; transmit the device identifier to the router as part of the registration process, resulting in the router storing the device identifier in a credential management system and enabling a proxy authentication setting for the router;

subsequent to the registration process, receive by the proxy application, the device identifier from the router in response to the router receiving an authorization request from the IoT device for a first-time access to the wireless network, the authorization request comprising the device identifier with no network password, and the router forwarding the

16

device identifier to the proxy application after determining that the router has proxy authentication enabled based on the device identifier and the proxy authentication setting; and

prompt the user of the mobile device to enter the network password, and transmit the network password in a message to the router, such that in response the router validates the network password and grants the IoT device access to the wireless network; and wherein responsive to the IoT device becoming disconnected from the first-time access to the wireless network, the IoT device resends the device identifier to the router for a second-time access to the wireless network without a need for another network authentication through the mobile device or the proxy application.

12. The system of claim **11**, further comprising an authentication mapper server in communication with the router, and wherein the authentication mapper server stores a mapping between a first application identifier associated with the first proxy application, and a second application identifier associated with the second proxy application.

* * * * *