




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : C07C 51/48, 53/08, B01D 11/04, C12P 7/40	A1	(11) International Publication Number: WO 99/00352 (43) International Publication Date: 7 January 1999 (07.01.99)
(21) International Application Number: PCT/US98/12202		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).
(22) International Filing Date: 12 June 1998 (12.06.98)		
(30) Priority Data: 08/885,841 30 June 1997 (30.06.97) US		
(71) Applicant: THE TEXAS A & M UNIVERSITY SYSTEM [US/US]; 310 Wisenbaker, College Station, TX 77843-3122 (US).		
(72) Inventors: HOLTZAPPLE, Mark, T.; 1805 Southwood Drive, College Station, TX 77840 (US). DAVISON, Richard, R.; 303 Crescent, Bryan, TX 77801 (US). LUETTICH, Torsten; Reginenstrasse 41, D-45130 Essen (DE).		
(74) Agents: POSORSKE, Laurence, H. et al.; Baker & Botts, L.L.P., The Warner, 1299 Pennsylvania Avenue, N.W., Washington, DC 20004 (US).		

(54) Title: RECOVERY OF FERMENTATION SALTS FROM DILUTE AQUEOUS SOLUTIONS



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

RECOVERY OF FERMENTATION SALTS FROM DILUTE AQUEOUS SOLUTIONS

BACKGROUND OF THE INVENTION

5 **Field of the Invention**

This invention relates to a new and novel technology for isolating fermentation salts from aqueous solution. The method of this invention extracts water from the solution to concentrate fermentation salts, in particular, carboxylate salts such as calcium acetate.

10 **Review of Related Art**

Numerous manufacturing processes produce aqueous wastes or process streams containing carboxylic acid. These include the manufacture of cellulose acetate, aspirin, camphor, and RDX explosives, as well as semi-chemical wood pulping and other processes that use acetic acid as a raw material or solvent. In 15 addition, there are many manufacturing methods for acetic acid involving recovery of acetic acid from aqueous solution. For example, the principal methods to produce acetic acid are carboxylation of methanol, liquid-phase oxidation of hydrocarbons such as butane and oxidation of acetaldehyde. Earlier processes, such as alcohol fermentation and the destructive distillation of wood, 20 yielded dilute aqueous solutions. More recently, processes have been proposed to produce acetic acid, or other carboxylic acids, from biomass employing rumen microorganisms that produce dilute aqueous solutions. The concentration of acid in these processes must, of necessity, be dilute, because high acid concentrations inhibit microbial growth.

25 Several processes have been developed to recover acetic acid from aqueous solutions. These methods include liquid-liquid solvent extraction, azeotropic distillation, and extractive distillation. Simple distillation is not appropriate because (1) the relative volatility between water and acetic acid is close to unity and becomes worse for dilute aqueous acetic acid solutions, and 30 (2) water is the more volatile component, compared to acetic acid; this means all

the water has to be vaporized from dilute acetic acid solutions, leading to a large energy cost per unit of acetic acid recovered.

Extractive distillation was used for years in the *Suida* process to recover acetic acid from pyroligneous acid which contains 6-7% acetic acid.

5 Recycled wood oils were used as the extractant. In acetic acid synthesis plants, azeotropic distillation was used for higher concentration streams. Methyl and ethyl acetates, diisopropyl ether, and benzene are commonly used entrainers for azeotropic distillation, although other esters and ethers, ketones, chlorinated hydrocarbons and alcohols have also been used.

10 In specific applications of acetic acid manufacturing, other processes might be used. For example, freeze concentration has been used for years as a backyard process for concentrating vinegar. Adsorption with carbon or anion exchangers and chemical derivatization, followed by separation and regeneration of the chemical derivatives, are also available. A conventional derivatization

15 method is the calcium acetate process for recovering acetic acid from pyroligneous acid.

In the calcium acetate derivation process, calcium hydroxide reacts with the acid to form calcium acetate, which is concentrated by evaporation. Then a strong acid, such as sulfuric acid, is added to liberate the free acid. This

20 approach consumes chemicals such as lime and sulfuric acid and produces gypsum as a waste aqueous salt by-product.

Recovery of carboxylic acids from water is one of the oldest applications of solvent extraction. Solvent extraction of carboxylic acid was proposed a century ago. With the development of more sophisticated extraction

25 techniques, such as countercurrent extraction, recovery of residual solvent from the raffinate phase by distillation, and the use of azeotropic distillation to remove coextracted water from the recovered acid, solvent extraction of carboxylic acids from aqueous solutions has replaced the calcium acetate derivation process.

In general, extraction from aqueous solutions has heretofore been the

30 most favored approach to recover acetic acid, except for feeds (aqueous

solutions) above about 80% (w/w) acetic acid content, where azeotropic distillation is preferred. Based on the development of new extractants, extractive processes, and the change in the economic structure, extraction is now favored for feeds containing acetic acid below 30% (w/w); extractive distillation is 5 preferred for feeds in the 30-80% (w/w) range; and azeotropic distillation and simple fractionation (distillation) are appropriate for more concentrated feeds.

In the literature, solvent extraction has been the main theme for recovering carboxylic acid from dilute aqueous solutions. Because the solvents tend to be partially water soluble, a unit operation is required to remove or 10 recover residual solvent from the raffinate. Typical extraction processes recover carboxylic acid from water using three unit operations: the extractor, a solvent regenerator, and a process to recover free carboxylic acid. In a conventional extraction process, one first extracts acid into the organic phase, followed by back-extracting acid into an aqueous phase, thus regenerating the organic phase. 15 In the regeneration process, the aqueous phase used to back extract acid from the extract is usually an aqueous solution containing a low-boiling alkaline solvent (e.g. trimethylamine) which can be easily evaporated. Using this process, carboxylic acid can be separated and recovered.

Among the extractants used to recover carboxylic acid are reactive, 20 basic extractants (e.g. tertiary amines or phosphine oxides) that can be used to gain greater solvent capacity and selectivity with respect to water and carboxylic acid. Although solvent extraction is a potentially attractive process for carboxylic acid recovery, it is usually deterred by the high affinity of these acids for water. Previous workers have characterized some extractants that provide a 25 relatively high equilibrium distribution coefficient for extracting carboxylic acid from aqueous solution. A high equilibrium distribution coefficient allows the use of lower solvent-to-feed flow rates.

Primary amines are too soluble in water to be used with aqueous 30 solutions. Secondary amines are subject to amide formation upon regeneration by distillation. Consequently, long-chain tertiary amines have become the most

favored extractant for recovering carboxylic acid from dilute aqueous solutions. With the use of appropriate diluents and swings of temperature or pH, tertiary amine extractant systems have become more powerful agents for carboxylic acid recovery.

5 Desalination

Solvent extraction has also been proposed as a method to recover potable water from sea water or brackish water. Extracting sea water with an amine solvent produced a concentrated brine (raffinate) and an extract containing a mixture of water and amine. Clear water was recovered by heating the water-laden extract to a higher temperature at which the solubility of solvent in water was greatly reduced. Previous discussions concerning the solvent extraction of water have been published by Davison et al. (see Davison, et al., "Structure and Amine-Water Solubility in Desalination by Solvent Extraction," *J. Chem. Eng. Data* 1960, **5**, 420-423; Davison, et al., "Thermodynamic Cycles For Recovery of Water by Solvent Extraction," *I&EC Process Design and Development*, 1964, **3**, 399-404; Davison, et al., "Phase Equilibria of Desalination Solvents: Water-NaCl-Amines," *J. Chem. Eng. Data* 1966, **2**, 304-309; Davison, et al., "A Solvent Extraction Desalination Pilot Plant," *Desalination*, 1967, **3**, 17-26; Davison and Hood, U. S. Patent 3,088,909; and Davison and Hood, U. S. Patent 20 3,424,675.)

Carboxylic acids from biomass

There has been increasing interest in using anaerobic bacteria to produce organic acids from biomass. A dilute aqueous stream of carboxylic acid can be produced by fermenting lignocellulosic biomass. The concentration in the 25 fermentation broths is limited by the autotoxicity of the acid to acetogenic fermentation bacteria. It may be as high as 6% (w/w), but concentrations of 2-4% are more typical. Product inhibition can be reduced by continuously removing the acid.

Extractive fermentation has been proposed to remove the inhibiting acid 30 *in situ* and thus increase the bioreactor productivity. However, at the pH where

the microbes grow (about 6.8), only 1% is undissociated acid; the rest is salts that will not be extracted, especially by tertiary amines. Most extractants work efficiently only at acidic pH, yet acidogenic anaerobes generally have poor growth rates below pH 6. Thus, extractive fermentation is not viable to remove 5 acid product *in situ*.

Moreover, after solvent-extracting carboxylic acid from the aqueous fermentation broth using high-molecular-weight tertiary amines, the acid-amine complexes must be broken to recover the free acid and recycle the amine extractant, either by azeotropic distillation or back-titration. For recovering 10 carboxylic acid from dilute aqueous solutions, the extraction-regeneration process requires both acid addition to adjust the pH and an extra solvent-extraction process to regenerate the primary extractant. Furthermore, the tertiary amines extractant (or phosphine oxide extractant) must necessarily have a high molecular weight to make it immiscible in water. However, it is 15 impossible to make these extractant amines perfectly immiscible in water, so some extractant is always present in the aqueous phase. Because of their high molecular weight, these extractants are non-volatile and cannot be recovered by stripping in a distillation column. Therefore, additional extractants must be added to replace that which is lost, thus incurring additional expense.

20 Necessarily, when produced by fermentation, the acid product is primarily present as a carboxylate salt. The pH of an aqueous solution of carboxylic acids is ordinarily low because the acids dissociate releasing hydronium ions in aqueous solution. To sustain active fermentation, it is necessary to add a neutralizing agent (i.e., lime or limestone) that reacts with the 25 hydronium ion and maintains a pH near to neutrality where microbial activity is greatest. Near neutrality, only about 1% of the product is carboxylic acid; the remainder is present as the carboxylate salt. Therefore the traditional technologies for recovering carboxylic acids are not easily applied, and a need exists for developing of alternative technologies.

SUMMARY OF THE INVENTION

Recovery of carboxylic acid from fermentation broths with conventional solvent extraction is not economical, especially when ideal extractants (i.e. those that can extract carboxylate salt into the organic phase) are not available

5 currently. Therefore, the inventors have developed a new process to concentrate fermentation broths by removing water from dilute aqueous solutions of the carboxylate salt (typically the calcium salt) rather than the conventional approach of removing acid from water. This novel extraction removes water from the aqueous phase, but selectively retains salts in the aqueous phase. As water is

10 extracted into the organic phase, salts concentrate in the aqueous phase. The water can be recovered from the organic phase by raising the temperature which causes the water to phase out of the organic phase. This recovered water can be returned to the fermentor after stripping residual organic material. In the process of the invention, residual organics are also stripped out of the concentrated

15 product.

This invention relates to a new and novel technology for isolating carboxylate salts and/or acids from an aqueous solution. Because it is difficult to extract acid from near-neutral pH fermentation broth, this invention provides a method of extracting the water instead, thereby concentrating the organic acid

20 and salt solutions.

This invention further relates to the manufacture of carboxylic acid in which the improvement is to concentrate dilute aqueous carboxylate salt solutions (2-5%) produced via fermentation. In particular, this invention pertains to the manufacture of carboxylic acid wherein the salt of carboxylic acid,

25 manufactured by fermentation (i.e., by rumen microorganisms, by mixed-acid fermentation, or by pure-culture fermentation) is recovered from the aqueous solution and the extractant is conveniently and economically recycled to the extraction process. The carboxylate salts need not be monocarboxylates and may contain other functional groups, as for example, hydroxyl groups. The

30 carboxylate salts need not be derivatives of saturated hydrocarbons, but may

contain unsaturation. Typical carboxylate salts that can be manufactured by fermentation and recovered by the method of this invention include acetates, propionates, lactates, succinates, and the like.

5 BRIEF DESCRIPTION OF THE FIGURES

Figure 1 shows a schematic representation of a process (Process A) for concentrating fermentation salts.

Figure 2 shows a schematic representation of a mixer/decanter that employs periodic cleaning.

10 Figure 3 shows a schematic representation of a method for achieving uniform gentle mixing of amine and water.

Figure 4 shows two possible configurations for parallel plates used to settle amine and water.

15 Figure 5 shows a schematic representation of a mixer/decanter that employs continuous cleaning.

Figure 6 shows a simplified schematic of Process A which indicates the equipment that affects process energetics.

Figure 7 shows a simplified schematic of Process B which indicates the equipment that affects process energetics.

20 Figure 8 shows a simplified schematic of Process C which indicates the equipment that affects process energetics.

Figure 9 shows a simplified schematic of a modified version of Process C.

25 Figure 10 shows a simplified schematic of a modified version of Process B.

DETAILED DESCRIPTION OF THE INVENTION

This invention, in a preferred embodiment, is a process in which fermentation broth, which contains dilute carboxylate salt, is contacted with a low-molecular-weight secondary or tertiary amine which has a high affinity for 30 water and a low affinity for carboxylate salt. From previous work on

desalination (Davison et al., *Phase Equilibria of Desalination Solvents: Water-NaCl-Amines*. *J. Chem. Eng. Data*. 1966, 2, 304-309), two low-molecular-weight tertiary amines, i.e. triethylamine (TEA) and *N,N*-diethylmethylamine (DEMA), were chosen because of their superior capacity to selectively extract 5 water from aqueous salt solutions in the proper temperature ranges. The temperature of the water-laden amine is increased by about 20-30°C which causes the water to separate from the amine and form another phase. The carboxylate salt remains in the fermentation broth and becomes concentrated. Residual amines in aqueous phases are recovered by adding alkali (e.g., lime) to 10 raise the pH, thus making the amines volatile. The residual amines are then recovered by stripping them out in a distillation column.

In the past, extraction of water from a salt solution has been applied to the recovery of drinking water from salt water, i.e., sea water, brackish water, or the like. The present invention may be distinguished from this previous 15 application as follows:

1. In the fermentation, one can select the cation which accompanies the carboxylate. Divalent ions (i.e., calcium) are excluded from the amine extractant more fully than monovalent ions (i.e., sodium, ammonium). Thus, by choosing a divalent cation, the water can be more selectively removed from the salt solution.
- 20 2. In contrast, the cations in sea water or brackish water are dictated by nature and typically are monovalent cations. As a result, the water and salt are not separated efficiently.
- 25 3. In the present invention, the salt is the desired product, whereas in the previous process, the water was the desired product. The carboxylate salt is much more desirable and valuable than the water, giving the present process favorable economics. In contrast, amine extraction of water is not economically attractive.
- 30 4. In the drinking water process, the water product must be virtually free of salt to be acceptable for human consumption. This requires the use of a large rectification section in addition to the stripping section. These added

rectification stages incur additional expense. In contrast, the present invention can tolerate higher concentrations of salt in the water stream because the water is simply recycled to the fermentor. Therefore the rectification section can have many fewer stages or be eliminated altogether.

5 4. Complete amine recovery from all aqueous streams is critical for good economics; otherwise, the expense of replacing the lost amine is too great. The amine is recovered by stripping it from the aqueous stream in a distillation column. To ensure that the amine is present as volatile free amine as opposed to non-volatile amine salts, it is necessary to raise the pH by adding alkali. In our 10 invention, this is easily accomplished by adding lime to the aqueous streams. There is little expense associated with this because a neutralizing agent must be added to the fermentor anyway. Thus, there are synergies and efficiencies associated with coupling the amine with the fermentor. In contrast, addition of alkali to the drinking water process incurs significant expense not only for the 15 alkali, but also for its recovery; it is not acceptable for the alkali to remain in the drinking water product. Complete amine removal from drinking water is essential due to its potential health effects.

Carboxylate salts which can be manufactured by fermentation and concentrated by the method of this invention include salts of acetic acid, 20 propionic acid, lactic acid, succinic acid, and the like. This method is also applicable to dilute aqueous solutions of carboxylate salts produced by methods other than fermentation.

According to the present invention, the organic phase comprises an 25 organic secondary or tertiary amine. Preferred amines include low-molecular-weight alkyl secondary or tertiary amines or mixtures thereof. Preferred amines are amines of the formula R_3N , wherein R is methyl, ethyl, n-propyl, or isopropyl. Most preferred amines are triethyl amine, N, N-diethylmethyl amine, and mixtures of these two amines. The use of various ratios of the two amines provides an extraction system that possesses different lower critical 30 temperatures. By selecting the appropriate amine compositions, it is possible to

operate the extraction process at any proposed temperature from 10°C to 70°C. Within this temperature range are both mesophilic and thermophilic acid-forming bacteria which gives flexibility in developing an appropriate fermentation system.

The most favored carboxylic-acid-producing microorganisms that use
5 lignocellulosic biomass are: (i) *mesophilic* (40°C) mixed cultures obtained from either cattle rumen or anaerobic sewage digesters, and (ii) thermophilic (55°C) mixed cultures from anaerobic sewage digesters. Another promising thermophile is the cellulytic organism *Clostridium thermocellum* which produces both acetic acid and ethanol generally in roughly equal amounts. Suitable fermentation
10 processes are described in greater detail in U.S. application Ser. No. 08/885,896, filed June 30, 1997, entitled "Method for Conversion of Biomass to Chemicals and Fuels," filed concurrently herewith and incorporated herein by reference.

To avoid unnecessary heating or cooling of fermentation broths, the extraction is operated at or near the fermentation temperature, as for example at
15 or near 40°C or 55°C depending on the microorganisms.

When the aqueous phase contacts the low-molecular-weight amine, the pH rises forming calcium hydroxide. Because calcium hydroxide is fairly insoluble, some precipitates thus removing calcium ions from solution. These ions are replaced with amine ions to form amine-carboxylate complexes in the
20 aqueous phase. The formation of water-soluble amine carboxylate is handled by adding calcium hydroxide to the strippers so calcium can replace the amine as the amine volatilizes.

Typically, lignocellulosic biomass is fermented to yield a dilute solution of carboxylate salts from which water may be extracted using low miscibility, 25 organic extractants. Preferably these organic extractants are low-molecular-weight secondary or tertiary amines, e.g. triethylamine (TEA), di-isopropyl amine (DIA), and N,N-diethylmethylamine (DEMA). At 40°C-55°C, which corresponds to typical fermentation temperatures, these low-molecular-weight tertiary amines or mixtures thereof can extract large amounts of water from
30 dilute aqueous solutions containing carboxylate salts. Thus, dilute carboxylate

solutions can be concentrated by selectively removing water. At lower temperatures, the amine phase contains 20-35% water and negligible carboxylate salt. When the temperature is raised, water phases out of the amine, allowing the amine to be recycled and reused to extract additional water. In a typical 5 example, using this approach, about 82.5% of water can be removed from a 3% dilute solution using conventional multi-stage, countercurrent extraction, thus providing a 15% concentrated carboxylate salt solution.

A typical embodiment of this invention may be described by reference to Figure 1. Fermentation broth 5 is filtered in solids separator 7 (e.g. filter, 10 hydroclone, centrifuge, settler) to remove insoluble residues 8 (e.g. cells, unreacted biomass). The solid-free solution 9 is sent to mixer 10 where lime 12 is added to increase the pH to approximately 11.5. The high pH precipitates minerals and organics (e.g. proteins, carbohydrate polymers, etc.). The slurry 15 is sent to solids separator 20 (e.g. filter, hydroclone, centrifuge, settler) where 15 the precipitate 25 is removed by pump 27. Figure 1 shows the precipitate being returned to the fermentor. Alternatively, it could be processed further to separate the minerals, protein, and carbohydrate polymers depending upon the value of these components.

Using pump 32, precipitate-free liquid 30 is sent to a series of 20 mixer/decanters 40 where it will be contacted countercurrently with water-lean amine 34. (Although Figure 1 shows a series of mixer/decanters are used to countercurrently contact the amine and water phases, other contacting devices may be used, such as packed columns, rotating-disc columns, oscillating-plate columns, etc. The choice of the appropriate contactor depends upon scale; 25 mixer/decanters are preferred for large flow rates. Although Figure 1 shows five mixer/decanters, fewer or more may be used.) Precipitate-free liquid 30 is sent to mixer/decanter 40e where it is mixed with amine from mixer/decanter 40d. The amine absorbs some water from the water phase thus increasing its salt concentration.

As shown in Figure 2, the amine/water mixture flows through a series of parallel plates 140 in the mixer/decanter and enters a gathering section 145 where the amine phase and water phase separate. The amine phase, having a lower density, is recovered from the top, and the water phase is recovered from 5 the bottom. Weirs 150 are set to regulate the height of the amine/water interface. Amine flows over the top and water is recovered from the underflow.

In the embodiment shown in Figure 1, water-rich amine phase 65 is sent to separator 55 to recover the absorbed water. Water phase 69 is sent to mixer/decanter 40d where it is mixed with amine phase from mixer/decanter 40c 10 which absorbs additional water further concentrating the water phase. This process is repeated in the other mixer/decanters. As the water phase moves from right to left, its salt concentration increases. As the amine phase moves from left to right, its water content increases.

In each of the mixer/decanters, water and amine are mixed. Because 15 there is a particularly large heat of mixing released when water-lean amine 34 is mixed with water 61, mixing for mixer/decanter 40a is performed in a separate vessel 52 which is provided with cooler 50. Other mixer/decanters (40b through 40e) also have a heat of mixing, but it is much less and is removed by heat 20 exchangers 45 which regulate the temperature. Water pumps 46 cause the water to flow through the heat exchangers and on to the adjacent mixer/decanter 40. Pumps are required only for the water flow; by arranging the mixer/decanters 40 at successively declining elevations, the amine will flow by gravity eliminating the need for amine pumps.

Water stream 51, which has the highest salt content, has dissolved amine 25 which must be removed. It is preheated in countercurrent heat exchanger 58 and is sent to stripper 53 where steam 59 vaporizes the amine. To ensure that amine is present as the volatile unionized species, rather than a nonvolatile ionized species, lime 54 is added to raise the pH. The volatile amine exits in stream 60 which also contains steam. Stream 60 is directed to separator 55 where it

provides some of the latent heat needed to separate water and amine. Amine-free concentrated product **62** is ready for further downstream processing.

Pump **66** transports water-rich amine **65** to countercurrent heat exchanger **67** where the temperature is raised. In heat exchanger **67**, as the 5 temperature is raised, the water begins to phase out of the amine. This process is completed in separator **55** where additional heat, in the form of steam **77**, is supplied to raise the temperature and supply the latent heat necessary to separate the water from the amine. Separator **55** has a design similar to the mixer/decanters **40**, except that a mechanical mixer is not required.

10 Water phase **68** issuing from separator **55** contains dissolved amine. It is preheated in countercurrent heat exchanger **70** and sent to stripper **75** where steam **74** vaporizes the amine. To ensure that amine is present as the volatile unionized species, rather than a nonvolatile ionized species, lime **76** is added to raise the pH. The volatile amine exits in stream **78** which also contains steam. 15 Stream **78** is directed to separator **55** where it provides some of the latent heat needed to separate water and amine. Amine-free water **79**, which has a very low salt content, is cooled in countercurrent heat exchanger **70** and countercurrent heat exchanger **67** and is returned to the fermentor. If excess water must be purged from the system, a side stream of water can be removed from stream **79** 20 and sent to the waste water treatment plant for ultimate discharge. Water-lean amine **34** issuing from separator **55** is pumped through countercurrent heat exchanger **67** and mixes with water in mixer **52**.

Mixing and decanting are normally performed in separate pieces of equipment. Mixing is typically performed in a stirred tank, pump, or an in-line 25 static mixer. Decanting can be performed in a quiet tank or in a parallel plate separator. Parallel plate separators were first described by Hazen in 1904.

In a preferred embodiment, this invention provides a device that mixes raffinate and extract phases together and then decants them to achieve separation. It has been discovered that decanting occurs quickly in a horizontal

tube. In order to capitalize on this observation, this invention provides the device shown in Figure 2. Among the unique features of this embodiment are that it combines both a mixer and decanter into a single device. Figure 2 shows a detailed sideview of the mixer decanter 40. It is divided into four major 5 sections: mixing section 130, settling section 135, gathering section 145, and weir section 150.

In the mixing section 130, water 110 and amine 120 are evenly mixed together using impellor 115. Because equilibrium is quickly and easily reached, mixing can be very gentle; therefore, emulsions are not formed and the amine 10 phase quickly decants from the water phase. Even though the amine flowrate is about five or six times greater than the water flowrate, water is the continuous phase and amine is the discontinuous phase. This type of operation allows the amine residence time to be very short which reduces the amine inventory and lowers costs. Figure 2 shows an impellor providing the mixing. Figure 3 shows 15 an alternative embodiment using a series of "fingers" 230 mounted on a shaft 220 which is held in place using bearings 240. The shafts are driven by motor 200 which rotates gears 210. Adjacent shafts rotate in opposite directions. The fingers on adjacent shafts are interspersed allowing uniform mixing to occur in mixing section 130. The degree of mixing is determined by the rotational speed 20 and the number of fingers per shaft. To promote even mixing, water and amine may be introduced at multiple points in the mixing section 130.

As shown in Figure 2, the settling section 135 consists of a series of parallel plates 140. The parallel plates have a short settling distance allowing the dispersed phases from the mixing section 130 to quickly coalesce. The short 25 amine residence time in settling section 135 reduces the amine inventory which saves capital costs. Figure 4 shows two possible embodiments of parallel plates. Both Figures 4a and 4b use rippled plates, much like those used as siding on buildings. The two versions differ only in the orientation of the parallel plates 140. In Figure 4a, every other plate is in the same orientation and in Figure 4b,

every plate is in the same orientation. The plate orientation shown in Figure 4b is preferred because it allows for very close plate spacing even if there are deep ripples. Close plate spacing ensures the flow is laminar, rather than turbulent, which promotes coalescence. As the amine/water phases flow between the 5 parallel plates, each phase coalesces; the amine phase (being less dense) floats to the highest point and the water phase (being more dense) sinks to the lowest point.

Figure 2 shows that gathering section **145** is simply a quiescent tank. The gathering section **145** is operated with water as the continuous phase and 10 amine as the dispersed phase. As coalesced amine exits from settling section **135**, it quickly floats to the top. To reduce interference with adjacent amine as it flows to the top, parallel plates **140** are successively longer lower in the settling section **135**. Solids, such as precipitated calcium hydroxide, settle in the gathering section and are removed by pump **190** and sent to solids separator **191** 15 (e.g. filter, hydroclone, centrifuge). The solids are returned to strippers **75** or **53** to provide the lime necessary to volatilize amine.

Figure 2 shows that weir section **150** consists of overflow weir **132** and underflow weir **131**. Overflow weir **132** sets the height of the upper surface of the amine and underflow weir **131** sets the height of the amine/water interface. 20 Amine phase flows over overflow weir **132** and water phase flows over underflow weir **131**. To reduce the amine residence time (and hence reduce the amine inventory), the underflow weir **131** is adjusted to minimize the thickness of the top amine layer.

A "rag layer" may collect at the amine/water interface, so pump **180** is 25 included to draw fluid from the amine/water interface and direct it to solids separator **181** (e.g. filter, hydroclone, centrifuge). Amine **182** is returned to gathering section **145**. Using steam **188**, separated solids **183** would be stripped of amine in chamber **189**. Exiting vapors **187** are sent to separator **55** to provide energy needed to phase separate water from amine. Depending upon the nature

of separated steam-stripped solids 184, they may be returned to the fermentor, or they may be disposed of in an appropriate manner.

Because the flow through parallel plates 140 is low, solids (such as precipitated calcium hydroxide) eventually may plug settling section 135. To 5 clean parallel plates 140, amine flow 120 would be discontinued. Valve 126 would be opened allowing water from elevated holding tank 125 to quickly flow by gravity through parallel plates 140 causing turbulent flow that entrains any solids that settled in the parallel plates. Entrained solids 194 are collected in gathering section 145 or surge tank 195. After the cleaning operation is 10 performed, amine flow 120 resumes and mixer/decanter 40 continues as before. During normal operation of mixer/decanter 40, pump 185 slowly returns water to elevated tank 125 in preparation for the next cleaning cycle.

In Figure 2, tanks 125 and 195, used to clean the parallel plates 140, must be large in order to develop the turbulent flow required to entrain solids. 15 Figure 5 shows an alternate embodiment in which parallel plates 140-5 are continuously cleaned where, advantageously, the cleaning equipment is considerably smaller. Louvers 320-5 may be opened or closed. When closed, a section of parallel plates 140-5 is isolated allowing it to be cleaned while the remainder of the parallel plates may perform their usual function. As shown in 20 Figure 5, louvers 320-5a and 320-5c are open allowing the upper and lower sections of parallel plates 140-5 to perform their usual function; however, louver 320-5b is closed, allowing the middle section of parallel plates 140-5 to be cleaned. As shown from View Z, valve 310-5b is opened whereas other valves 310-5a and 310-5c are closed. This valve arrangement allows high velocity 25 water, obtained from pump 185-5, to entrain solids in the middle section of parallel plates 140-5 and discharge the solids to gathering section 145-5 where they settle and are collected by pump 190-5.

Compared to other technologies, the mixer/decanter described in Figures 2 to 5 provides numerous advantages. Compared to separate mixers and

decanters, less piping is required. The degree of mixing is regulated by the agitation rate, and unlike the use of a pump as a mixer, very gentle mixing can be achieved. Furthermore, the degree of mixing is independent of the addition rate of amine and water giving greater control than an in-line static mixer. By

5 incorporating flow between parallel plates 140, the phases separate much more quickly than in a quiet tank. To facilitate complete separation of water/amine, the water residence time can be lengthened by increasing the volume of gathering section 145. In contrast, the amine residence time can be short by adjusting the height of weir 131 so that the amine layer is very thin.

10 Heat transfer is an important factor in optimizing this process. One preferred method for heating and cooling the amine-containing streams employs countercurrent heat exchangers 67. Plate-and-frame heat exchangers are generally preferred for low capital cost relative to heat transfer (heat transfer coefficients of 625 Btu/(ft²•h•°F) can be achieved). Additional energy savings

15 may be achieved by using very close approach temperatures in the hot and cold streams. For example, adding surface area to go from log-mean deltaT (LMDT) of 6.5 °C to 4.1 °C generates energy savings which more than pay for the increase in capital expense.

Using countercurrent heat exchanger 67 in the amine-dewatering
20 process, only sensible heat is required on the water-lean side, but the water-rich side has both sensible and latent heat requirements. As the water-rich side warms, the water phases out of the amine, and the latent heat requirement effectively raises the heat capacity. As a consequence, the temperature difference could be, e.g., only 1 °C on one end of the heat exchanger, but 10.9 °C
25 at the other end.

The process described in Figure 1 may be considered a "base case" which has the lowest capital cost, but also the lowest energy efficiency. Other process alternatives that have a higher energy efficiency are described in Table 1.

Table 1. Energy Costs

Process	Description	*Steam Cost (\$/lb HAc)
A	Base Case	0.010
B	Single-stage vapor-compression heat pump	0.0047
C	Multiple-stage steam ejector heat pump	0.0037
* steam cost = \$3/million Btu acetic acid concentration = 22 g HAc/L total acid concentration = 30 to 35 g/L		

Process A is a "base-case" that has minimal capital cost, but is not energy efficient (see Figure 1). Process B is more efficient because it employs a vapor-compression heat pump to transfer the heat of mixing (released at the absorption temperature, e.g. 40°C) to the separator (which operates at a higher temperature, e.g. 60°C). Unfortunately, because the density of the vapor is so low, very large compressors are required, incurring capital expense which may be prohibitive. Process C reduces the capital cost of heat pumps by employing low-cost steam ejectors rather than mechanical compressors. The steam is supplied from the strippers. Because steam ejectors are inefficient at high compression ratios, multiple-stage ejectors are employed allowing many of the stages to have a very low compression ratio. The multiple stages employed in Process C allow it to have the lowest energy cost. Because ejectors are very inexpensive, the capital cost of Process C is only slightly above Process A.

Figure 6 is a simplified version of Process A which shows the equipment that affects the process energetics. For simplicity, only two extraction stages are shown. Separator 55-6 is the major consumer of energy. It requires two forms of energy: (1) latent heat needed to phase water out of the amine, and (2) sensible heat needed to raise the temperature of the water-rich amine from the extraction temperature (e.g. 40°C) to the separation temperature (e.g. 60°C). By making countercurrent heat exchanger 67-6 sufficiently large, the sensible

heat demands by separator 55-6 are minimized. The latent heat demands are mostly met by the overhead vapors from strippers 53-6 and 75-6. Some additional energy can be provided by steam 77-6 which may result from other unit operations in the plant, such as multiple-effect evaporators or distillation

5 column condensers. Provided countercurrent heat exchanger 67-6 is sufficiently large, water-lean amine 34-6 will be cooled to approximately the extraction temperature (e.g. 40°C). Cooler 50-6 is required to remove the heat of mixing resulting from mixing water-lean amine 34-6 and water 61-6. Ideally, given an infinitely large countercurrent heat exchanger 67-6, the heat added to separator

10 55-6 is removed using cooler 50-6. In actuality, given a countercurrent heat exchanger 67-6 of finite size, some additional heat must be added to separator 50-6 to provide sensible heat. Similarly, some additional cooling must be provided by cooler 50-6 to remove sensible heat.

Figure 7 shows Process B, again emphasizing only that equipment which

15 affects process energetics. In this case, rather than rejecting the heat of mixing to cooler 50-6, a vacuum is pulled on mixer 52-7 by compressor 300-7 which causes some amine and water to evaporate cooling the liquid to the extraction temperature (e.g. 40°C). The compressed vapors 315-7 are sent to separator 55-7 which operates at its vapor pressure. Compressed vapors 315-7 condense

20 in separator 55-7 and provide the heat required to phase the water out of the amine. Compressor 300-7 is driven by steam turbine 310-7 which is fed with high-pressure steam 320-7 and rejects low-pressure steam 325-7. The low-pressure steam is sent to amine strippers 75-7.

Because Process B is more energy efficient than Process A, a single

25 stripper would generate more vapors than are need by separator 55-7. Therefore, the stripping operation is performed in multiple effects. Stripper 75-7a is operated at a higher temperature and pressure than stripper 75-7b which, in turn, is operated at a higher temperature and pressure than stripper 75-7c. Figure 7 shows three strippers, but fewer or more could be used depending upon

the cost of capital and the cost of energy. Also, stripper 53-7 could be operated in multiple effects, but it is much smaller and has less impact on process energetics. Low-pressure steam 325-7 from turbine 310-7 is sent to stripper 75-7a which operates at the highest temperature and pressure. Overhead vapors 5 330-7a from stripper 75-7a are sent to the reboiler of stripper 75-7b. Similarly, the overhead vapors 330-7b from stripper 75-7b are sent to the reboiler of stripper 75-7c. The overhead vapors 330-7c are sent directly to the separator 55-7 as is the overhead condensate 340-7. The amine-stripped water 79-7 is cooled countercurrently and is returned to the fermentor.

10 Because the vapor density of amine/water is very low at an extraction temperature of 40°C, the compressor 300-7 must be very large leading to very high capital costs. This problem could be overcome by the following approaches:

- 1) A secondary refrigerant (e.g. ammonia, Freon) could be 15 compressed rather than the amine/water vapors. This approach requires heat exchangers both in the separator 55-7 and mixing vessel 52-7 which adds cost and irreversibilities that negatively impact energy efficiency.
- 2) Precipitate-free fermentation broth 30-7 could be heated to a higher temperature so the extraction occurs at a higher temperature and the 20 amine/water in mixing vessel 52-7 has a higher vapor density. This approach requires an extra countercurrent heat exchanger to prewarm fermentation broth going to the extractor and precool liquid returning to the fermentor. Also, because there is an approach temperature needed in the countercurrent heat exchanger, extra heat will be needed to fully increase the temperature of the 25 fermentation broth going to the extractor, and extra cooling will be needed to cool the water returning to the fermentors.
- 3) The fermentation could be operated at thermophilic conditions (e.g. 55°C) so the extractors operate at a higher temperature resulting in a higher vapor density in mixer 52-7.

4) A highly volatile component (e.g. butane, fluorocarbon) could be added to the water-lean amine 34-7. This volatile component would raise the vapor density in mixer 52-7 allowing a more compact compressor to be employed. The highly volatile component would evaporate in mixer 52-7 and 5 would condense in separator 55-7, so it would mostly circulate. Although some of this volatile component will be in stream 350-7 and will enter the extractors, any volatile component in the amine phase will be recycled, and any volatile component in the water phase will be removed by the strippers; therefore, very little of this volatile component will be lost.

10 Figure 8 shows Process C which uses multiple-stage steam ejectors as heat pumps. High-pressure steam 74-8 (e.g. 180 psig) is put into stripper 75-8a which is the first in a series of multiple-stage strippers. The vapors 330-8c exiting stripper 75-8c are at a high enough pressure (e.g. 100 psig) to provide motive force to the steam ejectors 400-8 which pull a vacuum on mixer 52-8. 15 The vacuum evaporates amine and water from mixer 52-8 which are then compressed and condensed in contactors 410-8 causing water-rich amine 65-8 to increase in temperature. As the temperature rises, water begins to phase out of the water-rich amine, a process that is completed in separator 55-8. Because steam ejectors are inefficient at high compression ratios, the steam ejectors are 20 staged. Steam ejector 400-8a has the lowest compression ratio because the pressure in contactor 410-8a is low. Steam ejector 400-8c has the highest compression ratio because the pressure in separator 55-8 is relatively high. Although Figure 8 shows three heat pump stages, fewer or more may be used.

Figure 9 shows a variation on Process C in which the ejectors 400-9 pull 25 a vacuum on mixers 52-9 in multiple stages. Aqueous solution 61-9 is added to water-lean amine 34-9 in mixer 52-9c. Due to the heat of mixing, the temperature rises in mixer 52-9c, raising its vapor pressure. Using ejector 400-9c, vapors are removed from mixer 52-9c and compressed into separator 55-9. The liquid exiting mixer 52-9c is reduced in pressure and added to mixer 52-9b

where vapors are removed using ejector 400-9b and added to contactor 410-9b.

A similar process occurs in mixer 52-9a. The advantage of this multi-stage flashing process is that the compression ratio of each ejector 400-9 is reduced, resulting in steam savings.

5 The energy benefits of a multiple-stage heat pump can also be realized by using multiple-stage mechanical compressors instead of the steam ejectors (see Figure 10). To raise the vapor density, a volatile component (e.g. butane, fluorocarbon, etc.) can be added directly to the water-lean amine. The volatile component would circulate between multiple-stage mixers 52-10 and the
10 separator 55-10 such that very little of the volatile component would be present in the extractors 40-10. In the case of a hydrocarbon volatile component (e.g. butane), it will distribute primarily in the amine phase, helping to push water out in the separator 55-10. In the case of some fluorocarbons, they are substantially immiscible in both water and amine. They have a density higher than water, so
15 they would be drawn off the bottom of the gathering section of separator 55-10 and added directly to mixer 52-10c.

An important consequence of Process C is that it allows recovery of dilute acids without paying a large capital or energy penalty. The liquid residence time in the fermentor is largely determined by the product
20 concentration; lower product concentrations have a short residence time because product inhibition is less. The fermentor volume decreases with shorter liquid residence time; thus, for lower product concentrations, the fermentor can be smaller.

The energy estimates shown in Table 1 were calculated using a
25 simplifying assumption that the amount of water that phases out of the amine increases linearly with temperature. In actuality, for a single degree increase in temperature, more water phases out at low temperatures than at high temperatures. As a consequence, more of the heat pump energy will be needed at low temperatures where the compression ratio is smaller and less steam is

needed; therefore, the simplifying linear assumption will give a worst-case analysis. The real situation will require less energy than these projections.

The unique separation technique described in this invention provides a commercially viable method for separating and concentrating carboxylate salts 5 formed during fermentation with recycle of all streams and minimal waste.

Concentrated solutions of carboxylate salts obtained by the method of this invention may be further concentrated by evaporation, dried or converted to concentrated carboxylic acid solutions as will be readily apparent to those skilled in the art. Suitable processes for further converting of the concentrated 10 carboxylic acid salt solution of this invention into the desired product are described in U.S. Serial No. 08/885,896, filed June 30, 1997, entitled "Method for Conversion of Biomass to Chemicals and Fuels", filed concurrently herewith and incorporated herein by reference in its entirety.

We claim:

1. A process for the manufacture of carboxylic acid wherein
 - (1) lignocellulosic biomass is fermented to a carboxylate salt in the presence of an aqueous solution of calcium cations,
 - 5 (2) water is extracted from the carboxylate salts by contacting the aqueous solution with an organic extractant of the class consisting of low-molecular weight secondary or tertiary amine, to form a water/extractant mixture and a more concentrated solution of the carboxylate salt, and
 - (3) carboxylic acid is freed from the salt and purified.
- 10 2. The process of claim 1, where the low-molecular-weight secondary or tertiary amine is an amine of the formula R_3N , wherein R is hydrogen, methyl, ethyl, n-propyl, or isopropyl, or a mixture of such amines.
3. The process of claim 1, wherein the amine is triethylamine, N,N-diethylmethylamine, or a mixture thereof.
- 15 4. The process of claim 1, wherein the water is extracted at about the temperature of the fermentation.
5. The process of claim 1, wherein the organic extractant is recycled by heating the water/extractant mixture at a temperature sufficient to separate water therefrom, separating the water from the extractant, and recycling the extractant.
- 20 6. The process of claim 5, wherein the extractant is recycled to the extraction.
7. The process of claim 5, wherein the heating is performed in a heat exchanger.
8. The process of claim 7, wherein the heating is performed in the heat 25 exchanger by the presence of heated extractant therewithin.
9. The process of claim 1, wherein lime is added to the more concentrated solution of salt and the solution is stripped of dissolved extractant.
10. The process of claim 5, wherein the water separated from the extractant is further stripped to remove extractant.

11. The process of claim 10, wherein the water is treated with lime during the stripping process.

12. The process of claim 10, wherein the water is recycled to the fermentation process.

5 13. A process for the manufacture of a carboxylic acid wherein

(a) lignocellulosic biomass is fermented to carboxylate salts in the presence of an aqueous solution of calcium cations,

(b) water is extracted from the carboxylate salts by contacting the aqueous carboxylate salts solution with an organic extractant of the class

10 consisting of triethylamine, N,N-diethylmethylamine, and mixtures thereof, at about the temperature of the fermentation,

(c) the organic extractant is recycled by heating the water/extractant mixture in a heat exchanger to a temperature sufficient to separate water therefrom, separating the water from the extractant in a separator, and recycling

15 the extractant to the extraction,

(d) the aqueous carboxylate salts solution from step (b) is treated with lime and stripped to remove dissolved extractant from the carboxylate salts solution,

20 (e) the water from step (c) is treated with lime and stripped to remove extractant which is recycled to the separator and the water is recycled to the fermentation,

(f) the carboxylate salts solution is acidified and carboxylic acid is purified therefrom.

14. An extraction tank comprising

25 a mixing section adapted for mixing a first fluid input stream and a second fluid input stream;

a separating section comprising a plurality of plates parallel to each other and in substantially horizontal orientation; and

30 a gathering section adapted for collecting an upper fluid layer and a lower aqueous fluid layer, having two weirs, a first weir being in fluid communication

with the upper fluid layer and a second weir in fluid communication with the lower layer, the two weirs being in fluid communication with a first collection structure and a second collection structure, respectively;

5 wherein one end of the parallel plates of the separating section is in fluid communication with the mixing section and an other end of the parallel plates is in fluid communication with the gathering section.

15. The extraction tank of claim 14, wherein the parallel plates are rippled sheets.

16. The extraction tank of claim 14, wherein the end of the plurality of 10 plates in fluid communication with the gathering section slopes such that a lower plate extends further into the gathering section than the immediately higher plate.

17. The extraction tank of claim 14, wherein the gathering section further includes a well to collect settled solids and facilitate their removal.

15 18. The extraction tank of claim 14, where a pump removes material from the interface of the two fluids in the gathering section, whereby accumulated solids are removed.

19. The extraction tank of claim 14, wherein the mixing section contains a plurality of rotating shafts having projections, projections of respective shafts 20 being interspersed such that even, gentle mixing is obtained.

20. The extraction tank of claim 14, further comprising means for introducing a large flowrate of aqueous layer to the plurality of parallel plates whereby settled solids are flushed therefrom, and means for collecting the aqueous layer, wherein the solids settle for removal.

25 21. The extraction tank of claim 14, in which sections of the plurality of parallel plates can be cleaned of settled solids by isolating said sections and introducing a large flowrate of aqueous layer, collecting the aqueous flow in the gathering section, and recovering settled solids from the gathering section.

30 22. A method of extracting a solute component from a first fluid containing said solute component into a second fluid, wherein said first fluid and

said second fluid are immiscible and have different densities, said method comprising feeding said first and second fluids into the extraction tank of claim 14 and collecting the respective fluids from the first and second collection structures.

5 23. A process for concentrating an aqueous solution containing a carboxylate salt comprising

contacting the aqueous solution with an organic extractant of the class consisting of low-molecular-weight secondary or tertiary amine, to form a water/extractant mixture and a more concentrated solution of the carboxylate

10 salt; and

separating the water/extractant mixture from the more concentrated solution of the carboxylate salt.

24. A process for concentrating dilute fermentation salts comprising

(a) contacting fermentation broth with organic extractant of the class

15 consisting of low-molecular-weight secondary or tertiary amines, to form

water/extractant mixture and a more concentrated solution of the fermentation salts;

(b) heating the water/extractant mixture whereby water phases out of the extractant;

20 (c) stripping the water from step (b) to remove dissolved extractant,

(d) stripping the concentrated solution of fermentation salts from step (a) to remove dissolved extractant; and

(e) recycling the extractant from step (b) to extract additional water from fermentation broth.

25 25. The process of claim 24, wherein the fermentation broth is first

treated with alkali to increase the pH, thereby precipitating metal salts and dissolved organics.

26. The process of claim 25, wherein the alkali is lime.

27. The process of claim 24, wherein the low-molecular-weight secondary or tertiary amine is an amine of the formula R_3N wherein R is hydrogen, methyl, ethyl, n-propyl or isopropyl, or a mixture of such amines.
28. The process of claim 24, wherein the amine is triethylamine, N,N-5 diethylmethylamine, or a mixture thereof.
29. The process of claim 24, wherein the water/extractant mixture of step (b) is heated by condensing vapors from the strippers of steps (c) and (d).
30. The process of claim 24, wherein the water/extractant mixture of step (b) is heated by condensing water/amine vapors exiting a mechanical 10 compressor which applies suction to the contactors in which fermentation broth and organic extractant of step (a) are contacted.
31. The process of claim 30, wherein the organic extractant contains a volatile component which increases the vapor density at the suction to the compressor.
- 15 32. The process of claim 31, wherein the volatile component is a hydrocarbon or a fluorocarbon.
33. The process of claim 30, wherein the fermentation broth is preheated by a countercurrent heat exchanger, thereby raising the extraction temperature and increasing the vapor density at the suction to the compressor.
- 20 34. The process of claim 30, wherein the mechanical compressor is powered by a steam turbine, and further wherein exhaust steam from the turbine is added to the strippers of steps (c) and (d).
35. The process of claim 30, wherein the strippers of steps (c) and (d) are multiple-effect strippers, and further wherein the overhead vapors from the 25 stripper operating at the highest pressure is sent to the reboiler of the stripper operating at the next lower pressure.
36. The process of claim 30, wherein the mechanical compressor is staged and further wherein vapors from intermediate stages are added stage-wise to the water/extractant mixture of step (b).

37. The process of claim 24, wherein the water/extractant mixture of step (b) is heated by condensing water/amine vapors exiting a steam ejector which applies suction to the contactors of step (a).

5 38. The process of claim 37, further wherein the steam ejector is powered by high-pressure exhaust steam from the strippers of steps (c) and (d).

39. The process of claim 38, wherein which the strippers of steps (c) and (d) are multiple-effect strippers, and further wherein the overhead vapors from the stripper operating at the highest pressure are sent to the reboiler of the stripper operating at the next lower pressure.

10 40. The process of claim 37, wherein the steam ejector is staged, and further wherein vapors from intermediate stages are added stage-wise to the water/extractant mixture of step (b).

41. The process of claim 24, wherein lime is added to the strippers described in steps (c) and (d).

15 42. The process of claim 24, wherein which the fermentation broth contains carboxylate salt.

43. The process of claim 42, wherein the carboxylate salt is a calcium salt.

20 44. The process of claim 24, wherein the fermentation broth consists of a carboxylate salt produced by fermenting lignocellulosic biomass.

45. The process of claim 44, wherein the fermentation broth is a calcium carboxylate produced by fermenting lignocellulosic biomass.

25 46. The process of claim 44, wherein the lignocellulosic biomass is fermented to a carboxylate salt by a mixed culture of acid-forming microorganisms.

47. The process of claim 46, wherein a calcium carboxylate salt is produced using a mixed culture of acid-forming microorganisms.

30 48. The process of claim 24, further comprising the steps of condensing a secondary refrigerant in heat-exchange contact with the water/extract mixture of step (b),


evaporating said secondary refrigerant in heat-exchange contact with a contactor in which fermentation broth and organic extractant are contacted, and compressing said secondary refrigerant using a mechanical compressor to apply suction to said evaporating secondary refrigerant and to apply pressure to 5 said condensing secondary refrigerant.

49. The process of claim 48, wherein the secondary refrigerant is ammonia or Freon.

50. The process of claim 48, wherein the mechanical compressor is powered by a steam, turbine and further wherein the exhaust steam from the 10 turbine is added to the strippers of steps (c) and (d).

51. The process of claim 46, wherein the strippers of steps (c) and (d) are multiple-effect strippers, and further wherein the overhead vapors from the stripper operating at the highest pressure are sent to the reboiler of the stripper operating at the next lower pressure.

15 52. The process of claim 48, wherein the mechanical compressor is staged, and further wherein compressed vapors of secondary refrigerant from intermediate stages are in stage-wise, heat-exchange contact with the water/extractant mixture of step (b).



1




FIG. 2






FIG. 3

4/10

FIG. 4A

View X

FIG 4B

View X

5/10




FIG. 5






FIG. 6

7/10




8
FIG.




9/10

9
FIG.



10/10

FIG. 10



INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 98/12202

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 6 C07C51/48 C07C53/08 B01D11/04 C12P7/40

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
 IPC 6 C07C B01D C02F C12P

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category ^o	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DAVISON ET AL: "Phase equilibria of desalination solvents: water-NaCl-amines" JOURNAL OF CHEMICAL AND ENGINEERING DATA, vol. 2, 1966, pages 304-309, XP002082531 cited in the application see page 304, left-hand column, paragraph 1 see tables I,II see page 309, left-hand column	23
A	see page 304, left-hand column, paragraph 1 see tables I,II see page 309, left-hand column	1,13,24
A	EP 0 112 926 A (DAICEL CHEM) 11 July 1984 see page 7, line 13 - page 8, line 22 see example 1 see claim 1	1,13,14, 22-24
	---	-/-



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

^o Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

29 October 1998

Date of mailing of the international search report

11/11/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Held, P

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 98/12202

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 635 474 A (GLITSCH INC.) 25 January 1995 see column 4, line 42 - column 5, line 29 see claims 1-4 ----	1,13,23, 24
A	US 3 088 909 A (DAVISON ET AL) 7 May 1963 cited in the application see column 1, line 14 - line 18 see column 3, line 9 - line 51 see table 1 see claims 1,2,9,10 ----	1,13,24
A	EP 0 113 378 A (DAICEL CHEM) 18 July 1984 see page 1, line 4 - line 10 see page 12, line 4 - line 21 see page 14; example 1 see claim 1 ----	1,13,14, 22-24
A	US 5 050 997 A (SKLOKIN LEONID I ET AL) 24 September 1991 see column 1, line 7 - line 13 see column 2, line 19 - column 3, line 17 see claim 1 ----	14,22
A	US 4 235 602 A (MEYER MAURICE ET AL) 25 November 1980 see column 2, line 8 - line 9 see column 2, line 64 - column 3, line 21 see claim 1 see figure 1 -----	14,22

INTERNATIONAL SEARCH REPORT

Information on patent family members

Int'l Application No

PCT/US 98/12202

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
EP 0112926	A 11-07-1984	JP 1356645 C JP 59007131 A JP 61021616 B WO 8400364 A US 4883912 A		13-01-1987 14-01-1984 28-05-1986 02-02-1984 28-11-1989
EP 0635474	A 25-01-1995	US 5409579 A AU 673067 B AU 6349694 A BR 9402672 A CA 2124433 A CN 1103859 A JP 2587790 B JP 7053443 A US 5492603 A		25-04-1995 24-10-1996 19-01-1995 02-05-1995 13-01-1995 21-06-1995 05-03-1997 28-02-1995 20-02-1996
US 3088909	A 07-05-1963	NONE		
EP 0113378	A 18-07-1984	JP 1418645 C JP 59012706 A JP 62024413 B WO 8400310 A US 4562288 A		22-12-1987 23-01-1984 28-05-1987 02-02-1984 31-12-1985
US 5050997	A 24-09-1991	WO 8905684 A EP 0355159 A FI 893879 A, B		29-06-1989 28-02-1990 17-08-1989
US 4235602	A 25-11-1980	FR 2343905 A FR 2352573 A BE 852308 A CA 1106577 A DE 2710241 A GB 1576353 A NL 7702683 A, B, BR 7701496 A		07-10-1977 23-12-1977 12-09-1977 11-08-1981 22-09-1977 08-10-1980 13-09-1977 03-01-1978