



US 20070119901A1

(19) **United States**(12) **Patent Application Publication**  
**Ehrenfels et al.**(10) **Pub. No.: US 2007/0119901 A1**(43) **Pub. Date: May 31, 2007**(54) **SURGICAL FASTENER APPLYING  
APPARATUS**(60) Provisional application No. 60/240,461, filed on Oct.  
13, 2000.(75) Inventors: **Karl H. Ehrenfels**, Cheshire, CT (US);  
**David Ivanko**, Fairfield, CT (US);  
**Randolph F. Lehn**, Stratford, CT (US);  
**Roberto Pedros**, Seymour, CT (US);  
**Casaba L. Rethy**, Fairfield, CT (US);  
**Frank J. Viola**, Sandy Hook, CT (US)**Publication Classification**(51) **Int. Cl.**  
**A61B 17/04** (2006.01)  
(52) **U.S. Cl.** ..... **227/176.1; 227/19**(57) **ABSTRACT**


An improved surgical fastener applying apparatus includes a cartridge half-section and an anvil half-section with the cartridge and anvil half-sections being relatively movable from an unclamped position to a fully clamped position. The apparatus includes a replaceable staple cartridge assembly having a plurality of surgical staples and a pivotably mounted safety lock-out. The safety lock-out is pivotable between an initial position in which a relative movement of the cartridge and anvil half-sections to the fully clamped position is permitted and a blocking position in which a relative movement of the cartridge and anvil half-sections to return them to their fully clamped position after the plurality of staples have been at least partially fired is prevented. The apparatus further includes a pivotably mounted firing lever for moving a pair of camming surfaces longitudinally. In addition, each of the presently disclosed cartridge and anvil half-sections of the fastener applying apparatus includes a clamping lever, which clamping levers are configured and adapted to enable the applying apparatus to be opened by either one of the cartridge half-section and the anvil half-section.

Correspondence Address:

**UNITED STATES SURGICAL,  
A DIVISION OF TYCO HEALTHCARE  
GROUP LP  
195 MCDERMOTT ROAD  
NORTH HAVEN, CT 06473 (US)**

(73) Assignee: **Tyco Healthcare Group LP**(21) Appl. No.: **11/699,699**(22) Filed: **Jan. 29, 2007****Related U.S. Application Data**

(60) Continuation of application No. 11/356,912, filed on Feb. 16, 2006, which is a division of application No. 11/292,736, filed on Dec. 2, 2005, now Pat. No. 7,140,527, which is a division of application No. 10/399,071, filed on Apr. 10, 2003, now Pat. No. 7,055,730, filed as 371 of international application No. PCT/US01/32213, filed on Oct. 15, 2001.









FIG. 1




**FIG. 2**




**FIG. 3**




**FIG. 4**



**FIG. 5**



**FIG. 6**



**FIG. 7**




FIG. 8











FIG. 9



**FIG. 10**










FIG. 18






FIG. 17



**FIG. 19**



**FIG. 20**






FIG. 21






FIG. 26




FIG. 27




FIG. 28







FIG. 29



**FIG. 30**











FIG. 33





**FIG. 36**



**FIG. 35**




FIG. 37





FIG. 38








FIG. 40



**FIG. 41**



**FIG. 42**




FIG. 43




FIG. 44




FIG. 46




FIG. 45




FIG. 47




FIG. 48






FIG. 49



**FIG. 50**



**FIG. 51**

## SURGICAL FASTENER APPLYING APPARATUS

### CROSS REFERENCE TO RELATED APPLICATION

[0001] The present application claims priority of U.S. provisional application Ser. No. 60/240,461 filed on Oct. 13, 2000, the entire contents of which are hereby incorporated by reference.

### BACKGROUND

#### [0002] 1. Technical Field

[0003] The present disclosure relates to surgical fastener applying apparatus and more particularly to surgical fastener applicators for sequentially applying a plurality of surgical fasteners to body tissue.

#### [0004] 2. Discussion of Related Art

[0005] Surgical devices wherein tissue is first grasped or clamped between opposing jaw structures and then joined by means of surgical fasteners are well known in the art. In some such instruments a knife is provided to cut the tissue which has been joined by the fasteners. The fasteners are typically in the form of surgical staples however, other surgical fasteners may also be utilized, for example, clips or two part polymeric surgical fasteners.

[0006] Instruments for applying surgical fasteners typically include two elongated beam members which are respectively used to capture or clamp tissue therebetween. Typically, one of the beam members carries a disposable cartridge which houses a plurality of staples arranged in at least two lateral rows while the other beam member comprises an anvil which defines a surface for forming the staple legs as the staples are driven from the cartridge. Where two part fasteners are used, this beam member carries the mating part, e.g. the receiver, to the fasteners driven from the cartridge. Generally, the staple formation process is effected by the interaction between a longitudinally moving camming surface and a series of individual staple pusher member. As the camming surface travels longitudinally through the cartridge carrying member, the individual pusher members are biased laterally acting upon the staples to sequentially eject them from the cartridge. A knife may travel with the pusher between the staple rows to longitudinally cut the tissue between the rows of formed staples. Examples of such instruments are disclosed in U.S. Pat. No. 3,079,606 and U.S. Pat. No. 3,490,675.

[0007] A later stapler disclosed in U.S. Pat. No. 3,499,591 applies a double row of staples on each side of the incision. This is accomplished by providing a cartridge assembly in which a cam member moves through an elongate guide path between two sets of staggered staple carrying grooves. Staple drive members are located within the grooves and are positioned in such a manner so as to be contacted by the longitudinally moving cam to effect ejection of the staples.

### SUMMARY

[0008] It is an object of the present invention to provide a surgical fastener applying apparatus which apparatus will not fire if a disposable staple cartridge is not properly loaded within the apparatus or is not loaded in the apparatus at all.

[0009] It is another object of the present invention to provide a surgical fastener applying apparatus which will not open during the firing stroke of the apparatus.

[0010] It is a further object of the present invention surgical fastener applying apparatus which will not accept a completely fired or a partially fired disposable staple cartridge therein.

[0011] It is yet another object of the present invention to provide a surgical fastener applying apparatus which will not fire while in an unclamped state.

[0012] The presently disclosed apparatus includes a cartridge half-section and an anvil half-section with the cartridge and anvil half-sections being relatively movable from an unclamped position to a fully clamped position. The apparatus further includes a replaceable staple cartridge assembly receivable in the cartridge half-section. The cartridge assembly includes a plurality of surgical staples abutting a plurality of staple pusher members and a pivotably mounted safety lock-out. The safety lock-out is pivotable between an initial position, which permits a relative movement of the cartridge and anvil half-sections to the fully clamped position, and a blocking position, which prevents a relative movement of the cartridge and anvil half-sections from returning to the fully clamped position after the plurality of staples have been at least partially fired. The apparatus further includes a pair of camming surface extensions extending from a cam bar channel and positioned within the cartridge half-section and a pivotably mounted firing lever operatively associated with the pair of camming surfaces to move the pair of camming surfaces longitudinally, thereby sequentially firing the plurality of surgical staples in a direction transverse to a direction of travel of the pair of camming surfaces.

[0013] In addition, each of the presently disclosed cartridge and anvil half-sections of the fastener applying apparatus includes a clamping lever, which clamping levers are configured and adapted to enable the applying apparatus to be opened by either one of the cartridge half-section and the anvil half-section. The apparatus including a clamp latch configured and adapted to retain the clamp levers in a clamped orientation and a safety interlock assembly configured and adapted to prevent opening of either of the clamping levers after the firing lever has been moved distally.

### BRIEF DESCRIPTION OF THE DRAWINGS

[0014] Various embodiments of the presently disclosed surgical fastener applying apparatus will be described herein with reference to the accompanying drawing figures wherein:

[0015] FIG. 1 is a perspective view of one embodiment of a surgical fastener apparatus constructed in accordance with the present disclosure;

[0016] FIG. 2 is a top plan view of the embodiment of FIG. 1;

[0017] FIG. 3 is a side elevation view of the embodiment of FIG. 1;

[0018] FIG. 4 is a side elevation view of the embodiment of FIG. 1 taken from the opposite side of that shown in FIG. 3;

[0019] FIG. 5 is a bottom plan view of the embodiment of FIG. 1;

[0020] FIG. 6 is a front elevation view of the embodiment of FIG. 1;

[0021] FIG. 7 is a rear elevation view of the embodiment of FIG. 1;

[0022] FIG. 8 is a perspective view of a disposable staple cartridge assembly of the presently disclosed surgical fastener applying apparatus;

[0023] FIG. 9 is a perspective view with parts separated of the disposable staple cartridge assembly of FIG. 8;

[0024] FIG. 10 is a schematic view of a staple pusher pair;

[0025] FIG. 11 is an enlarged left distal perspective view of a staple cartridge loading and lockout mechanism;

[0026] FIG. 12 is an enlarged right side proximal perspective view of the loading and lockout mechanism of FIG. 11;

[0027] FIG. 13 is a perspective view with parts separated showing installation of a staple cartridge assembly on a cartridge half-section of the presently disclosed surgical fastener applying apparatus;

[0028] FIG. 14 is an enlarged perspective view from the bottom of the loading and lockout mechanism with a staple cartridge in place thereon;

[0029] FIG. 15 is an enlarged perspective view similar to FIG. 12, with a staple cartridge in place;

[0030] FIG. 16 is an enlarged side perspective view which shows the relative positioning of the loading and lockout mechanism with a staple cartridge installed and with an anvil half-section in place in a clamped condition;

[0031] FIG. 17 is a perspective view which shows a surgical stapler apparatus after partial or complete firing in an unclamped condition with a staple cartridge safety lockout in a locked out position;

[0032] FIG. 18 is an enlarged view of the indicated area of detail of FIG. 17;

[0033] FIG. 19 is a perspective view of the surgical stapler apparatus opened from an anvil half-section side with an anvil half-section clamp lever opened and a cartridge half-section clamp lever closed;

[0034] FIG. 20 is a perspective view of the surgical stapler apparatus opened from a cartridge half-section side with a cartridge half-section clamp lever opened and an anvil half-section clamp lever closed;

[0035] FIG. 21 is a perspective view with parts separated which shows the structural relationship of the various components of a clamp lever lockout and safety interlock mechanism;

[0036] FIG. 22 is a plan view looking down on the anvil half-section of the surgical stapler apparatus with a firing lever in the proximal-most position;

[0037] FIG. 23 is a cross-sectional view taken along section line 23-23 of FIG. 22;

[0038] FIG. 24 is an enlarged view of the indicated area of detail of FIG. 23;

[0039] FIG. 25 is an enlarged view of the indicated area of detail of FIG. 23;

[0040] FIG. 26 is a plan view similar to FIG. 22, which shows the firing lever advanced distally a short distance;

[0041] FIG. 27 is a cross-sectional view taken along section line 27-27 of FIG. 26;

[0042] FIG. 28 is an enlarged view of the indicated area of detail of FIG. 27;

[0043] FIG. 29 is an enlarged view of the indicated area of detail of FIG. 27;

[0044] FIG. 30 is a perspective view of the cartridge half-section of the surgical stapler apparatus;

[0045] FIG. 31 is a perspective view of a disposable staple cartridge assembly according to an alternative embodiment of the present invention;

[0046] FIG. 32 is a perspective view, with parts separated, of the disposable staple cartridge assembly of FIG. 31;

[0047] FIG. 33 is a perspective view of the disposable staple cartridge assembly as shown in FIG. 31 with the shipping wedge removed therefrom;

[0048] FIG. 34 is a perspective view of a cartridge half-section according to the alternative embodiment of the present invention;

[0049] FIG. 35 is an enlarged left distal perspective view of a staple cartridge loading and lockout mechanism;

[0050] FIG. 36 is an enlarged right side proximal perspective view of the loading and lockout mechanism of FIG. 35;

[0051] FIG. 37 is an enlarged perspective view, as seen from the bottom of the loading and lock out mechanism, according to the alternative embodiment of the present invention, with a staple cartridge in place thereon;

[0052] FIG. 38 is a partially exploded enlarged perspective view, as seen from the bottom of the loading and lock out mechanism shown in FIG. 38;

[0053] FIG. 39 is an enlarged perspective view similar to FIG. 36, with a staple cartridge in place;

[0054] FIG. 40 is an enlarged side perspective view which shows the relative positioning of the loading and lockout mechanism with a staple cartridge installed and with an anvil half-section in place in a clamped condition;

[0055] FIG. 41 is a perspective view of the surgical stapler apparatus opened from an anvil half-section side with an anvil half-section clamp lever opened and a cartridge half-section clamp lever closed;

[0056] FIG. 42 is a perspective view of the surgical stapler apparatus opened from a cartridge half-section side with a cartridge half-section clamp lever opened and an anvil half-section clamp lever closed;

[0057] FIG. 43 is a perspective view with parts separated which shows the structural relationship of the various components of a clamp lever lockout and safety interlock mechanism;

[0058] FIG. 44 is a cross-sectional view of the surgical stapler taken along the longitudinal center line thereof;

[0059] FIG. 45 is an enlarged view of the indicated area of detail of FIG. 44;

[0060] FIG. 46 is an enlarged view of the indicated area of detail of FIG. 44;

[0061] FIG. 47 is a cross-sectional view of the surgical stapler taken along the longitudinal center line thereof;

[0062] FIG. 48 is an enlarged view of the indicated area of detail of FIG. 47;

[0063] FIG. 49 is an enlarged view of the indicated area of detail of FIG. 47;

[0064] FIG. 50 is a perspective view of the cartridge half-section of the surgical stapler apparatus after partial or complete firing with a staple cartridge safety lockout in a locked out position; and

[0065] FIG. 51 is a perspective view of the surgical stapler apparatus opened from both the cartridge half-section side with the cartridge half-section clamp lever opened and from the anvil half-section side with the anvil half-section clamp lever opened.

#### DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

[0066] Preferred embodiments of the presently disclosed surgical fastener apparatus will now be described in detail with reference to the drawing figures wherein like reference numerals identify similar or identical structural elements. As shown in the drawings and described throughout the following description, as is traditional when referring to relative positioning on a surgical instrument, the term “proximal” refers to the end of the apparatus which is closer to the user and the term “distal” refers to the end of the apparatus which is further away from the user.

[0067] Referring initially to FIG. 1, an illustrative embodiment of the presently disclosed surgical fastener apparatus is illustrated therein and designated generally as surgical stapler 10. Surgical stapler 10 is particularly adapted to apply a plurality of adjacent rows of staples to body tissue clamped in between the instrument's two principle sections, a cartridge receiving half-section 12 and an anvil half-section 14. Typical applications of the presently disclosed surgical fastener apparatus are, for example, creating a hemostatic seal in general, thoracic, and urologic surgery for resection, transection and creation of anastomoses. Specific tissue structures in which the instrument may be used are, for example, the stomach, the large and small bowels, lungs and the esophagus.

[0068] FIGS. 1-7 illustrate one preferred overall ornamental design for the presently disclosed surgical fastener applying apparatus wherein. Each of these various figures illustrates surgical stapler 10 with an anvil tip removed to illustrate the end cross-section profile of the anvil half-section. The anvil tip is the same as the tip on the distal end of the staple cartridge.

[0069] Referring to FIGS. 8-10, surgical stapler 10 is designed for use with a disposable staple cartridge assembly such as single use disposable loading unit (“SULU”) 16 includes a cartridge body 18, a plurality of staple pusher members 20, a bottom cover 22, a knife 24 having an angled sharpened leading edge 24a, a plurality of staples 26, a

pivotably mounted safety lockout 28 and a removable shipping wedge 30. As with known staple cartridge designs, cartridge body 18 has a plurality of rows of staple retaining slots 32 formed therein. Surgical stapler 10 may be manufactured and assembled in different sizes to receive different size SULUs 16. For example, surgical stapler 10 can be made in different sizes to accept SULUs having staple line lengths of 60 mm, 80 mm, and 100 mm.

[0070] Alternatively, SULUs 16 may be adapted such that one common surgical stapler 10 will accept multiple different staple count SULUs. For example, SULUs 16 may be configured such that each different staple count SULU shares a common size cartridge body 18 to facilitate mounting on surgical stapler 10.

[0071] In the illustrated embodiment, there are two staggered rows of slots 32 formed on either side of a linear slotted track 34 which guides knife 24 during its longitudinal movement. A single staple 26 is positioned in each of slots 32. The staple rows preferably extend a distance distally beyond the distal end of knife track 34 to facilitate staple formation beyond the stroke length of knife 24.

[0072] Staple pushers 20 are aligned one each with slots 32 such that a single staple pusher 20 is positioned under the staple 26 retained in slot 32. Staple pushers 20 are formed such that they are attached to each other in groups of two offset oriented pusher pairs, shown schematically in FIG. 10, and have an actuating surface connecting each pair of two pushers 20.

[0073] The pusher pairs are arranged in two series, one on each side of slotted track 34, such that the actuating surfaces of each series of pusher pairs forms a line centered between the staggered row of staples 26. The actuating surfaces act as cam followers and interact with a pair of staggered camming surfaces 36, 38 (see FIG. 11) extending from a cam bar channel 40 to expel the pairs of staples 26 on each side of the knife track 34. As illustrated, camming surfaces 36, 38 form a single angle relative to horizontal. In certain application, for example, with staples having an unformed leg height of about 4.5 mm, camming surfaces 36, 38 may be formed of a plurality of angles to facilitate optimal staple deformation with a given firing force. As cam bar channel 40 is moved distally this sequence is repeated until the distal movement of cam bar channel 40 is either stopped intentionally by the user to form less than all of staples 26 or until all of staples 26 are expelled from SULU 16.

[0074] Bottom cover 22 partially encloses the bottom of a channel formed by the upper surface and side walls of cartridge body 18. A longitudinal ridge 22a is formed on the upper surface of bottom cover 22 and serves as a bearing surface for knife bearing channel 42 secured to the bottom edge of knife 24 as it travels in knife track 34. A pair of slots are formed one on either side of longitudinal ridge 22a. The outer limit of each slot being defined by the outer wall of cartridge body 18 on the respective side of ridge 22a. These slots facilitate reciprocating longitudinal movement of the camming surface extensions 36, 38 of cam bar channel 40. Knife bearing channel 42 which is wider than knife track 34, is secured to the bottom surface of the knife such that knife bearing channel member 42 rides between knife track 34 and longitudinal ridge 22a of bottom cover 22. In this manner, knife 24 is prevented from undergoing substantial vertical movement during longitudinal translation in knife track 34.

[0075] Safety lockout 28 is pivotably disposed on the upper proximal end of cartridge body 18 and is movable from a locked orientation to an unlocked orientation. Preferably, safety lockout 28 is biased away from the locked orientation towards an orientation substantially perpendicular to the longitudinal axis of cartridge body 18. Any suitable bias member may be utilized such as, for example, springs 44, 46. To overcome the bias towards the perpendicular orientation, safety lockout 28 includes a transverse horizontal surface 28a (see FIG. 24) formed on the underside thereof which engages a hook 24b formed on the upper edge surface of knife 24. This cooperative engagement serves to retain safety lockout 28 in the locked orientation wherein safety lockout 28 covers knife 24.

[0076] When surgical stapler 10 has been unclamped, as will be described in greater detail further herein, after either partial or complete firing, safety lockout 28 is biased to the perpendicular orientation (see FIGS. 17 and 18), extending upwardly away from cartridge half-section 12. In this manner, surgical stapler 10 cannot be re-clamped until the partial or completely fired SULU 16 is removed and replaced with a new SULU 16. Safety lockout 28 also provides a cut-out grasping surface 28b with which SULU 16 may readily be removed from surgical stapler 10.

[0077] As previously noted, shipping wedge 30 is removably attachable to cartridge body 18. When installed on SULU 16, shipping wedge 30 covers the entire surface area of the staple rows 26 and knife track 34. Additionally, shipping wedge 30 includes an abutment 30a extending upwardly and proximally from the upper proximal surface of shipping wedge 30. Abutment 30a in cooperation with safety lockout 28 covers sharpened distal edge 24a of knife 24. This feature prevents the knife from being exposed to the user during handling of SULU 16. Additionally, abutment 30a prevents pivotal movement of safety lockout 28 from the locked orientation. Thus, even if SULU 16 is properly loaded on surgical stapler 10, staples 26 cannot be fired until shipping wedge 30 is first removed.

[0078] Shipping wedge 30 also includes a post 30b extending downwardly from the underside near the proximal end. Post 30b fits into a complementary shaped opening 18c formed in cartridge body 18 at the proximal end of knife track 34. With shipping wedge 30 in place, post 30b blocks potential distal movement of knife 26. In an alternative embodiment, SULUs 16 may also be provided without a knife in applications where it is desirable to perform stapling without transection. In such an embodiment, knife 26 is replaced with a blank element to substitute for the knife to interact with safety lockout 28.

[0079] Cartridge body 18 is provided with several molded surfaces to facilitate mounting and alignment of SULU 16 with respect to cartridge half-section 12 of surgical stapler 10. Such alignment facilitating surfaces may be formed at any suitable location on the various components of cartridge body 18 to correspond with complementary surfaces on cartridge half-section 12. In the illustrated embodiment, locating/alignment feature surfaces 18a are formed extending downwardly on either side of SULU 16 near the proximal end thereof and molded surfaces 18b are formed on either side of cartridge body 18 near the distal end thereof. When SULU 16 is properly installed on surgical stapler 10, surfaces 18a seat in a pair of notches 48, 50 (see FIG. 13) formed in cartridge half-section 12.

[0080] Referring to FIGS. 11-16, a loading and lockout mechanism for SULU 16 will now be described in detail. In these figures, a channel frame 12a (see FIG. 21) of cartridge half-section 12 is not shown so that the loading and lockout mechanism can be illustrated more clearly. The loading and lockout mechanism facilitates loading of SULU 16 and prevents firing of surgical stapler 10 until SULU 16 is properly loaded on cartridge half-section 12 and surgical stapler 10 is properly clamped shut. The loading and lockout mechanism includes a rocker 52 which is pivotably mounted to channel frame 12a (see FIG. 21) of cartridge half-section 12 by way of transversely extending post portions 52a seating in openings formed through the sidewalls of channel frame 12a. Post portions 52a are provided with angled downwardly oriented surfaces to facilitate assembly of rocker 52 with channel frame 12a. Rocker 52 is preferably a molded plastic component and is provided with three slots, namely an open bottomed slots 52b, 52c to permit longitudinal movement of cam bar channel 40 and a closed slot 52d to permit passage of a center bar 54.

[0081] As best shown in FIGS. 12 and 14, rocker 52 is further provided with a downwardly extending blocking surface 52e which is in vertical alignment with an opening formed through the bottom surface of cam bar channel 40 when cam bar channel 40 is in its proximal-most position. Rocker 52 is biased, by way of a spring 56 being disposed between downwardly extending leg 52f and an end wall 58a of a beam member 58, toward a locked-out position wherein blocking surface 52e extends through opening 40a. In this manner, cam bar channel 40 is prevented from distal longitudinal movement. In versions of surgical stapler 10 using shorter SULUs 16, beam 58 may be eliminated.

[0082] Upon loading of SULU 16 on cartridge half-section as shown in FIG. 15 and 16, the spring bias maintains rocker 52 in the locked-out position. It is only when anvil half-section 14 is joined with cartridge half-section 12 and the half-sections clamped together thereby causing downwardly extending leg portions 60a formed on either side of anvil half-section channel member 60 to bias against SULU 16, that rocker 52 is urged to rotate by the camming action of proximal end surface of SULU 16 against the distal end surface of rocker 52. In this manner, blocking surface 52e is moved out of longitudinal alignment with opening 40a of cam bar channel 40 thereby permitting distal longitudinal movement thereof.

[0083] Referring to FIGS. 17 and 18, once surgical stapler 10 has been at least partially fired, if the instrument is opened, safety lockout 28 of SULU 16 automatically moves to the perpendicular orientation due to the spring bias mounting thereof. In this orientation, surgical stapler 10 cannot be re-clamped. Thus, if the user desires to apply further staples, SULU 16 must first be removed and replaced with a non-fired SULU 16.

[0084] Referring to FIGS. 19-21, surgical stapler 10 is provided with dual selectable clamping levers 62, 64 and a pivotably mounted firing lever 65. Clamping levers 62, 64 provide the user with the uniquely novel option of opening surgical stapler 10 from either half-section 12 or 14. Additionally, firing lever 65 provides the user with the ability to fire surgical stapler 10 from either the left or right side.

[0085] Clamping levers 62, 64 are pivotably mounted to cartridge half-section 12 and anvil half-section 14, respec-

tively. A pair of ergonomic contoured handles **66**, **68** are secured to clamping levers **62**, **64**, respectively to provide the user with a convenient gripping handle. To further enhance the gripping of surgical stapler **10** by the user, a pair of friction enhancing inserts **70**, **72** are secured to handles **66**, **68**. Inserts **70**, **72** may be formed of any suitable friction enhancing materials, for example, rubber. Half-sections **12** and **14** are preferably configured and dimensioned to provide the ability for the user to reach around both halves and comfortably close surgical stapler **10** with a one-handed operation to approximate the captured tissue.

[0086] Referring to FIGS. **21-23**, **25-27** and **29**, a clamp latch and safety interlock mechanism is provided at the proximal end of surgical stapler **10**. The clamp latch and safety interlock mechanism serves to retain clamp levers **62**, **64** in a clamped orientation as well as to provide a safety interlock which prevents opening of either clamp lever **62**, **64** once firing lever **65** is moved distally. Each half section **12** and **14** is provided with a clamp latch and safety interlock assembly which is essentially the same and which work to latch clamp levers **62**, **64** in a clamped configuration upon squeezing the clamp levers **62**, **64** to the closed position. Accordingly, the following description of the various components which make up the assembly will be directed to that for the cartridge half-section **12** as shown in FIG. **21**.

[0087] The clamp latch and safety interlock mechanism includes a distal clamp lever latch **74** and a proximal interlock latch **76** which is spring biased distally toward a latched position. When surgical stapler **10** is in the clamped configuration with firing lever **65** in the proximal-most position, a firing slide block **78** biases latch **76** proximally to overcome the distal spring bias, as shown in FIG. **25**, to position ledge **76a** out of lateral alignment with proximal ledge **74a** formed on latch **74** thereby positioning latch **76** in an unlatched position. In this position, the user may unclamp either clamp lever **62**, **64** by squeezing spring biased finger pad portions **80a**, **80b** of latch handle, release member **80** which urges latch **74** proximally such that distal ledge **74b** is moved out of lateral alignment with the blocking structure formed on cartridge half-section **12a** or anvil half-section **14a** (not shown).

[0088] Once firing lever **65** is moved distally to begin the firing sequence of surgical stapler **10**, as shown in FIGS. **26**, **27** and **29**, slide block **78** also moves distally thereby removing the biasing force which overcame the distal spring bias of latch **76**. Thus, ledge **76a** moves in to lateral alignment with ledge **74a** of latch **74** thereby preventing clamp lever **62** from being opened until firing lever **65** is once again moved to the proximal-most position. The instrument is thereby prevented from opening during the firing stroke.

[0089] Upon initial distal movement, firing lever **65** becomes locked-out from pivotal movement by way of firing lever **65** being cammed downwardly to overcome an upward spring bias, as shown in the operationally progressive views of FIGS. **25** and **29**. In particular, as best shown in FIG. **30**, recessed notches **65a**, **65b** are formed as keyways which engage a key **78a** formed on slide block **78**, respectively depending upon which side firing lever **65** is rotated to during firing. Firing lever **65** can be returned to the proximal-most position at any time during the firing stroke. Firing lever **65** must be returned to the proximal-most position

before the levers can be released and the instrument unclamped. As described previously, if the instrument is opened after firing either partially or completely, safety lockout **28** on SULU **16** is configured to prevent the user from re-clamping the instrument.

[0090] Turning now to FIGS. **31-51**, an alternative embodiment of a disposable staple cartridge assembly is generally shown as **116**. Staple cartridge assembly **116** includes a cartridge body **118**, a plurality of staple pusher members **120**, a bottom cover **122**, a knife **124** having an angled sharpened leading edge **124a**, a plurality of staples **126**, a pivotably mounted safety lockout **128** and a removable shipping wedge **130**. As with known staple cartridge designs, cartridge body **118** has a plurality of rows of staple retaining slots **132** formed therein.

[0091] Alternatively, cartridge assembly **116** may be adapted such that one common surgical stapler **100** (see FIGS. **41** and **42**) will accept multiple different staple count cartridge assemblies **116**. For example, cartridge assembly **116** may be configured such that each different staple count cartridge assembly **116** shares a common size cartridge body **118** to facilitate mounting on surgical stapler **100**.

[0092] In the present illustrated embodiment, there are two staggered rows of slots **132** formed on either side of a linear slotted track **134** which guides knife **124** during its longitudinal movement. A single staple **126** is positioned in each of slots **132**. The staple rows preferably extend a distance distally beyond the distal end of knife track **134** to facilitate staple formation beyond the stroke length of knife **124**. Staple-pushers **120** are formed such that they are attached to each other in groups of two offset oriented pusher pairs.

[0093] The pusher pairs are arranged in two series, one on each side of slotted track **134**, such that the actuating surfaces of each series of pusher pairs forms a line centered between the staggered row of staples **126**. The actuating surfaces act as cam followers and interact with a pair of staggered camming surfaces **136** and **138** (see FIGS. **34-36**) extending from a pair of cam bars **140** to expel the pairs of staples **126** on each side of the knife track **134**. As illustrated, camming surfaces **136** and **138** form a single angle relative to horizontal. As each cam bar **140** is moved distally this sequence is repeated until the distal movement of each cam bar **140** is either stopped intentionally by the user to form less than all of staples **126** or until all of staples **126** are expelled from cartridge assembly **116**.

[0094] Bottom cover **122** partially encloses the bottom of a channel formed by the upper surface and side walls of cartridge body **118**. A longitudinal ridge **122a** is formed on the upper surface of bottom cover **122** and serves as a bearing surface for knife bearing channel **142**, secured to the bottom edge of knife **124**, as knife **124** travels in knife track **134**. A pair of slots are formed one on either side of longitudinal ridge **122a**. The outer limit of each slot being defined by the outer wall of cartridge body **118** on the respective side of ridge **122a**. These slots facilitate reciprocating longitudinal movement of the camming surface extensions **136**, **138** of each cam bar **140**. Knife bearing channel **142** which is wider than knife track **134**, is secured to the bottom surface of the knife such that knife bearing channel member **142** rides between knife track **134** and longitudinal ridge **122a** of bottom cover **122**. In this manner, knife **124** is prevented from undergoing substantial vertical movement during longitudinal translation in knife track **134**.

[0095] Safety lockout 128 is pivotably disposed on the upper proximal end of cartridge body 118 and is movable from a locked orientation to an unlocked orientation. Preferably, safety lockout 128 is biased away from the locked orientation towards an orientation substantially perpendicular to the longitudinal axis of cartridge body 118. Any suitable bias member may be utilized such as, for example, spring 144. To overcome the bias towards the perpendicular orientation, safety lockout 128 includes a transverse horizontal surface 128a (see FIG. 45) formed on the underside thereof which engages a hook 124b formed on the upper edge surface of knife 124. This cooperative engagement serves to retain safety lockout 128 in the locked orientation when safety lockout 128 covers knife 124.

[0096] When surgical stapler 100 has been unclamped, as will be described in greater detail further herein, after either partial or complete firing, safety lockout 128 is biased to the perpendicular orientation (see FIG. 50), extending upwardly away from cartridge half-section 112. In this manner, surgical stapler 100 cannot be re-clamped until the partial or completely fired cartridge assembly 116 is removed and replaced with a new cartridge assembly 116. Safety lockout 128 also provides a cut-out grasping surface 128b with which cartridge assembly 116 may readily be removed from surgical stapler 100.

[0097] As previously noted, shipping wedge 130 is removably attachable to cartridge body 118. When installed on cartridge assembly 116, shipping wedge 130 covers the entire surface area of the staple rows 126 and knife track 134. Shipping wedge 130 includes a post 130b extending downwardly from the underside near the proximal end thereof. Post 130b fits into a complementary shaped opening 118c formed in cartridge body 118 at the proximal end of knife track 134. With shipping wedge 130 in place, post 130b blocks potential distal movement of knife 126. Post 130b maintains knife 134 retained within safety lockout 128 thereby ensuring that the sharpened distal edge 124a of knife 124 is covered. Once again, cartridge assembly 116 may be provided without a knife in applications where it is desirable to perform stapling without transection. In such an embodiment, knife 126 is replaced with a blank element to substitute for the knife to interact with safety lockout 128.

[0098] Cartridge body 118 includes a series of finger grips 127 formed along the upper sides of the body 118 near a proximal end thereof. The finger grips 127 assist the user in gripping the cartridge assembly 116 for both installation and removal of the cartridge assembly 116 from the cartridge half-section 112. Cartridge body 118 also includes a pair of resilient friction fingers 129 disposed on either side near a proximal end thereof. Friction fingers 129 are configured and adapted to project outwardly from the cartridge body 118 and to frictionally engage the inner surface of the cartridge half-section 112. In this manner, the friction fingers 129 prevent the cartridge assembly 116 from falling out of the cartridge half-section 112.

[0099] Referring to FIGS. 35-40, a loading and lockout mechanism for cartridge assembly 116 will now be described in detail. The loading and lockout mechanism facilitates loading of cartridge assembly 116 and prevents firing of surgical stapler 100 until cartridge assembly 116 is properly loaded on cartridge half-section 112 and surgical stapler 100 is properly clamped shut. The loading and

lockout mechanism includes a rocker 152 which is pivotably mounted to a channel frame 112a (see FIG. 43) of cartridge half-section 112 by way of transversely extending post portions 152a seating in openings formed through the side-walls of channel frame 112a. Post portions 152a are provided with angled downwardly oriented surfaces to facilitate assembly of rocker 152 with channel frame 112a. Rocker 152 is preferably a molded plastic component and is provided with three slots, namely an open bottomed slots 152b, 152c to permit longitudinal movement of cam bar channel 140 and a closed slot 152d to permit passage of a center bar 154.

[0100] As best shown in FIGS. 37 and 39, rocker 152 is further provided with a downwardly extending blocking surface 152e which is in vertical alignment with an opening 140a formed through the bottom surface of each cam bar 140 when each cam bar 140 is in its proximal-most position. Rocker 152 is biased, by way of a spring 156 which is disposed on transversely extending post portion 152a and between a ridge 152f formed on a side of the rocker 152 and upper surface of the cartridge half section 112 (see FIG. 35), toward a locked-out position wherein blocking surface 152e extends through opening 140a. In this manner, each cam bar 140 is prevented from distal longitudinal movement.

[0101] Upon loading cartridge assembly 116 on cartridge half-section 112 as shown in FIGS. 37-40 and, the spring bias maintains rocker 152 in the locked-out position. It is only when anvil half-section 114 is joined with cartridge half-section 112 and the half-sections clamped together thereby causing downwardly extending leg portions 160a formed on either side of anvil half-section channel member 160 to bias against cartridge assembly 116, that rocker 152 is urged to rotate by the camming action of proximal end surface of cartridge assembly 116 against the distal end surface of rocker 152. In this manner, blocking surface 152e is moved out of longitudinal alignment with opening 140a of each cam bar 140 thereby permitting distal longitudinal movement thereof.

[0102] Similar to the first embodiment, once surgical stapler 100 has been at least partially fired, if the instrument is opened, safety lockout 128 of cartridge assembly 116 automatically moves to the perpendicular orientation due to the spring bias mounting thereof. In this orientation, surgical stapler 100 cannot be re-clamped. Thus, if the user desires to apply further staples, fired or partially fired cartridge assemblies 116 must first be removed and replaced with a non-fired cartridge assembly 116.

[0103] Referring to FIGS. 41 and 42, surgical stapler 100 is provided with dual selectable clamping levers 162 and 164 and a pivotably mounted firing lever 165. Like clamping levers 62 and 64 of the first embodiment, clamping levers 162 and 164 of the present embodiment provide the user with the uniquely novel option of opening surgical stapler 100 from either half-section 112 or 114. Additionally, firing lever 165 provides the user with the ability to fire surgical stapler 100 from either the left or right side.

[0104] Clamping levers 162 and 164 are pivotably mounted to cartridge half-section 112 and anvil half-section 114, respectively. Clamping levers 162 and 164 provide the user with the ability to open the surgical stapler from either the anvil half-section 114, as seen in FIG. 41, the cartridge half-section 112, as seen in FIG. 42, or simultaneously from

both the cartridge half-section **112** and the anvil half-section **114**, as seen in FIG. **51**. A pair of ergonomic contoured handles **166** and **168** are secured to clamping levers **162** and **164**, respectively to provide the user with a convenient gripping handle. To further enhance the gripping of surgical stapler **100** by the user, a pair of friction enhancing inserts **170** and **172** are secured to handles **166** and **168**.

[0105] Unlike the first embodiment, the surgical stapler **100** according to the alternative embodiment does not have a safety interlock mechanism. In this manner, the user can open the surgical stapler **100** after a complete or partial firing of the cartridge assembly **116**. Referring now to FIGS. **43-49**, a clamp latch mechanism, according to the alternative embodiment, is provided at the proximal end of surgical stapler **100** which serves to retain clamp levers **162** and **164** in a clamped orientation. Each half section **112** and **114** is provided with a clamp latch mechanism which is essentially the same and which works to latch clamp levers **162** and **164** in a clamped configuration upon squeezing the clamp levers **162** and **164** to the closed position. Accordingly, the following description of the various components which make up the clamp latch mechanism will be directed to that for the cartridge half-section **112**.

[0106] As shown in FIG. **43**, the clamp latch mechanism includes a distal clamp lever latch **174** formed at a proximal end of the cartridge half-section **112** and latch handle release member **180** operatively coupled to a proximal end of clamp lever **162**. Latch handle release member **180** is spring biased proximally toward a latched position and is provided with a catch **132** or engaging clamp lever latch **174**. In order to release clamp lever **162**, the user presses release member **180** in the distal direction, thereby disengaging catch **182** from latch **174**.

[0107] In order to prevent inadvertent opening of the clamp lever **162**, release member **180** is provided with a projection **184** extending downwardly from a proximal end thereof, which projection **184** is seated within a guard **186** formed at the proximal end of the lever **162**. It is envisioned that the guard **186** can be integral with the handles **166** and **168** and made of a resilient material to enable the user to more easily move the guard **186** and thereby depress the release member **180**.

[0108] Further, as seen in FIG. **43**, surgical stapler **100** is provided with a firing lever slide block **188**. Slide block **188** includes a hub **190** projecting therefrom and configured and adapted to be received in a pivot hole **192** formed in firing lever **165**. Slide block **188** is configured and adapted to be slidably received in either the cartridge half-section **112** or the anvil half-section **114**. In use, the firing lever **165** is pivotable about hub **190** thereby providing the user with the ability to manipulate the firing lever **165** from either side of the surgical stapler **100**.

[0109] As seen in FIGS. **41-43** and **50**, surgical stapler **100** is provided with a staple gap adjustment mechanism **200** which enables each stapler **100** to be manufactured and assembled with a very precise staple gap between the cartridge assembly and the anvil structure of the surgical stapler. The staple gap adjustment mechanism **200** is the subject of commonly owned and co-pending U.S. provisional patent application, Ser. No. \_\_\_\_\_, filed on Oct. 5, 2001, entitled "Surgical Stapling Apparatus", attorney docket number 203-3067, the entire contents of which are

incorporated herein by reference. According to the present embodiment, gap adjustment mechanism **200** includes a pair of upstanding hinge plates **202** formed along the sides of the cartridge half-section **112** and an eccentric cam **206**. Each hinge plate **202** is provided with a coaxial through hole **204** formed therein and is configured and adapted to receive the eccentric cam **206** therein. In use, as the eccentric cam **206** is rotated, the eccentric cam **206** presses against the anvil half-section **114** until the desired staple gap between the anvil half-section **114** and the cartridge half section **112** is achieved. At which point the eccentric cam **206** is fixedly secured in the through holes **204**.

[0110] It will be understood that various modifications may be made to the embodiments of the surgical fastener applying apparatus disclosed herein. Therefore, the above description should not be construed as limiting, but merely as exemplifications of preferred embodiments. Those skilled in the art will envision other modifications within the scope and spirit of the present disclosure.

1-8. (canceled)

9. A surgical fastener applying apparatus, comprising:

a cartridge half-section and an anvil half-section, the cartridge half-section and anvil half-section being relatively movable from an unclamped position to a clamped position; and

a loading unit receivable in the cartridge half-section and having a plurality of staples and a plurality of staple pusher members;

the cartridge half-section having:

a frame;

a member being longitudinally movable through the loading unit to interact with the plurality of staple pusher members to fire the staples; and

a lockout mechanism arranged to block advancement of the member in a locked-out position of the lockout mechanism;

whereupon both loading of the loading unit in the surgical fastener applying apparatus and clamping of the cartridge and anvil half-sections moves the lockout mechanism to an unlocked position to allow advancement of the member.

10. The surgical fastener applying apparatus of claim 9, wherein the member is a cam bar slidably coupled to said cartridge half-section, wherein said cam bar includes a pair of camming surface extensions for interacting with the staple pusher members to fire the staples.

11. The surgical fastener applying apparatus of claim 10, wherein the lockout mechanism includes a rocker pivotably mounted to said cartridge half-section, said rocker including a downwardly extending blocking surface and being biased toward a locked-out position, wherein said blocking surface engages said member to prevent a longitudinal movement of said cam bar arrangement and said camming surface extensions.

12. The surgical fastener applying apparatus of claim 9, wherein said anvil half-section includes a downwardly extending portion configured and adapted to engage the loading unit, the loading unit urging said lockout mechanism to rotate.

13. A surgical fastener applying apparatus, comprising:
- a cartridge half-section and an anvil half-section, the cartridge half-section and anvil half-section being relatively movable from an unclamped position to a clamped position; and
  - a replaceable staple cartridge assembly selectively receivable in the cartridge half-section, the replaceable staple cartridge assembly including:
    - a plurality of surgical staples;
    - a plurality of staple pusher members; and
    - a lock-out, the lock-out being movable between an initial substantially horizontal position and a vertical blocking position extending between the cartridge and anvil half-sections, wherein the lock-out prevents the cartridge half-section and anvil half-section from returning to the clamped position after the plurality of staples have been at least partially fired.
14. The surgical fastener applying apparatus of claim 13, wherein the lock-out includes a transverse horizontal surface formed on an underside thereof, the transverse horizontal surface engaging a hook formed on an upper edge surface of a knife thereby retaining said lock-out in said blocking position.
15. The surgical fastener applying apparatus of claim 14, wherein said lock-out moves to said blocking position upon an unclamping of the cartridge and anvil half-sections after the plurality of staples have been at least partially fired.
16. The surgical fastener applying apparatus of claim 13, wherein the lock-out is confined between planes defined by opposed lateral side walls of said replaceable staple cartridge assembly when in the initial and blocking positions.
17. A surgical fastener applying apparatus, comprising:
- a cartridge half-section and an anvil half-section, the cartridge half-section and anvil half-section being relatively movable from an unclamped position to a clamped position; and
  - a replaceable staple cartridge assembly selectively receivable in the cartridge half-section, the replaceable staple cartridge assembly including:
    - a plurality of surgical staples;
    - a plurality of staple pusher members; and
    - a lock-out movable between an initial position permitting a relative movement of the cartridge half-section and anvil half-section to said clamped position and a blocking position preventing a relative movement of said cartridge half-section and anvil half-section to said clamped position after said plurality of staples have been at least partially fired, wherein the lock-out is confined between planes defined by opposed lateral side walls of said cartridge half-section when in the initial and blocking positions.
18. The surgical fastener applying apparatus of claim 17, wherein the lock-out includes a transverse horizontal surface

formed on an underside thereof, the transverse horizontal surface engaging a hook formed on an upper edge surface of a knife thereby retaining said lock-out in the blocking position.

19. The surgical fastener applying apparatus of claim 17, wherein the lock-out moves to the blocking position upon an unclamping of the cartridge and anvil half-sections after the plurality of staples have been at least partially fired.

20. The surgical fastener applying apparatus of claim 17, wherein the lock-out is confined between planes defined by opposed lateral side walls of said replaceable staple cartridge assembly when in the initial and blocking position.

21. A replaceable staple cartridge assembly for use in a surgical fastener applying apparatus having a cartridge half-section and an anvil half-section, the cartridge half-section and anvil half-section being relatively movable from an unclamped position to a clamped position, wherein the replaceable staple cartridge assembly comprises:

- a plurality of surgical staples;

- a plurality of staple pusher members; and

- a lock-out movable between an initial position permitting a relative movement of the cartridge half-section and anvil half-section to said clamped position and a blocking position preventing a relative movement of said cartridge half-section and anvil half-section to said clamped position after said plurality of staples have been at least partially fired, wherein the lock-out is confined between planes defined by opposed lateral side walls of said replaceable staple cartridge assembly when in the initial and blocking positions.

22. A replaceable staple cartridge assembly for use in a surgical fastener applying apparatus having a cartridge half-section and an anvil half-section, the cartridge half-section and anvil half-section being relatively movable from an unclamped position to a clamped position, wherein the replaceable staple cartridge assembly comprises:

- a plurality of surgical staples;

- a plurality of staple pusher members; and

- a lock-out movable between an initial position permitting a relative movement of the cartridge half-section and anvil half-section to the clamped position and a blocking position preventing a relative movement of the cartridge half-section and anvil half-section to said clamped position after said plurality of staples have been at least partially fired, wherein the lock-out is confined between planes defined by opposed lateral side walls of the cartridge half-section when in the initial and blocking position.

23. The replaceable staple cartridge assembly of claim 22, wherein the lock-out is interposed between planes defined by opposed lateral side walls of said replaceable staple cartridge assembly when in the initial and blocking positions.

\* \* \* \* \*