



(43) International Publication Date
31 October 2013 (31.10.2013)

- (51) International Patent Classification:
E21B 4/02 (2006.01)
- (21) International Application Number:
PCT/US2013/038446
- (22) International Filing Date:
26 April 2013 (26.04.2013)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
61/639,762 27 April 2012 (27.04.2012) US
- (71) Applicant: NATIONAL OILWELL VARCO, L.P.
[US/US]; 7909 Parkwood Circle Drive, Houston, Texas
77036 (US).
- (72) Inventors; and
- (71) Applicants : MARCHAND, Nicholas Ryan [CA/CA];
947 Blackmud Creek Crescent, Edmonton, Alberta T6W
1J3 (CA). CLAUSEN, Jeffery Ronald [US/US]; 11930
Golden Lodge Lane, Houston, Texas 77066 (US). PRILL,
Jonathan Ryan [CA/CA]; 7603-16 Avenue SW, Edmon-
ton, Alberta T6X 1M3 (CA).
- (74) Agent: FALESKI, Thaddeus J.; Conley Rose, P.C., 1001
McKinney, Suite 1800, Houston, Texas 77002 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report (Rule 48.2(g))

(54) Title: DOWNHOLE MOTOR WITH CONCENTRIC ROTARY DRIVE SYSTEM




FIG. 1

(57) Abstract: A downhole motor includes a bearing assembly having a mandrel rotatable within a cylindrical housing, with the mandrel co-rotatably engaging the rotor of a concentric rotary drive system incorporating an arrangement of housing-mounted gates pivotably deflectable by rotor lobes as the rotor rotates in response to fluid flow through an annular space between the rotor and the housing, building up pressure in longitudinal chambers formed between adjacent gates and lobes and thus inducing rotation of the mandrel. Preferably, the drive system is coupled directly to the bearing assembly, without need for a connecting driveshaft, and with the housing incorporating a bent sub positioned above the drive section. Alternatively, a bent sub may be positioned below the drive system in conjunction with the use of a driveshaft to connect the drive system to the bearing section, in order to position the bend as close as possible to the bit.



DOWNHOLE MOTOR WITH CONCENTRIC ROTARY DRIVE SYSTEM

FIELD OF THE DISCLOSURE

[0001] The present disclosure relates in general to bearing assemblies for downhole motors used in drilling of oil, gas, and water wells. The present disclosure also relates to drive systems incorporated in such downhole motors.

BACKGROUND

[0002] In drilling a wellbore into the earth, such as for the recovery of hydrocarbons or minerals from a subsurface formation, it is conventional practice to connect a drill bit onto the lower end of an assembly of drill pipe sections connected end-to-end (commonly referred to as a “drill string”), and then rotate the drill string so that the drill bit progresses downward into the earth to create the desired wellbore. In conventional vertical wellbore drilling operations, the drill string and bit are rotated by means of either a “rotary table” or a “top drive” associated with a drilling rig erected at the ground surface over the wellbore (or, in offshore drilling operations, on a seabed-supported drilling platform or a suitably adapted floating vessel).

[0003] During the drilling process, a drilling fluid (also commonly referred to in the industry as “drilling mud”, or simply “mud”) is pumped under pressure downward from the surface through the drill string, out the drill bit into the wellbore, and then upward back to the surface through the annular space between the drill string and the wellbore. The drilling fluid, which may be water-based or oil-based, is typically viscous to enhance its ability to carry wellbore cuttings to the surface. The drilling fluid can perform various other valuable functions, including enhancement of drill bit performance (e.g., by ejection of fluid under pressure through ports in the drill bit, creating mud jets that blast into and weaken the underlying formation in advance of the drill bit), drill bit cooling, and formation of a protective cake on the wellbore wall (to stabilize and seal the wellbore wall).

[0004] Particularly since the mid-1980s, it has become increasingly common and desirable in the oil and gas industry to use “directional drilling” techniques to drill horizontal and other non-vertical wellbores, to facilitate more efficient access to and production from larger regions of subsurface hydrocarbon-bearing formations than would be possible using only vertical wellbores. In directional drilling, specialized drill string components and

“bottomhole assemblies” (BHAs) are used to induce, monitor, and control deviations in the path of the drill bit, so as to produce a wellbore of desired non-vertical configuration.

[0005] Directional drilling is typically carried out using a downhole motor (commonly referred to as a “mud motor”) incorporated into the drill string immediately above the drill bit. A typical prior art mud motor includes several primary components, as follows (in order, starting from the top of the motor assembly):

- a top sub adapted to facilitate connection to the lower end of a drill string (“sub” being the common general term in the oil and gas industry for any small or secondary drill string component);
- a power section comprising a positive displacement motor of well-known type, with a helically-vaned rotor eccentrically rotatable within a stator section;
- a drive shaft housing configured to be straight, bent, or incrementally adjustable between zero degrees and a maximum angle;
- a drive shaft enclosed within the drive shaft housing, with the upper end of the drive shaft being operably connected to the rotor of the power section; and
- a bearing section comprising a cylindrical mandrel coaxially and rotatably disposed within a cylindrical housing, with an upper end coupled to the lower end of the drive shaft, and a lower end adapted for connection to a drill bit.

[0006] The mandrel is rotated by the drive shaft, which rotates in response to the flow of drilling fluid under pressure through the power section. The mandrel rotates relative to the cylindrical housing, which is connected to the drill string.

[0007] Conventional mud motors include power sections that use either a Moineau drive system or a turbine-type drive system. These types of power sections are relatively long, with typical lengths of 15-20 feet for Moineau-type power sections and 20-30 feet for turbines for motor sizes between 5” and 8” in diameter. For directional drilling with a bent motor assembly, it is optimal to position the bend within a few feet of the bit in order to achieve suitable levels of hole curvature and reasonable steerability of the assembly. Having the bend located above the power section or turbine would be too great a distance from the bit to be effective, so this requires the bend to be located below the power section or turbine. The bend is typically incorporated within the drive shaft housing. The driveshaft typically comprises

universal joints to accommodate the angular misalignment between the power section and bearing assembly, as well as the eccentric operation in the case of a Moineau power section. The driveshaft U-joints and threaded connections are typically the weakest parts of the motor assembly and the most common locations for fractures to occur.

[0008] U.S. Patents No. 6,280,169, No. 6,468,061, No. 6,939,117, and No. 6,976,832 (all of which are hereby incorporated by reference in their entirety) disclose similar types of fluid-powered rotary drive mechanisms. These mechanisms are capable of outputting levels of rotary speed and torque comparable to Moineau and turbine-type power sections, but in power sections as short as one to three feet in length. These mechanisms comprise a system of longitudinal lobes and gates, with intake and exhaust ports for directing fluid to build pressure between the lobes and gates to drive the rotation of the motor. The mechanisms operate with concentric rotation between the inner shaft and outer housing. The shorter length and concentric operation allow any of these drive systems to be incorporated directly within or attached to the mud motor bearing assembly, with no need for a driveshaft assembly with universal joints. The fixed or adjustable bent housing can be attached above the drive section while maintaining a bit-to-bend length that is as short as or shorter than in conventional downhole motors. The resulting overall length of the motor is dramatically shorter than in conventional assemblies.

[0009] These drive mechanisms do not require any elastomeric elements, in contrast to Moineau-type drive systems which incorporate elastomeric stator elements that limit the operational temperature for a Moineau-type system to a maximum of about 325-350° F. Additionally, the performance of Moineau-type drive systems tapers off sharply above 140° F. Therefore, these concentrically-operating drive systems are suitable for use in extremely high temperature and geothermal applications (500+ degrees F) that are beyond the limits of Moineau-type systems, with little or no drop in performance.

BRIEF SUMMARY

[00010] The present disclosure teaches a downhole motor incorporating a drive system comprising a system of longitudinal lobes and gates, with intake and exhaust ports for directing fluid to build pressure between the lobes and gates to drive the rotation of the motor. Preferably, the drive system is connected concentrically to the bearing assembly while maintaining a short enough length to allow the bent housing to be located above the drive section, and negating the need for a driveshaft to connect the drive section to the

bearing section as in prior art mud motors. Alternatively, the bend may be positioned below the drive section in combination with the use of a driveshaft assembly to connect the drive section to the bearing section, in order to position the bend as close as possible to the bit.

[00011] In a first aspect, the present disclosure teaches a rotary fluid drive system comprising:

- a first body and a second body, with a selected one of the bodies being coaxially disposed inside the other body to define a working fluid space therebetween, and with the second body being rotatable relative to the first body about a rotational axis;
- at least one gate supported by a selected one of the first and second bodies, such that each gate can swing or pivot about an axis parallel to the rotational axis;
- at least one lobe provided on the body not supporting the at least one gate;
- one or more fluid inlet ports directing fluid flow into the working fluid space; and
- one or more fluid outlet ports axially spaced from the fluid inlet ports and directing fluid flow out of the working fluid space;

wherein:

- for each gate, the body supporting the at least one gate defines a gate pocket into which the associated gate can swing when contacted by a lobe;
- each gate pocket and associated gate are relatively configured to form a debris chamber therebetween, capable of accommodating debris when the associated gate is disposed therewithin; and
- the rotary fluid drive system defines a fluid path through which a working fluid can enter and exit the drive system, wherein the fluid path includes the fluid inlets, the working fluid space, and the fluid outlets, such that a flow of a working fluid along the fluid path will cause rotation of the second body relative to the first body.

[00012] In certain embodiments, each gate and its associated gate pocket are relatively configured to form at least one gate pocket flow path through which fluid can flow from between the gate pocket and the gate and into the working fluid space, when the gate has swung to a maximum extent into the gate pocket. In such embodiments, each gate (which will have a free longitudinal edge) and its associated gate pocket may be relatively configured so that when a gate has swung to the maximum extent into its associated gate pocket, the

longitudinal edge will face and be spaced from a wall of the gate pocket so as to create a downstream portion of the gate pocket flow path.

[00013] In certain embodiments, a plurality of spaced projections may be formed on a surface of each gate surface facing its associated gate pocket, with the space or gap between adjacent projections creating an associated upstream portion of the pocket flow path. In such embodiments, the projections and the gate pockets may be relatively configured such that the projections can abut a surface of the gate pocket when the gate is swung to the maximum extent into its associated gate pocket. Preferably, though not necessarily, the projections will be evenly spaced along a length of a respective gate. The gaps between the projections may be sized such that the cumulative length of the gaps on each gate will correspond to at least 10% of the length of the gate. In alternative embodiments, the cumulative length of the gaps may correspond to at least 30% of the gate length, and in other embodiments it may correspond to up to 90% of the gate length.

[00014] Preferably, though not necessarily, each gate may have associated biasing means (such as a spring, by way of non-limiting example) to bias the gate to swing in a direction away from its associated gate pocket and toward the body provided with the at least one lobe. In embodiments provided with biasing means comprising a spring, the spring may extend along and within a longitudinal bore formed in the associated gate. In such embodiments, one end of each spring may be held rotationally fixed relative to the associated gate; optionally, that end of each spring may be keyed into a portion of the body provided with the gate pockets.

[00015] The inlet ports may be located upstream of the outlet ports, having reference to a direction of flow of the working fluid along the fluid path.

[00016] The rotary fluid drive may include a flow control mechanism disposed within the second body at a selected point between the inlet ports and the outlet ports.

[00017] In certain embodiments of the rotary fluid drive, the first body is disposed inside the second body. In alternative embodiments, the second body is disposed inside of the first body.

[00018] In a second aspect, the present disclosure teaches a rotary fluid drive system comprising:

- a first body and a second body, with a selected one of the bodies being coaxially disposed inside the other body to define a working fluid space therebetween, and with the second body being rotatable relative to the first body about a rotational axis;
- at least one gate supported by a selected one of the first and second bodies, such that each gate can swing or pivot about an axis parallel to the rotational axis;
- at least one lobe provided on the body not supporting the at least one gate;
- one or more fluid inlet ports directing fluid flow into the working fluid space; and
- one or more fluid outlet ports axially spaced from the fluid inlet ports and directing fluid flow out of the working fluid space;

wherein:

- for each gate, the body supporting the at least one gate defines a gate pocket into which the associated gate can swing when contacted by a lobe;
- each gate has a surface facing the associated gate pocket and having a plurality of projections, with gaps between adjacent projections defining a gate pocket flow path;
- the rotary fluid drive system defines a fluid path through which a working fluid can enter and exit the drive system, wherein the fluid path includes the fluid inlets, the working fluid space, and the fluid outlets, such that a flow of a working fluid along the fluid path will cause rotation of the second body relative to the first body; and
- a working fluid can flow via each gate pocket flow path from the associated gate pocket into the working fluid space when the associated gate is maximally deflected into its associated gate pocket.

[00019] In certain embodiments, each gate (which will have a free longitudinal edge) and its associated gate pocket may be relatively configured so that when a gate has swung to the maximum extent into its associated gate pocket, the longitudinal edge will face and be spaced from a wall of the gate pocket so as to create a downstream portion of the gate pocket flow path.

[00020] Preferably, though not necessarily, the projections will be evenly spaced along a length of a respective gate. The gaps between the projections may be sized such that the cumulative length of the gaps on each gate will correspond to at least 10% of the length of the gate. In alternative embodiments, the cumulative length of the gaps may correspond to at

least 30% of the gate length, and in other embodiments it may correspond to up to 90% of the gate length.

[00021] Preferably, though not necessarily, each gate may have associated biasing means (such as a spring, by way of non-limiting example) to bias the gate to swing in a direction away from its associated gate pocket and toward the body provided with the at least one lobe. In embodiments provided with biasing means comprising a spring, the spring may extend along and within a longitudinal bore formed in the associated gate. In such embodiments, one end of each spring may be held rotationally fixed relative to the associated gate; optionally, that end of each spring may be keyed into a portion of the body provided with the gate pockets.

[00022] The inlet ports may be located upstream of the outlet ports, having reference to a direction of flow of the working fluid along the fluid path.

[00023] The rotary fluid drive may include a flow control mechanism disposed within the second body at a selected point between the inlet ports and the outlet ports.

[00024] In a third aspect, the present disclosure teaches a drilling motor including:

- a bearing assembly comprising: a generally cylindrical housing having an upper end and a lower end; a generally cylindrical mandrel having an upper end, a lower end, and a longitudinal bore, with the mandrel being coaxially disposed within the housing so as to be rotatable relative thereto about a rotational axis; radial bearing means disposed in an annular space between the housing and the mandrel; and thrust bearing means disposed in an annular space between the housing and the mandrel;
- a generally cylindrical rotor having an upper end, a lower end, and a longitudinal bore, with the rotor being coaxially disposed within the housing so as to define a generally annular working fluid space therebetween, and with the rotor operatively engaging the mandrel so as to be rotatable therewith;
- a plurality of elongate gates;
- at least one axially-oriented lobe engageable with the gates during relative rotation between the rotor and the housing;
- one or more fluid inlets allowing fluid flow from an upper region of the rotor bore into the working fluid space; and

- one or more fluid outlets allowing fluid flow out of the working fluid space into a lower region of the rotor bore;

wherein the drilling motor defines a fluid path including the fluid inlets, the working fluid space, and the fluid outlets, such that a flow of a working fluid along the fluid path will cause relative rotation between the rotor and the housing, thereby causing each lobe to deflect each gate in sequence.

[00025] In some embodiments, the gates may be supported by the housing and pivotable about a pivot axis parallel to the rotational axis. In other embodiments, the gates may be supported by the rotor and pivotable about a pivot axis parallel to the rotational axis. In still other embodiments, the gates may be radially-actuating and supported by the housing or, alternatively, radially-actuating and supported by the rotor.

[00026] The drilling motor may include biasing means associated with the gates, for biasing the gates away from the component supporting the gates.

[00027] The drilling motor may be configured such that the mandrel engages the rotor so as to be coaxially rotatable therewith. Such coaxially rotatable engagement of the mandrel and the rotor may be effected by any functionally effective means, such as, without limitation:

- by means of a splined connection, with an upper portion of the mandrel coaxially disposed within the bore of the rotor;
- by means of respective mating lugs provided on the upper end of the mandrel and the lower end of the rotor;
- by means of a clutch mechanism disposed between the upper end of the mandrel and the lower end of the rotor;
- by means of a gear box disposed between the upper end of the mandrel and the lower end of the rotor;
- by means of a generally cylindrical coupling having a lower section with internal threading matingly engageable with external threading on the upper end of the mandrel, and having an upper section with internal splines matingly engageable with external splines on the lower end of the rotor;

- by means of a drive shaft having an upper end rigidly and coaxially engaging the lower end of the rotor, and a lower end incorporating a universal joint which engages a drive shaft housing coupled to the upper end of the mandrel; or
- by means of a drive shaft having an upper end incorporating an upper universal joint engaging an upper drive shaft housing coupled to the lower end of the rotor, and a lower end incorporating a lower universal joint which engages a drive shaft housing coupled to the upper end of the mandrel.

[00028] The housing of the drilling motor may incorporate a bent sub, which optionally may be either a fixed bent sub or an adjustable bent sub. In certain embodiments the bent sub will be located above the rotor; generally speaking, however, the location of the bent sub, when provided, will be a matter of design choice having regard to operational parameters. For example, in some embodiments a bent sub may be positioned below the rotor. In embodiments incorporating a drive shaft coaxially engaging the rotor and engaging the mandrel by means of a universal joint, a bent sub may be positioned proximal to the universal joint. In embodiments incorporating a drive shaft having upper and lower universal joints, a bent sub may be positioned between the universal joints.

[00029] In certain embodiments, the radial bearing means may be adapted to transfer radial loads from the mandrel to the housing through the rotor, such as, by way of non-limiting example, by adapting the rotor to serve as a radial bearing.

[00030] Optionally, the drilling motor may comprise flow control means, for altering the characteristics of fluid flow through the motor to regulate the rotational speed of the motor. In certain embodiments, the flow control means may be configured to allow fluid to bypass the working fluid space when the pressure differential across the working fluid space exceeds a pre-set value. In other embodiments, the flow control means may comprise, by way of non-limiting example:

- a relief valve coaxially disposed within the rotor;
 - a plate integral with a selected one of the mandrel and the rotor, and positioned to separate flow between the fluid inlets and the fluid outlets;
 - a nozzle for continuously bypassing a portion of the fluid flow through the rotor;
 - a burst disc positioned to separate flow between the fluid inlets and the fluid outlets;
- or

- means for diverting fluid to the exterior of the housing.

BRIEF DESCRIPTION OF THE DRAWINGS

[00031] Embodiments in accordance with the present disclosure will now be described with reference to the accompanying Figures, in which numerical references denote like parts, and in which:

[00032] **FIG. 1** is a longitudinal cross-section through a bearing assembly incorporating an embodiment of a rotary drive system in accordance with the present disclosure.

[00033] **FIG. 2** is an enlarged longitudinal cross-section through the bearing assembly and rotary drive system shown in FIG. 1.

[00034] **FIG. 3** is a transverse cross-section through the rotary drive system shown in FIGS. 1 and 2.

[00035] **FIG. 4** is an isometric view of one embodiment of one of the gates used in the rotary drive system shown in FIG. 3.

[00036] **FIG. 4A** is an isometric view of a torsion rod for use in conjunction with a gate as FIG. 4.

[00037] **FIG. 4B** is an isometric view of a gate preload ring for use in conjunction with torsion rods as in FIG. 4A.

[00038] **FIG. 5** is an isometric cross-section through the housing of the rotary drive system shown in FIGS. 1 to 3.

[00039] **FIG. 6** is an isometric cross-section through the rotary drive system shown in FIGS. 1 to 3, but with the mandrel and rotor not shown.

[00040] **FIGS. 7 and 8** are cross-sections through the rotary drive system as in FIG. 3, showing the lobed shaft in different rotational positions relative to the housing.

[00041] **FIG. 9** is a longitudinal cross-section through a bearing assembly incorporating an alternative embodiment in which the rotor of the rotary drive system engages the mandrel of bearing section in end-to-end relation.

[00042] **FIG. 9A** is a longitudinal cross-section through a variant of the bearing assembly in FIG. 9.

[00043] **FIG. 10** is an enlarged sectional detail of one embodiment of a relief valve system for use in conjunction with rotary drive systems in accordance with the present disclosure.

[00044] **FIG. 11** is an enlarged sectional detail of a variant of the relief valve shown in FIG. 10.

[00045] FIG. 12 is a cross-sectional detail of an end-to-end connection between the rotor and mandrel in an alternative embodiment of a rotary drive system in accordance with the present disclosure, using a threaded and splined connector.

[00046] FIGS. 12A and 12B are isometric and cross-sectional views, respectively, of the threaded and splined connector in FIG. 12.

[00047] FIG. 13 is a longitudinal cross-section through an alternative embodiment of a downhole motor incorporating a concentric rotary drive system in accordance with the present disclosure, in which the bent housing is located below the rotary drive system and the rotary drive system is operatively connected to the motor's bearing section by a drive shaft having a single U-joint.

[00048] FIG. 13A is an enlarged cross-sectional view of the bent housing and drive shaft of the downhole motor in FIG. 13.

[00049] FIG. 14 is a longitudinal cross-section through a further embodiment of a downhole motor incorporating a concentric rotary drive system in accordance with the present disclosure, in which the rotary drive system is connected to a conventional bearing section by means of a conventional drive shaft having two U-joints.

DETAILED DESCRIPTION

[00050] The Figures illustrate various embodiments of downhole motors in accordance with the present disclosure. FIG. 1 illustrates a bearing assembly 100 comprising a first embodiment 110 of a concentric rotary drive system connected at its upper end to the lower end of a bent housing 200, which incorporates a fixed or adjustable bent sub 210. Although the illustrated bearing assembly incorporates a bent housing, it is to be understood that this is not essential, as the bearing assembly and rotary drive systems in accordance with the present disclosure could alternatively be run without a bent housing (i.e., when drilling a straight or undeviated section of a wellbore).

[00051] Bearing assembly 100 includes an elongate mandrel 10 coaxially disposed within a generally cylindrical housing 20 so as to be rotatable relative thereto, with the lower end 12 of mandrel 10 projecting from the lower end 22 of housing 20 and being adapted for connection to a drill bit or other BHA components below the motor. Mandrel 10 has a central bore 14 for passage of a working fluid such as a drilling fluid. The upper end 205 of bent

housing **200** is adapted for connection to the drill string or to other BHA components above the motor.

[00052] The primary features of the bearing assembly **100** and rotary drive system **110** in FIG. 1 are illustrated in greater detail in FIGS. 2 and 3. Rotary drive system **110** includes a generally cylindrical central shaft **120** (alternatively referred to as rotor **120**) concentrically coupled to mandrel **10** so as to be rotatable therewith, and within housing **20**. Accordingly, a generally annular space **40** is formed between rotor **120** and housing **20**. Annular space **40** is alternatively referred to herein as a working fluid space **40**. End plates **42U** and **42L** are fixed within housing **20** and define the upper and lower boundaries of working fluid space **40**. End plates **42U** and **42L** also serve to constrain the axial position of rotor **120** relative to housing **20**.

[00053] In the illustrated embodiment, rotor **120** is concentrically coupled to mandrel **10** by means of a splined connection as shown in FIG. 3, with splines **16** projecting from the outer surface of mandrel **10** engaging mating grooves **122** on the inner surface of the bore of rotor **120**. However, rotor **120** could be co-rotatably coupled to mandrel **10** by other means. By way of non-limiting example only, mandrel **10** and rotor **120** could abut each other in end-to-end relation, while being rotatably coupled by a mechanism comprising mating axially-aligned lugs on each component, as in the alternative embodiment shown in FIG. 9 (in which the mating lugs on mandrel **10** and rotor **120** are indicated by reference numbers **19** and **129** respectively). Other exemplary means for rotatably coupling mandrel **10** and rotor **120** in end-to-end relation include threaded connections, splined connections, gear boxes, and clutch mechanisms in accordance with known technologies.

[00054] By way of non-limiting example, FIG. 12 depicts an alternative embodiment **400** of a bearing section incorporating a rotary drive system in accordance with the present disclosure, in which a threaded and splined coupling **410** is used to transfer torque from rotor **120** to mandrel **10**. In this embodiment, rotor **120** is supported by its own set of radial bearings **440** on both ends of the rotor (only lower radial bearings **440** are shown in FIG. 12).

[00055] As shown in FIGS. 12, 12A, and 12B, coupling **410** comprises a lower cylindrical section **420** having internal threading **425**, and an upper generally cylindrical section **430** the bore of which defines longitudinal splines **432** and grooves **435**. Upper and lower sections **430** and **420** are coaxially contiguous, with a central bore **415** in the transition section between upper and lower sections **430** and **420**. The upper end **10U** of mandrel **10** in this

embodiment is provided with external threading **15** engageable with internal threading **425** in lower section **420** of coupling **410**. The lower end **120L** of rotor **120** is formed with splines **115** engageable with grooves **435** on upper section **430** of coupling **410**.

[00056] As shown in FIGS. 1, 2, 5, 7, and 8, fluid inlet ports **116** are provided through mandrel **10** and rotor **120** in an upstream region of rotor **120** to allow fluid flow from mandrel bore **14** into working fluid space **40**, and fluid outlet ports **117** are provided through rotor **120** and mandrel **10** in a downstream region of rotor **120** to allow fluid flow from working fluid space **40** back into mandrel bore **14**. Accordingly, rotary drive system **110** can be considered as defining a fluid path through the rotary drive system, extending between a fluid intake zone in an upstream region **14U** of mandrel bore **14**, through inlet ports **116** into working fluid space **40**, and out of working fluid space **40** through outlet ports **117** into a fluid exit zone in a downstream region **14D** of mandrel bore **14** proximal to the lower end **120L** of rotor **120**, from which zone fluid flow can continue within mandrel bore **14** toward the bit.

[00057] As best seen in FIGS. 3, 5, 7, and 8 the outer perimeter surface of rotor **120** defines a plurality of uniformly-spaced longitudinal rotor lobes **124**. As best seen in FIGS. 3, 5, 6, 7, and 8, a plurality of elongate gates **130** are pivotably mounted within respective elongate gate-receiving pockets **26** in the inner surface **24** of the bore of housing **20**.

[00058] FIG. 4 illustrates one embodiment of a gate **130** in accordance with the present disclosure. In this embodiment, gate **130** has ends **131** (which may be designated upper and lower ends **131U** and **131L** depending on the orientation of gate **130** in a given embodiment of the drive system) and an elongate blade member **134** with a first blade surface **135** oriented toward the associated gate pocket **26**. The radially-outer end of blade member **134** has a longitudinal free edge **139** configured for substantially fluid-tight contact with the outer surfaces of rotor **120** (including, as the operational case may be, rotor lobes **124**). Free edge **139** of blade member **134** preferably (but not necessarily) has a thickened or bulbous section **136** projecting from first blade surface **135**. Thickened section **136** may be continuous or, as shown in FIGS 3-8, it may form a plurality of spaced projections **136A** extending from blade surface **135** toward the associated gate pocket **26**, with gaps **136B** being formed between adjacent projections **136A**.

[00059] The inner surface **24** of the bore of housing **20** is formed with elongate gate pockets **26** such that as lobed rotor **120** rotates within housing **20**, rotor lobes **124** will sequentially engage gates **130** and deflect them into their associated gate pockets **26** in housing **20** so that

rotor lobes **124** can pass by. Each gate **130** thus pivots between a lowered position (i.e., in contact with or closely adjacent to rotor **120**) when located between adjacent rotor lobes **124**, and a raised (or deflected) position when displaced into its associated gate pocket **26** by a passing rotor lobe **124**.

[00060] Optionally, projections **136A** and gate pockets **26** may be configured such that projections **136A** of a given gate **130** will abut a surface of the associated gate pocket **26** when gate **130** is maximally deflected into gate pocket **26**. Preferably, projections **136A** are evenly spaced along the length of gate **130**. In one embodiment, the cumulative length of gaps **136B**, as measured along the length of gate **130**, corresponds to at least 10% of the gate length. In an alternative embodiment, the cumulative length of gaps **136B** corresponds to at least 30% of the gate length. In yet another embodiment, the cumulative length of gaps **136B** corresponds to as much as 90% of the gate length.

[00061] In preferred embodiments, each gate pocket **26** incorporates a debris slot or chamber **27**, to accommodate or receive large particulate matter that might be present in the drilling fluid and which might otherwise impede full deflection of the associated gate **130** into gate pocket **26** by the passing rotor lobes **124**. This can be best appreciated with reference to FIG. 3, in which an exemplary gate denoted by reference character **130A** is shown fully deflected into its associated gate pocket **26A**. Oversize matter carried by the drilling fluid can temporarily reside within debris chamber **27A** as rotor lobes **124** pass by, rather than becoming lodged behind gate **130A** and impeding full deflection of gate **130A** into gate pocket **26A**, as might otherwise happen if the gate pockets were configured to closely match the profile of gates **130**.

[00062] FIG. 7 illustrates a variant gate denoted by reference number **130C**, having a debris channel **27C** formed in its outer face, and there is no debris chamber **27** formed into the variant gate pocket **26C** associated with gate **130C**.

[00063] Preferably, each gate **130** and associated gate pocket **26** are relatively configured to form at least one gate pocket flow path (denoted by dotted line **141** in FIG. 3), such that fluid can flow out of gate pocket **26** into working fluid space **40** even when gate **130** is maximally deflected into gate pocket **26**. In the embodiment shown in FIG. 3, gate pocket flow path **141** includes an upstream portion **141U** co-extensive with gaps **136B** in thickened section **136**. Gates **130** and gate pockets **26** are configured so that when a gate **130** is maximally deflected into its associated gate pocket **26**, the gate's free longitudinal edge **139** is spaced from a

longitudinal wall **143** of the gate pocket to create a downstream portion **141D** of gate pocket flow path **141**, in fluid communication with working fluid space **40**.

[00064] As best understood with reference to FIGS. 2, 3, 7, and 8, with gates **130** being biased into substantially fluid-tight contact with rotor **120**, working fluid space **40** between rotor **120** and housing **20** is divided into longitudinal chambers **140** between rotor lobes **124** and adjacent gates **130**. Longitudinal chambers **140** are bound at either end by end plates **42U** and **42L**. In operation, a pressurized working fluid (such as drilling mud pumped from surface, as conceptually indicated by flow arrows **F** in various of the Figures) is introduced into rotary drive system **110** through inlet ports **116**, thus pressurizing (at any given time) one or more longitudinal chambers **140** and inducing rotation of rotor **120** (and mandrel **10** along with it) relative to housing **20**. Opposite the high pressure side of the lobe, the fluid is directed through fluid outlet ports **117** and onward through the bit.

[00065] As may be appreciated with reference to FIGS. 7 and 8 in particular, the configuration and volume of each longitudinal chamber **140** will change as rotor **120** rotates within and relative to housing **20**. For example, FIG. 8 illustrates a first longitudinal chamber denoted by reference character **140A** having a comparatively large volume, and a second longitudinal chamber denoted by reference character **140B** having a greatly reduced volume as a rotor lobe **124B** approaches the associated gate **130B**. Accordingly, fluid must be conveyed out of chambers **140** to prevent the build-up of excessive fluid pressure. This is accomplished in the illustrated embodiments by forming rotor **120** with pressure relief channels **121** to convey drilling fluid from chambers **140** to fluid outlet ports **117** (as may be seen in FIGS. 3 and 5).

[00066] The pivotability of gates **130** may be enabled by any suitable means, and embodiments within the scope of the present disclosure are not limited or restricted to the use of any particular pivoting means. To provide one non-limiting example, each gate **130** may be provided with a longitudinal pin bore **133** generally as shown in FIG. 3, for receiving elongate pivot pins, the ends of which are rotatably received within pockets or bearings associated with housing **20**. In the specifically illustrated embodiments, however, gates **130** are pivotably retained within cylindrical pivot pockets **25** formed in housing **20**. In the embodiment shown in FIG. 4, each gate **130** has an elongate convexly-cylindrical surface **138** which is matingly receivable within a corresponding cylindrical pivot pocket **25** to form a cylindrical pivot interface. In the illustrated embodiment, the cylindrical portions of pivot

pockets **25** extend around an arc greater than 180 degrees, such the pivot pockets fully retain the gates without need for pivot pins as such; in effect, the portions of gates **130** having cylindrical surfaces **138** function as pivot pins.

[00067] Preferably, gates **130** are provided with biasing means for biasing gates **130** away from housing **20** and into substantially sealing contact with rotor **120**. Such biasing means could comprise torsion rod springs, torsion coil springs, cam bodies, fluid pressure, or any other suitable mechanical or hydraulic means. In one embodiment, and with particular reference to FIGS. 4, 4A, and 4B, the biasing means may comprise torsion rods **50** disposed within pin bores **133** provided in gates **130** as shown in FIG. 3. Each torsion rod **50** has a central section **52** of circular cross-section extending between upper and lower end sections **54U** and **54L** which are configured for engagement with rotational restraint means.

[00068] In the embodiment shown in FIG. 4A, this rotational restraint is enabled by forming upper and lower end sections **54U** and **54L** to be square in cross-section. FIG. 4B illustrates a gate preload ring **60** having a plurality of square holes **62** corresponding in number to the number of gates **130** in the rotary drive system **110**, with square holes **62** being sized for mating engagement with upper end section **54U** of torsion rod **50**. In the embodiment shown in FIGS. 1 and 2, preload ring **60** is coaxially fixed to housing **20** immediately above end plate **42U** so as to be non-rotatable relative to housing **20**, such that in the assembled drive system upper end **54U** of each torsion rod **50**, projecting from the upper end of its associated pin bore **133** at upper end **131U** of the associated gate **130**, will be matingly disposed within one of the square holes **62** in gate preload ring **60**. The upper ends of torsion rods **50** will thus be restrained against rotation relative to housing **20**, but the upper ends of torsion rods **50** will be unrestrained against rotation within the pin bores **133** of their associated gates **130** and relative to the upper ends **131U** thereof.

[00069] However, as may be understood with reference to FIG. 4, the lower ends **54L** of torsion rods **50** will be restrained against rotation relative to the lower ends **131L** of their associated gates **130**. In this embodiment, lower end **131L** of gate **130** is fitted with a cap member **70** having a square hole **72** for matingly receiving the square lower end **54L** of a torsion rod **50**, thus effectively locking torsion rod **50** against rotation relative to lower end **131L** of gate **130**. However, lower end **131L** of gate **130** is unrestrained against rotation relative to housing **20**. Accordingly, gates **130** and torsion rods **50** can be assembled in rotary drive system **110** such that sealing surfaces **137** associated with the outer edges **139** of gates

130 will initially be closely adjacent to or in contact with the surface of rotor **120**. Optionally, torsion rods **50** may be installed with an initial pre-torque biasing gates **130** against rotor **120**. Pivoting deflection of gates **130** caused by fluid flow through rotary drive system **110** will induce torsional strain (or increase any initial torsional strain) in torsion rods **50**, thus positively biasing gates **130** toward rotor **120**.

[00070] The number of rotor lobes **124** and the number of gates **130** can vary. Preferably, however, there will always be at least one fluid inlet port **116** and at least one fluid outlet port **117** located between adjacent rotor lobes **124** at any given time, and at least one gate **130** sealing between adjacent fluid inlet and outlet ports at any given time.

[00071] Torque and speed outputs of rotary drive system **110** are dependent on the length and radial height (i.e., gate lift) of chambers **140**. For a given drive system length, a smaller gate lift produces higher rotational speed and lower torque. Conversely, a larger gate lift produces higher torque and lower rotational speed. In preferred embodiments, different configurations of gates **130** and rotor lobes **124**, with varying levels of gate lift, can be used to achieve broad torque and speed ranges as may be required for different drilling applications, from low-speed / high-torque performance drilling to high-speed turbine applications.

[00072] Bearing assembly **100** comprises multiple bearings for transferring the various axial and radial loads between mandrel **10** and housing **20** that occur during the drilling process. Thrust bearings **102** and **103** transfer on-bottom and off-bottom operating loads, respectively, while radial bearing **104** and **105** transfers radial loads between mandrel **10** and housing **20**. In preferred embodiments, the thrust bearings and radial bearings are mud-lubricated PDC (polycrystalline diamond compact) insert bearings, and a small portion of the drilling fluid is diverted through the bearings to provide lubrication and cooling. In other embodiments, other types of mud-lubricated bearings may be used, or one or more of the bearings may be oil-sealed.

[00073] In the embodiment shown in FIG. 2, radial loads are transferred from mandrel **10** to housing **20** through bearing **104**, not from mandrel **10** to rotor **120**. In alternative embodiments, however, radial loads could be transferred through rotor **120** if desired, by using rotor **120** itself as a radial bearing in lieu of radial bearing **104**.

[00074] In the alternative embodiment shown in FIG. 9A, the arrangement of the radial and axial bearings is changed such that radial loads are carried by mandrel **10** and preferably not transferred to rotor **120**. In this embodiment, bearing assembly **100** section comprises a

lower radial bearing **301** (analogous to radial bearing **105** in FIG. 2) and an additional radial bearing **303** below the rotary drive assembly, serving the same general function as radial bearing **104** in the embodiment shown in FIG. 2 but in a different location. Another set of bearings **304** and **305** may be used to locate rotor **120** both radially and axially.

[00075] In preferred embodiments, no elastomeric dynamic seals are used. Leakage is minimized by maintaining small amounts of clearance between components within drive system **110**. Small amounts of leakage will reduce the overall efficiency of the drive system, but that is acceptable for this application. Efficiency will still equal or exceed that of a Moineau power section. Moreover, with no elastomeric dynamic seals being used, the motor will be suitable for high-temperature/geothermal applications that Moineau power sections cannot withstand.

[00076] Notwithstanding the foregoing discussion of thrust bearings and radial bearings in downhole motor bearing sections, it is to be noted that the particular types and arrangements of bearings that may be used in bearing assemblies incorporating rotary drive systems in accordance with the present disclosure are not directly relevant to such rotary drive systems, and do not form part of the broadest embodiments thereof.

[00077] FIGS. 2 and 3 illustrate optional additional features that are beneficial but not essential to rotary drive systems in accordance with the present disclosure. One such optional feature is a flow control mechanism in the form of a relief valve **150** which protects the assembly from excessive torque loads by limiting the amount of pressure that can build up within the rotary drive assembly. Relief valve **150** provides this protection by allowing fluid to bypass the rotary drive system when the fluid pressure exceeds a pre-set pressure, through a downstream bore **154** in relief valve **150** discharging into mandrel bore **14**. The relief valve **150** illustrated in FIGS. 2 and 3 is only one non-limiting example of a device that may optionally be used to limit pressure build-up in rotary drive systems in accordance with the present disclosure.

[00078] FIG. 10 illustrates one embodiment of a mechanical relief valve system **350** which can be used to limit differential pressure across the rotary drive system by bypassing flow through rotor **120**. This same mechanism could also be used as a speed control to limit RPM to a pre-set limit. Relief valve system **350** works such that fluid flow **F** enters the mechanism from right to left (as viewed with reference to FIG. 10), with relief valve system **350** sealing off flow so that it is forced through the rotary drive mechanism's fluid inlet and outlet ports

and gates (as generally described previously herein). When the differential pressure across relief valve system **350** reaches a pre-set limit, a valve **325**, biased by a spring **321**, will move to the left allowing a portion of the flow to bypass the rotary drive system through the center of rotor **120**. Valve **325** could alternatively be biased mechanically or hydraulically.

[00079] FIG. 11 illustrates an alternative mechanical relief valve assembly **350A**, which is operable in largely the same manner as described above with respect to relief valve system **350** shown in FIG. 10. Relief valve assembly **350A** works such that flow fluid enters the device from right to left, with relief valve assembly **350A** sealing off flow so that it is forced through the rotary drive mechanism's fluid inlet and exit ports and gates. When differential pressure reaches a pre-set limit, valve **325A**, biased by a spring **321A**, will move to the left allowing a portion of the flow to bypass the rotary drive system through the center of rotor **120**. Valve **325A** could alternatively be biased mechanically or hydraulically.

[00080] Alternatively, a mechanism similar to the two-speed motor disclosed in U.S. Patent No. 7,523,792 (which is hereby incorporated by reference in its entirety) could also be used to allow an operator two different speed ranges at a given flow rate using the same rotary drive geometry. This would be accomplished by turning fluid flow on and off. Alternatively, this could be accomplished by an electronically-controlled valve system. This valve system could react to drilling conditions such as vibration, bit whirl, and stick slip, and/or it could be communicated with, either from surface or from a downhole signal generator, to change the amount of fluid bypass through rotor **120** in the rotary drive system.

[00081] Notwithstanding the preceding discussion, it is not essential to limit differential pressure across rotary drive systems in accordance with the present disclosure. Alternative embodiments may use other forms of flow control such as, by way of non-limiting example, a solid plate (either integral with either the mandrel or the rotor, or a separately-sealed component) to separate flow between the fluid inlet and outlet ports. Alternative embodiments may use a nozzle to continuously bypass a portion of the flow through the rotor in order to reduce the rotary speed of the drive section. Alternative embodiments may also use a burst disc to separate flow between inlet and outlet ports. In the event that the burst disc capacity is exceeded and the disc ruptures, all or a portion of the flow would subsequently bypass through the rotor. Alternative embodiments may incorporate a flow diverter as described in U.S. Patent No. 6,976,832 to evenly distribute fluid intake and outlet flow along all or a portion of the length of the drive section.

[00082] Alternative embodiments may relieve pressure by bypassing drilling fluid directly to the annulus between housing **20** and the wellbore, or, alternatively, between bent housing **200** and the wellbore.

[00083] Another optional feature, illustrated in FIG. 2), is the use of sealing plates **160**, which comprise mating wear-resistant surfaces that leak only a small amount of drilling fluid, so that nearly all of the fluid diverted to lubricate and cool the bearings is directed back through the mandrel and onward through the bit. Rotary seals could be used in place of sealing plates **160**; alternatively, a flow restrictor of conventional type or diamond material (e.g., PDC) could be used.

[00084] In an alternative embodiment, the design could be changed to allow rotation of the stator section (housing **20** with gates **130**) relative to rotor **120** and mandrel **10**. This could be achieved, for example, by modifying the embodiments shown in FIGS. 1, 2, 9, and 9A. In such variant configurations, mandrel **10** would attach to the drill string, which would reverse the fluid flow path; i.e., whereas the fluid flow path **F** as shown in FIGS. 1, 2, and 9, is from right to left, the fluid flow path in the variant configurations would be from left to right, with the fluid inlet and outlet ports being suitably configured for this reversed fluid flow path. Having reference to FIGS. 2 and 9, this could necessitate design changes as follows:

- First, the bent sub could be moved to the left (i.e., lower) side of the mandrel.
- A suitable bit box sub would need to be added in place of the housing **200** to allow connection to the drill bit (alternatively, this connection could be a pin connection).
- The bypass valves would also need to be “flipped” to allow flow to bypass from left to right.

It will be readily apparent to those skilled in the art that driveshafts / clutches, additional stages in series or parallel, inlet and outlet ports, gate orientation, and bearings could be moved above or below the power section when holding the mandrel stationary and allowing the stator section (housing) to rotate.

[00085] Alternative embodiments may use rotary drive systems generally as disclosed in any of U.S. Patents No. 6,280,169, No. 6,468,061, and No. 6,939,117, in combination with similar coupling means within the drilling motor, and similar arrangements of bearings.

These systems utilize similar principles of operation, but with alternative forms of the gate/lobe system, such as radially-actuating gates as opposed to pivoting gates, or pivoting gates connected to the mandrel and engageable by lobes formed on the bearing section housing.

[00086] For example, referring to FIG. 3, housing **20**, gates **130**, and torsion rods **50** could be replaced with the necessary components from the system of radially-actuating gates illustrated in Figure 33 in U.S. Patent No. 6,280,169. As another example, referring again to FIG. 3, housing **20**, gates **130**, torsion rods **50**, and rotor **120** could be replaced with the necessary components from the system illustrated in Figure 9A in U.S. Patent No. 6,939,117, wherein the lobes are fixed to the housing and the gates are mounted about the outer surface of the mandrel.

[00087] Having regard to the preceding discussion, it is to be appreciated that concentric rotary drive systems in accordance with the present disclosure are not limited to embodiments in which the gates are mounted to the housing (and deflectable into gate pockets formed in the housing) and in which gate-actuating lobes are incorporated into a mandrel concentrically rotatable within the housing. The present disclosure also extends to alternative embodiments having gates mounted to the mandrel (and deflectable into gate pockets formed in the mandrel) and in which gate-actuating lobes are incorporated into the housing, and also to embodiments incorporating radially-actuating gates.

[00088] Accordingly, one category of concentric rotary drive systems in accordance with the present disclosure can be broadly described as comprising:

- a first body and a second body, with a selected one of the bodies being coaxially disposed inside the other body to define a working fluid space therebetween, and with the second body being rotatable relative to the first body about a rotational axis;
- at least one gate pivotably supported by a selected one of the first and second bodies, and pivotable about a pivot axis parallel to the rotational axis; and
- at least one lobe provided on the body not supporting the at least one gate, with the at least one lobe being configured to contact the at least one gate during rotation of the second body.

[00089] Therefore, the component referenced previously in this Detailed Description as

“housing 20” could, in alternative embodiments, be characterized as either the “first body” or the “second body”, with the component referenced as rotor 120 being characterized as either the “second body” or the “first body”. It will also be appreciated that in certain alternative embodiments the rotary drive system could be configured such that the selected body coaxially disposed within the other body could be non-rotating relative to the drill string; i.e., the other (or outer) body would be rotatable relative to the “selected” (i.e., inner) body. Persons skilled in the art will appreciate that such alternative embodiments can be put in to practice on the basis of the present disclosure, modified as a given embodiment may require having reference to the information provided herein and common general knowledge in the art, and without need for specific illustration, significant experimentation, or inventive input.

[00090] FIGS. 13 and 13A illustrate an alternative embodiment 500 of a downhole motor incorporating a concentric rotary drive system 110 in accordance with the present disclosure. In this variant embodiment, the bent sub 210 is located below rotary drive system 110, and rotary drive system 110 is operatively connected to the motor’s bearing section 100 by a drive shaft 510. Because rotary drive system 110 does not operate eccentrically like a conventional downhole motor drive section, drive shaft 510 requires a universal joint (U-joint) 515 only at its lower end 510L, where it engages a lower drive shaft housing 520 coupled to the upper end 10U of mandrel 10 of bearing section 100, adjacent to bent sub 210. At its upper end 510U, drive shaft 510 is connected rigidly and coaxially to the lower end 120L of rotor 120, by any functionally suitable means.

[00091] FIG. 14 illustrates a further alternative embodiment 600 of a downhole motor incorporating a concentric rotary drive system in accordance with the present disclosure. In this embodiment, rotary drive system 110 is connected to a conventional bearing section 100 by means of a conventional drive shaft 610 having upper and lower U-joints 615U and 615L at its upper and lower ends 610U and 610L. Lower U-joint 615L engages a lower drive shaft housing 620L coupled to the upper end 10U of mandrel 10, similar to the embodiment shown in FIGS. 13 and 13A. In this embodiment, bent sub 210 is located approximately midway between U-joints 615U and 615L.

[00092] Upper U-joint 615U engages an upper drive shaft housing 620U which in turn is connected rigidly and coaxially to lower end 120L of rotor 120. In the specific embodiment shown in FIG. 14, upper drive shaft housing 620U connects to rotor 120 by means of a threaded and splined coupling 650 generally similar to coupling 410 shown in FIGS. 12, 12A,

and 12B. However, this is by way of non-limiting example only, and the connection between upper drive shaft housing **620U** and rotor **120** could alternatively be effected by any functionally suitable means.

[00093] The embodiments of rotary drive system **110** illustrated in the Figures may be referred to as a single-stage drive system; i.e., having a single set of gates **130** associated with a lobed rotor **120**. However, alternative embodiments of rotary drive system **110** may incorporate multiple-stage drives as necessary or desirable to achieve required performance.

[00094] For embodiments having multiple power sections aligned in series, the power sections can be coupled by means of a splined and/or threaded connection, such as, for example, the connection illustrated in FIGS. 12, 12A, and 12B. Alternatively the power sections could be coupled by means of an arrangement as in the exemplary embodiment in FIG. 9, with component **129** being used on the right end of the rotor to connect to another power section of similar type, or to connect a power section as disclosed herein to a conventional Moineau or turbine-type drive system. This arrangement could also use a driveshaft between the rotary drive system and a Moineau or turbine drive system. This arrangement would allow for increased torque output, but with higher differential pressure than using just one power section.

[00095] In further alternative embodiments, a gear box could be incorporated into the coupling between two power sections coupled in series.

[00096] For embodiments having multiple power sections arranged to be run in parallel, two power sections as disclosed herein could be run end to end and coupled by means of splined, threaded, or clutch-type engagement as stated above. A flow diverter would be needed to send a portion of the flow past the first stage to the second stage only and then on to the bit. This flow diverter would allow flow to enter either the first stage or the second stage only, and then exit to the bit without entering the other stage. This arrangement would allow increased torque output at the same differential pressure across the rotary drive system.

[00097] It will be readily appreciated by those skilled in the art that various modifications to embodiments in accordance with the present disclosure may be devised without departing from the scope and teaching of the present teachings, including modifications which may use equivalent structures or materials hereafter conceived or developed. It is to be especially understood that the scope of the present disclosure is not intended to be limited to described or illustrated embodiments, and that the substitution of a variant of a claimed element or

feature, without any substantial resultant change in functionality, will not constitute a departure from the scope of the disclosure. It is also to be appreciated that the different teachings of the embodiments described and discussed herein may be employed separately or in any suitable combination to produce desired results.

[00098] In this patent document, any form of the word “comprise” is to be understood in its non-limiting sense to mean that any item following such word is included, but items not specifically mentioned are not excluded. A reference to an element by the indefinite article "a" does not exclude the possibility that more than one of the element is present, unless the context clearly requires that there be one and only one such element.

[00099] Any use of any form of the terms "connect", "engage", "couple", "attach", or any other term describing an interaction between elements is not meant to limit the interaction to direct interaction between the subject elements, and may also include indirect interaction between the elements such as through secondary or intermediary structure.

[000100] Relational terms such as “parallel”, “concentric”, and “coaxial” are not intended to denote or require absolute mathematical or geometrical precision. Accordingly, such terms are to be understood as denoting or requiring substantial precision only (e.g., “substantially parallel”) unless the context clearly requires otherwise.

[000101] Wherever used in this document, the terms “typical” and “typically” are to be interpreted in the sense of representative of common usage or practice, and are not to be interpreted as implying essentiality or invariability.

CLAIMS

WHAT IS CLAIMED IS:

1. A drilling motor comprising:
 - (a) a bearing assembly comprising: a generally cylindrical housing having an upper end and a lower end; a generally cylindrical mandrel having an upper end, a lower end, and a longitudinal bore, said mandrel being coaxially disposed within the housing so as to be rotatable relative thereto about a rotational axis; radial bearing means disposed in an annular space between the housing and the mandrel; and thrust bearing means disposed in an annular space between the housing and the mandrel;
 - (b) a generally cylindrical rotor having an upper end, a lower end, and a longitudinal bore, said rotor being coaxially disposed within the housing so as to define a generally annular working fluid space therebetween, with said rotor operatively engaging the mandrel so as to be rotatable therewith;
 - (c) a plurality of elongate gates;
 - (d) at least one axially-oriented lobe engageable with the gates during relative rotation between the rotor and the housing;
 - (e) one or more fluid inlets allowing fluid flow from an upper region of the rotor bore into the working fluid space; and
 - (f) one or more fluid outlets allowing fluid flow out of the working fluid space into a lower region of the rotor bore;

wherein the drilling motor defines a fluid path including the fluid inlets, the working fluid space, and the fluid outlets, such that a flow of a working fluid along the fluid path will cause relative rotation between the rotor and the housing, thereby causing each lobe to deflect each gate in sequence.

2. A drilling motor as in claim 1 wherein the gates are supported by the housing and pivotable about a pivot axis parallel to the rotational axis.
3. A drilling motor as in claim 1 wherein the gates are supported by the rotor and pivotable about a pivot axis parallel to the rotational axis.

4. A drilling motor as in claim 1 wherein the gates are radially-actuating and supported by the housing.
5. A drilling motor as in claim 1 wherein the gates are radially-actuating and supported by the rotor.
6. A drilling motor as in claim 1, further comprising biasing means associated with the gates.
7. A drilling motor as in claim 1 wherein the housing incorporates a bent sub located above the rotor.
8. A drilling motor as in claim 1 wherein the mandrel engages the rotor so as to be coaxially rotatable therewith.
9. A drilling motor as in claim 8, wherein the mandrel engages the rotor by means of a splined connection, with an upper portion of the mandrel coaxially disposed within the bore of the rotor.
10. A drilling motor as in claim 8, wherein the upper end of the mandrel engages the lower end of the rotor by means of respective mating lugs provided on the upper end of the mandrel and the lower end of the rotor.
11. A drilling motor as in claim 8, wherein the mandrel engages the rotor by means of a clutch mechanism disposed between the upper end of the mandrel and the lower end of the rotor.
12. A drilling motor as in claim 8, wherein the mandrel engages the rotor by means of a gear box disposed between the upper end of the mandrel and the lower end of the rotor.
13. A drilling motor as in claim 8, wherein the mandrel engages the rotor by means of a generally cylindrical coupling having a lower section with internal threading matingly engageable with external threading on the upper end of the mandrel, and having an upper section with internal splines matingly engageable with external splines on the lower end of the rotor.
14. A drilling motor as in claim 1 wherein the mandrel engages the rotor by means of a drive shaft, said drive shaft having an upper end rigidly and coaxially engaging the lower end

of the rotor, and a lower end incorporating a universal joint which engages a drive shaft housing coupled to the upper end of the mandrel.

15. A drilling motor as in claim 14 wherein the housing incorporates a bent sub positioned below the lower end of the rotor.

16. A drilling motor as in claim 15 wherein the bent sub is positioned proximal to the universal joint.

17. A drilling motor as in claim 1 wherein the mandrel engages the rotor by means of a drive shaft, said drive shaft having an upper end incorporating an upper universal joint engaging an upper drive shaft housing coupled to the lower end of the rotor, and a lower end incorporating a lower universal joint which engages a drive shaft housing coupled to the upper end of the mandrel.

18. A drilling motor as in claim 17 wherein the housing incorporates a bent sub positioned between the upper and lower universal joints.

19. A drilling motor as in claim 1 wherein the radial bearing means is adapted to transfer radial loads from the mandrel to the housing through the rotor.

20. A drilling motor as in claim 19 wherein the rotor is adapted to serve as a radial bearing.

21. A drilling motor as in claim 1, further comprising flow control means, for altering the characteristics of fluid flow through the motor to regulate the rotational speed of the motor.

22. A drilling motor as in claim 21, wherein the flow control means is configured to allow fluid to bypass the working fluid space when the pressure differential across the working fluid space exceeds a pre-set value.

23. A drilling motor as in claim 21, wherein the flow control means comprises a relief valve coaxially disposed within the rotor.

24. A drilling motor as in claim 21, wherein the flow control means comprises a plate integral with a selected one of the mandrel and the rotor, and positioned to separate flow between the fluid inlets and the fluid outlets.

25. A drilling motor as in claim 21, wherein the flow control means comprises a nozzle for continuously bypassing a portion of the fluid flow through the rotor.

26. A drilling motor as in claim 21, wherein the flow control means comprises a burst disc positioned to separate flow between the fluid inlets and the fluid outlets.
27. A drilling motor as in claim 21, wherein the flow control means comprises means for diverting fluid to the exterior of the housing.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 4A




FIG. 4B




FIG. 5




FIG. 6




FIG. 7




FIG. 8

10/18




FIG. 9




FIG. 9A




FIG. 10




FIG. 11




FIG. 12

15/18




FIG. 12A




FIG. 12B

500 →




FIG. 13




FIG. 13A




FIG. 14