



US010078922B2

(12) **United States Patent**  
**Patel**

(10) **Patent No.:** **US 10,078,922 B2**

(45) **Date of Patent:** **Sep. 18, 2018**

(54) **EYE TRACKING FOR DISPLAY  
RESOLUTION ADJUSTMENT IN A VIRTUAL  
REALITY SYSTEM**

2310/04 (2013.01); G09G 2340/0407  
(2013.01); G09G 2354/00 (2013.01)

(58) **Field of Classification Search**

CPC ..... G06K 9/00664-9/00704; G06F 3/0481;  
G06F 3/04817; G06F 9/4443; G06F  
3/04847; G06F 11/3664; G06T 19/00;  
G06T 17/00; H04N 5/272; G09G  
2340/0407; G09G 5/006; G09G  
2340/0421; G09G 2340/0414; G09G  
5/391; A63F 13/10

See application file for complete search history.

(71) Applicant: **Oculus VR, LLC**, Menlo Park, CA  
(US)

(72) Inventor: **Nirav Rajendra Patel**, San Francisco,  
CA (US)

(73) Assignee: **Oculus VR, LLC**, Menlo Park, CA  
(US)

(\* ) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

(56)

**References Cited**

U.S. PATENT DOCUMENTS

8,004,540 B1 \* 8/2011 Munter ..... G06F 3/1438  
345/2.2  
2002/0167461 A1 11/2002 Bronson  
(Continued)

(21) Appl. No.: **15/068,380**

(22) Filed: **Mar. 11, 2016**

(65) **Prior Publication Data**

US 2016/0267716 A1 Sep. 15, 2016

**Related U.S. Application Data**

(60) Provisional application No. 62/131,705, filed on Mar.  
11, 2015.

(51) **Int. Cl.**

**G06T 19/00** (2011.01)  
**G06F 3/01** (2006.01)  
**G06T 19/20** (2011.01)  
**G09G 3/3258** (2016.01)  
**G09G 5/373** (2006.01)  
**G09G 5/395** (2006.01)

(52) **U.S. Cl.**

CPC ..... **G06T 19/20** (2013.01); **G06F 3/013**  
(2013.01); **G09G 3/3258** (2013.01); **G09G**  
**5/373** (2013.01); **G09G 5/395** (2013.01); **G06T**  
**2219/2016** (2013.01); **G09G 2310/0224**  
(2013.01); **G09G 2310/0291** (2013.01); **G09G**

OTHER PUBLICATIONS

Reingold; Eyal; 2003; Gaze-Contingent Multiresolutional Displays:  
An Integrative Review; pp. 307-327.\*

*Primary Examiner* — Todd Buttram


(74) *Attorney, Agent, or Firm* — Fenwick & West LLP

(57)

**ABSTRACT**

A virtual reality system and a display device that can be  
used, for example, as part of the virtual reality system. The  
display device can have more than one data driver, such as  
an even row data driver and an odd row data driver. The  
display device can have a configurable resolution such that  
one region of the display device operates at full resolution  
while another region of the display device operates at a  
reduced resolution. The virtual reality system can also track  
an eye gaze and adjust the full resolution region of the  
display device to track the eye gaze.

**12 Claims, 17 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

2008/0278682	A1	11/2008	Huxlin et al.
2010/0253708	A1	10/2010	Kasai
2014/0077725	A1	3/2014	Lee et al.
2015/0348232	A1	12/2015	Biggs et al.
2016/0063961	A1	3/2016	Pyo et al.
2016/0155405	A1	6/2016	Kim et al.
2016/0240013	A1*	8/2016	Spitzer ..... G06F 3/013

\* cited by examiner




FIG. 1




FIG. 2A




FIG. 2B




FIG. 3





FIG. 3A



320

FIG. 3B




FIG. 4




FIG. 5




FIG. 6A




FIG. 6B




FIG. 7




FIG. 8A




FIG. 8B




FIG. 9A




FIG. 9B




FIG. 9C




FIG. 9D




FIG. 9E




FIG. 9F




FIG. 9G




FIG. 9H

FIG. 10A





FIG. 10B






FIG. 11




FIG. 12

1

## EYE TRACKING FOR DISPLAY RESOLUTION ADJUSTMENT IN A VIRTUAL REALITY SYSTEM

### CROSS REFERENCE TO RELATED APPLICATIONS

The present application claims priority from U.S. Provisional Patent Application No. 62/131,705, filed on Mar. 11, 2015, the contents of which are incorporated by reference herein in their entirety.

### BACKGROUND

The present disclosure generally relates to virtual reality systems and display operation in a virtual reality system.

Electronic displays include a plurality of pixels, which may each include a plurality of sub-pixels (e.g., a red sub-pixel, a green sub-pixel, etc.). Most displays are designed for use with cellphones, tablets and televisions. However, the characteristics of most displays are not ideal for use in a virtual reality (VR) headset where performance requirements (e.g. resolution and refresh rate) are more stringent than in typical displays.

### SUMMARY

In one embodiment, a display device comprises a display screen. The display screen includes a first pixel row of first pixels having respective storage capacitors, the first pixels connected to a first scan line, a second pixel row of second pixels having respective storage capacitors, the second pixels connected to a second scan line, first data lines connected to the first pixel row, and second data lines connected to the second pixel row. Additionally, a first data driver circuit drives the first pixel row via the first data lines. A second data driver circuit drives the second pixel row via the second data lines.

In one embodiment, a display device comprises a display screen having a plurality of pixels organized into pixel columns and pixel rows. A resolution circuit stores resolution configuration data indicative of a location of a first region of the display screen operating in reduced resolution and indicative of a location of a second region of the display screen operating in full resolution. A selective scaling circuit receives image data and processes the image data based on the resolution configuration data, the selective scaling circuit upscaling a first portion of the image data for the first region of the display screen and not upscaling a second portion of the image data for the second region of the display screen.

In one embodiment, a virtual reality system, comprises a virtual reality headset. The headset comprises a display having a first region operating in reduced resolution and a second region operating in full resolution. The headset also comprises an eye tracking sensor to generate gaze data indicative of a gaze direction of the eye. The virtual reality system adjusts a location of the second region operating in full resolution based on the gaze direction of the eye.

### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of a virtual reality system environment, according to an embodiment.

FIG. 2A is a wire diagram of a virtual reality headset, in accordance with an embodiment.

FIG. 2B is a cross section of the front rigid body of the embodiment of a VR headset shown in FIG. 2A.

2

FIG. 3 is an electronic display with dual row drivers, according to an embodiment.

FIG. 3A is the display from FIG. 3 where only the odd pixel rows are illustrated, according to an embodiment.

FIG. 3B is the display from FIG. 3 where only the even pixel rows are illustrated, according to an embodiment.

FIG. 4 is circuit diagram of a pixel P, according to an embodiment.

FIG. 5 is a timing diagram illustrating operation of the scan driver and data drivers, according to an embodiment.

FIG. 6A is a diagram illustrating a display screen, according to an embodiment.

FIG. 6B is a diagram illustrating a display screen with configurable effective resolution.

FIG. 7 illustrates a timing controller and data drivers supporting configurable effective resolution, according to an embodiment.

FIG. 8A illustrates selective scaling circuitry supporting configurable vertical resolution, according to one specific embodiment.

FIG. 8B illustrates selective scaling circuitry supporting configurable horizontal and vertical resolution, according to another embodiment.

FIG. 9A-9H illustrate operation of the display when operating in different resolution modes, according to an embodiment.

FIGS. 10A and 10B are diagrams illustrating the use of eye tracking to control a full resolution region of the display, according to an embodiment.

FIG. 11 is an interaction diagram for a virtual reality system that uses eye tracking to control a full resolution region of the display, according to an embodiment.

FIG. 12 illustrates the hardware architecture of computing device, according to one embodiment.

The figures depict embodiments of the present disclosure for purposes of illustration only. One skilled in the art will readily recognize from the following description that alternative embodiments of the structures and methods illustrated herein may be employed without departing from the principles, or benefits touted, of the disclosure described herein.

### DETAILED DESCRIPTION

#### System Overview

FIG. 1 is a block diagram of a virtual reality (VR) system environment 100, according to an embodiment. The system environment 100 shown by FIG. 1 comprises a VR headset 105 and a VR input interface 140 that are each coupled to the VR console 110 through wired connections 190 and 192. For example, the wired connection 190 can be a video cable coupling the VR headset 105 to the VR console 110. In other embodiments the devices may communicate wirelessly instead of through wired connections.

While FIG. 1 shows an example system 100 including one VR headset 105 and one VR input interface 140, in other embodiments any number of these components may be included in the system 100. For example, there may be multiple VR headsets 105 each having an associated VR input interface 140, with each VR headset 105 and VR input interface 140 communicating with the VR console 110. In alternative configurations, different and/or additional components may be included in the system environment 100.

The VR headset 105 is a head-mounted device that presents media to a user and is an example of a display device. Examples of media presented by the VR head set include one or more images, video, audio, or some combination thereof. In some embodiments, audio is presented via

an external device (e.g., speakers and/or headphones) that receives audio information from the VR headset **105**, the VR console **110**, or both, and presents audio data based on the audio information. An embodiment of the VR headset **105** is further described below in conjunction with FIGS. **2A** and **2B**. The VR headset **105** may comprise one or more rigid bodies, which may be rigidly or non-rigidly coupled to each other together. A rigid coupling between rigid bodies causes the coupled rigid bodies to act as a single rigid entity. In contrast, a non-rigid coupling between rigid bodies allows the rigid bodies to move relative to each other.

The VR headset **105** includes an electronic display **115**, eye tracking sensor **118**, and communication interface **125**. The VR headset **105** may include other components not shown in FIG. **100**, such as position sensors and location sensors (not shown). The interface **125** sends data to and receives data from the virtual reality console via the wired connection **190**.

The electronic display **115** displays images to the user in accordance with image data received from the VR console **110**. In various embodiments, the electronic display **115** may comprise a single electronic display or multiple electronic displays (e.g., a display for each eye of a user). Examples of the electronic display **115** include: an organic light emitting diode (OLED) display, a liquid crystal display (LCD), or other types of displays.

The electronic display **115** includes a display screen having a matrix of pixels organized into pixel columns and pixel rows. The electronic display **115** also includes display circuitry that receives image data from the virtual reality console **110** and generates pixel driving signals in order to produce visual images on the display screen from the image data.

In one embodiment, the electronic display **115** includes twice the number of data lines and data drivers of a typical display. The increased data lines and connection of the data lines to the pixels allows the refresh rate of the electronic display **115** to be doubled in frequency. The higher refresh rates increase the realism of moving images shown on the electronic display **115**. Similarly, the refresh rate can be maintained while increasing the time allowed per row to charge the pixel capacitors.

In one embodiment, the electronic display **115** can be selectively configured to have a higher effective resolution in a section of the screen that matches the direction of the user's gaze, while having a lower effective resolution in other sections of the screen not being viewed by a user. This reduces the required bandwidth needed to provide image data from the virtual reality console **110** to the virtual reality headset **105** via the wired connection **190** without any perceptible loss in image quality.

Eye tracking sensor **118** tracks the gaze of a user's eye and generates gaze data indicative of gaze direction of the user's eye. One example of an eye tracking sensor **118** is a camera that captures infrared light reflected off the pupil of the eye with an image sensor, and which generates gaze data in the form of captured images. The gaze data is then transmitted to the virtual reality console **110**, where the images are processed by the eye tracking module **150** to extract gaze direction from changes in reflections. The gaze direction is then used to selectively adjust the region of the display **115** that is to have higher resolution. The higher resolution region is continuously moved to track the user's gaze direction. In another embodiment, the eye tracking module **150** may be located within the virtual reality headset **105** such that the gaze direction is determined within the headset **105** itself. Other examples of eye tracking sensors **118** are

also possible, such as eye-attached tracking sensors and electric potential measurement sensors.

The VR input interface **140** is a device that allows a user to send action requests to the VR console **110**. An action request is a request to perform a particular action. For example, an action request may be to start or end an application or to perform a particular action within the application. The VR input interface **140** may include one or more input devices. Example input devices include: a keyboard, a mouse, a game controller, or any other suitable device for receiving action requests and communicating the received action requests to the VR console **110**. An action request received by the VR input interface **140** is communicated to the VR console **110**, which performs an action corresponding to the action request. In some embodiments, the VR input interface **140** may provide haptic feedback to the user in accordance with instructions received from the VR console **110**. For example, haptic feedback is provided when an action request is received, or the VR console **110** communicates instructions to the VR input interface **140** causing the VR input interface **140** to generate haptic feedback when the VR console **110** performs an action.

The VR console **110** provides media to the VR headset **105** for presentation to the user in accordance with information received from one or more of: the VR headset **105**, and the VR input interface **140**. Examples of VR consoles **110** include computers, video game consoles, and other computing devices.

In the example shown in FIG. **1**, the VR console **110** includes an interface **142**, an application store **145**, an eye tracking module **150**, and a virtual reality (VR) engine module **155**. The interface **142** sends data to and receives data (e.g. image data, gaze data) from the virtual reality headset **105** via the wired connection **190**.

The application store **145** stores one or more applications for execution by the VR console **110**. An application is a group of instructions, that when executed by a processor, generates content for presentation to the user. Content generated by an application may be in response to inputs received from the user via movement of the VR headset **105** or the VR interface device **140**. Examples of applications include: gaming applications, conferencing applications, video playback application, or other suitable applications.

The VR engine module **155** executes applications within the system environment **100** and receives gaze direction information from the eye tracking module **150**. Based on the received information, the VR engine **155** determines how content images are to be processed and provided to the VR headset **105**.

In one embodiment, the VR engine **155** determines, from the user's gaze direction, which region of the display **105** should be high resolution in order to match the user's gaze. For example, the VR engine **155** can estimate which pixels of the display **115** the gaze is focused on, and use those pixels as the center of the high resolution region (e.g. full resolution region). The VR engine **155** then generates resolution configuration data that specifies the location of the reduced resolution and full resolution regions of the display **115**. This resolution configuration data is provided to the VR headset **105** via interface **142** so that the display **115** can be configured to support reduced and full resolution regions. The VR engine **155** then generates and provides image data to the virtual reality headset **105** for display in the reduced and full resolution versions. The location of the full resolution window is adjusted to match the user's gaze such that the portion of the display **115** being viewed by the user always appears to be clear and sharp.

Additionally, the VR engine module **155** performs an action within an application executing on the VR console **110** in response to an action request received from the VR input interface **140** and provides feedback to the user that the action was performed. The provided feedback may be visual or audible feedback via the VR headset **105** or haptic feedback via the VR input interface **140**.

FIG. 2A is a wire diagram of a virtual reality (VR) headset **105**, in accordance with an embodiment. The VR headset **105** includes a front rigid body **205** and a band **210**. The front rigid body **205** includes one or more electronic display elements of the electronic display **115** (not shown) and the eye tracking sensors **118** (not shown). The front rigid body **205** includes a front side **220a**, a top side **220b**, a bottom side **220c**, a right side **220d**, and a left side **220e**.

FIG. 2B is a cross section of the front rigid body **205** of the embodiment of a VR headset **105** shown in FIG. 2A. The front rigid body **205** includes an electronic display **115**, and an eye tracking sensor **118** that generates gaze data indicative of the direction of the eye's **245** gaze. The eye tracking sensor **118** is pointed at the pupil **250** such that movements of the pupil **118** can be captured. Some components may not be shown in FIG. 2B, such as an optical block between the eye **245** and display **115** that bends the light from the display **115**.

#### Dual Data Driver Display

FIG. 3 is an electronic display **115** with dual row drivers, according to an embodiment. The electronic display **115** includes an active matrix display screen **310** and display circuitry **320**. The display screen **310** includes an active matrix of pixels **P** organized in pixel rows (R1-R4) and pixel columns. Although not shown in FIG. 3, generally each pixel **P** includes multiple sub-pixels producing red, green, and blue light and there would be additional data lines **DL** connected to each of the sub-pixels.

The display screen **310** includes data lines **DL** and scan lines **SL** connected to the pixels **P**. Data lines **DL** carry data voltages to the pixels **P** that represent target brightness levels of the pixels. Scan lines **SL** carry scan pulses to the pixels **P** that scan the data voltages into the pixels **P**. Scan lines **SL** may also be referred to as gate lines. Only 16 pixels **P**, 4 scan lines **SL** and 8 data lines **DL** are shown in FIG. 3 for ease of illustration. However, the display screen **310** typically has a larger number of pixels **P** (e.g. millions of pixels **P**), scan lines **SL** and data lines **DL**.

Referring briefly to FIG. 4, shown is a pixel **P** of the active matrix display screen **310**, according to an embodiment. Pixel **P** can represent any of the pixels **P** from FIG. 3. The pixel **P** is an OLED pixel. The pixel **P** includes a scan transistor **T1**, a storage capacitor **C**, a driving transistor **Td** and an OLED **D1**. When a scan pulse is applied from the scan line **SL** to the gate of scan transistor **T1**, scan transistor **T1** turns on and the data voltage on the data line **DL** is latched or scanned into the storage capacitor **C**. The data voltage stored in capacitor **C** turns on the driving transistor **T2**, which drives current through the OLED **D1** in accordance with the level of the data voltage and causes the OLED **D1** to emit light. In other embodiments the pixel **P** may have a different structure that uses additional transistors and electrical components other than those shown in FIG. 4.

Referring back to FIG. 3, each data line **DL** is connected to only half the pixel rows (R1-R4). The data lines **DL** can be divided into two subsets: odd data lines (DL-1, DL3, etc) and even data lines (DL-2, DL-4, etc). The two odd and even data lines alternate with each other. Odd data lines (DL-1, DL-3, etc) are connected only to odd pixel rows (R1, R3). The odd data lines (DL-1-DL3, etc) are not connected to

even pixel rows (R2, R4), and are therefore electrically isolated from the even pixel rows (R2, R4). Even data lines (DL-2, DL-4, etc) are connected only to even pixel rows (R2, R4) but not odd pixel rows (R1, R3), and are therefore electrically isolated from the even pixel rows (R2, R4).

In other words, each pixel column is driven by a pair of data lines **DL**, and the pixels **P** in the column are connected in alternating manner between the pair of data lines **DL**. For example, data line **DL-1** is connected to the pixels **P** in the odd rows (e.g. SL-1, SL-3). Data line **DL-2** is only connected to the pixels **P** in the even rows (e.g. SL-2, SL-4).

The display screen **310** includes two data drivers and twice as many data lines **DL** as conventional displays because each data line **DL** is only connected to half the pixels **P** in a column, such as the odd pixel rows or the even pixel rows, but not both. By including twice as many data lines **DL**, the refresh rate of the display can be doubled because each subsequent pixel row can be scanned before the previous pixel row has completed its scanning. Alternatively, the scan time for each pixel row can be increased while maintaining the same refresh rate.

FIG. 3A is the display from FIG. 3 where only the odd pixel rows are illustrated, according to an embodiment. The even pixel rows are hidden for ease of explanation. Odd scan line **SL-1** is connected to all of the pixels in one odd pixel row **R1**. Odd scan line **SL-3** is connected to all of the pixels in another odd pixel row **R3**. The odd data lines (DL-1, DL-3, etc) are connected to all of the odd pixel rows (R1, R3), but are not connected to any of the even pixel rows.

FIG. 3B is the display from FIG. 3 where only the even pixel rows are illustrated, according to an embodiment. The odd pixel rows are hidden for ease of explanation. Even scan line **SL-2** is connected to all of the pixels in one even pixel row **R2**. Even scan line **SL-4** is connected to all of the pixels in another even pixel row **R4**. The even data lines (DL-2, DL-4, etc) are connected to all of the even pixel rows (R2, R4), but are not connected to any of the odd pixel rows.

Referring back to FIG. 3, the display circuitry **320** includes a timing controller **330**, an odd row data driver **350**, an even row data driver **352** and a scan driver **340**. The timing controller **330**, odd row data driver **350**, even row data driver **352**, and scan driver **340** may all reside on a single integrated circuit (IC), or on separate ICs. In some embodiments the scan driver **340** may be fabricated with thin film transistors and be separate from the other circuits. In one embodiment, odd row data driver **350** and even row data driver **352** are located on opposite sides of the display screen **310**. Odd row data driver **350** is located at the top of the display screen, and even row data driver **352** is located on the bottom side of the display screen **310**.

The timing controller **330** receives image data **370** and allocates rows of the image data **370** between the odd data driver **350** and even data driver **352**. Odd rows of image data **372** are delivered to the odd data driver **350**. Even rows of image data **374** are delivered to the even data driver **352**. The odd row data driver **350** converts the image data **372** into data voltages that are driven onto the data lines **DL** connected to the odd pixel rows (R1, R3). The even row data driver **352** converts the image data **374** into data voltages that are driven onto the data lines **DL** connected to the even pixel rows (R2, R4).

The timing controller **330** also provides gate timing control signals **376** to control the operation of the scan driver **340**. The scan driver **340** generates scan pulses that are driven onto the scan lines **SL**. Each scan pulse scans in the data voltages to a pixel row. The pixels of a pixel row hold the data voltages in their respective storage capacitors.

Referring now to FIG. 5, illustrated is a timing diagram illustrating operation of the scan driver 340 and data drivers 350 and 352, according to an embodiment. The timing diagram includes signal waveforms for scan lines SL-1 through SL-4, and also for data lines DL-1 and DL2.

Data voltages d1 and d3 are driven onto data line DL-1 at different times. Scan pulse sc1 scans data voltage d1 into a pixel P in the first pixel row R1. Scan pulse sc3 scans data voltage d3 into a pixel P of the third pixel row R3.

Data voltages d2 and d4 are driven onto data line DL-2 at different times. Scan pulse sc2 scans data voltage d2 into a pixel P in the second pixel row R2. Scan pulse sc4 scans a data voltage d4 into a pixel P of the fourth pixel row R4.

Scan pulses sc1-sc4 are driven sequentially onto the scan lines SL. Each scan pulse overlaps with a previous scan pulse and next scan pulse in time. For example, scan pulse sc2 overlaps with scan pulse sc1 and scan pulse sc3. The scanning of each even pixel row thus overlaps with the scanning of each odd pixel row. Each pixel row can begin scanning before a previous pixel row has completed scanning. This scanning overlap allows the refresh rate of the display to be increased because the scanning of one row does not need to be completed before scanning of the next row begins. Similarly, the refresh rate can be maintained while increasing the time allowed per row to charge the pixel capacitors.

#### Configurable Resolution in Dual Driver Display

FIG. 6A is a diagram illustrating pixels of an electronic display 115, according to an embodiment. The display screen has a fixed native resolution of 1080×1080 (i.e. 1080 pixels wide, 1080 pixels tall). To achieve the best image quality, a frame of image data provided to the virtual reality headset 105 should match the native resolution of the display screen. However, transferring a video stream to the virtual reality headset 105 in a resolution that matches the native resolution of the display screen 310 can consume a large amount of bandwidth that exceeds the limits of the wired connection 190. In one embodiment, the electronic display 115 uses full resolution image frame data for one portion of the display screen, and uses reduced resolution image frame data for another portion of the display screen, thereby reducing the data bandwidth requirements of the wired connection 190.

FIG. 6B is a diagram illustrating a display screen of a display 115 with configurable effective resolution. The display 115 can be operated in a manner that causes it to have different effective resolutions in different regions of the display 115. Effective resolution may also be referred to herein as a supported resolution. The display 115 uses full resolution image data to display a full resolution image in one portion of the display, resulting in a full resolution region 610. The display uses partial resolution image data to display a partial resolution image in another portion of the display, resulting in a reduced resolution region 620.

The full resolution region 610 is shown as a window within and surrounded by the reduced resolution region 620. Image data 370B provided for the full resolution region 610 matches the native resolution of the full resolution region 610 and can be directly applied to the display screen 310 without upscaling. For example, the full resolution region 610 can have a native resolution of 400×400. It has an effective resolution of 400×400 because the image displayed in that region is generated from image frame data 370B having 400×400 resolution.

Image frame data 370A provided for the reduced resolution region 620 is lower than the native resolution of the reduced resolution region 620. The driver circuit 320

receives the reduced resolution image data 370A and upscales the image data before applying the upscaled image data to the display screen. For example, the reduced resolution region 620 can have a native resolution of 1080×1080. It has an effective resolution of 540×540 because the image displayed in that region is generated from image frame data 370A having 540×540 resolution. The image frame data 370A is upscaled by 2× in both the horizontal and vertical directions before it is displayed in the reduced resolution region 620.

In other embodiments the full resolution region 610 and reduced resolution region 620 may be different in size and shape. For example, the upper pixel rows of the display 115 may be the full resolution region while the lower pixel rows of the display 115 is the reduced resolution region. The sizes of the regions can be configured in any manner from the entire panel down to a single color in a row. Beneficially, operating only a portion of the display 115 in full resolution reduces the required bandwidth for image data transferred from the virtual reality console 110 to the virtual reality headset 105.

FIG. 7 illustrates a timing controller 330 and data drivers 350 and 352 supporting configurable resolution, according to an embodiment. The timing controller 330 is shown with a resolution register 705 and scaling circuitry 710. In one embodiment, the resolution register 705 can be a portion of a memory dedicated to storing configuration data, or can be a dedicated circuit for storing resolution configuration data.

The resolution register 705 stores resolution configuration data 706 describing regions of the display 115 that are to be operated in full resolution and regions of the display 115 that are to operate in reduced resolution. For example, the resolution configuration data 706 may include row/column coordinates of the boundaries of the full resolution region 610 and row/column coordinates of the boundaries of the reduced resolution region 620. The resolution configuration data 706 may be provided by the VR console 110 and then stored in the resolution register 705. The resolution configuration data 706 may also include information describing whether the resolution is being reduced in a vertical direction, horizontal direction, or both. The resolution configuration data 706 may also include information describing an amount of upscaling (e.g. 2×, 4×, none) that should be applied in each region of the display.

The selective scaling circuitry 710 receives image data 370 provided by the VR console 110, and also reads the resolution configuration data 706 from the resolution register 705. For a single image frame, the image data 370 can include both reduced resolution image data 370A and full resolution image data 370B. The scaling circuitry 710 uses the resolution configuration data 706 in determining which portions of the image data 370 are reduced resolution image data 370A intended for the reduced resolution region and which are full resolution image data 370B intended for the full resolution region. For portions of the image data 370 intended for the full resolution region 610 (i.e. full resolution image data 370A), the data does not need upscaling and is directly passed on to the odd row data driver or even row data driver 352. For portions of the image data 370 intended for the low resolution region (i.e. reduced resolution image data 370A), the scaling circuitry 720 upscales the image data 370 in the vertical direction, horizontal direction, or both.

The upscaling allows low resolution image data 370A to properly fill all of the pixels in the reduced resolution region 620. Typically upscaling involves duplicating image pixel data without using interpolation. Duplicating image pixel data in the vertical direction can include providing the same

row of image data **370** to both the odd row data driver **350** and even row data driver **352**, which results in the same image being displayed in two adjacent pixel rows. Duplicating image pixel data in the horizontal direction can include duplicating image pixel data across columns such that the same image pixel data is provided to adjacent pixels in a row. In other embodiments, the upscaling can include interpolation between adjacent pixels.

FIG. **8A** illustrates selective scaling circuitry **710** supporting configurable vertical resolution, according to one specific embodiment. The selective scaling circuitry **710** includes a de-multiplexer **804**, row buffers **806** and **808**, routing circuit **810** and control circuit **812**. This embodiment of the selective scaling circuitry **710** can duplicate rows of image data and provide the duplicated rows to both the odd row data driver **350** and even row data driver **352**, which allows for adjustment of vertical resolution. The circuitry shown in FIG. **8** is just one example of circuitry for adjusting vertical resolution, and in other embodiments other types of circuitry are possible.

De-multiplexer **804** receives the image data **370** and directs rows of the image data **370** to row buffer **806** or row buffer **808**. De-multiplexer **804** is controlled by multiplexer control signal **802**. Multiplexer control signal **802** switches states under control of the image data row clock (i.e. with each image data row) such that rows of image data are stored in alternating manner between row buffer **806** and row buffer **808**. Routing circuit **810** selectively directs rows of image data stored in row buffer **806** and **808** to odd row data driver **350** or even row data driver **352**.

Control circuit **812** generates one or more routing control signals **813** that control the routing of rows through the routing circuit **810**. Control circuit **812** generally changes the configuration of the routing circuit **810** at a rate that matches the scan frequency of the display. The register configuration data **706** sets at which row to switch from reduced resolution mode to full resolution mode and back. Thus, the state of the routing control signals **813** is controlled depending on whether an incoming row of the image data **370** is supposed to be handled in reduced resolution or full resolution mode, as indicated by the resolution configuration data **706** read from the resolution register **705**. This is explained in greater detail by reference to FIG. **9A-9H**.

FIG. **9A-9H** illustrate operation of the display **115** supporting different resolutions for different display regions, according to an embodiment. In FIG. **9A-9H**, the reduced resolution region of the display occupies pixel rows **1-4** and that the full resolution region of the display occupies pixel rows **5-7**. FIG. **9A-9E** illustrate operation of the display when operating in reduced resolution mode for the first four pixel rows of the display, which is the reduced resolution region. FIG. **9F-9H** illustrate operation of the display when operating in full resolution mode for pixel rows five through seven, which is the full resolution region.

Initially the display is in reduced region mode of operation for pixel rows one through four where pixel duplication is needed. In FIG. **9A**, an image data row **IDR1** is received and stored into row buffer **806**.

In FIG. **9B**, an image data row **IDR2** is received and stored into row buffer **808**. At the same time, image data row **IDR1** is routed from row buffer **806** to odd row data driver **350** and scanned into the first pixel row of the display screen **310**.

In FIG. **9C**, while image data row **IDR2** is still being stored into row buffer **808**, image data row **IDR1** is now routed from row buffer **806** to even row data driver **352** and scanned into the second pixel row of the display screen **310**.

In FIG. **9D**, an image data row **IDR3** is received and stored into row buffer **806**. At the same time, image data row **IDR2** is routed from row buffer **808** to the odd row data driver **350** and scanned into the third pixel row of the display screen **310**.

In FIG. **9E**, while image data row **IDR2** is still being stored into row buffer **806**, image data row **IDR2** is now routed from row buffer **808** to the even row data driver **352** and scanned into the fourth pixel row of the display screen **310**.

The display now switches to full resolution mode of operation for pixel rows five through seven where pixel duplication is not needed. In FIG. **9F**, an image data row **IDR4** is received and stored into row buffer **808**. At the same time, image data row **IDR3** is routed from row buffer **806** to the odd row data driver **350** and scanned into the fifth pixel row of the display screen **310**.

In FIG. **9G**, an image data row **IDR5** is received and stored into row buffer **806**. At the same time, image data row **IDR4** is routed from row buffer **808** to the even row data driver **352** and scanned into the sixth pixel row of the display screen **310**.

In FIG. **9H**, an image data row **IDR6** is received and stored into row buffer **808**. At the same time, image data row **IDR5** is routed from row buffer **806** to the odd row data driver **350** and scanned into the seventh pixel row of the display screen **310**.

It should be noted that, in reduced resolution mode, the incoming image row clock is half the speed of the scan clock scanning the rows into the display screen. In full resolution mode, the incoming row image row clock is the same as the scan clock scanning the rows into the display screen.

FIG. **8B** illustrates selective scaling circuitry **710** supporting configurable horizontal and vertical resolution, according to another embodiment. The selective scaling circuitry **710** of FIG. **8B** is similar to the selective scaling circuitry **710** of FIG. **8A**, but now includes a column upscaling circuit **820**, which allows for adjustment of effective horizontal resolution. The column upscaling circuit **820** can selectively duplicate pixels of the image data **370** across pixel columns so that reduced resolution image data can be upscaled to the native resolution of the display screen.

Control circuit **812** generates one or more control signals **816** that control whether the column upscaler **820** should upscale the incoming data **370**. When the register configuration data indicates that incoming data is intended for the reduced resolution region **620** of the screen, the control circuit **812** generates the control signal **816** in one state (e.g. logic high) to enable horizontal upscaling. When the register configuration data indicates that incoming data is intended for the reduced resolution region **610** of the screen, the control circuit **812** generates the control signal **816** in another state (e.g. logic low) to disable horizontal upscaling. Thus, the state of the control signals **816** is controlled depending on whether an incoming portion of the image data **370** is supposed to be handled in reduced resolution or full resolution mode, as indicated by the resolution configuration data read from the resolution register **705**.

The column upscaler **820** outputs image data **822** that may or may not be horizontally upscaled, depending on whether upscaling was needed. In any case, a row of the image data **822** now includes data for a number of pixels that matches a number of pixels in a pixel row of the display screen **310**. De-multiplexer **804** receives the image data **370** and directs rows of the image data **370** to row buffer **806** or row buffer **808**.

## 11

In another embodiment, different amounts of upscaling may be applied to different portions of the image data 370. For example, a high amount of upscaling (e.g. 4x) may be applied to image data intended for one display region, while a low amount of upscaling (e.g. 2x, no upscaling) may be applied to image data intended for another display region. Eye Tracking Control of Display Resolution

FIGS. 10A and 10B are diagrams illustrating the use of eye tracking to control a full resolution region 710 of the display 115, according to an embodiment. FIG. 10A includes an eye 245 having a gaze 1000 directed to a portion of the display 115. The display 115 is controlled such that the full resolution region 610 tracks the user's gaze 1000. For example, in FIG. 10B, the gaze direction 1000 has moved to the left. As a result, the full resolution region 610 is moved to the left to match the user's new gaze 1000.

In a human eye, the foveal region of the retina is the only part of the retina that permits 100% visual acuity. In a VR headset 105 where the display 115 is placed close to the user's eye 245, only a small portion of the display 100 is viewed by foveal region anyways while the rest of the display 115 is viewed by other parts of the retina. Thus, to the human eye, there is no loss in clarity if the portion of the display outside of the foveal region is not in full resolution.

FIG. 11 is an interaction diagram for using eye tracking to control a full resolution region of the display 115, according to an embodiment. The VR headset 105 tracks the eye and generates gaze data indicative of a gaze direction of the user's eye. The VR headset 105 transmits 1105 the gaze data to the VR console 110. The VR console 110 receives the gaze data and analyzes the gaze data to determine 1115 the user's gaze direction.

The VR console 110 determines, from the gaze direction, the region of the display that is to be full resolution and the region that is to have reduced resolution. The VR console 110 attempts to match the full resolution region with the gaze direction of the user in order to track the user's eye movements. The VR console 110 transmits 1125 resolution configuration data describing the adjusted location of the full resolution region, the adjusted location of the reduced resolution region or both sets of locations to the VR headset. The VR headset 105 receives the resolution configuration data and stores 1130 the resolution configuration data in a resolution register. In one embodiment, steps 1120, 1125, and 1130 result are steps involved in the adjustment of the location of the full resolution region 620.

The VR console 110 then generates 1135 image data for display at the VR headset 105. In each image frame, part of the image data is for the reduced resolution region 620 of the display, and part of the image data is for the full resolution region 610 of the display. The VR console 110 transmits 1140 the image data to the VR headset 105. The VR headset 105 processes 1145 the image data in accordance with the resolution configuration data. The processing includes upscaling portions of the image data corresponding to the reduced resolution region 620 of the display, and not upscaling portions of the image data corresponding to the full resolution region 610 of the display. The VR headset 105 then displays 1150 an image that has a full resolution region 610 and a partial resolution region 620 by providing the image data to the data drivers 350 and 352.

The process also repeats 1155 continuously at periodic intervals so that the full resolution region 610 is periodically adjusted to track the user's gaze.

## Other Considerations

FIG. 12 illustrates the hardware architecture of computing device 1200, according to one embodiment. In some

## 12

embodiments, the computing device 1200 may be used as VR console 110. The computing device includes components such as a processor 1202, a memory 1203, a storage module 1204, an input module (e.g., keyboard, mouse, and the like) 1206, a display module 1207 and a communication interface 1205, exchanging data and control signals with one another through a bus 1201. The storage module 1204 is implemented as one or more non-transitory computer readable storage media (e.g., hard disk drive), and stores software instructions 1240 that are executed by the processor 1202 in conjunction with the memory 1203 to implement the operations of the eye tracking module 150, virtual reality engine module 155, or other operations described herein. Operating system software and other application software may also be stored in the storage module 1204 to run on the processor 1202.

The foregoing description of the embodiments of the disclosure has been presented for the purpose of illustration; it is not intended to be exhaustive or to limit the disclosure to the precise forms disclosed. Persons skilled in the relevant art can appreciate that many modifications and variations are possible in light of the above disclosure.

The language used in the specification has been principally selected for readability and instructional purposes, and it may not have been selected to delineate or circumscribe the inventive subject matter. It is therefore intended that the scope of the disclosure be limited not by this detailed description, but rather by any claims that issue on an application based hereon. Accordingly, the disclosed embodiments are intended to be illustrative, but not limiting, of the scope of the disclosure, which is set forth in the following claims.

What is claimed is:

1. A virtual reality system, comprising:

a virtual reality headset comprising:

a display screen comprising a plurality of rows, and having a first region having a first native resolution and operating in reduced resolution by having an effective resolution lower than the first native resolution, and a second region having a second native resolution and operating in full resolution by having an effective resolution that is same as the second native resolution;

a selective scaling circuit configured to receive incoming rows of image data to be displayed on the display screen, and to scan the received rows of image data into rows of the display screen, wherein:

for the first region of the display screen, the rate at which incoming rows of image data are received is less than the rate at which the received rows are scanned into rows of the display screen, and

for the second region of the display screen, the rate at which the incoming rows of image data are received is the same as the rate at which the received rows are scanned into rows of the display screen; and

an eye tracking sensor to generate gaze data indicative of a gaze direction of the eye,

wherein a location of the second region operating in full resolution is adjusted based on the gaze direction of the eye.

2. The virtual reality system of claim 1, wherein the eye tracking sensor is a camera that generates gaze data in the form of an image of the eye.

3. The virtual reality system of claim 1, the location of the second region operating in full resolution is adjusted to match the gaze direction of the eye.

13

4. The virtual reality system of claim 1, further comprising:

a virtual reality console to receive the gaze data from the virtual reality headset, and to adjust the location of the second region operating in full resolution by transmitting resolution configuration data to the virtual reality headset indicative of an adjusted location of the second region of the display screen operating in full resolution.

5. The virtual reality system of claim 1, wherein the virtual reality console transmits image data to the virtual reality headset, and the virtual reality headset displays the image data on the display screen based on the resolution configuration data.

6. The virtual reality system of claim 1, wherein the second region is surrounded by the first region.

7. A method of operation in a virtual reality system, comprising:

displaying an image in a display of the virtual reality system, the display comprising a plurality of rows and including a first region having a first native resolution and operating in reduced resolution by having an effective resolution lower than the first native resolution, and a second region having a second native resolution and operating in full resolution by having an effective resolution that is same as the second native resolution, and wherein displaying the image comprises:

receiving incoming rows of the image to be displayed, and scanning the received image rows into rows of the display, wherein:

for the first region of the display, the rate at which incoming rows of the image are received is less

14

than the rate at which the received rows are scanned into rows of the display, and

for the second region of the display, the rate at which the incoming rows of the image are received is the same as the rate at which the received rows are scanned into rows of the display;

generating gaze data indicative of a gaze direction of an eye; and

adjusting a location of the second region operating in full resolution based on the gaze direction of the eye.

8. The method of claim 7, wherein the gaze data is an image of the eye generated from a camera.

9. The method of claim 7, wherein the location of the second region operating in full resolution is adjusted to match the gaze direction of the eye.

10. The method of claim 7, further comprising: receiving, at a virtual reality console, the gaze data from a virtual reality headset, and

wherein the location of the second region operating in full resolution is adjusted by transmitting resolution configuration data from the virtual reality console to the virtual reality headset indicative of an adjusted location of the second region of the display screen operating in full resolution.

11. The method of claim 7, wherein the virtual reality console transmits image data to the virtual reality headset, and the virtual reality headset displays the image data on the display screen based on the resolution configuration data.

12. The method of claim 7, wherein the second region is surrounded by the first region.

\* \* \* \* \*