

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
3 February 2011 (03.02.2011)

(10) International Publication Number
WO 2011/014265 A1

(51) International Patent Classification:
A61M 5/00 (2006.01)

(71) Applicant (for all designated States except US): **MEDEGEN, INC.** [US/US]; 101617 N. Hayden Road; Suite 100, Scottsdale, AZ 85260 (US).

(21) International Application Number:

PCT/US2010/024875

(72) Inventors; and

(22) International Filing Date:

22 February 2010 (22.02.2010)

(75) Inventors/Applicants (for US only): **MANSOUR, George, M.** [US/US]; 1684 Blue Ridge Drive, Pomona, CA 91766 (US). **BENNETT, James** [US/US]; 9371 Pioneer Lane, Corona, CA 92883 (US).

(25) Filing Language:

English

(74) Agents: **DELFLACHE, Marc, L.** et al.; Fulbright & Jaworski L.L.P., 2200 Ross Avenue, Suite 2800, Dallas, TX 75201-2784 (US).

(26) Publication Language:

English

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ,

(30) Priority Data:

12/512,719

30 July 2009 (30.07.2009)

US

[Continued on next page]

(54) Title: COLLAPSIBLE VALVE

(57) Abstract: A collapsible valve comprising a first portion with at least one dimple in a side thereof, and a second portion, the second portion being narrower than the first portion and arranged along an axial dimension of the first portion, the second portion including a cut therein.




FIG. 5



CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report (Art. 21(3))*

(84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH,

COLLAPSIBLE VALVE

TECHNICAL FIELD

[0001] The present disclosure relates, generally, to fluid flow devices and, more specifically, to valves for use in medical devices.

BACKGROUND OF THE INVENTION

[0002] Needleless access devices allow a healthcare professional to, *e.g.*, replace/add IV bags, and/or access an IV line without having to use a needle. FIGURE 1 is a cut-away view of a current needleless access device 100. Needleless access device 100 includes female luer fitting 101, male luer fitting 102, and valve 103. When in use, male luer fitting 102 is connected to, *e.g.*, a catheter or to a female luer, and female luer fitting 101 is connected to a fluid reservoir. Female luer fitting 101 is connected to the fluid reservoir via a second male luer fitting (not shown) that includes a hollow member inserted through the top of female luer fitting 101, collapsing valve 103 down into volume 104 to break the seal and create a fluid flow path. The hollow member of the second male luer fitting delivers the fluid, which flows around valve 103 into channels (not shown) in male luer fitting 102 and into the catheter or female luer.

[0003] Inside valve 103 is a gap (or septum, not shown), that is filled with air. Device 100 is a positive displacement device, so that when a new connection is made at female luer fitting 101, device 100 pulls fluid in from the male side of the valve (*i.e.*, the side proximate male luer fitting 102). When a disconnection is made at female luer fitting 101, device 100 pushes fluid in from the female side (*i.e.*, the side proximate the top of female luer fitting 101). The advantage of positive displacement is that when a disconnection is made, device 100 expels fluid out of the male luer fitting 102 and effectively flushing the catheter. By contrast, many devices on the market today have negative displacement, so that when a syringe is disconnected, such device pulls a little bit of fluid from the male luer side, which, if a catheter is being used, means that blood is pulled into the catheter lumen. Blood that is left in a catheter lumen may clot and cause health problems for the patient.

[0004] An additional feature of device 100 is that when the female end is accessed by a male luer (not shown), valve 103 is elastic so that it can bend out of the way to allow flow and then return to its original shape after a disconnection is made at the female end. Thus, device 100 re-seals itself and forms a flat surface that can be disinfected at the top surface 110 using an alcohol swab. By contrast, many devices on the market use plastic valves that cannot flex to move out of the way to allow flow, thus

requiring the use of valves that are slanted or incorporating features at the top, making swabbing difficult.

[0005] Device 100 has a symmetrical valve body providing symmetrical wall strength, as well as weakness points on both sides by virtue of duckbills 105. Furthermore, device 100 includes uniform wall thickness in the valve body, even at and around duckbills 105. The contact area between a luer and the top surface 110 of valve 103 and the type of luer motion will dictate the form of collapse of the valve body. Device 100 provides good performance, but could benefit from enhanced repeatability and controllability of collapse.

BRIEF SUMMARY OF THE INVENTION

[0006] Various embodiments of the invention are directed to valves, and to needleless access devices that use collapsible valves, which include a cut and at least one dimple to cause specific collapsing valve behavior. In one specific example, a cut is placed on a top portion of a valve, the top portion being narrower in diameter than a bottom portion and forming the top seal of a needleless access device. The bottom portion is substantially cylindrical, forming a septum, and including at least one dimple thereon. The dimple is angularly offset from the cut by approximately ninety degrees, enough so that a load point on the top surface of the valve is shifted away from the cut to delay the collapse of the cut and result in less forward fall of the top portion when the cut collapses. A method according to one embodiment is related to processes for manufacture of needleless access devices. Another embodiment is directed to a needleless access device that includes a collapsible valve.

[0007] The foregoing has outlined rather broadly the features and technical advantages of the present invention in order that the detailed description of the invention that follows may be better understood. Additional features and advantages of the invention will be described hereinafter which form the subject of the claims of the invention. It should be appreciated by those skilled in the art that the conception and specific embodiment disclosed may be readily utilized as a basis for modifying or designing other structures for carrying out the same purposes of the present invention. It should also be realized by those skilled in the art that such equivalent constructions do not depart from the spirit and scope of the invention as set forth in the appended claims. The novel features which are believed to be characteristic of the invention, both as to its organization and method of operation, together with further objects and advantages will be better understood from the following description when considered in connection with the accompanying figures. It is to be expressly understood, however, that each of the figures is provided for the purpose of illustration and description only and is not intended as a definition of the limits of the present invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] For a more complete understanding of the present invention, reference is now made to the following descriptions taken in conjunction with the accompanying drawings, in which:

[0009] FIGURE 1 is a cut-away view of a current needleless access device;

[0010] FIGURES 2A and 2B are cut-away views showing an exemplary needleless access device adapted according to one embodiment of the invention;

[0011] FIGURES 3A-C show views of a valve by itself;

[0012] FIGURES 4A and 4B show views ninety degrees from those of FIGURES 3A and 3B;

[0013] FIGURE 5 is an illustration of an exemplary needleless access device with a syringe inserted therein and collapsing an exemplary valve;

[0014] FIGURES 6A-6D illustrate the behavior of an exemplary valve, as pressure is applied by a syringe, but before collapse, according to embodiments of the invention;

[0015] FIGURES 7A-7B illustrate behavior of an exemplary valve as pressure is applied by a syringe, but before collapse, according to embodiments of the invention;

[0016] FIGURE 8 is an illustration of one scenario of use of an exemplary valve; and

[0017] FIGURE 9 shows three examples of a wide variety of cuts that can be applied to some embodiments of the invention.

DETAILED DESCRIPTION OF THE INVENTION

[0018] FIGURES 2A and 2B are cut-away views showing exemplary needleless access device 200 adapted according to one embodiment of the invention. The view in FIGURE 2B is rotated ninety degrees from that shown in FIGURE 2A.

[0019] Device 200 includes female luer fitting 201, male luer fitting 202, and valve 210. Valve 210 includes cut 211, which in this example, is referred to as a “smiley cut.” Valve 210 also includes dimples 212 and 213 on the outside of its lower portion and placed with axial and angular offsets from each other so that the body of valve 210 is not symmetrical. While cut 211 is referred to as a cut, it can be manufactured using any of a variety of techniques, including molding so that a cut is not actually made. An example of a material that may be used for male and female luer fittings 201 and 202 is polycarbonate, and an example of a material that may be used for valve 210 is silicone, though any of a variety of suitable materials may also be used in various embodiments.

[0020] Device 200 provides for positive displacement and self sealing, similar to the device shown in FIGURE 1. Male luer fitting 202 at the bottom, connects to a catheter or other medical device (not shown) that is connected to the body of the patient. A syringe (not shown) mates with female luer fitting 201 to collapse valve 210 into the cavity defined between male and female luer fittings 201 and 202. Fluid flow goes from the top of device 200, around valve 210, and through channels 230, 240 to middle channel 250 of male luer fitting 202. Valves 260 and 270 allow air to enter and escape septum 215 of valve 210.

[0021] When closed, valve 210 provides two seals. The first seal is at the top surface 280 of device 200. The second seal is at shoulder 290. As explained in more detail with respect to FIGURE 5, insertion of a syringe at female luer fitting 201 collapses valve 210, thereby breaking the seals. Valve 210 acts as a spring, so that when it is pushed it down, it collapses, and when the force is removed, it returns to its shape thereby resealing. Generally, the thicker the wall of valve 210, the more spring force, and the thinner the wall, the less spring force. Therefore, wall thickness affects characteristics, such as ease of syringe insertion and displacement. In one particular

example where valve 210 is approximately two centimeters in length, a wall thickness within the range of 0.030 and 0.038 inches provides acceptable displacement, sealing, and ease of use. Of course, at dimples 212 and 213 the wall thickness is less, as can be seen especially well at FIGURE 3A.

[0022] In one example, device 200 is manufactured by separately molding valve 210 and male and female luer fittings 201 and 202. Valve 210 is then placed in the cavity that is formed by male and female luer fittings 201 and 202. Male and female luer fittings 201 and 202 are positioned and welded. Device 200 is then sterilized and packaged. Other methods for manufacturing are possible, *e.g.*, by gluing rather than welding male and female luers 201 and 202, and are within the scope of embodiments.

[0023] FIGURES 3A-C show views of valve 210 by itself. FIGURE 3B shows a side view, FIGURE 3A shows a cut-away view, and FIGURE 3C shows a bottom view of valve 210. As can be seen, both the top portion and the bottom portion of valve 210 are annular (in this case, substantially cylindrically shaped), where the top portion includes smiley cut 211, and the bottom portion includes dimples 212 and 213. The bottom portion of valve 210 is substantially hollow, defining septum 215. FIGURES 4A and 4B show views ninety degrees from those of FIGURES 3A and 3B.

[0024] FIGURE 5 is an illustration of exemplary device 200 with exemplary syringe 510 inserted therein and collapsing valve 210. Smiley cut 211 collapses, tilting its top surface 216 to let fluid flow out of syringe 510. The lower portion of valve 210 also collapses, aided by dimples 212 and 213, which act as two weak points, placed to cause the lower portion to collapse before smiley cut 211 collapses. Arrows are added to FIGURE 5 to illustrate a path of fluid as it flows through syringe 510, around valve 210, and out of male luer 202.

[0025] In the embodiments shown in FIGURES 2-5, smiley cut 211 is placed relative to dimples 212 and 213 to facilitate specific collapsing behavior. FIGURES 6A-6D illustrate the behavior of valve 210, as pressure is applied by syringe 510, but before collapse. In the embodiment of FIGURES 2-6, dimple 213 is placed ninety degrees clockwise from smiley cut 211, which places load point 610 counterclockwise to smiley cut 211 (wherein clockwise and counterclockwise refer to the

orientation shown in FIGURES 2-6, where the valve 210 is shown with smiley cut 211 above the dimples). The placement of load point 610 is notable because a male luer fitting (not shown) associated with syringe 510 has a thread to connect to female luer fitting 201, thereby rotating syringe 510 as it is inserted (and in turn, putting rotational pressure on valve 210). As dimple 213 begins to collapse, pressure point 610 appears ninety degrees from smiley cut 211, where the side of the top portion of valve 210 is stronger than it is directly above smiley cut 211. In this embodiment, smiley cut 211 collapses later than it would in a scenario where load point 610 is placed directly over smiley cut 211.

[0026] By contrast, FIGURES 7A-7B illustrate behavior of valve 710 as pressure is applied by syringe 510, but before collapse, according to embodiments of the invention. In valve 710, smiley cut 211 is 180 degrees from dimple 213 and directly above dimple 212. Such placement of dimples 212, 213 and smiley cut 211 causes pressure point 720 to be directly above smiley cut 211, thereby causing smiley cut 211 to collapse sooner than it does in the scenario illustrated in FIGURES 6A-6D.

[0027] In many uses, both valve 210 and valve 710 are acceptable alternatives. However, in scenarios wherein syringe 510 includes a counterbore, early collapse of smiley cut 211 may cause the top of valve 710 to fall forward and become lodged in the counterbore, thereby somewhat impeding the flow of fluid. Such a scenario is shown in FIGURE 8, where the top of valve 710 is lodged in counterbore 820 of syringe 810. By contrast, valve 210 delays the collapse of smiley cut 211, providing a more vertical collapse of smiley cut 211 and avoiding blockage of syringe counterbores. Thus, in scenarios where a syringe includes a counterbore, valve 210 can be employed successfully. Both valve 210 and valve 710 can be successfully employed in applications using a syringe, such as that shown in FIGURES 5-7. Various embodiments can use any angular displacement of a dimple relative to a cut, with valve 210 and valve 710 illustrating two examples.

[0028] While valves 210 and 710 are shown with two dimples each, various embodiments are not so limited. For instance, more dimples may be added, and some embodiments may include only one dimple. Furthermore, embodiments are not limited to the use of smiley cuts, as other shaped cuts may be employed. For instance,

FIGURES 9A-9C show V-cut 910, U-cut 920, and “seagull” cut 930, which are but three examples of a wide variety of cuts that can be applied to embodiments.

[0029] As shown above, various embodiments include valves with flat tops that facilitate flow around, rather than through, said valves. Such features provide advantages over embodiments that use hard plastic, do not have flat tops, and/or allow flow through, rather than around valves. For instance, valves 210 and 710 of the embodiments described above provide positive displacement and are self-flushed, thereby providing better hygiene than negative displacement devices. Furthermore, the flat top surfaces of valves 210 and 710 can provide for better swabability than do devices with slanted or grooved tops, once again providing better hygienic qualities. Additionally, the dimples and cuts shown in the embodiments above provide for somewhat predictable collapse of the valves, and (especially in the case of valve 210) applicability to any of a variety of syringes.

[0030] Although the present invention and its advantages have been described in detail, it should be understood that various changes, substitutions and alterations can be made herein without departing from the spirit and scope of the invention as defined by the appended claims. Moreover, the scope of the present application is not intended to be limited to the particular embodiments of the process, machine, manufacture, composition of matter, means, methods and steps described in the specification. As one of ordinary skill in the art will readily appreciate from the disclosure of the present invention, processes, machines, manufacture, compositions of matter, means, methods, or steps, presently existing or later to be developed that perform substantially the same function or achieve substantially the same result as the corresponding embodiments described herein may be utilized according to the present invention. Accordingly, the appended claims are intended to include within their scope such processes, machines, manufacture, compositions of matter, means, methods, or steps.

CLAIMS

What is claimed is:

1. A collapsible valve comprising:
a first portion with at least one dimple in a side thereof; and
a second portion, the second portion being narrower than the first portion and
arranged along an axial dimension of the first portion, the second portion including a cut
therein.
2. The collapsible valve of claim 1 wherein the cut is angularly displaced
from the dimple by approximately 90 degrees.
3. The collapsible valve of claim 2 wherein the dimple is placed clockwise
relative to the cut.
4. The collapsible valve of claim 1 wherein the first portion is substantially
cylindrical.
5. The collapsible valve of claim 1 installed in a needleless access device.
6. The collapsible valve of claim 5, providing positive displacement.
7. The collapsible valve of claim 5, wherein the second portion has a flat top
that seals flush with a top surface of the needleless access device.
8. The collapsible valve of claim 1 comprising silicone.
9. The collapsible valve of claim 1 wherein the first and second portions are
annular.

10. A needleless access device comprising:
 - a female fitting;
 - a male fitting coupled to the female fitting, the male and female fittings defining an inside volume; and
 - a collapsible valve disposed within the inside volume, the collapsible valve comprising:
 - a first portion proximate the female fitting with a cut on a surface thereof; and
 - a second portion proximate the male fitting, arranged axially with respect to the first portion, the second portion including a dimple in a side thereof.
11. The needleless access device of claim 10, wherein the dimple is radially displaced from the cut on the surface of the first portion.
12. The needleless access device of claim 10, wherein the dimple is radially displaced from the cut on the surface of the first portion by approximately 90 degrees.
13. The needleless access device of claim 10, wherein the first portion forms a seal at the female fitting, creating a flat, top surface of the female fitting.
14. The needleless access device of claim 10, wherein the collapsible valve provides positive displacement.
15. The needleless access device of claim 10, wherein the female and male fittings comprise luer fittings.
16. The needleless access device of claim 10, wherein the second portion of the collapsible valve is substantially cylindrical.

17. A method for manufacturing a needleless access device, the method comprising:

disposing a collapsible valve inside a volume defined by a male fitting and a female fitting such that a first portion of the collapsible valve that is proximate the female fitting provides a seal at the opening of the female fitting, the collapsible valve comprising the first portion and a second portion arranged axially with respect to each other the second portion including a dimple in a side thereof, the dimple radially displaced from the cut on the surface of the first portion.

18. The method of claim 17 further comprising:
sterilizing and packaging the needleless access device.




FIG. 1
(*Prior Art*)




FIG. 2A




FIG. 2B





FIG. 3A

FIG. 3B




FIG. 3C

4/9





FIG. 4B

5/9




FIG. 5

6/9




FIG. 6D




FIG. 6C




FIG. 6B




FIG. 6A

7/9




FIG. 7D




FIG. 7C




FIG. 7B




FIG. 7A

8/9




FIG. 8




FIG. 9A




FIG. 9B




FIG. 9C

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US 10/24875

A. CLASSIFICATION OF SUBJECT MATTER

IPC(8) - A61M 5/00 (2010.01)

USPC - 604/249

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC(8) - A61M 5/00 (2010.01)

USPC - 604/249

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched
604/19, 33, 34, 48, 93.01, 246, 247, 256

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

PubWEST(USPT,PGPB,EPAB,JPAB); Google Scholar;

Search Terms Used: valve, connector, needleless, dimple, cut, notch, groove, weak\$, compress\$, positive displacement, positive pressure,

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2006/0027270 A1 (TRUITT et al.) 09 February 2006 (09.02.2006) Entire document, especially para[0005], para[0051], para[0055] - para[0057], para[0060], para[0073], para[0080] and FIGS. 1-2.	1-18
X ----- Y	US 5,730,418 A (FEITH et al.) 24 March 1998 (24.03.1998) Fig. 3, 4, 7, 8, esp. Fig. 7 & 8	1, 4-10, 13-16 ----- 2, 3, 11, 12, 17, 18
Y	US 5,782,816 A (WESCHMIDT et al.) 21 July 1998 (21.07.1998) Entire document, esp. Fig. 13	2, 3, 11, 12, 17, 18
A	US 2006/0025724 A1 (CHEN) 02 February 2006 (02.02.2006) Entire document	1-18
A	US 7,184,825 B2 (LEINSING et al.) 27 February 2007 (27.02.2007) Entire document	1-18

 Further documents are listed in the continuation of Box C.

* Special categories of cited documents:

- “A” document defining the general state of the art which is not considered to be of particular relevance
- “E” earlier application or patent but published on or after the international filing date
- “L” document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- “O” document referring to an oral disclosure, use, exhibition or other means
- “P” document published prior to the international filing date but later than the priority date claimed

- “T” later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- “X” document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- “Y” document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- “&” document member of the same patent family

Date of the actual completion of the international search

25 March 2010 (25.03.2010)

Date of mailing of the international search report

28 APR 2010

Name and mailing address of the ISA/US

Mail Stop PCT, Attn: ISA/US, Commissioner for Patents
P.O. Box 1450, Alexandria, Virginia 22313-1450
Facsimile No. 571-273-3201

Authorized officer:

Lee W. Young

PCT Helpdesk: 571-272-4300
PCT OSP: 571-272-7774