



## (12) Patent specification

(10) SE 539 828 C2

|                                 |            |                    |           |
|---------------------------------|------------|--------------------|-----------|
| (21) Patent application number: | 1650576-0  | (51) Int.Cl.:      |           |
| (45) Grant of patent:           | 2017-12-12 | <b>C09D 197/00</b> | (2006.01) |
| (41) Available to the public:   | 2017-10-30 | <b>B62D 25/20</b>  | (2006.01) |
| (22) Filing date:               | 2016-04-29 | <b>C08H 7/00</b>   | (2011.01) |
| (24) Effective date:            | 2016-04-29 | <b>C08L 97/00</b>  | (2006.01) |
| (30) Priority data:             | ---        | <b>C09D 5/08</b>   | (2006.01) |
|                                 |            | <b>C09D 133/06</b> | (2006.01) |
|                                 |            | C09D 5/34          | (2006.01) |
|                                 |            | C09J 133/06        | (2006.01) |
|                                 |            | C09J 197/00        | (2006.01) |

(73) Patentee: Innventia AB, Box 5604, 114 86 Stockholm SE  
 (72) Inventor: Fernando ALVARADO, Stockholm SE  
 Göran FLODBERG, Lidingö SE  
 (74) Agent: ZACCO SWEDEN AB, P.O. Box 5581 Valhallavägen 117N, 114 85, Stockholm SE  
 (54) Title: Lignin-containing sealant and/or coating compositions from renewable sources  
 (56) Cited documents: CN 102140293 A · CN 102140289 A · CN 102533019 A  
 (57) Abstract:

The present invention relates to lignin-containing compositions comprising:

10 to 50 percent by weight of lignin;

10 to 50 percent by weight of a liquid C2-C4 polyol; and

10 to 50 percent by weight of an acrylic resin;

wherein the percentages by weight are expressed relative to the total dry weight of the composition, and wherein the total dry weight of the composition amounts to 100 percent.

The present invention further relates to processes for sealing joints or coating surfaces using such a composition. Moreover, the present invention relates to joints sealed and surfaces coated using such a composition, as well as vehicles comprising such sealed joints and coated surfaces.

