

(12) **United States Patent**
Schurzig

(10) **Patent No.:** **US 11,006,229 B2**
(45) **Date of Patent:** **May 11, 2021**

(54) **MIDDLE EAR IMPLANT COUPLER FOR MECHANICAL COCHLEA STIMULATION VIA THE ROUND WINDOW**

(58) **Field of Classification Search**
CPC H04R 25/606; H04R 2225/67
See application file for complete search history.

(71) Applicant: **MED-EL Elektromedizinische Geraete GmbH, Innsbruck (AT)**

(56) **References Cited**

(72) Inventor: **Daniel Schurzig, Hannover (DE)**

U.S. PATENT DOCUMENTS

(73) Assignee: **MED-EL Elektromedizinische Geraete GmbH, Innsbruck (AT)**

4,645,504 A * 2/1987 Byers A61F 2/00
623/10

5,318,502 A 6/1994 Gilman
(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

WO WO 2012/118725 A1 9/2012
WO WO 2014/204880 A1 12/2014

(21) Appl. No.: **16/482,319**

OTHER PUBLICATIONS

(22) PCT Filed: **Feb. 23, 2018**

International Searching Authority/US, International Search Report and the Written Opinion of the International Searching Authority, Application No. PCT/US2018/019375, dated Apr. 26, 2018, 16 pages.

(86) PCT No.: **PCT/US2018/019375**

§ 371 (c)(1),

(2) Date: **Jul. 31, 2019**

(Continued)

(87) PCT Pub. No.: **WO2018/156867**

Primary Examiner — Ryan Robinson

PCT Pub. Date: **Aug. 30, 2018**

(74) *Attorney, Agent, or Firm* — Sunstein LLP

(65) **Prior Publication Data**

US 2019/0356995 A1 Nov. 21, 2019

(57) **ABSTRACT**

A round window coupling device is described for a hybrid electric-mechanical stimulation hearing implant system. A rigid outer shell securely fits into a round window niche in a cochlear outer surface of a recipient patient. An electrode groove in the outer surface of the outer shell snugly fits around a portion of a cochlear implant electrode array passing through the round window niche. A coupling filling is enclosed within the outer shell to couple mechanical vibrations from the proximal end to the distal end with minimal attenuation. A transducer receiver at the proximal end connects to and receives vibrations from a drive surface of a mechanical transducer. And a drive face at the distal end interfaces to perilymph fluid within the cochlea of the recipient patient to deliver vibrations from the coupling

(Continued)

Related U.S. Application Data

(60) Provisional application No. 62/463,763, filed on Feb. 27, 2017.

(51) **Int. Cl.**


H04R 25/00 (2006.01)

A61N 1/36 (2006.01)

H04R 25/02 (2006.01)

(52) **U.S. Cl.**

CPC **H04R 25/606** (2013.01); **A61N 1/36038** (2017.08); **H04R 25/02** (2013.01)



filling to the perilymph fluid with minimal attenuation for perception as sound.

9 Claims, 6 Drawing Sheets

(56)

References Cited

U.S. PATENT DOCUMENTS

5,782,744 A * 7/1998 Money H04R 25/606
600/25
6,259,951 B1 * 7/2001 Kuzma A61N 1/36038
607/57
6,628,991 B2 * 9/2003 Kuzma A61N 1/0541
607/137
6,889,094 B1 * 5/2005 Kuzma A61N 1/0541
607/137
7,283,874 B2 * 10/2007 Penner A61N 1/3718
607/33
8,285,384 B2 * 10/2012 Ball A61N 1/0541
607/57
8,396,570 B2 * 3/2013 Dadd A61N 5/0622
607/137

8,771,167 B2 * 7/2014 Grasso H04R 25/606
600/25
10,057,696 B2 * 8/2018 Cho H04R 25/606
10,661,075 B2 * 5/2020 Schachtele A61N 1/0541
2009/0240099 A1 * 9/2009 Conn A61N 1/0541
600/25
2009/0306458 A1 12/2009 Parker et al.
2010/0324355 A1 * 12/2010 Spitaels A61N 1/36038
600/25
2011/0295053 A1 * 12/2011 Ball H04R 25/606
600/25
2012/0071957 A1 3/2012 Carter
2017/0180889 A1 * 6/2017 Walraevens H04R 25/606
2017/0347209 A1 * 11/2017 Heasman H04R 25/606

OTHER PUBLICATIONS

European Patent Office, Extended European Search Report, Application No. 18758163.2, dated Jan. 21, 2020, 8 pages.
Geoffrey J. Service et al., *Alternative placement of the floating mass transducer in implanting the MED-EL Vibrant Soundbridge*, *Operative Techniques in Otolaryngology—Head and Neck Surgery*, W.B. Saunders, Amsterdam, NL, vol. 21, No. 3, Sep. 1, 2010, pp. 194-196, XP027541886, ISSN: 1043-1810.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 6A




FIG. 6B




FIG. 7

1

MIDDLE EAR IMPLANT COUPLER FOR MECHANICAL COCHLEA STIMULATION VIA THE ROUND WINDOW

This application claims priority from U.S. Provisional Patent Application, filed Feb. 27, 2017, which is incorporated herein by reference in its entirety.

TECHNICAL FIELD

The present invention relates to hearing implants and specifically an arrangement for electromechanical stimulation using a middle ear transducer and cochlear implant.

BACKGROUND ART

A normal ear transmits sounds as shown in FIG. 1 through the outer ear **101** to the tympanic membrane **102** which moves the bones of the middle ear **103** (malleus, incus, and stapes) that vibrate the oval window and round window membrane openings of the cochlea **104**. The cochlea **104** is a long narrow duct wound spirally about its axis for approximately two and a half turns in a human cochlea. It includes an upper channel known as the scala vestibuli and a lower channel known as the scala tympani, which are connected by the cochlear duct. The axial center of the cochlea **104** is called the modiolus where the spiral ganglion cells of the acoustic nerve **113** reside. In response to received sounds transmitted by the middle ear **103**, the fluid-filled cochlea **104** functions as a transducer to generate electric pulses which are sensed by the acoustic nerve **113** and sent to the brain.

FIG. 2 shows a functional representation of a normal cochlea **200**. The oval window membrane **201** comprises of a stiff center (stapes footplate) and a flexible surrounding across the opening to the fluid filled scala vestibuli **203**. Vibration from the footplate of the stapes drives the oval window membrane **203** creating pressure wave vibration in the fluid of scala vestibuli **203**. This in turn creates sympathetic pressure wave vibration in the fluid filled scala tympani **204** on the other side of the basilar membrane **205**. The pressure wave vibration of the fluid in the scala tympani **204** in turn drives the membrane of the round window membrane **202** with a frequency phase shift of for example 180 degrees at low frequencies from the vibration of the oval window membrane **201**.

Hearing is impaired when there are problems in the ability to transduce external sounds into meaningful action potentials along the neural substrate of the cochlea. To improve impaired hearing, hearing prostheses have been developed. For example, when the impairment is related to conductive hearing loss, a conventional hearing aid may be used to provide acoustic-mechanical stimulation to the auditory system in the form of amplified sound to the tympanic membrane. Or when the hearing impairment is associated with the cochlea, a cochlear implant with an implanted electrode carrier can electrically stimulate adjacent auditory neural tissue with small currents.

In some patients with some residual hearing in the lower acoustic frequencies, a conventional hearing aid and a cochlear implant can be combined together in a hybrid Electric Acoustic Stimulation (EAS) system. The hearing aid acoustically amplifies lower acoustic frequencies perceived by human ear, while the cochlear implant electrically stimulates the middle and high frequencies. See von Ilberg et al, *Electric-Acoustic Stimulation of the Auditory System*, ORL 61:334-340; Skarzynski et al, *Preservation of Low*

2

Frequency Hearing in Partial Deafness Cochlear Implantation (PDCI) Using the Round Window Surgical Approach, Acta Otolaryngol 2007; 127:41-48; Gantz & Turner, *Combining Acoustic and Electrical Speech Processing: Iowa/Nucleus Hybrid Implant*, Acta Otolaryngol 2004; 124:344-347; Gstöttner et al., *Hearing Preservation in Cochlear Implantation for Electric Acoustic Stimulation*, Acta Otolaryngol 2004; 124:348-352; all incorporated herein by reference.

FIG. 1 also shows some components of a typical EAS system which includes an external microphone that provides an acoustic signal input to an external signal processor **111** where two different signal processing paths are developed. An upper acoustic frequency range communications signal containing middle and high frequency components is converted into a digital data format, such as a sequence of data frames, for transmission via a transmitter coil **107** over a corresponding implanted receiver coil **106** into the electric implant **108**. Besides receiving the processed acoustic information, the electric implant **108** also performs additional signal processing such as error correction, pulse formation, etc., and produces an electric stimulation pattern (based on the extracted acoustic information) that is sent through an electrode lead **109** to an implanted electrode array **110**. Typically, this electrode array **110** includes multiple electrode contacts on its outer surface that provide selective electric stimulation of the cochlea **104**. The external signal processor **111** also creates a lower acoustic frequency range communications signal to a conventional hearing aid **105** in the ear canal which acoustically stimulates the tympanic membrane **102**, and in turn the middle ear **103** and cochlea **104**.

Middle ear implants (MEIs) are another alternative hearing prosthesis option for persons with moderate to severe conductive hearing loss who are insufficiently benefited by conventional mechanical hearing aids. Middle ear implants introduce a mechanical stimulation/vibration into the auditory system via a mechanical transducer implanted to an auditory structure in the middle ear, though the exact anatomical location at which this stimulation is delivered varies. For example, due to its small size, the Vibrant Soundbridge (VSB) device with its mechanical stimulator—the Floating Mass Transducer (FMT)—can be coupled to different auditory structures such as the incus, stapes/oval window or the round window. The hearing outcome that is achieved with the VSB strongly depends on the specific auditory coupling geometry. Currently, the hearing improvement with a VSB for frequencies >1 kHz has been shown to be better with coupling to the oval window or round window membranes, whereas lower frequencies are perceived better if the FMT is coupled to the incus.

FIG. 3 shows a simplified example of round window membrane stimulation where a mechanical middle ear stimulator, e.g., a floating mass transducer (FMT) **301** is placed with its flat front side directly in contact with the tissue of the round window membrane **202**. Electrical drive signals are delivered from the connecting cable **302** to the FMT **301** which in turns drives the round window membrane **202**. Preferably the FMT **301** is placed in the center of the round window membrane **202** where the tissue has its greatest possible elongation. But in existing round window coupling techniques, it is very difficult to determine whether or not the FMT **301** is properly positioned in relation to the round window membrane **202**, which is not visually accessible during surgery. For example, the FMT **301** may contact the bone surrounding the round window membrane **202** such that some of the vibrational energy does not enter the

cochlea **200**. In addition, when the FMT **301** is not orthogonal to the round window membrane **202**, that also decreases the amount of vibrational energy entering the cochlea **200**. Nonetheless, round window coupling is becoming ever more popular due to good performance with respect to speech recognition, and novel devices are in development for the improvement of this approach (e.g. the Hannover Coupler developed at the Hannover Medical School).

It has also been proposed that an EAS system could use a middle ear FMT for the acoustic mechanical stimulation instead of a conventional hearing aid, forming a CI/FMT system. See, Mueller et al. "Electro-Mechanical Stimulation of the Cochlea by Vibrating Cochlear Implant Electrodes" *Otology & Neurotology* 36.10 (2015): 1753-58; which is incorporated herein by reference in its entirety. For example, as shown in FIGS. 4A-4C, an FMT **402** can be incorporated at the distal end of a cochlear implant electrode lead **403**/the base of the electrode array **401** that is inserted into the cochlea via the round window membrane. Experimental results with such a CI/FMT arrangement were lower in amplitude for the FMT stimulation than as with conventional attachment of the FMT to the incus long process, but the loss disadvantage was significantly larger than might have been expected—insufficient vibrational energy is coupled into the cochlea.

SUMMARY

Embodiments of the present invention are directed to a round window coupling device for a hybrid electric-mechanical stimulation hearing implant system. A rigid outer shell has a proximal end, a distal end and an outer surface, and is configured to securely fit into a round window niche in a cochlear outer surface of a recipient patient. An electrode groove is located in the outer surface of the outer shell and is configured to snugly fit around a portion of a cochlear implant electrode array passing through the round window niche. A coupling filling is enclosed within the outer shell and is configured to couple mechanical vibrations from the proximal end of the outer shell to the distal end of the outer shell with minimal attenuation. A transducer receiver is located at the proximal end of the outer shell and is configured to connect to and receive vibrations from a drive surface of a mechanical transducer (e.g., a floating mass transducer (FMT)). And a drive face is located at the distal end of the outer shell and is configured to interface to perilymph fluid within the cochlea of the recipient patient to deliver vibrations from the coupling filling to the perilymph fluid with minimal attenuation for perception as sound.

In further specific embodiments, the drive face may comprise a drive membrane at the distal end of the outer shell. The coupling filling may comprise a silicone material or a liquid coupling material enclosed within end membranes located at each end of the outer shell. The outer shell may have a cylindrical shape or a frusto-conical shape configured to snugly fit into the round window niche to securely fix the coupling device and the electrode lead at the round window niche.

Embodiments of the present invention also include a hybrid electric-mechanical stimulation hearing implant system having a round window coupling device according to any of the foregoing.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows the anatomy of a human ear and various structures in a middle ear hearing implant system.

FIG. 2 shows a functional representation of a normal cochlea.

FIG. 3 shows a functional representation of a normal cochlea having a mechanical transducer engaged against the round window membrane.

FIGS. 4A-4C show details of prototype CI/FMT stimulation leads.

FIGS. 5A-5C show simplified versions of an FMT round window coupling device according to embodiments of the present invention.

FIGS. 6A-6B show examples of a CI/FMT round window coupling device according to embodiments of the present invention.

FIG. 7 shows an embodiment of a CI/FMT round window coupling device implanted in a recipient patient according to embodiments of the present invention.

DETAILED DESCRIPTION

Embodiments of the present invention are directed to a round window coupling device for a hybrid electric-mechanical stimulation hearing implant system that delivers vibrations from a connected middle ear transducer to the perilymph fluid in the cochlea with minimal attenuation. FIGS. 5A-5C show simplified versions of an FMT round window coupling device **500** according to embodiments of the present invention. The coupling device **500** has a rigid outer shell **501** (e.g. a rigid biocompatible polymer material) with a proximal end **503** and a distal end **504** and is configured to securely fit into a round window niche in a cochlear outer surface of a recipient patient.

A transducer receiver (e.g., a recessed receptacle) is located at the proximal **503** end of the outer shell **501** and is configured to connect to and receive vibrations from a drive surface of a mechanical transducer (e.g., a floating mass transducer (FMT)). A coupling filling **502** is enclosed within the outer shell **501** and is configured to couple mechanical vibrations from the proximal end **503** of the outer shell **501** to the distal end **504** of the outer shell **501** with minimal attenuation. For example, the coupling filling **502** may be soft, flexible, but non-compressible silicone material. The elasticity of the coupling filling **502** should be selected so that its natural internal oscillations are maximal within the frequency range of interest—i.e., frequencies at which the patient has reduced sound perception. A drive face is located at the distal end **504** of the outer shell **501** and is configured to interface to perilymph fluid within the cochlea of the recipient patient to deliver vibrations from the coupling filling **502** to the perilymph fluid with minimal attenuation for perception as sound. As shown in FIGS. 5A-5C, the coupling device **500** may have any advantageous specific shape such as generally cylindrical (FIG. 5A) or curved elbow (FIG. 5B). FIG. 5C shows a coupling device **500** having a generally frusto-conical shape that may advantageously configured to snugly fit into the round window niche to securely fix the coupling device **500** at the round window niche.

FIGS. 6A-6B show examples of a CI/FMT round window coupling device according to embodiments of the present invention that combine FMT coupling functionality with use of a cochlear implant electrode. In contrast to prior art CI/FMT efforts (e.g., FIGS. 4A-4C), embodiments of the present invention couple all of the mechanical energy of the FMT directly into the perilymph without losses, hence, serving as a decoupler of the FMT's vibrational energy from the electrode array.

5

The coupling device **600** has a rigid outer shell **601** (e.g. a rigid biocompatible polymer material) with a proximal end **603** and a distal end **604** and is configured to securely fit into a round window niche in a cochlear outer surface of a recipient patient. The coupling device **600** includes an electrode groove **605** that is located in the outer surface of the outer shell **601** and is configured to snugly fit around a portion of a cochlear implant electrode array passing through the round window niche. In the embodiment shown in FIG. 6A, the coupling device **600** has a generally cylindrical shape, while in the embodiment shown in FIG. 6B, the coupling device **600** has a generally frusto-conical shape configured to snugly fit into the round window niche to securely fix the coupling device **600** and the connected cochlear implant electrode lead at the round window niche.

A coupling filling is enclosed within the outer shell **601** and couples mechanical vibrations from the proximal end **603** to the distal end **604**. Also at the proximal end **603** is an FMT **607** that delivers the mechanical vibrations to the proximal end **603**. A drive face **606** is located at the distal end **504** of the outer shell **501** and is configured to interface to perilymph fluid within the cochlea of the recipient patient to deliver vibrations from the coupling filling to the perilymph fluid with minimal attenuation for perception as sound. The coupling filling may be soft, flexible, but non-compressible silicone material as discussed above, or a liquid coupling material enclosed within end membranes located at each end of the outer shell **601**, such that the end membrane at the distal end **604** serves as the drive face **606**. It will be noted that the coupling device **600**, and more specifically the proximal end **603** and/or the FMT **607**, can also usefully serve as a handling element to assist the implanting surgeon in controlling the cochlear implant lead during surgery.

FIG. 7 shows an embodiment of a CI/FMT round window coupling device **700** that is implanted in a recipient patient according to embodiments of the present invention. The coupling device **700** includes a transducer receiver **702** in the specific form of a recessed receptacle located at the proximal end of the coupling device **700** and is configured to connect to and receive vibrations from a drive surface of a mechanical transducer such as a floating mass transducer (FMT) **703** implanted in the middle ear **103**. An electrode groove **701** snugly fits around a distal end portion of a cochlear implant electrode lead **109** for an implanted electrode array **110** that passes through the round window niche into the cochlea **104**. A coupling filling **704** is enclosed within the coupling device **700** to couple mechanical vibrations from the connected FMT **703** to the implanted drive surface **705** with minimal attenuation to the perilymph fluid within the cochlea **104**.

Although various exemplary embodiments of the invention have been disclosed, it should be apparent to those

6

skilled in the art that various changes and modifications can be made which will achieve some of the advantages of the invention without departing from the true scope of the invention.

What is claimed is:

1. A round window coupling device for a hybrid electric-mechanical stimulation hearing implant system, the device comprising:

a rigid outer shell having a proximal end, a distal end and an outer surface, and configured to securely fit into a round window niche in a cochlear outer surface of a recipient patient;

an electrode groove in the outer surface of the outer shell configured to snugly fit around a portion of a cochlear implant electrode array passing through the round window niche, the cochlear implant electrode array external to the outer shell;

a coupling filling enclosed within the outer shell and configured to couple mechanical vibrations from the proximal end of the outer shell to the distal end of the outer shell with minimal attenuation;

a transducer receiver at the proximal end of the outer shell configured to connect to and receive vibrations from a drive surface of a mechanical transducer; and

a drive face at the distal end of the outer shell configured to interface to perilymph fluid within the cochlea of the recipient patient to deliver vibrations from the coupling filling to the perilymph fluid with minimal attenuation for perception as sound.

2. The coupling device according to claim 1, wherein the drive face comprises a drive membrane at the distal end of the outer shell.

3. The coupling device according to claim 1, wherein the coupling filling comprises non-compressible material.

4. The coupling device according to claim 3, wherein the non-compressible coupling filling comprises a silicone material.

5. The coupling device according to claim 3, wherein the non-compressible coupling filling comprises a liquid coupling material enclosed within end membranes located at each end of the outer shell.

6. The coupling device according to claim 1, wherein the outer shell has a cylindrical shape.

7. The coupling device according to claim 1, wherein the outer shell has a frusto-conical shape configured to snugly fit into the round window niche to securely fix the coupling device and the electrode lead at the round window niche.

8. The coupling device according to claim 1, wherein the mechanical transducer is a floating mass transducer (FMT).

9. A hybrid electric-mechanical stimulation hearing implant system having a round window coupling device according to any of claims 1-8.

* * * * *