

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
15 January 2009 (15.01.2009)

PCT

(10) International Publication Number
WO 2009/009131 A2

(51) International Patent Classification:
A61M 1/10 (2006.01)

(74) Agent: **TOPE-MCKAY, Cary, R.**; Tope-McKay & Associates, 23852 Pacific Coast Highway #311, Malibu, CA 90265 (US).

(21) International Application Number:
PCT/US2008/008539

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(22) International Filing Date: 11 July 2008 (11.07.2008)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/959,297 11 July 2007 (11.07.2007) US
61/010,786 11 January 2008 (11.01.2008) US

(71) Applicant (for all designated States except US): **CALIFORNIA INSTITUTE OF TECHNOLOGY** [US/US]; 1200 East California Blvd., MC 201-85, Pasadena, CA 91125 (US).

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **GHARIB, Morteza** [US/US]; 556 S. Berkeley Ave., San Marino, CA 91108 (US). **KHERADVAR, Arash** [US/US]; 300 Main Street, Columbia, SC 29208 (US). **GROSBERG, Anna** [US/US]; 434 S. Catalina Ave., #201, Pasadena, CA 91106 (US).

Published:

— without international search report and to be republished upon receipt of that report

(54) Title: CARDIAC ASSIST SYSTEM USING HELICAL ARRANGEMENT OF CONTRACTILE BANDS AND HELICALLY-TWISTING CARDIAC ASSIST DEVICE

(57) Abstract: A cardiac assist system using a helical arrangement of contractile bands and a helically-twisting cardiac assist device are disclosed. One embodiment discloses a cardiac assist system comprising at least one contractile elastic band helically arranged around a periphery of a patient's heart, where upon an actuation the band contracts helically, thereby squeezing the heart and assisting the pumping function of the heart. Another embodiment discloses a helically twisting cardiac-apex assist device comprising an open, inverted, substantially conical chamber with two rotatable ring portions of different diameters located at the base and apex of the chamber, with a plurality of substantially helical connecting elements positioned substantially flush with the chamber wall and connecting the two rotatable ring portions, whereby a relative twisting motion of the two rings causes a change in volume of the chamber thereby assisting the cardiac pumping function.



WO 2009/009131 A2

[0001] CARDIAC ASSIST SYSTEM USING HELICAL ARRANGEMENT OF
CONTRACTILE BANDS AND HELICALLY-TWISTING CARDIAC ASSIST
DEVICE

5 [0002] PRIORITY CLAIM

[0003] The present application is a non-provisional patent application, claiming the
benefit of priority of U.S. Provisional Application No. 60/959,297, filed on July 11,
2007, entitled "Method for reinforcing the cardiac pumping function," and U.S.
10 Provisional Application No. 61/010,786, filed on January 11, 2008, entitled
"Helically twisting cardiac-apex assist device."

[0004] BACKGROUND OF THE INVENTION

15 [0005] (1) Field of Invention

[0006] The present invention relates to a system and device for assisting cardiac
pumping function and, more specifically, to a system and device which assists the
cardiac pumping function through a helical arrangement of contractile members.

20 [0007] (2) Description of Related Art

[0008] Methods of assisting cardiac pumping function are known in the art. Existing
methods have provided assisted contraction transmitted radially or longitudinally
around the heart. These motions, however, do not mimic the natural contractile
motions of the heart, resulting in inefficient pumping and strain on the heart.

25

[0009] Thus, a continuing need exists for a cardiac assist device which mimics the
natural contractile motions of the heart to achieve a more efficient pumping
function.

30

[00010] SUMMARY OF INVENTION

[00011] The present invention relates to a system and device for assisting cardiac pumping function and, more specifically, to a system and device which assists the cardiac pumping function through a helical arrangement of contractile members.

5

[00012] In one aspect, the present invention teaches a cardiac assist system comprising at least one contractile elastic band configured for helical arrangement around a periphery of a patient's heart, where upon an actuation the at least one contractile band contracts helically, thereby squeezing the heart and assisting the pumping function of the heart.

10

[00013] In another aspect, the system further comprises at least one elastic band arranged in a shape selected from the group consisting of a helix and a double helix.

15

[00014] In yet another aspect of the system of the present invention, the at least one elastic band is comprised of a material selected from the group consisting of biocompatible elastic, viscoelastic materials, active polymers, shape-memory alloys, natural contractile muscle bands, and artificial contractile muscle bands.

20

[00015] In a further aspect, actuation of the system occurs via specific contraction wave propagation.

[00016] In another aspect, the system is configured such that the helical contraction is synchronized with the motion of the heart by a pacemaker.

25

[00017] In yet another aspect, the system further comprises a feedback mechanism for adjusting the contraction based on inputs received from the patient's cardiovascular system, the inputs being selected from the group consisting of ventricular pressure, volume, pulse pressure, ECG, volume, and pace maker signal.

30

[00018] In a further aspect of the system of the present invention, the at least one contractile band is configured to cover up the infarcted and ischemic areas of the heart's epicardial surface, thereby preventing aneurismal remodeling of the heart.

5 [00019] In another aspect, the present invention comprises a surgical method for attaching contractile muscle tissue around a patient's heart in a helical arrangement.

[00020] Another aspect of the present invention teaches a helically twisting cardiac-apex assist device comprising an open, inverted, substantially conical chamber having an apex, a base, and an elastic chamber wall, the chamber being of a shape and size
10 appropriate for fitting snugly over the apex of a heart. The device further comprises two rotatable ring portions of different diameters, the ring with the larger diameter circumscribing the base of the conical chamber, and the ring with the smaller diameter located near the apex of the chamber. The device further comprises a
15 plurality of substantially helical connecting elements positioned substantially flush with the chamber wall and connecting the two rotatable ring portions, whereby one ring can be twisted relative to the other, causing the helical connecting elements to deform helically, thereby increasing or decreasing a distance between the two rings, and correspondingly increasing or decreasing a volume of the chamber, thereby
20 providing assistance to the pumping functions of the heart.

[00021] In yet another aspect the device further comprises an actuator connected with the ring at the apex of the chamber, the actuator configured for anchoring inside a patient's chest cavity, whereby the actuator powers the twisting motion of one ring
25 relative to the other.

[00022] In a further aspect of the device of the present invention, the actuator is selected from a group consisting of a twisting rotor and muscle tissue.

30 [00023] In another aspect, the device is configured such that the actuator is synchronized with the motion of the heart by a pacemaker.

[00024] In yet another aspect of the device of the present invention, the ring portions and helical connecting portions are comprised of a material selected from the group consisting of shape memory materials and composite materials.

5

[00025] In another aspect, the elastic chamber wall is comprised of a material selected from the group consisting of biocompatible elastic and viscoelastic material.

10

[00026] The present invention also includes a method for surgical implantation of a helically-twisting cardiac-apex assist device with a heart, the method comprising acts of performing a partial, distal bi-ventriculectomy on the heart, and attaching the device with the heart's ventricles.

15

[00027] In another aspect of the method, in the act of performing the partial, distal bi-ventriculectomy, a patient's ventricular septum and papillary muscles are preserved.

20

[00028] In yet another aspect, the surgical method further comprises the act of attaching the device with another body part for support, the other body part being selected from the group consisting of the sternum and the base of the heart.

25

[00029] Finally, the method of the present invention further comprises the act of attaching a patient's papillary muscles and interventricular septum to the device with preservation of their blood supply.

[00030] BRIEF DESCRIPTION OF THE DRAWINGS

[00031] The objects, features and advantages of the present invention will be apparent from the following detailed descriptions of the various aspects of the invention in conjunction with reference to the following drawings, where:

30

[00032] FIG. 1A is a front-view illustration showing two possible arrangements of a contractile band grasping a heart;

[00033] FIG. 1B is a back view illustration showing two possible arrangements of a contractile band grasping a heart;

[00034] FIG. 1C is a bottom view illustration showing two possible arrangements of a contractile band grasping a heart;

[00035] FIG. 2A is an MRI image showing the myofibril structure of a heart;

[00036] FIG. 2B is an MRI image showing the myofibril structure of a heart with the contours of the myofibril structure highlighted with a white line;

[00037] FIG. 2C is an illustration showing the contours of the myofibril structure independent of the heart;

[00038] FIG. 3 is an illustration showing the helically-twisting cardiac assist device of the present invention;

[00039] FIG. 4A is an illustration showing the helically-twisting cardiac assist device of the present invention in elongated position and attached with a heart;

[00040] FIG. 4B is an illustration showing the helically-twisting cardiac assist device of the present invention in contracted position and attached with a heart;

[00041] FIG. 5A is an illustration showing a heart with a dotted line indicating the approximate location of the partial, distal bi-ventriculectomy;

[00042] FIG. 5B is an illustration showing the helically-twisting cardiac assist device of the present invention attached with the apex of a heart; and

[00043] FIG. 5C is an illustration showing the helically-twisting cardiac assist device of the present invention with attachment points to the base of a heart.

5 [00044] DETAILED DESCRIPTION

[00045] The present invention relates to a system and device for assisting cardiac pumping function and, more specifically, to a system and device which assists the cardiac pumping function through a helical arrangement of contractile members. The following description is presented to enable one of ordinary skill in the art to make and use the invention and to incorporate it in the context of particular applications. Various modifications, as well as a variety of uses in different applications will be readily apparent to those skilled in the art, and the general principles defined herein may be applied to a wide range of embodiments. Thus, the present invention is not intended to be limited to the embodiments presented, but is to be accorded the widest scope consistent with the principles and novel features disclosed herein.

[00046] In the following detailed description, numerous specific details are set forth in order to provide a more thorough understanding of the present invention. However, it will be apparent to one skilled in the art that the present invention may be practiced without necessarily being limited to these specific details. In other instances, well-known structures and devices are shown in block diagram form, rather than in detail, in order to avoid obscuring the present invention.

25 [00047] The reader's attention is directed to all papers and documents which are filed concurrently with this specification and which are open to public inspection with this specification, and the contents of all such papers and documents are incorporated herein by reference. All the features disclosed in this specification, (including any accompanying claims, abstract, and drawings) may be replaced by alternative features serving the same, equivalent or similar purpose, unless expressly

30

stated otherwise. Thus, unless expressly stated otherwise, each feature disclosed is only one example of a generic series of equivalent or similar features.

5 [00048] Furthermore, any element in a claim that does not explicitly state “means for” performing a specified function, or “step for” performing a specific function, is not to be interpreted as a “means” or “step” clause as specified in 35 U.S.C. Section 112, Paragraph 6. In particular, the use of “step of” or “act of” in the claims herein is not intended to invoke the provisions of 35 U.S.C. 112, Paragraph 6.

10 [00049] Further, if used, the labels left, right, front, back, top, bottom, forward, reverse, clockwise and counter clockwise have been used for convenience purposes only and are not intended to imply any particular fixed direction. Instead, they are used to reflect relative locations and/or directions between various portions of an object.

15 [00050] (1) Introduction

[00051] The present invention relates to a system and device for assisting cardiac pumping function and, more specifically, to a system and device which assists the cardiac pumping function through a helical arrangement of contractile members.
20 The description section below is divided into two parts corresponding to the two main embodiments of the present invention. Section (2) below discloses a cardiac assist system using a helical arrangement of contractile bands and surgical method for implanting the same, while section (3) discloses a helically-twisting cardiac assist device and surgical method for implanting the same.

25

[00052] (2) Cardiac Assist System Using Helical Arrangement of Contractile Bands

[00053] In one aspect, the present invention teaches a cardiac assist system that works based on the contraction of at least one contractile elastic band 100 grasping the heart 102 as shown in FIGs. 1A-C. The contractile band 100 may be arranged in a
30 helix, a double helix, or any other substantially helical arrangement which mimics the natural pumping function of the heart. The arrangements shown in FIGs. 1A-C

comprise two possible arrangements of a single contractile band 100 arranged in a double helix around the heart 102, attached to itself at an attachment point 104. The helical band arrangement assists both left and right ventricles during diastole to receive blood from the atria more efficiently, and helps both ventricles to eject the blood more effectively during systole and to improve both local and global cardiac function. The elastic bands 100 can be made of any types of biocompatible elastic or viscoelastic materials such as, but not limited to elastomers like *Resilin*, silicone rubber, or *Polyisobutylene*. Other materials suitable for the elastic bands are shape-memory alloys, natural contractile muscle bands, and artificial contractile muscle bands. The bands may also have a framework made of shape-memory materials/fibers.

[00054] The system works based on the idea that if contraction waves transmit through the bands at optimal angles around the heart, its pumping efficiency would be higher than if the contraction waves transmit radially or longitudinally. The general operating principles for this system are based on the operating principles of naturally occurring myofibril structures, which can be seen in recent MRI data as detailed in Helm, P., et al., Measuring and Mapping Cardiac Fiber and Laminar Architecture Using Diffusion Tensor MR Imaging. Ann NY Acad Sci; 2005. **1047(1):** p. 296-307. Unlike the myoplasty concept, this system not only assists the heart globally but also reinforces local function. FIG. 2A shows an MRI image of the myofibril structure of a heart 200. FIG. 2B is a similar MRI image with the contours of the myofibril structure highlighted with a white line 202. FIG. 3A is an illustration showing the contours of the myofibril structure 204 independent of the heart.

[00055] Another aspect of the cardiac assist system is synchronization of the contraction of the contractile bands with the natural heart motion. Synchronization would be made by devices such as, but not limited to, external and/or internal pacemakers. The activation of the band(s) can mimic the Purkinje activation of the cardiac muscle, i.e. starting at the apex and propagating to the periphery, or follow any

other specific contraction wave propagation scheme. This system can also have a feedback mechanism where the contraction waves sent through the bands are adjusted based on inputs received from the heart or vasculature; inputs such as but not limited to blood pressure, volume, ECG, pulse pressure, pace maker signal, etc. As a result the device would be able to self-adjust to changing demands of the heart. In another aspect, the system covers the infarcted/ischemic areas of the epicardial surface of the heart to prevent aneurismal remodeling. The present invention also improves coronary blood flow by accentuating the cardiac motion and pumping function of the heart.

[00056] (3) Helically-Twisting Cardiac Assist Device

[00057] In another aspect, the present invention teaches a cardiac assist device that works based on a helically twisting mechanism. The device assists both left and right ventricles during diastole to receive blood from the atria more efficiently, and helps both ventricles to eject the blood more effectively during systole. The shell of the device, as shown in FIG. 3, is an open, inverted, substantially conical chamber 300 having an apex 302, a base 304, and an elastic chamber wall 306, the chamber being of a shape and size appropriate for fitting snugly over the apex of a heart. Inside the conical chamber are two rotatable ring portions of different diameters, the ring with the larger diameter 308 circumscribing the base 304 of the conical chamber 300, and the ring with the smaller diameter 310 located near the apex 302 of the chamber 300. A plurality of substantially helical connecting elements 311 connects the two ring portions 308 and 310 and is substantially flush with the chamber wall 306. The device further comprises an actuator portion 312 connected with the smaller ring 310, where the actuator 312 is configured for anchoring inside a patient's chest cavity. The actuator 312 powers a twisting motion 314 of one ring relative to the other. The actuator 312 can be a motor such as a twisting rotor, which can be attached anywhere inside the chest, or the actuator 312 can be an internal power source such as *latissimus dorsi* muscle or any other internal structure. Twisting 314 the rings 308 and 310 in opposite relative directions, as shown in FIGs. 4A-B, results in deviation of the helical elements 311 from their

original angles, which increases or decreases the distance 400 between two rings.

In the case of increasing distance, the chamber induced dilation results in generation of negative pressure during diastole. In contrast, by decreasing the rings' relative distance, the device provides extra pumping force during systole. FIGs. 4A-B also show the device attached with a heart 402. Furthermore, the actuation of the device can be synchronized with the motion of the heart by an external or internal pace-maker.

[00058] The rings and helical elements of the device can be made of different selections of shape memory material such as *nitinol* and/or composite materials. The chamber wall can be made of any type of biocompatible elastic or viscoelastic materials such as, but not limited to, elastomers like *Resilin*, silicone rubber, *Polyisobutylene*, etc.

[00059] The present invention also includes a surgical procedure to implant the device via two or more sequential stages. The first stage, as shown in FIG. 5A, is a partial, distal bi-ventriculectomy 500 with preservation of the anatomical structures such as but not limited to ventricular septum 502 and the papillary muscles. In the second stage, as shown in FIG. 5B, the device 504 is attached to the ventricles 506. The device 504 can be stitched directly to the ventricles 506 and/or supported by additional connections to other internal organs such as but not limited to the sternum or the base of the heart 508. The papillary muscles, interventricular septum 502 and the other structures can be attached to the device 504 with preservation of their blood supply.

CLAIMS

What is claimed is:

1. A cardiac assist system comprising:

5 at least one contractile elastic band configured for helical arrangement
around a periphery of a patient's heart, where upon an actuation the at least one
contractile band contracts helically, thereby squeezing the heart and assisting the
pumping function of the heart.

2. The system of Claim 1, wherein the at least one elastic band is arranged in a shape
10 selected from the group consisting of a helix and a double helix.

3. The system of Claim 1, wherein the elastic band is comprised of a material selected
from the group consisting of biocompatible elastic, viscoelastic materials, active
polymers, shape-memory alloys, natural contractile muscle bands, and artificial
15 contractile muscle bands.

4. The system of Claim 1, wherein actuation occurs via specific contraction wave
propagation.

- 20 5. The system of Claim 1, wherein the system is configured such that the helical
contraction is synchronized with the motion of the heart by a pacemaker.

6. The system of Claim 1, further comprising a feedback mechanism for adjusting the
contraction based on inputs received from the patient's cardiovascular system, the
25 inputs being selected from the group consisting of ventricular pressure, volume,
pulse pressure, ECG, volume, and pace maker signal.

7. The system of Claim 1, where the at least one contractile band is configured to
cover up the infarcted and ischemic areas of the heart's epicardial surface, thereby
30 preventing aneurismal remodeling of the heart.

8. A surgical method comprising the act of attaching contractile muscle tissue around a patient's heart in a helical arrangement.

9. A helically twisting cardiac-apex assist device comprising:

5 an open, inverted, substantially conical chamber having an apex, a base, and an elastic chamber wall, the chamber being of a shape and size appropriate for fitting snugly over the apex of a heart;

 two rotatable ring portions of different diameters, the ring with the larger diameter circumscribing the base of the conical chamber, and the ring with the
10 smaller diameter located near the apex of the chamber; and

 a plurality of substantially helical connecting elements positioned substantially flush with the chamber wall and connecting the two rotatable ring portions,

 whereby one ring can be twisted relative to the other, causing the helical
15 connecting elements to deform helically, thereby increasing or decreasing a distance between the two rings, and correspondingly increasing or decreasing a volume of the chamber, thereby providing assistance to the pumping functions of the heart.

10. The device of Claim 9, further comprising an actuator connected with the ring at the
20 apex of the chamber, the actuator configured for anchoring inside a patient's chest cavity, whereby the actuator powers the twisting motion of one ring relative to the other.

11. The device of Claim 9, wherein the actuator is selected from a group consisting of a
25 twisting rotor and muscle tissue.

12. The device of Claim 9, configured such that the actuator is synchronized with the motion of the heart by a pacemaker.

13. The device of Claim 9, wherein the ring portions and helical connecting portions are comprised of a material selected from the group consisting of shape memory materials and composite materials.

5 14. The device of Claim 9, wherein the elastic chamber wall is comprised of a material selected from the group consisting of biocompatible elastic and viscoelastic material.



10 15. A method for surgical implantation of a helically-twisting cardiac-apex assist device with a heart, comprising acts of:
performing a partial, distal bi-ventriculectomy on the heart; and
attaching the device with the heart's ventricles.


15 16. The method of Claim 15, wherein the act of performing the partial, distal bi-ventriculectomy, a patient's ventricular septum and papillary muscles are preserved.

20 17. The method of Claim 15, further comprising the act of attaching the device with another body part for support, the other body part being selected from the group consisting of the sternum and the base of the heart.

25 18. The method of Claim 15, further comprising the act of attaching a patient's papillary muscles and interventricular septum to the device with preservation of their blood supply.

1/5





3/5




FIG. 3

4/5




FIG. 4A

FIG. 4B




FIG. 5A




FIG. 5B




FIG. 5C