

CORRECTED VERSION

(19) World Intellectual Property
Organization
International Bureau



(10) International Publication Number
WO 2014/105694 A8

(43) International Publication Date
3 July 2014 (03.07.2014)

(51) International Patent Classification:
B60C 11/00 (2006.01) *C08L 9/06* (2006.01)
C08J 3/05 (2006.01)

(21) International Application Number:
PCT/US2013/076895

(22) International Filing Date:
20 December 2013 (20.12.2013)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/747,663 31 December 2012 (31.12.2012) US

(71) Applicants (for all designated States except US): **COMPAGNIE GENERALE DES ETABLISSEMENTS MICHELIN** [FR/FR]; 12 Cours Sablon, F-63000 Clermont-ferrand (FR). **MICHELIN RECHERCHE ET TECHNIQUE S.A.** [CH/CH]; Route Louis Braille 10, CH-1763 Granges-Paccot (CH).

(72) Inventors; and

(71) Applicants (for US only): **CATO, Anthony, Derbin** [US/US]; c/o Michelin North America, Inc., Intellectual Property Dept, 515 Michelin Road, Greenville, SC 29605 (US). **STUBBLEFIELD, Raymond** [US/US]; c/o Michelin North America, Inc., Intellectual Property Dept, 515 Michelin Road, Greenville, SC 29605 (US). **SAINTIGNY, Xavier** [FR/US]; c/o Michelin North America, Inc., Intellectual Property Dept, 515 Michelin Road, Greenville, SC 29605 (US). **PIFFARD, Olivier** [FR/US]; c/o Michelin North America, Inc., Intellectual Property Dept, 515 Michelin Road, Greenville, SC 29605 (US).

(74) Agent: **CAMPIGOTTO, Frank, J.**; Michelin North America, Inc., Intellectual Property Dept., 515 Michelin Road, Greenville, SC 29605 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— of inventorship (Rule 4.17(iv))

Published:

— with international search report (Art. 21(3))

(48) Date of publication of this corrected version:

17 September 2015

(15) Information about Correction:
see Notice of 17 September 2015

(54) Title: TIRE TREAD WITH INCOMPATIBLE RUBBERS

(57) Abstract: A tread for a tire, the tread comprising a rubber composition that is based upon a cross-linkable elastomer composition, the cross-linkable elastomer composition comprising, per hundred parts by weight of rubber (phr), a high-Tg rubber being a highly unsaturated diene elastomer having a glass transition temperature of between -30 °C and 0 °C, a low-Tg rubber being a highly unsaturated diene elastomer having a glass transition temperature of between -110 °C and -60 °C. The high-Tg and the low-Tg elastomers are incompatible and this provides, among other advantages, improved snow traction of the tread when compared to tire treads having lower Tg.



WO 2014/105694 A8