

(12) **United States Patent**  
**Makam et al.**

(10) **Patent No.:** **US 10,162,944 B2**  
(45) **Date of Patent:** **Dec. 25, 2018**

(54) **LIBRARY STYLE MEDIA DRM APIS IN A HOSTED ARCHITECTURE**

(58) **Field of Classification Search**  
CPC .. G06F 21/105; H04L 63/06; H04L 2463/101  
See application file for complete search history.

(71) Applicant: **ARRIS Enterprises LLC**, Suwanee, GA (US)

(56) **References Cited**

(72) Inventors: **Ambikacharan P. Makam**, San Diego, CA (US); **Paul Moroney**, La Jolla, CA (US); **Steven Anderson**, San Diego, CA (US); **Rafie Shamsaasef**, San Diego, CA (US); **Nicol C. P. So**, Newtown, PA (US)

U.S. PATENT DOCUMENTS

- 7,319,759 B1 \* 1/2008 Peinado ..... H04L 9/0825 380/277
- 2004/0001594 A1 \* 1/2004 Krishnaswamy ... H04L 63/0428 380/277
- 2004/0003270 A1 \* 1/2004 Bourne ..... G06F 21/10 713/193
- 2004/0158731 A1 \* 8/2004 Narin ..... G06F 21/6263 726/27
- 2014/0047558 A1 \* 2/2014 Veerubhotla ..... G06F 21/105 726/28

(73) Assignee: **ARRIS Enterprises LLC**, Suwanee, GA (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 176 days.

\* cited by examiner

*Primary Examiner* — Morshed Mehedi  
(74) *Attorney, Agent, or Firm* — Thomas A. Ward

(21) Appl. No.: **15/085,970**

(57) **ABSTRACT**

(22) Filed: **Mar. 30, 2016**

Systems and methods are provided for digital rights management of licensed media content. Client library components and server library components provide digital rights management services. A client-side hosting application accesses client library functionality through invocation of client application programming interfaces (APIs). A server-side hosting application accesses server library functionality through invocation of server APIs. Licenses for specific media content can be requested and issued, and appropriately licensed media content can be played. Client and server library components can function essentially absent direct communication, such as that employing a transport layer. Communications between client and server library components can be carried by the hosting applications.

(65) **Prior Publication Data**

US 2016/0292398 A1 Oct. 6, 2016

**Related U.S. Application Data**

(60) Provisional application No. 62/140,076, filed on Mar. 30, 2015.

(51) **Int. Cl.**  
**H04L 29/00** (2006.01)  
**G06F 21/10** (2013.01)  
**H04L 29/06** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **G06F 21/105** (2013.01); **H04L 63/06** (2013.01); **H04L 2463/101** (2013.01)

**8 Claims, 15 Drawing Sheets**




FIG 1




FIG 2







FIG 3



**FIG 4**



**FIG 5**





FIG 6




FIG 7




FIG 8A




FIG 8B




FIG 9




FIG 10




FIG 11




FIG 12




FIG 13





FIG 14



1

## LIBRARY STYLE MEDIA DRM APIS IN A HOSTED ARCHITECTURE

### CLAIM OF PRIORITY

This application claims priority under 35 U.S.C. § 119(e) from earlier filed U.S. Provisional Application Ser. No. 62/140,076, filed Mar. 30, 2015, which is hereby incorporated by reference.

### TECHNICAL FIELD

The present disclosure relates to the field of digital rights management (DRM), particularly to client and server DRM services in association with client and server applications.

### BACKGROUND

Typical digital rights management (DRM) systems and methods comprise end-to-end structures in which a client DRM module directly and actively communicates with a server DRM module, in order to perform DRM related transactions. A client DRM module and server DRM module typically communicate directly, via a transport layer. The server DRM module can be stateful, and can persist a database. In such systems, the communication scheme for client and server DRM modules can be additional to and can rely on underlying communication schemes. In such systems, the communication scheme for client and server DRM modules can replicate network services that are managed by a hosting system.

### SUMMARY

Thus, DRM systems and methods are needed that can easily integrate and work within an existing ecosystem, without necessarily replicating and/or relying on some underlying communication schemes and without need to persist a database on the server. Such systems and methods can be adapted to end-to-end media delivery systems by integrating into the end-point processes of content injection and content consumption.

Systems and methods for digital rights management of licensed media content are depicted and described herein. Client library components and server library components can provide digital rights management services. Such services can be provided in association with specified operating system platforms. A client-side hosting application can access client library functionality through invocation of client application programming interfaces (APIs). A server-side hosting application can access server library functionality through invocation of server APIs. Licenses, that is, DRM licenses, for specific media content can be requested and issued, and thus appropriately licensed media content can be accessed and/or played.

In some embodiments, a server-side hosting application can proactively issue such licenses to a client. That is, a client application can be issued licenses additional to those requested. Identification of specific media content corresponding to the additional licenses can be responsive to license cues. License cues can comprise specified parameters such as those associated with a user profile, and/or usage patterns.

License Identification Information (LII) can be delivered by more than one mechanism. A license request transaction can convey a bundled plurality of LII. Thus a single instance of a license request transaction can request a plurality of

2

licenses. A hosting application can retrieve LII from a backend system, or, embed LII in content files. Delivery mechanisms support both of license prefetching and obtaining a license at time of playback.

Client and server library components support abstraction at the client application level. A relatively small number of calls from, and interactions with, the client application can deliver powerful specific DRM services comprising many interactions and steps. Some of the invocations of such DRM services can be absent direct interactions with the client application.

In one embodiment, the present disclosure provides for a method for digital rights management (DRM) of licensed media content, the method comprising provisioning a DRM client module with a unique client certificate and storing the certificate, a client application issuing a DRM license request that corresponds to specified media content and employs the certificate and occurs after a specific interaction between a client application and the DRM client module, the client application receiving in response to the DRM license request a first DRM license and additional DRM licenses respectively corresponding to the specified media content and additional media content, the DRM client module deriving a content key from the first DRM license, the client application initiating play of the specified media content, and, the playing of the specified media content by employing the content key.

In another provided embodiment of a method for digital rights management of licensed media content, a method comprises provisioning a DRM client module with a unique client certificate and storing the certificate, a client application initiating play of specified media content, the client application receiving a notification of license need, the client application issuing a DRM license request that corresponds to specified media content and employs the certificate and occurs after a specific interaction between a client application and the DRM client module, the client application receiving in response to the DRM license request a DRM license corresponding to the specified media content, the DRM client module deriving a content key from the DRM license, and, playing of the specified media content by employing the content key.

In another embodiment, the present disclosure provides for a system for digital rights management of licensed media content, the system comprising a client application and a DRM client module, in which the client application is configured to: be provisioned with a unique client certificate, invoke the DRM client module to store the certificate, issue a DRM license request that corresponds to specified media content and employs the certificate and occurs after a specific interaction between a client application and the DRM client module, receive a first DRM license and additional DRM licenses respectively corresponding to the specified media content and additional media content, and initiate play of the specified media content; in which the DRM client module is configured to derive a content key from the first digital rights management license, and, in which play of the specified media content employs the content key.

### BRIEF DESCRIPTION OF THE DRAWINGS

Further details of the present invention are explained with the help of the attached drawings in which:

FIG. 1 depicts a content delivery ecosystem

FIG. 2 depicts a Hosted DRM system

FIG. 3 depicts Hosted DRM system processing for: get unique client certificate/key  
 FIG. 4 depicts Hosted DRM system processing for: DRM license acquisition request  
 FIG. 5 depicts Hosted DRM system processing for: Content key and rights information  
 FIG. 6 depicts Hosted DRM system processing for: DRM license acquisition response  
 FIG. 7 depicts a use case for: provisioning a device  
 FIG. 8A depicts a use case for license acquisition  
 FIG. 8B depicts a use case for: license acquisition, detail  
 FIG. 9 depicts a use case for: Play Streaming content: iOS  
 FIG. 10 depicts a use case for: Play Streaming content: Android, PC and MAC  
 FIG. 11 depicts a use case for: Play Streaming content: Set-top Boxes (STBs)  
 FIG. 12 depicts a use case for: Initiate acquiring license  
 FIG. 13 depicts a client API Overview  
 FIG. 14 depicts a server API Overview

DETAILED DESCRIPTION

The ARRIS SecureMedia (ASM) Software Development Kit (SDK) can provide access to a collection of client and server services. These services enable the integration of Digital Rights Management (DRM) services with client and server applications. Employing ASM client and server Application Programming Interfaces (APIs), client applications can provide for delivery of DRM licensed media content to authorized devices securely, and on a variety of platforms.

Details of ARRIS SecureMedia Client (ASMC) and Server (ASMS) components are herein described, as they fit into a content delivery ecosystem, depicted in diagram 1000. The descriptions comprise use cases and APIs exposed by client and server libraries. Some functions are defined from the application (app) perspective, as the “caller” of the services exposed by the SDK APIs.

Client and server SDKs each comprise passive library modules that can be used by a hosting application. Notably, in some embodiments, such modules do not employ out of band network access and thus do not directly exchange messages. That is, the modules function essentially absent direct communication, such as that employing a transport layer. In described embodiments, DRM transactions can be created as message blocks by DRM components, and carried by the hosting application to the other party as depicted in diagram 1000.

A client hosting application 1001 can access ASMC DRM library 1002 components and hence their functionality by invoking client APIs. A server-side hosting application 1003 can access SMCS DRM library 1004 components and hence their functionality by invoking server APIs. Communications between DRM components 1002 1004 can be accomplished through the corresponding hosting applications 1001 1003.

Client hosting application 1001 can be described as a hierarchically superior application HSA, and particularly so with respect to ASMC DRM Library 1002. Server hosting application 1003 can be described as a hierarchically superior application HSA, and particularly so with respect to ASMS DRM Library 1004. Herein, a client hosting application 1001 can be alternatively referred to as a client application or client app. Herein, a server hosting application 1003 can be alternatively referred to as a server application or server app.

A client application interface with ARRIS Client DRM module (ASMC), client media player interface with ASMC module, and infrastructure component License Server interface with ARRIS Server DRM module (ASMS) are specified herein.

Some acronyms employed in the descriptions herein comprise:

Acronym	Description
API	Application Programming Interface
ASM	ARRIS SecureMedia
ASMC SDK	ARRIS SecureMedia Client SDK
ASMS SDK	ARRIS SecureMedia Server SDK
HLS	HTTP Live Streaming
DRM	Digital Rights Management
LKGT	Last Known Good Time
OPUS	Online Personalization Update Server
SDK	Software Development Kit
ECM	Entitlement Control Message
STB	Set Top Box
TEE	Trusted Execution Environment
URL	Uniform Resource Locator
CPI	Content Protection Information
LIBundle or LIB	License Identification Bundle
LII	License Identification Information

A License Identification Bundle (LIB) can be used in license request generation. A LIB structure can contain one or more License Identification Information (LII). A LIB can be used by a client app in conjunction with a DRM key-system in order to fetch licenses required for access to specific content. LIB can be built by the infrastructure during content packaging, as defined within the scope of the DRM key-system.

A License Identification Information (LII) can serve as a provider domain unique identifier. A LII can unambiguously point to license information corresponding to specified content. Such license information can be required in order to render content.

A License structure can comprise content rights, key, and/or any associated content metadata. A specific piece of content can have multiple associated licenses.

Content Protection Information (CPI) can point to a license that is required in order to render a specified content and/or content component. The CPI can be delivered in band (e.g. in a MPEG Part-12 file, and/or a DASH transport stream, and/or a transport stream ECM). The CPI can be delivered out of band (e.g. in the HLS playlist an d/or DASH MPD). CPI can be employed by ASMC\_SetKey API.

Within the descriptions herein, individual functions and elements are alternatively described as steps and/or functions.

Within the descriptions herein, “playback” can encompass play of stored media and play of streamed media and play of any other known and/or convenient forms of media. Thus “playback” is not restricted to ‘playing back.’ Such “playback” can alternatively be described as “play” and “playing.”

Diagram 2000 depicts DRM SDK libraries in an example hosted system. Within an operator infrastructure 2021 a License Server 2026 hosts server-side ASMS DRM library modules 2027. A client application 2011 hosts client-side ASMC DRM library modules 2012. ASMC DRM library modules can locally utilize certificates and keys 2013 and license files 2014. Client application 2011 can interact with online personalization update server, OPUS Server 2015. for access to client certificates and keys. A package 2024 within

the operator infrastructure **2021** can provide content delivery **2015** for the client application **2011**.

Notable Arris DRM-related transactions are shown in the diagram **2000** and further illustrated and described in diagrams **3000 4000 5000 6000**. Client application **2011** can interact with OPUS server **2015** to “Get Unique Client Certificate/Key” **2001**. Client application **2011** can issue a request for a DRM license to License Server **2026** with “DRM License Acquisition Req Msg” **2002**. License Server **2026** can provide a corresponding response by “DRM License Acquisition Resp. Msg” **2004**. License Server **2026** can provide a request, content key, and rights information to the ASMS DRM library **2027** modules by “Content Key & Rights Insertion/DRM Msg” **2003**.

Content Provider Back Office **2022** can be provided by a content provider. It can determine and provide appropriate granting of access (entitlement) to a client device for a specific content.

Content Key Manager **2023** can be provided by a content provider. It can create and/or manage content encryption key(s) CEK that can be required for encryption and/or decryption of content. Such content can comprise audio, video, and/or any other known and/or convenient content.

Packager **2024** can be provided by a content provider. It can provide content suitable for consumption on a client device by performing a variety of functions. Such functions can comprise encrypting audio and/or video tracks, encoding content at various bit rates and/or at various resolutions, and packaging protected content into various media file formats. In some embodiments, packaged content can be made available to client devices over a Content Distribution Network.

Certificate Revocation Service **2025** can be provided by a content provider. It can provide a Certificate Revocation List CRL. The CRL can provide a list of blacklisted client certificates. In some embodiments such blacklisted client certificates can be revoked and/or denied access to the system.

In element Client Revocation Check **2031**, a License Server **2026** can obtain a CRL. License Server **2026** can determine a blacklisted status for a client device that requests a content license.

Element Client Entitlement Check **2032** can be invoked upon a client device request for a content license. License Server **2026** can engage with Back Office **2022** to determine appropriate access corresponding to a specific consumer and specific selected content.

As Packager **2024** prepares content, it can request corresponding Content Key Info **2033** from Content Key Manager **2023**. Such Content Key Info **2033** can comprise content key information and metadata elements. Packager **2024** can provide content manifest files that comprise those elements. In some embodiments, a client DRM component can employ such content key information and metadata in requesting a content license for access and/or playback of the corresponding content.

In the descriptions herein, “transaction” can identify embodiments that provide one or more distinct DRM services. Such a service, by way of non-limiting examples, can be provisioning a device, license acquisition, playing of content, and/or initiating license acquisition. A transaction can comprise another transaction. A transaction can comprise numerous interactions between system elements, and numerous steps.

In the descriptions herein, an “interaction” can comprise embodiments in which components interact. By way of non-limiting examples, such interactions can comprise an

individual step such as a data transmission between client and server applications, and/or, a multi-step operation such as a message exchange between components such as client and server applications and client and server library components. An interaction can comprise numerous steps.

Diagram **3000** depicts details of an embodiment of “Get Unique Client Certificate/Key” **2001**, corresponding to step **3001** “get unique client certificate/key” which can comprise further steps.

In step **3002** (of step **3001**), a client app **2011** can issue a request for a “provisioning request” from ASMC DRM library **2012**.

In step **3003** (of step **3001**), ASMC DRM modules can generate an OPUS request message.

In step **3004** (of step **3001**), the client app can send the OPUS request message to OPUS Server **2015**, receive a corresponding response, and provide the response to the ASMC DRM library modules.

In step **3005** (of step **3001**), which can comprise further steps, ASMC DRM modules can store certificates and keys.

In step **3051** (of step **3005**), ASMC DRM modules can process the OPUS response.

In step **3052** (of step **3005**), ASMC DRM modules can securely store a certificate and a private key. In some embodiments, stored certificates and keys can be employed in future, that is, in later-occurring transactions and/or processes.

Diagram **4000** depicts details of an embodiment of “DRM License Acquisition Req Msg” **2002**, corresponding to step **4001** “DRM License Acquisition request” which can comprise further steps.

In step **4002** (of **4001**), a client app can request a license for a specific piece of content.

In step **4003** (of **4001**), ASMC DRM modules can create a license acquisition request message.

In step **4004** (of **4001**), the client app can send the license acquisition request message to a license server **2026**.

Diagram **5000** depicts details of an embodiment for “Content Key and Rights Information” **5001**, some steps of which correspond to of “Content Key & Rights Insertion/DRM Msg” **2003**. Step **5001** “Content Key and Rights Information” can comprise further steps.

In step **5002** (of **5001**), License Server **2026** can perform an authorization check for requested content. Such an authorization check can correspond to “Client Entitlement Check” **2032** and can comprise interactions with a back office server database, such as “Content Provider Back Office” **2022**.

In step **5003** (of **5001**), a license server **2026** can provide the request DRM message, content key and rights information to ASMS DRM modules **2027**.

Diagram **6000** depicts details of an embodiment for “DRM License Acquisition response” **6001**, some steps of which correspond to of “DRM License Acquisition Resp. Msg” **2004**. Step **6001** “Content Key and Rights Information” can comprise further steps.

In step **6002** (of **6001**), ASMS DRM modules can process the request message and creates a response. The response can comprise embedded license material and current server-time for the requested content. In some embodiments, the provided current server-time can be employed for secure time management on a client.

In step **6003** (of **6001**), a license server such as License Server **2026** can send the response to a client app **2011**.

In step **6004** (of **6001**), ASMS DRM modules can create a license file. Step **6004** can comprise further steps.

In step **6041** (of **6004**), a client app **2011** can pass the response message to ASMC DRM modules **2012** for license creation.

In step **6042** (of **6004**), ASMC DRM modules can create and store a license file **2014** corresponding to the requested content. The license file can be stored for future usage.

In step **6043** (of **6004**), a client app **2011** can request local playback of the licensed content.

In step **6044** (of **6004**), ASMC DRM modules can provide a content key corresponding to the requested content. Thus a client device can employ the key to render the content. Alternatively, ASMC DRM modules can perform decryptions and provide clear content. Thus a client device can employ the clear content to render the content.

Assumptions and Requirements:

Some system embodiments can operate under the following assumptions and/or requirements:

1. The ASMS DRM module (server side) shall not require any persistent database.

2. The ASMC DRM module (client side) does not have access to the IP transport layer (Eg: cannot communicate with other modules over the network). The application layer shall manage transport of DRM messages between ASMC DRM client and ASMC DRM server modules.

3. The client application can invoke the ASMC DRM module to “request license” upon making a service choice.

4. The Media player module can receive content with Content Protection Information (CPI). The CPI can be a keytag or an ECM equivalent. The keytag can inform the ASMC DRM module of a specific license ID in use, and can provide related DRM specific information. Each new reception of CPI, inherently referencing a content key, can cause the player to send that CPI to its decryption component. Decryption components can comprise software plug-ins, NSURL, and/or CDM. This plug-in (hardware or software) can extract any relevant information, such as the IV. The plug-in can act as an interface, and send a key request to the DRM library. The DRM library can send the resulting key to the plug-in in a client platform dependent manner. This can ensure that a client application will not have access to the content key. The plug-in dependent interface can allow for the usage of NSURL for Apple iOS clients, an obfuscated DRM decryption plug-in for Android software players, and/or hardware related solutions for TEE architectures and STBs.

Software Components

Some embodiments of the ARRIS DRM system comprise libraries with defined interfaces in C and Java. In some embodiments, there is essentially no transport layer built in to these library components. They can rely solely on the application layer to send and receive DRM messages between the DRM client library and DRM server library. The ASMS DRM library can be optimized to maintain client authentication and registration data in a session, for any future (limited duration) usage; however, it doesn’t require any database or persistent data storage. In some embodiments, the ASMC DRM client side libraries are available in a variety of specific environments and/or platforms. Such environments can comprise iOS, Android, Mac and/or Windows platforms. In some embodiments, an ASMS DRM server side library is available for Linux.

Diagram **7000** illustrates a use case for provisioning a client device. A client device can be provisioned in order to access secure content from a server.

In step **7011** client app **7001** calls and ASMC SDK **7002** receives ASMC\_GetProvisioning Request(prov\_req).

In step **7012** ASMC SDK **7002** checks local cuts.

In step **7013** ASMC SDK **7002** provides and client app **7001** receives DRM\_Msg\_blob.

In step **7014** client app **7001** submits and OPUS **7003** receives DRM\_Msg\_blob.

In step **7015** OPUS **7003** provides and client app receives **7001** OPUS\_response\_msg\_blob.

In step **7016** client app **7001** calls and ASMC SDK **7002** receives ASMC\_ProcessProvisioning Reply(OPUS\_response\_msg\_blob).

In step **7017** ASMC SDK **7002** stores certificates.

In step **7018** ASMC SDK **7002** provides and client app **7001** receives OK.

Diagrams **8000** and **8100** depict a use case for acquiring a license, that is, license acquisition. A client application can acquire a license prior to playing a specific content.

In step **8010**, client app **8001** acquires LIBundle.

In step **8011** server app **8003** calls ASMS\_Init(CRL\_CBHandle,CRL\_File) in order to initialize the overall DRM system. The call is received by ASMS SDK **8004**.

In diagram **8100**, element **8111** depicts further detail of step **8011**. ASMS\_Init can be called with either of the call-back handle “CRL\_CBHandle” or the file “CRL\_File,” corresponding to a certificate revocation list. In step **8012** ASMS SDK **8004** stores CRL\_CBHandle or CRL\_File.

In step **8013** ASMS SDK **8004** provides OK to server app **8003**.

In step **8014** client app **8001** calls ASMC\_GetLicenseRequest(LIBundle,appData,continueFlag, . . . ). The call is received by ASMC SDK **8002**.

In step **8015** ASMC SDK **8002** creates a message blob “msg blob.” Object **8124** can serve to identify media content. In some embodiments, a message blob can be a data object that can be made opaque through cryptographic methods.

In diagram **8100**, element **8115** depicts further detail of the message blob created in step **8015**. The message blob can comprise a License Identification Bundle, a Client Certificate, and/or appData such as In\_appData as herein described regarding ASMC\_GetLicenseRequest.

In step **8016** ASMC SDK **8002** provides and client app **8001** receives ASMC\_msg\_blob.

In step **8017** client app **8001** provides and server app **8003** receives ASMC\_msg\_blob. In steps **8018** through **8022**, server app **8003** can proactively generate license requests and hence licenses. That is, server app **8003** receives some specified license information within ASMC\_msg\_blob of step **8017**. In further steps **8018** through **8022**, server app **8003** can perform steps and/or transactions advocating for additional licenses. Server app can provide specific identifying information corresponding to the additional licenses. This identifying information can be responsive to license cues **8118**, depicted in diagram **8100**. Such cues can comprise parameters and/or usage patterns to which the server app **8003** has access. In some embodiments, a server app can develop and/or manage such cues. In some embodiments the cues can further comprise any known and/or additional structures and methods as are suitable to the purpose.

In step **8018** server app **8003** calls and ASMS SDK **8004** receives ASMS\_RetrieveKeyIDs(ASMC\_msg\_blob). ASMS\_RetrieveKeyIDs retrieves a list of key IDs from the ASMC\_msg\_blob.

In step **8019** ASMS SDK **8004** provides and server app **8003** receives “handle, keyIDs[ ].” That is, the server app **8003** receives a list of key IDs “keyIDs[ ]” and the corresponding DRM handle.

Step **8020** depicts server app **8003** checking entitlements corresponding to a particular device with “Check Entitlements (deviceID).”

Step **8021** depicts server app **8003** getting keys and rights with “Get keys, rights . . .”

In step **8022** server app **8003** calls and ASMS SDK **8004** receives ASMS\_CreateLicense(handle, Struct\_KeyInfo[ ]).

In step **8023** ASMS SDK **8004** provides CRL callback OR Check CRL\_File, corresponding to the selected option of step **8011** ASMS\_Init.

In step **8024** ASMS SDK **8004** creates message blob “msg blob.”

In diagram **8100**, element **8124** depicts further detail of the message blob created in step **8024**. The message blob **8124** can comprise rights information corresponding to streaming and/or SnG.

In step **8025** ASMS SDK **8004** provides and server app **8003** receives ASMS\_msg\_blob.

In step **8026** server app **8003** provides and client app receives **8001** ASMS\_msg\_blob.

In step **8027** client app **8001** calls and ASMC SDK **8002** receives ASMC\_ProcessLicense Reply(ASMS\_msg\_blob).

In step **8028** ASMC SDK **8002** processes the “msg blob.”

In step **8029** ASMC SDK **8002** can store one or more licenses. The licenses can comprise content keys and license information. In descriptions herein, a content key can be alternatively described as a key. In some playback scenario embodiments, such keys can be derived from the stored license or licenses. Deriving a key in such a manner can be alternatively described herein as extracting or retrieving a key. By way of non-limiting example, diagram **10000** depicts a use case for Play Streaming Content. In step **10013** of the diagram, a digital rights management client module **10003** can derive a key from a stored license.

In step **8030** ASMC SDK **8002** provides and client app **8001** receives “SUCCESS:licIDLList/CONTINUE/ERROR.” That is, the client app **8001** receives a status message. The status message can indicate success and provide corresponding license identification “SUCCESS:licIDLList,” indicate to continue processing “CONTINUE,” and/or indication an error “ERROR.”

In step **8031** server app **8003** calls and ASMS SDK **8004** receives ASMS\_Close.

In step **8032** ASMS SDK **8004** provides and server app **8003** receives OK.

Step **8033** depicts a selectably repeatable execution loop of steps **8014** through **8030**. A selection can be made responsive to the status message of step **8030**.

#### Opaque Tunneling

Some embodiments notably comprise messaging methods that can be described as opaque tunneling, with regard to messaging between client application and server application. Opaque tunneling provides for secure communications between client and server applications. Although client and server applications can be in direct communication, there can be a need for secure messaging services that can be supported by the client and server DRM modules.

In the case of messaging from a client application to a server application, a message from the client application can be passed to client library components for encoding/encryption. The encoded/encrypted message can be returned to the client application that can directly communicate it to the server application. The server application can pass the encoded/encrypted message to the server library components for decoding/decryption. The decoded/decrypted message can finally be delivered to the server application.

Secure messaging from server application to client application can be accomplished similarly. A message starting from a server application can be passed through server library components for encoding/encryption and returned to the server application. The server application can directly communicate the message to the client application. The client application can pass the encoded/encrypted message to the client library components for decoding/decryption. The decoded/decrypted message can finally be delivered to the client application.

By way of non-limiting example, a client application to server application secure communication is depicted in diagrams **8000** and **8100**, corresponding to a license acquisition process.

In response to client message ASMC\_GetLicenseRequest( ) **8014**, the ASMC DRM library components of ASMC SDK **8002** can generate an encoded/encrypted ASMC\_msg\_blob in step **8015** and provide it to the client application **8001**. The ‘blob’ can be communicated directly to server application **8003**. In turn, server app **8003** can pass the encoded message to server library components **8004** with ASMS\_RetrieveKeyIDS( ) in step **8018**. The server component **8004** can decode/decrypt the message and provide it to server app **8002**.

In some notable embodiments, the direct client-to-server communication ASMC\_msg\_blob of step **8017** can take place over insecure links without compromising the secure nature of the encrypted/encoded message.

Specific interactions within the license acquisition use case depicted in diagrams **8000** and **8100** have been employed for non-limiting examples of opaque tunneling. Notably, other use cases and interactions depicted herein can comprise such methods.

#### Multiple Delivery Methods for License Identification Information Structures

ASMC and ASMS components support a plurality of delivery mechanisms for License Identification Information (LII). A hosting application can retrieve LII from a backend system, or, embed LII in content files. Delivery mechanisms support both license prefetching and obtaining a license at time of playback.

In diagram **8000**, a LIBundle comprising LII can be obtained prior to calling ASMC\_GetLicenseRequest in step **8014**. In this case, a client application **8001** provides the LII. By way of examples, such an LII can be obtained from a back office entity **2022** such as depicted in diagram **2000**, and/or by other customer specific information available to the client application. In this manner, a license can be ‘prefetched’ and thus contribute to minimizing delay for playback operations. In some embodiments, such a prefetching operation requires getting LIBundle data from a component other than an ASMC library component.

#### Client Application Abstraction

ASMC and ASMS components support abstraction at the client application level. In some embodiments, a relatively small number of calls from, and interactions with, the client application can deliver powerful specific DRM services comprising many interactions and steps. Diagrams **8000** and **8100** depict an exemplary embodiment of this concept in a license acquisition use case. Client app **8001** issues API calls ASMC\_GetLicenseRequest in step **8014**, ASMC\_ProcessLicenseReply in step **8026**, and selectively repeats the acquisition process per element **8033**. The system provides numerous additional interactions and steps responsive to those very few direct interactions with the client application. The additional interactions and steps can comprise specific DRM services, such as license creation. License creation can

## 11

specifically comprise step **8018** ASMS\_RetrieveKeyIDs( ) and step **8019** that returns a handle and keys. Elements of license creation, and other interactions and steps, can be performed absent direct interactions with the client application.

Diagram **12000** corresponds to an embodiment in which a license can be obtained at the point of playback. Upon determining that a corresponding license does not exist in step **12014**, a LIBundle comprising LII can be generated in step **12015**. In some embodiments, such an operation for obtaining a license at the time of playback requires that the client application get LIBundle data from an ASMC component. In diagram **12000**, this is depicted as step **12016** in which ASMC DRM-Core **12004** provides ASMC\_Aquire-LicenseRequest(LIBundle, . . . ).

Diagram **9000** depicts a use case for playing streaming content in a specified operating system environment. The environment can be an iOS environment. In some embodiments, an iOS native HLS player can be employed for playing streaming content. In some embodiments, a CPI of #EXT-X-KEY tag corresponds to HLS content type.

In step **9010** NSURL module **9003** invokes Register Custom\_protocol. In some embodiments, a custom protocol such as "asm://" can be registered.

In step **9011** client app **9001** calls and media player **9002** receives Play(contentURL,inHomeStatus, . . . )

In step **9012** media player **9002** parses media in order to extract CPI "Parse media, Extract CPI."

In step **9013** media player **9002** provides and NSURL module **9003** receives getKey\_custom\_protocol(CPI).

In step **9014** NSURL module **9003** and ASMC DRM-Core **9004** receives "GetKey( . . . )."

In step **9015** ASMC DRM-Core **9004** invokes "Read local License(exist)."

In step **9016** ASMC DRM-Core **9004** provides and NSURL module **9003** receives a key "Key."

In step **9017** NSURL module **9003** provides and media player **9002** receives a "Key."

In step **9018** media player **9002** can "Decrypt and Continue playback."

Diagram **10000** depicts a use case for Play Streaming content corresponding to a variety of operating system environments. Such environments can comprise Android, PC, and MAC environments. Such operating system environments can alternatively be described as platforms.

A software media player can support an obfuscated DRM decryption plug-in, in order to play streaming content on Android, PC and Mac platforms. In a "most secure" software implementation embodiment, a media player can be provided as part of the ASMC SDK.

Some embodiments of PC and Mac implementations can be browser based solutions. In such cases, APIs can be advantageously provided in JavaScript. Such implementations can be advantageously compatible with Microsoft ActiveX, NPAPI Plugins and/or Google PNaCl environments.

Diagram **10000** depicts ASMC SDK **10005** with a dotted line surrounding the Media Player **10002**. The dotted line depicts that in some embodiments, it can be desirable and/or advantageous to have the Media Player **10002** and the DRM Plug-in **10003** disposed within the same "secure sandbox."

In step **10010** client app **10001** calls and media player receives **10002** ASMC\_Play(contentURL,inHomeStatus, . . . ).

In step **10011** media player **10002** parses media in order to extract CPI, depicted as "Parse media, Extract CPI."

## 12

In step **10012** media player **10002** calls and DRM plug-in **10003** receives ASMC\_Setkey(contentType,CPI).

In step **10013** DRM plug-in **10003** invokes "local license Exist." In this step **10013** a digital rights management client module **10003** can derive a key from a stored license. This step **10013** can be employed in determining whether or not a local license exists for content corresponding to a specific request. Additional embodiments herein comprise steps in which a digital rights management client module can derive a key from a stored license.

In step **10014** DRM plug-in **10003** provides and media player **10002** receives "handle."

In step **10015** media player **10002** calls and DRM plug-in **10003** receives ASMC\_Decrypt(handle,dec\_type, enc\_content\_block,IV,isLastBlock, . . . ).

In step **10016** DRM plug-in **10003** provides and media player **10002** receives "clear\_content\_block."

In step **10017** media player **10002** continues playback.

Diagram **11000** depicts a use case for Play Streaming content corresponding to a Set Top Box environment. In some embodiments, a Set Top Box environment can be characterized as comprising one or more application- and/or vendor-specific hardware elements that support specific functionalities.

In some embodiments, ASMC SDK module **11003** can execute within a TEE (trusted execution environment). In some such embodiments, a protected video-path can be provided in hardware.

In step **11010** client app **11001** calls and STB media player **11002** receives Play(contentURL, . . . ).

In step **11011** STB media player **11002** parses a manifest.

In step **11012** STB media player **11002** calls and ASMC SDK **11003** receives ASMC\_Setkey(contentType,CPI).

In step **11013** ASMC SDK **11003** provides and Hardware Interface Module **11004** receives "HW\_setKey(key)."

In step **11014** Hardware Interface Module **11004** provides and ASMC SDK **11003** receives "OK."

In step **11015** ASMC SDK **11003** provides and STB media player **11002** receives "handle."

In step **11016** STB media player **11002** calls and ASMC SDK **11003** receives ASMC\_Decrypt(handle,dec\_type, enc\_content\_block,IV,isLastBlock, . . . )

In step **11017** ASMC SDK **11003** invokes and Hardware Interface Module **11004** receives HW\_decrypt (enc\_content\_block).

In step **11018** ASMC SDK **11003** provides and STB media player **11002** receives "OK."

In step **11019** Hardware Interface Module **11004** invokes "Send Clear\_content\_block to Decode and Render."

Diagram **12000** depicts a use case for Initiate acquiring a license. In some embodiments, an ASM Client DRM module can "throw" notifications to a client application module. Such notifications can indicate a status, and/or request a particular action to be initiated.

If a valid license does not exist locally at the time of content playback, but was requested by the player, the ASMC DRM module can notify the client application module to initiate license acquisition. Upon successfully acquiring license in a timely manner, content playback can resume without interruption.

To some extent, diagram **12000** details content playback for iOS platform environment embodiments. Such a notification mechanism can be similar for other platforms, such as Android, PC and MAC.

In step **12010** client app **12001** calls and media player **12002** receives Play(contentURL,inHomeStatus, . . . )

13

In step 12011 media player 12002 parses media and extracts CPI.

In step 12012 media player 12002 invokes and iOS NSURL module 12003 receives “Custom\_url\_getKey (CPI).”

In step 12013 iOS NSURL module 12003 invokes and ASMC DRM-Core 12004 receives “GetKey (CPI).”

In step 12014 ASMC DRM-Core 12004 determines that a “Local license Does NOT exist.”

In step 12015 ASMC DRM-Core 12004 generates a LIBundle, responsive to the CPI.

In step 12016 ASMC DRM-Core 12004 provides and client app 12001 receives a notification of license need, Notification(ASMC\_NOTIFY\_START\_ACQUIRE\_LICENSE,LIBundle). That is, ASMC DRM-Core 12004 notifies client app 12001 that a license is required, corresponding to the LIBundle of step 12015.

In step 12017 client app 12001 calls and ASMC DRM-Core 12004 receives ASMC\_AcquireLicenseRequest(LIBundle, . . .).

In step 12018 ASMC DRM-Core 12004 provides and client app 12001 receives “OK.”

In step 12019 client app 12001 calls ASMC DRM-Core 12004 receives ASMC\_AcquireLicenseReply( . . .).

In step 12020 ASMC DRM-Core 12004 can store a license: “Store license.”

In step 12021 ASMC DRM-Core 12004 provides and client app 12001 receives “OK.”

In step 12022 ASMC DRM-Core 12004 can read a local license file

In step 12023 ASMC DRM-Core 12004 provides and iOS NSURL module 12003 receives a key “Key.”

In step 12024 iOS NSURL module provides and iOS NSURL module 12003 receives “Key.”

In step 12025 media player 12002 can “Decrypt and continue playback.”

Step 12026 depicts selectable execution loop of steps 12014 through 12021. These steps are performed upon determining that a valid local license does not exist.

ASMC—Client DRM APIs

API syntax and definition for client ASMC SDK APIs are herein described. APIs are defined in the C programming language herein. In some embodiments, specific platforms can have APIs defined in a specific language that can correspond to the platform. By way of non-limiting examples, an iOS platform can have corresponding APIs defined in Objective-C; an Android platform can have corresponding APIs defined in Java. In some embodiments, the platforms can be iOS, Android, PC, MAC, connected TV devices, STBs, and/or game consoles. Corresponding languages can comprise Objective-C, C, C++, Javascript and/or Java.

Diagram 13000 depicts a client side ASMC SDK 13003 comprising DRM APIs 13004 13010, DRM Plugin API 13005 13030, and MediaPlayer API 13006. These client side application programming interfaces can provide DRM services for a client application component 13001. A client application 13001 can comprise a media player component such as MediaPlayer 13002. The media player component can have access to ASMC SDK components DRM Plugin API 13005 13030 and MediaPlayer API 13006 13040.

ASMC\_Init 13011 can instantiate a new ASMC Client.

50 syntax/definition ASMC\_RESULT ASMC\_Init(void\* storageSpaceHandle)

14

-continued

Parameters storageSpaceHandle: Application context handle. Handle to persistent storage space. Eg: device’s internal storage specific to the application.  
5 Null - if platform has default persistent storage space. Eg: iOS sandbox.  
Returns On Success: ASMC\_SUCCESS  
On Error: Error messages  
Type Synchronous API

10 ASMC\_Close 13012 can clear the initialization.

15 syntax/definition ASMC\_RESULT ASMC\_Close()  
Parameters None  
Returns On Success: ASMC\_SUCCESS  
Type Synchronous API

ASMC\_GetProvisioningRequest 13013 can be employed by a client application to create a DRM message blob that can be sent to an OPUS server, in order to get client provisioning information. Such provisioning information can comprise a client certificate. This API can return FQDN of a server. In some embodiments, the application layer can treat the DRM message blob as an opaque data set. The message blob can be well defined in a DRM component.

20 syntax/definition ASMC\_RESULT ASMC\_GetProvisioningRequest (byte\* out\_drm\_msg\_blob, int\* out\_drm\_msg\_blob\_length, char\* out\_prov\_fqdn)  
Parameters:  
25 out\_drm\_msg\_blob Output parameter. The DRM message blob as byte array.  
out\_drm\_msg\_blob\_length Output parameter. The DRM message blob length.  
out\_prov\_fqdn Output parameter. Default FQDN of the OPUS server.  
Returns On Success: ASMC\_SUCCESS  
On Error: Error messages  
Type Synchronous API

ASMC\_ProcessProvisioningReply 13014: A client application module can use this API to complete client provisioning, by submitting data received from the OPUS server. The application module can deliver a DRM message blob (per description herein of ASMC\_GetProvisioningRequest 13013) to an OPUS server, and can submit the response to an ASMC DRM module using this API.

50 syntax/definition ASMC\_RESULT ASMC\_ProcessProvisioningReply (byte \* in\_opus\_resp\_blob, int in\_opus\_resp\_blob\_length)  
Parameters:  
55 in\_opus\_resp\_blob input parameter. Response received from OPUS server.  
in\_opus\_resp\_blob\_length input parameter. Response length.  
Returns On Success: ASMC\_SUCCESS  
On Error: Error messages  
Type Synchronous API

ASMC\_GetProvisioningStatus 13015 returns provisioning status.

65 syntax/definition ASMC\_RESULT ASMC\_GetProvisioningStatus (int \*outProvStatus)

15

-continued

---

<u>Parameters:</u>	
out_provStatus	Output parameter. Indicates provisioning status. AMSC_PROVISIONED - client is provisioned. AMSC_NOT_PROVISIONED - client is not provisioned.
Returns	On Success: ASMC_SUCCESS On Error: Error messages
Type	Synchronous API

---

A client application can employ ASMC\_GetLicenseRequest **13016** to create a DRM message blob. The DRM message blob can be sent to a Licensing server, in order to get content rights information and keys for a specific license.

A LII (License identification information) data structure can be defined. A LIBundle (License Identification Bundle) data structure can be defined, and can contain at least one LII.

When pre-fetching a license, a client application can get LIBundle data from a non-ASMC component. When getting a license at the time of playback, a client application can get LIBundle data from an ASMC component (notification), per the description of 'initiate acquiring a license' and as depicted in diagram **12000** herein. The application layer can treat a DRM message blob as an opaque data block. This message blob can be a well defined DRM object. The application module can deliver the DRM message blob to a license server and the server can submit the data to ASMS DRM module in order to get a response DRM message blob. The application module can call ASMC\_GetLicenseRequest and ASMC\_ProcessLicenseReply APIs per the description of "license acquisition" and as depicted in diagrams **8000** and **8100** herein, to complete the process of acquiring license for the content.

ASMC\_GetLicenseRequest **13016**:

---

syntax/definition	ASMC_RESULT ASMC_GetLicenseRequest (char* in_LIBundle, int in_LIBundleLen, char* in_appData, int in_appDataLen, bool in_continueFlag, bool in_forceFlag, byte* out_ASMC_msg_blob, int* out_ASMC_msg_blob_length)
<u>Parameters:</u>	
in_LIBundle	Input parameter. License Identification Bundle (LIBundle). LIBundle data block is a bundle of License Identification Information (LII). Contains necessary information to identify license(s) to acquire. Example: list of licenseID(s).
In_LiBundleLen	Input parameter. Length of LIBundle data block.
In_appData	Input parameter. Application Data (appData) Application data to be interpreted by application module on client and server. This could have a list of mediaIDs. This data shall not be interpreted by the DRM module.
In_appDataLen	Input parameter. Length of appData.
in_continueFlag	Input parameter. True indicates: API is invoked as a response to "continue" from ASMC_ProcessLicenseReply API. False indicates: This API is invoked for the first time for a specific media key, as a part of invoking multiple APIs for acquiring license for the content.
in_forceFlag	Input Parameter. True indicates: Proceed to acquire license, even if a valid license already exists locally.

16

-continued

---

out_ASMC_msg_blob	Output parameter. The DRM message blob as byte array. Generated by the client DRM module to be processed by the server DRM module.
out_ASMC_msg_blob_length	Output parameter. The above mentioned DRM message blob length.
<u>Returns</u>	
ASMC_SUCCESS	No Error.
ASMC_ERR_LICENSE_ALREADY_EXIST	A valid (not expired) License for requested media license ID, already exists locally. This error code is not used if the "force" flag was present in the request.
Type	Synchronous API

---

The client application module can use ASMC\_ProcessLicenseReply **13017** to process a DRM message blob received from a License server. Return values can indicate if the process of acquiring license for the content is complete or not complete. After successfully acquiring a license, a license for live streaming content can be stored in memory, but not necessarily persisted between subsequent sessions. For sync-n-go content the license can be persistently stored on a device.

An application module can deliver a DRM message blob to a License server (as per the description of ASMC\_GetLicenseRequest **13016** herein, and can submit the resulting response message blob to an ASMC DRM module, employing ASMC\_ProcessLicenseReply **13017**. ASMC\_ProcessLicenseReply **13017** can return "ASMC\_CONTINUE" to indicate that the process of acquiring licenses for the content is not yet complete. An application module can call ASMC\_GetLicenseRequest **13016** and ASMC\_ProcessLicenseReply **13017** per the description of "license acquisition" and as depicted in diagrams **8000** and **8100** herein, to complete a process of acquiring licenses for content.

ASMC\_ProcessLicenseReply **13017**:

---

syntax/definition	ASMC_RESULT ASMC_ProcessLicenseReply (byte* in_ASMS_msg_blob, int in_ASMS_msg_blob_length, char** out_licenseIDList, int* out_licenseIDListLen)
<u>Parameters:</u>	
in_ASMS_msg_blob	Input parameter. Response received from License server.
in_ASMS_msg_blob_length	Input parameter. Response length.
out_licenseIDList	Output parameter. List of licenseIDs. LicenseID can be a fixed byte length.
out_licenseIDListLen	Output parameter. licenseID list length.
<u>Returns</u>	
ASMC_SUCCESS	Indicates license acquisition is complete.
ASMC_CONTINUE	Indicates license acquisition is to be continued.
On Error:	Error messages
Type	Synchronous API

---

ASMC\_GetLocalRightsInfo **13018** can return locally stored rights information for a specific licenseID or a list of licenseIDs. This method can be used to get rights information for a single, multiple, or all locally stored license IDs.

---

syntax/definition	ASMC_RESULT ASMC_GetLocalRightsInfo (unsigned char* in_licenseIDList, int in_licenseIDListLen, char** out_rightsInfoList, int* out_rightsInfoListLen)
-------------------	---

17

-continued

---

Parameters:

in_licenseIDList	Input parameter. List of license IDs, to get the rights information. If the list is null, it indicates all locally existing licenses. Note: Each license ID is fixed length.
in_licenseIDListLen	Input parameter. Indicates number of license IDs in licenseIDList. If license ID list is null, this parameter shall be zero.
out_rightsInfo	Output parameter. Content rights information in JSON format, as described in Section 4.3 below. Note: The rights information has license ID as one of the element.
out_rightsInfoLen	Output parameter. Rights information string length.

---

Returns

On Success:	ASMC-SUCCESS
On Error:	Error messages
Type	Synchronous API

---

ASMC\_GetLocalLicenseIdentifiers **13019** can return a list of license IDs for existing licenses. Each license ID can identify a specific license. ASMC\_GetLocalLicenseIdentifiers is alternatively identified as ASMC\_GetLocalLicenseIDs herein.

---

syntax/definition	ASMC_RESULT ASMC_GetLocalLicenseIDs (unsigned char** out_licenseIDList, int* out_licenseIDListLen)
-------------------	--

---

Parameters:

out_licenseIDList	Output parameter. Concatenated list of license IDs of all local licenses. Each license ID can be of fixed length.
out_licenseIDListLen	Output parameter. Indicates number of licenseIDs in licenseIDList.

---

Returns

On Success:	ASMC-SUCCESS
On Error:	Error messages
Type	Synchronous API

---

ASMC\_DeleteLicense **13020** can remove locally stored content rights information by deleting the corresponding license. License(s) to be deleted can be identified by licenseID and/or by mediaID. The method supports deleting multiple licenses through a list of Identifiers (licenseID/mediaID). Licenses can also have a deletion time internal corresponding to each license. Such licenses can be described as self-policing. A Client application can pass a list of licenseIDs and/or a list of mediaIDs, for deleting licenses.

---

syntax/definition	ASMC_RESULT ASMC_DeleteLicense (unsigned char* in_licenseIDList, int in_licenseIDListLen, char* in_mediaIDList, int in_mediaIDListLen, char* out_deleteConfirmationData)
-------------------	--

---

Parameters:

in_licenseIDList	Input parameter. Concatenated list of license IDs for licenses to be deleted. Each license ID can be of fixed length.
in_licenseIDListLen	Input parameter. Indicates number of license IDs in licenseIDList.
in_mediaIDList	Input parameter. Concatenated list of media IDs for licenses to be deleted.
in_mediaIDListLen	Input parameter. Indicates number of media IDs in mediaIDList.

---

18

-continued

---

out_deleteConfirmationData	Output parameter. Provides authenticated proof of deletion. Data block definition TBD.
----------------------------	--

---

Returns

On Success:	ASMC-SUCCESS
On Error:	Error messages
Type	Synchronous API

---

ASMC\_SetKey **13031** can be used by a media player to set a content key for a specific CPI data. It can return a unique DRM handle which can be used for decryption.

---

15	syntax/definition	ASMC_RESULT MSC_SetKey(char* in_contentType, char* in_CPI, int in_CPILen, DRMHANDLE* out_handle);
----	-------------------	---

---

Data Structure:

20	CPI	Content Protection Information. CPI data block contains necessary information to identify a single specific license. For example, CPI can have licenseID among other information.
----	-----	---

---

Parameters:

25	In_contentType	Input parameter. contentType identifies the type of content format to be decrypted (e.g. MPEG part-12, HLS, WebM or DASH).
	in_CPI	Input parameter. Content Protection Information (CPI) data block contains necessary information to identify a specific license and related content specific information.
	In_CPILen	Input parameter. Length of CPI data block.
	out_handle	Output Parameter. DRM handle

---

Returns

35	On Success:	ASMC-SUCCESS
	On Error:	Error messages
	Type	Synchronous API

---

ASMC\_Decrypt **13032** can be used to decrypt media segments, after ASMC\_SetKey function is successful.

---

45	syntax/definition	ASMC_RESULT MSC_SetKey(char* in_contentType, char* in_CPI, int in_CPILen, DRMHANDLE* out_handle);
----	-------------------	---

---

Parameters:

50	In_handle	DRM handle received from ASMC_SetKey API.
	In_decType	Input parameter. Indicates decryption type.
	inputBuffer	Input encrypted buffer.
	inputLen	Encrypted buffer length
	In_IV	Initialization vector.
	In_IVLen	Input parameter. Initialization vector length.
	outBuffer	Output decrypted buffer
	outputLen	Output buffer length
55	isLastBlock	True: indicates this is last block and to reset IV after every chunk as initial IV.

---

Returns

60	On Success:	ASMC_SUCCESS indicates successful decryption. Output buffer will have clear data.
	On Error:	Error messages
	Type	Synchronous API

---

ASM DRM—Rights Data Definition: The Rights Data comprises content rules associated with licensed content that can be issued by the license server. The Rights Data can be represented in JSON format. Rights Data elements are described in JSON format herein, immediately below:

Schema Name	JSON Tag Name	JSON Field Name	Description	JSON Data Type
RightsInfo	Version	Version Number	Rights Information	Object
	General	Key ID	Version of the Rights data definition structure	Integer
		ExpiryTime	Key identifier aka licenseID	Object String*
		GracePeriod	Expiration time	Integer (in UTC time)
	PurchaseModel	Media ID	Playback grace period	Integer (in seconds)
		Model	Media Identifier	String
		PlayWindow	Different purchase models	String ("Rental", "Subscription", "Purchase")
		PlayDuration	Play window	Integer (in Days)
	CopyControlData	RCT	Play Duration	Integer (in Hours)
		CIT	Redistribution Control Trigger	Integer
		APS	Constrained Image Trigger	Integer
		CCI	Analog Protection System	Integer
	CopyControlEnhancement	AirPlayEnabled	Copy Control Indicator	Object
		HDMIDisabled	Copy Control Enhancement	Boolean
		DigitalCompressed Disabled	AirPlay Enabled	Boolean
		AnalogSunset	HDMI Disabled	Boolean
		AnalogDisabled Movable	Digital Compression Disabled	Boolean
		DomainCopy	Analog Sunset Token	Boolean
			Analog Disabled	Boolean
			Allowing to move licensed content	Boolean
			Allowing to copy licensed content within DRM domain	Boolean

MediaPlayer APIs **13040** is a client SDK component. It can be used to control playback of media files and/or streams. The MediaPlayer API specifications herein can typically apply to PC, MAC and/or Android platforms.

ASMC\_Play **13041** can start content playback, in a specified surface view. Play can start from the very beginning of a content file or stream. If the Seek API is called just prior to ASMC\_Play, play can proceed from a position specified by Seek. In order for an application to bookmark a playback position, it can call getCurrentPosition to record the position. Subsequently, when playback is to be restarted, it can employ a Seek call to pass in the bookmarked position, immediately prior to a play call.

syntax/definition	void ASMC_Play(string contentURI, SurfaceView view, enum inHomeStatus)
Parameters:	
contentURI	The content URI.
View	Surface view is specific to Android platform.
inHomeStatus	Indicates if the client device is playing the content in-home or out of home or not applicable. Example: enum inHomeStatus {in-home, outside-home, not-applicable}

-continued

45	Exc eptions:	
	FileNotFoundException	content file not found exception
	InvalidRegistrationMSCException	exception to indicate that the device does not have valid registration status.
50	Type	Synchronous API

ASMC\_Pause **13042** can pause content playback.

55	syntax/definition	Void ASMC_Pause( )
	Type	Synchronous API

ASMC\_Resume **13043** can resume content playback after a pause.

60	syntax/definition	Void ASMC_Resume( )
	Type	Synchronous API

ASMC\_Stop **13044** can stop content playback. It clears the media player resources.

65	ASMC_Stop	ASMC_Stop <b>13044</b> can stop content playback. It clears the media player resources.
----	-----------	---

syntax/definition Type	Void ASMC_Stop( ) Synchronous API
---------------------------	--------------------------------------

ASMC\_Seek **13045** can set a play position to an input time offset. The offset can be requested in seconds.

syntax/definition Type	ASMC_RESULT ASMC_Seek(ASMC_Time startPosition) Synchronous API
---------------------------	---

ASMC\_GetCurrentPosition **13046** can return a current content position. The position can be specified in terms of time offset in seconds.

syntax/definition Type	ASMC_Time ASMC_GetCurrentPosition( ) Synchronous API
---------------------------	---

ASMC\_EnableFullScreen **13047** can toggle a player screen (view) size between full screen and small screen, depending on a value of the input parameter.

syntax/definition Parameters: Type	void ASMC_EnableFullScreen(Boolean isFullScreen) Type
FullScreen	If isFullScreen is true the player can capture the size specified in the setFullScreenSize API. If isFullScreen is false, the player can capture the size specified in the setSmallScreenSize API.

ASMC\_SetDisplay **13048** API can be called whenever the surface is changed. For example, a foreground to background change can require a call to this method in order to re-set the surface. In some embodiments, this method can be specific to Android platforms.

syntax/definition Parameters: Type	void ASMC_SetDisplay(SurfaceHolder sh) Type
Sh	Surface Holder. Ex: android.view.SurfaceHolder.

ASMC\_SetEventListener **13049** can be used to register a listener. A registered listener can thereby get notifications to render closed captions, and/or to get DRM errors for Playback and play completion.

syntax/definition Parameters: Type	void ASMC_SetEventListener(OnEventListener listener) Type
Listener	Listener object

ASMC\_SetSmallScreenSize **13050** can set a small screen size.

This method can set a video render position and size depending on the value of the origin (represented by x and y), and width and height parameters. In some embodiments, a call this method or setFullScreenSize can be required, in order to enable video on screen.

syntax/definition Parameters: Type	void ASMC_SetSmallScreenSize(int x, int y, int width, int height) Type
x, y	Origin position of the video screen.
Width, height	Width and height of the video screen.

ASMC\_GetAvailableCaptions **13051** can request a list of available captions/subtitles.

syntax/definition Parameters: Type	ASMC_RESULT ASMC_GetAvailableCaptions(char** out_capAttributes) Type
out_capAttributes	List of ISO 639-2 language codes and a one-byte flag for each, i.e. 'y' or 'n' can indicate whether it is with easy reader feature (ERF) or not. Each language can be represented as a three byte long character string. For instance the string "eng y" can indicate that English is available with ERF. English without ERF is also available can be indicated by returning two strings, i.e. "eng y" and "eng n". In a case where captions streams are present, but the language is unknown, it can return a set of reserved values starting from 'qaa'. So if there are two unknown language caption streams, one can be 'qaa' and the second 'qab'.

Returns:  
ASMC\_SUCCESS No error.  
ASMC\_ERR\_ Caption languages are not specified or not currently available.  
PLAYER\_LANG\_ available.  
NOT\_AVAIL  
Type Synchronous API

ASMC\_SetCaption **13052** can Enable and disable closed captions (CC), and select a caption language. The selection can be considered a preference. In an embodiment where the caption selection is not controllable, a primary caption stream can be chosen.

syntax/definition Parameters: Type	ASMC_RESULT ASMC_SetCaption(bool ccSetFlag, char* language, bool withERF) Type
CcSetFlag	TRUE: Turn CC ON. FALSE: Turn CC OFF
Language withERF	Selected language (ISO 639-2 language code)

Returns:  
ASMC\_SUCCESS No error.  
ASMC\_ERR\_ Action not valid. Invalid action may also be returned in case of incorrect or unsupported language code.  
PLAYER\_INVALID\_ACTION  
Type Synchronous API

ASMC\_GetAvailableAudio **13053** can request a list of available audio streams.

syntax/definition Parameters: Type	ASMC_RESULT ASMC_GetAvailableAudio(char** out_audAttributes) Type
out_audAttributes	List of ISO 639-2 language codes and a one-byte flag, i.e. 'y' or 'n' can indicate whether a descriptive video service (DVS) is available. Each language can be represented as a three byte long character string. For instance the string "eng y" can indicate that English with DVS is available. If English without DVS is also available, two strings can be returned to so indicate: "eng y" and "eng n".

ASMC\_GetAvailableAudio **13053** can request a list of available audio streams.

-continued

---

Returns:

---

ASMC_SUCCESS	No error.
ASMC_ERR_	Audio languages are not specified or not currently available
PLAYER_LANG_	
NOT_AVAIL	
Type	Synchronous API

---

ASMC\_SetAudio **13054** can select an audio stream when multiple audio streams are present. Such a case can be typical of OTT embodiments. This selection can be considered a preference. If a choice is not available, a primary language can be selected.

---

syntax/definition	ASMC_RESULT ASMC_SetAudio (char* language, bool withDVS)
Parameters:	
Language	Selected language, represented as ISO 639-2, three character code.
WithDVS	A boolean flag indicating with or without DVS (Descriptive Video Service). TRUE means with and FALSE means without.
Returns:	
ASMC_SUCCESS	No error.
ASMC_ERR_	Action not valid. Invalid action can also be returned in case of incorrect or unsupported language.
PLAYER_INVALID_ACTION	
Type	Synchronous API

---

Diagram **14000** depicts a server side ASMS SDK **14003** comprising DRM APIs **14004 14010**. These server side application programming interfaces, illustrated as DRM APIs **14004 14010**, can provide DRM services for a License server component, such as License Service **14001**. The APIs are herein described with the C programming language. Some embodiments can comprise equivalent JAVA interfaces.

ASMS\_Init **14011** can initialize the overall DRM system. Initialization of the SecureMedia DRM core SDK system can be required, prior to exercising individual APIs. This call can be required at least once per each host process, in order to create a single instance of the DRM SDK core module within a user thread and/or process. Additional calls to ASMS\_Init **14011** with different parameters can increment instance counts. In some embodiments such instance counts can be employed for closely coupled calls.

---

syntax/definition	int ASMS_Init(void* crl_cb_handle)
Parameters:	
Crl_cb_handle	Call back handle (function pointer) to check for CRL
Returns:	On Success: SMHN_SUCCESSFUL, if the call is successful. On Error: Error messages
Type	Synchronous API

---

ASMS\_Close **14012** can de-initialize the overall DRM system for each instantiated object. This call can typically be invoked at least once before each user process and/or thread is terminated and as the last call to the DRM system. For each ASMS\_Init API, a pairing call to this API can properly terminate the corresponding DRM instance. A last call to this API can close the instance and perform clean up of out-standing memory allocations.

---

syntax/definition	int ASMS_Close( )
Returns:	ASMS_SUCCESSFUL, if the call is successful. ASMS_Error code otherwise.
Type	Synchronous API

---

A License server module can employ ASMS\_RetrieveKeyIDs **14013** to retrieve a list of key IDs from a client DRM message blob.

---

syntax/definition	ASMS_RESULT ASMS_RetrieveKeyIDs(byte* in_ASMC_msg_blob, void* out_handle, unsigned char** out_keyIDList, int* out_keyIDListLen)
Parameters:	
in_ASMC_msg_blob	Input parameter. DRM message blob from client, to be processed.
out_handle	Output parameter. DRM handle.
out_keyIDList	Output parameter. Concatenated list of key IDs. Each license ID can be of fixed length.
out_keyIDListLen	Output parameter. Indicates length of keyIDList.
Returns:	On Success: ASMC_SUCCESS. On Error: Error messages
Type	Synchronous API

---

The License server module can use ASMS\_CreateLicense **14014** to create license(s) and to securely package them into a server DRM message blob. The DRM message blob can be processed by ASMC client DRM module. The License server can send the server DRM message blob to a client Application, to be processed by a client DRM module.

---

syntax/definition	ASMS_RESULT ASMS_CreateLicense (void* in_handle, void* in_struct_keyInfo[ ], int in_struct_keyInfoLen, byte* out_ASMC_msg_blob, int* out_ASMC_msg_blobLen)
Parameters:	
in_handle	Input parameter. DRM handle.
In_struct_keyInfo[ ]	Input parameter. A list of keyInfo structure. In_struct_keyInfo structure can contain: KeyID Key KeyLen Rights information Rights information length Example: struct keyInfo{ unsigned char* keyID; unsigned char* key; int keyLen; char* rights_info; int rights_info_len; }; Refer to ASM DRM - Rights Data Definition
in_struct_keyInfoLen	Input parameter. Length of the list of media key info structure.
out_ASMC_msg_blob	Output parameter. Response DRM message blob.
out_ASMC_msg_blobLen	Output parameter. The above mentioned DRM message blob length.
Returns:	On Success: ASMC_SUCCESS. On Error: Error messages
Type	Synchronous API

---

System Architecture Overview  
Basic Client Model

The basic client model comprises a DRM function represented by a library (statically or dynamically linked), a Player function and an application. In embodiments employing a software player, such as Android environments, the

player can have a plug-in that interfaces to a DRM function that decrypts content. In other embodiments, such as iOS, the player can directly decrypt content. An application is not required to run the DRM function as a “process.” The application can merely call each of the defined APIs, as needed, in order to make use of the DRM function services.

An application can tell the client library to “request a license” whenever a service choice is made.

A player can receive content with “content protection information” (CPI). The CPI can be a keytag (such as for HLS) or equivalent information. Equivalent information can be from a DASH MDP or an ECM equivalent. All of these can be described as a mechanism indicating the specific content key in use.

Upon new reception of a keytag or equivalent, which references a new content key, the player can send the keytag or equivalent to its plug-in component. Such plug-in embodiments can comprise hardware and/or software. The plug-in can extract any relevant information, such as an initialization vector (IV), and send a key request to the DRM library. The DRM library can return the key to the plug-in, in a plug-in dependent manner. Thus the application can operate without directly processing a key.

The platform dependent interface can flexibly support the use of NSURL for Apple iOS clients, an obfuscated DRM decryption plug-in for Android software players, and/or hardware related solutions for TEE architectures and STBs.

#### Temporal Key Change

For linear (broadcast) channels, keys can change over time. A license request can allow for multiple time slot keys to be returned if desired, such as current and next. In some situations, the next key is not yet prepared, in order for security to be maintained. In some example embodiments, a system might offer its ‘next’ key an hour before its use, but not 24 hours, if that is the key change rate.

A mechanism can request the new (next) license and thus next keys during a broadcast. Thus, License requests can return all licenses that are determined relevant by the infrastructure. Such licenses can be referenced by an N byte content “license ID”. In some embodiments of linear services, (the case for temporally changing keys), infrastructure can return two keys (and license IDs), current and next. Some typical VOD application embodiments can require just a single content key and license.

One approach to acquiring the relevant linear channel content keys attaches a DRM specific field (called “License Identification Bundle”) to content directory WebPages or descriptions. In such a case, infrastructure can deduce which current and next key is appropriate to return to the DRM subsystem upon a subsequent request for a license.

A second approach can use a transaction involving the client application and its infrastructure, which returns the relevant content key licenses. Identifying and/or providing the relevant content key licenses can be based upon system specific data such as the linear channel asset name.

In a third approach, an application requests no license at acquire time. Instead, the player can process the content URL, receive the initial content or playlist or MPD, discover which license and thus which key is required, and request it from the DRM library. The client DRM library can provide a notification to the application layer when it is requested to provide a key for which it does not have a license. Thus the application can issue a real-time license request, and attempt to acquire the key in time to reply to the player plug-in. Such a notification can typically be used for an error case. In some

embodiments, acquisition can be relatively more reliable and/or rapid if either of the first two approaches are employed.

The application layer can drive license requests, and the application can have awareness of what type of service is being viewed. Notably, in some embodiments, more than one license request can be subsequent to and associated with a specific instance of provisioning with certificate. The application layer may require knowledge of when a new license might be required, in order to request the license adequately in advance of when needed. The relevant keys can be defined, managed and timed by the operator infrastructure, so that the client application layer can be provided with whatever knowledge it requires of the time to request a new license. If an initial license request is made near a key change boundary, two licenses may be returned in response. If a request is made far from such a boundary, a single license may be returned in response, as the infrastructure defines. For a specific license ID request, if a license ID is associated with a desired asset, the correct key(s) are returned in the content license.

#### Multiple Component Keys Per Service

Some embodiments support multiple component keys per service. In alternative DRM embodiments, different keys can be assigned to audio and video, or other components, as defined by the content standard in use. In this case, the infrastructure can return a set of licenses as needed. For linear services, a current set and a next set can be returned. For additional flexibility, each license can comprise an application defined field called the “media ID,” which allows for identifying a group of licenses as being related to a single media asset.

#### Optimal Linear Service Acquisition

Some embodiments support optimal linear service acquisition. Multiple linear channel licenses can be delivered on a single request, since a consumer’s subscription status can be known. The API can comprise a ‘continue’ flag, so that a request to deliver tens or hundreds of licenses can be broken up as desired. In some embodiments, the licenses can be broken up into a smaller current viewed channel license set, for quick acquisition, and a set of all subsequent licenses.

An embodiment providing multiple linear channel licenses corresponding to a single request is herein depicted and described in diagrams **8000** and **8100**. License cues **8118** can comprise, inter alia, a consumer’s subscription status. By way of non-limiting example, licenses can be requested and hence obtained corresponding to content recommended to a user, such as content specifically identified within a program guide and/or catalog.

Licenses can comprise deletion times. Thus, license storage can be described as self-policing. Upon application calls to the DRM library, license storage can be reviewed and old licenses can be deleted. As a further optimization, upon a license request, the DRM library can check which licenses it already has, thus avoiding unnecessary duplicate fetches.

#### On-Demand Linear

In the case of mobile clients, it may not be optimal to deliver licenses for other subscription channels in advance, as the particular service access may be conditioned on whether a mobile device is in home or out of home at the instant of initial service access. This can also apply to re-use of a license valid for a previously tuned channel, which can become invalid due to a transition in location. Three alternative approaches for license delivery are herein described.

First, the system can acquire a new license when requested, even if one is already present; this allows the

infrastructure to examine the request's IP traffic flow and determine the in home or out of home status before replying with a license.

Second, the system can support advanced delivery, and re-use, but allow the application to delete any given license as needed. In this manner, the application can delete licenses for one or more linear assets in response to an in home/out of home transition, which can force the DRM library to acquire a new license. New licenses can be issued with the location factored in.

A third approach can be to issue all licenses with their usage rules including any in-home restriction. In this case, the DRM library can be required to support an API whereby its location can be set by the application layer. In some embodiments, such an approach may be somewhat less secure, as it may be subject to hacking of the application's location algorithm.

For flexibility, the application license request can comprise a 'force' flag, so that the DRM library can responsively delete its current license and acquire a new one. The infrastructure may also cause this action in some scenarios: a license request that returns a set of licenses can replace any internally stored licenses with the new versions. Further, a flag can be present in the rights section of the license indicating any in-home qualification.

#### Banding:

In some typical embodiments, several channels can have the same license, and/or the same sequence of content keys. This can allow fewer licenses to be acquired and stored, which can be advantageous for rapid acquisition and/or pre-delivery of licenses. The same license ID can be used for multiple linear channels. Thus a license ID and an application level channel or asset name would not necessarily be equivalent indicators. Typically, channels sharing a license ID referencing a specific content key can share all subsequent license IDs.

#### "Start Over" Services

In some embodiments, start over services for linear channels require no special handling in the DRM libraries of the client and the infrastructure. An application layer function can determine that a request can be made for a (stored) linear channel in the past, and determine that the DRM libraries can still deliver licenses and keys as directed by the infrastructure and player stream.

#### Secure Time

In embodiments of the DRM library that are not autonomous, there can be a limited capability to provide a secure time. A call to "acquire license" can return a current (secured) value of the current time from the infrastructure, and that time can be stored as the "last known good time." (LKGT) A request to return a key to the player for stored [local] service playback can be checked for license rights expiry. Further, local platform time can be stored at the time of LKGT, so that the LKGT can be advanced (never reversed) by estimating the apparent elapsed time from the LKGT storage time and the key request time. For some embodiments, it is recommended that the LKGT not be replaced with this estimate, as the estimate may be in error due to user clock manipulation. With this recommendation, the estimated time can be used to decide if the license has expired at the time of key request only. In this fashion, the DRM library can make its 'best guess.' Two errors can be returned to the player in the event of expiry, "expiration" and "estimated expiration." This latter can support GUI indications to the user to prompt restoration of the clock time, if desired. Notably, high value content can be flagged for a

required license request at playback time, so that the secure time can be checked absolutely.

For TEE based designs, there can be hardware secure time internally to the TEE, which can make rights expiry advantageously more secure.

#### Domains

In the case of a group of devices assigned to a single user's domain, content sharing can be supported. A device can copy an encrypted asset from the storage of one device to the storage of another, without risking theft, as the content key is not known. For an on-line device in the same domain as the first, that device can request a license. Upon the infrastructure determining the other device to be "in the domain" and the content to be allowed for domain access, a license can be returned.

In the case of an off-line device, one that is outside of current network connection, access can still be supported if the infrastructure system can selectively re-encrypt its assets per user. That is, a set of locally stored content in the domain accessible category for user N can be delivered initially re-encrypted in a new key selected for all such content, but only for that single user domain. Each device can be granted that single license in advance, and can share content "at will."

Some embodiments of the DRM system require direct support for domains, in which off-line devices must support domains without infrastructure re-encryption. Specifically, a key and key ID can be allocated for a user domain key [per user], and that key's license pre-distributed to the members of that domain. Content downloaded to a member of the domain can come with a normal license [directed to the device] as well as a special "domain license." This special license can contain the content key encrypted under a domain key common to all domain members. The license can carry a flag indicating that it is a domain license, and can also include the key ID of the user domain key.

Although the present invention has been described above with particularity, this was merely to teach one of ordinary skill in the art how to make and use the invention. Many additional modifications will fall within the scope of the invention, as that scope is defined by the following claims.

The invention claimed is:

1. A method for digital rights management of licensed video media content, comprising:
  - issuing a digital rights management license request corresponding to first media content, responsive to a unique client certificate, the first media content comprising one or more elements of the video media;
  - receiving a first digital rights management license corresponding to the first media content, responsive to the digital rights management license request;
  - receiving one or more additional digital rights management licenses corresponding to second media content, responsive to the digital rights management license request;
  - deriving a content key from the first digital rights management license;
  - initiating play of one or more elements of the first media content;
  - playing one or more elements of the first media content, responsive to the content key;
  - wherein a client application on a video player is configured to issue the digital rights management license request, to receive the first digital rights management license, and to receive the additional digital rights management licenses; and

29

wherein a digital rights management client module providing the video media is configured to derive the content key.

2. The method of claim 1, further comprising:  
 providing an online personalization update server; 5  
 wherein the online personalization update server provides the unique client certificate.

3. The method of claim 1: wherein the specified operating system platform is an iOS platform, an Android platform, a PC platform, or a MAC platform. 10

4. The method of claim 1, further comprising the step of: issuing one or more additional digital media rights license requests, responsive to the unique client certificate.

5. The method of claim 1, further comprising the steps of: 15  
 providing an operator infrastructure comprising a server application; and,  
 providing a digital rights management server module;  
 wherein the server application is configured to invoke the digital rights management server module to provide the first digital rights management license and the additional digital rights management licenses; 20  
 wherein the digital rights management server module is configured to provide the first digital rights management license and the additional digital rights management licenses. 25

6. The method of claim 5 further comprising the steps of: providing a license identification bundle, comprising a plurality of license identification information structures;  
 requesting a plurality of digital rights management licenses within the first transaction; 30

30

wherein the plurality of digital rights management licenses respectively correspond to the plurality of license identification information structures; and,  
 wherein the license identification bundle is provided prior to issuing the digital rights management license request.

7. The method of claim 5 further comprising the steps of: providing a license identification bundle, comprising a plurality of license identification information structures, and subsequent to initiating play of one or more elements of the first media content;  
 requesting a plurality of digital rights management licenses within the first transaction;  
 wherein the plurality of digital rights management licenses respectively correspond to the plurality of license identification information structures; and,  
 wherein the digital rights management client module is configured to provide the license identification bundle.

8. The method of claim 5 further comprising the steps of: providing a first transaction that comprises issuing the digital rights management license request;  
 processing a plurality of interactions;  
 completing the first transaction; and,  
 initiating play of one or more elements of the first media content;  
 wherein the plurality of interactions comprises interactions between the client application and the digital rights management client module, and, interactions between the digital rights management client module and the digital rights management server module.

\* \* \* \* \*