



(51) International Patent Classification:  
A61N 7/02 (2006.01)

(21) International Application Number:  
PCT/US2014/022804

(22) International Filing Date:  
10 March 2014 (10.03.2014)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
61/784,790 14 March 2013 (14.03.2013) US  
61/814,167 19 April 2013 (19.04.2013) US

(71) Applicant: RECOR MEDICAL, INC. [US/US]; 1049 Elwell Court, Palo Alto, CA 94303 (US).

(72) Inventors: TAYLOR, Kevin; 238 23rd Ave, San Mateo, CA 94403 (US). MERINO, Jamie; 78 Heath Cote Rd, Elmont, NY 11003 (US). CHANDLER, Paul; 209 Quarry Lane, Santa Cruz, CA 95060 (US). RAQUET, Jacob; 16157 E. Mozart Ave, Los Gatos, CA 95032 (US). GANDIONCO, Isidro, M.; 36520 Alder Ct., Fremont, CA 94536 (US). ROTH, Austin, R.; 300 23rd Ave., San Mateo, CA 94403 (US).

(74) Agent: CHRISTENSEN, Michael, R.; Knobbe Martens Olson & Bear, LLP, 2040 Main Street, 14th Floor, Irvine, CA 92614 (US).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: ULTRASOUND-BASED NEUROMODULATION SYSTEM



(57) Abstract: A neuromodulation system including a catheter has a balloon along its distal end. An ultrasound transducer positioned within an interior of the balloon can be selectively activated to emit acoustic energy radially outwardly, targeting nerve tissue and other portions of the subject anatomy. Targeted nerve tissue can be heated by the application of ultrasonic energy to neuromodulate the tissue. The system may be delivered over a guidewire. A catheter enhances fluid delivery to a distal end of the catheter while reducing an overall diameter of the catheter. The catheter comprises a guidewire lumen that is eccentric relative to a center axis of the catheter.

## ULTRASOUND-BASED NEUROMODULATION SYSTEM

### BACKGROUND

#### Field

[0001] This application relates generally to minimally-invasive devices, systems and methods of energy delivery to a targeted anatomical location of a subject, and more specifically, to catheter-based, intraluminal devices and systems configured to emit ultrasonic energy for the neuromodulation (e.g., ablation, necrosing, etc.) of nerve tissue.

#### Description of the Related Art

[0002] Catheter-based energy delivery systems can be used to access and treat portions of a subject's anatomy minimally-invasively. Such systems can be advanced through a subject's vasculature to reach a target anatomical site. Various embodiments disclosed herein provide improved devices, systems and methods related to energy delivery within a subject.

### SUMMARY

[0003] According to some embodiments, a catheter for enhancing fluid delivery to a distal end of the catheter while reducing an overall diameter of the catheter comprises a guidewire lumen oriented along an axis that is eccentric relative to a center axis of the catheter (e.g., not positioned along the radial centerline or along the central axis or longitudinal axis of the catheter). The guidewire lumen being can be configured to receive a guidewire therethrough in order to intraluminally deliver the catheter to a target location within a subject. The catheter further comprises at least one fluid lumen configured to transfer a fluid through the catheter. In one embodiment, the eccentric orientation of the guidewire lumen within the catheter allows the cross-sectional area of the at least one fluid lumen to be increased.

[0004] According to some embodiments, the catheter further comprises at least one centering assembly located at or near the distal end of the catheter, wherein the at least one centering assembly comprises a passage that is positioned along the center axis of the catheter. In some embodiments, a guidewire is configured to be positioned through the passage of the at least one centering assembly so that the guidewire is generally radially

centered along the distal end of the catheter, while the guidewire is configured to eccentrically located within the guidewire lumen of the catheter. In some embodiments, the at least one centering assembly is located immediately adjacent the distal end of the catheter (e.g., such that the centering assembly at least partially touches or otherwise engages or abuts the catheter). In one embodiment, the at least one centering assembly is separated from the distal end of the catheter by a separation distance (e.g., 0-1 mm, 1-2 mm, 2-3 mm, 3-4 mm, 4-5 mm, 5-10 mm, more than 10 mm, etc.). In some embodiments, the at least one centering assembly is located proximal to the distal end of the catheter (e.g., at least partially within the catheter).

**[0005]** In some embodiments, the ultrasonic transducers are operated in a range of from 1 to 20 MHz (e.g., 1-5 MHz, 5-10 MHz, 10-15 MHz, 15-20 MHz, 8-10 MHz, other values or ranges within the foregoing, etc.). In one embodiment, for example, the ultrasound transducer of the system is configured to operate at a frequency of about 9 MHz. In other embodiments, however, the frequency at which a transducer is operated can be below 1 MHz (e.g., 0.1-0.2, 0.2-0.3, 0.3-0.4, 0.4-0.5, 0.5-0.6, 0.6-0.7, 0.7-0.8, 0.8-0.9, 0.9-1.0 MHz, frequencies between the foregoing ranges, less than 0.1 MHz, etc.) or above 20 MHz (e.g., 20-25, 25-30 MHz, frequencies between the foregoing ranges, above 30 MHz, etc.), as desired or required for a particular application or use. The power supplied to the ultrasound transducer can vary, as desired or required, and in some embodiments, is 5 to 80 Watts (e.g., 5 to 50, 5 to 10, 10 to 20, 20 to 30, 30 to 40, 40 to 50, 50 to 60, 60 to 70, 70 to 80 Watts, power levels between the foregoing ranges, etc.) at the transducer.

**[0006]** In some embodiments, the ultrasonic transducer is activated for about 10 seconds to 5 minutes (e.g., 10-30 seconds, 30 seconds to 1 minute, 30 seconds to 5 minutes, 1 to 3 minutes, about 2 minutes, 10 seconds to 1 minute, 1 to 2 minutes, 2 to 3 minutes, 3 to 4 minutes, 4 to 5 minutes, time periods between the foregoing ranges, etc.). In other embodiments, the ultrasonic transducer is activated for less than 10 seconds (e.g., 0-1, 1-2, 2-3, 3-4, 4-5, 5-6, 6-7, 7-8, 8-9, 9-10 seconds, time periods between the foregoing ranges, etc.) or more than 5 minutes (e.g., 5-6, 6-7, 7-8, 8-9, 9-10, 10-15, 15-20 minutes, time periods between the foregoing, more than 20 minutes, etc.).

**[0007]** According to some embodiments, the system comprises an ultrasound transducer having a variety of shapes. The transducer can be cylindrical or non-cylindrical. In some embodiments, the transducer comprises, at least in part, an hourglass shape, a barbell shape, a convex shape or surface, a concave shape or surface and cone shape, an irregular shape and/or the like.

**[0008]** According to some embodiments, prior to inflation of a balloon or other expandable member, the ultrasonic transducer is activated to measure the vessel's diameter. In one embodiment, this is accomplished by sending out a single (or a distinct number of) ultrasonic waves and recording the time period required for the signals to return (e.g., bounce back) to the transducer surface. Thus, in some embodiments, a control system of the system can be configured to both emit acoustic energy and detect it (e.g., at or along the outside of the transducer).

**[0009]** According to some embodiments, a system comprises an array of transducers (e.g., an array comprising 2, 3, 4, 5, 6, 7, 8, 9, 10, 10-15, more than 15 transducers, etc.). In embodiments comprising 2 or more transducers (e.g., an array of transducers), one or more of the transducers can be configured to emit more or less ultrasonic energy than one or more other transducers. In some embodiments, the amount of acoustic energy that is emitted by the plurality of transducers varies (e.g., linearly, non-linearly, randomly, etc.) along a longitudinal axis of the system. In some embodiments, one or some ultrasound transducer of a system emit (or are configured to emit) greater acoustic energy in one or more directions in relation to one or more other directions.

**[0010]** According to some embodiments, an ultrasound transducer includes differing wall thickness (e.g., along its longitudinal axis). In embodiments comprising two or more transducers, the wall thickness of one transducer is greater or less than the wall thickness of another transducer. In some embodiments, one or more transducers of a system can be independently controllable (e.g., such that power and/or frequency to one transducer can be different than power and/or frequency to another transducer, etc.). In some embodiments, two or more transducers of a system are controlled together or in unison. In one embodiment, a transducer can include an eccentric or non-uniform backing lumen or opening.

**[0011]** According to some embodiments, the transducer comprises a varying wall thickness along at least a portion of its circumferential extent. Accordingly, rotating the transducer can alter the acoustic energy pattern emitted by the transducer and/or alter one or more other aspects of energy emission (e.g., frequency, efficiency, etc.) during use. In some embodiments, one or more regions, surfaces and/or other portions of a transducer can be at least partially masked, covered, obstructed, etc. in order to alter the acoustic energy profile of the transducer during use. In one embodiment, at least a portion of the transducer is masked or otherwise covered by selective plating and/or etching of the electrodes along the transducer, covering a portion of the transducer, using one or more features of the balloon, etc.).

**[0012]** According to some embodiments, ultrasonic energy is directed directly within the tissue of the targeted nerve tissue (e.g., sympathetic nerves). In any of the embodiments disclosed herein, a balloon and/or other expandable structure or member can be used to at least partially expand the area or volume of tissue being treated (e.g., the renal artery, other body lumen or vessel, etc. can be radially expanded). In some embodiments, an ablation system includes a balloon (e.g., positioned at least partially around one or more transducers), but no fluid is configured to be circulated through the balloon during use. In one embodiment, the balloon can be inflated with one or more gases, liquids and/or fluids (e.g., in order to expand the balloon, so that balloon contacts the adjacent wall of the targeted vessel, so that the one or more transducers of the system are radially centered or generally radially centered within the vessel, etc.), but no fluids are circulated through the balloon. In some embodiments, the balloon is configured to maintain an inflated or expanded state without the continuous or intermittent delivery of fluid therethrough.

**[0013]** In some embodiments, a catheter of the system comprises a chip (e.g., a smart catheter) and/or one or more related components or features (e.g., an identification device or reader, a transducer, etc.). In one embodiment, a generator can detect which catheter is being used. In some embodiments, the system can monitor one or more aspects of a therapy or procedure using one or more metrics that are detected, such as, for example, pressure, temperature, flowrate, vessel diameter, thermal profile, presence and/or degree of spasm of a vessel, degree of narrowing of a vessel and/or the like. In some embodiments,

such information is used in a control scheme to regulate one or more aspects of the generator and/or other components or devices of the system (e.g., to modulate power, frequency, duration of procedure, automatic shutoff, billing, patient records or other recordkeeping, memorization of a procedure for other reasons, etc.).

**[0014]** According to some embodiments, the at least one fluid lumen of the catheter includes an axis that is eccentric to the central axis of the catheter (e.g., one or more fluid lumens are not oriented along or near the central or longitudinal axis of the catheter). According to some embodiments, the at least one fluid lumen comprises a non-circular shape to increase the cross-sectional area of the at least one fluid lumen. In one embodiment, the at least one fluid lumen includes a circular shape along the periphery of the catheter. In some embodiments, the at least one fluid lumen comprises a fluid delivery lumen and a fluid return lumen.

**[0015]** According to some embodiments, the catheter comprises an over-the-wire design such that the guidewire lumen extends from a proximal end to the distal end of the catheter. In some embodiments, the catheter comprises a rapid exchange design such that the guidewire lumen is located only along a distal portion of the catheter. In one embodiment, a proximal portion of the catheter that does not include a guidewire lumen comprises a groove or recess along an exterior surface of the catheter, wherein the groove or recess is configured to receive a guidewire therein.

**[0016]** According to some embodiments, the distal end of the catheter is attached to a balloon, wherein the at least one fluid lumen is in fluid communication with an interior of the balloon to enable fluids to be delivered to and/or from the interior of the balloon through the at least one fluid lumen. In some embodiments, the catheter further includes an energy delivery device (e.g., ultrasound device, RF electrode, microwave device, etc.) located at least partially within the balloon. In some embodiments, the catheter comprises a 5 French or 6 French catheter.

**[0017]** According to some embodiments, an intraluminal (e.g., intravascular), ultrasound-based ablation system comprises a catheter comprising at least one fluid lumen and a guidewire lumen, wherein the guidewire lumen is not positioned along the cross-sectional centerline of the catheter, and a balloon positioned along a distal end of the catheter,

an interior of the balloon being in fluid communication with the at least one fluid lumen of the catheter, wherein the balloon is configured to inflate when fluid is delivered into the interior through the at least one lumen of the catheter. The system further includes an ultrasound transducer positioned within the balloon, a distal tip comprising a central passage, wherein the balloon is positioned between the catheter and the distal tip and an electrically non-conductive member extending from the guidewire lumen to the central passage of the distal tip, the electrically non-conductive member positioned through an interior of the ultrasound transducer and configured to receive a guidewire. The system additionally comprises a backing member positioned between the electrically non-conductive member and the ultrasound transducer, the backing member being configured to support the ultrasound transducer. In some embodiments, the system comprises one or more centering assemblies positioned proximal to the catheter between the distal end of the catheter and the distal tip. In some embodiments, the centering assembly comprises a center opening or passage configured to receive the electrically non-conductive member, wherein the radial orientation of the center opening is offset relative to the radial orientation of the guidewire lumen of the catheter, wherein the center opening of the centering assembly is aligned with the cross-sectional centerline of the catheter and the balloon so as to radially center the ultrasound transducer when a guidewire is positioned through the electrically non-conductive member.

**[0018]** According to some embodiments, the electrically non-conductive member comprises polyimide. In some embodiments, the centering assembly comprises a plurality of wings extending radially outwardly from the center opening, the wings configured to engage an inner surface of the balloon. In one embodiment, the centering assembly comprises at least three wings. According to some embodiments, the centering assembly a plurality of wings that are evenly or unevenly distributed around the circumference of the assembly (e.g., spaced apart at 90° or 120° intervals). In other embodiments, a centering assembly can include fewer (e.g., 1, 2) or more (e.g., 4, 5, 6, more than 6, etc.) than 3 wings. According to some embodiments, the outer diameter of the centering assembly (e.g., taken along the outermost portions of the wings) is identical or substantially identical (e.g., within about 0-1%, 1-2%, 2-3%, 3-4%, 4-5%, more than 5%) of the outer diameter of the catheter. In some

embodiments, the centering assembly comprises one or more suitable materials (e.g., thermoplastics, metals, alloys, combinations thereof, etc.).

**[0019]** In some embodiments, the balloon 14 (e.g., including the proximal portion 15, the main radially expandable portion, etc.) is extruded from a single material or member. In some embodiments, the proximal portion of the balloon can comprise a greater thickness of the extruded material or portion relative to the distal portions of the balloon. In some embodiments, the thickness of the proximal portion of the balloon is greater than the thickness of more distally located portions (e.g., along the main, radially expandable portion of the balloon) by about 0-10%, 10-20%, 20-30%, 30-40%, 40-50%, 50-60%, 60-70%, 70-80%, 80-90%, 90-100%, 100-125%, 125-150%, 150-200%, greater than 200%, percentages between the foregoing values and/or the like. In some embodiments, the distal portion of the balloon includes a generally cylindrical portion that is configured to maintain its shape during use (e.g., when cooling fluid is circulated through the balloon interior). In some embodiments, the proximal and distal portions of the balloon can be secured to the catheter and the tip, respectively, using one or more attachment methods or devices (e.g., adhesives, pressure or friction fit connections, fasteners, etc.).

**[0020]** According to some embodiments, in order to transition from a peripheral lumen of the catheter to the central opening of the centering assembly, the guidewire is angled through a portion of the catheter system (e.g., between the distal end of the catheter and the proximal end of the centering assembly). The guidewire can be angled within the proximal, cylindrical portion of the balloon at angle  $\Theta$ , which, in some embodiments, is about 0-40° (e.g., about 0-5°, 5-10°, 10-15°, 15-20°, 20-25°, 25-30°, 30-35°, 35-40°, angles between the foregoing, etc.). In some embodiments, the angle  $\Theta$  is greater than about 40° (e.g., about 40-50°, 50-60°, greater than 60°, etc.).

**[0021]** In some embodiments, the cross-sectional area of each of the fluid lumens of the catheter is about 0.00005 to 0.00012 square inches (e.g., 0.00005 to 0.00006, 0.00006 to 0.00007, 0.00007 to 0.00008, 0.00008 to 0.00009, 0.00009 to 0.00010, 0.00010 to 0.00011, 0.00011 to 0.00012 square inches, areas between the foregoing, etc.), less than about 0.00005 square inches, more than about 0.00012 square inches for a 6 French catheter, and about 0.00003 to 0.00010 square inches (e.g., 0.00003 to 0.00004, 0.00004 to 0.00005,



0.00005 to 0.00006, 0.00006 to 0.00007, 0.00007 to 0.00008, 0.00008 to 0.00009, 0.00009 to 0.00010 square inches, areas between the foregoing, etc.), less than about 0.00003 square inches, more than about 0.00010 square inches for a 5 French catheter. In some embodiments, by eliminating a central lumen (e.g., a central guidewire lumen) within the catheter, the size of one or more of the other lumens (e.g., the fluid lumens) can be increased.

**[0022]** In some embodiments, the at least one fluid lumen comprises a fluid delivery lumen and a fluid return lumen. In some embodiments, the catheter further comprises an electrical conductor lumen, wherein each of the electrical conductor lumen and the at least one fluid lumen is not positioned along the cross-sectional centerline of the catheter.

**[0023]** According to some embodiments, the guidewire lumen is positioned along an entire length of the catheter. In some embodiments, the guidewire lumen is positioned only along a distal portion of the catheter, so that the catheter comprises a rapid exchange type catheter. In one embodiment, the catheter comprises a groove or recess along at least a proximal length of the catheter that does not comprise a guidewire lumen, the groove being configured to at least partially receive an adjacent guidewire. In some embodiments, the catheter comprises a 5 French or 6 French catheter. In some embodiments, the system is configured to be advanced into a subject via femoral or radial access. In one embodiment, the at least one fluid lumen comprises a non-circular shape (e.g., oval, triangular, irregular, etc.).

**[0024]** In some embodiments, the catheter includes a rapid-exchange design in which the catheter comprises a guidewire lumen only partially along its length. In one embodiment, the guidewire lumen extends only through the distal-most portion of the catheter (e.g., along a length immediately proximal to the balloon). In some embodiments, the catheter comprises an interior guidewire lumen only along the last 5 to 30 cm (e.g., 5-6, 6-8, 8-10, 10-12, 12-14, 14-16, 16-18, 18-20, 20-25, 25-30 cm, lengths between the foregoing, etc.) of the catheter's distal end. In some embodiments, the catheter comprises a guidewire lumen only along 0-30% (e.g., 0-5%, 5-10%, 10-15%, 15-20%, 20-25%, 25-30%, percentages between the foregoing, etc.) of its length (e.g., the distal end of catheter).

[0025] According to some embodiments, an intravascular, ultrasound-based ablation system comprises a catheter including at least one fluid lumen, a guidewire lumen and an electrical cable lumen, wherein each of the at least one fluid lumen, the guidewire lumen and the electrical cable lumen is not positioned along the cross-sectional centerline of the catheter (e.g., the electrical cable lumen is eccentric relative to the longitudinal or central axis of the catheter). In some embodiments, the system additionally comprises a balloon positioned along a distal end of the catheter, wherein an interior of the balloon is in fluid communication with the at least one fluid lumen of the catheter, and wherein the balloon is configured to inflate when fluid is delivered into the interior through the at least one lumen of the catheter. In some embodiments, the system further comprises an ultrasound transducer (e.g., a cylindrical transducer) positioned within the balloon, a distal tip, wherein the balloon is positioned between the catheter and the distal tip, and an electrically non-conductive member extending distally from the guidewire lumen through an interior of the ultrasound transducer, the electrically non-conductive member being configured to receive a guidewire. In some embodiments, the system further includes a centering assembly positioned proximal to the catheter between the distal end of the catheter and the distal tip, the centering assembly comprising a center opening configured to receive the electrically non-conductive member, wherein the center opening of the centering assembly is aligned with the cross-sectional centerline of the catheter and the balloon so as to radially center the ultrasound transducer when a guidewire is positioned through the electrically non-conductive member.

[0026] According to some embodiments, the electrically non-conductive member comprises polyimide. In some embodiments, the centering assembly comprises a plurality of wings extending radially outwardly from the center opening, the wings configured to engage an inner surface of the balloon. In one embodiment, the guidewire lumen is positioned along an entire length of the catheter. In some embodiments, the guidewire lumen is positioned only along a distal portion of the catheter, so that the catheter comprises a rapid exchange type catheter. In some embodiments, the catheter comprises an exterior groove along at least a proximal length of the catheter, the groove being configured to at least partially receive an adjacent guidewire.

[0027] According to some embodiments, an intravascular, ultrasound-based ablation system includes a catheter comprising a guidewire lumen, at least one cable lumen and at least one fluid lumen, and a balloon or other expandable structure or member positioned at a distal end of the catheter, wherein an interior of the balloon is in fluid communication with the at least one fluid lumen of the catheter. In some embodiments, the balloon is configured to inflate when fluid (e.g., cooling fluid) is delivered into the interior through the at least one fluid lumen of the catheter. The system further comprises a tip extending distally from a distal end of the balloon, wherein the tip comprises an internal guidewire passage, and one or more ultrasound transducers positioned within the balloon. In some embodiments, the ultrasound transducer includes a cylindrical tube with inner and outer surfaces, each of the inner and outer surfaces comprising an electrode, wherein the ultrasound transducer defines an internal space adjacent the inner electrode surface, the internal space being in fluid communication with the interior cavity of the balloon so that, when in use, fluid entering the balloon passes along both the inner and outer surfaces to transfer heat away from the ultrasound transducer.

[0028] In some embodiments, at least one electrical cable (e.g., coaxial cable) is routed or otherwise positioned within the at least one cable lumen of the catheter, wherein the at least one electrical cable is electrically coupled to the electrodes along the inner and outer surfaces of the ultrasound transducer. The system further includes a backing member or post extending from the catheter to the tip and connecting the catheter with the tip. In some embodiments, the backing member is positioned within the internal space of the ultrasound transducer, wherein the backing member comprises a central opening that is generally aligned with the guidewire lumen of the catheter and the internal guidewire passage of the tip to permit the system to be delivered to a desired vascular position over a guidewire. In some embodiments, the backing member serves as a fluid barrier between fluid circulated within the balloon interior and the central opening.

[0029] According to some embodiments, the backing member comprises an electrically insulating material (e.g., polyimide, another polymeric material, etc.) along an interior surface of the central opening of the backing member so as to prevent electrical conduction between a guidewire and the backing member. In some embodiments, the

guidewire lumen extends from a proximal end of the catheter to the balloon. In other embodiments, the guidewire lumen extends from a location between the proximal and distal ends of the catheter to the distal end of the catheter, such that the catheter comprises a rapid exchange design.

**[0030]** According to some embodiments, an intravascular, ultrasound-based ablation system comprises a catheter having at least one cable lumen and at least one fluid lumen, a balloon or other expandable structure positioned at a distal end of the catheter, an interior of the balloon being in fluid communication with the at least one fluid lumen of the catheter and an ultrasound transducer positioned within the balloon, wherein the ultrasound transducer comprises a cylindrical tube having a proximal end and a distal end and inner and outer surfaces. In some embodiments, each of the inner and outer surfaces comprises an electrode, wherein the proximal end of the cylindrical tube comprising a stepped portion, and wherein a portion of the outer diameter formed by the outer surface of the cylindrical tube is smaller than a portion of the outer diameter of the cylindrical tube located distal to the stepped portion. The system further comprises at least one electrical cable positioned within the at least one cable lumen of the catheter, the at least one electrical cable being configured to supply electrical power to the ultrasound transducer, wherein the at least one electrical cable comprises a first conductor and a second conductor.

**[0031]** In some embodiments, the system further comprises one or more a stand-off assemblies located within an interior and along or near the proximal end of the cylindrical tube of the ultrasound transducer. In one embodiment, the stand-off assembly is electrically conductive and in contact with, at least intermittently, the electrode along the inner surface of the cylindrical tube of the ultrasound transducer, wherein the first conductor is connected to an exterior of the cylindrical tube along the stepped portion, and wherein the second conductor is connected to the stand-off assembly so that the second conductor is electrically coupled to the electrode along the inner surface of the cylindrical tube. The system further comprise a ring surrounding the stepped portion of the cylindrical tube, the ring being sized and shaped to surround the portion of the outer diameter of the cylindrical tube located distal to the stepped portion, wherein the ring is electrically conductive so that the first connector is electrically coupled to the electrode along the outer surface of the cylindrical tube, and

wherein the ring allows for more uniform electrical loading of the ultrasound transducer when the electrical transducer is energized.

**[0032]** According to some embodiments, the ring comprises conductive solder. In some embodiments, the ring comprises a conductive machined ring or other member or feature that couples around the stepped portion of the cylindrical tube. In some embodiments, the stepped portion extends approximately 5% to 25% (e.g., 5% to 10%, 10% to 15%, 15% to 20%, 20% to 25%, etc.) of a length of the cylindrical tube. In one embodiment, the stepped portion comprises a portion of the cylindrical tube that is removed using grinding or other removal techniques. In some embodiments, an impedance of the at least one electrical cable substantially matches an impedance of the ultrasound transducer. In some embodiments, the impedance of the electrical cable and the ultrasound transducer is approximately 40 to 60 ohms (e.g., 50, 40-42, 42-44, 44-46, 46-48, 48-50, 50-52, 52-54, 54-56, 56-58, 58-60 ohms, etc.). In some embodiments, the diameter or other cross-sectional dimension of the stepped portion 68a is 50-95% (e.g., 50-55, 55-60, 60-65, 65-70, 70-75, 75-80, 80-85, 85-90, 90-95%, percentages between the foregoing ranges, etc.) of the outer diameter 66a of the transducer. In other embodiments, the diameter or other cross-sectional dimension of the stepped portion 68a is less than 50% (e.g., 20-30, 30-40, 40-50%, percentages between the foregoing ranges, less than 20%, etc.) or greater than 95% (e.g., 95-96, 96-97, 97-98, 98-99, 99-100%, percentages between the foregoing ranges, etc.) of the outer diameter 66a of the transducer.

**[0033]** According to some embodiments, the electrical impedance of the electrical conductors (e.g., the one or more electrical cables that electrically couple the transducer to the power supply) can be matched or substantially matched (e.g., within about 0-10%, 0.1%, 0.2%, 0.3%, 0.4%, 0.5%, 0.5-1%, 1-2%, 2-3%, 3-4%, 4-5%, 5-6%, 6-7%, 7-8%, 8-9%, 9-10%, etc.) to the electrical impedance of the ultrasound transducer.

**[0034]** According to some embodiments, an intravascular, ultrasound-based ablation system comprises a catheter having a cable lumen extending from a proximal end to a distal end of the catheter, an ultrasound transducer positioned at or near a distal end of the catheter, wherein the ultrasound transducer comprises a cylindrical tube with inner and outer surfaces, wherein each of the inner and outer surface comprising an electrode. The system

further comprises a backing member or post extending from the distal end of the catheter and positioned within an interior of the ultrasound transducer, wherein the backing member is configured to support the ultrasound transducer, and wherein the backing member is electrically coupled to the electrode along the inner surface of the cylindrical tube of the ultrasound transducer. In some embodiments, the system comprises an electrical cable positioned within the cable lumen of the catheter and extending from the proximal end to the distal end of the catheter, wherein a proximal end of the electrical cable is coupled to a generator configured to selectively provide electrical power to the ultrasound transducer through the electrical cable. In one embodiment, the electrical cable comprises a first electrical connector and a second electrical connector, wherein the first connector is electrically coupled to the electrode along the outer surface of the ultrasound transducer, and wherein the second connector is electrically coupled to the backing member and the electrode along the inner surface of the ultrasound transducer. In some embodiments, an impedance of the electrical cable is substantially equal to an impedance of the ultrasound transducer, thereby providing a more efficient power transfer from the generator to the ultrasound transducer when the ablation system is in use.

**[0035]** According to some embodiments, the electrical cable comprises a coaxial cable. In one embodiment, the backing member or post comprises at least one stand-off assembly that electrically couples the backing member to the electrode along the inner surface of the cylindrical tube of the ultrasound transducer. In some embodiments, the backing member or post is coupled to both the proximal and the distal ends of the transducer. In some embodiments, the impedance of the electrical cable and the ultrasound transducer is approximately 40 to 60 ohms (e.g., approximately 50 ohms). In some embodiments, the first connector of the electrical cable is electrically coupled to the electrode while not physically attached to the outer surface of the ultrasound transducer.

**[0036]** According to some embodiments, an intravascular, ultrasound-based ablation system includes a catheter comprising at least one fluid lumen, a balloon or other expandable member positioned at a distal end of the catheter, wherein an interior of the balloon is in fluid communication with the at least one fluid lumen of the catheter, and wherein the balloon is configured to inflate when fluid is delivered into the interior through

the at least one lumen of the catheter. The system further comprises an ultrasound transducer positioned within the balloon, wherein the ultrasound transducer includes a cylindrical tube with inner and outer surfaces, wherein each of the inner and outer surface comprising an electrode. In some embodiments, the ultrasound transducer defines an internal space adjacent the inner electrode surface, wherein the internal space is in fluid communication with the interior cavity of the balloon so that, when in use, fluid entering the balloon passes along both the inner and outer surfaces to cool the ultrasound transducer. In some embodiments, the system additionally comprises a fluid transfer device configured to selectively deliver a cooling fluid within the balloon when the ultrasound transducer is activated in order to transfer heat away from the ultrasound transducer during use, wherein the fluid transfer device comprises a reservoir for storing a volume of cooling fluid and a movable member configured to move within an interior of the reservoir in order to transfer cooling fluid through the at least one fluid lumen of the catheter to the balloon, and wherein the reservoir is sized to store sufficient cooling fluid for an entire ablation procedure.

**[0037]** In some embodiments, cooling fluid is circulated through the system in such a manner so that the temperature along the interior wall of the vessel surrounding the transducer is maintained at a temperature of about 50-55°C (e.g., 50°C, 51°C, 52°C, 53°C, 54°C, 55°C, etc.). In other embodiments, the target temperature can be below 50°C (e.g., 30-35°C, 35-40°C, 40-45°C, 45-50°C, temperatures between the foregoing ranges, less than 30°C, etc.) or greater than 55°C (e.g., 55-60°C, 60-65°C, 65-70°C, 70-75°C, temperatures between the foregoing ranges, greater than 75°C, etc.). In addition, in some embodiments, the temperature of the vessel wall is maintained within such a target range (e.g., 50-55°C, 30-75°C, etc.), while the temperature of tissue approximately 0.5 mm to 8 mm (e.g., 1 mm to 6 mm, where, in some embodiments, target tissue is located) is heated to about 60-80°C (e.g., 60-70°C, 70-80°C, 65-75°C, etc.), 50-100°C (e.g., 50-60°C, 60-70°C, 70-80°C, 80-90°C, 90-100°C, temperatures between the foregoing ranges, etc.), greater than 100°C, when the transducer is activated.

**[0038]** In some embodiments, the volume of the reservoir is approximately 50 ml to 1,000 ml (e.g., 50-100, 100-200, 200-300, 300-400, 400-500, 500-600, 600-700, 700-800, 800-900, 900-1,000 ml, capacities between the foregoing, etc.). In other embodiments, the

volume of the reservoir is less than 50 ml (e.g., 20-30, 30-40, 40-50 ml, volumes between the foregoing ranges, less than 20 ml) or greater than 1,000 ml (e.g., 1,000-1,100, 1,100-1,200, 1,200-1,300, 1,300-1,400, 1,400-1,500, 1,500-2,000, 2,000-3,000, 3,000-5,000 ml, volumes between the foregoing ranges, greater than 5,000 ml, etc.).

**[0039]** According to some embodiments, the movable member is coupled to a motor for selectively advancing the movable member relative to the reservoir. In one embodiment, the motor comprises a stepper motor or another type of motor. In some embodiments, the fluid transfer device comprises a syringe pump. In some embodiments, the catheter comprises a fluid delivery lumen and a fluid return lumen, wherein cooling fluid is delivered to the balloon from the fluid transfer device via the fluid delivery lumen, and wherein cooling fluid is withdrawn from the balloon via the fluid return lumen. In some embodiments, the fluid transfer lumen is in fluid communication with a first fluid transfer device, and wherein the fluid return lumen is in fluid communication with a second fluid transfer device, wherein both the first and the second fluid transfer devices are operated simultaneously to circulate cooling fluid through the balloon during an ablation procedure. In some embodiments, the fluid transfer device is configured to deliver cooling fluid through the at least one fluid lumen of the catheter and into the balloon at a flowrate of 30-50 ml/min (e.g., 30-40 ml/min, 40-50 ml/min, 35-45 ml/min, 40 ml/min). In other embodiments, the fluid transfer device is configured to deliver cooling fluid through the at least one fluid lumen of the catheter and into the balloon at a flowrate of less than 30 ml/min (e.g., 0-10, 10-20, 20-25, 25-30 ml/min, flowrates between the foregoing, etc.) or greater than 50 ml/min (e.g., 50-60, 60-70, 70-80, 80-90, 90-100 ml/min, flowrates between the foregoing, greater than 100 ml/min, etc.).

**[0040]** A method of intraluminally ablating or otherwise neuromodulating nerve tissue using an ultrasound-based ablation system includes advancing a catheter of the ablation system intraluminally to a target anatomical location of a subject, wherein the system comprises a balloon positioned at a distal end of the catheter, an interior of the balloon being in fluid communication with at least one fluid delivery lumen and at least one fluid return lumen of the catheter, wherein an ultrasound transducer is positioned within the interior of the balloon. The method further includes circulating cooling fluid through the interior of the



balloon by transferring cooling fluid from a fluid transfer device through the at least one fluid lumen of the catheter and transferring cooling fluid away from the interior of the balloon through the at least one fluid return lumen and activating the ultrasound transducer positioned within the balloon to ablate nerve tissue adjacent to the target anatomical location of the subject. In some embodiments, cooling fluid is circulated adjacent the ultrasound transducer within the balloon when the ultrasound transducer is activated. In some embodiments, the fluid transfer device comprises a reservoir for storing a volume of cooling fluid and a movable member configured to move within an interior of the reservoir in order to transfer cooling fluid through the at least one fluid lumen of the catheter to the balloon, wherein the reservoir is sized to store sufficient cooling fluid for an entire ablation procedure.

**[0041]** According to some embodiments, the movable member (e.g., plunger) is coupled to a motor for selectively advancing the movable member relative to the reservoir. In one embodiment, the motor comprises a stepper motor or another type of motor or actuator. In some embodiments, the fluid transfer device comprises a syringe pump or another type of pump. In some embodiments, cooling fluid is circulated through the balloon at a flowrate of 30-50 ml/min (e.g., 30-40 ml/min, 40-50 ml/min, 35-45 ml/min, 40 ml/min, etc.).

**[0042]** According to some embodiments, a coupling configured for use in an outlet of a fluid container (e.g., IV bag) includes a hub configured to abut against the outlet of the coupling, wherein the hub is configured to prevent over-insertion of the coupling into the fluid container. In some embodiments, a proximal end of the hub comprises a fitting configured for attachment to a fluid conduit. The coupling further comprises a spike portion extending distally from the hub, wherein a length of the spike is 0.5 inches to 3 inches. In some embodiments, the coupling comprises at least two fluid lumens (e.g., 2, 3, 4, 5, more than 5, etc.) that extend throughout an entire length of the coupling from the proximal end of the hub to a distal end of the spike, wherein the lumens place an interior of the fluid container in fluid communication with at least one fluid conduit secured to the hub. In some embodiments, the coupling permits at two different fluid sources to be placed in fluid communication with an interior of a fluid container comprising only a single outlet. In some embodiments, such a coupling or spike can be used on an IV bag or other fluid container that

is placed in fluid communication with a syringe pump of a treatment system. Thus, the IV bag can be configured to store additional fluid that will be delivered through a delivery lumen into a balloon and/or can be configured to store excess fluid being returned from the balloon via a return lumen in the catheter. Thus, the coupling can be placed in fluid communication with the catheter and/or the syringe pump of the treatment system. In some embodiments, the inner diameters of the internal lumens or passages of the spike or coupling are approximately 0.05 to 0.125 inches (e.g., 0.05-0.06, 0.06-0.07, 0.07-0.08, 0.08-0.09, 0.09-0.1, 0.1-0.11, 0.11-0.125 inches, diameter between the foregoing, etc.) and the minimum penetration distance 80 is about 1.5 inches (e.g., 0.75, 1.0, 1.25, 1.5 inches, distances between the foregoing, less than 0.75 inches, more than 1.5 inches, 1.5-2.0 inches, 2.0-3.0 inches, more than about 3 inches, etc.).

[0043] In some embodiments, the spike includes a taper along at least a portion of its length, so that a cross-sectional dimension of the spike is smaller along the distal end of the spike than a cross-sectional dimension of the spike along a proximal end of the spike. In some embodiments, the spike comprises a cone-shaped, with either a linear or non-linear (e.g., curved) profile. In some embodiments, the spike is configured for placement into an IV bag comprising only a single outlet or port. In some embodiments, the coupling comprises two fluid lumens.

[0044] The methods summarized above and set forth in further detail below describe certain actions taken by a practitioner; however, it should be understood that they can also include the instruction of those actions by another party. Thus, actions such as “advancing a catheter intraluminally” or “activating a transducer” include “instructing advancing a catheter intraluminally” and “instructing activating a transducer.”

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0045] FIG. 1 illustrates an ultrasound-based treatment system according to one embodiment.

[0046] FIG. 2 illustrates a detailed side view of a distal end of the system depicted in FIG. 1.

[0047] FIG. 3 illustrates a side cross-sectional view of the distal end of an ultrasound-based system according to one embodiment.

[0048] FIG. 4 illustrates a section view across a portion of the system of FIG. 3.

[0049] FIG. 5 illustrates a partial cross-sectional view of the expandable member and ultrasound transducer according to one embodiment.

[0050] FIG. 6 illustrates a partial cross-sectional view of the ultrasound transducer of FIG. 5.

[0051] FIG. 6a illustrates a cross-sectional view of an ultrasound transducer having a stepped portion according to another embodiment.

[0052] FIG. 6b illustrates a partial perspective view of the transducer of FIG. 6b.

[0053] FIG. 6c illustrates a partial cross-sectional view of an ultrasound transducer according to another embodiment;

[0054] FIG. 7 illustrates the fluid lumens of an ultrasound-based system according to one embodiment.

[0055] FIG. 8 illustrates an IV bag and spike or coupling inserted therein according to one embodiment.

[0056] FIG. 9 illustrates a distal end of a catheter system (with the balloon hidden for clarity) according to one embodiment.

[0057] FIG. 10 illustrates a side view of the catheter system of FIG. 9.

[0058] FIG. 11 illustrates a perspective view of the catheter system of FIG. 9.

[0059] FIG. 12 illustrates one embodiment of a centering assembly.

[0060] FIG. 13 illustrates the centering assembly of FIG. 12 positioned along the distal end of a catheter according to one embodiment.

[0061] FIGS. 14 and 15 illustrate different perspective views of a distal end of a catheter assembly according to one embodiment comprising a centering assembly.

[0062] FIG. 16 illustrates a cross-sectional view of a catheter according to one embodiment.

[0063] FIG. 17 illustrates a cross-sectional view of a catheter according to another embodiment.

[0064] FIG. 18 illustrates a partial perspective view of one embodiment of a catheter comprising an external groove or recess.

## DETAILED DESCRIPTION

**[0065]** In the various embodiments described herein, catheter-based systems and methods for treating targeted tissue of a subject are disclosed. The systems and methods are particularly useful in neuromodulation procedures (e.g., denervation). For example, as discussed in greater detail herein, the systems can be used to target select nerve tissue of the subject. Targeted nerve tissue can be heated by the application of ultrasonic energy thereto in order to neuromodulate (e.g., ablate, necrose, stimulate, etc.) the tissue. In other embodiments, the application of ultrasonic energy can be used to target other adjacent tissue of a subject, either in lieu of or in addition to nerve tissue. Accordingly, the systems and methods disclosed herein can be used to treat hypertension, other nerve-mediated diseases and/or any other ailment. The systems and methods disclosed herein can also be used in ablative procedures of non-nerve tissue (including, but not limited to, tumors, cardiac tissue, and other tissue types). Arrhythmias are treated according to one embodiment.

**[0066]** The catheter-based systems disclosed herein can be delivered intraluminally (e.g., intravascularly) to a target anatomical region of the subject, such as, for example, the renal artery, another targeted vessel or lumen, etc. Once properly positioned within the target vessel, the ultrasound transducer can be activated to selectively deliver acoustic energy radially outwardly from a distal end of the system and toward the targeted tissue. The transducer can be activated for a particular time period and at a particular energy level (e.g., power, frequency, etc.) in order to accomplish the desired effect on the targeted tissue (e.g., to achieve a target temperature). In embodiments where the targeted tissue is nerve tissue, the systems are configured to deliver ultrasonic energy through the adjacent wall of the vessel in which the system is positioned. For example, with respect to the renal artery, targeted nerve tissue is typically located about 0.5 mm to 8 mm (e.g., about 1 mm to 6 mm) from the vessel wall. In some embodiments, nerve tissue is located 0.5, 1, 1.5, 2, 2.5, 3, 3.5, 4, 4.5, 5, 5.5, 6, 6.5, 7, 7.5, 8 mm, distances between the foregoing, away from the interior wall of the vessel. In other embodiments, nerve tissue can be located less than 0.5 mm or greater than 8 mm from the interior wall of the vessel. Accordingly, ultrasonic energy can be used to heat the nerve tissue to at least partially neuromodulate the nerve tissue. As used herein, neuromodulation shall be given its ordinary meaning and shall include, without

limitation, complete or partial ablation, necrosis, stimulation and/or the like. In some embodiments, the acoustic energy is delivered radially outwardly from the ultrasound transducer, permitting the delivery of ultrasonic energy to target nerve tissue regardless of the radial orientation of such nerve tissue relative to a vessel (e.g., renal artery). In some embodiments, the acoustic energy is delivered along an entire, continuous circumference of the transducer. In other embodiments, however, the acoustic energy is emitted non-continuously or intermittently around the circumference of the transducer. Further, as discussed in greater detail herein, the various systems disclosed herein can be configured to deliver a cooling fluid to the anatomical region being treated in order to protect certain tissue of the subject (e.g., to prevent or reduce the likelihood of stenosis or other damage to the wall of the vessel through which energy is delivered during a procedure). For example, cooling fluid can be selectively delivered to and/or circulated within a balloon that at least partially surrounds the transducer.

#### General System Components and Features

[0067] FIGS. 1 and 2 illustrate an ultrasound-based ablation system 100 according to one embodiment. As shown, the system 10 can comprise a catheter 12 having a proximal end 20 and a distal end 22, an expandable member 14 (e.g., balloon) along the distal end of the catheter and one or more ultrasound transducers 16 positioned within the expandable member 14. A proximal portion of the system can comprise a handle 8 and one or more connectors or couplings (e.g., an electrical coupling 32 for connecting the system to a power generator, one or more ports 34 for placing the system in fluid communication with a cooling fluid, etc.).

[0068] In some embodiments, the catheter 12 includes one or more lumens that can be used as fluid conduits, electrical cable passageways, guidewire lumen and/or the like. For example, as illustrated in FIG. 5, the catheter 12 can include at least one cable lumen 24 that is shaped, sized and otherwise configured to receive an electrical cable 28 (e.g., coaxial cable, wire, other electrical conductor, etc.). The electrical cable 28 advantageously permits the electrode of the system's ultrasound transducer to be selectively activated in order to emit acoustic energy to a subject.

[0069] The catheter 12 can also include at least one fluid lumen 26 for transferring cooling fluid (e.g., water, saline, other liquids or gases, etc.) to and from the balloon or other expandable member 14 located at the distal end of the system. As discussed in greater detail herein, in some embodiments, the catheter comprises at least two fluid lumens 26, one for delivering cooling fluid to the balloon and the other for returning the cooling fluid from the balloon. However, the catheter 12 can include only a single fluid lumen or more than two fluid lumen (e.g., 3, 4, more than 4, etc.), as desired or required. As described in greater detail herein, the lumens can be located along any part of the cross-sectional area of the catheter (e.g., along the centerline, offset from the centerline, etc.) and/or can include any cross-sectional shape (e.g., circular, oval, rectangular or other polygonal, irregular, etc.), as desired or required.

[0070] As illustrated in FIGS. 2 and 3, the ultrasound transducer 16 can be positioned completely within an interior of the expandable member 14 (e.g., balloon). In some embodiments, as shown in FIG. 2, when expanded, the outer wall of the balloon 14 is generally parallel with the walls of the cylindrical ultrasound transducer 16. The balloon 14 can be a compliant, semi-compliant or non-compliant medical balloon, as desired or required. Thus, when inflated, the balloon or other expandable member that at least partially surrounds the transducer can at least partially contact the adjacent wall of the vessel. In some embodiments, however, one or more portions of the balloon are configured to not contact the adjacent vessel wall when expanded. In some embodiments, the ultrasound transducer 16 is liquid cooled along both its outer and inner electrodes, meaning that cooling liquid entering the balloon 14 is permitted to pass across both the exterior and interior surfaces of the cylindrical transducer to transfer heat away from the transducer. In some embodiments, the cooling liquid or other fluid can directly contact the exterior and/or interior surfaces of the transducer. The transducer 16 can include a reflective interface (e.g., along its interior) so as to permit ultrasonic energy generated at the inner electrode (e.g. along the interior surface of the cylindrical transducer) to be reflected radially outwardly.

[0071] Additional details regarding possible ultrasonic transducer designs and embodiments (e.g., both structurally and operationally) and/or catheter-based ultrasound delivery systems are provided in U.S. Patent Application No. 11/267,123, filed on July 13,

2001 and published as U.S. Publ. No. 2002/0068885 on June 6, 2002; U.S. Patent Application No. 09/905,227, filed July 13, 2001 and issued as U.S. Patent No. 6,635,054 on October 21, 2003; U.S. Patent Application No. 09/904,620, filed on July 13, 2001 and issued as U.S. Patent No. 6,763,722 on July 20, 2004; U.S. Patent Application No. 10/783,310, filed February 20, 2004 and issued as U.S. Patent No. 7,837,676 on November 23, 2010; U.S. Patent Application No. 12/227,508, filed on February 3, 2010 and published as U.S. Publ. No. 2010/0130892 on May 27, 2010; U.S. Patent Application No. 10/611,838, filed on June 30, 2003 and published as U.S. Publ. No. 2004/0082859 on April 29, 2004; and PCT Appl. No. PCT/US2011/025543, filed on February 18, 2011 and published as PCT Publ. No. WO 2012/112165 on August 23, 2012. The entireties of all the foregoing applications is hereby incorporated by reference herein and made a part of the present application.

**[0072]** With continued reference to FIG. 1, one or more electrical cables that supply electrical power to the transducer 16 can be coupled via the electrical coupling 32 located at the proximal end of the system. In some embodiments, the electrical coupling comprises a standard or non-standard connection to a power supply and controller (not illustrated). For example, in some embodiments, the electrical coupling 32 can be easily and quickly attached and detached to a power supply and controller. As is described in greater detail below, the fluid lumen(s) 26 of the catheter can be used to selectively transfer fluid (e.g., cooling fluid) between a fluid transfer device (e.g., fluid pump) and the interior of the balloon or other expandable member 14. The cooling fluid can be used to inflate the expandable member 14 and to provide cooling (e.g., when the ultrasound transducer 16 is activated) in order to transfer heat away from the ultrasound transducer 16 and/or the surrounding tissue of the subject during use.

**[0073]** The system 100 can be delivered to the target anatomical location (e.g., a renal artery) via femoral, radial or other intravascular access. The system can be delivered through the vasculature or other lumen of the subject either with or without the assistance of a guidewire. Accordingly, as discussed in greater detail below, the catheter and other components of the system can include a guidewire lumen or other passages to permit delivery over a guidewire. In other embodiments, a steerable catheter or sheath and/or any other

guiding device or method can be used to deliver the system to the targeted anatomical location of the subject.

[0074] In some embodiments, the ultrasonic transducers are operated in a range of from 1 to 20 MHz (e.g., 1-5 MHz, 5-10 MHz, 10-15 MHz, 15-20 MHz, 8-10 MHz, other values or ranges within the foregoing, etc.). In one embodiment, for example, the ultrasound transducer of the system is configured to operate at a frequency of about 9 MHz. In other embodiments, however, the frequency at which a transducer is operated can be below 1 MHz (e.g., 0.1-0.2, 0.2-0.3, 0.3-0.4, 0.4-0.5, 0.5-0.6, 0.6-0.7, 0.7-0.8, 0.8-0.9, 0.9-1.0 MHz, frequencies between the foregoing ranges, less than 0.1 MHz, etc.) or above 20 MHz (e.g., 20-25, 25-30 MHz, frequencies between the foregoing ranges, above 30 MHz, etc.), as desired or required for a particular application or use. The power supplied to the ultrasound transducer can vary, as desired or required, and in some embodiments, is 5 to 80 Watts (e.g., 5 to 50, 5 to 10, 10 to 20, 20 to 30, 30 to 40, 40 to 50, 50 to 60, 60 to 70, 70 to 80 Watts, power levels between the foregoing ranges, etc.) at the transducer. As noted above, the period of time during which the ultrasound is activated for a particular treatment procedure can vary, and can also depend on one or more other factors, such as, for example, the power level at the transducer, the frequency of ultrasonic energy emitted, the size of the vessel or other tissue being treated, the age, weight and gender of the patient being treated and/or the like. However, in some embodiments, the ultrasonic transducer is activated for about 10 seconds to 5 minutes (e.g., 10-30 seconds, 30 seconds to 1 minute, 30 seconds to 5 minutes, 1 to 3 minutes, about 2 minutes, 10 seconds to 1 minute, 1 to 2 minutes, 2 to 3 minutes, 3 to 4 minutes, 4 to 5 minutes, time periods between the foregoing ranges, etc.). In other embodiments, the ultrasonic transducer is activated for less than 10 seconds (e.g., 0-1, 1-2, 2-3, 3-4, 4-5, 5-6, 6-7, 7-8, 8-9, 9-10 seconds, time periods between the foregoing ranges, etc.) or more than 5 minutes (e.g., 5-6, 6-7, 7-8, 8-9, 9-10, 10-15, 15-20 minutes, time periods between the foregoing, more than 20 minutes, etc.), as desired or required for a particular application or treatment protocol.

[0075] In some embodiments, the delivery of ultrasound energy during the execution of a treatment protocol is continuous or substantially continuous, e.g., without any interruptions or fluctuations in frequency, power, duty cycle and/or any other parameters. In



other embodiments, however, the frequency, power, duty cycle and/or any other parameter is modified during the course of a procedure. For example, in some embodiments, the delivery of acoustic energy is modulated (e.g., between an on or off position, between a high and low level, etc.) to prevent or reduce the likelihood of overheating of adjacent (e.g., targeted or non-targeted tissue). Additional information regarding such modulation is provided in co-pending U.S. Application No. 12/227,508, filed on February 3, 2010 and published as U.S. Publication No. 2010/0130892 on May 27, 2010, the entirety of which is incorporated by reference herein and made part of the present application.

[0076] Referring now to FIG. 2, in several embodiments, the system can be delivered intravascularly through a subject so that the transducer is positioned within a target vessel (e.g., a renal artery) 36 and adjacent nerve tissue N to be neuromodulated. As shown, the expandable member (e.g., balloon) 14 can be inflated (e.g., using a cooling fluid and/or any other fluid). Expansion of the balloon 14 can cause the wall of the balloon to at least partially engage the adjacent interior wall of the vessel 36. As discussed herein, however, in some embodiments, inflation of the balloon does not cause the balloon to contact the interior wall and/or any other portion of the adjacent vessel or lumen. In addition, in some embodiments, expansion of the balloon or other expandable member 14 causes the transducer 16 to be generally centered within the vessel. The ultrasound transducer 16 can be activated to generate ultrasonic energy that passes radially outwardly through the balloon and to the adjacent tissue of the subject. For example, the ultrasonic or acoustic energy can pass through the wall of the vessel 36 and heat the adjacent nerve tissue N. In some embodiments, sufficient energy is delivered to the nerve tissue N to cause a desired heating and/or other response. Thus, the energy delivered to the nerve tissue can neuromodulate (e.g., necrose, ablate, stimulate, etc.) the nerves, as desired or required.

#### Guidewire-Enabled Catheter System

[0077] As noted above, the ultrasound treatment systems described herein can be configured to be delivered to a target anatomical location of a subject with or without the use of a guidewire. FIG. 3 illustrates a cross-sectional view of the distal end of an ultrasound-based ablation system 100 that is configured to be delivered over a guidewire. As shown, the ultrasound transducer 16 can comprise a cylindrical tube 44 comprising a piezoelectric

material (e.g., PZT, lead zirconate titanate, etc.) with inner and outer electrodes 46, 48 along the inner and outer surfaces of the cylindrical tube 44, respectively. When activated, the piezoelectric material vibrates transverse to the longitudinal direction of the cylindrical tube 44 (e.g., radially).

[0078] With continued reference to FIG. 3, the transducer 16 is generally supported within the interior of the balloon 14 using a backing member or post 56. As shown, the backing member 56 can extend from the catheter 12 to a distal tip 18. For example, in some embodiments, the backing member 56 is positioned within adjacent openings of the catheter and tip. Further, the balloon or other expandable member 14 can be secured along an exterior or other portion of the catheter and tip.

[0079] In order to permit liquid cooling along both the inner and outer electrodes 46, 48 of the transducer, the transducer can include one or more stand-off assemblies 50. As shown schematically in FIGS. 3 and 4, for example, the stand-off assemblies 50 can be positioned along or near each end of the transducer and couple the cylindrical portion of the transducer 16 to the backing member 56. The stand-off assemblies 50 can define one or more annular openings 55 through which cooling fluid may enter the interior space 52 of the cylindrical tube. One or more of the stand-off assemblies 50 can be electrically conductive so as to electrically couple the inner electrode 46 of the transducer 16 to the backing member or post 56. As discussed in greater detail herein, for example, in some embodiments, one or more conductors of the electrical cable 28 can be electrically coupled to the backing member 56. The conductors can be directly or indirectly coupled to the backing member, as desired or required. Thus, as the power generator is activated, current can be delivered from the cable 28 to the inner electrode 46 of the transducer via the post 56 and the stand-off assembly 50. According to one embodiment, this advantageously eliminates the need to electrically couple the cable directly to the inner electrode of the transducer.

[0080] With reference to FIG. 4, the stand-off assembly 50 can have a plurality of ribs or attachment points 54 that engage the inner electrode 46. The number, dimensions and placement of the ribs 54 can vary, as desired or required. For example, in some embodiments, as illustrated in FIG. 4, a total of three ribs 54 are generally equally-spaced apart from one another at an angle of 120°. However, in other embodiments, the quantity,

shape, size, orientation, spacing and/or other details of the rigs or other attachment points can vary, as desired or required by a particular design or application.

[0081] With further reference to FIG. 3, the internal space 52 defined by the ultrasound transducer 16 can allow the piezoelectric material to vibrate both outwardly and inwardly in the transverse direction. As discussed herein, the internal space 52 of the transducer can be in fluid communication with the interior cavity 38 of the expandable member 14 so that, when in use, fluid entering the expandable member 14 can pass along and cool both the inner and outer surfaces of the ultrasound transducer 44. The cooling fluid can be used to maintain a desired temperature threshold along the interior wall of the vessel (e.g., renal artery) while allowing a higher temperature profile a particular distance radially away from the vessel wall. For example, such a configuration can permit ultrasonic energy to provide targeted heating to a specific location or zone located at a particular distance from the transducer. In some embodiments, such a configuration can advantageously permit targeted nerve tissue to be neuromodulated (e.g., necrosed, ablated, etc.) while protecting the vessel wall from unwanted harm or injury (e.g., stenosis, ablation or reconstruction, scarring, etc.). Likewise, for embodiments that treat tissue other than nerves, target tissue can be treated, while protecting non-target tissue.

[0082] According to some embodiments, as illustrated in FIGS. 3 and 4, the ultrasound-based ablation system 100 can be configured for delivery over a guidewire (e.g., regular guidewire, rapid-exchange system, etc.). Thus, the catheter can include a central guidewire lumen 60. In addition, other portions of the system can also include a lumen or other passage for receiving a guidewire. For example, the backing member or post 56 and the tip 18 can each comprise a central opening, lumen or passage 62, 64 that are generally aligned with the guidewire lumen 60 of the catheter. In one embodiment, the guide wire lumen 60 of the catheter 12 extends from the proximal end 20 of the catheter to the distal tip 18. Alternatively, a monorail guidewire configuration could be used, where the catheter rides on the wire just on the tip section distal to the transducer. In another embodiment, the guidewire lumen 58 extends from a location between the proximal 20 and distal 22 ends of the catheter to the distal end 22 of the catheter, such that the catheter comprises a rapid exchange design (e.g., one in which the guidewire lumen of the catheter does not extend to

the proximal end of the catheter). In any of the embodiments disclosed herein, regardless of whether or not the system is configured for delivery over a guidewire, the catheter could comprise one or more pull wires or other features (e.g., steerable catheters or sheaths) that permit the system to be selectively manipulated (e.g., for selective deflection of the catheter) to aid in the delivery and placement within the subject, either in lieu of or in addition to a guidewire lumen.

[0083] In some embodiments, the backing member 56 advantageously serves as a fluid barrier between the cooling fluid circulated within the expandable member 14 and the central opening, lumen or passage 62 through which the guidewire is routed. In some embodiments, the backing member or post 56 can include one or more layers of an electrically insulating material or member 57 (e.g., polyimide, other polymeric or elastomeric material, other natural or synthetic material, etc.) along an interior surface of the central opening 62 of the backing member 56 so as to prevent or reduce the likelihood of electrical conduction between the guidewire 58 and the backing member 56. Such an electrically insulating member 57 can also provide one or more other benefits to the system, such as, for example, reduced friction between the guidewire and the post. As illustrated in FIG. 3, the various lumens or other openings of the catheter 12, backing member or post 56 and the distal tip 18 can be generally aligned and sized and shaped so as to allow a guidewire to freely and easily pass therethrough. Thus, the size, shape and other details of the lumens can be customized according to a particular application or use (e.g., based, at least in part, on the size of the catheter, the size of the guidewire, etc.).

#### Electrical Loading of Transducer

[0084] FIG. 5 illustrates a partial cross-sectional view of the expandable member (e.g., balloon) 14 and ultrasound transducer 16 of an ultrasound-based ablation system 100 according to one embodiment. As shown in FIG. 5, in some embodiments, the ultrasound transducer 16 comprises a uniform and cylindrical outer and inner diameters to provide for a uniform distribution of acoustic energy radially emanating therefrom (e.g., toward adjacent nerve tissue surrounding a vessel). In some embodiments, the outer and inner surfaces of the transducer 16 are coaxial and parallel with one another. Such a configuration can help ensure that a generally equal acoustic energy profile is delivered by the transducer during use.

Accordingly, localized hotspots of ultrasonic energy, where a greater amount of heating is observed along one circumferential area and/or longitudinal area of the treatment region, are eliminated (or their likelihood is reduced). Further, as noted herein, adjacent portions of the balloon or other expandable member 14 can also include a uniform and/or flat profile upon expansion, such that outer and inner surfaces of the cylindrical transducer are generally parallel with the wall of the expanded balloon. Such a feature can help ensure that acoustic energy delivered by the transducer moves radially outwardly with little or no deflection at the balloon and/or the balloon-tissue interface.

**[0085]** In some embodiments, the acoustic energy profile of the transducer can be negatively affected by attaching anything to the outside and/or inside surfaces of the transducer tube (e.g., along the outer and/or inner electrodes of the transducer). For example, connecting an electrical conductor of the electrical cable that supplies current to the transducer can result in a diminished or undesirable acoustic energy profile. In such a configuration, for example, the wire or other electrical connection may be positioned along the outer surface of the electrode, which can disrupt the uniformity of such a surface and the uniformity of the acoustic energy pattern originating therefrom. Embodiments for eliminating the need to attach any electrical conductors or other leads to the outer and inner electrodes of a transducer are illustrated in, e.g., FIGS. 5, 6 and 6c.

**[0086]** In FIGS. 5 and 6, the cylindrical tube 44 can include a distal, non-stepped portion 66 and a proximal, stepped portion 68. As shown, the non-stepped portion comprises an outer electrode 48 along the exterior surface of the tube 44 and an inner electrode 46 along an interior surface of the tube. In some embodiments, the outer and/or inner electrodes can extend completely or partially along the length of the tube 44. As discussed in greater detail below, the non-stepped portion of the transducer 16 can comprise a vast majority of the transducer length, such as, for example, 50-95% or 60-90% (e.g., 50-60%, 60-70%, 70-80%, 80-90%, 90-95%, 90-99%, percentages between the foregoing ranges, etc.) of the overall length of the transducer 16. In other embodiments, however, the non-stepped portion can extend along less than 60% (e.g., 40-50%, 50-55%, 55-60%, less than 40%, etc.) or greater than 95% (e.g., 95-96, 96-97, 97-98, 98-99%, more than 99%, etc.) of the overall length of the transducer, as desired or required.

[0087] With continued reference to FIGS. 5 and 6, the proximal, stepped portion 68 includes an outer diameter 68a that is less than the outer diameter 66a of the non-stepped portion 66. In other words, the cylindrical tube 44 can comprise a step change in outer diameter along one of its ends (e.g., the proximal end). In the depicted embodiments, the stepped portion includes a generally flat or non-sloped step. However, in other embodiments, the step can include, without limitation, a sloped, non-flat, curved or rounded, undulating, roughened or otherwise uneven surface profile. Regardless of its exact shape and configuration, as shown in FIGS. 5 and 6, the stepped portion 68 of the tube can provide a surface on which a conductor of the electrical cable 28 can be positioned and/or to which it can attach. By placing an additional at least partially electrically conductive material or member along the outside of the conductor at the stepped portion of the tube, the cable can be advantageously electrically coupled to the outer electrode 48 of the transducer without attaching any conductors along an outer diameter or portion of the transducer. Accordingly, the cylindrical outer surface of the transducer can be maintained along the entire or substantially the entire length of the transducer to provide for a more even acoustic energy profile when the transducer is activated.

[0088] In some embodiments, the stepped portion 68 can be fabricated or otherwise manufactured by machining and/or grinding away a proximal portion of the tube's outer diameter 66a. As noted herein, such a step can include a uniform or constant outer diameter; however, in other embodiments, the stepped portion comprises a non-flat (e.g., rounded, curved, sloped, etc.) or irregular profile, as desired or required. In other embodiments, the stepped portion 68 can be fabricated or otherwise created by manufacturing the cylindrical tube 44 as a single piece of material with the step integrated into the tube during formation (e.g., by casting or molding the step into the original design). In yet another embodiment, the cylindrical tube 44 with the step can be created as two separate components (e.g., one with a larger diameter and one with the step diameter) which are bonded together (e.g., by welds, adhesives, rivets, screws, threaded couplings or features on the tube itself, press-fit connections, other mechanical or non-mechanical features, etc.).

[0089] In one embodiment, the cable 28 that supplies electrical current to the transducer comprises a coaxial cable having an inner conductor 28a and outer tubular

conducting shield 28b. As shown in FIG. 6, the inner conductor 28a can be electrically coupled with the outer electrode 48 (e.g., via attachment to the stepped portion), while the outer tubular conducting shield 28b can be electrically coupled with the inner electrode 46 of the cylindrical tube 44. In other embodiments, the conductors of the coaxial cable can be reversed and/or different types of electrical cables or connectors can be used.

[0090] With continued reference to FIG. 5, one or more rings and/or other components 72 can be placed around the stepped portion 68 of the tube to form a generally constant outer diameter along an entire length of the transducer 16 (e.g., both along the stepped and non-stepped regions). For example, an electrically conductive ring 72 can surround the stepped portion 68 of the cylindrical tube 44 to electrically couple the outer electrode 48 to the inner conductor 28a. The ring 72 can be sized and shaped to have substantially the same outer diameter as the outer diameter 66a of the non-stepped portion 66 and provide a substantially continuous, flat and/or uniform outer surface for the entire transducer. In such an embodiment, the ring 72 can act as an active portion of the transducer 16 and allow for more uniform electrical loading of the ultrasound transducer when the electrical transducer is energized. The ring can be a machined ring having very precise dimensions. The ring, which comprises one or more metals or alloys (e.g., brass, stainless steel, etc.), can include a solid or partially-solid (e.g., having one or more hollow portions or area) design. The ring can include a uniform or unitary structure. Alternatively, in some embodiments, the ring or other member or components that is positioned along the outside of the stepped portion of the tube can include two or more pieces (e.g., 2, 3, 4, more than 4, etc.) that are configured to secure to one another when properly positioned relative to the stepped portion.

[0091] In other embodiments, one or more other components can be placed over the stepped portion 68 of the tube. For example, one or more layers of solder or other masses of at least partially electrically conductive can be deposited and secured to the outside of the stepped portion. Such layers or masses can include an outer diameter that matches the outer diameter 66a of the non-stepped portion 66 of the transducer. In some embodiments, an outer surface of the conductive electrical solder or other material or component placed along the outside of the stepped portion is reshaped or otherwise treated to achieve a substantially

uniform overall outer diameter for the transducer (e.g., by mechanical grinding, etching, or polishing).

[0092] In some embodiments, the stepped portion 68 extends approximately 5% to 25% (e.g., 5% to 10%, 10% to 15%, 15% to 20%, 20% to 25%, etc.) of a length of the cylindrical tube 44. For example, the stepped portion 68 (and the corresponding ring, solder or other material or component placed around the stepped portion) can be approximately 1 mm in length, while the non-stepped portion 66 can be approximately 5 mm in length.

[0093] Alternatively, the cylindrical tube 44 can include a stepped portion 68 without an electrically conductive ring or other component 72. In such embodiments, the stepped portion 68 can form an inactive portion (or a partially inactive portion) of the transducer 16 and the distal, non-stepped portion 66 can form the active portion of the transducer 16. One or more electrical connections (e.g., wires, other conductors, traces, etc.) can be placed along the inactive stepped portion and be routed to the outer electrode of the non-stepped portion 66 of the transducer.

[0094] In some embodiments, as illustrated in FIGS. 6a and 6b, the tube 16 comprises a stepped portion 68' that extends only partially around the tube. Thus, the stepped portion 68' can include one or more (e.g., 2, 3, 4, more than 4, etc.) regions of the tube 16 that are recessed or that otherwise do not extend to the outer circumference of the tube. Alternatively, as illustrated and discussed herein with reference to FIG. 6, the stepped portion 68 can extend completely around the tube.

[0095] With continued attention to the embodiment illustrated in FIGS. 6a and 6b, an end (e.g., proximal end) of the tube 16 can include, for example, oppositely oriented flattened or non-circular features along the stepped portion 68'. As noted in greater detail herein, the tube 16 can be manufactured (e.g., cast, formed, etc.) with a desired stepped portion 68'. In other embodiments, however, the features of the stepped portion 68' can be created by removing material from one or more regions of a cylindrical tube. For example, the stepped portion 68' can be created by selectively cutting, grinding and/or otherwise removing material from the tube.

[0096] As illustrated in the embodiment illustrated in FIGS. 6a and 6b, the tube 16 can comprise upper and lower flattened regions along the stepped portion 68'. In other



embodiments, however, the stepped portion 68' can include fewer (e.g., one) or more (e.g., 3, 4, 5, 6, more than 6, etc.) flattened features or portions and/or other recesses (e.g., relative to the main outer diameter of the tube). Such features or recesses of the stepped portion can be continuous or discontinuous and/or may include any shape (e.g., flat, curved or rounded, irregular, fluted, undulating, etc.), as desired or required. In some embodiments, for example, the stepped portion includes a length of the tube 16 having a smaller outer diameter than the major outer diameter of the tube (e.g., the adjacent main portion of the tube). Therefore, the stepped portion can comprise a generally circular outer diameter (e.g., FIG. 6) that extends completely around the tube.

[0097] In some embodiments, the diameter or other cross-sectional dimension of the stepped portion 68a is 50-95% (e.g., 50-55, 55-60, 60-65, 65-70, 70-75, 75-80, 80-85, 85-90, 90-95%, percentages between the foregoing ranges, etc.) of the outer diameter 66a of the transducer. In other embodiments, the diameter or other cross-sectional dimension of the stepped portion 68a is less than 50% (e.g., 20-30, 30-40, 40-50%, percentages between the foregoing ranges, less than 20%, etc.) or greater than 95% (e.g., 95-96, 96-97, 97-98, 98-99, 99-100%, percentages between the foregoing ranges, etc.) of the outer diameter 66a of the transducer.

[0098] As shown in FIG. 6a, regardless of the exact shape and configuration of the stepped portion 68', one or more wires or other electrical conductors 28 (e.g., portions of a cable) can be advantageously secured to the outer surface of the tube. Since, in such embodiments, the outer surface of the tube 16 along the stepped portion 68' does not extend to the major outer diameter of the tube 16, the conductors 28 can be retained within the major outer diameter. As discussed herein with reference to FIG. 6, one or more components, materials and/or the like 72' can be positioned along the stepped portion 68' to match or substantially match the final major outer diameter of the stepped portion 68' to the adjacent portion (e.g., non-stepped portion) of the tube 16. Such components and/or materials 72' can comprise, without limitation, solder (e.g., silver-based solder, conductive epoxy, other flowable or malleable materials, mechanical rings and/or the like. Such components and/or materials can be at least partially electrically conductive in order to electrically couple the one

or more conductors 28 positioned along the stepped portion 68' to the outer electrode of the transducer.

[0099] With reference to FIG. 6c, in some embodiments, the distal ring 72 does not extend past the innermost portion of the adjacent stand-off assembly 50 that is positioned between the backing member or post 56 and the transducer. In other words, the distance from the end of the transducer tube 44 to the proximal end of the ring 72 (designated as distance X2 in FIG. 6c) is less than the distance from the end of the tube to the proximal end of the stand-off assembly 50 (designated as distance X1 in FIG. 6c). Such a configuration can help ensure that the acoustic energy profile generated by the transducer is uniform, both radially around the circumference of the transducer and axially along the length of the transducer. In some embodiments, if X2 is equal to or greater than X1 (e.g., in other words, if the ring 72 extends proximally to the stand-off assembly 50), the manner in which the transducer is permitted to vibrate during use can be negatively impacted, thereby causing at least partial non-uniformity (e.g., radial and/or axial) of the resulting acoustic pattern generated from the transducer.

#### Electrical Impedance Matching

[0100] As discussed herein, the ultrasonic transducer 16 can convert input electrical energy into ultrasonic energy that is delivered radially outwardly (e.g., toward target nerve tissue or other tissue adjacent a vessel wall). In some embodiments, for ultrasonic transducers, the power factor, or conversion rate from electrical energy into generated acoustical energy, can be relatively low. Thus, a large portion of the electrical power delivered by the power supply may be lost as wasted heat. Accordingly, in one embodiment, to increase the efficiency of the ultrasound system, the electrical impedance of the electrical conductors (e.g., the one or more electrical cables 28 that electrically couple the transducer to the power supply) can be matched or substantially matched (e.g., within about 0-10%, 0.1%, 0.2%, 0.3%, 0.4%, 0.5%, 0.5-1%, 1-2%, 2-3%, 3-4%, 4-5%, 5-6%, 6-7%, 7-8%, 8-9%, 9-10%, etc.) to the electrical impedance of the ultrasound transducer 44. Thus, in some embodiments, by matching or substantially matching the impedance values of the cable and the transducer, the electrical load of the system can help reduce or minimize the electrical

inefficiency of the system, while increasing or maximizing the amount of power transferred to the transducer.

[0101] Accordingly, in some embodiments, the ultrasound system 100 comprises only a single cable (e.g., coaxial cable) routed through a corresponding lumen of the catheter and electrically coupled to the transducer. The electrical cable can be selected to match or substantially match an impedance of the ultrasound transducer. For example, in some embodiments, the impedance of both the electrical cable and the ultrasound transducer is approximately 40 to 60 ohms (e.g., 50, 40-42, 42-44, 44-46, 46-48, 48-50, 50-52, 52-54, 54-56, 56-58, 58-60 ohms, etc.). In other embodiments, the impedance of the electrical cable and the ultrasound transducer can be less than 40 ohms or greater than 60 ohms, as desired or required.

#### Cooling fluid considerations

[0102] FIG. 7 schematically illustrates one embodiment of a catheter-based ultrasound system 100 having at least two fluid lumens 26a, 26b positioned within the catheter 12. As shown, each lumen 26a, 26b of the catheter is placed in fluid communication with a separate fluid transfer device (e.g., pump). Further, with reference back to FIG. 1, each lumen 26a, 26b can be in fluid communication with corresponding pumps or other fluid transfer devices (not shown) via ports 34a, 34b (e.g., a luer fittings, other standard or non-standard couplings, etc.). Accordingly, cooling fluid can be injected, infused or otherwise delivered into the vessel to transfer heat away from the transducer and/or other areas at or near the treatment site. As discussed herein, such heat transfer can protect adjacent tissue of the subject (e.g., the wall of the vessel in which the system is placed), can help maintain the transducer within a desired temperature range during use (e.g., for safety and/or performance reasons) and/or the like.

[0103] According to some embodiments, the cooling fluid that is circulated through the balloon at the distal end of the system can include, for example, saline, water and/or any other liquid or fluid. The cooling fluid can be room temperature or actively cooled (e.g., cooled relative to room temperature, body temperature, etc.), as desired or required. In some embodiments, cooling fluid is circulated through the system in such a manner so that the temperature along the interior wall of the vessel surrounding the

transducer is maintained at a temperature of about 50-55°C (e.g., 50°C, 51°C, 52°C, 53°C, 54°C, 55°C, etc.). In other embodiments, the target temperature can be below 50°C (e.g., 30-35°C, 35-40°C, 40-45°C, 45-50°C, temperatures between the foregoing ranges, less than 30°C, etc.) or greater than 55°C (e.g., 55-60°C, 60-65°C, 65-70°C, 70-75°C, temperatures between the foregoing ranges, greater than 75°C, etc.), as desired or required. In addition, in some embodiments, the temperature of the vessel wall is maintained within such a target range (e.g., 50-55°C, 30-75°C, etc.), while the temperature of tissue approximately 0.5 mm to 8 mm (e.g., 1 mm to 6 mm, where, in some embodiments, target tissue is located) is heated to about 60-80°C (e.g., 60-70°C, 70-80°C, 65-75°C, etc.), 50-100°C (e.g., 50-60°C, 60-70°C, 70-80°C, 80-90°C, 90-100°C, temperatures between the foregoing ranges, etc.), greater than 100°C, when the transducer is activated. The higher temperature at a particular distance away from the vessel wall can be due, at least in part, on the less effective cooling by the cooling fluid at those distances away from the balloon. In some embodiments, raising the temperature of nerve and/or other nerve tissue to about 60-80°C can help perform the desired neuromodulation (e.g., ablation, necrosing, stimulation, etc.) to such tissue. A treatment protocol that accomplishes the desired heating of the targeted tissue (e.g. nerves) while maintaining adjacent vessel tissue to safe levels (e.g., to reduce the likelihood of stenosis or other damage to such tissue) can be based, either completely or in part, on empirical or experimental data.

**[0104]** Certain vessels (e.g., renal arteries) in which the system can be placed can have a relatively small catheter diameter. As a result, the diameter of the fluid lumens 26a, 26b located within the catheter may also need to be reduced. As the diameter of the fluid lumens 26 are decreased, the pressure required to move the cooling fluid increases (e.g., due to an increase in back pressure and head losses through the fluid lumens). As a result, in some arrangements, increased cooling fluid pressure can be required by one or more of the pumps or other fluid transfer devices in fluid communication with the system. However, if the system fluid pressure is increased to a high enough value, the increased pressure of the balloon can create one or more safety concerns. For example, the balloon itself may be susceptible to rupture or other damage. Further, the pressure created within the balloon can cause the balloon to expand to a degree that poses a risk of harm to the adjacent tissue of the

subject (e.g., the artery or other vessel of the subject may rupture or otherwise be damaged). Accordingly, in some embodiments, it is desirable to regulate and limit the pressure within the balloon. For example, in some embodiments, the internal pressure of the balloon 14 is maintained at about 1.5-2 ATM (e.g., for a 6 FR catheter).

**[0105]** As illustrated in FIG. 7, in one embodiment, the fluid lumens 26a, 26b can include a delivery lumen 26a and a return lumen 26b for supplying and returning cooling fluid to and from, respectively, the balloon or other expandable member 14. The use of separate fluid lumens 26a, 26b can help reduce the overall internal pressure of the balloon during use, while still being able to circulate cooling fluid at a target flowrate through the balloon interior. Thus, a desired flowrate of cooling fluid can be sustained through the system without over-pressurizing the balloon 14. This is due, in part, because the vacuum created through the return lumen 26b (e.g., by one of other pumps P) helps reduce the pressure within the balloon interior accordingly. By way of example, the delivery lumen 26a can have a pressure of approximately 70 psig and the return lumen 26b can have a vacuum of 10 psig. Thus, under those circumstances, the internal pressure of the balloon is about 30 psig (e.g.,  $(70 \text{ psig} - 10 \text{ psig}) / 2 = 30 \text{ psig}$ ).

**[0106]** In one embodiment, the pumps P or other fluid transfer devices that are placed in fluid communication with the fluid lumens 26a, 26b comprise positive displacement pump, such as a peristaltic pump. However, in some circumstances, when the back-pressures associated with delivering the cooling fluid to the balloon is above a particular threshold, peristaltic pumps or similar positive displacement pumps are unable to deliver the necessary flowrate of cooling fluid to the balloon.

**[0107]** Accordingly, in some embodiments, one or more pumps P of the systems can comprise a syringe pump. A syringe pump can include a reservoir for storing a volume of cooling fluid and a movable member configured to move (e.g., slide) within an interior of the reservoir. The movement of the movable member within the corresponding reservoir exerts the necessary backpressure on the fluid (e.g., cooling fluid) stored within the reservoir and transfers the fluid through the fluid delivery lumen 26a of the catheter and into the balloon. In some embodiments, the use of such syringe pumps can provide sufficient force to achieve the required backpressure at a desired flowrate of cooling fluid. The movable

members of syringe or other such pumps can be selectively moved by one or more stepper motors or other mechanical devices. In such embodiments, the stepper motor can prevent and/or minimize deflection of the movable member caused by the corresponding torques, moments and forces.

**[0108]** According to some embodiments, the reservoir of the syringe or other pump P in fluid communication with the fluid lumen 26a and the balloon 14 is sized and otherwise configured to store a sufficient volume of cooling fluid for an entire treatment procedure. In some embodiments, the volume of the reservoir is approximately 50 ml to 1,000 ml (e.g., 50-100, 100-200, 200-300, 300-400, 400-500, 500-600, 600-700, 700-800, 800-900, 900-1,000 ml, capacities between the foregoing, etc.). In other embodiments, the volume of the reservoir is less than 50 ml (e.g., 20-30, 30-40, 40-50 ml, volumes between the foregoing ranges, less than 20 ml) or greater than 1,000 ml (e.g., 1,000-1,100, 1,100-1,200, 1,200-1,300, 1,300-1,400, 1,400-1,500, 1,500-2,000, 2,000-3,000, 3,000-5,000 ml, volumes between the foregoing ranges, greater than 5,000 ml, etc.), as desired or required.

**[0109]** In one embodiment, the fluid lumens 26 can be operated simultaneously to circulate cooling fluid through the expandable members 14 during an ablation procedure. In one embodiment, the flowrate of cooling fluid through the lumens 26 can be between 30-50 ml/min (e.g., 30-40 ml/min, 40-50 ml/min, 35-45 ml/min, 40 ml/min).

#### IV bag connector

**[0110]** IV bags used for the storage of cooling fluid in connection with the various systems disclosed herein can have two outlet ports (e.g., for mating to the two fluid lumens 26 of the catheter). In other embodiments, however, the IV bag 200 is constructed with only a single inlet/outlet port 210, as depicted in FIG. 8. In such embodiments, a dual lumen spike or coupling 74 can be inserted within the port 210 of the IV bag 200 to enable fluid to be transferred both to and from the bag. This can effectively turn a single-port IV bag into a dual port IV bag without redesigning the bag itself.

**[0111]** In some embodiments, the dual lumen spike or coupling 74 can comprise two or more lumens or passages 76, 78 that are separated from one another. Such separate passage 76, 78 can be connected to different fluid conduit or sources, as desired or required. As shown, the spike 74 can include a proximal hub 82 that is shaped, sized and otherwise

configured to abut against an end of bag's port 210 (or other inlet or outlet). A proximal conduit 84 can be inserted within or otherwise placed in fluid communication with one or more fluid sources (e.g., lumen of a catheter as disclosed herein, a pump, etc.). In some embodiments, the spike can include a minimum penetration depth 80 into the IV bag to ensure adequate flow (e.g., supply and return) into and out of the bag. Such a minimum penetration depth can help prevent or reduce the likelihood of short-circuiting of fluids entering and exiting the bag 200. In some embodiments, the inner diameters of the internal lumens or passages 76, 78 of the spike or coupling 74 are approximately 0.05 to 0.125 inches (e.g., 0.05-0.06, 0.06-0.07, 0.07-0.08, 0.08-0.09, 0.09-0.1, 0.1-0.11, 0.11-0.125 inches, diameter between the foregoing, etc.) and the minimum penetration distance 80 is about 1.5 inches (e.g., 0.75, 1.0, 1.25, 1.5 inches, distances between the foregoing, less than 0.75 inches, more than 1.5 inches, 1.5-2.0 inches, 2.0-3.0 inches, more than about 3 inches, etc.).

[0112] In some embodiments, such a coupling or spike 74 can be used on an IV bag or other fluid container that is placed in fluid communication with a syringe pump of a treatment system. Thus, the IV bag can be configured to store additional fluid that will be delivered through a delivery lumen into a balloon and/or can be configured to store excess fluid being returned from the balloon via a return lumen in the catheter. Thus, the coupling 74 can be placed in fluid communication with the catheter and/or the syringe pump of the treatment system.

#### Vessel Diameter Detection

[0113] In some embodiments, prior to inflation of a balloon or other expandable member 14, the ultrasonic transducer 16 can be activated to measure the vessel's diameter. This can be accomplished by sending out a single (or a distinct number of) ultrasonic waves and recording the time period required for the signals to return (e.g., bounce back) to the transducer surface. Thus, in some embodiments, a control system of the system can be configured to both emit acoustic energy and detect it (e.g., at or along the outside of the transducer). By detecting the diameter of the vessel (e.g., renal artery) at a desired treatment location, the clinician can make any necessary adjustments to the procedure (e.g., what size balloon to use, how much energy should be delivered to the subject and for what time period, etc.).

Miscellaneous Concepts

[0114] In any of the embodiments disclosed herein, the system can comprise an ultrasound transducer having a variety of shapes. The transducer can be cylindrical or non-cylindrical, as desired or required. For example, in some embodiments, the transducer comprises, at least in part, an hourglass shape, a barbell shape, a convex shape or surface, a concave shape or surface and cone shape, an irregular shape and/or the like.

[0115] In some embodiments, a system comprises an array of transducers (e.g., an array comprising 2, 3, 4, 5, 6, 7, 8, 9, 10, 10-15, more than 15 transducers, etc.). In embodiments comprising 2 or more transducers (e.g., an array of transducers), one or more of the transducers can be configured to emit more or less ultrasonic energy than one or more other transducers. In some embodiments, the amount of acoustic energy that is emitted by the plurality of transducers varies (e.g., linearly, non-linearly, randomly, etc.) along a longitudinal axis of the system. In some embodiments, one or some ultrasound transducer of a system emit (or are configured to emit) greater acoustic energy in one or more directions in relation to one or more other directions.

[0116] In any of the embodiments disclosed herein, an ultrasound transducer can include differing wall thickness (e.g., along its longitudinal axis). In embodiments comprising two or more transducers, the wall thickness of one transducer is greater or less than the wall thickness of another transducer. In some embodiments, one or more transducers of a system can be independently controllable (e.g., such that power and/or frequency to one transducer can be different than power and/or frequency to another transducer, etc.). In some embodiments, two or more transducers of a system are controlled together or in unison. In one embodiment, a transducer can include an eccentric or non-uniform backing lumen or opening.

[0117] In any of the embodiments disclosed herein, the transducer comprises a varying wall thickness along at least a portion of its circumferential extent. Accordingly, rotating the transducer can alter the acoustic energy pattern emitted by the transducer and/or alter one or more other aspects of energy emission (e.g., frequency, efficiency, etc.) during use. In some embodiments, one or more regions, surfaces and/or other portions of a transducer can be at least partially masked, covered, obstructed, etc. in order to alter the



acoustic energy profile of the transducer during use. For example, at least a portion of the transducer can be masked or otherwise covered by selective plating and/or etching of the electrodes along the transducer, covering a portion of the transducer, using one or more features of the balloon, etc.). Additional information regarding such masking or selective blocking of ultrasonic energy emitted from a transducer is provided in PCT Application No. PCT/US2011/025543, filed on January 18, 2011 and published on August 23, 2012 as PCT Publication WO 2012/112165, the entirety of which is incorporated by reference herein and made a part of this application.

**[0118]** In some embodiments, ultrasonic energy is directed directly within the tissue of the targeted nerve tissue (e.g., sympathetic nerves). In any of the embodiments disclosed herein, a balloon and/or other expandable structure or member can be used to at least partially expand the area or volume of tissue being treated (e.g., the renal artery, other body lumen or vessel, etc. can be radially expanded). In some embodiments, an ablation system includes a balloon (e.g., positioned at least partially around one or more transducers), but no fluid is configured to be circulated through the balloon during use. For example, in one embodiment, the balloon can be inflated with one or more gases, liquids and/or fluids (e.g., in order to expand the balloon, so that balloon contacts the adjacent wall of the targeted vessel, so that the one or more transducers of the system are radially centered or generally radially centered within the vessel, etc.), but no fluids are circulated through the balloon. Thus, the balloon can be configured to maintain an inflated or expanded state without the continuous or intermittent delivery of fluid therethrough.

**[0119]** In some embodiments, a catheter of the system comprises a chip (e.g., a smart catheter) and/or one or more related components or features (e.g., an identification device or reader, a transducer, etc.). Accordingly, the generator can detect which catheter is being used. Further, the system can monitor one or more aspects of a therapy or procedure using one or more metrics that are detected, such as, for example, pressure, temperature, flowrate, vessel diameter, thermal profile, presence and/or degree of spasm of a vessel, degree of narrowing of a vessel and/or the like. Such information can be used in a control scheme to regulate one or more aspects of the generator and/or other components or devices of the system (e.g., to modulate power, frequency, duration of procedure, automatic shutoff,

billing, patient records or other recordkeeping, memorization of a procedure for other reasons, etc.).

#### Catheter Embodiments

**[0120]** According to some embodiments, as illustrated in FIG. 9-15, the catheter 12 comprises a guidewire lumen 13d that is generally offset relative to the centerline of the catheter. In other words, the guidewire lumen 13d of the catheter is not along the centerline or center of the catheter. Such a configuration could be incorporated into any catheter design, irrespective of size (5 French, 6 French, etc.), type (e.g., over-the-wire, rapid exchange, etc.) and/or the like. For example, such a catheter can be incorporated into any treatment system disclosed herein or variation thereof. As discussed in greater detail herein, an offset orientation of the guidewire lumen can permit other lumens (e.g., the delivery and/or return fluid lumens) 13b, 13c (see, e.g., FIGS. 16 and 17) to be enlarged given a specific catheter outer diameter.

**[0121]** With continued reference to FIGS. 9-15, a centering assembly 90 can be positioned adjacent or near the distal end of the catheter 12. Such a centering assembly 90 can center the guidewire GW within the interior of the balloon 14 and/or distal tip 18. Accordingly, the transducer 16 and other components (e.g., the electrically non-conductive member, backing member or post, etc.) through which the guidewire GW is routed can be advantageously centered (e.g., radially) within the balloon 14. As discussed in greater detail herein, centering of the transducer within the balloon 14 can help provide a more evenly distributed acoustic energy profile in the radial direction from the transducer 16 during use. As a result, if the balloon is centered or substantially centered within the target vessel (e.g., renal artery), acoustic energy is delivered in a uniform manner to the adjacent tissue of the subject. Thus, targeted anatomical tissues (e.g., nerves) surrounding the vessel in which the system is placed can be heated in a more predictable and consistent manner.

**[0122]** As depicted in the perspective view of FIG. 12, the centering assembly 90 can include two or more wings 92 that extend radially outwardly from a central hub. The hub can include a central opening 96 through which a guidewire GW can pass. As discussed in greater detail herein, an electrically non-conductive tube or other member 57 (e.g., comprising polyimide) can be positioned within the central opening 96 of the centering

assembly. Thus, in such embodiments, a guidewire GW can be routed through the electrically non-conductive tube 57 and the central opening 96 of the centering assembly. In any of the embodiments disclosed herein, the electrically non-conductive tube or member 57 can extend from the distal end of the catheter 12 (e.g., from a guidewire lumen of the catheter) to the distal tip 18 (e.g., an interior passage of the distal tip), through the interior of the transducer 16. According to some embodiments, the centering assembly 90 comprises three wings 92 that are evenly distributed around the circumference of the assembly 90 (e.g., spaced apart at 120° intervals). In other embodiments, however, a centering assembly can include fewer (e.g., 1, 2) or more (e.g., 4, 5, 6, more than 6, etc.) wings 92 as desired or required.

**[0123]** In some embodiments, the wings 92 include a curved outer surface. Such an outer surface can be generally smooth and configured to contact an adjacent surface of one or more components of the catheter system (e.g., catheter, balloon, etc.). In some embodiments, the curved outer surface of the wings 92 are shaped so as to match the adjacent interior surface of the balloon or other adjacent component of the system against which they may rest. As discussed in greater detail herein, the centering assembly 90 can be secured within a desired portion of the catheter system using one or more attachment methods or devices, such as, for example, adhesives, fasteners, hot melt connections, friction fit or press fit connections and/or the like. In some embodiments, the outer diameter of the centering assembly 90 (e.g., taken along the outermost portions of the wings 92) is identical or substantially identical (e.g., within about 0-1%, 1-2%, 2-3%, 3-4%, 4-5%, more than 5%) of the outer diameter of the catheter 12. The centering assembly can comprise one or more suitable materials (e.g., thermoplastics, metals, alloys, combinations thereof, etc.).

**[0124]** With continued reference to FIGS. 9 and 10, the centering assembly 90 can help center the guidewire GW and the various components that are supported along the guidewire GW within the interior of the balloon 14 when the catheter system is in use. As shown, such components include the electrically non-conductive member (e.g., polyimide) 57, the ultrasound transducer 16 and the backing member or post 56 positioned between the non-conductive member and the transducer. As noted above, the electrically non-conductive member or tube 57 can extend partially or entirely through the interior of the balloon (e.g.,

from the distal end of the catheter 12 to the distal tip 18). The electrically non-conductive tube 57, which in some embodiments comprises polyimide and/or another thermoplastic material, can advantageously electrically shield a metal guidewire GW from other components of the system (e.g., the backing member or post 56, transducer 16, etc.). As noted above, by radially centering the transducer 16 within the balloon 14, the centering assembly 90 helps to ensure that the energy profile of the acoustic energy delivered by the transducer 16 during use is generally uniform in the radial direction (e.g., circumferentially around the transducer and balloon). In some embodiments, this provides more even and consistent heating of tissue (e.g., renal nerves) around the targeted portion of the vessel (e.g., renal artery) into which the catheter system is positioned during a treatment procedure.

**[0125]** As illustrated in FIGS. 9, 10 and 13, the centering assembly 90 enables the guidewire GW to transition from an radially non-centered position of the catheter 12 (e.g., from a peripheral or non-centered lumen 13d of the catheter 12) to a radially centered orientation through the assembly 90 and components distal to the assembly (e.g., a majority of the balloon 14, the distal tip 18, etc.). The guidewire GW can transition from a peripheral lumen 13d of the catheter 12 to the central opening 96 of the centering assembly 90 within a transition region along the proximal portion 15 of the balloon 14. In some embodiments, such a proximal portion 15 of the balloon comprises a generally cylindrical shape that is not configured to expand when fluid is circulated through the balloon 14. In other words, such a proximal portion 15 will maintain its outer shape during use (e.g., as cooling fluid is circulated within the balloon).

**[0126]** In some embodiments, the entire balloon 14 (e.g., including the proximal portion 15, the main radially expandable portion, etc.) is extruded from a single material or member. In order to maintain the proximal portion 15 of the balloon from expanding during use, the proximal portion can comprise a greater thickness of the extruded material or portion relative to the distal portions of the balloon 14. For example, in some embodiments, the thickness of the proximal portion 15 of the balloon is greater than the thickness of more distally located portions (e.g., along the main, radially expandable portion of the balloon) by about 0-10%, 10-20%, 20-30%, 30-40%, 40-50%, 50-60%, 60-70%, 70-80%, 80-90%, 90-100%, 100-125%, 125-150%, 150-200%, greater than 200%, percentages between the

foregoing values and/or the like. The distal portion of the balloon 14 can also include a generally cylindrical portion that is configured to maintain its shape during use (e.g., when cooling fluid is circulated through the balloon interior). As depicted in FIGS. 10 and 11, the proximal and distal portions of the balloon can be secured to the catheter 12 and the tip 18, respectively, using one or more attachment methods or devices (e.g., adhesives, pressure or friction fit connections, fasteners, etc.).

[0127] According to some embodiments, in order to transition from a peripheral lumen 13d of the catheter 12 to the central opening 96 of the centering assembly 90, the guidewire GW is angled through a portion of the catheter system (e.g., between the distal end of the catheter 12 and the proximal end of the centering assembly 90). For example, as illustrated in FIG. 10, the guidewire GW can be angled within the proximal, cylindrical portion 15 of the balloon 14 at angle  $\Theta$ , which, in some embodiments, is about 0-40° (e.g., about 0-5°, 5-10°, 10-15°, 15-20°, 20-25°, 25-30°, 30-35°, 35-40°, angles between the foregoing, etc.). However, in other embodiments, the angle  $\Theta$  is greater than about 40° (e.g., about 40-50°, 50-60°, greater than 60°), as desired or required.

[0128] As illustrated in FIG. 14, in addition to the guidewire lumen 13d discussed above, the catheter 12 can comprise one or more other lumens 13a, 13b, 13c. For example, in the depicted embodiment, the catheter 12 includes a lumen 13a for routing one or more electrical conductors (e.g., coaxial cables) 28 to the distal end of the system. As discussed in greater detail herein, such cables or other electrical conductors 28 can electrically couple the inner and outer electrodes of the transducer 16 to a generator. In addition, the catheter can include one or more fluid lumens 13b, 13c that are shaped, sized and otherwise configured to transfer cooling fluid (e.g., water, saline, other liquid or gas, etc.) to and/or from the interior of the balloon 14. For example, in some embodiments, the catheter comprises separate fluid delivery 13b and fluid return 13c lumens that are in fluid communication with the balloon interior.

[0129] According to some embodiments, the catheter 12 does not include any central lumens. In other words, all of the lumens 13a-13d of the catheter can be located away from the radial centerline of the catheter (e.g., along the periphery of the catheter, locations between the radial centerline of the catheter and the periphery, etc.). Such a configuration

can allow the various lumens 13a-13d to be more tightly packed within the cross-sectional area of the catheter. For example, in some embodiments, a certain minimum flowrate of cooling fluid is required or desired through the balloon 14 during use. For instance, the minimum required or desired flowrate for such a cooling fluid can be about 40 ml/min (e.g., about 40-42, 42-45, 45-50, 50-60 ml/min, flowrates between the foregoing, greater than 50 ml/min, etc.).

**[0130]** Accordingly, in order to transfer cooling fluid to and/or from the interior balloon at a desired or required flowrate while preventing over-pressurization of the balloon, the fluid lumens 13b, 13c of the catheter 12 can comprise a minimum cross sectional size. Such a design can also help ensure that the delivery of fluid through the catheter lumens occurs at acceptable flowrates, velocities, headlosses and/or other fluid dynamic considerations. In some embodiments, for example, the cross-sectional area of each of the fluid lumens 13b, 13c of the catheter 12 is about 0.00005 to 0.00012 square inches (e.g., 0.00005 to 0.00006, 0.00006 to 0.00007, 0.00007 to 0.00008, 0.00008 to 0.00009, 0.00009 to 0.00010, 0.00010 to 0.00011, 0.00011 to 0.00012 square inches, areas between the foregoing, etc.), less than about 0.00005 square inches, more than about 0.00012 square inches for a 6 French catheter, and about 0.00003 to 0.00010 square inches (e.g., 0.00003 to 0.00004, 0.00004 to 0.00005, 0.00005 to 0.00006, 0.00006 to 0.00007, 0.00007 to 0.00008, 0.00008 to 0.00009, 0.00009 to 0.00010 square inches, areas between the foregoing, etc.), less than about 0.00003 square inches, more than about 0.00010 square inches for a 5 French catheter. Thus, by eliminating a central lumen (e.g., a central guidewire lumen) within the catheter 12, the size of one or more of the other lumens (e.g., the fluid lumens 13b, 13c) can be advantageously increased. This can be particularly helpful smaller diameter catheters, such as, for example, 5 French catheters, which may be advanced through the subject's anatomy using radial access.

**[0131]** One embodiment of a cross-sectional area of a catheter 12 is illustrated in FIG. 16. As shown, the catheter can include four lumens 13a-13d, each of which is oriented away from the radial centerline CL of the catheter. The lumens 13a, 13d can comprise a circular or oval shape. However, the shape of one or more of the lumens can be non-circular, as desired or required. For example, in the depicted embodiment, the catheter comprises two

fluid lumens 13b, 13c having a generally irregular shape (e.g., having one or more curved portions that generally surround and fit around the adjacent circular lumens 13a, 13d). Thus, as shown, the cross-sectional size of each of the fluid lumens 13b, 13c can be advantageously increased (e.g., relative to a circular or oval lumen). In addition, such an orientation allows for the various lumens 13a-13d of a catheter to be more tightly packed. For example, in some embodiments, the combined cross-sectional shape of the lumens 13a-13d is approximately 60-90% (e.g., 60-65%, 65-70%, 70-75%, 75-80%, 80-85%, 85-90%, percentages between the foregoing values, etc.) of the entire cross-sectional area of the catheter. In some embodiments, none of the lumens 13a-13d comprises a circular or oval shape. For example, all of the lumens can include a generally irregular shape, such as the shape of the fluid lumens 13b, 13c of FIG. 16.

[0132] As noted above, such a strategic orientation of the lumens (e.g., in which the amount of non-lumen space is reduced or minimized) can permit the use of smaller catheter sizes for a particular treatment procedure. For example, the ability to include larger, non-circular fluid lumens 13b, 13c can allow for the necessary delivery of cooling fluid to and from the balloon interior by using a smaller catheter size (e.g., 5 French, 6 French, etc.). This can be particularly helpful when advancing the catheter through smaller diameter portions of the subject's vasculature (e.g., via radial access).

[0133] According to some embodiments, the cross-sectional orientation of the various lumens 13a-13d can be maintained throughout the entire length of the catheter. For example, the lumens illustrated in FIG. 16 can extend from a proximal to a distal end of the catheter 12. Such a catheter can include a traditional over-the-wire design in which the entire length of the catheter is routed over a guidewire GW during the advancement of the catheter to the target anatomical site.

[0134] However, in other embodiments, as noted herein, the catheter can include a rapid-exchange design in which the catheter comprises a guidewire lumen 13d only partially along its length. For example, the guidewire lumen 13d can extend only through the distal-most portion of the catheter (e.g., along a length immediately proximal to the balloon). In some embodiments, the catheter comprises an interior guidewire lumen 13d only along the last 5 to 30 cm (e.g., 5-6, 6-8, 8-10, 10-12, 12-14, 14-16, 16-18, 18-20, 20-25, 25-30 cm,

lengths between the foregoing, etc.) of the catheter's distal end. In some embodiments, the catheter comprises a guidewire lumen 13d only along 0-30% (e.g., 0-5%, 5-10%, 10-15%, 15-20%, 20-25%, 25-30%, percentages between the foregoing, etc.) of its length (e.g., the distal end of catheter).

**[0135]** According to some embodiments, for catheters 12 that include such a rapid-exchange design, a proximal portion of the catheter does not include an interior guidewire lumen. A cross-sectional area along a proximal end of one embodiment of such a catheter 12 is illustrated in FIG. 17. As shown, the catheter 12 can include a groove, slot, recess or other opening 113 that is sized, shaped and otherwise configured to accommodate an adjacent guidewire GW. Such a groove or recess 113 can advantageously permit the guidewire to be positioned therein (e.g., at least through the length of the proximal length of the catheter that does not include an interior guidewire lumen). One embodiment of a catheter 12 comprising such a groove or recess 113 is illustrated in the partial perspective view of FIG. 18. As shown in FIG. 18 and noted above, such a groove or recess 113 can extend from the proximal end of the catheter 12 to a location proximal to the distal end of the catheter 12 and the balloon 14.

**[0136]** Such a configuration comprising a groove or recess 113 can facilitate positioning the catheter 12 and the guidewire through a smaller diameter sheath or guiding catheter during a treatment procedure. As noted herein, the use of smaller catheters, sheaths and other components can be helpful when using a radial access approach. For example, in such a rapid exchange catheter design, the guidewire can be nestled or otherwise positioned within the groove or recess 113 of the catheter along the entire length or substantially the entire length of the catheter. In some embodiments, for the entire length of the catheter 12, the guidewire is configured to be located either within the groove or recess 113 (e.g., along the proximal end of the catheter) or within the guidewire lumen of the catheter 12 (e.g., along the most distal end of the catheter). Thus, in such embodiments, the guidewire does not need to extend along the outer circular area formed by the catheter. This can advantageously permit the catheter and guidewire to be positioned within a smaller delivery catheter or sheath. As noted herein, such a smaller delivery catheter or sheath can permit the device to be delivered to a target vessel of the subject through smaller vasculature or access points of



the subject (e.g., radial access). Relatedly, such a configuration can allow the system to include a larger main catheter, which can provide the cross-sectional areas of one or more of the internal lumens of the main catheter to be maximized or increased. Accordingly, the area of the fluid lumens (e.g., the fluid delivery lumen, the fluid return lumen, etc.) can be increased (e.g., relative to a rapid exchange catheter that does not include a groove or recess 113).

[0137] In some embodiments, for example, such a design can facilitate the passage of cooling fluid through the catheter (e.g., reduced head loss), thereby improving circulation of cooling fluid through a balloon located along the distal end of the main catheter. These features can be especially advantageous when the guidewire lumen along the distal end of the catheter (e.g., distal to the groove or recess 113) is eccentrically-located in the catheter. For example, in such embodiments, the orientation of the eccentrically-located guidewire lumen further helps to increase the area of one or more other lumens of the catheter (e.g., fluid lumens).

[0138] Further, in some embodiments for example, the inclusion of a groove or recess 113 along the outside of the catheter can allow the ablation and/or other intravascular procedure to be performed using a shorter guidewire. This may, in certain circumstances, allow a procedure to be completed with fewer personnel (e.g., the surgeon or other physician may be able to handle the procedure by himself or herself and/or with fewer assistants).

[0139] To assist in the description of the disclosed embodiments, words such as upward, upper, bottom, downward, lower, rear, front, vertical, horizontal, upstream, downstream have been used above to describe different embodiments and/or the accompanying figures. It will be appreciated, however, that the different embodiments, whether illustrated or not, can be located and oriented in a variety of desired positions.

[0140] Although several embodiments and examples are disclosed herein, the present application extends beyond the specifically disclosed embodiments to other alternative embodiments and/or uses of the inventions and modifications and equivalents thereof. It is also contemplated that various combinations or subcombinations of the specific features and aspects of the embodiments may be made and still fall within the scope of the inventions. Accordingly, it should be understood that various features and aspects of the

disclosed embodiments can be combine with or substituted for one another in order to form varying modes of the disclosed inventions. Thus, it is intended that the scope of the present inventions herein disclosed should not be limited by the particular disclosed embodiments described above, but should be determined only by a fair reading of the claims that follow.

[0141] While the inventions are susceptible to various modifications, and alternative forms, specific examples thereof have been shown in the drawings and are herein described in detail. It should be understood, however, that the inventions are not to be limited to the particular forms or methods disclosed, but, to the contrary, the inventions are to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the various embodiments described and the appended claims. Any methods disclosed herein need not be performed in the order recited. The methods disclosed herein include certain actions taken by a practitioner; however, they can also include any third-party instruction of those actions, either expressly or by implication. For example, actions such as “advancing a catheter intraluminally” or “activating a transducer” include “instructing advancing a catheter intraluminally” and “instructing activating a transducer.” The ranges disclosed herein also encompass any and all overlap, sub-ranges, and combinations thereof. Language such as “up to,” “at least,” “greater than,” “less than,” “between,” and the like includes the number recited. Numbers preceded by a term such as “about” or “approximately” include the recited numbers. For example, “about 10 mm” includes “10 mm.” Terms or phrases preceded by a term such as “substantially” include the recited term or phrase. For example, “substantially parallel” includes “parallel.”

WHAT IS CLAIMED IS:

1. An intravascular, ultrasound-based ablation system comprising:
  - a catheter comprising at least one fluid lumen;
  - a balloon positioned at a distal end of the catheter, an interior of the balloon being in fluid communication with the at least one fluid lumen of the catheter, wherein the balloon is configured to inflate when fluid is delivered into the interior through the at least one fluid lumen of the catheter;
  - a tip extending distally from a distal end of the balloon;
  - an ultrasound transducer positioned within the balloon, the ultrasound transducer comprising a cylindrical tube with inner and outer surfaces, each of the inner and outer surfaces comprising an electrode, wherein the ultrasound transducer defines an internal space adjacent the inner electrode surface, the internal space being in fluid communication with the interior cavity of the balloon so that, when in use, fluid entering the balloon passes along both the inner and outer surfaces to transfer heat away from the ultrasound transducer; and
  - a backing member extending from the catheter to the tip and connecting the catheter with the tip, the backing member positioned within the internal space of the ultrasound transducer.
2. The system of Claim 1, wherein the catheter further comprises a guidewire lumen.
3. The system of Claim 1, wherein the catheter further comprises at least one cable lumen.
4. The system of Claim 3, further comprising at least one electrical cable positioned within the at least one cable lumen of the catheter, the at least one electrical cable being electrically coupled to the electrodes along the inner and outer surfaces of the ultrasound transducer.
5. The system of Claim 2, wherein the backing member comprises a central opening configured to receive a guidewire, wherein the backing member serves as a fluid barrier between fluid circulated within the balloon interior and the central opening.

6. The system of Claim 5, wherein the central opening of the backing member is generally aligned with the guidewire lumen of the catheter and an internal guidewire passage of the tip to permit the system to be delivered to a desired vascular position over a guidewire.

7. The system of Claim 2, wherein the central opening of the backing member is offset relative to the guidewire lumen of the catheter.

8. The system of Claim 5, wherein the backing member comprises an electrically insulating material along an interior surface of the central opening of the backing member so as to prevent electrical conduction between a guidewire and the backing member.

9. The system of Claim 8, wherein the electrically non-conductive material comprises polyimide.

10. The system of Claim 2, wherein the guidewire lumen extends from a proximal end of the catheter to the balloon.

11. The system of Claim 2, wherein the guidewire lumen extends from a location between the proximal and distal ends of the catheter to the distal end of the catheter, such that the catheter comprises a rapid exchange design.

12. The system of Claim 1, wherein the cylindrical tube of the ultrasound transducer comprises a proximal end and a distal end, wherein the proximal end of the cylindrical tube comprises a stepped portion, wherein a portion of the outer diameter formed by the outer surface of the cylindrical tube is smaller than a portion of the outer diameter of the cylindrical tube located distal to the stepped portion, the system further comprising:

at least one electrical cable configured to supply electrical power to the ultrasound transducer, wherein the at least one electrical cable comprises a first conductor and a second conductor;

a stand-off assembly located within an interior and along or near the proximal end of the cylindrical tube of the ultrasound transducer, the stand-off assembly being electrically conductive and in contact with, at least intermittently, the electrode along the inner surface of the cylindrical tube of the ultrasound transducer; wherein the first conductor is connected to an exterior of the cylindrical tube along the stepped portion, and wherein the second conductor is connected to the stand-off assembly so that the second conductor is electrically coupled to the electrode along the inner surface of the cylindrical tube; and

a ring surrounding the stepped portion of the cylindrical tube, the ring being sized and shaped to surround the portion of the outer diameter of the cylindrical tube located distal to the stepped portion, wherein the ring is electrically conductive so that the first connector is electrically coupled to the electrode along the outer surface of the cylindrical tube, and wherein the ring allows for more uniform electrical loading of the ultrasound transducer when the electrical transducer is energized.

13. The system of Claim 12, wherein the ring comprises conductive solder.

14. The system of Claim 12, wherein the ring comprises a conductive machined ring that couples around the stepped portion of the cylindrical tube.

15. The system of Claim 12, wherein the stepped portion extends approximately 5% to 25% of a length of the cylindrical tube.

16. The system of Claim 12, wherein the stepped portion comprises a portion of the cylindrical tube that is removed using grinding or other removal techniques.

17. The system of Claim 12, wherein an impedance of the at least one electrical cable substantially matches an impedance of the ultrasound transducer.

18. The system of Claim 17, wherein the impedance of the electrical cable and the ultrasound transducer is approximately 40 to 60 ohms.

19. The system of Claim 18, wherein the impedance of the electrical cable and the ultrasound transducer is approximately 50 ohms.

20. The system of Claim 4, wherein an impedance of the at least one electrical cable substantially matches an impedance of the ultrasound transducer, thereby providing a

more efficient power transfer from the generator to the ultrasound transducer when the ablation system is in use.

21. The system of Claim 4, wherein the at least one electrical cable comprises a coaxial cable.

22. The system of Claim 20, wherein the backing member comprises at least one stand-off assembly that electrically couples the backing member to the electrode along the inner surface of the cylindrical tube of the ultrasound transducer.

23. The system of Claim 20, wherein the impedance of the electrical cable and the ultrasound transducer is approximately 40 to 60 ohms.

24. The system of Claim 23, wherein the impedance of the electrical cable and the ultrasound transducer is approximately 50 ohms.

25. The system of Claim 20, wherein the first connector of the electrical cable is electrically coupled to the electrode while not physically attached to the outer surface of the ultrasound transducer.

26. The system of Claim 2, wherein the guidewire lumen oriented along an axis that is eccentric relative to a center axis of the catheter, wherein the eccentric orientation of the guidewire lumen within the catheter allows the cross-sectional area of the at least one fluid lumen to be increased.

27. The system of Claim 26, further comprising at least one centering assembly located at or near the distal end of the catheter, wherein the at least one centering assembly comprises a passage that is positioned along the center axis of the catheter, wherein a guidewire is configured to be positioned through the passage of the at least one centering assembly so that the guidewire is generally radially centered along the distal end of the catheter, while the guidewire is configured to eccentrically located within the guidewire lumen of the catheter.

28. The system of Claim 27, wherein the at least one centering assembly is located immediately adjacent the distal end of the catheter.

29. The system of Claim 27, wherein the at least one centering assembly is separated from the distal end of the catheter by a separation distance.

30. The system of Claim 27, wherein the at least one centering assembly is located proximal to the distal end of the catheter.

31. The system of Claim 27, wherein the at least one fluid lumen includes an axis that is eccentric to the central axis of the catheter.

32. The system of Claim 27, wherein the at least one fluid lumen comprises a non-circular shape to increase the cross-sectional area of the at least one fluid lumen.

33. The system of Claim 27, wherein the at least one fluid lumen comprises a fluid delivery lumen and a fluid return lumen.

34. The system of Claim 27, wherein the catheter comprises an over-the-wire design such that the guidewire lumen extends from a proximal end to the distal end of the catheter.

35. The system of Claim 27, wherein the catheter comprises a rapid exchange design such that the guidewire lumen is located only along a distal portion of the catheter.

36. The system of Claim 35, wherein a proximal portion of the catheter that does not include a guidewire lumen comprises a groove along an exterior surface of the catheter, wherein the groove is configured to receive a guidewire therein.

37. The system of Claim 27, wherein the catheter comprises a 5 French or 6 French catheter.

38. The system of Claim 1, further comprising a fluid transfer device configured to selectively deliver a cooling fluid within the balloon when the ultrasound transducer is activated in order to transfer heat away from the ultrasound transducer during use, wherein the fluid transfer device comprises a reservoir for storing a volume of cooling fluid and a movable member configured to move within an interior of the reservoir in order to transfer cooling fluid through the at least one fluid lumen of the catheter to the balloon, wherein the reservoir is sized to store sufficient cooling fluid for an entire ablation procedure.

39. The system of Claim 38, wherein the movable member is coupled to a motor for selectively advancing the movable member relative to the reservoir.

40. The system of Claim 39, wherein the motor comprises a stepper motor.

41. The system of Claim 38, wherein the fluid transfer device comprises a syringe pump.

42. The system of Claim 38, wherein the at least one fluid lumen of the catheter comprises a fluid delivery lumen and a fluid return lumen, wherein cooling fluid is delivered to the balloon from the fluid transfer device via the fluid delivery lumen, and wherein cooling fluid is withdrawn from the balloon via the fluid return lumen.

43. The system of Claim 42, wherein the fluid delivery lumen is in fluid communication with a first fluid transfer device, and wherein the fluid return lumen is in fluid communication with a second fluid transfer device, wherein both the first and the second fluid transfer devices are operated simultaneously to circulate cooling fluid through the balloon during an ablation procedure.

44. The system of Claim 38, wherein the fluid transfer device is configured to deliver cooling fluid through the at least one fluid lumen of the catheter and into the balloon at a flowrate of 30 to 50 ml/min.

45. A method of intraluminally ablating nerve tissue using the ablation system according to any one of the preceding claims.

46. The method of Claim 45, comprising intraluminally advancing the system to a targeted intraluminal location of the subject, and activating the ultrasound transducer.

47. An intravascular, ultrasound-based ablation system comprising:

- a catheter comprising at least one fluid lumen and a guidewire lumen, wherein the guidewire lumen is not positioned along the cross-sectional centerline of the catheter;

- a balloon positioned along a distal end of the catheter, an interior of the balloon being in fluid communication with the at least one fluid lumen of the catheter, wherein the balloon is configured to inflate when fluid is delivered into the interior through the at least one lumen of the catheter;

- an ultrasound transducer positioned within the balloon;

- a distal tip comprising a central passage, wherein the balloon is positioned between the catheter and the distal tip;

- an electrically non-conductive member extending from the guidewire lumen to the central passage of the distal tip, the electrically non-conductive member



positioned through an interior of the ultrasound transducer and configured to receive a guidewire;

a backing member positioned between the electrically non-conductive member and the ultrasound transducer, the backing member being configured to support the ultrasound transducer; and

a centering assembly positioned proximal to the catheter between the distal end of the catheter and the distal tip, the centering assembly comprising a center opening configured to receive the electrically non-conductive member, wherein the radial orientation of the center opening is offset relative to the radial orientation of the guidewire lumen of the catheter, wherein the center opening of the centering assembly is aligned with the cross-sectional centerline of the catheter and the balloon so as to radially center the ultrasound transducer when a guidewire is positioned through the electrically non-conductive member.

48. The system of Claim 47, wherein the electrically non-conductive member comprises polyimide.

49. The system of Claim 47 or 48, wherein the centering assembly comprises a plurality of wings extending radially outwardly from the center opening, the wings configured to engage an inner surface of the balloon.

50. The system of Claim 49, wherein the centering assembly comprises at least three wings.

51. A system according to any one of Claims 47 to 50, wherein the at least one fluid lumen comprises a fluid delivery lumen and a fluid return lumen.

52. A system according to any one of Claims 47 to 51, wherein the catheter further comprises an electrical conductor lumen, wherein each of the electrical conductor lumen and the at least one fluid lumen is not positioned along the cross-sectional centerline of the catheter.

53. A system according to any one of Claims 47 to 52, wherein the guidewire lumen is positioned along an entire length of the catheter.

54. A system according to any one of Claims 47 to 53, wherein the guidewire lumen is positioned only along a distal portion of the catheter, so that the catheter comprises a rapid exchange type catheter.

55. The system of Claim 54, wherein the catheter comprises a groove along at least a proximal length of the catheter that does not comprise a guidewire lumen, the groove being configured to at least partially receive an adjacent guidewire.

56. A system according to any one of Claims 47 to 55, wherein the catheter comprises a 5 French or 6 French catheter.

57. A system according to any one of Claims 47 to 56, wherein the system is configured to be advanced into a subject via femoral or radial access.

58. A system according to any one of Claims 47 to 57, wherein the at least one fluid lumen comprises a non-circular shape.

59. An intravascular, ultrasound-based ablation system comprising:

- a catheter comprising at least one fluid lumen, a guidewire lumen and an electrical cable lumen, wherein each of the at least one fluid lumen, the guidewire lumen and the electrical cable lumen is not positioned along the cross-sectional centerline of the catheter;

- a balloon positioned along a distal end of the catheter, an interior of the balloon being in fluid communication with the at least one fluid lumen of the catheter, wherein the balloon is configured to inflate when fluid is delivered into the interior through the at least one lumen of the catheter;

- a cylindrical ultrasound transducer positioned within the balloon;

- a distal tip, wherein the balloon is positioned between the catheter and the distal tip;

- an electrically non-conductive member extending distally from the guidewire lumen through an interior of the ultrasound transducer, the electrically non-conductive member being configured to receive a guidewire;

a centering assembly positioned proximal to the catheter between the distal end of the catheter and the distal tip, the centering assembly comprising a center opening configured to receive the electrically non-conductive member, wherein the center opening of the centering assembly is aligned with the cross-sectional centerline of the catheter and the balloon so as to radially center the ultrasound transducer when a guidewire is positioned through the electrically non-conductive member.

60. The system of Claim 59, wherein the electrically non-conductive member comprises polyimide.

61. The system of Claim 59 or 60, wherein the centering assembly comprises a plurality of wings extending radially outwardly from the center opening, the wings configured to engage an inner surface of the balloon.

62. A system according to any one of Claims 59 to 61, wherein the guidewire lumen is positioned along an entire length of the catheter.

63. A system according to any one of Claims 59 to 62, wherein the guidewire lumen is positioned only along a distal portion of the catheter, so that the catheter comprises a rapid exchange type catheter.

64. The system of Claim 63, wherein the catheter comprises an exterior groove along at least a proximal length of the catheter, the groove being configured to at least partially receive an adjacent guidewire.

65. An intravascular, ultrasound-based ablation system comprising:

a catheter comprising a guidewire lumen, at least one cable lumen and at least one fluid lumen;

a balloon positioned at a distal end of the catheter, an interior of the balloon being in fluid communication with the at least one fluid lumen of the catheter, wherein the balloon is configured to inflate when fluid is delivered into the interior through the at least one fluid lumen of the catheter;

a tip extending distally from a distal end of the balloon, the tip comprising an internal guidewire passage;

an ultrasound transducer positioned within the balloon, the ultrasound transducer comprising a cylindrical tube with inner and outer surfaces, each of the inner and outer surfaces comprising an electrode, wherein the ultrasound transducer defines an internal space adjacent the inner electrode surface, the internal space being in fluid communication with the interior cavity of the balloon so that, when in use, fluid entering the balloon passes along both the inner and outer surfaces to transfer heat away from the ultrasound transducer;

at least one electrical cable positioned within the at least one cable lumen of the catheter, the at least one electrical cable being electrically coupled to the electrodes along the inner and outer surfaces of the ultrasound transducer; and

a backing member extending from the catheter to the tip and connecting the catheter with the tip, the backing member positioned within the internal space of the ultrasound transducer, wherein the backing member comprises a central opening that is generally aligned with the guidewire lumen of the catheter and the internal guidewire passage of the tip to permit the system to be delivered to a desired vascular position over a guidewire, wherein the backing member serves as a fluid barrier between fluid circulated within the balloon interior and the central opening.

66. The system of Claim 65, wherein the backing member comprises an electrically insulating material along an interior surface of the central opening of the backing member so as to prevent electrical conduction between a guidewire and the backing member.

67. The system of Claim 66, wherein the electrically non-conductive material comprises polyimide.

68. A system according to any one of Claims 65 to 67, wherein the guidewire lumen extends from a proximal end of the catheter to the balloon.

69. A system according to any one of Claims 65 to 68, wherein the guidewire lumen extends from a location between the proximal and distal ends of the catheter to the distal end of the catheter, such that the catheter comprises a rapid exchange design.

70. An intravascular, ultrasound-based ablation system comprising:
- a catheter comprising at least one cable lumen and at least one fluid lumen;
  - a balloon positioned at a distal end of the catheter, an interior of the balloon being in fluid communication with the at least one fluid lumen of the catheter;
  - an ultrasound transducer positioned within the balloon, the ultrasound transducer comprising a cylindrical tube having a proximal end and a distal end and inner and outer surfaces, wherein each of the inner and outer surfaces comprises an electrode; the proximal end of the cylindrical tube comprising a stepped portion, wherein a portion of the outer diameter formed by the outer surface of the cylindrical tube is smaller than a portion of the outer diameter of the cylindrical tube located distal to the stepped portion;
  - at least one electrical cable positioned within the at least one cable lumen of the catheter, the at least one electrical cable being configured to supply electrical power to the ultrasound transducer, wherein the at least one electrical cable comprises a first conductor and a second conductor;
  - a stand-off assembly located within an interior and along or near the proximal end of the cylindrical tube of the ultrasound transducer, the stand-off assembly being electrically conductive and in contact with, at least intermittently, the electrode along the inner surface of the cylindrical tube of the ultrasound transducer; wherein the first conductor is connected to an exterior of the cylindrical tube along the stepped portion, and wherein the second conductor is connected to the stand-off assembly so that the second conductor is electrically coupled to the electrode along the inner surface of the cylindrical tube; and
  - a ring surrounding the stepped portion of the cylindrical tube, the ring being sized and shaped to surround the portion of the outer diameter of the cylindrical tube located distal to the stepped portion, wherein the ring is electrically conductive so that the first connector is electrically coupled to the electrode along the outer surface of the cylindrical tube, and wherein the ring allows for more uniform electrical loading of the ultrasound transducer when the electrical transducer is energized.
71. The system of Claim 70, wherein the ring comprises conductive solder.

72. The system of Claim 70 or 71, wherein the ring comprises a conductive machined ring that couples around the stepped portion of the cylindrical tube.

73. A system according to any one of Claims 70 to 72, wherein the stepped portion extends approximately 5% to 25% of a length of the cylindrical tube.

74. A system according to any one of Claims 70 to 72, wherein the stepped portion comprises a portion of the cylindrical tube that is removed using grinding or other removal techniques.

75. A system according to any one of Claims 70 to 74, wherein an impedance of the at least one electrical cable substantially matches an impedance of the ultrasound transducer.

76. The system of Claim 75, wherein the impedance of the electrical cable and the ultrasound transducer is approximately 40 to 60 ohms.

77. The system of Claim 76, wherein the impedance of the electrical cable and the ultrasound transducer is approximately 50 ohms.

78. An intravascular, ultrasound-based ablation system comprising:

- a catheter comprising a cable lumen extending from a proximal end to a distal end of the catheter;

- an ultrasound transducer positioned at or near a distal end of the catheter, the ultrasound transducer comprising a cylindrical tube with inner and outer surfaces, each of the inner and outer surface comprising an electrode;

- a backing member extending from the distal end of the catheter and positioned within an interior of the ultrasound transducer, the backing member configured to support the ultrasound transducer, wherein the backing member is electrically coupled to the electrode along the inner surface of the cylindrical tube of the ultrasound transducer;

an electrical cable positioned within the cable lumen of the catheter and extending from the proximal end to the distal end of the catheter, wherein a proximal end of the electrical cable is coupled to a generator configured to selectively provide electrical power to the ultrasound transducer through the electrical cable, the electrical cable comprising a first electrical connector and a second electrical connector, wherein the first connector is electrically coupled to the electrode along the outer surface of the ultrasound transducer, and wherein the second connector is electrically coupled to the backing member and the electrode along the inner surface of the ultrasound transducer;

wherein an impedance of the electrical cable is substantially equal to an impedance of the ultrasound transducer, thereby providing a more efficient power transfer from the generator to the ultrasound transducer when the ablation system is in use.

79. The system of Claim 78, wherein the electrical cable comprises a coaxial cable.

80. The system of Claim 78 or 79, wherein the backing member comprises at least one stand-off assembly that electrically couples the backing member to the electrode along the inner surface of the cylindrical tube of the ultrasound transducer.

81. A system according to any one of Claims 78 to 80, wherein the impedance of the electrical cable and the ultrasound transducer is approximately 40 to 60 ohms.

82. The system of Claim 81, wherein the impedance of the electrical cable and the ultrasound transducer is approximately 50 ohms.

83. A system according to any one of Claims 78 to 82, wherein the first connector of the electrical cable is electrically coupled to the electrode while not physically attached to the outer surface of the ultrasound transducer.

84. An intravascular, ultrasound-based ablation system comprising:

a catheter comprising at least one fluid lumen;

a balloon positioned at a distal end of the catheter, an interior of the balloon being in fluid communication with the at least one fluid lumen of the catheter, wherein the balloon is configured to inflate when fluid is delivered into the interior through the at least one lumen of the catheter;

an ultrasound transducer positioned within the balloon, the ultrasound transducer comprising a cylindrical tube with inner and outer surfaces, each of the inner and outer surface comprising an electrode, wherein the ultrasound transducer defines an internal space adjacent the inner electrode surface, the internal space being in fluid communication with the interior cavity of the balloon so that, when in use, fluid entering the balloon passes along both the inner and outer surfaces to cool the ultrasound transducer; and

a fluid transfer device configured to selectively deliver a cooling fluid within the balloon when the ultrasound transducer is activated in order to transfer heat away from the ultrasound transducer during use, wherein the fluid transfer device comprises a reservoir for storing a volume of cooling fluid and a movable member configured to move within an interior of the reservoir in order to transfer cooling fluid through the at least one fluid lumen of the catheter to the balloon, wherein the reservoir is sized to store sufficient cooling fluid for an entire ablation procedure.

85. The system of Claim 84, wherein the movable member is coupled to a motor for selectively advancing the movable member relative to the reservoir.

86. The system of Claim 85, wherein the motor comprises a stepper motor.

87. A system according to any one of Claims 84 to 86, wherein the fluid transfer device comprises a syringe pump.

88. A system according to any one of Claims 84 to 87, wherein the at least one fluid lumen of the catheter comprises a fluid delivery lumen and a fluid return lumen, wherein cooling fluid is delivered to the balloon from the fluid transfer device via the fluid delivery lumen, and wherein cooling fluid is withdrawn from the balloon via the fluid return lumen.



89. The system of Claim 88, wherein the fluid transfer lumen is in fluid communication with a first fluid transfer device, and wherein the fluid return lumen is in fluid communication with a second fluid transfer device, wherein both the first and the second fluid transfer devices are operated simultaneously to circulate cooling fluid through the balloon during an ablation procedure.

90. A system according to any one of Claims 84 to 89, wherein the fluid transfer device is configured to deliver cooling fluid through the at least one fluid lumen of the catheter and into the balloon at a flowrate of 30-50 ml/min.

91. A method of intraluminally ablating nerve tissue using an ultrasound-based ablation system, the method comprising:

advancing a catheter of the ablation system intraluminally to a target anatomical location of a subject, wherein the system comprises a balloon positioned at a distal end of the catheter, an interior of the balloon being in fluid communication with at least one fluid delivery lumen and at least one fluid return lumen of the catheter, wherein an ultrasound transducer is positioned within the interior of the balloon;

circulating cooling fluid through the interior of the balloon by transferring cooling fluid from a fluid transfer device through the at least one fluid lumen of the catheter and transferring cooling fluid away from the interior of the balloon through the at least one fluid return lumen; and

activating the ultrasound transducer positioned within the balloon to ablate nerve tissue adjacent to the target anatomical location of the subject, wherein cooling fluid is circulated adjacent the ultrasound transducer within the balloon when the ultrasound transducer is activated;

wherein the fluid transfer device comprises a reservoir for storing a volume of cooling fluid and a movable member configured to move within an interior of the reservoir in order to transfer cooling fluid through the at least one fluid lumen of the catheter to the balloon, wherein the reservoir is sized to store sufficient cooling fluid for an entire ablation procedure.

92. The method of Claim 91, wherein the movable member is coupled to a motor for selectively advancing the movable member relative to the reservoir.

93. The method of Claim 92, wherein the motor comprises a stepper motor.

94. A system according to any one of Claims 92 to 93, wherein the fluid transfer device comprises a syringe pump.

95. A system according to any one of Claims 92 to 94, wherein cooling fluid is circulated through the balloon at a flowrate of 30 to 50 ml/min.

96. A coupling configured for use in an outlet of a fluid container, the coupling comprising:

a hub configured to abut against the outlet of the coupling, the hub being configured to prevent over-insertion of the coupling into the fluid container, a proximal end of the hub comprising a fitting configured for attachment to a fluid conduit;


a spike portion extending distally from the hub, wherein a length of the spike is 0.5 inches to 3 inches;


wherein the coupling comprising at least two fluid lumens that extend throughout an entire length of the coupling from the proximal end of the hub to a distal end of the spike, the at least two lumens placing an interior of the fluid container in fluid communication with at least one fluid conduit secured to the hub; and



wherein the coupling permits at two different fluid sources to be placed in fluid communication with an interior of a fluid container comprising only a single outlet.


97. The coupling of Claim 96, wherein the spike includes a taper along at least a portion of its length, so that a cross-sectional dimension of the spike is smaller along the distal end of the spike than a cross-sectional dimension of the spike along a proximal end of the spike.

98. The coupling of Claim 96 or 97, wherein the spike is configured for placement into an IV bag comprising only a single outlet or port.












FIG. 6a




FIG. 6b






FIG. 6c










FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18

# INTERNATIONAL SEARCH REPORT

International application No.

PCT/US14/22804

## A. CLASSIFICATION OF SUBJECT MATTER

IPC(8) - A61N 7/02 (2014.01)

USPC - 600/470

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC(8) - A61B 8/12, 17/00, 17/22, 17/32, 18/00, 18/04, 18/24, 19/00; A61M 25/00; A61N 7/00, 7/02 (2014.01)

USPC - 600/439, 459, 466, 467, 470; 601/2; 606/27

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

MicroPatent (US-G, US-A, EP-A, EP-B, WO, JP-bib, DE-C,B, DE-A, DE-T, DE-U, GB-A, FR-A); Google Scholar; ProQuest Dialog; Medline/PubMed: ablate, balloon, catheter, connect, dental, dermatology, detach, direct, electromagnetic, energy, exchange, fluid, handheld, handpiece, heat, intravascular, laser, microprocessor, rapid, screw, target, temperature, transfer, ultrasound

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5324255 A (PASSAFARO, JD, et al.) June 28, 1994; figures 1, 4; column 2, lines 38-41; column 7, lines 11-23, 47-50; column 9, lines 14-20 column 15, lines 58-62	1-25, 38-44, 45/1-25, 45/38-44, 46/45/1-25, 46/45/38-44, 91-93, 94/92, 94/93
Y	US 2002/0065512 A1 (FJIELD, T, et al.) May 30, 2002; figures 1-3, 11, 13, 19-22; paragraph [0045], [0048], [0059], [0062], [0075], [0080]-[0083], [0099], [0104]	1-25, 38-44, 45/1-25, 45/38-44, 46/45/1-25, 46/45/38-44, 91-93, 94/92, 94/93
Y	WO 2011/139589 A2 (LEUNG, MS, et al.) November 10, 2011; figures 10, 11, 14, 39, 40; page 136, 147; paragraphs [00224], [00243], [00285], [00286], [00484], [00486]	7, 16, 45/1-25, 45/38-44, 46/45/1-25, 46/45/38-44, 91, 92, 93, 94/92, 94/93
Y	US2004/0044286 A1 (HOSSACK, NH, et al.) March 04, 2004; figure 2; paragraph [0055]	8, 9, 45/8, 45/9, 46/45/8, 46/45/9
Y	US 5327885 A (GRIFFITH, JM) July 12, 1994; column 8, lines 7-17	11, 45/11, 46/45/11
Y	US 2010/0168737 A1 (GRUNEWALD, DE) July 01, 2010; figure 7; paragraph [0054]	13, 45/13, 46/45/13
Y	US 2012/0078278 A1 (BALES, TO, Jr, et al.) March 29, 2012; paragraph [0213]	14, 45/14, 46/45/14

☒ Further documents are listed in the continuation of Box C.



\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

08 June 2014 (08.06.2014)

Date of mailing of the international search report

09 JUL 2014

Name and mailing address of the ISA/US

Mail Stop PCT, Attn: ISA/US, Commissioner for Patents  
P.O. Box 1450, Alexandria, Virginia 22313-1450

Facsimile No. 571-273-3201

Authorized officer:

Shane Thomas

PCT Helpdesk: 571-272-4300

PCT OSP: 571-272-7774



## INTERNATIONAL SEARCH REPORT

International application No.

PCT/US14/22804

## C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 4841977 A (GRIFFITH, JM, et al.) June 27, 1989; figure 8; column 9, lines 12-14; column 18, lines 66-68; column 19, lines 1-5	17-20, 22-25, 45/17-20, 45/22-25, 46/45/17-20, 46/45/22-25, 78-79
Y	US 7678104 B2 (KEIDAR, Y) March 16, 2010; figures 4-6; column 5, lines 6-12	25, 45/25, 46/45/25
Y	US 2012/0004656 A1 (JACKSON, J, et al.) January 05, 2012; paragraph [0050]	39-41, 45/39-41, 46/45/39-41, 85, 86, 87/84-86, 92-93, 94/92-93
Y	US 5713849 A (BOSMA, G, et al.) February 03, 1998; figures 1, 2; column 2, lines 25-47	96, 97, 98/96, 98/67
Y	US 2011/0004184 A1 (PROKSCH, K, et al.) January 06, 2011; figure 2; paragraph [0030], [0032]	96, 97, 98/96, 98/67
Y	US 2009/0124964 A1 (LEACH, JS, et al.) May 14, 2009; paragraph [0105]	96, 97, 98/96, 98/67
A	US 5769812 A (STEVENS, JH, et al.) June 23, 1998; figures 39, 40; column 45, lines 47-67; column 46, lines 1-6	26, 27-37, 45/26-37, 46/45/26-37