




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : F02B 63/04, 37/00, 37/10	A1	(11) International Publication Number: WO 98/45589 (43) International Publication Date: 15 October 1998 (15.10.98)
(21) International Application Number: PCT/US98/04410 (22) International Filing Date: 10 March 1998 (10.03.98) (30) Priority Data: 08/833,555 7 April 1997 (07.04.97) US (71) Applicant: SIEMENS ELECTROMECHANICAL COMPONENTS, INC. [US/US]; 200 South Richland Creek Drive, Princeton, IN 47671 (US). (72) Inventor: McGIBBON, Brian, John; 4366 McNay Court, West Bloomfield, MI 48323 (US). (74) Agents: PASCHBURG, Donald, B. et al.; Siemens Corporation, Intellectual Property Dept., 186 Wood Avenue South, Iselin, NJ 08830 (US).		(81) Designated States: CN, JP, KR, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>

(54) Title: EXHAUST-DRIVEN TURBINE-POWERED ALTERNATOR**(57) Abstract**

The exhaust gas from an engine can be used to generate electrical power for a vehicle. On demand, the exhaust gas can power a turbine which in turn will drive an alternator to generate electricity for the vehicle's loads.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

EXHAUST-DRIVEN TURBINE-POWERED ALTERNATOR**Background of the Invention**

In conventional automobiles and trucks, accessories
5 are driven by a series of belts connected to the flywheel
of the engine. Such accessories include the alternator,
the water pump, the air conditioning compressor, the power
steering pump, and the secondary air pump. These loads
present a significant drain on the engine. An alternative
10 means of powering these devices would decrease the load on
the engine and improve its performance.

Brief Description of Drawings

The invention will be more fully understood and
15 further advantages will become apparent when reference is
made to the following detailed description of the invention
and the accompanying drawings in which:

Figure 1 is a schematic diagram of an exhaust gas-
driven electrical vehicle power system; and

20 Figures 2-4 are schematic diagrams of alternative
exhaust gas-driven electrical vehicle power systems.

Description of the Invention

The exhaust gas from a vehicle's engine can be used to
25 provide electrical power to a load. The exhaust gas drives
one or more turbines positioned in the exhaust line which
in turn drives an alternator. A controlled bypass gate and
passage flanking the turbine can selectively pass a desired
portion of the exhaust gas through the turbine while the
30 balance passes around the turbine.

An automotive exhaust system having an exhaust gas-
powered electrical system is shown in Figure 1. The system
is powered by the exhaust gas which leaves the engine 10
through an exhaust manifold 20. In this figure, the
35 exhaust system is of the single-pipe exhaust variety, but
it could also be a dual pipe system or some other
configuration. The engine 10 can be an internal combustion

device or some other engine that produces an exhaust gas that will drive a turbine.

5 The manifold 20 is connected to a bypass gate valve 30 that can channel the exhaust gas from the manifold 20 through a turbine input manifold 42 to a turbine 40 and a turbine bypass 50. It should be understood that anywhere from zero to 100% of the exhaust gas can be directed by the bypass gate valve through the turbine 40. Powered by the exhaust gas, the turbine 40 drives an alternator 60 and the
10 exhaust gas exits the turbine 40 through a turbine exhaust 70. The turbine exhaust 70 and the exhaust bypass 50 are both connected to an exhaust pipe 80 leading perhaps to a muffler (not shown). The turbine 40 can be sized to maximize its output over the desired operating range of the
15 engine.

The bypass gate valve 30 could be controlled by a bypass controller 32 responsive to the speed of the alternator 60 and perhaps the load conditions. The speed can be measured as a function of the alternator shaft speed
20 or the alternator output voltage, as will readily occur to those skilled in the art. Further, if the turbine speed is too high to properly run the alternator 60, a gear reduction unit 44 could be inserted between the turbine 40 and the alternator 60.

25 In most applications, the desired output would be direct current. Therefore, a rectifier 62 would rectify the output of the alternator 60. The output of the rectifier 62 in turn could provide power to a variety of loads commonly found in an automobile such as a water pump, radiator fan, air conditioner compressor, and a power
30 steering pump. Instead of a conventional belt drive off the crankshaft, each of these devices could be driven by an electric motor receiving power from the alternator 60.

If there is sufficient power output from the
35 alternator 60, electric heaters could be provided for the passenger compartment in lieu of water-based heat exchangers commonly employed. Electric heaters would

reduce the size of the heater system and provide relatively instantaneous heat, eliminating the wait for the engine to warm up. Such heaters could be placed in more than one location to provide zone control and uniform heating.

5 A variation of the system of Figure 1 is illustrated in Figure 2. This alternative system employs two turbines, each handling a different speed range. An engine 100 produces exhaust gas that exits through an exhaust manifold 120 and enters a three-way bypass gate valve 130. The
10 bypass gate valve 130 directs the exhaust gas to a first turbine 140, a second turbine 150, or a turbine bypass 160.

The first turbine 140 has a turbine input manifold 142, a turbine shaft 144, and a turbine exhaust 146; similarly, the second turbine 150 has a turbine input
15 manifold 152, a turbine shaft 154, and a turbine exhaust 156. The two turbine shafts 144 and 154 drive an alternator 170. Finally, the turbine bypass 160 and the two turbine exhausts 146 and 156 are all connected to an exhaust pipe 180. A rectifier is not shown but could
20 readily be used with this arrangement.

Depending the engine speed and the load, the bypass gate valve 130 can be set to direct the exhaust gas to one turbine or the other, as appropriate. A bypass gate valve control 190, responsive to the alternator speed and perhaps
25 the load conditions can be provided to control bypass gate valve 130.

If desired, multiple turbines, each sized to a different exhaust gas flow and speed, could be employed to provide drive throughout the range of engine speeds.
30 Alternatively, the turbines could be identical in size and the bypass gate valve 130 could selectively channel exhaust gas to one or more turbines to achieve the desired output.

In some configurations, the exhaust gas flow at low engine speeds (e.g., at start up) may not provide
35 sufficient power to the turbine to turn the alternator (or alternators). As illustrated in Figure 3, the engine 300 powers a mechanical drive, such as a belt-driven magnetic

clutch 320 connected to the alternator 330, which also has a turbine drive 340. The engine 300 has an exhaust manifold 302 connected to a bypass gate valve 310 that can channel the exhaust gas from the manifold 302 to the turbine drive 340. When the exhaust gas flow is sufficient, the magnetic clutch 320 will disengage, and a bypass control 312 will direct the bypass gate 310 to direct the exhaust gas through the turbine drive 340 to turn the shaft of the alternator 330.

The arrangement of Figure 1 can be modified for use in a hybrid vehicle. Such a vehicle might be alternately powered by a relatively small internal combustion engine and an electric motor running on batteries. If the engine were programmed to run at a single speed (or within a narrow speed range), the bypass gate valve 30 and the turbine bypass 50 of Figure 1 could be eliminated, as shown in Figure 4. The turbine 40 could be optimized for the gas flow at the single speed to develop maximum torque. The resultant output of the rectifier 62 would be supplied to the batteries 400.

While there has been described what is believed to be the preferred embodiment of the invention, those skilled in the art will recognize that other and further modifications may be made thereto without departing from the spirit of the invention, and it is intended to claim all such embodiments that fall within the true scope of the invention.

What is claimed is:

- 1 1. An apparatus for generating electricity for an
2 electrical load, the apparatus being powered by exhaust gas
3 passing out of an exhaust line of an engine, comprising:
4 at least one turbine positioned in the exhaust line
5 and powered by the exhaust gas, the turbine having an
6 output shaft;
7 an alternator for generating alternating current
8 electricity mechanically linked to the output shaft of the
9 turbine;
10 a bypass gate and passage flanking the turbine, for
11 selectively, variably passing at least a portion of the
12 exhaust gas around the turbine; and
13 a control module, responsive to the electrical load
14 and the pressure of the exhaust gas, for controlling the
15 bypass gate.
- 1 2. An apparatus as set forth in claim 1, further
2 comprising a plurality of turbines positioned in the
3 exhaust line and individually and selectively powered by
4 the exhaust gas.
- 1 3. An apparatus as set forth in claim 1, further
2 comprising selectively-enabled means directly powered by
3 the engine for mechanically driving the alternator.
- 1 4. A vehicular electric generating system for
2 providing electrical power to a load, for a vehicle having
3 an internal combustion engine that produces exhaust gas
4 that passes out through an exhaust line, comprising:
5 at least one turbine positioned in the exhaust line
6 and powered by the exhaust gas, the turbine having an
7 output shaft;
8 an alternator for generating alternating current
9 electricity mechanically linked to the output shaft of the
10 turbine;

11 a bypass gate and passage flanking the turbine, for
12 selectively, variably passing at least a portion of the
13 exhaust gas around the turbine; and

14 a control module, responsive to the electrical load
15 and the pressure of the exhaust gas, for controlling the
16 bypass gate.

1 5. A vehicular electric generating system as set
2 forth in claim 4, further comprising a plurality of
3 turbines positioned in the exhaust line and individually
4 and selectively powered by the exhaust gas.

1 6. A vehicular electric generating system as set
2 forth in claim 4, further comprising selectively-enabled
3 means directly powered by the engine for mechanically
4 driving the alternator.

1 7. A vehicular electric generating system for
2 providing electrical power to a load, for a vehicle having
3 an engine that operates within a narrow speed range and
4 produces exhaust gas that passes out through an exhaust
5 line, comprising:

6 at least one turbine positioned in the exhaust line
7 and powered by the exhaust gas, the turbine having an
8 output shaft; and

9 an alternator for generating alternating current
10 electricity mechanically linked to the output shaft of the
11 turbine.

1 8. A method for generating electricity and providing
2 electrical power to a load in a vehicle having an engine
3 that produces exhaust gas that passes out through an
4 exhaust line, at least one turbine positioned in the
5 exhaust line, and an alternator for generating alternating
6 current electricity mechanically linked to the output shaft
7 of the turbine, comprising the steps of:

8 powering the turbine with the exhaust gas to turn the
9 turbine and the output shaft;
10 turning the alternator to generate electricity; and
11 in response to the load and the pressure of the
12 exhaust gas, regulating the quantity of exhaust gas
13 impinging on the turbine.




FIG. 1






FIG. 4

**FIG. 2**

**FIG. 3**

INTERNATIONAL SEARCH REPORT

Inter nal Application No
PCT/US 98/04410

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 F02B63/04 F02B37/00 F02B37/10

According to International Patent Classification(IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 F02B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PATENT ABSTRACTS OF JAPAN vol. 008, no. 120 (M-300), 6 June 1984 & JP 59 026375 A (KENJI OKUJIMA), 10 February 1984,	1,3,4,6
A	see abstract	7,8
X	EP 0 141 634 A (ISUZU MOTORS LTD) 15 May 1985 see figure 1 see abstract	1
A	see page 12, line 10 - page 13, line 17	2,4,5,7, 8
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

° Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance
"E" earlier document but published on or after the international filing date
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
"O" document referring to an oral disclosure, use, exhibition or other means
"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
"&" document member of the same patent family

Date of the actual completion of the international search

19 May 1998

Date of mailing of the international search report

26/05/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Wassenaar, G

INTERNATIONAL SEARCH REPORT

Inter. Application No

PCT/US 98/04410

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 235 390 A (BBC BROWN BOVERI & CIE) 9 September 1987 see figure 1 see abstract see column 4, line 26 - line 44 see column 5, line 29 - line 48 ---	1
X	EP 0 420 705 A (ISUZU MOTORS LTD) 3 April 1991 see page 1 see abstract	1,3
A	see column 5, line 22 - column 6, line 24 -----	4,6-8

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 98/04410

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0141634 A	15-05-1985	JP 60197144 A	05-10-1985
		JP 1747476 C	25-03-1993
		JP 4032927 B	01-06-1992
		JP 60095124 A	28-05-1985
		JP 2025177 C	26-02-1996
		JP 7024457 B	15-03-1995
		JP 60098855 A	01-06-1985
		AU 586411 B	13-07-1989
		AU 3481384 A	02-05-1985
		US 4694654 A	22-09-1987
EP 0235390 A	09-09-1987	CH 669977 A	28-04-1989
		CN 1006625 B	31-01-1990
		DK 100987 A, B,	28-08-1987
		JP 2091731 C	18-09-1996
		JP 8006603 B	29-01-1996
		JP 62205896 A	10-09-1987
		KR 9513199 B	25-10-1995
		SU 1471952 A	07-04-1989
		US 4760702 A	02-08-1988
EP 0420705 A	03-04-1991	JP 1858508 C	27-07-1994
		JP 3117632 A	20-05-1991
		DE 69008291 D	26-05-1994
		DE 69008291 T	04-08-1994
		US 5079913 A	14-01-1992