



US011364581B2

(12) **United States Patent**
Day et al.

(10) **Patent No.:** **US 11,364,581 B2**
(45) **Date of Patent:** **Jun. 21, 2022**

(54) **FLEXIBLE MANUFACTURING SYSTEM FOR AIRCRAFT STRUCTURES**

2215/04 (2013.01); Y10T 29/50 (2015.01);
Y10T 408/03 (2015.01); Y10T 408/52 (2015.01)

(71) Applicant: **The Boeing Company**, Chicago, IL (US)

(58) **Field of Classification Search**
CPC ... B23P 21/004; B23B 41/00; B23B 2215/04; B64F 5/10; Y10T 29/50; Y10T 408/03; Y10T 408/52
See application file for complete search history.

(72) Inventors: **Dan Dresskell Day**, Seattle, WA (US); **Clayton Lynn Munk**, Maple Valley, WA (US); **Steven John Schmitt**, Snohomish, WA (US); **Eric M. Reid**, Kenmore, WA (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(73) Assignee: **The Boeing Company**, Chicago, IL (US)

4,006,650 A 2/1977 Elmer
4,108,566 A 8/1978 Jones
4,445,588 A 5/1984 Kautetzky
4,477,216 A 10/1984 Van De Motter et al.
4,483,080 A 11/1984 Knoll
(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 223 days.

(21) Appl. No.: **16/590,114**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Oct. 1, 2019**

CA 2497249 A1 8/2006
CA 2793202 A1 6/2013
(Continued)

(65) **Prior Publication Data**

US 2020/0030925 A1 Jan. 30, 2020

OTHER PUBLICATIONS

Related U.S. Application Data

Korean Office Action with English translation, dated Jun. 28, 2021 regarding 10-2015-0051728, 9 pages.

(62) Division of application No. 14/558,867, filed on Dec. 3, 2014, now Pat. No. 10,427,254.

(Continued)

(60) Provisional application No. 61/986,824, filed on Apr. 30, 2014.

Primary Examiner — Ryan J. Walters
(74) *Attorney, Agent, or Firm* — Yee & Associates, P.C.


(51) **Int. Cl.**
B64F 5/00 (2017.01)
B23P 21/00 (2006.01)
B23B 41/00 (2006.01)
B64F 5/10 (2017.01)

(57) **ABSTRACT**

A method and apparatus for manufacturing an aircraft structure. A drivable support may be driven from a first location to a second location to bring the drivable support together with at least one other drivable support to form a drivable support system. A structure may be held in a desired position using the drivable support system.

(52) **U.S. Cl.**
CPC **B23P 21/004** (2013.01); **B23B 41/00** (2013.01); **B64F 5/10** (2017.01); **B23B**

40 Claims, 28 Drawing Sheets



(56)

References Cited

FOREIGN PATENT DOCUMENTS

EP	2792431	A1	10/2014
GB	2095215	A	9/1982
GB	2329138	A	3/1993
GB	2473100	A	3/2011
GB	2498977	A	8/2013
JP	2000095197	A	4/2000
JP	2002283158	A	10/2002
JP	2013123794	A	6/2013
KR	100999191	B1	12/2010
WO	2010018340	A2	2/2010
WO	2013117971	A1	8/2013
WO	2014193602	A2	12/2014

OTHER PUBLICATIONS

Extended European Search Report, dated Sep. 22, 2015, regarding Application No. EP14196571.5, 8 pages.

Partial European Search Report, dated Sep. 30, 2015, regarding Application No. EP14196480.9, 6 pages.

Extended European Search Report, dated Oct. 2, 2015, regarding Application No. EP14196553.3, 7 pages.

Extended European Search Report, dated Jan. 27, 2016, regarding Application No. EP14196480.9, 10 pages.

Extended European Search Report, dated Apr. 8, 2016, regarding Application No. EP14196494.0, 6 pages.

Extended European Search Report, dated May 2, 2016, regarding Application No. EP14196483.3, 7 pages.

Extended European Search Report, dated May 2, 2016, regarding Application No. EP14196468.4, 7 pages.

Extended European Search Report, dated May 3, 2016, regarding Application No. EP14196548.3, 7 pages.

Canadian Intellectual Property Office Search Report, dated Feb. 24, 2017, regarding Application No. 2,883,614, 17 pages.

Canadian Intellectual Property Office Search Report, dated Feb. 23, 2017, regarding Application No. 2,896,059, 11 pages.

Canadian Intellectual Property Office Office Action, dated Mar. 1, 2017, regarding Application No. 2,882,420, 7 pages.

Canadian Intellectual Property Office Office Action, dated Mar. 31, 2017, regarding Application No. 2,882,466, 20 pages.

Canadian Intellectual Property Office Office Action, dated Mar. 30, 2017, regarding Application No. 2,882,4485, 17 pages.

Canadian Intellectual Property Office Office Action, dated Apr. 25, 2017, regarding Application No. 2,886,500, 19 pages.

Canadian Intellectual Property Office Examination Report, dated Dec. 14, 2017, regarding Application No. 2,882,446, 16 pages.

Canadian Intellectual Property Office Office Action, dated Feb. 15, 2018, regarding Application No. 2,883,614, 20 pages.

Chinese Intellectual Property Office, Notification of First Office Action, dated Apr. 24, 2018, regarding Application No. 201510213555.9, 11 pages.

State Intellectual Property Office of PRC, Notification of First Office Action, Search Report, and English Translation, dated May 31, 2018, regarding Application No. 201510179806.6, 20 pages.

State Intellectual Property Office of PRC, Notification of First Office Action, Search Report, and English Translation, dated Jun. 21, 2018, regarding Application No. 201510210496.X, 20 pages.

European Patent Office Communication Report, dated Nov. 19, 2018, regarding Application No. 14196553.3, 7 pages.

European Patent Office Communication Report, dated Nov. 20, 2018, regarding Application No. 14196494.0, 4 pages.

State Intellectual Property Office of PRC Notification of Second Office Action with English Translation, dated Oct. 18, 2018, regarding Application No. 2015102135559, 10 pages.

Canadian Intellectual Property Office Canadian Office Action, dated Dec. 3, 2018, regarding Application No. CA2883614, 6 pages.

Japanese Notice of Reasons for Rejection and English Translation, dated Jan. 29, 2019, regarding Application No. 2015052833, 8 pages.

Japanese Notice of Reasons for Rejection and English Translation, dated Feb. 19, 2019, regarding Application No. 2015082572, 6 pages.

Office Action, dated Mar. 4, 2016, regarding U.S. Appl. No. 14/558,850, 24 pages.

Final Office Action, dated Aug. 2, 2016, regarding U.S. Appl. No. 14/558,850, 33 pages.

Office Action, dated Nov. 10, 2016, regarding U.S. Appl. No. 14/558,850, 23 pages.

Notice of Allowance, dated Apr. 24, 2017, regarding U.S. Appl. No. 14/558,850, 11 pages.

Office Action, dated May 12, 2016, regarding U.S. Appl. No. 14/558,859, 27 pages.

Notice of Allowance, dated Jul. 7, 2016, regarding U.S. Appl. No. 14/558,859, 29 pages.

Office Action, dated May 12, 2016, regarding U.S. Appl. No. 14/558,899, 35 pages.

Final Office Action, dated Nov. 17, 2016, regarding U.S. Appl. No. 14/558,899, 36 pages.

Notice of Allowance, dated Feb. 27, 2017, regarding U.S. Appl. No. 14/558,899, 13 pages.

Office Action, dated May 3, 2017, regarding U.S. Appl. No. 14/559,034, 55 pages.

Final Office Action, dated Oct. 2, 2017, regarding U.S. Appl. No. 14/559,034, 21 pages.

Notice of Allowance, dated Jan. 17, 2018, regarding U.S. Appl. No. 14/559,034, 13 pages.

Office Action, dated Nov. 29, 2017, regarding U.S. Appl. No. 14/558,853, 78 pages.

Notice of Allowance, dated Mar. 2, 2018, regarding U.S. Appl. No. 14/558,834, 8 pages.

Notice of Allowance, dated May 18, 2018, regarding U.S. Appl. No. 14/558,853, 18 pages.

Final Office Action, dated Aug. 30, 2018, regarding U.S. Appl. No. 14/558,867, 17 pages.

Office Action, dated Mar. 27, 2019, regarding U.S. Appl. No. 15/989,054, 38 pages.

Notice of Allowance, dated May 17, 2019 regarding U.S. Appl. No. 14/558,867, 21 pages.

Office Action dated Feb. 28, 2018 regarding U.S. Appl. No. 14/558,867, 18 pages.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11





FIG. 13






FIG. 16




FIG. 17





FIG. 18






FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30

FLEXIBLE MANUFACTURING SYSTEM FOR AIRCRAFT STRUCTURES

This application is a divisional of U.S. patent application Ser. No. 14/558,867, filed Dec. 3, 2014, now U.S. Pat. No. 10,427,254, which claims the benefit of U.S. Provisional Patent Application Ser. No. 61/986,824, filed Apr. 30, 2014, and entitled "Flexible Manufacturing System for Aircraft Structures."

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is related to the following patent applications: entitled "Crawler Robot and Supporting Platform," U.S. patent application Ser. No. 14/558,850, now U.S. Pat. No. 9,776,330; entitled "System and Method for Positioning an Automated Assembly Tool Relative to a Structure," U.S. patent application Ser. No. 14/558,853, now U.S. Pat. No. 10,118,714; entitled "Metrology System for Positioning Assemblies," U.S. patent application Ser. No. 14/559,034, now U.S. Pat. No. 10,000,298; entitled "Mobile Automated Assembly Tool for Aircraft Structures," U.S. patent application Ser. No. 14/558,859, now U.S. Pat. No. 9,486,917; entitled "Mobile Automated Overhead Assembly Tool for Aircraft Structures," U.S. patent application Ser. No. 14/558,899, now U.S. Pat. No. 9,708,079; and entitled "Apparatus, System, and Method for Supporting a Wing Assembly," U.S. patent application Ser. No. 14/558,834, now U.S. Pat. No. 10,017,277, each assigned to the same assignee, and each incorporated herein by reference in its entirety.

BACKGROUND INFORMATION

1. Field

The present disclosure relates generally to aircraft and, in particular, to manufacturing aircraft structures. Still more particularly, the present disclosure relates to a method and apparatus for performing operations to manufacture aircraft structures using an automated drivable assembly system.

2. Background

Manufacturing aircraft structures may be a complex and time-consuming process. Thousands of parts may be designed and assembled to complete an aircraft structure. Progressive assembly of these parts may be completed by moving the aircraft structure to different locations in the manufacturing facility. Various operations are performed on the aircraft structure in each of the locations.

Existing assembly systems for aircraft structures use fixed monument fixtures arranged throughout the manufacturing facility. In this illustrative example, a "fixed monument fixture" is a structure that is immovably connected to the facility floor, wall, or other portion of the manufacturing facility. For example, without limitation, a fixed monument fixture that is bolted to the facility floor may be used to hold an aircraft structure in a desired position while it is being assembled.

Human operators and their tools maneuver about these fixed monument fixtures to perform operations on the aircraft structure. For instance, human operators may bring various parts to the fixed monument fixture, position those parts relative to the aircraft structure held by the fixed monument fixture, and perform operations such as drilling,

fastening, coating, and inspecting, among others. Countless labor hours are needed for human operators to assemble and inspect the aircraft structure.

Once a certain point in assembly is reached, the aircraft structure may be removed from the fixed monument fixture and moved to a new location within the manufacturing facility. In the new location, the structure may again be secured to a fixed monument fixture, recalibrated, and assembled. The movement and repositioning of the aircraft structure may cause undesired delays in the manufacturing process, which increase the production time for the aircraft structure.

In addition, the process of using fixed monument fixtures may take up more room than desired in the manufacturing facility, allow limited access to the aircraft structure for human operators, or both. The need for human operators to transport parts to fixed monument fixtures and maneuver within and around these fixed monument fixtures also may increase the time, complexity, and cost of assembling the aircraft more than desired.

Additionally, fixed monument fixtures may be difficult to modify or move since fixed monument fixtures are heavy, secured to the floor, or both. Therefore, fixed monument fixtures may be inflexible and may be useful for only one assembly build configuration. Accordingly, there is a need for a method and apparatus that provides a more efficient, flexible, higher production rate process for assembling aircraft without the use of fixed monument fixtures attached to the manufacturing facility floor.

SUMMARY

In one illustrative embodiment, a flexible manufacturing system for an aircraft structure may comprise a drivable support. The drivable support may be driven from a first location and brought together with at least one other drivable support to form a drivable support system at a second location on a floor of a manufacturing environment. The drivable support system may be configured to hold a structure in a desired position.

In another illustrative embodiment, a method for manufacturing an aircraft structure may be provided. A drivable support may be driven from a first location to a second location to bring the drivable support together with at least one other drivable support to form a drivable support system. A structure may be held in a desired position using the drivable support system.

In another illustrative embodiment, a flexible manufacturing system may comprise a drivable support, a plurality of autonomous tool systems, a metrology system, and a controller in communication with the metrology system, the drivable support system, and the plurality of autonomous tool systems. The drivable support may be configured to be driven from a first location and brought together with at least one other drivable support to form a drivable support system at a second location on a floor of a manufacturing environment. The drivable support system may be configured to hold the structure in a desired position. The drivable support system and the structure may be configured to drive to a third location while operations are being performed on the structure. The plurality of autonomous tool systems may be configured to perform the operations on the structure. The plurality of autonomous tool systems may be further configured to drive across the floor of the manufacturing environment. The metrology system may be configured to determine a current position for at least one of the drivable support system, the plurality of autonomous tool systems, or

the structure. The controller may be configured to control operation of at least one of the drivable support system or the plurality of autonomous tool systems.

In yet another illustrative embodiment, a system for manufacturing an aircraft structure may comprise a group of crawler robots and a mobile platform. The group of crawler robots may be positioned on a structure. The group of crawler robots may be configured to move along a surface of the structure to install fasteners in the structure. The mobile platform may be configured to drive across a floor of a manufacturing environment. The mobile platform may be further configured to place the group of crawler robots on the surface of the structure.

In still another illustrative embodiment, a method for manufacturing an aircraft structure may be provided. A drivable platform may be driven across a floor of a manufacturing environment to place a group of crawler robots on a structure. The group of crawler robots may be positioned relative to a surface of the structure to install fasteners in the structure.

In another illustrative embodiment, a system for manufacturing an aircraft structure may comprise a hexapod and a movement system associated with the hexapod. The hexapod may be positioned relative to a surface of a structure. The hexapod may be configured to move relative to the surface of the structure to install a fastener in the structure. The movement system may be configured to drive the hexapod across a floor of a manufacturing environment to position the hexapod relative to the structure.

In yet another illustrative embodiment, a method for manufacturing an aircraft structure may be provided. A hexapod may be driven across a floor of a manufacturing environment to position the hexapod relative to a structure using a movement system associated with the hexapod. The hexapod may be positioned relative to a surface of the structure to install a fastener in the structure.

In still another illustrative embodiment, a flexible manufacturing system for a structure may comprise a mobile support system, a plurality of autonomous tool systems, a metrology system, and a controller in communication with the metrology system and the plurality of autonomous tool systems. The mobile support system may be configured to hold the structure in a desired position. The mobile support system may be further configured to carry the structure between a plurality of work cells during a performance of operations for manufacturing the structure. The plurality of autonomous tool systems may be configured to perform the operations on the structure. The plurality of autonomous tool systems may be further configured to move with the mobile support system. The metrology system may be configured to generate metrology data for at least one of the mobile support system, the plurality of autonomous tool systems, or the structure. The controller may be configured to control operation of the plurality of autonomous tool systems using the metrology data.

In another illustrative embodiment, a flexible manufacturing system for a structure may comprise a translatable support system, a plurality of autonomous tool systems, a metrology system, and a controller in communication with the metrology system and the plurality of autonomous tool systems. The translatable support system may be configured to hold the structure in a desired position. The translatable support system may be further configured to move with the structure from a first location to a second location during a performance of operations for manufacturing the structure. The plurality of autonomous tool systems may be configured to perform the operations on the structure. The plurality of

autonomous tool systems may be further configured to move with the translatable support system. The metrology system may be configured to generate metrology data for at least one of the translatable support system, the plurality of autonomous tool systems, or the structure. The controller may be configured to control operation of the plurality of autonomous tool systems using the metrology data.

In yet another illustrative embodiment, a method for positioning a tool on a surface may be provided. The tool may be moved relative to the surface to roughly position the tool within a selected region on the surface using a first movement system. The tool may be further moved relative to the surface with at least one degree of freedom to precisely position the tool at a selected position within the selected region on the surface using a second movement system.

In still another illustrative embodiment, a method for positioning a tool on a surface may be provided. The tool may be moved relative to the surface to roughly position the tool within a selected region on the surface using a first movement system. The tool may be further moved relative to the surface with at least one degree of freedom to precisely position the tool at a selected position within the selected region on the surface using a second movement system. An element associated with the tool may be aligned for performing an operation at the selected position relative to the selected position using a third movement system.

In another illustrative embodiment, a flexible manufacturing system for an aircraft structure may comprise a first group of drivable supports, a second group of drivable supports, a first elongate platform and a second elongate platform. The first group of drivable supports may be driven from a first location and brought together with the second group of drivable supports at a second location on a floor of a manufacturing environment. The first elongate platform may be connected to the first group of drivable supports. The first group of drivable supports may drive the first elongate platform to the second location. The second elongate platform may be connected to the second group of drivable supports. The second group of drivable supports may drive the second elongate platform to the second location. The first elongate platform and the second elongate platform may hold a structure in a desired location and may carry the structure through the manufacturing environment.

In yet another illustrative embodiment, a method for manufacturing an aircraft structure may be presented. A first group of drivable supports, connected to a first elongate platform, may be driven from a first location to a second location on a floor of a manufacturing environment. A second group of drivable supports, connected to a second elongate platform, may be driven to position the second elongate platform relative to the first elongate platform. A structure used to form the aircraft structure may be connected to the first elongate platform and the second elongate platform. The structure may be held in a desired position using the first elongate platform and the second elongate platform.

The features and functions can be achieved independently in various embodiments of the present disclosure or may be combined in yet other embodiments in which further details can be seen with reference to the following description and drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the illustrative embodiments are set forth in the appended claims. The

5

illustrative embodiments, however, as well as a preferred mode of use, further objectives and features thereof, will best be understood by reference to the following detailed description of an illustrative embodiment of the present disclosure when read in conjunction with the accompanying drawings, wherein:

FIG. 1 is an illustration of a block diagram of a manufacturing environment in accordance with an illustrative embodiment;

FIG. 2 is an illustration of an isometric view of a manufacturing environment in accordance with an illustrative embodiment;

FIG. 3 is an illustration of a work cell with wing assembly components staged for installation in accordance with an illustrative embodiment;

FIG. 4 is an illustration of a drivable support system positioned in a work cell in accordance with an illustrative embodiment;

FIG. 5 is an illustration of a drivable support system with a wing assembly in accordance with an illustrative embodiment;

FIG. 6 is an illustration of a wing assembly and a drivable support system in accordance with an illustrative embodiment;

FIG. 7 is an illustration of a loading device loading a panel on a wing assembly in accordance with an illustrative embodiment;

FIG. 8 is an illustration of autonomous tool systems performing operations on a panel in accordance with an illustrative embodiment;

FIG. 9 is an illustration of a section of a wing assembly with a tack driller in accordance with an illustrative embodiment;

FIG. 10 is an illustration of autonomous tool systems performing operations on a panel in accordance with an illustrative embodiment;

FIG. 11 is an illustration of a section of a wing assembly with a crawler robot and a drivable platform in accordance with an illustrative embodiment;

FIG. 12 is an illustration of a loading device with a panel in accordance with an illustrative embodiment;

FIG. 13 is an illustration of a loading device with a panel in accordance with an illustrative embodiment;

FIG. 14 is an illustration of assembly systems performing operations on a panel in accordance with an illustrative embodiment;

FIG. 15 is an illustration of an assembly system performing operations on a surface of a wing assembly in accordance with an illustrative embodiment;

FIG. 16 is an illustration of a wing in a work cell in accordance with an illustrative embodiment;

FIG. 17 is an illustration of a top view of a work cell in accordance with an illustrative embodiment;

FIG. 18 is an illustration of a manufacturing environment in accordance with an illustrative embodiment;

FIG. 19 is an illustration of a drivable support system with elongate platforms in accordance with an illustrative embodiment;

FIG. 20 is an illustration of a drivable support system and a wing assembly in accordance with an illustrative embodiment;

FIG. 21 is an illustration of an enlarged view of a connection device and a point on a wing assembly in accordance with an illustrative embodiment;

FIG. 22 is an illustration of a flowchart of a process for positioning a tool on a surface in accordance with an illustrative embodiment;

6

FIG. 23 is an illustration of a flowchart of a process for performing operations on a structure in accordance with an illustrative embodiment;

FIG. 24 is an illustration of a flowchart of a process for operating a flexible manufacturing system to perform operations on a structure in accordance with an illustrative embodiment;

FIG. 25 is an illustration of a flowchart of a process for controlling operation of a plurality of autonomous tool systems in accordance with an illustrative embodiment;

FIG. 26 is an illustration of a flowchart of a process for management of a manufacturing environment in accordance with an illustrative embodiment;

FIG. 27 is an illustration of a flowchart of a process for using a drivable support system to build a wing assembly in accordance with an illustrative embodiment;

FIG. 28 is an illustration of a data processing system in the form of a block diagram in accordance with an illustrative embodiment;

FIG. 29 is an illustration of an aircraft manufacturing and service method in the form of a block diagram in accordance with an illustrative embodiment; and

FIG. 30 is an illustration of an aircraft in the form of a block diagram in which an illustrative embodiment may be implemented.

DETAILED DESCRIPTION

The illustrative embodiments recognize and take into account one or more different considerations. For example, without limitation, the illustrative embodiments recognize and take into account that it may be desirable to assemble an aircraft structure without the use of fixed monument fixtures at different locations within the manufacturing facility. These fixed monument fixtures may be large, bulky, structures that take up significant amounts of space in the manufacturing facility. As a result, the number of work cells available in the manufacturing facility may be limited, which reduces the number of aircraft structures that may be assembled at the same time.

Additionally, the illustrative embodiments recognize and take into account that when maintenance or rework needs to be performed on the fixed monument fixtures, production of aircraft structures may be slowed until the fixed monument fixture is repaired. Fixed monument fixtures are not easily replaceable without significantly reducing the production rate of aircraft structures within the manufacturing facility.

The illustrative embodiments also recognize and take into account that it may be desirable to reconfigure devices in an assembly system based on the layout of the manufacturing facility being used, the type of aircraft structure being built, or a combination thereof. For instance, it may be desirable to a manufacturer to bring a number of devices to an empty manufacturing environment, where no fixed monument fixtures or other structures are present. The manufacturer may then arrange or assemble the devices as needed to promote efficient manufacturing of the aircraft structure. After initially arranging such devices, the illustrative embodiments recognize and take into account that it may be desirable to rearrange the devices, change the configuration of the devices, modify the length of the assembly line, perform more operations at a single location, or make some other change or adjustment. In other words, it may be desirable for the devices to be arranged and rearranged to form many different non-fixed fixtures.

The illustrative embodiments further recognize and take into account that it may be desirable to increase the speed at

which an aircraft structure is assembled. For example, without limitation, it may be desirable to automate various operations using robotic devices. As another example, it may be desirable to move the aircraft structure between locations in the manufacturing facility without disconnecting the aircraft structure from the fixture holding the aircraft structure. It also may be desirable to move the aircraft structure to another location without having to place the aircraft structure back onto another set of fixed monument fixtures before performing additional operations. All of these actions require reconfiguration of the aircraft structure which may increase the time, complexity, and cost of manufacturing the aircraft structure.

Thus, the illustrative embodiments may provide a method and apparatus for performing operations on an aircraft structure. This aircraft structure may take the form of a wing, a fuselage, a stabilizer, a flap, a door, a slat, an aileron, a spoiler, or other component for an aircraft or some other non-aircraft structure. A flexible manufacturing system may include a drivable support driven from a first location and brought together with at least one other drivable support to form a drivable support system, or non-fixed fixture, at a second location on a floor of a manufacturing environment. The drivable support system may be configured to hold a structure in a desired position and drive the drivable support system carrying the assembly to a third location while operations are being performed on the assembly.

Referring now to the figures and, in particular, with reference to FIG. 1, an illustration of a block diagram of a manufacturing environment is depicted in accordance with an illustrative embodiment. In this illustrative example, manufacturing environment 100 is an environment in which flexible manufacturing system 102 may be used to manufacture product 104.

In an illustrative example, manufacturing environment 100 may be empty before flexible manufacturing system 102 is initially arranged within manufacturing environment 100. In other words, manufacturing environment 100 may be an empty manufacturing facility, building, unit, or other suitable location used to manufacture product 104. Flexible manufacturing system 102 may be moved into manufacturing environment 100, arranged, and reconfigured as needed to promote efficient manufacturing of product 104. Flexible manufacturing system 102 may be a manufacturing system having the flexibility to change to produce new product types, the ability to change the order of operations executed on a part for product 104, the ability to use multiple devices to perform the same operation on a part, the ability to handle large-scale changes in volume, capacity, or capability, or some combination thereof.

In this illustrative example, flexible manufacturing system 102 may be a manufacturing system that is at least partially automated. In one illustrative example, flexible manufacturing system 102 is a substantially fully automated system for manufacturing product 104. When flexible manufacturing system 102 is fully automated, it may take the form of an autonomous flexible manufacturing system.

Flexible manufacturing system 102 may be movable and reconfigurable in this illustrative example. In particular, one or more components in flexible manufacturing system 102 may be movable to various locations 103 in manufacturing environment 100. None of the components in flexible manufacturing system 102 are fixed in a specified location.

As used herein, a device that is “movable” may mean that the item can move or be moved. In some cases, a movable device may take the form of a mobile device.

A device that is “mobile” may be able to move from one location in three-dimensional space to another location in three-dimensional space. In particular, an entirety of the device, which may include all of the components that make up the device, may be capable of moving or being moved from one location in three-dimensional space to another location in three-dimensional space. In this manner, the device is not fixed to a particular location.

When flexible manufacturing system 102 includes mobile devices, flexible manufacturing system may be referred to as a mobile assembly system. Flexible manufacturing system 102 does not include a fixed monument fixture in this illustrative example. In some cases, a mobile device may take the form of a drivable device.

A device that is “drivable” may be able to move from one location in three-dimensional space to another location in three-dimensional space as described above. Movement of a drivable device may be controlled using, for example, without limitation, a controller for the device, a system controller for flexible manufacturing system 102, or some other type of controller.

Depending on the implementation, movement of a drivable device may be controlled at least one of electronically, mechanically, electromechanically, or manually. In this manner, a drivable device may be capable of moving or being moved in its entirety in a number of different ways. In some cases, movement of a drivable device may be both electronically and manually controlled. For example, the device may be drivable across floor 107 of manufacturing environment 100 to assemble product 104.

In this depicted example, product 104 is a physical object that is comprised of any number of parts, components, sub-assemblies, assemblies, or systems. These items may be assembled to form product 104. In some cases, product 104 may be partially assembled in manufacturing environment 100 and then moved to another location for additional assembly. Product 104 may be referred to as a structure, an aircraft structure, a part, or an aircraft part in some instances.

In one illustrative example, product 104 may take the form of wing 108 for aircraft 109. In other illustrative examples, product 104 may take the form of an aircraft structure selected from one of a fuselage, a vertical stabilizer, a control surface, a horizontal stabilizer and other suitable structures. Further, product 104 may be an automobile, an aircraft, a ship, a satellite, an engine, a building, or other types of structures in some cases.

Structure 110 may correspond to product 104 during manufacturing of product 104. Specifically, structure 110 may be product 104 during various stages of manufacturing. In this manner, structure 110 may be one or more components used to form product 104, a partially completed product 104, or a fully completed product 104. In some illustrative examples, structure 110 may be referred to as an assembly for product 104.

When structure 110 corresponds to wing 108, structure 110 may be referred to as wing assembly 105. In this depicted example, components may be added to structure 110 as structure 110 moves about manufacturing environment 100.

As depicted, manufacturing environment 100 may include locations 103. In particular, manufacturing environment 100 may include first location 113, second location 115, third location 117, and fourth location 119. In this illustrative example, locations 103 may be different physical positions within manufacturing environment 100.

Manufacturing environment 100 may include plurality of work cells 112. Plurality of work cells 112 are areas in

manufacturing environment **100** where flexible manufacturing system **102** works on structure **110**. A location in locations **103** may correspond to a work cell in work cells **112** in some cases. For instance, one or more of locations **103** may be in one of plurality of work cells **112**.

Various tasks **111** may be performed in each work cell in plurality of work cells **112**. For example, without limitation, in one work cell, spars and ribs may be connected to each other to form a framework for wing **108**. In another work cell, skin panels may be attached to the framework. In yet another work cell, a sealant, paint, or other materials may be applied to wing **108**.

In this depicted example, each work cell in plurality of work cells **112** may have dimensions **114**. Dimensions **114** may represent measurements of the size of each of the different work cells in plurality of work cells **112**. For instance, dimensions **114** may include a length, a width, a height, and other suitable dimensions for each work cell in plurality of work cells **112**.

Dimensions **114** for each work cell in plurality of work cells **112** may be the same or different in this illustrative example. In some cases, dimensions **114** may change as structure **110** moves through plurality of work cells **112**. In other cases, dimensions **114** may change based on at least one of a size or a layout of manufacturing environment **100**.

As used herein, the phrase “at least one of,” when used with a list of items, means different combinations of one or more of the listed items may be used and only one of the items in the list may be needed. The item may be a particular object, thing, or category. In other words, “at least one of” means any combination of items or number of items may be used from the list, but not all of the items in the list may be required.

For example, “at least one of item A, item B, and item C” may mean item A; item A and item B; item B; item A, item B, and item C; or item B and item C. In some cases, “at least one of item A, item B, and item C” may mean, for example, without limitation, two of item A, one of item B, and ten of item C; four of item B and seven of item C; or some other suitable combination.

As illustrated, flexible manufacturing system **102** may comprise a number of different components. As used herein, a “number of” items may be one or more items. For instance, a number of components may be one more components.

In this illustrative example, flexible manufacturing system **102** may include support system **101**, plurality of autonomous tool systems **118**, drive control system **121**, navigator **124**, transformer **126**, and loading system **127**. These systems may be referred to collectively as “components” in flexible manufacturing system **102**.

At least one of the components in flexible manufacturing system **102** may be reconfigurable. In this illustrative example, substantially all of the components in flexible manufacturing system **102** are reconfigurable depending on the particular implementation of flexible manufacturing system **102**.

As used herein, “reconfigurable” may refer to the ability of components within a system to be rearranged. This rearrangement may be in terms of a change in position of one component relative to another component. The position may be the location of the component using three-dimensional coordinates, the orientation of the component, or both.

The position of components within flexible manufacturing system **102** may be “dynamically reconfigured.” In other words, components within support system **101** may be

rearranged in real-time as structure **110** is moved through manufacturing environment **100**.

In another illustrative example, each component within support system **101** also may be independently reconfigurable. In other words, devices within each component may be rearranged, recalibrated, or otherwise changed during manufacturing of wing **108**.

As an example, when a component has three devices, one or more of those devices may be reconfigured within the component without rearranging the position of the component relative to other components in flexible manufacturing system **102**. In this manner, flexible manufacturing system **102** as a whole, as well as each component within flexible manufacturing system **102**, may be dynamically reconfigured as needed. When one or more of the components in flexible manufacturing system **102** are reconfigured, reconfiguration **128** of those components has occurred.

In this illustrative example, reconfiguration **128** of components within flexible manufacturing system **102** may occur during manufacturing of product **104**. In particular, reconfiguration **128** of at least one of the components within flexible manufacturing system **102** may be performed based on changes in at least one of dimensions **114** in different work cells in plurality of work cells **112**, status **129** of operations **130** for structure **110**, or a status of any one of the components in flexible manufacturing system **102**.

As an example, when an autonomous tool system in plurality of autonomous tool systems **118** goes offline, another autonomous tool system in plurality of autonomous tool systems **118** may take over for the offline device. This action results in reconfiguration **128** of plurality of autonomous tool systems **118**. In another illustrative example, when dimensions **114** in plurality of work cells **112** are limited, more of operations **130** may be performed in a single work cell.

In still other illustrative examples, reconfiguration **128** may include changing the order of operations **130**. In this case, because each of the components within flexible manufacturing system **102** can move relative to other components in flexible manufacturing system **102**, these components are moved to a desired position within manufacturing environment **100**.

As another example, reconfiguration **128** may occur based on manufacturing parameters **132** for wing **108**. Manufacturing parameters **132** may include size of product **104** being manufactured, the type of plurality of autonomous tool systems **118** needed, a production rate, the materials used, safety considerations, airline regulations, other suitable parameters, or a combination thereof.

In this depicted example, support system **101** may be used to support and hold structure **110** as structure **110** moves through manufacturing environment **100**. In this manner, support system **101** carries structure **110** through manufacturing environment **100**.

Support system **101** may include a number of components that drive across floor **107** in manufacturing environment **100**. When support system **101** includes drivable components, support system **101** takes the form of drivable support system **116**.

Drivable support system **116** may take the form of a rapid autonomous barge intelligent tool (RABIT) in some cases. Drivable support system **116** may be referred to as a transportable support system or a mobile support system.

Drivable support system **116** may be configured to hold structure **110** in desired position **133** as it drives across floor **107**. In this illustrative example, drivable support system

11

116 may carry structure 110 between plurality of work cells 112 during performance of operations 130.

As illustrated, drivable support system 116 may comprise support structures 152 and bridge system 136. Drivable support system 116 also may be physically associated with rail system 138. As used herein, a first component, such as drivable support system 116, may be considered to be associated with a second component, such as rail system 138, by being secured to the second component, bonded to the second component, mounted to the second component, welded to the second component, fastened to the second component, connected to the second component in some other suitable manner, or a combination thereof. The first component also may be connected to the second component using a third component. Further, the first component may be considered to be associated with the second component by being formed as part of, as an extension of the second component, or a combination thereof.

In this illustrative example, support structures 152 each may be individually drivable. When support structures 152 are drivable, support structures 152 take the form of drivable supports 135. Drivable support 137 is one of drivable supports 135 in this illustrative example. Drivable support 137 may be a device configured to be driven from first location 113 and brought together with at least one other drivable support in drivable supports 135 to form drivable support system 116 at second location 115 on floor 107 of manufacturing environment 100.

Drivable support system 116 may take the form of non-fixed fixture 169. In this manner, drivable support system 116 may function as a monument that is drivable, movable, translatable, or otherwise configured to be moved in its entirety between locations 103 in manufacturing environment 100. Once drivable support system 116 is formed, drivable support system 116 may be configured to carry structure 110 to third location 117 while operations 130 are being performed on structure 110. As an example, third location 117 may be a location in one of plurality of work cells 112. Drivable support system 116 also may carry structure 110 between a number of additional locations in manufacturing environment 100.

Each one of drivable supports 135 may be configured to hold one of parts 191 for structure 110 and drive across floor 107 of manufacturing environment 100 to position each respective part relative to one another under the command of controller 122 in drive control system 121. For instance, drivable support 137 may carry a spar across floor 107 to position the spar relative to structure 110. As another example, drivable support 137 may bring a group of ribs to structure 110.

Each of drivable supports 135 may be connected to structure 110 at different connection points 167 on structure 110 in this illustrative example. Connection points 167 are physical locations on structure 110 to which drivable supports 135 connect.

In this depicted example, each of drivable supports 135 may be a module that can be moved away from drivable support system 116 and replaced with another. In this manner, drivable support system 116 may be reconfigured for a different sized wing. As another example, a new drivable support may be used to replace one of drivable supports 135 that may malfunction or need maintenance, for some other reason, or a combination thereof.

Drivable supports 135 may be mechanical stanchions, upright supports, automated guided vehicles, pillars, or may take other forms in this illustrative example. Each of drivable supports 135 may be equipped with various mechanical

12

and electrical components such as, for example, without limitation, a controller, an actuator, a clamping device, a pneumatic tool, a hydraulic tool, and other suitable devices configured to hold structure 110 in desired position 133.

In some illustrative examples, each of drivable supports 135 may be associated with its own movement system. When drivable supports 135 are brought together to form drivable support system 116, the individual movement systems corresponding to drivable supports 135 may move collectively between locations 103.

In other illustrative examples, a collective movement system may be configured to move drivable support system 116 in its entirety. For instance, a tug or other type of movement system may be connected to one or more of drivable supports 135 to move or propel drivable support system 116 from one location to another location in manufacturing environment 100.

As depicted, desired position 133 may be a configuration for structure 110 in three-dimensional space. For example, without limitation, desired position 133 may include a location, an orientation, a height above floor 107, or some other suitable configuration in manufacturing environment 100. Desired position 133 may be selected based on the size of structure 110, the type of operations 130 being performed on structure 110, and other suitable parameters.

Drivable supports 135 may be associated with connection devices 195. Connection devices 195 may be referred to as fixturing devices, fixturing points, connection points, or connection tools in some illustrative examples.

Connection devices 195 each may connect to a different one of connection points 167 on structure 110. Connection devices 195 may be configured to connect to structure 110 at connection points 167 to hold at least a portion of structure 110 above floor 107. Connection devices 195 may move vertically, tilt, or otherwise position the different parts 191 on structure 110.

Controller 122 may be configured to control each of connection devices 195 individually, to change its height, angle, length, or other parameters. Controller 122 also may be configured to control the collective of connection devices 195 corresponding to drivable supports 135 forming drivable support system 116.

In addition, controller 122 may be configured to extend or retract each of connection devices 195. In this manner, precise positioning of parts 191 of structure 110 may be completed to achieve desired position 133 for structure 110.

In some illustrative examples, one or more of connection devices 195 may be configured to connect to structure 110 at control points 193. Control points 193 are connection points 167 with additional functions.

Control point 171 may be one of control points 193. Control point 171 may be a location on structure 110 that may be controllable such that control point 171 may be brought into alignment with a reference coordinate system for structure 110 or for product 104 being manufactured.

For example, without limitation, the reference coordinate system may be a reference coordinate system based on product 104 or the object or platform for which product 104 is being manufactured. When product 104 being assembled is, for example, without limitation, wing 108 for aircraft 109, the reference coordinate system may be airplane coordinate system 183. In such a case, control point 171 may be at a known location on structure 110 with respect to airplane coordinate system 183.

Control point 171 may be used to transition between airplane coordinate system 183 and global coordinate system 181 for manufacturing environment 100. Global coordinate system 181

dinate system **181** may be identified using metrology system **120**. Global coordinate system **181** may be a shop or manufacturing coordinate system.

The location of control point **171** in global coordinate system **181** may correspond with the location of control point **171** in airplane coordinate system **183**. In this manner, for example, without limitation, locations within airplane coordinate system **183** at which particular operations are to be performed may be transformed into locations within global coordinate system **181**. Further, locations within global coordinate system **181** at which particular operations are being performed may be transformed into locations within airplane coordinate system **183**. These transformations may occur using transformer **126**.

For example, control point **171** may be used to transition between global coordinate system **181** for manufacturing environment **100** and a wing coordinate system for wing **108** or airplane coordinate system **183** for aircraft **109**. In this manner, control point **171** may be used to locate structure **110** with respect to airplane coordinate system **183**.

The collective of connection devices **195** corresponding to drivable supports **135** may be attached to the parts used to assemble a product, such as wing **108**, at connection points **167**. This collective of connection devices **195** may hold parts **191** at connection points **167** to restrain assembly dimensional shape within tolerances. The collective of connection devices **195** also may hold the parts in the desired position for assembly of wing **108**. Connection points **167** may be attachment points on the structure. For instance, connection points **167** may be leading or trailing edge attachment points or control surface hinge points for structures such as slats, spoilers, rudders, flaps, control surfaces, or other points where something can be attached to the structure during the build process.

In this illustrative example, drivable supports **135** may substantially prevent structure **110** from moving in an undesired manner. Structure **110** may move in an undesired manner when structure **110** moves outside of selected tolerances. For instance, structure **110** may move in an undesired manner when structure **110** tilts, sways, rotates, vibrates, or moves in some other manner outside of desired position **133**.

In some cases, drivable supports **135** may be connected to one another by platform structure **134**. In this illustrative example, platform structure **134** may be an object positioned under structure **110**. Platform structure **134** may comprise a number of platforms that connect drivable supports **135** to one another. In this manner, platform structure **134** may temporarily connect drivable supports **135**. Platform structure **134** and drivable supports **135** may then collectively carry structure **110** throughout plurality of work cells **112** from location to location. When platform structure **134** drives across floor **107**, platform structure **134** may be referred to as a drivable platform structure.

As depicted, bridge system **136** may be a structure connected to drivable supports **135**. For instance, drivable supports **135** may hold bridge system **136**. As another example, bridge system **136** may connect two or more drivable supports **135**. In another illustrative example, bridge system **136** may be connected to drivable supports **135** in some other manner.

In this depicted example, bridge system **136** may be configured to provide access to structure **110** by human operator **142**. For example, without limitation, bridge system **136** may allow access for human operator **142** to a portion of structure **110** that would not otherwise be

accessed from floor **107** of manufacturing environment **100**. As another example, bridge system **136** may provide a walkway over structure **110**.

In one illustrative example, bridge system **136** may be connected to drivable supports **135**. In this case, drivable supports **135** drive bridge system **136** from one location to another location in manufacturing environment **100**. In the illustrative example, a group of drivable supports **135** may move bridge system **136**. For example, without limitation, three supports, four supports, seven supports, or some other suitable number of drivable supports **135** may move bridge system **136** into place.

When bridge system **136** is connected to drivable supports **135**, connection devices **195** may be located on bridge system **136** instead of being located on each of drivable supports **135**. For instance, bridge system **136** may comprise elongate platform **177** on which connection devices **195** are positioned. Depending on the implementation, connection devices **195** may be equally spaced at fixed intervals along elongate platform **177** or spaced at intervals that may change by moving one or more of connection devices **195**.

Elongate platform **177** is an elevated platform in this illustrative example. When elongate platform **177** is used, structure **110** is connected to connection devices **195** positioned along elongate platform **177**.

In an illustrative example, elongate platform **177** may take the form of a beam. In other illustrative examples, elongate platform **177** may take the form of any physical structure having a shape and size configured to hold and support structure **110**.

In some instances, more than one elongate platform is used. When more than one elongate platform is used, connection devices **195** may be positioned on each platform in various configurations.

In an illustrative example, connection devices **195** may be positioned along the length of elongate platform **177**. For instance, connection devices **195** may be positioned adjacent to one another along the entire length of elongate platform **177**. In this manner, more of connection devices **195** may be implemented in an illustrative embodiment without increasing the number of drivable supports **135** used. Each of connection devices **195** positioned along elongate platform **177** correspond to one or more of connection points **167** of structure **110**.

In this depicted example, each of drivable supports **135** may move a portion of elongate platform **177**. For instance, each of drivable supports **135** oriented underneath elongate platform **177** may move a point on elongate platform **177** in at least one of the x-direction, the y-direction, or the z-direction. Drivable supports **135** also may rotate a point on elongate platform **177** about the x-axis, the y-axis, or the z-axis to position elongate platform **177** as desired.

As an example, drivable support **137** may use a z-ram or other lift device to lift a portion of elongate platform **177** higher above the ground to compensate for uneven areas of floor **107**. In this manner, drivable support **137** may move to control the flatness of elongate platform **177** and accordingly, control the position of corresponding portions of structure **110**. As another example, drivable support **137** may tilt elongate platform **177** such that connection devices **195** connected to elongate platform **177** bring control points **193** on structure **110** into alignment.

The movement of elongate platform **177** may occur in addition to, or in place of, movement of connection devices **195** individually to reposition part of structure **110**. In this manner, select connection devices **195**, drivable supports

135, portions of elongate platform 177, or some combination thereof may move to precisely position part of structure 110.

In some cases, connection devices 195 may be fixed on elongate platform 177. In such a case, connection devices 195 may not move individually. Instead, drivable supports 135 move elongate platform 177 to properly position structure 110. In other examples, however, one or more of connection devices 195 may move as well.

In an illustrative example, bridge system 136 also may be used to supply a number of utilities 179 to one or more devices in flexible manufacturing system 102. Utilities 179 may include at least one of electricity, water, air, communications, or other utilities.

For example, without limitation, elongate platform 177 may include channel 185. A number of lines 187 may run through channel 185. In an illustrative example, lines 187 may be structures through which utilities 179 run. For instance, some of lines 187 may take the form of cables carrying electricity or communications. In other illustrative examples, lines 187 carry air. In some cases, lines 187 may be deposited within elongate platform 177, attached underneath elongate platform 177, oriented along elongate platform 177 in some other manner, or a combination thereof.

In this depicted example, portions of bridge system 136 may come together to support structure 110 using drivable supports 135. For example, without limitation, a first group of drivable supports 135 may move elongate platform 177 into manufacturing environment 100 to support a leading edge of structure 110. In a similar fashion, a second group of drivable supports 135 may move a second elongate platform into manufacturing environment 100 to support a trailing edge of structure 110. In some illustrative examples, the first elongate platform and the second elongate platform may be connected using various end supports, latches, locks, mechanical structures, electrical structures, structural members, or other suitable devices.

Elongate platform 177 may balance a number of loads applied to connection devices 195 by structure 110 being connected to connection devices 195. In particular, elongate platform 177 may distribute the number of loads along elongate platform 177 to drivable supports 135. In this manner, elongate platform 177 may be referred to as a load-balancing structure.

As drivable supports 135 move bridge system 136 into place, drivable supports 135 may be adjusted to provide desired load handling. For instance, when traveling at an incline in manufacturing environment 100, drivable supports 135 under elongate platform 177 may move elongate platform 177 up or down to compensate for the load of structure 110. As a result, elongate platform 177 may balance the load applied by structure 110 to connection devices 195. Load balancing helps to reduce or eliminate undesired encounters with other objects, inconsistencies forming in floor 107 due to the unbalanced load of structure 110, or other undesired events.

As illustrated, rail system 138 may be associated with bridge system 136 and portions of structure 110. Rail system 138 may be configured to provide fall protection 144 for human operator 142. As an example, rail system 138 may provide a barrier such that human operator 142 does not fall off elongate platform 177 in bridge system 136.

In another illustrative example, rail system 138 may be arranged on structure 110 to provide separation between plurality of autonomous tool systems 118 and human operator 142. For example, without limitation, rail system 138 may be positioned about perimeter 140 of structure 110 to separate plurality of autonomous tool systems 118 from

human operator 142. Rail system 138 may be used in addition to, or in place of, other fall protection devices such as cables, grips, ties, suspension devices, and slip protection, among others.

In this depicted example, drivable support system 116 may carry structure 110 through manufacturing environment 100. In this manner, drivable supports 135 remain connected to structure 110 as structure 110 moves between plurality of work cells 112. No fixed monument structures are needed to hold structure 110 in place within any of plurality of work cells 112. Structure 110 is driven from location to location without detaching structure 110 from drivable support system 116.

Because drivable support system 116 may move with structure 110, each of drivable supports 135 may be dynamically adjusted to compensate for various differences in plurality of work cells 112. For instance, one or more of drivable supports 135 may be adjusted to compensate for conditions such as, for example, without limitation, uneven floors, platform deflections, debris, and access requirements for plurality of autonomous tool systems 118, among others. Adjustments may be made to connection devices 195 as well.

As depicted, plurality of autonomous tool systems 118 may be drivable devices configured to perform operations 130 on structure 110. In an illustrative example, plurality of autonomous tool systems 118 may move freely within manufacturing environment 100 between locations 103 to perform operations 130.

Each of plurality of autonomous tool systems 118 may be referred to as mobile tools or automated tools in some cases. Plurality of autonomous tool systems 118 may comprise at least one of a crawler robot, a tack driller, a hexapod, a lower panel driller, an upper panel driller, or some other suitable device.

Plurality of autonomous tool systems 118 also may be configured to drive from location to location with drivable support system 116. In this illustrative example, plurality of autonomous tool systems 118 may drive between plurality of work cells 112 as drivable support system 116 also drives between plurality of work cells 112.

In this depicted example, plurality of autonomous tool systems 118 includes autonomous tool system 131. Autonomous tool system 131 may have a number of different components in this illustrative example. For instance, autonomous tool system 131 may include at least one of a drilling system, a fastening system, a loading system, a measurement device, a coating system, an inspection system, a sealing system, a cleaning system, or other suitable types of devices configured to perform operations 130 on structure 110. Autonomous tool system 131 may take the form of automated guided vehicle 197 (AGV) in some illustrative examples.

In this illustrative example, plurality of autonomous tool systems 118 may be configured to move between plurality of work cells 112 without human intervention. For example, each of plurality of autonomous tool systems 118 may be capable of communicating with controller 122, navigating through manufacturing environment 100, and performing operations 130 without instructions from human operator 142. Each of plurality of autonomous tool systems 118 may know its position in manufacturing environment 100 relative to other tools, drivable support system 116, structure 110, and other objects.

In this illustrative example, plurality of autonomous tool systems 118 may include first portion 147 and second

portion 148. A “portion” of plurality of autonomous tool systems 118 may comprise one or more tools in this illustrative example.

As depicted, operations 130 may be performed on structure 110 in manufacturing environment 100. Operation 139 may be one of operations 130. Operation 139 may be selected from one of a drilling operation, a fastening operation, an inspecting operation, a sealing operation, a measurement operation, a leveling operation, a cleaning operation, and other suitable types of operations. When operations 130 are performed during assembly of structure 110, operations 130 may be referred to as assembly operations.

Each of plurality of autonomous tool systems 118 may perform one or more of operations 130. In this illustrative example, a number of operations 130 may be performed in each of plurality of work cells 112.

As depicted, plurality of autonomous tool systems 118 may be configured to operate simultaneously to perform operations 130 on structure 110. As used herein, when plurality of autonomous tool systems 118 perform operations “simultaneously,” two or more tools perform operations at substantially the same time.

For example, without limitation, autonomous tool system 131 may drill holes in one portion of structure 110, while another one of plurality of autonomous tool systems 118 may drill holes in a different portion of structure 110. In another illustrative example, first portion 147 of plurality of autonomous tool systems 118 may perform drilling, measuring, and fastening operations, while second portion 148 of plurality of autonomous tool systems 118 may perform sealing and coating operations.

In yet another illustrative example, first portion 147 of plurality of autonomous tool systems 118 may be positioned relative to first side 150 of structure 110 to perform drilling operations. At the same time, second portion 148 of plurality of autonomous tool systems 118 may be positioned relative to second side 151 of structure 110 to perform drilling operations.

As illustrated, metrology system 120 may include one or more measurement devices. Metrology system 120 may be configured to generate metrology data 154 for at least one of drivable support system 116, plurality of autonomous tool systems 118, structure 110, or other components within manufacturing environment 100. Metrology data 154 may be referred to as position data or position information in some examples.

In this depicted example, metrology system 120 may take the form of a photogrammetry system, a laser tracker system, an indoor global positioning system (iGPS), or other suitable types of measurement systems. Metrology system 120 may include plurality of sensor systems 156 in some illustrative examples. A sensor system in plurality of sensor systems 156 may have a number of sensors and other components. Plurality of sensor systems 156 may comprise targets, target systems, transmitters, receivers, transceivers, or other suitable components.

In this illustrative example, some of plurality of sensor systems 156 in metrology system 120 may be connected to drivable supports 135 in drivable support system 116. For example, without limitation, one of plurality of sensor systems 156 may be mounted on each of drivable supports 135 or secured to drivable supports 135 in some other manner. When some of plurality of sensor systems 156 are connected to drivable supports 135, metrology system 120 may track drivable support system 116 as drivable support system 116 moves.

When elongate platform 177 in bridge system 136 is implemented in an illustrative embodiment, some of plurality of sensor systems 156 are connected to elongate platform 177. These sensors may be used to determine the flatness of elongate platform 177.

Plurality of sensor systems 156 also may be connected to structure 110 in this illustrative example. For instance, some of plurality of sensor systems 156 may be positioned on first side 150 or second side 151 of structure 110 to serve as reference locations for metrology system 120. In other examples, one or more of plurality of sensor systems 156 are positioned at each of control points 193 on structure 110.

In an illustrative example, some of plurality of sensor systems 156 also may be positioned on each of plurality of autonomous tool systems 118. Metrology system 120 may scan plurality of sensor systems 156 using at least one of a laser, a camera, or some other suitable device to generate metrology data 154.

As illustrated, metrology data 154 may include data that indicates the location and orientation of an object in three-dimensional space. For instance, metrology data 154 may include coordinates 160 of an object associated with one of plurality of sensor systems 156. Coordinates 160 may include Cartesian coordinates for the object in global coordinate system 181.

As an example, metrology system 120 may generate coordinates 160 for autonomous tool system 131. In another illustrative example, metrology system 120 may generate coordinates 160 for a point on the surface of elongate platform 177. In still another illustrative example, metrology system 120 may generate coordinates 160 for a portion of structure 110. From coordinates 160, as well as any orientation information contained in metrology data 154, position 162 of structure 110 may be adjusted to desired position 133.

Metrology system 120 may provide feedback control 199 for flexible manufacturing system 102 based on metrology data 154. For instance, metrology system 120 may locate at least one of drivable supports 135, points on elongate platform 177, plurality of autonomous tool systems 118, control points 193 of structure 110, or other components. After locating these components, drive control system 121 may reconfigure one or more of these components as desired.

In this illustrative example, drive control system 121 comprises various components used to control movement and may include controller 122, navigator 124, and transformer 126. Controller 122, navigator 124, and transformer 126 each may be implemented in software, hardware, firmware, or a combination thereof.

When software is used, the operations performed by any one of controller 122, navigator 124, or transformer 126 may be implemented using, for example, without limitation, program code configured to run on a processor unit. When firmware is used, the operations performed by any one of controller 122, navigator 124, or transformer 126 may be implemented using, for example, without limitation, program code and data and stored in persistent memory to run on a processor unit.

When hardware is employed, the hardware may include one or more circuits that operate to perform the operations performed by any one of controller 122, navigator 124, or transformer 126. Depending on the implementation, the hardware may take the form of a circuit system, an integrated circuit, an application specific integrated circuit (ASIC), a programmable logic device, or some other suitable type of hardware device configured to perform any number of operations.

With a programmable logic device, the device may be configured to perform the number of operations. The device may be reconfigured at a later time or may be permanently configured to perform the number of operations. Examples of programmable logic devices include, for example, a programmable logic array, a programmable array logic, a field programmable logic array, a field programmable gate array, and other suitable hardware devices. Additionally, the processes may be implemented in organic components integrated with inorganic components and may be comprised entirely of organic components excluding a human being. For example, the processes may be implemented as circuits in organic semiconductors.

In some illustrative examples, the operations, processes or both performed by controller 122, navigator 124, or transformer 126 may be performed using organic components integrated with inorganic components. In some cases, the operations, processes, or both may be performed entirely by organic components, excluding a human being. As one illustrative example, circuits in organic semiconductors may be used to perform these operations, processes, or both.

In an illustrative example, controller 122 may be implemented in computer system 164. Navigator 124, transformer 126, or both also may be implemented in computer system 164. Computer system 164 may be one or more computers. When more than one computer is present in computer system 164, the computers may communicate with each other over a communications medium such as a network. In some cases, each of controller 122, navigator 124, and transformer 126 are implemented in separate computer systems.

As depicted, controller 122 may be a device configured to control operation of plurality of autonomous tool systems 118 using metrology data 154. Controller 122 may be in communication with metrology system 120, plurality of autonomous tool systems 118, and other components within flexible manufacturing system 102.

When one component is “in communication” with another component, the two components may be configured to send signals back and forth over a communications medium. For example, without limitation, controller 122 may communicate with metrology system 120 wirelessly over a network. In another illustrative example, controller 122 may communicate with other components via a wired connection.

In this depicted example, controller 122 may be configured to send commands 166 to various components within flexible manufacturing system 102. In this illustrative example, commands 166 may include navigation instructions, operation instructions, steering, position instructions, and other suitable types of instructions.

As depicted, controller 122 may send commands 166 to drivable support system 116 to change position 162 of structure 110 based on metrology data 154 generated by metrology system 120. For instance, commands 166 may be sent to drivable support system 116 when position 162 of structure 110 has deviated from desired position 133. In this case, one or more of drivable supports 135, connection devices 195, or both may actuate to move structure 110 to desired position 133 based on commands 166. After structure 110 is moved, metrology system 120 may again determine position 162 of structure 110 to provide feedback control 199.

Controller 122 also may be configured to send commands 166 to plurality of autonomous tool systems 118 in this illustrative example. For example, without limitation, controller 122 may be configured to assign tasks 111 to plurality of autonomous tool systems 118 in commands 166 sent to

plurality of autonomous tool systems 118. Each of tasks 111 may include one or more operations 130.

Further, controller 122 may be configured to monitor status 170 of tasks 111 assigned to plurality of autonomous tool systems 118 and status 172 of plurality of autonomous tool systems 118. In this illustrative example, status 170 of tasks 111 may be a state of tasks 111. For example, without limitation, status 170 may represent the number of tasks 111 that have been completed by plurality of autonomous tool systems 118. Status 170 also may include an indication of a level of completion for tasks 111. In some cases, some of tasks 111 may be performed substantially concurrently or may overlap in time.

Status 170 may include a numerical value in some illustrative examples. For instance, status 170 may indicate that fifty percent of tasks 111 are complete. In another example, status 170 may indicate the number of holes left to be drilled. In still another illustrative example, status 170 may be at least one of “complete,” “in-progress,” or other suitable states of tasks 111.

In this depicted example, status 172 may be an indicator of the state of each of plurality of autonomous tool systems 118. For example, without limitation, status 172 may indicate whether each one of plurality of autonomous tool systems 118 is online, offline, in a standby mode, in-route, or in other states of operation.

In other illustrative examples, status 172 may indicate which one of operations 130 is being performed. As an example, status 172 may indicate that inspection of a hole is being performed. In another example, status 172 may indicate that a fastener is being installed. In still another illustrative example, status 172 may indicate that autonomous tool system 131 is currently changing tools.

In this illustrative example, controller 122 may be configured to reassign tasks 111 between plurality of autonomous tool systems 118 based on at least one of status 170 of tasks 111 or status 172 of plurality of autonomous tool systems 118. As an example, controller 122 may reassign tasks 111 when autonomous tool system 131 goes offline. In this manner, assembly of wing 108 is not interrupted by autonomous tool system 131 going offline.

In another illustrative example, controller 122 may reassign tasks 111 when some of tasks 111 are complete. As a result, controller 122 may efficiently allocate resources within flexible manufacturing system 102. In assigning and reassigning tasks 111 to plurality of autonomous tool systems 118, controller 122 may be configured to change position 174 of each of plurality of autonomous tool systems 118 based on metrology data 154 generated by metrology system 120. In particular, path 176 may be generated for each of plurality of autonomous tool systems 118 based on metrology data 154.

As depicted, navigator 124 is a component in drive control system 121 that may be configured to generate path 176 for each of plurality of autonomous tool systems 118 to perform operations 130. Navigator 124 may be referred to as a navigation system in some instances.

In this illustrative example, path 176 may be a route through manufacturing environment 100. For example, without limitation, path 176 may be a route for autonomous tool system 131 to get from second location 115 to third location 117 to perform operations 130.

Path 176 may be generated and modified for each of plurality of autonomous tool systems 118 in real-time. Path 176 may change as metrology system 120 continuously locates the components in manufacturing environment 100 to provide feedback control 199.

For instance, path 176 may be generated to avoid undesired encounters between autonomous tool system 131 and other objects in manufacturing environment 100, falls from structure 110, or other undesired events. In this illustrative example, navigator 124 may generate path 176 in the form of a set of instructions, waypoints, or other information usable by autonomous tool system 131.

As depicted, transformer 126 may be in communication with navigator 124, metrology system 120, and controller 122. In some cases, such as when transformer 126 is implemented in hardware, transformer 126 may be referred to as a transformation device.

Transformer 126 may be configured to transform metrology data 154 generated by metrology system 120 to airplane coordinates 178 in airplane coordinate system 183. In this manner, transformer 126 transforms coordinates 160 to airplane coordinates 178 usable to move plurality of autonomous tool systems 118 relative to structure 110.

Airplane coordinate system 183 may represent a reference coordinate system in which airplane parts are located in three-dimensional space. Airplane coordinate system 183 may be based on an origin or reference point in aircraft 109.

In this depicted example, transformation from coordinates 160 to airplane coordinates 178 is desirable as part of positioning the plurality of autonomous tool systems with respect to structure 110. Path 176 may be generated by navigator 124 based on airplane coordinates 178 received from transformer 126 such that autonomous tool system 131 moves to a desired location relative to structure 110.

In some cases, one or more components in drive control system 121 may be remote to one another. In still other illustrative examples, controller 122 may be remote to flexible manufacturing system 102.

As depicted, loading system 127 may be a structure configured to position at least one of first skin panel 180 or second skin panel 182 relative to structure 110. In this illustrative example, first skin panel 180 may take the form of upper skin panel 184 for wing 108. Second skin panel 182 may take the form of lower skin panel 186 for wing 108.

In this depicted example, loading system 127 may comprise first loading device 188 and second loading device 190. First loading device 188, second loading device 190, or both may be selected from one of a loading platform, an elevator, a track system, a robotic arm, a gantry, and other suitable types of devices. Metrology system 120 may locate first loading device 188 and second loading device 190 to provide feedback control 199 as these devices are moved from location to location.

As depicted, first loading device 188 may be configured to position upper skin panel 184 relative to structure 110. For instance, first loading device 188 may place upper skin panel 184 on first side 150 of structure 110. Operations 130 may then be performed on upper skin panel 184 by plurality of autonomous tool systems 118.

In a similar fashion, second loading device 190 may be configured to position lower skin panel 186 relative to structure 110. As an example, second loading device 190 may place lower skin panel 186 on second side 151 of structure 110. Operations 130 may be performed on lower skin panel 186 by plurality of autonomous tool systems 118.

In this illustrative example, steering direction 196 may be provided for various components in flexible manufacturing system 102. As an example, steering direction 196 may be provided for plurality of autonomous tool systems 118, drivable support system 116, each of drivable supports 135, and other devices moving from location to location in manufacturing environment 100. Steering direction 196 may

take the form of commands, instructions, path generation, physically changing the direction of movement of the device, and other methods of guidance. In this illustrative example, steering direction 196 may dynamically change as conditions within manufacturing environment 100 change.

Steering direction 196 may be provided by at least one of controller 122, human operator 142, or some other suitable device. In other illustrative examples, each steerable device may steer itself, not under the direction of a controller.

As an example, controller 122 may send commands 166 to steer autonomous tool system 131. In yet another example, human operator 142 may steer drivable support 137 by physically changing its direction.

The reconfigurability of flexible manufacturing system 102 may allow operations 130 to be performed in an efficient manner, without undesired intervention by human operators. Controller 122 may control operation of all of the components in flexible manufacturing system 102 at the same time, taking into account the position and status of one another. Feedback control 199 provided by metrology system 120 allows for coordinated control of flexible manufacturing system 102. As a result, plurality of autonomous tool systems 118 may work simultaneously to assemble wing 108.

Moreover, each of the components within flexible manufacturing system 102 may be reconfigured depending on the size of manufacturing environment 100. Without the use of fixed monument fixtures, flexible manufacturing system 102 may provide a more efficient way of assembling wing 108 than some currently used systems.

In addition, because accuracy in performing operations 130 comes from a combination of functions provided by metrology system 120, navigator 124, and controller 122, instead of the structural rigidity of a fixed monument fixture, drivable supports 135 may comprise lighter materials or fewer materials than a fixed monument fixture. As a result, drivable supports 135 may be lighter and cost less.

As another desirable feature, the use of elongate platform 177 may require fewer sensors to accurately locate and adjust the position of structure 110. For example, without limitation, instead of positioning one of plurality of sensor systems 156 on each of control points 193, connection devices 195, or both, several sensors can be placed on the surface of elongate platform 177 to determine its flatness. One or more portions of elongate platform 177 is then adjusted to bring structure 110 into alignment. The use of fewer sensors may further reduce up-front set up costs.

The illustration of flexible manufacturing system 102 in FIG. 1 is not meant to imply physical or architectural limitations to the manner in which an illustrative embodiment may be implemented. Other components in addition to or in place of the ones illustrated may be used. Some components may be optional. Also, the blocks are presented to illustrate some functional components. One or more of these blocks may be combined, divided, or combined and divided into different blocks when implemented in an illustrative embodiment.

For example, without limitation, more than one of structure 110 may be present in manufacturing environment 100 at the same time. When more than one of structure 110 is present in manufacturing environment 100, components may be added to each structure 110 simultaneously to form multiple wings. The ability to reconfigure plurality of autonomous tool systems 118 may allow the same set of tools to be used on multiple wing assemblies at the same time, increasing the rate of production of wings for aircraft.

In another illustrative example, additional sensor systems may be implemented in the components in flexible manu-

facturing system **102**. For instance, each of plurality of autonomous tool systems **118** may include a sensor system configured to generate position information, measure depth of holes, or perform other processes.

As yet another illustrative example, each of the components within flexible manufacturing system **102** may comprise a separate controller configured to control operations of that particular device. Each of these controllers may communicate with controller **122**.

In still another illustrative example, plurality of autonomous tool systems **118** work in tandem with human operators within manufacturing environment **100**. As an example, a number of human operators may be present in plurality of work cells **112** to oversee progress of flexible manufacturing system **102**, perform additional operations **130**, or for some other reason.

As another example, flexible manufacturing system **102** may include a movement system. This movement system may be configured to move drivable support system **116** between plurality of work cells **112**. In this case, the movement system may include a track system, wheels, a tug, an automated guided vehicle (AGV), or some other suitable type of movement device. In another illustrative example, the movement system may be integrated in drivable support system **116** and retract when drivable support system **116** reaches its destination within a work cell.

In another illustrative example, additional sensor systems may be employed to generate various types of information with respect to the components in flexible manufacturing system **102**, structure **110**, or both. For example, without limitation, force sensors, also referred to as load sensors, may be used in load balancing. These load sensors may be implemented at various points along the length of elongate platform **177** to determine loads applied to elongate platform **177** by structure **110**. From this sensor feedback, elongate platform **177** may be moved such that overloading does not occur.

With reference now to FIG. 2, an illustration of an isometric view of a manufacturing environment is depicted in accordance with an illustrative embodiment. In this depicted example, manufacturing environment **200** with work cells **202** may be an example of a physical implementation for manufacturing environment **100** with plurality of work cells **112** shown in block form in FIG. 1.

As illustrated, wing assemblies **204** may move through work cells **202**. Each of wing assemblies **204** may be an example of a physical implementation for structure **110** in FIG. 1. In each of work cells **202**, operations may be performed on wing assemblies **204** to form wings for an aircraft (not shown in this view).

As illustrated, manufacturing environment **200** may include flexible manufacturing system **206** to perform operations on wing assemblies **204**. Flexible manufacturing system **206** may provide pulsed continuous movement of wing assemblies **204**. Pulsed continuous movement may be movement from one of work cells **202** to another one of work cells **202**, stopping within each work cell temporarily for operations to be performed.

Flexible manufacturing system **206** may include drivable support system **208**, autonomous tool systems **210**, metrology system **212**, and system controller **214**. Drivable support system **208**, autonomous tool systems **210**, metrology system **212**, and system controller **214** may be examples of physical implementations for drivable support system **116**, plurality of autonomous tool systems **118**, metrology system **120**, and controller **122** shown in block form in FIG. 1.

All of the components within flexible manufacturing system **206** may move throughout manufacturing environment **200** between work cells **202**. In this manner, components may move from location to location in work cells **202** to perform operations on any one of wing assemblies **204**. Flexible manufacturing system **206** also may be reconfigurable based on the layout and size of manufacturing environment **200**, the size and manufacturing needs of wing assemblies **204**, and other suitable parameters.

In this illustrative example, a wing assembly (not shown in this view) may move between work cell **216**, work cell **218**, work cell **220**, work cell **222**, and work cell **224** as operations are being performed. The wing assembly may be carried between these work cells by various components in flexible manufacturing system **206**. In addition, components within flexible manufacturing system **206** drive from work cell to work cell to move with the wing assembly in this illustrative example.

FIGS. 3-16 show the progression of an assembly process using flexible manufacturing system **206** in manufacturing environment **200** from FIG. 2. FIGS. 3-16 show a wing assembly moving through various work cells **202**.

Turning to FIG. 3, an illustration of a work cell with wing assembly components staged for installation is depicted in accordance with an illustrative embodiment. In this depicted example, work cell **216** is shown.

As depicted, components for wing assembly **302** may be present in work cell **216**. In particular, structural members **304** for wing assembly **302** may be present in work cell **216**. Wing assembly **302** may be an example of a physical implementation for structure **110** shown in FIG. 1.

In work cell **216**, structural members **304** may be staged. Structural members **304** may be units that provide structural support and load handling capability for a wing (not shown).

Structural members **304** may include spars **306** and ribs **308** in this illustrative example. Additionally, a number of adapter fittings, hinges, and other components may be staged in work cell **216**.

In FIG. 4, an illustration of drivable support system **208** from FIG. 2 positioned in a work cell is depicted in accordance with an illustrative embodiment. In this depicted example, drivable support system **208** is positioned in work cell **218**.

As depicted, drivable support system **208** may include supports **402**. Supports **402** may be an example of a physical implementation for drivable supports **135** shown in block form in FIG. 1. Each of supports **402** drives from location to location within manufacturing environment **200**. When supports **402** come together to form drivable support system **208**, supports **402** move collectively from work cell to work cell as operations are performed on wing assembly **302**.

In this illustrative example, each of supports **402** may be moved from another location in manufacturing environment **200** to reach work cell **218**. As an example, each of supports **402** may be moved and arranged relative to one another to form drivable support system **208**, a non-fixed fixture. A platform (not shown in this view) may connect supports **402** to one another in some illustrative examples.

In an illustrative example, each of supports **402** may be interchangeable. In other words, supports **402** may be capable of being used in place of one another. In this manner, reconfiguring supports **402** may be done more quickly than if supports **402** had to be arranged in a particular order.

Supports **402** bring parts (not shown) of wing assembly **302** together from various locations in manufacturing environment **200**. As an example, one of supports **402** may bring a portion of wing assembly **302** from work cell **216**, while

25

another one of supports 402 may bring a different portion of wing assembly 302 from work cell 216. In another illustrative example, supports 402 may be arranged first and then wing assembly 302 may be connected to supports 402 thereafter. Each of supports 402 may have connection devices (not shown) that are connected to a different portion of wing assembly 302 at different control points (not shown).

In some illustrative examples, some of supports 402 may be brought together to form drivable support system 208 and carry wing assembly 302 from one location to a second location in manufacturing environment 200. At the same time, other supports 402 may be brought together into another type of non-fixed fixture, or second drivable support system, to carry another portion of wing assembly 302 from yet another location in manufacturing environment 200 to the second location or some other location.

In this case, drivable support system 208 and the second drivable support system may combine into a new collective to form a new non-fixed fixture. Subsequently, additional supports 402 may be added or removed as desired, bringing parts to wing assembly 302 at various locations. In this manner, the illustrative embodiments allow several collectives of supports 402 to come together at different points and times during the assembly process to form new non-fixed fixtures bringing the assemblies they carry into inclusion in a larger overarching assembly.

Support 403 may be an example of one of supports 402. Support 403 may be a module that is interchangeable with other supports 402 in this illustrative example.

In this depicted example, supports 402 may be arranged adjacent to one another within work cell 218. First portion 404 of supports 402 may be positioned opposite second portion 406 of supports 402 to hold wing assembly 302 in a horizontal configuration.

As illustrated, wing assembly 302 may be received by drivable support system 208. Wing assembly 302 may be moved in the direction of arrow 414 to be received by drivable support system 208. In other illustrative examples, a group of supports 402 may pick up a portion of wing assembly 302 and bring it to work cell 218, much like a human operator would bring different parts to the assembly to facilitate attachment of those parts.

Referring next to FIG. 5, an illustration of drivable support system 208 with wing assembly 302 from FIG. 4 is depicted in accordance with an illustrative embodiment. Wing assembly 302 has been driven in the direction of arrow 414.

In this depicted example, first portion 404 of supports 402 may hold side 500 of wing assembly 302. In a similar fashion, second portion 406 may hold side 502 of wing assembly 302. Supports 402 may be adjusted vertically in the direction of arrow 503 to accommodate a desired height for wing assembly 302. The desired height may change between work cells 202, depending on the type of operations being performed.

As depicted, each of supports 402 may be secured to wing assembly 302 at different points along side 500 and side 502 of wing assembly 302. Supports 402 may be connected to wing assembly 302 using any mechanical method configured to hold wing assembly 302 in a desired manner. For example, without limitation, supports 402 may clamp wing assembly 302 in position using connection devices (not shown).

In this illustrative example, bridge system 504 has been connected to drivable support system 208. Human operators 506 may use bridge system 504 to access and view wing

26

assembly 302. Bridge system 504 and human operators 506 may be examples of physical implementations for bridge system 136 and human operator 142 shown in block form in FIG. 1.

As depicted, rail system 508 may be associated with bridge system 504. Rail system 508 may be an example of a physical implementation for rail system 138 shown in block form in FIG. 1.

Rail system 508 may include rails 510 on bridge system 504. Rails 510 may reduce the risk of human operators 506 falling off bridge system 504. In this manner, rail system 508 may provide fall protection for human operators 506.

Various operations may be performed while wing assembly 302 is in work cell 218. For example, without limitation, ribs 308 may be drilled and fastened.

Additionally, wing assembly 302 may be scanned by metrology system 212 to analyze the position of structural members 304 in wing assembly 302. Metrology system 212 relies on various sensors (not shown in this view) to determine the position of structural members 304. System controller 214 may be in communication with metrology system 212 and compare the position of structural members 304 to a desired position. Adjustments may be made in response to this comparison. Metrology system 212 may provide feedback control as the adjustments are made until a desired position is reached.

In yet another illustrative example, wing assembly 302 may be leveled and a front spar hinge line may be set. Panel 512 may then be positioned relative to side 514 of wing assembly 302. Panel 512 may be an example of a physical implementation for upper skin panel 184 shown in FIG. 1. Panel 512 is moved in the direction of arrow 414 to be placed on top of wing assembly 302 in this illustrative example.

In FIG. 6, an illustration of wing assembly 302 and drivable support system 208 shown in the direction of lines 6-6 in FIG. 5 is depicted in accordance with an illustrative embodiment. Bridge system 508 has been removed such that components within drivable support system 208 may be seen in greater detail.

In this illustrative example, various support structures may be placed between each of supports 402 to create platform 600. Platform 600 may be a continuous platform in this illustrative example. Tow gate 602 also may be added to connect first portion 404 of supports 402 with second portion 406 of supports 402. Tow gate 602 may be configured to connect to a tug or other movement system to move drivable support system 208 between work cells 202 shown in FIG. 2.

In this depicted example, human operators 506 may move about work cell 218. Human operators 506 may monitor the assembly process for wing assembly 302, perform operations, or both. In this illustrative example, human operators 506 may have access to all portions of wing assembly 302.

With reference next to FIG. 7, an illustration of a loading device loading a panel on wing assembly 302 from FIG. 6 is depicted in accordance with an illustrative embodiment. In this depicted example, loading device 700 has moved panel 512 in the direction of arrow 414 in FIG. 6. Loading device 700 may be an example of a physical implementation for first loading device 188 shown in block form in FIG. 1.

Loading device 700 may place panel 512 on side 514 of wing assembly 302 in this illustrative example. Operations may then be performed on panel 512.

In this depicted example, rails 702 may be positioned on panel 512 of wing assembly 302. Rails 702 may be part of rail system 508 and may be configured to reduce the risk of

human operators **506** falling from wing assembly **302**. Rails **702** also may separate human operators **506** from undesired encounters with autonomous tool systems **210** shown in FIG. 2.

In FIG. 8, an illustration of a portion of autonomous tool systems **210** from FIG. 2 performing operations on panel **512** from FIG. 7 is depicted in accordance with an illustrative embodiment. In this depicted example, a portion of autonomous tool systems **210** may be deployed onto surface **800** of panel **512**.

As illustrated, drilling devices **802** may be deployed on surface **800** of panel **512**. Drilling devices **802** may be examples of physical implementations for plurality of autonomous tool systems **118** shown in block form in FIG. 1. Drilling devices **802** may take the form of tack drillers in this illustrative example.

In this illustrative example, drilling devices **802** may be autonomous devices configured to drill holes in panel **512** and install tack fasteners (not shown in this view). These tack fasteners provide clamp up at select locations to help mitigate shimming, misalignment, or other issues for structural members **304** shown in FIGS. 3-6. Tack driller **804** shown in section **806** of wing assembly **302** may be one of drilling devices **802**.

In this depicted example, drilling devices **802** may move about surface **800** of panel **512** at the same time, performing drilling and fastening operations simultaneously at different locations on panel **512**. Drilling devices **802** communicate with system controller **214** shown in FIG. 2. Specifically, drilling devices **802** may receive instructions from system controller **214**. These instructions may include a path of movement and the different operations to be performed.

Position feedback may be generated about each of drilling devices **802**. This feedback may be generated by metrology system **212**, active components on drilling devices **802**, or a combination thereof. For instance, as drilling devices **802** move about panel **512**, drilling devices **802** may continuously provide feedback to system controller **214**. This feedback may include position information, status, results of an inspection performed on panel **512**, and other suitable information.

System controller **214** then uses this feedback to reposition drilling devices **802**, to ensure holes are drilled in the correct location, to avoid collisions between drilling devices **802**, and to more efficiently assign tasks between drilling devices **802**. As a result, each of drilling devices **802** may move along surface **800** of panel **512** without undesired encounters with one another or human operators **506**, falling off wing assembly **302**, drilling holes in undesired locations, or a combination thereof.

In some illustrative examples, after drilling devices **802** have completed their drilling and fastening operations, human operators **506** may perform additional operations on panel **512**. For example, without limitation, human operators **506** may locate, drill, and install components on the underside (not shown) of panel **512**. These components may include shear ties, stringer end fittings, disbond arrest fasteners, and other suitable components. In other illustrative examples, other autonomous tool systems **210** may install these components.

In some illustrative examples, additional components may be included in work cell **218**. For instance, a counterbalance system (not shown in this view) may be connected to each of drilling devices **802**. In this illustrative example, the counterbalance system may be configured to offset the weight of one of drilling devices **802**. For instance, the counterbalance system may be removably attached to tack

driller **804** and may include pulleys, weights, connectors, cables, and other components.

Subsequent to the tack drilling process, drilling devices **802** may be removed from surface **800** of panel **512**. Panel **512** may then be unloaded by loading device **700** for deburring, cleaning, and sealing (removal not shown in this view).

In this illustrative example, drivable support system **208** with wing assembly **302** may be moved to work cell **220** as shown in FIG. 10. Drivable support system **208** with wing assembly **302** may be moved in the direction of arrow **808** to work cell **220**.

Referring now to FIG. 9, an illustration of section **806** of wing assembly **302** from FIG. 8 with tack driller **804** is depicted in accordance with an illustrative embodiment. In this depicted example, tack driller **804** may move along surface **800** of panel **512** using movement system **900**.

Tack driller **804** may have on-board controller **902**. On-board controller **902** communicates with system controller **214** shown in FIG. 2 and receives instructions to navigate surface **800** of panel **512**. On-board controller **902** for tack driller **804** may establish a local coordinate system by synchronizing on magnets that are pre-installed in wing assembly **302**.

Tool **904** on tack driller **804** may be used to drill holes and insert the tack fasteners. Human operators **506** may manually install a nut on each tack fastener and tighten within selected tolerances.

To protect the safety of human operators **506**, system controller **214** may control movement of drilling devices **802**, including tack driller **804**, to avoid human operators **506**. In some examples, drilling devices **802** are taken offline completely. In other illustrative examples, rail system **508** is modified to separate drilling devices **802** from human operators **506**. In still other illustrative examples, other safety measures may be provided. For instance, a group of proximity sensors may be used to sense human operators **506** and adjust the behavior of drilling devices **802** accordingly.

In FIG. 10, an illustration of autonomous tool systems **210** performing operations on panel **512** from FIG. 8 is depicted in accordance with an illustrative embodiment. Drivable support system **208** with wing assembly **302** has been moved in the direction of arrow **808** to work cell **220**. Work cell **220** may be an example of a physical implementation for one of plurality of work cells **112** shown in FIG. 1.

As depicted, crawler robots **1001** may be placed on surface **800** of panel **512** by crawler support **1002**. Crawler support **1002** may include drivable platforms in this illustrative examples. In other cases, when used with autonomous tool systems other than crawler robots **1001**, crawler support **1002** may be referred to as autonomous tool system support. These drivable platforms may be configured to drive across the floor of manufacturing environment **200** and place the group of crawler robots **1001** on surface **800** of the structure, in this case, panel **512**.

Crawler robots **1001** with crawler support **1002** may be examples of physical implementations for plurality of autonomous tool systems **118** in FIG. 1. Each of crawler robots **1001** may include a flextrack system in this illustrative example.

One of crawler robots **1001** may correspond to one of crawler support **1002** in this illustrative example. In addition to placing crawler robots **1001** on surface **800** of panel **512**, crawler support **1002** may provide power, move utility cables, or assist crawler robots **1001** with other processes. Crawler robot **1004** and drivable platform **1006** are shown in section **1008** of wing assembly **302**.

In this depicted example, crawler robots **1001** may be autonomous devices configured to drill countersunk holes in panel **512**, inspect the holes and the countersink depth of those holes, install fasteners (not shown in this view), and inspect the installed fasteners. These fasteners may be interference fit fasteners in this illustrative example.

In an illustrative example, an “interference fit” fastener may have a shank with a diameter that is greater than the diameter of the cylindrical portion of the hole in which it is installed. Friction between the post and the cylindrical portion of the hole holds the fastener in place. The interference fit of the fastener may increase the fatigue life of the parts that the fastener is connecting, namely, panel **512** and its substructure. The interference fit fastener also may substantially prevent fastener movement relative to the hole.

In this depicted example, crawler robots **1001** may move about surface **800** of panel **512** at the same time, performing drilling and fastening operations simultaneously at different locations on panel **512**. Crawler robots **1001** may communicate with system controller **214** shown in FIG. **2**.

In particular, crawler robots **1001** may receive instructions from system controller **214**. These instructions may include a path of movement and the different operations to be performed. Throughout movement, crawler robots **1001** may continuously provide feedback to system controller **214**. This feedback may include position information, status, results of inspection performed on panel **512**, and other suitable information.

System controller **214** then uses this feedback to reposition crawler robots **1001**, to ensure holes are drilled in the correct location, to avoid collisions between crawler robots **1001**, and to more efficiently assign tasks between crawler robots **1001**. As a result, each of crawler robots **1001** may move along surface **800** of panel **512** without undesired encounters with one another or human operators **506**, falling off wing assembly **302**, or both. Additionally, the feedback increases accuracy of operations performed by crawler robots **1001**. Feedback also may be provided by metrology system **212** as metrology system **212** scans manufacturing environment **200**, as described above.

Crawler robots **1001** may be configured to provide “one-up assembly” of fasteners in panel **512**. In this illustrative example, “one-up” assembly may refer to the process of drilling and fastening joints without having to disassemble parts for cleaning or deburring. One-up assembly may increase the speed at which wings are manufactured. In this illustrative example, crawler robots **1001** include crawler robot **1004**.

After one-up assembly is performed using crawler robot **1004**, crawler robot **1004** may be removed using drivable platform **1006**. Wing assembly **302** with drivable support system **208** may be moved in the direction of arrow **1010** to work cell **222** as shown in FIG. **12**.

FIG. **11** shows an illustration of section **1008** of wing assembly **302** with crawler robot **1004** and drivable platform **1006** from FIG. **10** in accordance with an illustrative embodiment. In this illustrative example, crawler robot **1004** may be equipped with movement system **1100**, movement system **1101**, and tools **1102**.

As depicted, movement system **1100** may comprise wheels that move crawler robot **1004** along surface **800** of panel **512**. These wheels may be retractable in some illustrative examples.

Movement system **1101** may include a track system in this illustrative example. Movement system **1101** may be configured to move crawler robot **1004** back and forth in the direction of arrow **1104**.

As illustrated, tools **1102** may include at least one of an inspection system, a fastener system, a drilling system, a positioning system, or other suitable tools. Crawler robot **1004** also may include on-board controller **1106** in communication with system controller **214** in FIG. **2**.

Drivable platform **1006** may have pick and place arm **1108** and utility arm **1110** in this illustrative example. Pick and place arm **1108** may place crawler robot **1004** onto surface **800** of wing assembly **302**. Utility arm **1110** may move utility cables (not shown in this view) that may be attached to crawler robot **1004**. These utility cables may supply tools **1102** with at least one of electricity, air supply, communications, or other desirable utilities.

In this illustrative example, counterbalance system **1112** may be associated with utility arm **1110** and connected to crawler robot **1004**. Counterbalance system **1112** may be configured to offset the weight of crawler robot **1004** on panel **512**. Counterbalance system **1112** may be removably attached to crawler robot **1004** in this illustrative example.

In an illustrative example, counterbalance system **1112** may comprise cable **1113**, pulley **1114** attached to utility arm **1110** and weight **1116**. Weight **1116** may be less than or equal to the weight of crawler robot **1004**. Counterbalance system **1112** with weight **1116** reduces the risk of inconsistencies forming in panel **512** that could be caused by the weight of crawler robot **1004**. In other illustrative examples, other counterbalance systems may be possible.

Turning next to FIG. **12**, an illustration of a loading device with a panel is depicted in accordance with an illustrative embodiment. In this depicted example, loading device **1200** is shown carrying panel **1202** for wing assembly **302**.

Wing assembly **302** and drivable support system **208** have been moved in the direction of arrow **1010** to work cell **222**. Loading device **1200**, panel **1202**, and work cell **222** may be examples of physical implementations for second loading device **190**, lower skin panel **186**, and one of plurality of work cells **112**, respectively, shown in block form in FIG. **1**.

As depicted, loading device **1200** may move panel **1202** in the direction of arrow **1206** to position panel **1202** under wing assembly **302**. Loading device **1200** may then lift panel **1202** into a desired position relative to side **1208** of wing assembly **302**.

Operations may be performed on panel **1202** by assembly systems **1210**. Assembly systems **1210** may include a lower panel tool system in this illustrative example. This lower panel tool system may take the form of a lower panel driller.

In FIG. **13**, an illustration of loading device **1200** with panel **1202** from FIG. **12** is depicted in accordance with an illustrative embodiment. In this illustrative example, loading device **1200** may comprise platform **1300**, movement system **1302**, and movement system **1304**.

As depicted, platform **1300** may be a structure configured to provide support for movement system **1304** and panel **1202**. Movement system **1302** may be a number of components configured to move loading device **1200** with panel **1202** about manufacturing environment **200**. In this depicted example, movement system **1302** may include at least one of a track system, mecanum wheels, omni wheels and other types of omni-directional wheels, retractable wheels, a gantry system, a tug, or some other suitable movement device.

In this illustrative example, movement system **1304** may be a group of devices configured to move panel **1202** up and down in the direction of arrow **1306**. As used herein, a “group of” items may be one or more items. In this illustrative example, a group of devices may include one or more devices.

In this manner, movement system **1304** may position panel **1202** relative to side **1208** of wing assembly **302** in FIG. **12**. Position feedback may be generated for the components within loading device **1200**, panel **1202**, or both, as described above.

Movement system **1304** may be a lift in this illustrative example. This lift may be a hydraulic lift, a pneumatic lift, or some other suitable type of lift. In particular, movement system **1304** may employ a scissor jack, a bottle jack, and other suitable types of lifts. In some cases, movement system **1304** also may be configured to tilt panel **1202** as needed. Movement system **1304** may provide crude positioning of panel **1202** relative to wing assembly **302** (not shown in this view).

In this depicted example, movement system **1304** may include repositionable headers **1308**. Repositionable headers **1308** may contact panel **1202**. In this illustrative example, repositionable headers **1308** may be structures configured to position panel **1202** in a desired manner. Repositionable headers **1308** may provide more precise positioning for panel **1202** relative to wing assembly **302**.

As illustrated, utility cable **1310** may be used to connect loading device **1200** with various utilities. For example, without limitation, utility cable **1310** may be used to provide electricity to loading device **1200**. Utility cable **1310** also may provide a communications link between system controller **214** and loading device **1200** for command and control of loading device **1200**.

With reference next to FIG. **14**, an illustration of assembly systems **1210** performing operations on panel **1202** from FIG. **12** is depicted in accordance with an illustrative embodiment. In this depicted example, loading device **1200** has moved panel **1202** in the direction of arrow **1206**.

In this depicted example, operations may have been performed on panel **1202** to secure panel **1202** to side **1208** of wing assembly **302**. For instance, tack drilling and fastening may have been performed to hold panel **1202** in place relative to side **1208** of wing assembly **302**.

In this depicted example, assembly systems **1210** may be deployed under panel **1202**. Assembly systems **1210** may be an example of a physical implementation for plurality of autonomous tool systems **118** shown in block form in FIG. **1**. Assembly systems **1210** may include a hexapod in this illustrative example.

As depicted, assembly systems **1210** may be autonomous devices configured to perform operations on panel **1202**. For example, without limitation, assembly systems **1210** may clamp structures, drill holes, measure holes, install fasteners, seal fasteners, and perform other types of operations on panel **1202**. In an illustrative example, assembly systems **1210** may move under panel **1202** in the direction of arrow **1206** to perform these operations. In this illustrative example, assembly system **1400** and one of assembly systems **1210** moves under panel **1202** in the direction of arrow **1206** to perform such operations.

In some cases, the position of wing assembly **302** may need to be adjusted to accommodate assembly systems **1210**. In an illustrative example, system controller **214** communicates with drivable support system **208** to move wing assembly **302** vertically in the direction of arrow **503** as needed.

In this depicted example, each of assembly systems **1210** may move under panel **1202** at the same time, performing drilling and fastening operations simultaneously at different locations along panel **1202**. Assembly systems **1210** may communicate with system controller **214** shown in FIG. **2**.

Assembly systems **1210** may receive instructions from system controller **214** and provide feedback to system controller **214**. Metrology system **212** also may provide feedback to locate each of assembly systems **1210**. In this manner, system controller **214** may tightly control the operations of assembly systems **1210**. Each of assembly systems **1210** may move under panel **1202** without undesired encounters with one another or human operators, movement beyond the work area, or both.

In some illustrative examples, assembly systems **1210** may perform drilling and fastening operations in more than one of work cells **202**. For instance, assembly systems **1210** may drill a first portion of the holes needed in panel **1202** (not shown). After the first portion is drilled, panel **1202** may need to be lowered from side **1208** of wing assembly **302** to be cleaned and deburred.

In this case, panel **1202** may then be reattached to wing assembly **302** and a second portion of the holes may be drilled in panel **1202**. Assembly systems **1210** may perform one-up assembly on the remaining fasteners for the second portion of the holes. In other cases, operations may be performed by assembly systems **1210** in some other manner, depending on the particular implementation.

After operations in work cell **222** are completed, drivable support system **208** with wing assembly **302** may move to work cell **224** shown in FIG. **16**. Drivable support system **208** with wing assembly **302** may move in the direction of arrow **1404** to work cell **224** in this illustrative example.

Turning now to FIG. **15**, an illustration of assembly system **1400** performing operations on a surface of wing assembly **302**, shown in the direction of lines **15-15** in FIG. **14**, is depicted in accordance with an illustrative embodiment. In this depicted example, assembly system **1400** has moved in the direction of arrow **1206** in FIG. **14** to be positioned relative to surface **1500** of panel **1202**.

As depicted, assembly system **1400** may be equipped with movement system **1502**, motion platform **1504**, and tools **1506** on end effector **1508**. Movement system **1502** may move assembly system **1400** into a desired area. Motion platform **1504** then may be used to precisely position end effector **1508** with tools **1506** relative to surface **1500** of panel **1202**.

Assembly system **1400** may include on-board controller **1510** configured to communicate with system controller **214** in FIG. **2**. As assembly system **1400** moves, assembly system **1400** may provide position feedback to system controller **214**. Metrology system **212** also may track the position of assembly system **1400**.

In this illustrative example, movement system **1502** may comprise wheels that move assembly system **1400** under surface **1500** of panel **1202**. These wheels may be retractable once assembly system **1400** is in a desired position.

Motion platform **1504** may provide seven degrees of freedom of movement for tools **1506** in this illustrative example. In an illustrative example, degrees of freedom may refer to the movement of tools **1506** in three-dimensional space.

As illustrated, tools **1506** may be arranged on end effector **1508** attached to motion platform **1504**. Tools **1506** may include at least one of an inspection system, a clamping system, a sensor system, a fastener system, a drilling system, a positioning system, or other suitable tools.

When tools **1506** include an inspection system, the inspection system may inspect the holes drilled by assembly system **1400**. The inspection system also may inspect the

fasteners installed by assembly system **1400**. Inspection results may be communicated to system controller **214** in some cases.

In FIG. **16**, an illustration of a wing in work cell **224** is depicted in accordance with an illustrative embodiment. In this depicted example, drivable support system **208** with wing assembly **302** has moved into work cell **224** in the direction of arrow **1404** in FIG. **14**.

Overhead assembly system **1600** may perform operations on panel **512** in this illustrative example. Overhead assembly system **1600** may be another example of a physical implementation for one of plurality of autonomous tool systems **118** shown in block form in FIG. **1**.

In this illustrative example, overhead assembly system **1600** may include motion platform **1602** with tools **1604** on end effector **1606**. Motion platform **1602**, tools **1604**, and end effector **1606** may be implemented in a manner similar to motion platform **1504**, tools **1506**, and end effector **1508**, as described above.

Motion platform **1602** may be roughly positioned above panel **512** using overhead support system **1608** equipped with movement system **1610**. More precise positioning of motion platform **1602**, as well as end effector **1606**, is provided by various other moving components associated with overhead assembly system **1600**. Overhead assembly system **1600** also may include on-board controller **1612** that communicates with system controller **214** and other components.

After overhead assembly system **1600** performs its operations on wing assembly **302**, operations within manufacturing environment **200** now may be complete. A dolly (not shown in this view) may be positioned under wing assembly **302** as supports **402** are separated.

Wing assembly **302** may continue with assembly work that does not require precision fixturing until wing assembly **302** is needed for installation in an aircraft. Drivable support system **208**, including all or a portion of supports **402**, may be moved back to work cell **216** to receive another wing assembly.

With reference next to FIG. **17**, an illustration of a top view of work cell **224**, shown in the direction of lines **17-17** in FIG. **16** is depicted in accordance with an illustrative embodiment. In this view, various autonomous tool systems **210** perform operations simultaneously on wing assembly **302**. Under the coordinated control of system controller **214**, each of autonomous tool systems **210** may perform operations on wing assembly **302** without colliding with one another and/or falling off of wing assembly **302**, and so forth.

Referring next to FIG. **18**, an illustration of manufacturing environment **200**, shown in the direction of lines **18-18** in FIG. **16**, is depicted in accordance with an illustrative embodiment. As shown in this view, wing assemblies **204** are being manufactured throughout various work cells **202**.

In this illustrative example, work cells **202** are arranged in configuration **1800**. Configuration **1800** is a u-shaped configuration in this illustrative example. As depicted, the components within flexible manufacturing system **206** have been rearranged from the configuration shown in FIGS. **2-17** to form configuration **1800**. Because no fixed monument fixtures are used, complete reconfiguration of flexible manufacturing system **206** is possible.

Further, because all of autonomous tool systems **210** used to manufacture wing assemblies **204** are drivable and are not fixed to the floor, those tools may drive from work cell to work cell, regardless of what configuration of manufacturing

environment **200** is desired. Unlike many existing assembly line solutions, an illustrative embodiment completely alleviates the need for, and requirement for, fixed monument fixtures holding a wing assembly, fixed tooling, tools that are fixed to the manufacturing facility, and other inflexible structures.

In other illustrative examples, the components within flexible manufacturing system **206** may be reconfigured in some other manner. In an example, wing assemblies **204** may be pulsed laterally.

Since autonomous tool systems **210** are free to move about manufacturing environment **200**, different autonomous tool systems **210** may be used to manufacture wing assemblies **204** in various work cells **202** at the same time. As a result, multiple wing assemblies **204** may be continuously pulsed through manufacturing environment **200** to increase the efficiency of the manufacturing process. This increase in efficiency leads to a higher production rate than with some currently used systems.

Each of the components within manufacturing environment **200** may be reconfigured in this illustrative example. For instance, when a different type of wing is being manufactured, the type of autonomous tool systems **210** used may be different. Further, some of autonomous tool systems **210** may not be needed.

In still other illustrative examples, supports **402** may hold wing assembly **302** in a vertical configuration. In this case, autonomous tool systems **210** may be configured to function differently to perform operations on wing assembly **302**.

As another example, the size of wing assembly **302** may require additional supports **402** to be added to drivable support system **208**, additional autonomous tool systems **210** to be used, or a combination thereof. The size of work cells **202** also may be adjusted depending on the length of wing assembly **302**. In each case, the components within flexible manufacturing system **206** are reconfigured to meet different manufacturing needs.

FIGS. **19-21** show an alternative implementation for a mobile support system. In FIGS. **19-21**, a bridge system with elongate platforms is shown. Instead of being attached to connection devices on each drivable support, the illustrative examples in FIGS. **19-21** employ connection devices positioned along the length of an elongate platform.

Referring to FIG. **19**, an illustration of a drivable support system with elongate platforms is depicted in accordance with an illustrative embodiment. In this illustrative example, drivable support system **1900** is shown in work cell **1901**. Work cell **1901** may be an example of yet another physical implementation for one of plurality of work cells **112** shown in block form in FIG. **1**. Work cell **1901** may be part of manufacturing environment **200**, shown in FIG. **2**, or may be positioned in a different facility.

As depicted, drivable support system **1900** includes drivable supports **1902**, elongate platform **1904**, and elongate platform **1906**. Drivable support system **1900** and drivable supports **1902** are examples of physical implementations for drivable support system **116** and drivable supports **135**, respectively, shown in block form in FIG. **1**. Elongate platform **1904** and elongate platform **1906** are both examples of physical implementations for elongate platform **177** in FIG. **1**.

As illustrated, first group **1908** of drivable supports **1902** may be connected to elongate platform **1904**. Second group **1910** of drivable supports **1902** may be connected to elongate platform **1906**. Elongate platform **1904**, elongate platform **1906**, or both may have a shape that corresponds to a desired shape of a wing.

Each of first group **1908** and second group **1910** of drivable supports **1902** include seven supports evenly spaced underneath a respective elongate platform. Drivable supports **1902** are automated guided vehicles in this example.

In other illustrative examples, other numbers of drivable supports **1902** may be used under each beam, depending on the particular implementation. Spacing between each support also may vary.

In this illustrative example, first group **1908** of drivable supports **1902** may move elongate platform **1904** into a desired position. For example, first group **1908** of drivable supports **1902** may collectively move elongate platform **1904** with respect to a number of axes **1912** to position elongate platform **1904** relative to wing assembly **1914**.

In a similar fashion, second group **1910** of drivable supports **1902** may collectively move elongate platform **1906** with respect to axes **1912** to position elongate platform **1904** relative to wing assembly **1914**. Wing assembly **1914** is an example of a physical implementation for structure **110** shown in block form in FIG. 1.

In an illustrative example, a first group of connection devices **1916** are associated with elongate platform **1904**. Connection devices **1916** may be positioned along a length of elongate platform **1904** as shown in this view.

A second group of connection devices **1918** may be associated with elongate platform **1906**. Connection devices **1918** may be positioned along a length of elongate platform **1906** in this illustrative example.

Connection devices **1916** and connection devices **1918** may correspond to connection points (obscured in this view) on wing assembly **1914**. Connection devices **1916** and connection devices **1918** hold wing assembly **1914** in a desired position. As an example, connection device **1917** connects to point **1919** on wing assembly **1914**.

Point **1919** may be a connection point that is independently movable using connection device **1917**. Point **1919** may be a control point as well as a connection point. In other cases, point **1919** may simply be a fixed connection point that only moves as the elongate platform moves. Connection device **1917** is shown in section **1921** in this illustrative example.

As depicted, human operators **1920** move about elongate platform **1904** and elongate platform **1906**. In addition, various autonomous tool systems (not shown in this view) may move about drivable support system **1900** to perform operations on wing assembly **1914**.

In this depicted example, each of drivable supports **1902** may be equipped with a movement system configured to move its corresponding elongate platform with respect to axes **1912**. Such movement may include translation, rotation, or some other suitable movement. Drivable supports **1902** dynamically adjust the elongate platforms to keep wing assembly **1914** in alignment, compensate for uneven terrain in the manufacturing environment, allow autonomous tool systems access to wing assembly **1914**, balance the load of wing assembly **1914** at any given point, reduce deflection in the beam, or some combination thereof. For example elongate platform **1904** may be moved using a movement system on at least one drivable support in first group **1908** of drivable supports **1902**.

Elongate platform **1904** and elongate platform **1906** are substantially flat beams in this illustrative example. In other words, the upper surface of each beam may be planar with deviations within selected tolerances. Elongate platform **1904** and elongate platform **1906** are manufactured to be substantially flat beams such that misalignments at a point

along the beam will reveal misalignments in a corresponding portion of wing assembly **1914** connected to that beam.

Adjustments may be made based on position information collected by a metrology system, such as metrology system **120** described in FIG. 1. With the use of elongate platform **1904** and elongate platform **1906**, however, fewer sensors are needed to position wing assembly **1914** as desired. Instead of requiring sensors at each control point, the metrology system may be used to determine flatness of each elongate platform and, from that flatness determination, one or more drivable supports **1902** may be adjusted to bring the entire work plane back into alignment.

Elongate platform **1904** and elongate platform **1906** also allow a greater number of connection devices to be used without increasing the number of drivable supports **1902** needed. Connection devices **1916** and connection devices **1918** may be positioned on elongate platform **1904** and elongate platform **1906**, respectively, at desired intervals to meet engineering specifications, while still allowing tools to easily maneuver about wing assembly **1914**. By using fewer supports, more space is available for tools to perform operations simultaneously.

Although drivable support system **1900** is shown with two elongate platforms and two portions of drivable supports **1902**, more than two are possible. For instance, several smaller beams and corresponding drivable supports **1902** may be arranged to form drivable support system **1900**.

In other illustrative examples, a first set of load sensors (not shown) may be connected to elongate platform **1904** and configured to identify a load applied to elongate platform **1904** by wing assembly **1914**. A second set of load sensors (not shown) may be connected to elongate platform **1906** and configured to identify a load applied to elongate platform **1906** by wing assembly **1914**. These sensors may constantly provide feedback for the system.

Turning now to FIG. 20, an illustration of drivable support system **1900** and wing assembly **1914** shown in the direction of lines **20-20** in FIG. 19 is depicted in accordance with an illustrative embodiment. In this view, channel **2000** in elongate platform **1904** and channel **2002** in elongate platform **1906** are shown. Channel **2000** and channel **2002** are examples of physical implementations for channel **185** in elongate platform **177** shown in block form in FIG. 1.

At least one of channel **2000** and channel **2002** provide a wire raceway in this illustrative example. For instance, cables **2004** may run through channel **2000** and cables **2006** may run through channel **2002** to provide utilities to drivable support system **1900**, autonomous tool systems working on wing assembly **1914**, human operators **1920** using power tools, or a combination thereof. Cables **2004** and cables **2006** are examples of physical implementations for lines **187** from FIG. 1. In other illustrative examples, air lines or other devices may be run through channel **2000**, channel **2002**, or both.

In FIG. 21, an illustration of an enlarged view of section **1921** with connection device **1917** and point **1919** on wing assembly **1914** from FIG. 19 is depicted in accordance with an illustrative embodiment. In this depicted example, connection device **1917** may have connector **2100**. Connector **2100** directly attaches to point **1919** on wing assembly **1914** in this illustrative example.

In this illustrative example, connector **2100** is rigidly connected to wing assembly **1914** at point **1919**. To adjust the position of connector **2100**, one or more of drivable supports **1902** (not shown in this view) move to bring surface **2102** of elongate platform **1904**, and consequently point **1919** of wing assembly **1914**, back into alignment.

In alternative embodiments, connector **2100** and other components in connection device **1917** may move. However, in the embodiments shown in FIGS. **19-21**, that type of movement is not required to provide desired alignment for wing assembly **1914**.

The illustrations of manufacturing environment **200** and the components within manufacturing environment **200** in FIGS. **2-18**, as well as drivable support system **1900** shown in FIGS. **19-21**, are not meant to imply physical or architectural limitations to the manner in which an illustrative embodiment may be implemented. Other components in addition to or in place of the ones illustrated may be used. Some components may be optional.

The different components shown in FIGS. **2-21** may be illustrative examples of how components shown in block form in FIG. **1** can be implemented as physical structures. Additionally, some of the components in FIGS. **2-21** may be combined with components in FIG. **1**, used with components in FIG. **1**, or a combination of the two.

With reference now to FIG. **22**, an illustration of a flowchart of a process for positioning a tool on a surface is depicted in accordance with an illustrative embodiment. The process described in FIG. **22** may be implemented to position autonomous tool system **131** and components within autonomous tool system **131** relative to a surface on structure **110**. A combination of components including controller **122**, various movement systems, and other devices may be used to position autonomous tool system **131**. Metrology system **120** may be used to locate autonomous tool system **131** as it is being positioned.

The process may begin by moving autonomous tool system **131** relative to a surface of structure **110** to roughly position autonomous tool system **131** within a selected region on the surface using a first movement system (operation **2200**). An example of a first movement system for an autonomous tool system may be movement system **1610** for overhead assembly system **1600** shown in FIG. **16**.

Next, the process may move autonomous tool system **131** relative to the surface of structure **110** with at least one degree of freedom to precisely position autonomous tool system **131** at a selected position within the selected region on the surface using a second movement system (operation **2202**). For instance, a second movement system may move motion platform **1602** toward surface **800** of panel **512**, as shown in FIG. **16**.

The process then may align an element associated with autonomous tool system **131** for performing operation **139** at the selected position relative to the selected position using a third movement system (operation **2204**), with the process terminating thereafter. The element may be end effector **1508** with tools **1604** as shown in FIG. **16**. In this case, motion platform **1504** may be the third movement system configured to precisely position end effector **1508** relative to surface **800** of panel **512** at a desired location to perform an operation.

In FIG. **23**, an illustration of a flowchart of a process for performing operations **130** on structure **110** is depicted in accordance with an illustrative embodiment. The process illustrated in FIG. **23** may be implemented by flexible manufacturing system **102** in manufacturing environment **100** shown in FIG. **1**.

The process begins by driving drivable support **137** from first location **113** to second location **115** to bring drivable support **137** together with at least one other drivable support to form drivable support system **116** (operation **2300**). Next, the process may hold structure **110** in desired position **133** using drivable support system **116** (operation **2302**).

Thereafter, the process may drive structure **110** from second location **115** to third location **117** on floor **107** of manufacturing environment **100** using drivable support system **116** (operation **2304**). The process may then perform operations **130** on structure **110** using plurality of autonomous tool systems **118** (operation **2306**), with the process terminating thereafter.

In operation **2306**, operations **130** may be performed on structure **110** while structure **110** is being driven or steered from second location **115** to third location **117**. In other words, operations **130** may be performed while structure **110** is being carried by drivable support system **116**. Plurality of autonomous tool systems **118** may be driven to third location **117** from various locations **103** in manufacturing environment **100** to perform these operations.

Referring next to FIG. **24**, an illustration of a flowchart of a process for operating flexible manufacturing system **102** to perform operations on structure **110** is depicted in accordance with an illustrative embodiment. The process may begin by generating metrology data **154** for a component within flexible manufacturing system **102** (operation **2400**). For instance, metrology system **120** may be used to identify a current position for at least one of drivable support system **116**, plurality of autonomous tool systems **118**, or structure **110**.

The process then compares the current position of the component identified in metrology data **154** to a desired position for the component (operation **2402**). Next, the process moves the component based on the comparison (operation **2404**). As an example, controller **122** may command autonomous tool system **131** to drive between locations **103** in manufacturing environment **100**. Controller **122** may steer autonomous tool system **131** to avoid collisions with other components in manufacturing environment **100**.

As the component moves, the process monitors the position of the component within manufacturing environment **100** (operation **2406**). Operation **2406** may be implemented using metrology system **120** to provide feedback control **199**.

The process then controls operation of the component (operation **2408**), with the process terminating thereafter. For instance, controller **122** may assign and reassign tasks to the component, take the component offline, reposition the component, command the component to perform an action, or a combination thereof.

The operations described in FIG. **24** may occur substantially concurrently for each component in flexible manufacturing system **102**. For instance, controller **122** may control operation of plurality of autonomous tool systems **118** throughout operations **130**. Moreover, metrology system **120** may continuously generate metrology data **154** to ensure that components within flexible manufacturing system **102** are in a desired position.

In FIG. **25**, an illustration of a flowchart of a process for controlling operation of plurality of autonomous tool systems **118** is depicted in accordance with an illustrative embodiment. The process illustrated in FIG. **25** may be implemented by controller **122** as part of operation **2408** in FIG. **24**.

The process begins by determining whether operations **130** need to be performed on structure **110** (operation **2500**). If operations need to be performed, the process then identifies tasks **111** to be performed on structure **110** (operation **2502**). Controller **122** may prioritize tasks **111** in some cases.

Next, the process assigns tasks **111** to plurality of autonomous tool systems **118** (operation **2504**). The process then

sends commands **166**, with the assigned tasks **111**, to plurality of autonomous tool systems **118** (operation **2506**). Thereafter, the process monitors status **170** of tasks **111** assigned to plurality of autonomous tool systems **118** (operation **2508**).

The process also monitors status **172** of plurality of autonomous tool systems **118** (operation **2510**). The process then reassigns tasks **111** between plurality of autonomous tool systems **118** based on at least one of status **170** of tasks **111** or status **172** of plurality of autonomous tool systems **118** (operation **2512**), returning to operation **2500** thereafter.

Returning to operation **2500**, if no operations need to be performed on structure **110**, the process terminates. In this case, wing **108** may be complete. In another example, when assembly of wing **108** is not complete, the process described in FIG. **25** may temporarily terminate and be reinitiated at a later time.

In FIG. **26**, an illustration of a flowchart of a process for management of a manufacturing environment is depicted in accordance with an illustrative embodiment. The process illustrated in FIG. **26** may be used to reconfigure manufacturing environment **100** shown in block form in FIG. **1** based on manufacturing needs.

The process begins by determining manufacturing parameters **132** for product **104** (operation **2600**). Next, the process reconfigures flexible manufacturing system **102** based on manufacturing parameters **132** (operation **2602**). For example, without limitation, at least one of drivable support system **116**, plurality of autonomous tool systems **118**, or metrology system **120** may be reconfigured based on manufacturing parameters **132** for wing **108**.

The process then performs operations **130** on structure **110** based on manufacturing parameters **132** for product **104** (operation **2604**). As operations **130** are being performed, the process monitors the health of flexible manufacturing system **102** (operation **2606**). The health of flexible manufacturing system **102** may include status **172** of plurality of autonomous tool systems **118**, status **129** of operations **130**, and the position of human operator **142**, among others.

A determination is then made as to whether a portion of flexible manufacturing system **102** may need to be reconfigured (operation **2608**). If not, the process returns to operation **2606**.

If one or more components within flexible manufacturing system **102** need to be reconfigured, the process returns to operation **2602** as described above. In this manner, flexible manufacturing system **102** is reconfigurable based on manufacturing parameters **132** for wing **108**. Flexible manufacturing system **102** is also reconfigurable in real-time based on changes monitored by controller **122**.

Referring now to FIG. **27**, an illustration of a flowchart of a process for using a drivable support system to build a wing assembly is depicted in accordance with an illustrative embodiment. The process illustrated in FIG. **27** may be implemented using drivable support system **116** with elongate platform **177** shown in block form in FIG. **1**.

The process may begin by driving a first group of drivable supports **135** connected to a first elongate platform from first location **113** to second location **115** to bring the first group of drivable supports together with second group of drivable supports **135** connected to a second elongate platform (operation **2700**). The first group of drivable supports **135** with the first elongate platform may be a front spar tooling system in this illustrative example.

The process may then drive a second group of drivable supports **135** connected to a second elongate platform to position the second elongate platform relative to the first

elongate platform (operation **2702**). The second group of drivable supports **135** with the second elongate platform may be a rear spar tooling system.

Next, end supports may be installed between the first elongate platform and the second elongate platform (operation **2704**). End supports may be optional components used to enhance the stability of the system.

Thereafter, the process may identify a position for the first elongate platform and the second elongate platform (operation **2706**). For example, metrology data **154** may be generated for each elongate platform using metrology system **120**.

The process may then determine whether the position of the first elongate platform and the second elongate platform correspond to a desired position for the first elongate platform and the second elongate platform (operation **2708**). If the position and the desired position correspond within selected tolerances, the process may continue to operation **2722**. In this illustrative example, the desired position for the elongate platforms is a position that will ensure alignment, within selected tolerances, of parts of the wing assembly.

In operation **2708**, if the position and the desired position do not correspond within selected tolerances, the process may adjust the position of at least one of the first elongate platform and the second elongate platform (operation **2710**). The position of the elongate platforms is adjusted by moving drivable supports **135** as needed to flatten the work plane.

Thereafter, a first group of structural members may be positioned relative to the first elongate platform and the second elongate platform (operation **2712**). For example, without limitation, front and rear spars may be loaded onto each respective elongate platform by attaching the spars to various connection devices along the length of the elongate platforms.

Next, a second group of structural members may be positioned relative to the first group of structural members and aligned using index features (operation **2714**). As an example, ribs may be loaded between spars and indexed accordingly to form a ladder assembly.

The process may then determine whether the position of the first elongate platform and the second elongate platform have changed (operation **2716**). For instance, metrology system **120** may scan drivable support system **116** again to make sure the first elongate platform and the second elongate platform are substantially flat.

If the position has not changed, the process proceeds to operation **2722**. If the position has changed, the process again may adjust the position of at least one of the first elongate platform and the second elongate platform (operation **2718**).

Thereafter, the process secures the drivable supports (operation **2720**). In operation **2720**, drivable supports **135** may be fixed in place such that drivable supports **135** do not move in an undesired manner. For example, without limitation, the wheels attached to drivable supports **135** may be locked or retracted.

The process then may perform operations **130** to build wing assembly **105** (operation **2722**), with the process terminating thereafter. As an example, upper skin panel **184** may be loaded and tacked to the structural member. Plurality of autonomous tool systems **118** may move about drivable support system **116** to perform operations **130**.

Throughout operations **130**, metrology system **120** may be used to confirm proper alignment of the first elongate platform and the second elongate platform. In addition, other

sensors, such as load sensors, may provide force sensor feedback to not overload wing assembly **105**, drivable support system **116**, or both.

After operations **130** are performed as desired, drivable support system **116** may move wing assembly **105** to other locations within manufacturing environment **100**. Force sensors, as well as metrology system **120**, may be employed to ensure load balancing, as well as precise positioning of the first elongate platform and the second elongate platform.

In some illustrative examples, each group of drivable supports **135** and its respective elongate platform may need to be attached to one another. In such a case, a position of drivable supports **135** relative to structure **110** in manufacturing environment **100** may be determined using metrology system **120**.

A number of the drivable supports **135** may be driven to first location **113** to form the first group of drivable supports **135** based on a proximity of the number of drivable supports **135** to structure **110**. For example, the four drivable supports **135** that are closest to structure **110** and available for use may be driven to first location **113** to form first group of drivable supports **135**. The first group of drivable supports **135** may then be connected to the first elongate platform.

The second group of drivable supports **135** may be formed in a similar fashion and subsequently attached to the second elongate platform. In this manner, drive control system **121** may efficiently allocate drivable support resources within manufacturing environment **100**, further expediting the build process for structure **110**.

The flowcharts and block diagrams in the different depicted embodiments illustrate the architecture, functionality, and operation of some possible implementations of apparatuses and methods in an illustrative embodiment. In this regard, each block in the flowcharts or block diagrams may represent at least one of module, a segment, a function, or a portion a combination thereof of an operation or step.

In some alternative implementations of an illustrative embodiment, the function or functions noted in the blocks may occur out of the order noted in the figures. For example, in some cases, two blocks shown in succession may be executed substantially concurrently, or the blocks may sometimes be performed in the reverse order, depending upon the functionality involved. Also, other blocks may be added in addition to the illustrated blocks in a flowchart or block diagram.

Turning now to FIG. **28**, an illustration of a data processing system in the form of a block diagram is depicted in accordance with an illustrative embodiment. Data processing system **2800** may be used to implement one or more computers in computer system **164** in FIG. **1**. As depicted, data processing system **2800** includes communications framework **2802**, which provides communications between processor unit **2804**, storage devices **2806**, communications unit **2808**, input/output unit **2810**, and display **2812**. In some cases, communications framework **2802** may be implemented as a bus system.

Processor unit **2804** is configured to execute instructions for software to perform a number of operations. Processor unit **2804** may comprise a number of processors, a multi-processor core, some other type of processor, or some combination thereof, depending on the implementation. In some cases, processor unit **2804** may take the form of a hardware unit, such as a circuit system, an application specific integrated circuit (ASIC), a programmable logic device, or some other suitable type of hardware unit.

Instructions for the operating system, applications, programs, or both run by processor unit **2804** may be located in

storage devices **2806**. Storage devices **2806** may be in communication with processor unit **2804** through communications framework **2802**. As used herein, a storage device, also referred to as a computer readable storage device, is any piece of hardware capable of storing information on a temporary basis, permanent basis, or both. This information may include, but is not limited to, at least one of data, program code, or other information.

Memory **2814** and persistent storage **2816** are examples of storage devices **2806**. Memory **2814** may take the form of, for example, a random access memory or some type of volatile or non-volatile storage device. Persistent storage **2816** may comprise any number of components or devices. For example, persistent storage **2816** may comprise a hard drive, a flash memory, a rewritable optical disk, a rewritable magnetic tape, or some combination of the above. The media used by persistent storage **2816** may or may not be removable.

Communications unit **2808** allows data processing system **2800** to communicate with other data processing systems, devices, or some combination thereof. Communications unit **2808** may provide communications using physical communications links, wireless communications links, or a combination thereof.

Input/output unit **2810** allows input to be received from and output to be sent to other devices connected to data processing system **2800**. For example, input/output unit **2810** may allow user input to be received through at least one of a keyboard, a mouse, or some other type of input device. As another example, input/output unit **2810** may allow output to be sent to a printer connected to data processing system **2800**.

Display **2812** is configured to display information to a user. Display **2812** may comprise, for example, without limitation, selected from one of a monitor, a touch screen, a laser display, a holographic display, a virtual display device, or some other type of display device.

In this illustrative example, the processes of the different illustrative embodiments may be performed by processor unit **2804** using computer-implemented instructions. These instructions may be referred to as program code, computer usable program code, or computer readable program code and may be read and executed by one or more processors in processor unit **2804**.

In these examples, program code **2818** is located in a functional form on computer readable media **2820**, which is selectively removable, and may be loaded onto or transferred to data processing system **2800** for execution by processor unit **2804**. Program code **2818** and computer readable media **2820** together form computer program product **2822**. In this illustrative example, computer readable media **2820** may be computer readable storage media **2824** or computer readable signal media **2826**.

Computer readable storage media **2824** is a physical or tangible storage device used to store program code **2818** rather than a medium that propagates or transmits program code **2818**. Computer readable storage media **2824** may be, for example, without limitation, an optical or magnetic disk or a persistent storage device that is connected to data processing system **2800**.

Alternatively, program code **2818** may be transferred to data processing system **2800** using computer readable signal media **2826**. Computer readable signal media **2826** may be, for example, a propagated data signal containing program code **2818**. This data signal may be an electromagnetic signal, an optical signal, or some other type of signal that can

be transmitted over physical, wireless communications links, or some combination thereof.

The illustration of data processing system **2800** in FIG. **28** is not meant to provide architectural limitations to the manner in which the illustrative embodiments may be implemented. The different illustrative embodiments may be implemented in a data processing system that includes components in addition to or in place of those illustrated for data processing system **2800**. Further, components shown in FIG. **28** may be varied from the illustrative examples shown.

The illustrative embodiments of the disclosure may be described in the context of aircraft manufacturing and service method **2900** as shown in FIG. **29** and aircraft **3000** as shown in FIG. **30**. Turning first to FIG. **29**, an illustration of an aircraft manufacturing and service method is depicted in the form of a block diagram in accordance with an illustrative embodiment. During pre-production, aircraft manufacturing and service method **2900** may include specification and design **2902** of aircraft **3000** in FIG. **30** and material procurement **2904**.

During production, component and subassembly manufacturing **2906** and system integration **2908** of aircraft **3000** in FIG. **30** takes place. Thereafter, aircraft **3000** in FIG. **30** may go through certification and delivery **2910** in order to be placed in service **2912**. While in service **2912** by a customer, aircraft **3000** in FIG. **30** is scheduled for routine maintenance and service **2914**, which may include modification, reconfiguration, refurbishment, and other maintenance or service.

Each of the processes of aircraft manufacturing and service method **2900** may be performed or carried out by a system integrator, a third party, an operator, or a combination thereof. In these examples, the operator may be a customer. For the purposes of this description, a system integrator may include, without limitation, any number of aircraft manufacturers and major-system subcontractors; a third party may include, without limitation, any number of vendors, subcontractors, and suppliers; and an operator may be an airline, a leasing company, a military entity, a service organization, and so on.

With reference now to FIG. **30**, an illustration of an aircraft is depicted in the form of a block diagram in which an illustrative embodiment may be implemented. In this example, aircraft **3000** is produced by aircraft manufacturing and service method **2900** in FIG. **29** and may include airframe **3002** with plurality of systems **3004** and interior **3006**. Examples of systems **3004** include one or more of propulsion system **3008**, electrical system **3010**, hydraulic system **3012**, and environmental system **3014**. Any number of other systems may be included. Although an aerospace example is shown, different illustrative embodiments may be applied to other industries, such as the automotive industry.

Apparatuses and methods embodied herein may be employed during at least one of the stages of aircraft manufacturing and service method **2900** in FIG. **29**. In particular, flexible manufacturing system **102** from FIG. **1** may be used during various stages of aircraft manufacturing and service method **2900** to perform operations **130** on airframe **3002**. For example, without limitation, flexible manufacturing system **102** may be used to perform operations **130** during component and subassembly manufacturing **2906**. Components within flexible manufacturing system **102** also may be reconfigured for use during system integration **2908**, routine maintenance and service **2914**, or some other stage of aircraft manufacturing and service method **2900**. For instance, plurality of autonomous tool

systems **118** also may be used to rework portions of airframe **3002** during routine maintenance and service **2914**.

In one illustrative example, components or subassemblies produced in component and subassembly manufacturing **2906** in FIG. **29** may be fabricated or manufactured in a manner similar to components or subassemblies produced while aircraft **3000** is in service **2912** in FIG. **29**. As yet another example, one or more apparatus embodiments, method embodiments, or a combination thereof may be utilized during production stages, such as component and subassembly manufacturing **2906** and system integration **2908** in FIG. **29**. One or more apparatus embodiments, method embodiments, or a combination thereof may be utilized while aircraft **3000** is in service **2912**, during maintenance and service **2914** in FIG. **29**, or a combination thereof. The use of a number of the different illustrative embodiments may substantially expedite the assembly, reduce the cost of aircraft **3000**, or both.

Thus, the illustrative embodiments may provide a method and apparatus for performing operations **130** on product **104** for aircraft **109**. Product **104** may take the form of wing **108** for aircraft **109**. Flexible manufacturing system **102** may comprise drivable support system **116**, plurality of autonomous tool systems **118**, metrology system **120**, and controller **122**. Drivable support system **116** may be configured to hold structure **110** in desired position **133** and move with structure **110** between plurality of work cells **112** during performance of operations **130**. Plurality of autonomous tool systems **118** may be configured to perform operations **130** on structure **110** and move with drivable support system **116**. Metrology system **120** may be configured to generate metrology data **154** for at least one of drivable support system **116**, plurality of autonomous tool systems **118**, or structure **110** and move with drivable support system **116**. Controller **122** may be in communication with metrology system **120** and plurality of autonomous tool systems **118**. Controller **122** may be configured to control operation of plurality of autonomous tool systems **118** using metrology data **154**. At least one of drivable support system **116**, plurality of autonomous tool systems **118**, or metrology system **120** may be reconfigurable.

With the use of an illustrative embodiment, wing **108** may be assembled without the use of fixed monument fixtures at different locations within manufacturing environment **100**. Flexible manufacturing system **102** is completely reconfigurable to take into consideration changing manufacturing conditions. Components within flexible manufacturing system **102** can be reconfigured to modify the length of the assembly line, perform more operations at a single location, or a combination thereof.

The illustrative embodiments also increase the speed at which wing **108** is assembled. Plurality of autonomous tool systems **118** automate various operations using robotic devices. Plurality of autonomous tool systems **118** are also configured such that structure **110** does not have to be lifted as high as with some currently used systems. For instance, assembly system **1400**, as shown in FIG. **14**, are designed such that the wing assembly can be set lower.

In addition, flexible manufacturing system **102** includes various safety features and controls features integrated within the system. As an example, bridge system **136** and rail system **138** provide the necessary access for human operators, while also providing fall protection **144**. Controller **122** controls each of the components in flexible manufacturing system **102** such that undesired encounters

between components, between components and the ground, and between components and human operators, may be reduced or eliminated.

An illustrative embodiment may reconfigure components to support structure **110** in various ways. When bridge system **136** is equipped with elongate platforms, a number of additional connection devices **195** may be used to hold and align parts of structure **110** relative to one another. The implementation of elongate platforms in drivable support system **116** provides additional connections to structure **110** without adding the cost of an additional drivable support. In addition, using fewer drivable supports **135** results in more room to maneuver plurality of autonomous tool systems **118** between drivable supports **135** and promotes greater access to structure **110**. Fewer sensors also may be used to accurately track and align the elongate platforms. These features all result in a system that reduces the cost needed to produce and implement an assembly system.

Because drivable support system **116** is freely movable about manufacturing environment **100**, no monuments or other fixed structures are needed. With the use of an illustrative embodiment, operators do not have to remove structure **110** from fixed monument fixtures and reposition it in different work cells. Rather, drivable support system **116** moves as structure **110** moves. In this manner, manufacturing time needed for wing **108** is reduced. Further, the number of human operators performing operations also may be reduced. As a result, cost savings may be realized.

The description of the different illustrative embodiments has been presented for purposes of illustration and description, and is not intended to be exhaustive or limited to the embodiments in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. Further, different illustrative embodiments may provide different features as compared to other desirable embodiments. The embodiment or embodiments selected are chosen and described in order to best explain the principles of the embodiments, the practical application, and to enable others of ordinary skill in the art to understand the disclosure for various embodiments with various modifications as are suited to the particular use contemplated.

What is claimed is:

1. A flexible manufacturing system for an aircraft structure comprising:

a drivable support connected to a first elongate platform and driven from a first location to a second location and brought together with at least one other drivable support connected to a second elongate platform and driven to the second location to form a drivable support system at the second location on a floor of a manufacturing environment, wherein the first elongate platform is attached to a plurality of points along a first side of the structure at the second location and the second elongate platform is attached to a plurality of points along a second side of the structure at the second location, in which the drivable support system is configured to hold the structure in a desired position.

2. The flexible manufacturing system of claim 1, wherein the drivable support system is configured to drive the structure to a third location while operations are being performed on the structure.

3. The flexible manufacturing system of claim 2, wherein steering direction is provided for at least one of the drivable support, the drivable support system, or a plurality of autonomous tool systems.

4. The flexible manufacturing system of claim 1 further comprising:

a plurality of autonomous tool systems configured to perform operations on the structure while the structure is driven to a third location.

5. The flexible manufacturing system of claim 4, wherein the plurality of autonomous tool systems is configured to drive across the floor of the manufacturing environment.

6. The flexible manufacturing system of claim 4, wherein the plurality of autonomous tool systems comprise at least one of a crawler robot, a tack driller, a hexapod, a lower panel driller, and an upper panel driller.

7. The flexible manufacturing system of claim 4, wherein the plurality of autonomous tool systems are configured to operate simultaneously to perform the operations on the structure.

8. The flexible manufacturing system of claim 4 further comprising:

a metrology system configured to determine a current position of at least one of the drivable support system, the plurality of autonomous tool systems, or the structure, relative to one another.

9. The flexible manufacturing system of claim 8, wherein the metrology system comprises:

a plurality of sensor systems connected to at least one of the plurality of autonomous tool systems or each drivable support in the drivable support system.

10. The flexible manufacturing system of claim 8 further comprising:

a controller in communication with the metrology system, the drivable support system, and the plurality of autonomous tool systems, in which the controller is configured to control operation of at least one of the metrology system, the drivable support system, or the plurality of autonomous tool systems.

11. The flexible manufacturing system of claim 10, wherein the controller controls operation of each drivable support in the drivable support system individually.

12. The flexible manufacturing system of claim 10, wherein a plurality of drivable supports in the drivable support system are configured to separate from each other and drive to a fourth location after the structure is removed from the drivable support system.

13. The flexible manufacturing system of claim 12, wherein the fourth location is the first location.

14. The flexible manufacturing system of claim 10, wherein reconfiguration of the flexible manufacturing system is performed based on changes in at least one of dimensions of the manufacturing environment, a status of the operations for the structure, a status of the drivable support system, or a status of the plurality of autonomous tool systems.

15. The flexible manufacturing system of claim 10, wherein the drivable support system comprises:

a plurality of drivable supports, wherein each drivable support in the plurality of drivable supports is connected to the first elongate platform or the second elongate platform and is configured to drive across the floor of the manufacturing environment under command of the controller.

16. The flexible manufacturing system of claim 15, wherein the plurality of drivable supports are interchangeable with one another.

17. The flexible manufacturing system of claim 15, wherein the drivable support system further comprises:

a plurality of connection devices associated with the first elongate platform and the second elongate platform, and wherein each of the plurality of connection devices is configured to connect to the structure.

47

18. The flexible manufacturing system of claim 17, wherein the controller is configured to control a height of the plurality of connection devices.

19. The flexible manufacturing system of claim 17, wherein the controller is configured to control an extension of the plurality of connection devices.

20. The flexible manufacturing system of claim 15, wherein the drivable support system is a rapid autonomous barge intelligent tool (RABIT).

21. The flexible manufacturing system of claim 15, wherein the drivable support system comprises:

a bridge system connected to the first elongate platform or the second elongate platform and configured to provide access to the structure by a human operator; and

a rail system configured to provide fall protection for the human operator.

22. The flexible manufacturing system of claim 15, wherein the controller is configured to send commands to the plurality of drivable supports to change a current position of at least one portion of the structure based on the current position of the portion determined by the metrology system.

23. The flexible manufacturing system of claim 15, wherein the controller is configured to assign tasks to the plurality of drivable supports in commands sent to the plurality of drivable supports.

24. The flexible manufacturing system of claim 23, wherein the controller is configured to monitor a status of the tasks assigned to the plurality of drivable supports and a status of the plurality of drivable supports.

25. The flexible manufacturing system of claim 23, wherein the controller is configured to reassign the tasks between the plurality of drivable supports based on at least one of a status of the tasks or a status of the plurality of drivable supports.

26. The flexible manufacturing system of claim 15, wherein the controller is configured to send commands to the plurality of autonomous tool systems to perform the operations on the structure.

27. The flexible manufacturing system of claim 26, wherein the controller is configured to assign tasks to the plurality of autonomous tool systems in the commands sent to the plurality of autonomous tool systems.

28. The flexible manufacturing system of claim 26, wherein the controller is configured to monitor a status of tasks assigned to the plurality of autonomous tool systems and a status of the plurality of autonomous tool systems.

29. The flexible manufacturing system of claim 26, wherein the controller is configured to reassign tasks between the plurality of autonomous tool systems based on at least one of a status of the tasks or a status of the plurality of autonomous tool systems.

30. The flexible manufacturing system of claim 1, wherein the aircraft structure is selected from one of a fuselage, a vertical stabilizer, a wing, a control surface, and a horizontal stabilizer.

31. The flexible manufacturing system of claim 1 further comprising:

a navigator in communication with a controller and configured to generate a path for a plurality of autonomous tool systems to reach a desired position relative to the structure.

32. The flexible manufacturing system of claim 31 further comprising:

a transformer in communication with the navigator, a metrology system, and the controller, wherein the transformer is configured to transform coordinates of a

48

current position of a component of the flexible manufacturing system determined by the metrology system into airplane coordinates.

33. The flexible manufacturing system of claim 32, wherein the path is generated by the navigator based on the airplane coordinates received from the transformer.

34. The flexible manufacturing system of claim 1 further comprising:

a loading system configured to move relative to the floor of the manufacturing environment to position at least one of an upper skin panel or a lower skin panel relative to the structure.

35. The flexible manufacturing system of claim 34, wherein the loading system comprises:

a first loading device configured to position the upper skin panel relative to the structure; and

a second loading device configured to position the lower skin panel relative to the structure.

36. The flexible manufacturing system of claim 1, wherein the drivable support system is configured to carry the structure between the first location, the second location, a third location, and a number of additional locations in the manufacturing environment.

37. The flexible manufacturing system of claim 1, wherein operations are performed on the structure while the drivable support system holds the structure in the desired position.

38. The flexible manufacturing system of claim 37, wherein the operations include at least one of a drilling operation, a fastening operation, an inspecting operation, a sealing operation, a measurement operation, a leveling operation, or a cleaning operation.

39. A flexible manufacturing system for a structure comprising:

a first plurality of drivable supports connected to a first elongate platform and driven from a first location to a second location to move the first elongate platform from the first location to the second location, wherein the first elongate platform is attached to a plurality of points along a first side of the structure at the second location; and

a second plurality of drivable supports connected to a second elongate platform and driven to the second location to move the second elongate platform to the second location, wherein the second elongate platform is attached to a plurality of points along a second side of the structure at the second location, wherein the first plurality of drivable supports, the first elongate platform attached to the structure, the second plurality of drivable supports, and the second elongate platform attached to the structure form a drivable support system at the second location on a floor of a manufacturing environment, in which the drivable support system is configured to hold the structure in a desired position.

40. A method for manufacturing a structure, the method comprising:

connecting a first plurality of drivable supports to a first elongate platform;

driving the first plurality of drivable supports with the first elongate platform connected thereto from a first location to a second location to move the first elongate platform from the first location to the second location;

attaching the first elongate platform to a plurality of points along a first side of the structure at the second location;

connecting a second plurality of drivable supports to a second elongate platform;

driving the second plurality of drivable supports with the second elongate platform connected thereto to the second location to move the second elongate platform to the second location;
attaching the second elongate platform to a plurality of 5 points along a second side of the structure at the second location, wherein the first plurality of drivable supports, the first elongate platform attached to the structure, the second plurality of drivable supports, and the second elongate platform attached to the structure form a 10 drivable support system for the structure; and holding the structure in a desired position using the drivable support system.

* * * * *