(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
3 April 2014 (03.04.2014)

WIPO | PCT

(10) International Publication Number
WO 2014/052147 A2

(51) International Patent Classification:
A61G 7/08 (2006.01) *G05D 1/02* (2006.01)

(21) International Application Number:
PCT/US2013/060558

(22) International Filing Date:
19 September 2013 (19.09.2013)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
13/630,087 28 September 2012 (28.09.2012) US

(71) Applicant: **ELWHA LLC** [US/US]; 11235 SE 6th Street, Suite 200, Bellevue, Washington 98004-6481 (US).

(72) Inventors: **HYDE, Roderick A.**; 9915 - 161st Avenue N.E., Redmond, Washington 98052 (US). **MALASKA, Stephen L.**; 7415 232nd Avenue NE, Redmond, Washington 98053 (US).

(74) Agents: **MALASKA, Stephen L.** et al.; 11235 SE 6th Street, Suite 200, Bellevue, Washington 98004-6841 (US).

(81) Designated States *(unless otherwise indicated, for every kind of national protection available)*: AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States *(unless otherwise indicated, for every kind of regional protection available)*: ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,

[Continued on next page]

(54) Title: AUTOMATED SYSTEMS, DEVICES, AND METHODS FOR TRANSPORTING AND SUPPORTING PATIENTS




Fig. 1

(57) Abstract: Systems, devices, and methods are described for moving a patient to and from various locations, care units, etc., within a care facility. For example a transport and support vehicle includes a body structure including a plurality of rotatable members operable to frictionally interface the vehicle to a travel path and to move the vehicle along the travel path, and a surface structured and dimensioned to support an individual subject. A transport and support vehicle can include, for example, an imager operably coupled to one or more of a power source, a steering assembly, one or more of the plurality of rotatable members, etc., and having one or more modules operable to control the power source, steering assembly, one or more of the plurality of rotatable members, etc., so as to maintain an authorized operator in the image zone.

WO 2014/052147 A2

TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— *without international search report and to be republished upon receipt of that report (Rule 48.2(g))*

Automated Systems, Devices, and Methods for Transporting and Supporting Patients

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application is related to and/or claims the benefit of the earliest available effective filing date(s) from the following listed application(s) (the "Priority Applications"), if any, listed below (*e.g.*, claims earliest available priority dates for other than provisional patent applications or claims benefits under 35 USC § 119(e) for provisional patent applications, for any and all parent, grandparent, great-grandparent, etc. applications of the Priority Application(s)). In addition, the present application is related to the "Related Applications," if any, listed below.

Priority Applications:

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation-in-part of United States Patent Application No. **13/630,087**, titled **AUTOMATED SYSTEMS, DEVICES, AND METHODS FOR TRANSPORTING AND SUPPORTING PATIENTS,** naming **Roderick A. Hyde and Stephen L. Malaska** as inventors, filed **28 September 2012** with attorney docket no. **0112-002-001-000000**, which is currently co-pending or is an application of which a currently co-pending application is entitled to the benefit of the filing date.

The United States Patent Office (USPTO) has published a notice to the effect that the USPTO's computer programs require that patent applicants reference both a serial number and indicate whether an application is a continuation, continuation-in-part, or divisional of a parent application. Stephen G. Kunin, *Benefit of Prior-Filed Application*, USPTO Official Gazette March 18, 2003. The USPTO further has provided forms for the Application Data Sheet which allow automatic loading of bibliographic data but which require identification of each application as a continuation, continuation-in-part, or divisional of a parent application. The present Applicant Entity (hereinafter "Applicant") has provided above a specific reference to the application(s) *from which priority is being*

claimed as recited by statute. Applicant understands that the statute is unambiguous in its specific reference language and does not require either a serial number or any characterization, such as "continuation" or "continuation-in-part," for claiming priority to U.S. patent applications. Notwithstanding the foregoing, Applicant understands that the USPTO's computer programs have certain data entry requirements, and hence Applicant has provided designation(s) of a relationship between the present application and its parent application(s) as set forth above, but expressly points out that such designation(s) are not to be construed in any way as any type of commentary and/or admission as to whether or not the present application contains any new matter in addition to the matter of its parent application(s).

All subject matter of the Priority Applications and the Related Applications and of any and all parent, grandparent, great-grandparent, etc. applications of the Priority Applications and the Related Applications, including any priority claims, is incorporated herein by reference to the extent such subject matter is not inconsistent herewith.

SUMMARY

In an aspect, the present disclosure is directed to, among other things, a vehicle for transporting an individual subject. In an embodiment, the vehicle incudes a body structure including a plurality of rotatable members operable to frictionally interface the vehicle to a travel path and to move the vehicle along the travel path, and a surface structured and dimensioned to support an individual subject. . In an embodiment, the vehicle incudes a steering assembly operably coupled to at least one of the rotatable members. In an embodiment, the vehicle incudes a power source operably coupled to one or more of the plurality of rotatable members and configured to rotate at least one of the plurality of rotatable members. In an embodiment, the vehicle incudes an imager operable to image a person within an image zone, and a verification module for determining whether the person in the image zone is an authorized operator of the vehicle. In an embodiment, the imager is operably coupled to the power source and the body structure, the imager including one or more modules having circuitry operable to control the power source and steering assembly so as to maintain the authorized operator in the image zone.

In an aspect, the present disclosure is directed to, among other things, a self-propelled operator-guided bed. In an embodiment, the self-propelled operator-guided bed includes an operator-authorization device having a communication interface that acquires

operator-guide verification information from an identification device associated with an operator-guide. In an embodiment, the operator-authorization device includes one or more tracking sensors operable to track one or more locations of the identification device. In an embodiment, the operator-authorization device includes one or more tracking sensors operable to track information associated with the operator-guide and the identification device carried by, worn by, affixed to the operator, or the like. In an embodiment, the self-propelled operator-guided bed includes a bedframe structure (*e.g.*, a bed, a bedframe, a steerable bed, a steerable bedframe, and the like) having a surface configured (*e.g.*, arranged, adapted, constructed, dimensioned, sized, structured, having structures, etc.) to support a patient.

In an embodiment, the bedframe structure is operably coupled to a transport assembly having a plurality of rotatable members operable to frictionally interface the self-propelled operator-guided bed to a travel path and to move the self-propelled operator-guided bed along the travel path. In an embodiment, the self-propelled operator-guided bed includes a steering assembly operable to vary a steering angle, an orientation, a velocity, etc., of at least one of the plurality of rotatable members. In an embodiment, the self-propelled operator-guided bed includes a powertrain having a power source, motor, transmission, drive shafts, differentials, a final drive etc., for driving one or more of the plurality of rotatable members. In an embodiment, the self-propelled operator-guided bed includes a navigation controller operably coupled to the operator-authorization device and the bedframe structure. In an embodiment, the navigation controller includes a module having circuitry operable to provide a control signal to navigate the bedframe structure along a travel path based on one or more detected locations of the identification device.

In an aspect, the present disclosure is directed to, among other things, a vehicle for transporting an individual subject. In an embodiment, the vehicle includes a body structure, an operator-authorization device, and an imager. In an embodiment, the body structure includes a surface so dimensioned, configured, and arranged to be adapted to support an individual subject, and a plurality of rotatable members operable to frictionally interface the vehicle to a travel path and to move the vehicle along the travel path. In an embodiment, the operator-authorization device includes an input interface operable to acquire verification information associated with an operator (*e.g.*, a guide, a human operator, an operator, or the like), the operator being different from the individual subject. In an embodiment, the operator-authorization device includes a verification module for

determining whether the operator is an authorized operator. In an embodiment, the imager includes one or more modules having circuitry for operably coupling the imager to at least one of the power source and the steering assembly, and for operating the power source and steering assembly so as to maintain the authorized operator in the image zone based on one or more inputs from the imager. In an embodiment, the vehicle includes a power source operably coupled to one or more of the plurality of rotatable members.

In an aspect, the present disclosure is directed to, among other things, a self-propelled operator-guided vehicle system. In an embodiment, the self-propelled operator-guided vehicle system includes one or more self-propelled operator-guided vehicles, each including a bedframe structure having a surface configured to support a patient. In an embodiment, the bedframe structure includes a transport assembly having a plurality of rotatable members operable to frictionally interface the vehicle to a travel path and to move the vehicle along the travel path. In an embodiment, the self-propelled operator-guided vehicle system includes a navigation system configured to vary one or more of propulsion, braking, or steering angle of at least one of the plurality of rotatable members.

In an embodiment, the self-propelled operator-guided vehicle system includes an operator-authorization device operably coupled to the transport assembly and having one or more sensors and a communication interface. In an embodiment, the one or more sensors are operable to detect an operator-guide identification device associated with an operator-guide. In an embodiment, the communication interface is configured to acquire operator-guide verification information from the operator-guide identification device. In an embodiment, the operator-authorization device is configured to acquire information indicative of at least one of an operator-guide authorization status, an operator-guide location, an operator-guide identity, an operator-guide reference physical movement, access status, and the like. In an embodiment, the operator-authorization device is configured to generate one or more control commands for causing the transport assembly to maintaining the self-propelled operator-guided vehicle at a target separation from the authorized operator-guide identification device, based on the at least one of the operator-guide authorization status, the operator-guide identity, and the operator-guide reference physical movement information.

In an aspect, the present disclosure is directed to, among other things, an article of manufacture including a non-transitory signal-bearing medium bearing one or more instructions for causing a system , computing device, processor, etc., to detect an operator-

guide identification device associated with operator-guide. In an embodiment, the article of manufacture includes a non-transitory signal-bearing medium bearing one or more instructions for causing a system, computing device, processor, etc., to acquire operator-guide verification information from the operator-guide identification device. In an embodiment, the operator-guide verification information to be acquired includes information indicative of at least one of an operator-guide authorization status, an operator-guide identity, and an operator-guide reference guidance information. In an embodiment, the article of manufacture includes a non-transitory signal-bearing medium bearing one or more instructions for causing a system, computing device, processor, etc., to generate one or more control commands for maintaining a self-propelled operator-guided vehicle at target separation from the operator-guide identification device. In an embodiment, the article of manufacture includes a non-transitory signal-bearing medium bearing one or more instructions for causing a system, computing device, processor, etc., to detect a location of the operator-guide identification device associated with the operator-guide. In an embodiment, the article of manufacture includes a non-transitory signal-bearing medium bearing one or more instructions for causing a system, computing device, processor, etc., to generate one or more control commands for maintaining the self-propelled operator-guided vehicle at a target separation from the operator-guide identification device responsive to a change of location of the operator-guide identification device relative to the self-propelled operator-guided vehicle.

In an aspect, the present disclosure is directed to, among other things, a self-propelled operator-guided vehicle for transporting and supporting at least one individual subject. In an embodiment, the self-propelled operator-guided vehicle includes an operator-authorization device having one or more image sensors. In an embodiment, the one or more image sensors are operable to acquire image information of an operator within an operator-guide zone. In an embodiment, the self-propelled operator-guided vehicle includes a verification module for determining whether the operator is an authorized operator based on the image information. In an embodiment, the self-propelled operator-guided vehicle includes a bedframe structure having a surface configured to support an individual subject, and a transport assembly having a plurality of rotatable members operable to frictionally interface a self-propelled operator-guided vehicle to a travel path and to move the vehicle along the travel path. In an embodiment, the self-

propelled operator-guided vehicle includes a steering assembly operable to vary a steering angle, an orientation, a velocity, etc., of at least one of the plurality of rotatable members.

In an embodiment, the self-propelled operator-guided vehicle includes a power source and a motor for driving one or more of the plurality of rotatable members. In an embodiment, the self-propelled operator-guided vehicle includes an operator-guided vehicle navigation controller operably coupled to at least one of the operator-authorization device, the steering assembly, the power source, and the motor. In an embodiment, the operator-guided vehicle navigation controller includes a control command module operable to determine physical movement information from the image information. In an embodiment, the operator-guided vehicle navigation controller includes a control command module operable to map one or more detected physical movements of the authorized operator within the operator-guide zone to at least one input correlated with one or more navigation control commands for controlling the self-propelled operator-guided vehicle, based on the physical movement information.

In an aspect, the present disclosure is directed to, among other things, an article of manufacture including a non-transitory signal-bearing medium bearing one or more instructions for acquiring physical movement image information of an operator within an operator-guide zone. In an embodiment, the article of manufacture includes a non-transitory signal-bearing medium bearing one or more instructions for determining operator-guide verification information for the operator within the operator-guide zone based on the physical movement image information. In an embodiment, the article of manufacture includes a non-transitory signal-bearing medium bearing one or more instructions for mapping one or more detected physical movements of the operator within the operator-guide zone to at least one input correlated with one or more navigation control commands for controlling a self-propelled operator-guided bed.

In an aspect, the present disclosure is directed to, among other things, a self-propelled hospital bed navigation control system including an operator-guided vehicle navigation controller. In an embodiment, the operator-guided vehicle navigation controller includes one or more sensors operable to detect at least one operator within an operator-guide zone associated with a self-propelled operator-guided hospital bed. In an embodiment, the self-propelled operator-guided hospital bed includes a bedframe structure having a surface configured to support an individual subject. In an embodiment, the self-propelled operator-guided hospital bed includes a plurality of rotatable members operable

to frictionally interface the vehicle to a travel path and to move the vehicle along the travel path. In an embodiment, the self-propelled operator-guided hospital bed includes a steering assembly operable to vary a steering angle, an orientation, a velocity, etc., of at least one of the plurality of rotatable members. In an embodiment, the self-propelled operator-guided hospital bed includes a power source and a motor for driving one or more of the plurality of rotatable members. In an embodiment, the self-propelled hospital bed navigation control system includes an operator movement mapping module operably coupled to the operator-guided vehicle navigation controller and to at least one of the plurality of rotatable members, the power source, and the motor.

In an embodiment, the operator movement mapping module is configured to map one or more detected physical movements of the operator within the operator-guide zone to at least one input correlated with one or more navigation control commands for controlling the self-propelled operator-guided vehicle. In an embodiment, the operator movement mapping module is configured to generate a control signal to at least one of the plurality of rotatable members, the power source, a braking mechanism, and the motor to navigate the self-propelled operator-guided vehicle based on the one or more navigation control commands.

In an aspect, the present disclosure is directed to, among other things, a self-propelled hospital bed including an operator-guided vehicle navigation controller having an audio-activated control module operable to receive an audio input. In an embodiment, the self-propelled hospital bed includes a bedframe structure operably coupled to the operator-guided vehicle navigation controller. In an embodiment, the bedframe structure includes a surface configured to support an individual subject, and a plurality of rotatable members operable to frictionally interface the self-propelled hospital bed to a travel path and to move the vehicle along the travel path. In an embodiment, the self-propelled hospital bed includes a bedframe structure having a steering assembly operable to vary a steering angle, an orientation, a velocity, etc., of at least one of the plurality of rotatable members. In an embodiment, the self-propelled hospital bed includes a bedframe structure having a power source, and a motor for driving one or more of the plurality of rotatable members. In an embodiment, the operator-guided vehicle navigation controller includes an audio input mapping module having circuitry operable to correlate an audio input to at least one navigation control command for controlling at least one of propulsion, braking, and steering of the self-propelled hospital bed.

In an aspect, the present disclosure is directed to, among other things, a self-propelled hospital bed controller system, including an operator-guided vehicle navigation controller. In an embodiment, the operator-guided vehicle navigation controller includes an audio-activated control module having one or more transducers operable to receive an audio input. In an embodiment, the operator-guided vehicle navigation controller includes an audio input mapping module having circuitry operable to correlate an audio input to at least one navigation control command for controlling at least one of propulsion, braking, and steering of the self-propelled hospital bed. In an embodiment, the operator-guided vehicle navigation controller includes a speech recognition control module operable to receive speech input. In an embodiment, the operator-guided vehicle navigation controller includes a voice control module operable to receive a voice input.

In an aspect, the present disclosure is directed to, among other things, a self-propelled, operator-guided vehicle for transporting and supporting at least one individual subject including an operator-guide verification and navigation controller having one or more sensors operable to acquire at least one digital image of an operator within an operator-guide zone. In an embodiment, the self-propelled hospital bed includes an operator-guide verification operably coupled to a navigation controller. In an embodiment, navigation controller includes one or more modules having circuitry operable to control a power source, a steering assembly, or the like so as to maintain the self-propelled hospital bed along a travel route.

In an embodiment, the body structure includes a surface configured to support an individual subject, the body structure including at least three wheels and a steering assembly. In an embodiment, the self-propelled hospital bed includes a power source operably coupled to one or more of the at least three wheels. In an embodiment, the operator-guide verification and navigation controller includes a module having circuitry operable to map one or more detected physical movements of the operator within the operator-guide zone, and imaged in the at least one digital image, to at least one input correlated with one or more navigation control commands for controlling the self-propelled operator-guided vehicle.

In an aspect, the present disclosure is directed to, among other things, a self-propelled operator-guided vehicle control system including an operator-authorization device having one or more sensors operable to detect one or more physical movements of the operator within the operator-guide zone. In an embodiment, the operator-authorization

device is operably coupled to one or more sensors and configured to detect a location of the operator within the operator-guide zone.

In an embodiment, the self-propelled operator-guided vehicle control system includes a self-propelled operator-guided vehicle navigation controller having circuitry operable to provide a control signal to map the one or more detected physical movements of the operator within the operator-guide zone to at least one input correlated with one or more navigation control commands for controlling the self-propelled operator-guided vehicle. In an embodiment, the self-propelled operator-guided vehicle navigation controller includes circuitry operable to navigate a self-propelled operator-guided vehicle based on the one or more navigation control commands.

In an aspect, the present disclosure is directed to, among other things, a self-propelled operator-guided vehicle capable of transporting and supporting at least one person and operable to identify, follow, monitor, etc., an operator within an operator-guide zone using real-time automatic image recognition. In an embodiment, the self-propelled operator-guided vehicle is operably coupled to a real-time object recognition device. In an embodiment, the real-time object recognition device is configured to identify groups of pixels indicative of one or more physical movements associated with an operator within an operator-guide zone imaged in the at least one digital image. In an embodiment, the real-time object recognition device is configured to generate one or more connected components of a graph representative of groups of pixels indicative of the one or more physical movements associated with the operator imaged in the at least one digital image. In an embodiment, the real-time object recognition device is configured to correlate the one or more connected components of the graph to at least one input associated with one or more navigation control commands for controlling the self-propelled operator-guided vehicle.

In an aspect, the present disclosure is directed to, among other things, a self-guided, patient support and transport vehicle including a self-guided-vehicle navigation controller. In an embodiment, the self-guided-vehicle navigation controller includes a route-to-destination control module having circuitry operable to generate route-to-destination information based on one or more patient verification inputs. In an embodiment, the self-guided patient-support and transport vehicle includes a body structure including a surface configured to support an individual, a transport assembly, a steering assembly, a power source, and a motor. In an embodiment, the transport

assembly includes a plurality of rotatable members operable to frictionally interface the vehicle to a travel path and to move the vehicle along the travel path. In an embodiment, the steering assembly is configured to vary a steering angle, an orientation, a velocity, etc., of at least one of the plurality of rotatable members. In an embodiment, the motor is operable to drive one or more of the plurality of rotatable members. In an embodiment, the self-guided patient-support and transport vehicle navigation controller is operably coupled to at least one of the plurality of rotatable members, the power source, and the motor, and configured to generate one or more control commands for navigating the self-guided patient-support and transport vehicle to at least a first target location along a travel route based on the route-to-destination information.

In an aspect, the present disclosure is directed to, among other things, a self-guided patient-support and transport system including one or more self-propelled patient-support and transport vehicles. In an embodiment, each self-propelled patient-support and transport vehicle includes a self-guided-vehicle navigation controller configured to determine position, velocity, acceleration, bearing, direction, rate-of-change of bearing, rate-of-change of direction, etc., of the self-guided patient-support and transport vehicle. In an embodiment, each self-propelled patient-support and transport vehicle includes a self-guided-vehicle navigation controller configured to generate self-guided patient-support and transport vehicle status information based on at least one of a determined position, velocity, acceleration, bearing, direction, rate-of-change of bearing, rate-of-change of direction, etc., of the self-guided patient-support and transport vehicle. In an embodiment, each self-propelled patient-support and transport vehicle includes a self-guided-vehicle navigation controller configured to generate route-to-destination information based on one or more target location inputs and the self-guided patient-support and transport vehicle status information. In an embodiment, each self-propelled patient-support and transport vehicle includes a self-guided-vehicle navigation controller configured to generate one or more control commands for automatically navigating the self-guided patient-support and transport vehicle to a second position along a travel route based on the route-to-destination information.

In an aspect, the present disclosure is directed to, among other things, an article of manufacture including a non-transitory signal-bearing medium bearing one or more instructions that cause a system, computing device, processor, etc., to determine a position, velocity, acceleration, bearing, direction, rate-of-change of bearing, rate-of-

change of direction, etc., of a self-guided hospital bed. In an embodiment, the article of manufacture includes a non-transitory signal-bearing medium bearing one or more instructions for generating self-guided hospital bed status information. In an embodiment, the article of manufacture includes a non-transitory signal-bearing medium bearing one or more instructions for generating route-to-destination information based on one or more target location inputs and the self-guided hospital bed status information.

In an aspect, the present disclosure is directed to, among other things, a remotely guided, omnidirectional, self-propelled patient-support vehicle including a vehicle navigation controller having a communication module. In an embodiment, the communication module includes at least one of a receiver, a transmitter, and a transceiver operable to communicate with a remote navigation network and to receive control command information (*e.g.*, route-to-destination data, navigation data, location based control commands, etc.) from the remote navigation network. In an embodiment, a remotely guided, omnidirectional, self-propelled patient-support vehicle includes a route-status module including circuitry operable to provide one or more of travel route image information, patient-support vehicle geographic location information, patient-support vehicle travel direction information, patient-support vehicle travel velocity information, patient-support vehicle propulsion information, or patient-support vehicle braking information.

In an embodiment, a remotely guided, omnidirectional, self-propelled patient-support vehicle includes a body structure operably coupled to the vehicle navigation controller. In an embodiment, the body structure includes a surface configured to support a patient. In an embodiment, the body structure includes a plurality of rotatable members operable to frictionally the patient-support vehicle to a travel path and to move the patient-support vehicle along the travel path In an embodiment, the body structure is operably coupled to a steering assembly operable to vary a steering angle, an orientation, a velocity, etc., of at least one of the plurality of rotatable members. In an embodiment, the self-propelled patient-support vehicle includes a power source operably coupled to one or more of the plurality of rotatable members and a motor operable to drive one or more of the plurality of rotatable members. In an embodiment, the vehicle navigation controller includes a patient destination module for generating one or more control commands for navigating a remotely guided self-propelled patient-support vehicle to at least a first patient destination along a patient travel route based on the control command information

from the remote navigation network. In an embodiment, a power source is operably coupled to one or more of the plurality of rotatable members and configured to rotate at least one of the plurality of rotatable members based on the control command information from the remote navigation network.

In an aspect, the present disclosure is directed to, among other things, a remotely guided self-propelled patient-support vehicle including a body structure configured to support a patient in need of transport. In an embodiment, the body structure is operably coupled to a transport assembly including a steering assembly and a power train. In an embodiment, the remotely guided self-propelled patient-support vehicle includes a navigation controller having a communication interface. In an embodiment, the communication interface includes at least one of a receiver, a transmitter, and a transceiver operable to communicate with a remote navigation network. In an embodiment, the communication interface includes at least one of a receiver, a transmitter, and a transceiver operable to receive travel-route information and at least one of propulsion control command information, braking command information, and steering command information from the remote navigation network. In an embodiment, the communication interface includes at least one of a receiver, a transmitter, and a transceiver operable to receive travel-route information necessary to reach a patient destination along a patient travel route. In an embodiment, the vehicle navigation controller is operably coupled to at least one of the transport assembly, the steering assembly, and the power train and configured to generate at least one navigation control command for controlling at least one of propulsion, braking, and steering of a remotely guided self-propelled patient-support vehicle based on the propulsion control command information, the braking command information, or the steering command information from the remote navigation network.

The foregoing summary is illustrative only and is not intended to be in any way limiting. In addition to the illustrative aspects, embodiments, and features described above, further aspects, embodiments, and features will become apparent by reference to the drawings and the following detailed description.

BRIEF DESCRIPTION OF THE FIGURES

Figure 1 is a perspective view of a system including a vehicle for transporting an individual subject according to one embodiment.

Figure 2 is a perspective view of a system including a vehicle for transporting an individual subject according to one embodiment.

Figure 3 is a perspective view of a system including a vehicle for transporting an individual subject according to one embodiment.

Figure 4 shows a schematic diagram of an article of manufacture according to one embodiment.

Figure 5 shows a schematic diagram of an article of manufacture according to one embodiment.

Figure 6 shows a schematic diagram of an article of manufacture according to one embodiment.

DETAILED DESCRIPTION

In the following detailed description, reference is made to the accompanying drawings, which form a part hereof. In the drawings, similar symbols typically identify similar components, unless context dictates otherwise. The illustrative embodiments described in the detailed description, drawings, and claims are not meant to be limiting. Other embodiments may be utilized, and other changes may be made, without departing from the spirit or scope of the subject matter presented here.

Figure 1 shows a system **100** (*e.g.,* an operator-guided vehicle system, a self-guided patient-support and transport system, a self-propelled operator-guided vehicle system, a remotely guided patient-support vehicle system, a self-propelled operator-guided vehicle system, a remotely guided, omnidirectional, self-propelled patient-support vehicle system, etc.), in which one or more methodologies or technologies can be implemented such as, for example, an automated vehicle system for transporting and physically supporting patients, an automated patient transport system that responds to an operator guide, a self-propelled hospital bed system, a self-propelled hospital bed system employing image-based navigation, a remotely guided hospital bed system, a remote-controlled patient transport systems, or the like.

In an embodiment, the system **100** includes a transport and support vehicle **102** (*e.g.*, a bed, a gurney, a stretcher, a wheelchair, etc.) for transporting an individual subject (*e.g.*, a patient, a human subject, an animal subject, etc.). For example, in an embodiment, the system **100** includes a transport and support vehicle **102** for transporting a patient from at least a first location to a second location. In an embodiment, the system **100** includes a

transport and support vehicle **102** for transporting one or more individual subjects to, from, or within a facility (*e.g.*, a healthcare provider facility, a hospital, a home, a room, etc.), or the like.

In an embodiment, the transport and support vehicle **102** includes a body structure **104** (*e.g.*, a vehicle structure, a bed structure, a bedframe, a steerable body structure, a steerable bed, etc.) including a surface **106** arranged and dimensioned to support an individual subject. For example, in an embodiment, the body structure **104** includes one or more mattress **108**, bed decks, patient support structures, body part posturing devices, etc., arranged and dimensioned to support an individual subject.

In an embodiment, the transport and support vehicle **102** includes a plurality of rotatable members **110** operable to frictionally interface the vehicle to a travel path and to move the vehicle along the travel path. Non-limiting examples of rotatable members **110** include wheels **112**, casters, ball rollers, continuous tracks, drive wheels, steer wheels, propellers, or the like. In an embodiment, rotatable members **110** include one or more of motors, rotors, hubs, cranks, sprockets, brake assemblies, bearing assemblies, etc. In an embodiment, the transport and support vehicle **102** includes one or more wheels **112**. In an embodiment, the transport and support vehicle **102** includes one or more wheels **112**, each wheel having an electric wheel hub motor **114**. In an embodiment, the pluralities of rotatable members **110** include one or more brushless electric motors. In an embodiment, one or more of the rotatable members **110** are operably coupled to one or more actuators that use an electrical current or magnetic actuating force to vary the motion of a rotating component (*e.g.*, an actuator that rotates an axle coupled to the wheel to give it steering, an actuator that activates a rotating component forming part of an electric brake system, a magnetic bearing, a magnetic torque device, a brushless electric motor, etc. to vary velocity, etc.).

In an embodiment, the transport and support vehicle **102** includes a power source **116** and a motor **118** operably coupled one or more of the plurality of rotatable members **110**, and configured to drive one or more of the plurality of rotatable members **110**. In an embodiment, the transport and support vehicle **102** includes a powertrain **120** operably coupled to a power source **116**. In an embodiment, the powertrain **120** is configured to supply power to one or more power train components to generate power and deliver it to a travel path surface. Non-limiting examples of powertrain components include motors, engines, transmissions, drive-shafts, differentials, drive rotatable members, final drive

assemblies, or the like. In an embodiment, the transport and support vehicle **102** includes one or more powertrains **120**. In an embodiment, the transport and support vehicle **102** includes a powertrain **120** operably coupled to a plurality of rotatable members **110** and configured to cause a change in position, acceleration, direction, momentum, or the like, of the transport and support vehicle **102.**

In an embodiment, each rotatable member **110** is operably coupled to a respective powertrain **120** and a steering assembly **126**. In an embodiment, each rotatable member **110** can be controlled separately. For example, in an embodiment, a steering angle, an orientation, a velocity, etc., can be controlled separately for each rotatable member **110**. In an embodiment, a rotatable member **110** is operably coupled to at least a first electromagnetic motor that drives a rotatable member **110** and a second electromagnetic motor that can steer the rotatable member **110**. In an embodiment, each of the first, second, third electromagnetic motor, etc., can be separately controlled for precise movement. In an embodiment, each electromagnetic motor is powered by a battery. In an embodiment a plurality of electromagnetic motors is powered by a single battery.

In an embodiment, one or more of the rotatable members **110** are operably coupled to one or more actuator devices that use an electrical current or magnetic actuating force to vary the motion of a rotating component (*e.g.*, an actuator that rotates an axle coupled to a rotatable member **110** to give it steering, an actuator that activates a rotating component forming part of an electric brake system, actuator devices that use an electrical current or magnetic actuating force to control a magnetic bearing, a magnetic torque device, a brushless electric motor, etc. to vary velocity, etc.).

In an embodiment, the transport and support vehicle **102** includes one or more drive rotatable members **110** operable to receive torque from the powertrain **120**. For example, in an embodiment, during operation, one or more drive wheels provide a driving force for the transport and support vehicle **102**. In an embodiment, the transport and support vehicle **102** takes the form of a multi-wheel drive transport and support vehicle. For example, in an embodiment, the transport and support vehicle **102** includes a two-wheel drive transport and support vehicle having two driven wheels. In an embodiment, the transport and support vehicle **102** takes the form of a two-wheel drive vehicle, a four-wheel drive vehicle, an all-drive vehicle, or the like. . In an embodiment, the transport and support vehicle **102** is configured for omni-directional travel.

In an embodiment, the transport and support vehicle **102** includes one or more drive control modules **122**. In an embodiment, a module includes, among other things, one or more computing devices such as a processor (*e.g.,* a microprocessor), a central processing unit (CPU), a digital signal processor (DSP), an application-specific integrated circuit (ASIC), a field programmable gate array (FPGA), or the like, or any combinations thereof, and can include discrete digital or analog circuit elements or electronics, or combinations thereof. In an embodiment, a module includes one or more ASICs having a plurality of predefined logic components. In an embodiment, a module includes one or more FPGAs, each having a plurality of programmable logic components.

In an embodiment, the drive control modules **122** includes a module having one or more components operably coupled (*e.g.*, communicatively, electromagnetically, magnetically, ultrasonically, optically, inductively, electrically, capacitively coupled, or the like) to each other. In an embodiment, a module includes one or more remotely located components. In an embodiment, remotely located components are operably coupled, for example, *via* wireless communication. In an embodiment, remotely located components are operably coupled, for example, *via* one or more receivers **132**, transmitters **134**, transceivers **136**, or the like. In an embodiment, the drive control module **122** includes a module having one or more routines, components, data structures, interfaces, and the like.

In an embodiment, a module includes memory that, for example, stores instructions or information. For example, in an embodiment, at least one control module includes memory that stores operator-guide verification information, operator-guide identification information, operator-guide registration information, patient identification information, navigation plan information, travel path markings information, travel-route status information, vehicle status information, travel-route status information, etc. Non-limiting examples of memory include volatile memory (*e.g.,* Random Access Memory (RAM), Dynamic Random Access Memory (DRAM), or the like), non-volatile memory (*e.g.,* Read-Only Memory (ROM), Electrically Erasable Programmable Read-Only Memory (EEPROM), Compact Disc Read-Only Memory (CD-ROM), or the like), persistent memory, or the like. Further non-limiting examples of memory include Erasable Programmable Read-Only Memory (EPROM), flash memory, or the like. In an embodiment, the memory is coupled to, for example, one or more computing devices by one or more instructions, information, or power buses. In an embodiment, the drive

control module **122** includes memory that, for example, stores operator-guide identification information, travel-route status information, or the like. In an embodiment, the operator-authorization device **130** includes memory that, for example, stores object tracking information, operator-zone registration information, control command information, gesture information, or the like.

In an embodiment, a module includes one or more computer-readable media drives, interface sockets, Universal Serial Bus (USB) ports, memory card slots, or the like, and one or more input/output components such as, for example, a graphical user interface, a display, a keyboard, a keypad, a trackball, a joystick, a touch-screen, a mouse, a switch, a dial, or the like, and any other peripheral device. In an embodiment, a module includes one or more user input/output components that are operably coupled to at least one computing device configured to control (electrical, electromechanical, software-implemented, firmware-implemented, or other control, or combinations thereof) at least one parameter associated with, for example, controlling one or more of driving, navigating, braking, or steering the transport and support vehicle **102**.

In an embodiment, a module includes a computer-readable media drive or memory slot that is configured to accept signal-bearing medium (*e.g.,* computer-readable memory media, computer-readable recording media, or the like). In an embodiment, a program for causing a system to execute any of the disclosed methods can be stored on, for example, a computer-readable recording medium (CRMM), a signal-bearing medium, or the like. Non-limiting examples of signal-bearing media include a recordable type medium such as a magnetic tape, floppy disk, a hard disk drive, a Compact Disc (CD), a Digital Video Disk (DVD), Blu-Ray Disc, a digital tape, a computer memory, or the like, as well as transmission type medium such as a digital or an analog communication medium (*e.g.,* a fiber optic cable, a waveguide, a wired communications link, a wireless communication link (*e.g.,* receiver **132**, transmitter **134**, transceiver **136**, transmission logic, reception logic, etc.). Further non-limiting examples of signal-bearing media include, but are not limited to, DVD-ROM, DVD-RAM, DVD+RW, DVD-RW, DVD-R, DVD+R, CD-ROM, Super Audio CD, CD-R, CD+R, CD+RW, CD–RW, Video Compact Discs, Super Video Discs, flash memory, magnetic tape, magneto-optic disk, MINIDISC, non-volatile memory card, EEPROM, optical disk, optical storage, RAM, ROM, system memory, web server, or the like.

In an embodiment, the transport and support vehicle **102** is operably coupled to one or more rotatable members **110** having a braking system. The braking system can include, but is not limited to, a disc brake system, an electronic brake system, a drum brake system, or the like. In an embodiment, the transport and support vehicle **102** is operably coupled to one or more rotatable members **110** having a regenerative brake system. In an embodiment, the transport and support vehicle **102** is operably coupled to one or more brake control modules **124**.

In an embodiment, the transport and support vehicle **102** is operably coupled to steering assembly **126** having one or more modules, mechanisms, components, linkages, steering gear assemblies, or the like operable to steer the transport and support vehicle **102**. In an embodiment, the steering assembly **126** is operable to vary a steering angle, an orientation, a velocity, etc., of at least one of a plurality of rotatable members **110**. For example, in an embodiment, the transport and support vehicle **102** is operably coupled to steering assembly **126** having one or more electro-mechanical elements operable to vary a steering angle, an orientation, a velocity, etc., of at least one of a plurality of rotatable members **110**. In an embodiment, the steering assembly **126** is operable to vary a steering angle, an orientation, a velocity, etc., of at least one of a plurality of wheels **112**. In an embodiment, the transport and support vehicle **102** is operably coupled to steering assembly **126** having one or more components linkages, steering gear assemblies, rod assemblies, or the like that aid in directing the transport and support vehicle **102** along a target course. In an embodiment, the transport and support vehicle **102** is operably coupled to steering assembly **126** having one or more actuators, electric wheel hub motors, magnetic bearings, magnetic torque devices, brushless electric motors, or the like that aid in directing the transport and support vehicle **102** along a target course.

In an embodiment, for example, the transport and support vehicle **102** is operably coupled to one or more steer wheels operable to change direction of the transport and support vehicle **102**. In an embodiment, the steering assembly **126** is operably coupled to power steering assembly.

In an embodiment, the steering assembly **126** includes one or more sensors **150** (*e.g.*, yaw-rate sensors, angular velocity sensors, steering angle sensors, wheel speed sensors, position sensors, etc.). For example, in an embodiment, the steering assembly **126** includes a steering sensor operable to detect a steering angle, orientation, etc., associated with a steered one of the plurality of rotatable members **110**. In an

embodiment, the steering assembly **126** includes a vehicle velocity sensor operable to detect a velocity of the transport and support vehicle **102**. In an embodiment, the steering assembly **126** is operably coupled to vehicle acceleration sensor operable to detect an acceleration of the vehicle. In an embodiment, the steering assembly **126** is operably coupled to vehicle position sensor operable to detect a geographical location of the vehicle. In an embodiment, the steering assembly **126** is operably coupled to rotational rate sensor operable to detect a rate of rotation of the transport and support vehicle **102**.

In an embodiment, the transport and support vehicle **102** includes at least three wheels **112**, and the steering assembly **126** is operable to vary a steering angle, an orientation, a velocity, etc., of at least one of the at least three wheels **112**. In an embodiment, the transport and support vehicle **102** includes one or more steering control modules **128**. For example, in an embodiment, the transport and support vehicle **102** includes one or more steering control modules **128** having circuitry operable to vary a steering angle, an orientation, a velocity, etc., of at least one of the plurality of rotatable members **110**.

In an embodiment, the transport and support vehicle **102** includes an imager **138** operable to locate an operator (e.g., an authorized operator **140**, an off-board operator, an off-board guide, an operator different from the on-board patient, or the like) within operator-guide zone **142** (*e.g.*, an image zone, or the like). In an embodiment, the imager **138** is operably coupled to a power source, such as the power source **116,** and the body structure **104**, and includes one or more modules having circuitry operable to operate the power source **116** and steering assembly **126** so as to maintain the transport and support vehicle **102** at a target separation from an authorized operator within operator-guide zone **142**. In an embodiment, the steering assembly **126** is communicatively coupled, physically coupled, electromagnetically coupled, magnetically coupled, ultrasonically coupled, optically coupled, inductively coupled, electrically coupled, capacitively coupled, wirelessly coupled, or the like) to the imager **138** and is configured to vary a vehicle heading based on one or more inputs from the imager indicative of a change in position by the authorized operator **140**. In an embodiment, the steering assembly **126** is communicatively coupled to the imager **138** and is configured to vary a vehicle heading based on a change in position by the authorized operator **140**. In an embodiment, the steering assembly **126** is communicatively coupled to the imager **138** and is operable to control a direction of travel based on one or more inputs from the imager indicative of a

sensed change in position by the authorized operator **140**. In an embodiment, the steering assembly **126** is operable to vary a steering angle, an orientation, a velocity, etc., of at least one of a plurality of rotatable members **110** based on a change in position by the authorized operator **140**.

In an embodiment, the imager **138** includes a camera and a facial-recognition module including circuitry configured to locate, identify, authorize, etc., an operator within an operator-guide zone **142**. For example, in an embodiment, the imager **138** includes one or more modules having circuitry, such as, one or more sensor **150** (*e.g.*, optical sensors, cameras, radiofrequency sensors, three-dimensional sensors (*e.g.*, 3-D sensors operable to capture information about the shape of a face, etc.) or the like) operable to acquire image information. In an embodiment, during operation, the imager **138** determines an individual's identity by detecting and analyzing distinct features of an individual's face surface (*e.g.*, structural features of the eye sockets, chin, nose, etc.). In an embodiment, the imager **138** includes three-dimensional sensor-based face recognition modalities. For example, in an embodiment, the imager **138** includes one or more infrared light sensor operable to measures depth, position, motion, or the like. In an embodiment, the imager **138** comprises a multimodal biometric sensor for identifying persons, objects, or the like. Various facial-recognition hardware, programs, software, etc., are known and can be used.

In an embodiment, the imager **138** includes an optical camera, a stereo optical camera, or the like. In an embodiment, the imager **138** includes at least one of a radar module having an optical radar, a microwave radar device, Doppler radar device, and the like. In an embodiment, the imager **138** can be used to measure velocity. In an embodiment, the imager **138** includes a rangefinder device (*e.g.*, laser range finder, acoustic range finder, rangefinder camera, sonic ranging module, or the like) to determine the approximate distance of the operator from the vehicle.

In an embodiment, the transport and support vehicle **102** takes the form of a self-propelled operator-guided bed including an operator-authorization device **130**. In an embodiment, the operator-authorization device **130** is configured to acquire verification information associated with an operator **140**. For example, in an embodiment, the transport and support vehicle **102** is operably coupled to an operator-authorization device **130** having an input interface and one or more modules operable to acquire verification information associated with an operator **140**.

In an embodiment, the input interface includes a graphical user interface. In an embodiment, the input interface includes a tablet computing device, a smartphone, or a mobile device. In an embodiment, the input interface includes an information input device, a scanner, a card reader/writer device. In an embodiment, the input interface includes a keyboard, a plug-in subscriber identification module (SIM) card, or a Flash drive. In an embodiment, the input interface includes a wire carrying a coded signal.

In an embodiment, the operator-authorization device **130** is operably coupled to at least one of a receiver **132**, a transceiver **134**, and a transmitter **136** operable to acquire the verification information associated with the operator **140**. In an embodiment, the operator-authorization device **130** includes a graphical user interface. In an embodiment, the operator-authorization device **130** includes a tablet computing device, a smartphone, or a mobile device.

In an embodiment, the input interface includes at least one of a receiver, a transceiver, and a transmitter to acquire the verification information associated with an operator. In an embodiment, the operator-authorization device **130** includes an information input device, a scanner, or a card reader/writer device (*e.g.*, smart-card reader, magnetic swipe card reader, optical card reader, media reader/writer, etc.). In an embodiment, the operator-authorization device **130** includes a verification module **144** for determining whether the operator is an authorized operator **140**.

In an embodiment, the operator-authorization device **130** includes a communication interface **131** configured to acquire operator-guide verification information from an identification device **146** associated with an operator-guide. In an embodiment, the operator-authorization device **130** includes routines, components, data structures, interfaces, and the like, operable to acquire operator-guide verification information from an identification device **146** associated with an operator-guide. For example, during operation, a plurality of tracking sensors operably coupled to a tracking module **148** follow, monitor, track, etc., changes in a location of a person carrying the operator-authorization device **130** by monitoring a communication signal from the operator-authorization device **130**. Accordingly, in an embodiment, the tracking module **148** is configured to correlate at least one measurand from one or more of the plurality of tracking sensors to one or more physical movements of a user carrying the identification device **146**. In an embodiment, the operator-authorization device **130** includes at least one

of a receiver **132**, a transceiver **134**, and a transmitter **136** operable to acquire the verification information associated with the operator-guide.

In an embodiment, the operator-authorization device **130** includes a negotiation module **152** configured to initiate a discovery protocol that allows the operator-authorization device **130** and the identification device **146** associated with the operator-guide to identify each other and negotiate one or more pre-shared keys. For example, in an embodiment, the operator-authorization device **130** includes a negotiation module **152** having routines, components, data structures, interfaces, and the like, operable to initiate a discovery protocol that allows the operator-authorization device **130** and the identification device **146** associated with the operator-guide to identify each other and negotiate one or more pre-shared keys.

In an embodiment, at least one of the operator-authorization device **130** and the identification device **146** is responsive based on at least one of an authorization protocol, an authentication protocol, an activation protocol, a negotiation protocol, and the like. For example, during operation, in an embodiment, at least one of the operator-authorization device **130** and the identification device **146** implements a discovery and a registration protocol that allows the operator-authorization device **130** and the identification device **146** to find each other and negotiate one or more pre-shared keys. This negotiation is implemented using a variety of technologies, methodologies, and modalities including, for example, using aggressive-mode exchanges, main-mode exchanges, quick-mode exchanges, or combinations thereof. In an embodiment, at least one of the operator-authorization device **130** and the identification device **146** is operable to establish an Internet Security Association and Key Management Protocol (ISAKMP) security association (SA), between the operator-authorization device **130** and the identification device **146** using one or more negotiations schemas. Non-limiting examples of negotiation types include aggressive-mode negotiation, main-mode negotiation, quick-mode negotiation, or the like. Further limiting examples of negotiation types include aggressive mode negotiation using pre-shared key authentication followed by quick-mode negotiation, aggressive mode using digital signature authentication followed by quick-mode negotiation, main mode negotiation using digital signature authentication followed by quick-mode negotiation, main mode negotiation using encrypted nonce-based authentication followed by quick-mode negotiation, main mode negotiation using pre-shared key authentication followed by quick-mode negotiation, or the like. In an

embodiment, the ISAKMP SA is used to protect subsequent key exchanges between peer devices (*e.g.*, *via* quick-mode negotiation protocols, or the like).

In an embodiment, at least one of the operator-authorization device **130**, the identification device **146,** and the other devices disclosed herein operates in a networked environment using connections to one or more remote computing devices (*e.g.*, a common network node, a network computer, a network node, a peer device, a personal computer, a router, a server, a tablet PC, a tablet, etc.) and typically includes many or all of the elements described above. In an embodiment, the connections include connections to a local area network (LAN), a wide area network (WAN), or other networks. In an embodiment, the connections include connections to one or more enterprise-wide computer networks, intranets, and the Internet. In an embodiment, the system **100**, the transport and support vehicle **102**, the operator-authorization device **130**, or the like operate in a cloud computing environment including one or more cloud computing systems (*e.g.*, private cloud computing systems, public cloud computing systems, hybrid cloud computing systems, or the like).

In an embodiment, the operator-authorization device **130** includes at least one of a receiver **132**, a transceiver **134**, and a transmitter **136** that acquires various information as necessary, including for example, operator-guide identification information, operator-guide authorization status information, and the like. In an embodiment, the operator-authorization device **130** is operably coupled to one or more distal sensors that acquire travel path markings information. In an embodiment, the operator-authorization device **130** includes memory having patient-specific route-to-destination information stored thereon. In an embodiment, operator-authorization device **130** is configured to acquire route-to-destination information. In an embodiment, the operator-authorization device **130** is configured to acquire patient identification information. In an embodiment, the operator-authorization device **130** is configured to acquire self-propelled operator-guided vehicle status information. In an embodiment, the operator-authorization device **130** is configured to acquire travel-route status information.

In an embodiment, the operator-authorization device **130** is operably coupled to the transport assembly and includes one or more sensors operable to detect an operator-guide identification device **146** associated with an operator-guide. In an embodiment, the operator-authorization device **130** includes a communication interface **131** having one or more modules configured to acquire operator-guide verification information from the

operator-guide identification device **146**. For example, in an embodiment, during operation, the operator-guide identification device **146** is interrogated by an electromagnetic energy signal, an acoustic signal, or the like, generated by the operator-authorization device **130** to elicit an authorization key. Upon authorization, information such as operator-guide authorization status information, operator-guide identity information, operator-guide reference guidance information, operator-guide verification information, physical movement image information, route-to-destination information, vehicle status information, etc., is shared. In an embodiment, once located, identified, authorized, etc. a method includes tracking staff, patients, vehicles, events, or the like to determine a compliance status.

In an embodiment, the operator-authorization device **130** includes one or more modules operable to acquire information indicative of at least one of an operator-guide authorization status, an operator-guide identity, and an operator-guide reference physical movement information. In an embodiment, the operator-authorization device **130** includes one or more modules that generate one or more control commands for causing the transport assembly to maintaining the self-propelled operator-guided vehicle at a target separation from the authorized operator-guide identification device **146** based on the at least one of the operator-guide authorization status, the operator-guide identity, and the operator-guide reference physical movement information.

In an embodiment, the operator-authorization device **130** is configured to acquire navigation plan information (*e.g.*, hospital physical layout information, route information, obstacle information, real-time hospital traffic information, destination information, origination information, etc.) from the operator-guide identification device **146** and to cause the generation of the one or more control commands for causing the transport assembly to maintain the self-propelled operator-guided vehicle at the target separation from the authorized operator-guide identification device **146** based on the navigation plan information.

In an embodiment, operator-authorization device **130** includes a navigation module **154** is operably coupled to the one or more sensors **150** and configured to detect a location of the operator-guide identification device **146** associated with the operator-guide. Non-limiting examples of sensors **150** include acoustic sensors, optical sensors, electromagnetic energy sensors, image sensors, photodiode arrays, charge-coupled devices (CCDs), complementary metal–oxide–semiconductor (CMOS) devices, transducers,

optical recognition sensors, infrared sensors, radio frequency components sensors, thermo sensor, or the like. In an embodiment, the operator-authorization device **130** includes a navigation module **154** operably coupled to the one or more sensors **150** and configured to determine a location of the operator-guide identification device **146** relative to the transport and support vehicle **102**. In an embodiment, operator-authorization device **130** includes a navigation module **154** operably coupled to the one or more sensors **150** and configured to generate one or more control commands for maintaining the self-propelled operator-guided vehicle at target separation from the operator-guide identification device **146** responsive to a change of location of the operator-guide identification device **146** relative to the transport and support vehicle **102**. In an embodiment, the operator-guide identification device **146** includes one or more transducers that detect and convert acoustic signals emitted from the operator-authorization device **130** into electronic signals.

In an embodiment, the transport and support vehicle **102** includes one or more modules operable to register the operator-guide identification device **146** relative to the transport and support vehicle **102** and to generate registration information. In an embodiment, the navigation module **154** is configured to locate, register, and track the operator-guide identification device **146** with at least one operator-guide zone **142**, and to generate operator-guide zone registration information. In an embodiment, the navigation module **154** is configured to register the operator-guide identification device **146** relative to one operator-guide zone **142** and to generate registration information and one or more navigation control commands based on the registration information.

In an embodiment, the navigation module **154** is configured to register the operator-guide identification device **146** relative to the transport and support vehicle **102** and to generate registration information. For example, during operation, the navigation module **154** maps (*e.g.*, spatially aligns, registers, projects, correlates, etc.) the geographical location of operator-guide identification device **146** relative to the geographical location of the transport and support vehicle **102**. In an embodiment, the navigation module **154** is configured to generate one or more navigation control commands for maintain the transport and support vehicle **102** at a target separation form the operator-guide identification device **146** based on the on the registration information. In an embodiment, the navigation module **154** registers a plurality of objects by mapping coordinates from one object to corresponding points in another object. In an embodiment, the navigation module **154** registers objects (*e.g.*, operator-guide zones, travel path

locations, target and reference objects, targets and focal regions, images, etc.) using one or more transformations.

Non-limiting examples of registration techniques or methodologies include deformable registration, landmark-based registration, or rigid registration. *See e.g.*, Paquin et al., *Multiscale Image Registration*, Mathematical Biosciences and Engineering, Vol. 3:2 (2006); *see also* Paquin, Dana, PhD, *Multiscale Methods for Image Registration*, Ph.D. dissertation, Stanford University (2007); Zitova et al., *Image Registration Methods: a Survey*, Image and Vision Computing (21) pp. 977-1000 (2003); each of which is incorporated herein by reference. In an embodiment, registration includes techniques or methodologies for spatially aligning images taken using different imaging modalities, taken at different times, or that vary in perspective. Further non-limiting examples of registration techniques or methodologies include deformable multiscale registration, hybrid multiscale landmark registration, multiscale image registration, or rigid multiscale registration. In an embodiment, registration includes one or more of feature detection, feature identification, feature matching, or transform modeling. In an embodiment, registration includes mapping features of a first object with the features of a second object. In an embodiment, registration includes determining a point-by-point correspondence between two objects, regions, or the like. In an embodiment, registration includes determining a point-by-point correspondence between an object and a location. For example, in an embodiment, registration includes determining a point-by-point correspondence between an object and an operator-guide zone **142**.

In an embodiment, the operator-authorization device **130** includes a navigation module **154** operably coupled to the one or more sensors **150** and configured to generate one or more control commands for maintaining a velocity differences between a transport and support vehicle's **102** and the operator-guide within a target range. In an embodiment, the operator-authorization device **130** includes a navigation module **154** operably coupled to the one or more sensors **150** and configured to generate one or more control commands for maintaining a velocity differences between the transport and support vehicle **102** and the operator-guide within a target range.

In an embodiment, operator-authorization device **130** is configured to generate route-to-destination information responsive to a displacement of the operator-guide identification device **146** relative the transport and support vehicle **102**. In an embodiment, operator-authorization device **130** is configured to generate route-to-

destination information responsive to a detected velocity difference between the operator-guide identification device **146** and the transport and support vehicle **102**. In an embodiment, operator-authorization device **130** is configured to generate one or more control commands for controlling one or more of propulsion, braking, or steering responsive to movement of the operator-guide identification device **146**. In an embodiment, operator-authorization device **130** is configured to generate one or more control commands for controlling one or more of propulsion, braking, or steering responsive to movement of the operator-guide identification device **146** responsive to a communication loss between the operator-guide identification device **146** and the transport and support vehicle **102**.

In an embodiment, the transport and support vehicle **102** takes the form a self-propelled operator-guided bed including a navigation controller **156** and a bedframe structure. In an embodiment, the navigation controller **156** is configured to register the transport and support vehicle **102** relative to a portion of a travel path and to generate registration information. In an embodiment, the navigation controller **156** is operably coupled to the operator-authorization device **130** and the bedframe structure. In an embodiment, the navigation controller **156** includes one or more navigation modules **154** having circuitry operable to provide a control signal to navigate the bedframe structure along a travel path based on the one or more detected locations of the identification device **146**. In an embodiment, the operator-authorization device **130** includes navigation module **154** having circuitry operable to generate and implement one or more control commands for controlling one or more of propulsion, braking, or steering responsive to one or more detected locations of the identification device **146**. In an embodiment, the navigation controller **156** include one or more object sensors and is configured to maintain the bedframe structure at a target separation from an object proximate the travel path. In an embodiment, the navigation controller **156** is configured to maintain the bedframe structure at a target separation from a wall proximate the travel path.

In an embodiment, the transport and support system **100** includes one or more self-propelled operator-guided vehicles. In an embodiment, each self-propelled operator-guided vehicle includes a bedframe structure having a surface **106** configured to support a patient, the bedframe structure including a transport assembly having a plurality of rotatable members **110** to frictionally interface the vehicle to a travel path and to move the vehicle along the travel path and a navigation system configured to vary one or more of

propulsion, braking, or steering angle of at least one of the plurality of rotatable members **110**.

In an embodiment, the transport and support vehicle **102** includes an operator-authorization device **130** having one or more image sensors for acquiring image information of an operator within an operator-guide zone **142**. In an embodiment, operator-authorization device **130** includes a verification module **144** for determining whether the operator is an authorized operator **140** based on the image information. In an embodiment, the operator-authorization device **130** includes one or more modules operable to determine one or more of operator-guide identification information or operator-guide authorization status information based on the image information. In an embodiment, the operator-authorization device **130** is configured to determine at least one of operator-guide identification and operator-guide authorization status information based on the one or more detected physical movements of the operator within the operator-guide zone **142**.

In an embodiment, the transport and support vehicle **102** includes an operator-guided vehicle navigation controller **156**. For example, in an embodiment, the transport and support vehicle **102** includes an operator-guided vehicle navigation controller **156** operably coupled to at least one or more of the operator-authorization device **130**, the steering assembly **126**, the power source **116**, or the motor **118**. In an embodiment, the operator-guided vehicle navigation controller **156** includes a control command module operable to determine physical movement information from the image information and to map one or more detected physical movements of the authorized operator **140** within the operator-guide zone **142** to at least one input correlated with one or more navigation control commands for controlling the transport and support vehicle **102** based on the physical movement information. In an embodiment, the operator-guided vehicle navigation controller **156** is configured to navigate the transport and support vehicle **102** based on the one or more navigation control commands. In an embodiment, the operator-guided vehicle navigation controller **156** is responsive to the operator-authorization device **130**, and the one or more navigation control commands, for controlling one or more of propulsion, braking, or steering to direct the transport and support vehicle **102** along a travel route.

In an embodiment, the operator-guided vehicle navigation controller **156** is responsive to the operator-authorization device **130**, and the one or more navigation

control commands, for determining a travel route for the transport and support vehicle **102**. In an embodiment, operator-guided vehicle navigation controller **156** is operably coupled to at least one of the one or more image sensors and is configured to determine a travel route based on the one or more detected physical movements of the operator within the operator-guide zone **142**. In an embodiment, operator-guided vehicle navigation controller **156** is operably coupled to a geographical positioning system as is configured to determine one or more travel destinations based on the one or more detected physical movements of the operator within the operator-guide zone **142**.

In an embodiment, it may be necessary to move a patient to and from various locations, care units, etc., within a care facility. Patients undergoing numerous diagnostic procedures, interventional procedures, etc., may require transport to more than one location. An operator (*e.g.*, a care provider, an orderly, a nurse, at doctor, etc.) may assist the patient onto a transport and support vehicle **102**, and to one or more target destinations. More than one operator may be necessary along the way to reach more than one destination. During operation, an operator my approach the transport and support vehicle **102** to guide it to a target destination along a travel route. In an embodiment, a protocol can be activated to determine, for example, whether the operator is authorized to assist that transport and support vehicle **102**, whether the correct patient is on the transport and support vehicle **102**, a status of one or more travel routes, a status of one or more destination locations, etc., or the like.

In an embodiment, the transport and support vehicle **102** is configured to respond to an operator that will assist it to reach one or more destinations along a travel route. In an embodiment, prior to engaging with the operator, the transport and support vehicle **102** determines whether the operator proximate to the transport and support vehicle **102**, within an operator-guide zone **142,** etc., is authorized to guide the transport and support vehicle **102** to a destination. For example, in an embodiment, the transport and support vehicle **102** is operably coupled to an operator-authorization device **130** including a verification module **144** for determining whether the operator is an authorized operator **140**. In an embodiment, the verification module **144** includes circuitry for determining whether the physical coupling member associated with the at least one human corresponds to an authorized operator **140**. In an embodiment, the operator-authorization device **130** is operably coupled to communication interface **131** configured to acquire operator-guide verification information from an identification device **146** associated with an operator-

guide. In an embodiment, the operator-authorization device **130** is operably coupled to an imager **138** including a camera and a facial-recognition module having circuitry configured to locate, identify, authorize, etc., an operator within an operator-guide zone **142**.

Once it has been determined that an operator is an authorized operator **140** of the transport and support vehicle **102**, the operator-authorization device **130** is operable to enable an automatic controlled state, a manual controlled state, an operator-guided state, or remote controlled state of the transport and support vehicle **102**. For example, in an embodiment, in an operator-guided state, the transport and support vehicle **102** determines navigation control commands for controlling the transport and support vehicle **102** based on gesture information, movement information, or the like, associated with an authorized operator **140**.

In an embodiment, the operator-authorization device **130** is operably coupled to a steering assembly **126** that varies a vehicle heading based on one or more inputs from the imager **138** indicative of a change in position by the authorized operator **140**. In an embodiment, the operator-authorization device **130** is operably coupled to a navigation module **154** that generates one or more control commands for maintaining the self-propelled operator-guided vehicle at target separation from the operator-guide identification device **146** responsive to a change of location of the operator-guide identification device **146** relative to the transport and support vehicle **102**. In an embodiment, the operator-authorization device **130** is operably coupled to one or more sensors **150** that image and track a movement of a least a portion of the operator within the operator-guide zone **142**, and generates one or more navigation control commands for controlling the transport and support vehicle **102** based on a measurand indicative of change in position of the portion of the operator.

Accordingly, in an embodiment, the authorized operator **140** assist, guides, controls, actuates, etc., the patient transport and support vehicle **102** to one or more target destinations along a travel route.

Referring to Figure 2, in an embodiment, the transport and support vehicle **102** includes a virtual object generator **202**. For example, in an embodiment, the transport and support vehicle **102** includes a virtual object generator **202** operably coupled to the operator-guide vehicle navigation controller **156**. In an embodiment, during operation, the virtual object generator **202** is configured to generate a virtual representation **204** of at

least one of a locality **206** of the operator within the operator-guide zone **142** and a locality the transport and support vehicle **102** within a physical space on a virtual display **206**. In an embodiment, the operator-authorization device **130** is configured to track at least a portion of the operator within the operator-guide zone **142** and to update a virtual object **208** in a virtual space corresponding to the physical location of at least one of the transport and support vehicle **102** and the portion of the operator within the operator-guide zone **142**. In an embodiment, the transport and support vehicle **102** includes a virtual object generator **202** operably coupled to the operator-guide vehicle navigation controller **156** and configured to generate a virtual representation **210** of the one or more navigation control commands on a virtual display.

In an embodiment, the transport and support vehicle **102** includes a virtual object generator **202** operably coupled to the operator-guide vehicle navigation controller **156** and configured to generate a virtual representation **212** corresponding to the physical location of the transport and support vehicle **102** on a virtual display. In an embodiment, the transport and support vehicle **102** includes a virtual object generator **202** operably coupled to the operator-guide vehicle navigation controller **156** and configured to generate a virtual representation **214** corresponding to the portion of the operator within the operator-guide zone **142** on a virtual display. In an embodiment, the operator-authorization device **130** is configured to image one or more physical movements of the operator **140** within the operator-guide zone **142** responsive to the image information and to update a virtual object **210** in a virtual space corresponding to the one or more physical movements of the operator within the operator-guide zone **142**.

In an embodiment, the transport and support vehicle **102** includes one or more sensors **150** that image and track a movement of a least a portion of the operator within the operator-guide zone **142**. For example, in an embodiment, the operator-guided vehicle navigation controller **156** includes a navigation module **154** that is operably coupled to the one or more movement recognition and tracking sensors and is configured to generate one or more navigation control commands for controlling the transport and support vehicle **102** based on a measurand indicative of change in position of the portion of the operator. In an embodiment, the operator-guided vehicle navigation controller **156** is operable to generate one or more control commands for maintaining a separation **160** between the transport and support vehicle **102** and the operator within the operator-guide zone **142** within a target range. In an embodiment, the operator-guided vehicle navigation controller

156 is operable to generate one or more control commands for maintaining a velocity difference between the transport and support vehicle **102** and the operator within the operator-guide zone **142** within a target range.

In an embodiment, the transport and support vehicle **102** includes one or more sensors **150** that image and track a movement of a least a portion of the operator within an operator-guide zone **142** while the operator is proximate a side, front, or rear portion of the transport and support vehicle **102**. For example, in an embodiment, the transport and support vehicle **102** includes one or more movement recognition and tracking sensors that image and real-time track at least a portion of the operator while the operator is proximate a side, front, or rear portion of the transport and support vehicle **102**. In an embodiment, the transport and support vehicle **102** includes one or more movement recognition and tracking sensors that image and real-time track at least a portion of the operator within the operator-guide zone **142**. In an embodiment, the transport and support vehicle **102** includes one or more sensors **150** that determine proximity information (*e.g.*, signal strength, propagation time, phase change, etc.) indicative of a transport and support vehicle **102** location relative to an operator within the operator-guide zone **142**. In an embodiment, the transport and support vehicle **102** includes one or more movement recognition and tracking sensors operable to image one or more hand or arms gestures of the operator. In an embodiment, the transport and support vehicle **102** includes one or more movement recognition and tracking sensors operable to image one or more hand or arms gestures of an authorized operator **140**, an operator, an guide, an operator different from the on-board patient, or the like. Non-limiting examples of movement recognition and tracking sensors include optical sensors, cameras, radiofrequency sensors, three-dimensional sensors, electro-optical sensors, infra-red sensors, network of sensors, distributed set of sensors, location sensors, etc. In an embodiment, the transport and support vehicle **102** takes the form of transport and support vehicle **102**. In an embodiment, the operator-guided vehicle navigation controller **156** is operably coupled to the one or more movement recognition and tracking sensors and is configured to determine gestures information from image information and to map the one or more hand or arms gestures of the operator within the operator-guide zone **142** to at least one input correlated with one or more navigation control commands for controlling the transport and support vehicle **102** based on the gesture information.

In an embodiment, the operator-guided vehicle navigation controller **156** is operable to enable an automatic controlled state, a manual controlled state, an operator-guided state, or remote controlled state of the transport and support vehicle **102** based on a measurand from the one or more movement recognition and tracking sensors indicative that operator is not within the operator-guide zone **142**. In an embodiment, the operator-guided vehicle navigation controller **156** operable to initiate a standby mode, based on a measurand from the one or more movement recognition and tracking sensors indicative that operator is absent from the operator-guide zone **142**. In an embodiment, the operator-guided vehicle navigation controller **156** operable to initiate a no-operator protocol, based on a measurand from the one or more movement recognition and tracking sensors indicative that an authorized operator 140 is not within the operator-guide zone **142**.

In an embodiment, the transport and support vehicle **102** includes self-propelled hospital bed navigation control system that includes an operator-guided vehicle navigation controller **156** including a navigation module **154** having one or more sensors **150** operable to detect at least one operator within an operator-guide zone **142**.

In an embodiment, the transport and support vehicle includes a bedframe structure. In an embodiment, the bedframe structure includes a surface **106** arranged and dimensioned to support an individual subject. In an embodiment, the plurality of rotatable members **110** is adapted and configured to frictionally interface the vehicle to a travel path and to move the vehicle along the travel path. In an embodiment, the steering assembly **126** operable to vary a steering angle, an orientation, a velocity, etc., of at least one of the plurality of rotatable members **110**. In an embodiment, the power source **116** and the motor **118** are operable to drive the one or more of the plurality of rotatable members **110**.

In an embodiment, the operator-guided vehicle navigation controller **156** is configured to detect the at least one operator within an operator-guide zone **142** located proximate the self-propelled hospital bed based on at least one measurand from the one or more sensors **150**. In an embodiment, the operator-guided vehicle navigation controller **156** is configured to detect the at least one operator within an operator-guide zone **142** located proximate a side portion of the self-propelled hospital bed based on at least one measurand from the one or more sensors **150**. In an embodiment, the operator-guided vehicle navigation controller **156** is configured to detect the at least one operator within an operator-guide zone **142** located proximate a distal portion of the self-propelled hospital bed based on at least one measurand from the one or more sensors **150**. In an

embodiment, the operator-guided vehicle navigation controller **156** includes at least one communication interface **131** configured to detect an identification device **146** associated with the at least one operator based on at least one measurand from the one or more sensors **150**.

In an embodiment, the operator-guided vehicle navigation controller **156** includes one or more optical sensors operable to detect an optical authorization signal from an identification device **146** associated with the at least one operator. In an embodiment, the operator-guided vehicle navigation controller **156** includes one or more transducers operable to detect an acoustic authorization signal from an identification device **146** associated with the at least one operator. In an embodiment, the operator-guided vehicle navigation controller **156** includes one or more imagers **138** to acquire an image of a human proximate the self-propelled hospital bed or of a badge associated with the at least one operator. In an embodiment, the operator-guided vehicle navigation controller **156** is operably coupled to a device associated with the at least one operator via an input-or-output port, the navigation controller **156**. In an embodiment, the operator-guided vehicle navigation controller **156** is operably connected to a physical coupling member associated with the at least one operator via an input-or-output port.

In an embodiment, the operator-guided vehicle navigation controller **156** includes a verification module **144** including circuitry for determining whether the physical coupling member associated with the at least one human corresponds to an authorized operator **140**. In an embodiment, the operator-guided vehicle navigation controller **156** includes a communication interface **131** operable to initiating a discovery protocol that allows the operator-guided vehicle navigation controller **156** and an identification device **146** associated with the at least one operator to identify each other and negotiate one or more pre-shared keys. In an embodiment, the operator-guided vehicle navigation controller **156** includes at least one a receiver **132**, transmitter **134**, or transceiver **136** configured to detect an identification device **146** associated with the at least one operator. In an embodiment, the operator-guided vehicle navigation controller **156** includes one or more electromagnetic energy sensors that detect a wireless signal from identification device **146** associated with at least one operator. In an embodiment, the operator-guided vehicle navigation controller **156** includes one or more optical sensors configured to detect radiation reflected form one or more retro-reflector elements associated with the at least one operator. In an embodiment, the operator-guided vehicle navigation controller **156**

includes one or more optical sensors configured to detect radiation reflected from one or more retro-reflector elements along a travel path.

In an embodiment, the transport and support vehicle **102** includes an operator movement mapping module. For example, in an embodiment, the transport and support vehicle **102** includes an operator movement mapping module operably coupled to the operator-guided vehicle navigation controller **156** and to at least one of the plurality of rotatable members **110**, the power source **116**, and the motor **118**. In an embodiment, the operator movement mapping module is operable to map one or more physical movements of the operator within the operator-guide zone **142** to at least one input correlated with one or more navigation control commands for controlling the transport and support vehicle **102**. In an embodiment, the operator movement mapping module is operable to generate a control signal to at least one of the plurality of rotatable members **110**, the power source **116**, and the motor **118** to navigate the transport and support vehicle **102** based on the one or more navigation control commands.

In an embodiment, the operator movement mapping module includes circuitry configured to map one or more gestures of the human operator within the operator-guide zone to at least one input correlated with one or more navigation control commands for controlling the self-propelled operator-guided vehicle, and to generate a control signal to at least one of the plurality of rotatable members **110**, the power source **116**, and the motor **118** to navigate the self-propelled operator-guided vehicle based on the one or more navigation control commands.

In an embodiment, the operator movement mapping module includes circuitry configured to map one or more physical movements of the human operator resulting in a change in separation distance of the human operator within the operator-guide zone from the bed, to at least one input correlated with one or more navigation control commands for controlling the self-propelled operator-guided vehicle, and to generate a control signal to at least one of the plurality of rotatable members **110**, the power source **116**, and the motor **118** to navigate the self-propelled operator-guided vehicle based on the one or more navigation control commands.

Referring to Figure 3, in an embodiment, the transport and support vehicle **102** includes a fail-safe control system **300**. For example, in an embodiment, the fail-safe control system **300** include one or more fail-safe devices **302** that physically couple the transport and support vehicle **102** to the at least one operator **140**. In an embodiment, the

transport and support vehicle **102** includes a fail-safe control system **300** having a fail-safe module **308** including circuitry operable to activate a fail-safe protocol when the operator **140** is no longer detected. For example, during operation, the operator **140** couples an information carrier **304** to an interface port **306** of the transport and support vehicle **102**. Upon coupling, a verification module **144** determines whether the operator **140** is an authorized operator. In an embodiment, the fail-safe control system **300** is operable to activate a fail-safe protocol during a fail-safe mode of operation. For example, in an embodiment, the fail-safe control system **300** is operable to activate a fail-safe protocol responsive to an indication that the transport and support vehicle **102** and the at least one operator are no longer physically coupled via the fail-safe control system **300**. In an embodiment, the fail-safe control system **300** includes one or more modules operable to activate a fail-safe protocol when the information carrier **304** is no longer detected. In an embodiment, fail-safe control system **300** includes a connection assembly for coupling the operator-guided transport and support vehicle **102** to a physical coupling member associated with the least one operator. In an embodiment, the fail-safe control system **300** is operable to activate a fail-safe protocol when the coupling to the physical coupling member is lost. In an embodiment, the transport and support vehicle **102** includes a fail-safe control system **300** having an input-or-output interface to operably connect an information carrier **304** associated with the at least one operator **140** to the operator-guided vehicle navigation controller **156**.

In an embodiment, the transport and support vehicle **102** includes an audio input recognition control device **310** (*e.g.*, voice-command recognition device, speech recognition device, audio tone control input device, etc.) including one or more acoustic sensor operable to recognize speech input, and to generate a transport route based on the speech input. In an embodiment, the transport and support vehicle **102** includes an audio-activated control module **312** operable to receive an audio input and to correlate the audio input to at least one navigation control command for controlling at least one of propulsion, braking, and steering of the transport and support vehicle **102**.

In an embodiment, the transport and support vehicle **102** includes an audio control module **314** operably coupled to the operator-guided vehicle navigation controller **156** and configured to receive one or more voice command inputs from the operator and to identify one or more potential matching symbols for the one or more voice commands. In an embodiment, the potential one or more matching symbols include at least one navigation

control command for controlling the transport and support vehicle **102**. In an embodiment, the potential one or more matching symbols include at least one navigation control command for controlling a destination of the transport and support vehicle **102**. In an embodiment, the potential one or more matching symbols include at least one navigation control command for controlling an orientation of the transport and support vehicle **102**. In an embodiment, the potential one or more matching symbols include at least one navigation control command for controlling at least one of propulsion, braking, and steering of the transport and support vehicle **102**.

In an embodiment, the transport and support vehicle **102** includes a voice-command recognition device **316** including a voice-command control module **318** having one or more transducers operable to recognize an operator-specific input, receive one or more speech inputs, and generate transport route information based on the one or more speech inputs. In an embodiment, the transport and support vehicle **102** includes a speech recognition device **318** including one or more speech control modules **320** operable to correlate speech input to at least one navigation control command for controlling at least one of propulsion, braking, and steering of the transport and support vehicle **102**.

In an embodiment, the transport and support vehicle **102** includes one or more navigation systems (*e.g.*, a laser navigation system, an optical navigation system, a sonic navigation system, a vision navigation system, etc.). . In an embodiment, the transport and support vehicle **102** includes a navigation system including one or more navigation modules. For example, in an embodiment, the transport and support vehicle **102** includes a navigation module having a global position circuitry for detecting a geographical location of the transport and support vehicle **102.**

In an embodiment, the transport and support vehicle **102** includes an optical navigation system operably coupled to the operator-guided vehicle navigation controller **156** and including one or more electromagnetic energy sensors. In an embodiment, the operator-guided vehicle navigation controller **156** configured to generate a control signal to at least one of the plurality of rotatable members **110**, the power source **116**, and the motor **118** to navigate the transport and support vehicle **102** based on one or more measurands outputs from the optical navigation system.

In an embodiment, the transport and support vehicle **102** includes an inertial navigation system operably coupled to the operator-guided vehicle navigation controller **156**, and including one or more motion sensors or rotation sensors. In an embodiment, the

operator-guided vehicle navigation controller **156** is configured to generate at least one of position information, orientation information, and velocity information based on one or more measurands outputs from the inertial navigation system. In an embodiment, the transport and support vehicle **102** includes a collision avoidance system operably coupled to the operator-guided vehicle navigation controller **156** and including one or more sensors **150** operable to detect a travel path condition. In an embodiment, the operator-guided vehicle navigation controller **156** configured to generate a control signal to at least one of the plurality of rotatable members **110**, the power source **116**, and the motor **118** to navigate the transport and support vehicle **102** based on one or more measurands outputs from the collision avoidance system.

In an embodiment, the transport and support vehicle **102** includes a collision avoidance system operably coupled to the operator-guided vehicle navigation controller **156** and including one or more sensors **150** operable to detect a travel path condition. In an embodiment, the operator-guided vehicle navigation controller **156** is configured to generate a control signal to control at least one of propulsion, braking, and steering of the transport and support vehicle **102** based on one or more measurands outputs from the collision avoidance system. In an embodiment, the transport and support vehicle **102** includes one or more moment of inertia sensors operably coupled to the operator-guided vehicle navigation controller **156**. In an embodiment, the operator-guided vehicle navigation controller **156** configured to generate one or more navigation control commands for controlling the transport and support vehicle **102** based on at least one measurand from the one or more moment of inertia sensor. In an embodiment, the transport and support vehicle **102** includes one or more weight sensors operably coupled to the operator-guided vehicle navigation controller **156**, the operator-guided vehicle navigation controller **156** configured to generate one or more navigation control commands for controlling the transport and support vehicle **102** based on at least one measurand from the one or more weight sensors **150**.

In an embodiment, the transport and support vehicle **102** includes a plurality of distance measuring sensors for determining a travel distance from a location on the transport and support vehicle **102** to a remote object. In an embodiment, the transport and support vehicle **102** includes a plurality of travel-path sensors for detecting a remote object along a travel path of the transport and support vehicle **102**. In an embodiment, the transport and support vehicle **102** includes an audio-activated control module **312** operable

to receive an audio input. For example, in an embodiment, the operator-guided vehicle navigation controller **156** includes an audio input mapping module having circuitry operable to correlate the audio input to at least one navigation control command for controlling at least one of propulsion, braking, and steering of the transport and support vehicle **102**.

In an embodiment, the transport and support vehicle **102** includes a plurality of wheels **112**, each wheel having an electric wheel hub motor **114** such that, during operation. In an embodiment, the operator-guided vehicle navigation controller **156** varies an applied current to each electric wheel hub motor **114** based on an audio input.

In an embodiment, the audio-activated control module **312** is operable to receive one or more voice command inputs from an operator and to identify one or more potential matching symbols for the one or more voice commands. In an embodiment, the one or more potential matching symbols including at least one navigation control command for controlling at least one of propulsion, braking, and steering of the transport and support vehicle **102**. In an embodiment, the audio-activated control module **312** includes a voice-command recognition device **316** including one or more transducers operable to detect an operator-specific input and to generate transport route based on the operator-specific input. In an embodiment, the audio-activated control module **312** includes a speech recognition device **318** configured to correlate speech input to at least one navigation control command for controlling at least one of propulsion, braking, and steering of the transport and support vehicle **102**. In an embodiment, the audio-activated control module **312** includes a speech recognition device **318** configured to correlate speech input to one or more navigation control commands for controlling a steering angle of at least one of the plurality of rotatable members **110**.

In an embodiment, the transport and support vehicle **102** includes an operator-guided vehicle navigation controller **156** including an audio-activated control module **312** having one or more transducers operable to receive an audio input, and an audio input mapping module including circuitry operable to correlate the audio input to at least one navigation control command for controlling at least one of propulsion, braking, and steering of the transport and support vehicle **102**. In an embodiment, the audio-activated control module **312** includes one or more modules having circuitry operable to receive one or more voice command inputs from an operator and to generate one or more potential matching symbols for the one or more voice commands. In an embodiment, the one or

more potential matching symbols including at least one navigation control command for controlling at least one of propulsion, braking, and steering of the transport and support vehicle **102**.

In an embodiment, the audio-activated control module **312** includes a voice-command recognition device **316** including one or more transducers operable to acquire an operator-specific input. In an embodiment, the audio-activated control module **312** is configured to generate transport route based on the operator-specific input. In an embodiment, the audio-activated control module **312** includes a speech recognition device **318** configured to correlate speech input to at least one navigation control command for controlling at least one of propulsion, braking, and steering of the transport and support vehicle **102**.

In an embodiment, the transport and support vehicle **102** includes an operator-guide verification and navigation controller **156** including one or more sensors operable to acquire at least one digital image of an operator within an operator-guide zone **142**. In an embodiment, the operator-guide verification and navigation controller **156** includes one or more modules having circuitry operable to map one or more physical movements of the operator within the operator-guide zone **142** and imaged in the at least one digital image to at least one input correlated with one or more navigation control commands for controlling the transport and support vehicle **102**. In an embodiment, the operator-guide verification and navigation controller **156** is configured to navigate the transport and support vehicle **102** to at least a first location responsive to the one or more navigation control commands.

In an embodiment, the transport and support vehicle **102** includes an operator-authorization device **130** including one or more sensors that detect one or more physical movements of the operator within the operator-guide zone **142**. In an embodiment, the transport and support vehicle **102** includes a self-propelled operator-guided vehicle navigation controller **156** having a computing device and memory to provide a control signal to map the one or more physical movements of the operator within the operator-guide zone **142** to at least one input correlated with one or more navigation control commands for controlling the transport and support vehicle **102**. In an embodiment, the transport and support vehicle **102** includes a self-propelled operator-guided vehicle navigation controller **156** having a computing device and memory to provide a control signal to navigate a transport and support vehicle **102** based on the one or more navigation control commands.

In an embodiment, the transport and support vehicle **102** includes a real-time object recognition device configured to identify groups of pixels indicative of one or more physical movements associated with an operator within an operator-guide zone **142** imaged in the at least one digital image. For example, in an embodiment, the transport and support vehicle **102** includes a real-time object recognition device including one or more modules having circuitry configured to identify groups of pixels indicative of one or more physical movements associated with an operator within an operator-guide zone **142** imaged in the at least one digital image. In an embodiment, the transport and support vehicle **102** includes a real-time object recognition device configured to generate one or more connected components of a graph representative of groups of pixels indicative of the one or more physical movements associated with the operator imaged in the at least one digital image. In an embodiment, the transport and support vehicle **102** includes a real-time object recognition device configured to correlate the one or more connected components of the graph to at least one input associated with one or more navigation control commands for controlling the transport and support vehicle **102**.

In an embodiment, the transport and support vehicle **102** includes a self-guided-vehicle navigation controller **156** having a route-to-destination control module including circuitry operable to generate route-to-destination information based on one or more patient verification inputs. In an embodiment, the self-guided-vehicle navigation controller **156** includes a travel-route status acquisition circuit operable to acquire real-time travel-route status information. In an embodiment, the self-guided-vehicle navigation controller **156** includes an alternate route-to-destination generation circuit operable to generate route-to-destination information responsive to the travel-route status information indicative of an adverse condition present along the travel route. In an embodiment, the self-guided-vehicle navigation controller **156** includes an optical guidance system configured to determine the first position of a transport and support vehicle **102**.

In an embodiment, the self-guided-vehicle navigation controller **156** includes circuitry operable to generate one or more control commands for navigating the transport and support vehicle **102** along a multi-floor travel route. In an embodiment, the self-guided-vehicle navigation controller **156** is operably coupled to at least one of the plurality of rotatable members **110**, the power source **116**, and the motor **118**, and configured to generate one or more control commands for navigating the transport and support vehicle **102** to at least a first target location along a travel route based on a patient verification

input. In an embodiment, the self-guided-vehicle navigation controller **156** is operably coupled to at least one of the plurality of rotatable members **110**, the power source **116**, and the motor **118**, and configured to generate one or more control commands for navigating the transport and support vehicle **102** to at least a first target location along a travel route based on one or more inputs indicative of a change in health status of a patient being transported.

In an embodiment, the transport and support vehicle **102** includes one or more memory device structures having travel route information or object along travel route information stored thereon. In an embodiment, the transport and support vehicle **102** includes one or more memories having reference travel route information stored thereon. In an embodiment, the self-guided-vehicle navigation controller **156** includes a communication interface **131** configured to request real-time path traffic status information and to update the route-to-destination information based on the response to the request real-time path traffic status information. In an embodiment, the self-guided-vehicle navigation controller **156** is configured to generate one or more control commands for controlling one or more of propulsion, braking, or steering responsive to an input from one or more sensors operably coupled to the self-guided-vehicle navigation controller **156** and configured to detect a location of a remote object along a travel route.

In an embodiment, the self-guided-vehicle navigation controller **156** is configured to generate one or more control commands for navigating the transport and support vehicle **102** to at least a first target location along a travel route based on the route-to-destination information. For example, in an embodiment, the self-guided-vehicle navigation controller **156** is operably coupled to at least one of the plurality of rotatable members **110**, the power source **116**, and the motor **118** and is configured to generate one or more control commands for navigating the transport and support vehicle **102** to at least a first target location along a travel route based on the route-to-destination information.

In an embodiment, the route-to-destination control module includes a patient-in-route circuit configured to acquire travel-route status information, the travel-route status information to be acquired including one or more of travel-route traffic information, travel-route obstacle location information, travel-route map information, or travel-route geographical location information, and to generate updated route-to-destination information responsive to the travel-route status information. In an embodiment, the route-to-destination control module includes a patient-in-route circuit configured to report

transport and support vehicle **102** location information along one or more target travel-route locations. In an embodiment, the route-to-destination control module includes a patient-in-route circuit configured to report self-guided patient-support and transport location arrival information.

In an embodiment, the transport and support vehicle **102** includes a navigation module having one or more sensors **150** to determine a position, velocity, or acceleration of the transport and support vehicle **102**. In an embodiment, the inertial navigation module configured to generate transport and support vehicle **102** status information responsive to changes to the position, velocity, or acceleration of the transport and support vehicle **102**.

In an embodiment, the transport and support vehicle **102** includes a navigation module including one or more sensors **150** to determine a bearing, a direction, a rate-of-change of bearing, or a rate-of-change of direction of the self-guided patient-support vehicle. In an embodiment, the inertial navigation module configured to generate transport and support vehicle **102** status information responsive to a change to the bearing, the direction, the rate-of-change of bearing, or the rate-of-change of direction of the transport and support vehicle **102**.

In an embodiment, the transport and support vehicle **102** includes a voice-command recognition device **316** operably coupled to the self-guided-vehicle navigation controller **156** and having one or more audio sensors operable to recognize an audio input. In an embodiment, the self-guided-vehicle navigation controller **156** is configured to generate one or more control commands based on the audio input.

In an embodiment, the transport and support vehicle **102** includes a voice-command recognition device **316** including one or more audio sensors operable to recognize an operator-specific audio input and to enable an automatic controlled state, a manual controlled state, an operator-guided state, or remote controlled state of the self-guided-vehicle navigation controller **156** based on the audio input. In an embodiment, the voice-command recognition device **316** configured to enable an automatic controlled state, a manual controlled state, an operator-guided state, or remote controlled state of the self-guided-vehicle navigation controller **156** based on the audio input

In an embodiment, the transport and support vehicle **102** includes one or more weight sensors or moments of inertia sensor, such that, during operation, the self-guided-vehicle navigation controller **156** is configured to determine weight information or a

moment of inertia information, and one or more control commands for navigating the transport and support vehicle **102** to a second position along a travel route based on at least one of the weight information and the moment of inertia information.

In an embodiment, the transport and support vehicle **102** includes one or more sensors **150** configured to detect one or more travel path markings along a travel path and to generate travel path markings information. In an embodiment, the self-guided-vehicle navigation controller **156** is configured to generate route-to-destination information based on one or more target location inputs and the travel path makings information. In an embodiment, the transport and support vehicle **102** includes one or more sensors **150** configured to detect one or more travel path markings along a travel path and to generate travel path makings information, the self-guided-vehicle navigation controller **156** configured to generate registration information for real-time registering of the transport and support vehicle **102** relative to the one or more travel path markings. In an embodiment, the self-guided-vehicle navigation controller **156** configured to register the transport and support vehicle **102** relative to the one or more travel path markings.

In an embodiment, a self-guided patient-support and transport system, includes one or more transport and support vehicle **102**, each transport and support vehicle **102** including a self-guided-vehicle navigation controller **156** configured to determine a position, velocity, acceleration, bearing, direction, or a rate-of-change of bearing, or rate-of-change of direction of the transport and support vehicle **102** and generate transport and support vehicle **102** status information. In an embodiment, a self-guided patient-support and transport system includes one or more transport and support vehicle **102**, each transport and support vehicle **102** including a self-guided-vehicle navigation controller **156** configured to generate route-to-destination information based on one or more target location inputs and the transport and support vehicle **102** status information. In an embodiment, a self-guided patient-support and transport system, includes one or more transport and support vehicle **102**, each transport and support vehicle **102** including a self-guided-vehicle navigation controller **156** configured to generate one or more control commands for automatically navigating the transport and support vehicle **102** to a second position along a travel route based on the route-to-destination information.

In an embodiment, a remotely guided, omnidirectional, transport and support vehicle **102** includes a vehicle navigation controller **156** including a communication module having at least one of a receiver **132**, transmitter **134**, and transceiver **136** operable

to communicate with a remote navigation network and to receive control command information (*e.g.*, route-to-destination information, navigation information, location based control commands, etc.) from the remote navigation network. In an embodiment, the vehicle navigation controller **156** includes a route-status module including circuitry operable to provide one or more of travel route image information, patient-support vehicle geographic location information, patient-support vehicle travel direction information, patient-support vehicle travel velocity information, patient-support vehicle propulsion information, or patient-support vehicle braking information.

In an embodiment, the vehicle navigation controller **156** is operably coupled to at least one of a body structure, a plurality of rotatable members **110**, a steering assembly **126**, a power source **116**, and a motor **118**. In an embodiment, the vehicle navigation controller **156** is configured to generate one or more control commands for navigating a remotely guided, self-propelled, transport and support vehicle **102** to at least a first patient destination along a patient travel route based on the control command information from the remote navigation network. For example, in an embodiment, the vehicle navigation controller **156** includes a patient destination module for generating one or more control commands for navigating a remotely guided, self-propelled, transport and support vehicle **102** to at least a first patient destination along a patient travel route based on the control command information from the remote navigation network.

In an embodiment, the vehicle navigation controller **156** is configured to navigate to a target patient destination satisfying a threshold criterion responsive to receipt of the control command information responsive to control command information received from the remote navigation network. In an embodiment, the vehicle navigation controller **156** is configured to navigate to a target patient destination responsive to control command information received from the remote navigation network. In an embodiment, the vehicle navigation controller **156** is configured to switch from an automatic controlled state, a manual controlled state, an operator-guided state, or a remote controlled state to a different one of the automatic controlled state, the manual controlled state, or the remote controlled state, responsive to control command information received from the remote navigation network.

In an embodiment, the transport and support vehicle **102** includes one or more travel route sensors **150** operably coupled to the vehicle navigation controller **156**. In an embodiment, the one or more travel route sensors **150** are configured to detect a travel

distance of at least one travel increment along the patient travel route. In an embodiment, the vehicle navigation controller **156** is configured to determine one or more of a total travel distance, a travel direction, or a travel velocity based on the travel distance of the at least one travel increment along the patient travel route. In an embodiment, the vehicle navigation controller **156** is configured to generate one or more control commands for varying one or more of propulsion, braking, or steering to direct the transport and support vehicle **102** along the target patient travel route based on the travel distance of the at least one travel increment along the patient travel route.

In an embodiment, the transport and support vehicle **102** includes a speech recognition module that causes the vehicle navigation controller **156** to execute one or more control commands for navigating a remotely guided, self-propelled, transport and support vehicle **102** to a subsequent travel position along a patient travel route responsive to an input from the speech recognition module. In an embodiment, the transport and support vehicle **102** includes a speech recognition module that causes the vehicle navigation controller **156** to execute one or more control commands for toggling between two or more control states. In an embodiment, the transport and support vehicle **102** includes one or more travel route sensors **150** that generate at least one measurand indicative of movement of a remotely guided, self-propelled, transport and support vehicle **102** to a surface region traversed by a remotely guided, self-propelled, transport and support vehicle **102** and generate vehicle displacement information based on the at least one measurand indicative of movement. In an embodiment, the transport and support vehicle **102** includes at least one traction wheel for propelling a remotely guided, self-propelled, transport and support vehicle **102** along a travel route.

In an embodiment, the vehicle navigation controller **156** includes one or more system sub-controllers. In an embodiment, the vehicle navigation controller **156** is operably coupled to one or more of propulsion controllers, braking controllers, or steering controllers. In an embodiment, the vehicle navigation controller **156** includes one or more of propulsion controllers, braking controllers, or steering controllers. In an embodiment, the vehicle navigation controller **156** is operably coupled to one or more of a propulsion system, a brake system, or a steering system of a remotely guided, self-propelled, transport and support vehicle **102**. In an embodiment, the vehicle navigation controller **156** is operably coupled to one or more of a propulsion system, a brake system, or a steering system of a remotely guided, self-propelled, transport and support vehicle **102** and is

operable to switch the state of at least one of the propulsion system, the brake system, and the steering system from an automatic controlled state, a manual controlled state, an operator-guided state, or a remote controlled state, to a different one of the automatic controlled state, the manual controlled state, or the remote controlled state.

In an embodiment, the vehicle navigation controller **156** is operable to connect to a local area network (LAN), a wide area network (WAN), an enterprise-wide computer network, an enterprise-wide intranet, or the Internet. In an embodiment, a remotely guided, transport and support vehicle **102** includes a body structure having a transport assembly having a steering assembly **126** and a power train. In an embodiment, the transport and support vehicle **102** includes a vehicle navigation controller **156** including a communication interface **131** having at least one of a receiver **132**, transmitter **134**, and transceiver **136** operable to communicate with a remote navigation network and to receive travel-route information and at least one of propulsion control command information, braking command information, or steering command information from the remote navigation network so as to reach a patient destination along a patient travel route. In an embodiment, the vehicle navigation controller **156** is operably coupled to at least one of transport assembly, steering assembly **126**, and power train, and configured to generate at least one navigation control command for controlling at least one of propulsion, braking, and steering of a remotely guided, self-propelled, transport and support vehicle **102** based on the propulsion control command information, the braking command information, or the steering command information from the remote navigation network.

In an embodiment, the vehicle navigation controller **156** is configured to generate one or more control commands for navigating a remotely guided, self-propelled, transport and support vehicle **102** to at least a first patient travel position responsive to the travel-route information and the at least one of propulsion control command information, braking command information, and steering command information from the remote navigation network. In an embodiment, the transport and support vehicle **102** includes one or more travel route sensors **150** that monitor a distance traveled by a remotely guided, self-propelled, transport and support vehicle **102**. In an embodiment, the vehicle navigation controller **156** is configured to generate a plurality of target travel increments corresponding to a patient travel route to a patient destination.

In an embodiment, the transport and support vehicle **102** includes a self-propelled patient-support status reporter device including one or more transceivers or transmitters

that generate an output indicative of an authorization to operate the self-propelled patient-support and transport vehicle. In an embodiment, the vehicle navigation controller **156** is configured to execute one or more navigation control commands for controlling one or more of propulsion, braking, or steering to direct the transport and support vehicle **102** along the patient travel route responsive to the travel-route information and the at least one of propulsion control command information, braking command information, and steering command information from the remote navigation network.

Referring to Figure 4, in an embodiment, an article of manufacture **402** includes a non-transitory signal-bearing medium bearing one or more instructions for detecting an operator-guide identification device **146** associated with operator-guide. In an embodiment, an article of manufacture **402** includes a non-transitory signal-bearing medium bearing one or more instructions for acquiring operator-guide verification information from the operator-guide identification device **146**. In an embodiment, the operator-authorization device **130** to be acquired including information indicative of at least one of an operator-guide authorization status, an operator-guide identity, and an operator-guide reference guidance information. In an embodiment, an article of manufacture **402** includes a non-transitory signal-bearing medium bearing one or more instructions for generating one or more control commands for maintaining a self-propelled operator-guided vehicle at target separation from the operator-guide identification device **146**. In an embodiment, an article of manufacture **402** includes a non-transitory signal-bearing medium bearing one or more instructions for detecting a location of the operator-guide identification device **146** associated with the operator-guide.

In an embodiment, an article of manufacture **402** includes a non-transitory signal-bearing medium bearing one or more instructions for generating one or more control commands for maintaining the self-propelled operator-guided vehicle at a target separation from the operator-guide identification device **146** responsive to a change of location of the operator-guide identification device **146** relative to the self-propelled operator-guided vehicle. In an embodiment, an article of manufacture **402** includes a non-transitory signal-bearing medium bearing one or more instructions for determining a location of the operator-guide identification device **146** associated with the operator-guide relative to the self-propelled operator-guided vehicle. In an embodiment, an article of manufacture **402** includes a non-transitory signal-bearing medium bearing one or more instructions for determining a velocity difference between the operator-guide identification device **146** and

the self-propelled operator-guided vehicle. In an embodiment, an article of manufacture **402** includes a non-transitory signal-bearing medium bearing one or more instructions for controlling one or more of propulsion, braking, or steering responsive to detected velocity difference between the operator-guide identification device **146** and the self-propelled operator-guided vehicle.

Referring to Figure **5**, in an embodiment, an article of manufacture **502** includes a non-transitory signal-bearing medium bearing one or more instructions for acquiring physical movement image information of an operator within an operator-guide zone **142**. In an embodiment, an article of manufacture **502** includes a non-transitory signal-bearing medium bearing one or more instructions for determining operator-guide verification information for the operator within the operator-guide zone **142** based on the physical movement image information. In an embodiment, an article of manufacture **502** includes a non-transitory signal-bearing medium bearing one or more instructions for mapping one or more physical movements of the operator within the operator-guide zone **142** to at least one input correlated with one or more navigation control commands for controlling a self-propelled operator-guided bed.

In an embodiment, an article of manufacture **502** includes a non-transitory signal-bearing medium bearing one or more instructions for navigating the self-propelled operator-guided bed based on the one or more navigation control commands. In an embodiment, an article of manufacture **502** includes a non-transitory signal-bearing medium bearing one or more instructions for generating a virtual representation of at least one of a locality of the operator within the operator-guide zone **142** and a locality the self-propelled operator-guided bed on a virtual display **206**. In an embodiment, an article of manufacture **502** includes a non-transitory signal-bearing medium bearing one or more instructions for generating a virtual representation of the one or more physical movements on a virtual display **206**. In an embodiment, an article of manufacture **502** includes a non-transitory signal-bearing medium bearing one or more instructions for generating a virtual representation of the one or more navigation control commands on a virtual display **206**.

In an embodiment, an article of manufacture **502** includes a non-transitory signal-bearing medium bearing one or more instructions for determining a travel route based on one or more detected physical movements of the operator within the operator-guide zone **142**. In an embodiment, an article of manufacture **502** includes a non-transitory signal-bearing medium bearing one or more instructions for determining at least a first travel

destination based on the one or more detected physical movements of the operator within the operator-guide zone **142**. In an embodiment, an article of manufacture **502** includes a non-transitory signal-bearing medium bearing one or more instructions for registering a physical location of the operator within the operator-guide zone **142** relative the self-propelled operator-guided bed, and generating registration information. In an embodiment, an article of manufacture **502** includes a non-transitory signal-bearing medium bearing one or more instructions for generating a virtual representation of at least one of a locality of the operator within the operator-guide zone **142** and a locality the self-propelled operator-guided bed within a physical space on a virtual display **206** based on the registration information. In an embodiment, an article of manufacture **502** includes a non-transitory signal-bearing medium bearing one or more instructions for controlling one or more of propulsion, braking, or steering of the self-propelled operator-guided bed based on the at least one input.

Referring to Figure 6, in an embodiment, an article of manufacture **602** includes a non-transitory signal-bearing medium bearing one or more instructions for determining a position, velocity, acceleration, bearing, direction, rate-of-change of bearing, rate-of-change of direction, etc., of a self-guided hospital bed. In an embodiment, an article of manufacture **602** includes a non-transitory signal-bearing medium bearing one or more instructions for generating self-guided hospital bed status information. In an embodiment, an article of manufacture **602** includes a non-transitory signal-bearing medium bearing one or more instructions for generating route-to-destination information based on one or more target location inputs and the self-guided hospital bed status information. In an embodiment, an article of manufacture **602** includes a non-transitory signal-bearing medium bearing one or more instructions for generating one or more control commands for navigating the self-guided hospital bed to a second position along a travel route based on the route-to-destination information. In an embodiment, an article of manufacture **602** includes a non-transitory signal-bearing medium bearing one or more instructions for enabling at least one of remote control, manual control, and automatic control of at least one of a propulsion system, braking system, and steering system of the self-guided hospital bed based on the position, velocity, acceleration, bearing, direction, rate-of-change of bearing, or rate-of-change of direction of the self-guided hospital bed.

The claims, description, and drawings of this application may describe one or more of the instant technologies in operational/functional language, for example as a set of

operations to be performed by a computer. Such operational/functional description in most instances can be specifically-configured hardware (*e.g.*, because a general purpose computer in effect becomes a special purpose computer once it is programmed to perform particular functions pursuant to instructions from program software).

Importantly, although the operational/functional descriptions described herein are understandable by the human mind, they are not abstract ideas of the operations/functions divorced from computational implementation of those operations/functions. Rather, the operations/functions represent a specification for the massively complex computational machines or other means. As discussed in detail below, the operational/functional language must be read in its proper technological context, i.e., as concrete specifications for physical implementations.

The logical operations/functions described herein are a distillation of machine specifications or other physical mechanisms specified by the operations/functions such that the otherwise inscrutable machine specifications may be comprehensible to the human mind. The distillation also allows one of skill in the art to adapt the operational/functional description of the technology across many different specific vendors' hardware configurations or platforms, without being limited to specific vendors' hardware configurations or platforms.

Some of the present technical description (*e.g.*, detailed description, drawings, claims, etc.) may be set forth in terms of logical operations/functions. As described in more detail in the following paragraphs, these logical operations/functions are not representations of abstract ideas, but rather representative of static or sequenced specifications of various hardware elements. Differently stated, unless context dictates otherwise, the logical operations/functions are representative of static or sequenced specifications of various hardware elements. This is true because tools available to implement technical disclosures set forth in operational/functional formats—tools in the form of a high-level programming language (*e.g.*, C, java, visual basic), etc.), or tools in the form of Very high speed Hardware Description Language ("VHDL," which is a language that uses text to describe logic circuits–)—are generators of static or sequenced specifications of various hardware configurations. This fact is sometimes obscured by the broad term "software," but, as shown by the following explanation, what is termed "software" is a shorthand for a massively complex interchaining/specification of ordered-matter elements. The term "ordered-matter elements" may refer to physical components

of computation, such as assemblies of electronic logic gates, molecular computing logic constituents, quantum computing mechanisms, etc.

For example, a high-level programming language is a programming language with strong abstraction, *e.g.*, multiple levels of abstraction, from the details of the sequential organizations, states, inputs, outputs, etc., of the machines that a high-level programming language actually specifies. See, *e.g.*, Wikipedia, High-level programming language, http://en.wikipedia.org/wiki/High-level_programming_language (as of June 5, 2012, 21:00 GMT). In order to facilitate human comprehension, in many instances, high-level programming languages resemble or even share symbols with natural languages. See, *e.g.*, Wikipedia, Natural language, http://en.wikipedia.org/wiki/Natural_language (as of June 5, 2012, 21:00 GMT).

It has been argued that because high-level programming languages use strong abstraction (*e.g.*, that they may resemble or share symbols with natural languages), they are therefore a "purely mental construct." (*e.g.*, that "software" – a computer program or computer –programming—is somehow an ineffable mental construct, because at a high level of abstraction, it can be conceived and understood in the human mind). This argument has been used to characterize technical description in the form of functions/operations as somehow "abstract ideas." In fact, in technological arts (*e.g.*, the information and communication technologies) this is not true.

The fact that high-level programming languages use strong abstraction to facilitate human understanding should not be taken as an indication that what is expressed is an abstract idea. In an embodiment, if a high-level programming language is the tool used to implement a technical disclosure in the form of functions/operations, it can be understood that, far from being abstract, imprecise, "fuzzy," or "mental" in any significant semantic sense, such a tool is instead a near incomprehensibly precise sequential specification of specific computational –machines—the parts of which are built up by activating/selecting such parts from typically more general computational machines over time (*e.g.*, clocked time). This fact is sometimes obscured by the superficial similarities between high-level programming languages and natural languages. These superficial similarities also may cause a glossing over of the fact that high-level programming language implementations ultimately perform valuable work by creating/controlling many different computational machines.

The many different computational machines that a high-level programming language specifies are almost unimaginably complex. At base, the hardware used in the computational machines typically consists of some type of ordered matter (*e.g.*, traditional electronic devices (*e.g.*, transistors), deoxyribonucleic acid (DNA), quantum devices, mechanical switches, optics, fluidics, pneumatics, optical devices (*e.g.*, optical interference devices), molecules, etc.) that are arranged to form logic gates. Logic gates are typically physical devices that may be electrically, mechanically, chemically, or otherwise driven to change physical state in order to create a physical reality of Boolean logic.

Logic gates may be arranged to form logic circuits, which are typically physical devices that may be electrically, mechanically, chemically, or otherwise driven to create a physical reality of certain logical functions. Types of logic circuits include such devices as multiplexers, registers, arithmetic logic units (ALUs), computer memory devices, etc., each type of which may be combined to form yet other types of physical devices, such as a central processing unit (CPU)—the best known of which is the microprocessor. A modern microprocessor will often contain more than one hundred million logic gates in its many logic circuits (and often more than a billion transistors). See, *e.g.*, Wikipedia, Logic gates, http://en.wikipedia.org/wiki/Logic_gates (as of June 5, 2012, 21:03 GMT).

The logic circuits forming the microprocessor are arranged to provide a microarchitecture that will carry out the instructions defined by that microprocessor's defined Instruction Set Architecture. The Instruction Set Architecture is the part of the microprocessor architecture related to programming, including the native data types, instructions, registers, addressing modes, memory architecture, interrupt and exception handling, and external Input/Output. See, *e.g.*, Wikipedia, Computer architecture, http://en.wikipedia.org/wiki/Computer_architecture (as of June 5, 2012, 21:03 GMT).

The Instruction Set Architecture includes a specification of the machine language that can be used by programmers to use/control the microprocessor. Since the machine language instructions are such that they may be executed directly by the microprocessor, typically they consist of strings of binary digits, or bits. For example, a typical machine language instruction might be many bits long (*e.g.*, 32, 64, or 128 bit strings are currently common). A typical machine language instruction might take the form "11110000101011110000111100111111" (a 32 bit instruction).

It is significant here that, although the machine language instructions are written as sequences of binary digits, in actuality those binary digits specify physical reality. For example, if certain semiconductors are used to make the operations of Boolean logic a physical reality, the apparently mathematical bits "1" and "0" in a machine language instruction actually constitute a shorthand that specifies the application of specific voltages to specific wires. For example, in some semiconductor technologies, the binary number "1" (*e.g.*, logical "1") in a machine language instruction specifies around +5 volts applied to a specific "wire" (*e.g.*, metallic traces on a printed circuit board) and the binary number "0" (*e.g.*, logical "0") in a machine language instruction specifies around -5 volts applied to a specific "wire." In addition to specifying voltages of the machines' configuration, such machine language instructions also select out and activate specific groupings of logic gates from the millions of logic gates of the more general machine. Thus, far from abstract mathematical expressions, machine language instruction programs, even though written as a string of zeros and ones, specify many, many constructed physical machines or physical machine states.

Machine language is typically incomprehensible by most humans (*e.g.*, the above example was just ONE instruction, and some personal computers execute more than two billion instructions every second). See, *e.g.*, Wikipedia, Instructions per second, http://en.wikipedia.org/wiki/Instructions_per_second (as of June 5, 2012, 21:04 GMT).

Thus, programs written in machine language—which may be tens of millions of machine language instructions long—are incomprehensible. In view of this, early assembly languages were developed that used mnemonic codes to refer to machine language instructions, rather than using the machine language instructions' numeric values directly (*e.g.*, for performing a multiplication operation, programmers coded the abbreviation "mult," which represents the binary number "011000" in MIPS machine code). While assembly languages were initially a great aid to humans controlling the microprocessors to perform work, in time the complexity of the work that needed to be done by the humans outstripped the ability of humans to control the microprocessors using merely assembly languages.

At this point, it was noted that the same tasks needed to be done over and over, and the machine language necessary to do those repetitive tasks was the same. In view of this, compilers were created. A compiler is a device that takes a statement that is more comprehensible to a human than either machine or assembly language, such as "add 2 + 2

and output the result," and translates that human understandable statement into a complicated, tedious, and immense machine language code (*e.g.*, millions of 32, 64, or 128 bit length strings). Compilers thus translate high-level programming language into machine language.

This compiled machine language, as described above, is then used as the technical specification which sequentially constructs and causes the interoperation of many different computational machines such that humanly useful, tangible, and concrete work is done. For example, as indicated above, such machine language– the compiled version of the higher-level language– functions as a technical specification which selects out hardware logic gates, specifies voltage levels, voltage transition timings, etc., such that the humanly useful work is accomplished by the hardware.

Thus, a functional/operational technical description, when viewed by one of skill in the art, is far from an abstract idea. Rather, such a functional/operational technical description, when understood through the tools available in the art such as those just described, is instead understood to be a humanly understandable representation of a hardware specification, the complexity and specificity of which far exceeds the comprehension of most any one human. Accordingly, any such operational/functional technical descriptions may be understood as operations made into physical reality by (a) one or more interchained physical machines, (b) interchained logic gates configured to create one or more physical machine(s) representative of sequential/combinatorial logic(s), (c) interchained ordered matter making up logic gates (*e.g.*, interchained electronic devices (*e.g.*, transistors), DNA, quantum devices, mechanical switches, optics, fluidics, pneumatics, molecules, etc.) that create physical reality representative of logic(s), or (d) virtually any combination of the foregoing. Indeed, any physical object which has a stable, measurable, and changeable state may be used to construct a machine based on the above technical description. Charles Babbage, for example, constructed the first computer out of wood and powered by cranking a handle.

Thus, far from being understood as an abstract idea, it can be recognizes that a functional/operational technical description as a humanly-understandable representation of one or more almost unimaginably complex and time sequenced hardware instantiations. The fact that functional/operational technical descriptions might lend themselves readily to high-level computing languages (or high-level block diagrams for that matter) that share some words, structures, phrases, etc. with natural language simply cannot be taken as an

indication that such functional/operational technical descriptions are abstract ideas, or mere expressions of abstract ideas. In fact, as outlined herein, in the technological arts this is simply not true. When viewed through the tools available to those of skill in the art, such functional/operational technical descriptions are seen as specifying hardware configurations of almost unimaginable complexity.

As outlined above, the reason for the use of functional/operational technical descriptions is at least twofold. First, the use of functional/operational technical descriptions allows near-infinitely complex machines and machine operations arising from interchained hardware elements to be described in a manner that the human mind can process (*e.g.*, by mimicking natural language and logical narrative flow). Second, the use of functional/operational technical descriptions assists the person of skill in the art in understanding the described subject matter by providing a description that is more or less independent of any specific vendor's piece(s) of hardware.

The use of functional/operational technical descriptions assists the person of skill in the art in understanding the described subject matter since, as is evident from the above discussion, one could easily, although not quickly, transcribe the technical descriptions set forth in this document as trillions of ones and zeroes, billions of single lines of assembly-level machine code, millions of logic gates, thousands of gate arrays, or any number of intermediate levels of abstractions. However, if any such low-level technical descriptions were to replace the present technical description, a person of skill in the art could encounter undue difficulty in implementing the disclosure, because such a low-level technical description would likely add complexity without a corresponding benefit (*e.g.*, by describing the subject matter utilizing the conventions of one or more vendor-specific pieces of hardware). Thus, the use of functional/operational technical descriptions assists those of skill in the art by separating the technical descriptions from the conventions of any vendor-specific piece of hardware.

In view of the foregoing, the logical operations/functions set forth in the present technical description are representative of static or sequenced specifications of various ordered-matter elements, in order that such specifications may be comprehensible to the human mind and adaptable to create many various hardware configurations. The logical operations/functions disclosed herein should be treated as such, and should not be disparagingly characterized as abstract ideas merely because the specifications they

represent are presented in a manner that one of skill in the art can readily understand and apply in a manner independent of a specific vendor's hardware implementation.

At least a portion of the devices or processes described herein can be integrated into an information processing system. An information processing system generally includes one or more of a system unit housing, a video display device, memory, such as volatile or non-volatile memory, processors such as microprocessors or digital signal processors, computational entities such as operating systems, drivers, graphical user interfaces, and applications programs, one or more interaction devices (*e.g.,* a touch pad, a touch screen, an antenna, etc.), or control systems including feedback loops and control motors (*e.g.,* feedback for detecting position or velocity, control motors for moving or adjusting components or quantities). An information processing system can be implemented utilizing suitable commercially available components, such as those typically found in data computing/communication or network computing/communication systems.

Those having skill in the art will recognize that the state of the art has progressed to the point where there is little distinction left between hardware and software implementations of aspects of systems; the use of hardware or software is generally (but not always, in that in certain contexts the choice between hardware and software can become significant) a design choice representing cost vs. efficiency tradeoffs. Those having skill in the art will appreciate that there are various vehicles by which processes or systems or other technologies described herein can be effected (*e.g.*, hardware, software, firmware, etc., in one or more machines or articles of manufacture), and that the preferred vehicle will vary with the context in which the processes, systems, other technologies, etc., are deployed. For example, if an implementer determines that speed and accuracy are paramount, the implementer may opt for a mainly hardware or firmware vehicle; alternatively, if flexibility is paramount, the implementer may opt for a mainly software implementation that is implemented in one or more machines or articles of manufacture; or, yet again alternatively, the implementer may opt for some combination of hardware, software, firmware, etc. in one or more machines or articles of manufacture. Hence, there are several possible vehicles by which the processes, devices, other technologies, etc., described herein may be effected, none of which is inherently superior to the other in that any vehicle to be utilized is a choice dependent upon the context in which the vehicle will be deployed and the specific concerns (*e.g.*, speed, flexibility, or predictability) of the implementer, any of which may vary. In an embodiment, optical aspects of

implementations will typically employ optically-oriented hardware, software, firmware, etc., in one or more machines or articles of manufacture.

The herein described subject matter sometimes illustrates different components contained within, or connected with, different other components. It is to be understood that such depicted architectures are merely examples, and that in fact, many other architectures can be implemented that achieve the same functionality. In a conceptual sense, any arrangement of components to achieve the same functionality is effectively "associated" such that the desired functionality is achieved. Hence, any two components herein combined to achieve a particular functionality can be seen as "associated with" each other such that the desired functionality is achieved, irrespective of architectures or intermedial components. Likewise, any two components so associated can also be viewed as being "operably connected", or "operably coupled, " to each other to achieve the desired functionality, and any two components capable of being so associated can also be viewed as being "operably coupleable, " to each other to achieve the desired functionality. Specific examples of operably coupleable include, but are not limited to, physically mateable, physically interacting components, wirelessly interactable, wirelessly interacting components, logically interacting, logically interactable components, etc.

In an embodiment, one or more components may be referred to herein as "configured to," "configurable to," "operable/operative to," "adapted/adaptable," "able to," "conformable/conformed to," etc. Such terms (*e.g.,* "configured to") can generally encompass active-state components, or inactive-state components, or standby-state components, unless context requires otherwise.

The foregoing detailed description has set forth various embodiments of the devices or processes *via* the use of block diagrams, flowcharts, or examples. Insofar as such block diagrams, flowcharts, or examples contain one or more functions or operations, it will be understood by the reader that each function or operation within such block diagrams, flowcharts, or examples can be implemented, individually or collectively, by a wide range of hardware, software, firmware in one or more machines or articles of manufacture, or virtually any combination thereof. Further, the use of "Start," "End," or "Stop" blocks in the block diagrams is not intended to indicate a limitation on the beginning or end of any functions in the diagram. Such flowcharts or diagrams may be incorporated into other flowcharts or diagrams where additional functions are performed before or after the functions shown in the diagrams of this application. In an embodiment,

several portions of the subject matter described herein is implemented *via* Application Specific Integrated Circuits (ASICs), Field Programmable Gate Arrays (FPGAs), digital signal processors (DSPs), or other integrated formats. However, some aspects of the embodiments disclosed herein, in whole or in part, can be equivalently implemented in integrated circuits, as one or more computer programs running on one or more computers (*e.g.,* as one or more programs running on one or more computer systems), as one or more programs running on one or more processors (*e.g.,* as one or more programs running on one or more microprocessors), as firmware, or as virtually any combination thereof, and that designing the circuitry or writing the code for the software and or firmware would be well within the skill of one of skill in the art in light of this disclosure. In addition, the mechanisms of the subject matter described herein are capable of being distributed as a program product in a variety of forms, and that an illustrative embodiment of the subject matter described herein applies regardless of the particular type of signal-bearing medium used to actually carry out the distribution. Non-limiting examples of a signal-bearing medium include the following: a recordable type medium such as a floppy disk, a hard disk drive, a Compact Disc (CD), a Digital Video Disk (DVD), a digital tape, a computer memory, etc.; and a transmission type medium such as a digital or an analog communication medium (*e.g.,* a fiber optic cable, a waveguide, a wired communications link, a wireless communication link (*e.g.,* transmitter, receiver, transmission logic, reception logic, etc.), etc.).

While particular aspects of the present subject matter described herein have been shown and described, it will be apparent to the reader that, based upon the teachings herein, changes and modifications can be made without departing from the subject matter described herein and its broader aspects and, therefore, the appended claims are to encompass within their scope all such changes and modifications as are within the true spirit and scope of the subject matter described herein. In general, terms used herein, and especially in the appended claims (*e.g.,* bodies of the appended claims) are generally intended as "open" terms (*e.g.,* the term "including" should be interpreted as "including but not limited to, " the term "having" should be interpreted as "having at least, " the term "includes" should be interpreted as "includes but is not limited to, " etc.). Further, if a specific number of an introduced claim recitation is intended, such an intent will be explicitly recited in the claim, and in the absence of such recitation no such intent is present. For example, as an aid to understanding, the following appended claims may

contain usage of the introductory phrases "at least one" and "one or more" to introduce claim recitations. However, the use of such phrases should not be construed to imply that the introduction of a claim recitation by the indefinite articles "a" or "an" limits any particular claim containing such introduced claim recitation to claims containing only one such recitation, even when the same claim includes the introductory phrases "one or more" or "at least one" and indefinite articles such as "a" or "an" (*e.g.,* "a" and/or "an" should typically be interpreted to mean "at least one" or "one or more"); the same holds true for the use of definite articles used to introduce claim recitations. In addition, even if a specific number of an introduced claim recitation *is* explicitly recited, such recitation should typically be interpreted to mean *at least* the recited number (*e.g.,* the bare recitation of "two recitations, " without other modifiers, typically means *at least* two recitations, or *two or more* recitations). Furthermore, in those instances where a convention analogous to "at least one of A, B, and C, etc." is used, in general such a construction is intended in the sense of the convention (*e.g.,* " a system having at least one of A, B, and C" would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together, etc.). In those instances where a convention analogous to "at least one of A, B, or C, etc." is used, in general such a construction is intended in the sense of the convention (*e.g.,* " a system having at least one of A, B, or C" would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together, etc.). Typically a disjunctive word or phrase presenting two or more alternative terms, whether in the description, claims, or drawings, should be understood to contemplate the possibilities of including one of the terms, either of the terms, or both terms unless context dictates otherwise. For example, the phrase "A or B" will be typically understood to include the possibilities of "A" or "B" or "A and B."

With respect to the appended claims, the operations recited therein generally may be performed in any order. Also, although various operational flows are presented in a sequence(s), it should be understood that the various operations may be performed in orders other than those that are illustrated, or may be performed concurrently. Examples of such alternate orderings includes overlapping, interleaved, interrupted, reordered, incremental, preparatory, supplemental, simultaneous, reverse, or other variant orderings, unless context dictates otherwise. Furthermore, terms like "responsive to," "related to," or

other past-tense adjectives are generally not intended to exclude such variants, unless context dictates otherwise.

While various aspects and embodiments have been disclosed herein, other aspects and embodiments are contemplated. The various aspects and embodiments disclosed herein are for purposes of illustration and are not intended to be limiting, with the true scope and spirit being indicated by the following claims.

CLAIMS

What is claimed is:

1. A vehicle for transporting an individual subject, comprising:
a body structure including a plurality of rotatable members operable to frictionally interface the vehicle to a travel path and to move the vehicle along the travel path, and a surface structured and dimensioned to support an individual subject;
a steering assembly operably coupled to at least one of the rotatable members;
a power source operably coupled to one or more of the plurality of rotatable members and configured to rotate at least one of the plurality of rotatable members;
an imager operable to image a person within an image zone, and
a verification module for determining whether the person in the image zone is an authorized operator of the vehicle;
wherein the imager is operably coupled to the power source and the body structure, the imager including one or more modules having circuitry operable to control the power source and steering assembly so as to maintain the authorized operator in the image zone.

2. The vehicle for transporting the individual subject of claim 1, wherein the imager includes an image recognition module operable to recognize a badge associated with the operator.

3. The vehicle for transporting the individual subject of claim 1, wherein the steering assembly is communicatively coupled to the imager and is configured to vary a vehicle heading based on one or more inputs from the imager indicative of a change in position by the authorized operator.

4. The vehicle for transporting the individual subject of claim 1, wherein the steering assembly includes at least one of a steering sensor configured to detect a steering angle associated with a steered one of the plurality of rotatable members; a vehicle acceleration sensor configured to detect an acceleration of the vehicle, a vehicle

position sensor configured to detect a location of the vehicle, and a rotational rate sensor configured to detect a rate of rotation of the vehicle.

5. A self-propelled operator-guided vehicle system, comprising:

a self-propelled operator-guided vehicle including a bedframe structure having a surface configured to support a patient, the bedframe structure including a plurality of rotatable members operable to frictionally interface the vehicle to a travel path and to move the vehicle along the travel path, and a navigation system configured to vary one or more of propulsion, braking, or steering angle of at least one of the plurality of rotatable members;

an operator-authorization device operably coupled to the transport assembly and having

one or more sensors operable to detect an operator-guide identification device associated with an operator-guide, and

a communication interface configured to acquire operator-guide verification information from the operator-guide identification device,

the operator-authorization device configured to

acquire information indicative of at least one of an operator-guide authorization status, an operator-guide identity, and operator-guide reference physical movement information; and

generate one or more control commands for causing the transport assembly to maintaining the self-propelled operator-guided vehicle at a target separation from the authorized operator-guide identification device based on the at least one of the operator-guide authorization status, the operator-guide identity, and the operator-guide reference physical movement information.

6. The self-propelled operator-guided vehicle system of claim 5, wherein the operator-authorization device is configured to acquire navigation plan information from the operator-guide identification device and to cause the generation of the one or more control commands for causing the transport assembly to maintaining the self-propelled operator-guided vehicle at the target separation from the authorized operator-guide identification device based on the navigation plan information.

7. The self-propelled operator-guided vehicle system of claim 5, wherein the operator-authorization device includes a navigation module operably coupled to the one or more sensors and is configured to generate one or more control commands for maintaining a velocity differences between the self-propelled operator-guided vehicle and the operator-guide identification device within a target range.

8. The self-propelled operator-guided vehicle system of claim 5, wherein the operator-authorization device is configured to generate one or more control commands for controlling one or more of propulsion, braking, or steering responsive to movement of the operator-guide identification device responsive to a communication loss between the operator-guide identification device and the self-propelled operator-guided vehicle.

9. A self-propelled operator-guided vehicle for transporting and supporting at least one individual subject, comprising:

an operator-authorization device including

a one or more image sensors for acquiring image information of a human operator within an operator-guide zone, and

a verification module for determining whether the human operator is an authorized operator based on the image information;

a bedframe structure including a surface configured to support an individual subject and a transport assembly having a plurality of rotatable members operable to frictionally interface a self-propelled operator-guided vehicle to a travel path and to move the vehicle along the travel path, and a steering assembly operable to vary a steering angle of at least one of the plurality of rotatable members;

a powertrain for driving one or more of the plurality of rotatable members; and

an operator-guided vehicle navigation controller operably coupled to at least one or more of the operator-authorization device, the steering assembly, and the powertrain, the operator-guided vehicle navigation controller including a control command module operable to determine physical movement information from the image information and to map one or more physical movements of the authorized human operator within the operator-guide

zone to at least one input correlated with one or more navigation control commands for controlling the self-propelled operator-guided vehicle based on the physical movement information.

10. The self-propelled operator-guided vehicle for transporting and supporting the at least one individual subject of claim 9, further comprising:

a virtual object generator operably coupled to the operator-guide vehicle navigation controller and configured to generate a virtual representation of at least one of a locality of the human operator within the operator-guide zone or a locality the self-propelled operator-guided vehicle within a physical space on a virtual display.

11. The self-propelled operator-guided vehicle for transporting and supporting the at least one individual subject of claim 9, further comprising:

a virtual object generator operably coupled to the operator-guide vehicle navigation controller and configured to generate a virtual representation of the one or more navigation control commands on a virtual display.

12. A self-propelled hospital bed navigation control system, comprising:

an operator-guided vehicle navigation controller including

one or more sensors operable to detect at least one human operator within an operator-guide zone associated with a self-propelled operator-guided hospital bed having

a bedframe structure including a surface configured to support an individual subject,

a plurality of rotatable members operable to frictionally interface the vehicle to a travel path and to move the vehicle along the travel path,

a steering assembly operable to vary a steering angle of at least one of the plurality of rotatable members,

a power source, and

a motor for driving one or more of the plurality of rotatable members; and

an operator movement mapping module operably coupled to the operator-guided

vehicle navigation controller and to at least one of the plurality of rotatable members, the power source, and the motor;

the operator movement mapping module configured to

map one or more physical movements of the human operator within the operator-guide zone to at least one input correlated with one or more navigation control commands for controlling the self-propelled operator-guided vehicle, and

generate a control signal to at least one of the plurality of rotatable members, the power source, and the motor to navigate the self-propelled operator-guided vehicle based on the one or more navigation control commands.

13. The self-propelled hospital bed navigation control system of claim 12, wherein the operator-guided vehicle navigation controller includes one or more transducers operable to detect an acoustic authorization signal from an identification device associated with the at least one human operator.

14. The self-propelled hospital bed navigation control system of claim 12, further comprising:

a fail-safe control system that physically couples the self-propelled hospital bed to the at least one human operator, the operator-guided vehicle navigation controller operable to activate a fail-safe protocol during a fail-safe mode of operation.

15. The self-propelled hospital bed navigation control system of claim 12, further comprising:

a collision avoidance system operably coupled to the operator-guided vehicle navigation controller and including one or more sensors operable to detect a travel path condition, the operator-guided vehicle navigation controller configured to generate a control signal to at least one of the plurality of rotatable members, the power source, a braking mechanism, and the motor to navigate the self-propelled operator-guided vehicle based on one or more measurands outputs from the collision avoidance system.

16. A self-propelled hospital bed controller system, comprising:

an operator-guided vehicle navigation controller including an audio-activated control module having one or more transducers operable to receive an audio input from an operator; and

an audio input mapping module including circuitry operable to correlate the audio input from the operator to at least one navigation control command for controlling at least one of propulsion, braking, and steering of the self-propelled hospital bed.

17. The self-propelled hospital bed controller system of claim 16, wherein the audio-activated control module includes a speech recognition device configured to correlate speech input to at least one navigation control command for controlling at least one of propulsion, braking, and steering of the self-propelled hospital bed.



100
102
130 Operator-Authorization Device
131
Antenna
132 Receiver
134 Transmitter
136 Transceiver
150 Sensor
150 Sensor
150 Sensor
144 Verification Module
148 Tracking Module
152 Negotiation Module
154 Navigation Module
122 Drive Control Module
124 Brake Control Module
128 Steering Control Module
156 Navigation Controller
138 Imager 132 134 136
150 Sensor
Object Sensor
Tracking Sensor
Movement Sensor
Image Sensor
Propulsion Controller
Registration Module
Cont. Command Module
146
142
140
160
138
106
128
108
154
102
104
124
110
122
118
120
116
126
112
114
110

Fig. 1



102
202 Virtual Object Generator
122 Drive Control Module
124 Brake Control Module
128 Steering Control Module
144 Verification Module
148 Tracking Module
152 Negotiation Module
154 Navigation Module
156 Navigation Controller
Propulsion Controller
Registration Module
Cont. Command Module
150 Sensor
Object Sensor
Tracking Sensor
Movement Sensor
Image Sensor
138 Imager
132
136
134
User Interface
Network
146
208
210
212
214
204
206
102
104
112
110
154
108
124
122
128
110
118
114
106
126
112
116
160
138
140

Fig. 2



300
202 Virtual Object Generator
122 Drive Control Module
124 Brake Control Module
128 Steering Control Module
144 Verification Module
148 Tracking Module
152 Negotiation Module
154 Navigation Module
156 Navigation Controller
308 Fail-Safe Module
310 Audio Input Control Device
312 Audio-Activated Cont. Module
314 Audio Control Module
316 Voice-Command Recogn. Dev.
318 Speech Recognition Device
320 Speech Control Module
146
208
210
212
214
204
206
102
104
112
110
154
108
124
122
128
118
110
114
126
112
140
160
306
304
302

Fig. 3

Fig. 4

402
one or more instructions for detecting an operator-guide identification device associated with operator-guide
one or more instructions for acquiring operator-guide verification data from the operator-guide identification device, the operator-guide verification data to be acquired including data indicative of at least one of an operator-guide authorization status, an operator-guide identity, or an operator-guide reference guidance data
one or more instructions for generating one or more control commands for maintaining a self-propelled operator-guided vehicle at target separation from the operator-guide identification device
one or more instructions for detecting a location of the operator-guide identification device associated with the operator-guide
one or more instructions for generating one or more control commands for maintaining the self-propelled operator-guided vehicle at a target separation from the operator-guide identification device responsive to a change of location of the operator-guide identification device relative to the self-propelled operator-guided vehicle
one or more instructions for determining a location of the operator-guide identification device associated with the operator-guide relative to the self-propelled operator-guided vehicle
one or more instructions for determining a velocity difference between the operator-guide identification device and the self-propelled operator-guided vehicle
a non-transitory signal-bearing medium bearing one or more instructions for controlling one or more of propulsion, braking, or steering responsive to detected velocity difference between the operator-guide identification device and the self-propelled operator-guided vehicle

Fig. 5

502
one or more instructions for acquiring physical movement image data of a human operator within an operator-guide zone
one or more instructions for determining operator-guide verification data for the human operator within the operator-guide zone based on the physical movement image data
one or more instructions for mapping one or more physical movements of the human operator within the operator-guide zone to at least one input correlated with one or more navigation control commands for controlling a self-propelled operator-guided bed
one or more instructions for navigating the self-propelled operator-guided bed based on the one or more navigation control commands
one or more instructions for generating a virtual representation of at least one of a locality of the human operator within the operator-guide zone or a locality the self-propelled operator-guided bed on a virtual display
one or more instructions for generating a virtual representation of the one or more physical movements on a virtual display
bearing one or more instructions for generating a virtual representation of the one or more navigation control commands on a virtual display
one or more instructions for determining a travel route based on one or more detected physical movements of the human operator within the operator-guide zone
one or more instructions for determining at least a first travel destination based on the one or more detected physical movements of the human operator within the operator-guide zone
one or more instructions for registering a physical location of the human operator within the operator-guide zone relative the self-propelled operator-guided bed, and generating registration data
one or more instructions for generating a virtual representation of at least one of a locality of the human operator within the operator-guide zone or a locality the self-propelled operator-guided bed within a physical space on a virtual display based on the registration data
one or more instructions for controlling one or more of propulsion, braking, or steering of the self-propelled operator-guided bed based on the to at least one input

Fig. 6

602

one or more instructions for determining a position, velocity, acceleration, bearing, direction, rate-of-change of bearing, or rate-of-change of direction of a self-guided hospital bed

one or more instructions for generating self-guided hospital bed status data

one or more instructions for generating route-to-destination data based on one or more target location inputs and the self-guided hospital bed status data

one or more instructions for generating one or more control commands for navigating the self-guided hospital bed to a second position along a travel route based on the route-to-destination data

one or more instructions for enabling at least one of remote control, manual control, or automatic control of at least one of a propulsion system, braking system, or steering system of the self-guided hospital bed based on the position, velocity, acceleration, bearing, direction, rate-of-change of bearing, or rate-of-change of direction of the self-guided hospital bed