

(19) **DANMARK**

(10) **DK/EP 3183121 T6**



(12)

Begrænsning af europæisk patentskrift

Patent- og
Varemærkestyrelsen

-
- (51) Int.Cl.: **B 41 J 2/175 (2006.01)** **G 03 G 15/02 (2006.01)** **G 03 G 15/08 (2006.01)**
G 03 G 21/18 (2006.01) **G 06 K 15/02 (2006.01)** **H 04 N 1/60 (2006.01)**
- (45) Oversættelsen bekendtgjort den: **2021-12-20**
- (80) Dato for Den Europæiske Patentmyndigheds bekendtgørelse om begrænsning af patentet: **2021-11-03**
- (86) Europæisk ansøgning nr.: **14898357.0**
- (86) Europæisk indleveringsdag: **2014-08-19**
- (87) Den europæiske ansøgnings publiceringsdag: **2017-06-28**
- (86) International ansøgning nr.: **US2014051684**
- (87) Internationalt publikationsnr.: **WO2016028272**
- (84) Designerede stater: **AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR**
- (73) Patenthaver: **Hewlett-Packard Development Company, L.P., 11445 Compaq Center Drive, W. Houston, Texas 77070, USA**
- (72) Opfinder: **NICHOLS, Stephen J., , Vancouver, Washington 98683, USA**
GONDEK, Jay S., , Vancouver, Washington 98683, USA
WARD, Jefferson P., , Vancouver, Washington 98683, USA
- (74) Fuldmægtig i Danmark: **NORDIC PATENT SERVICE A/S, Bredgade 30, 1260 København K, Danmark**
- (54) Benævnelse: **TRANSFORMATIONSKORT I EN PRINTERPATRON**
- (56) Fremdragne publikationer:
US-A1- 2002 075 344
US-A1- 2011 187 771
US-A1- 2013 028 648

Description

BACKGROUND

- 5 **[0001]** Output devices such as printers may implement a subtractive color model, like a cyan, magenta, yellow, and black (CYMK) color model, while input devices such as computer monitors, mobile phones, and other input devices may implement an additive color model, like an red, green and blue (RGB) color model.
- 10 **[0002]** To output data from an input device, such as a graphic, text or a combination thereof, output devices may convert the additive color model into a subtractive color model via a print color transform. Manufacturers and/or vendors are challenged to provide print color transform such that graphics and/or text are outputted from output devices, like a printer, with more accurate color representation.
- 15 US 2011/187771 A1 describes a printing system including a printer and an imaging material supply cartridge. The imaging material supply cartridge includes a memory having partitions which include portions, regions or blocks of memory. Each partition includes one or more different pieces of data or data fields. The data fields are grouped into their various designated partitions based upon attributes of the data fields, e.g., based upon how the particular data field
- 20 is to be accessed and whether or not or how the data field is encrypted.

BRIEF DESCRIPTION OF THE DRAWINGS

- [0003]** The following detailed description references the drawings, wherein:
- 25 FIG. 1 is an example block diagram of a printer cartridge including a transform wrapper to build a transform map;
- FIG. 2 is example block diagram of a memory device of FIG. 1;
- FIG. 3 is an example block diagram of a printer cartridge including instructions for generating a transform map at the printer cartridge; and
- 30 FIG. 4 is an example flowchart of a method for generating a transform map at a printer cartridge.

DETAILED DESCRIPTION

- 5 **[0004]** Specific details are given in the following description to provide a thorough understanding of examples. However, it will be understood that examples may be practiced without these specific details. For example, systems may be shown in block diagrams in order not to obscure examples in unnecessary detail.
- 10 **[0005]** Print color transforms may be dependent on a particular ink or toner formulation. Therefore, it may be desirable to provide color tables along with the printer inks or toners, rather than include them in printer firmware or a printer driver. However, compared to storing color tables in printer firmware, the management of color data in printer supplies may be more complicated. For instance, a customer may have installed a mix of supply versions in the
- 15 printer, and different supplies may have changes in inks and color tables and may support different media. In addition, those supplies may be used by multiple printers, or be used in printers that have not yet been developed.
- 20 **[0006]** Accordingly, examples herein may include a system embedded in the print cartridge memory, which allows for multiple versions and permutations of inks, color tables, print media, and/or printers. In one example, a printer cartridge may include a memory device. A transform wrapper may be stored on the memory device. The transform wrapper may dynamically build a transform map for a printer based on metadata stored at the memory device. The metadata may indicate at least one of a type of depositing material, transform map, print media and printer.
- 25 **[0007]** The transform wrapper may use the metadata for building transform data from more primitive data elements, or other existing transforms. This data transform or encoding may provide flexibility to handle the different versions and permutations that may arise, such as changes in inks, media support, color tables, and printers. For example, including a color table
- 30 map on a printer cartridge may offer improved ink/toner types to customers that didn't exist at a time the original product was manufactured. Also, examples may be able to correct color tables in printers in the field for errors discovered after the start of manufacturing.

[0008] Further, examples may correct colortables due to changes in media and add support for media types that didn't exist at the time the product was manufactured. Moreover, examples may introduce inks/toners with different color characteristics as well as introduce different improved color tables for a single color, without requiring the customer to replace all ink/toner supplies to correct for errors. Examples may further reduce a required memory storage space on the printer cartridge for storing color tables.

[0009] Referring now to the drawings, FIG. 1 is an example block diagram of a printer cartridge 100 including a transform wrapper 120 to build a transform map 140. The printer cartridge 100 may be any type of cartridge to store a depositing material. Example depositing materials may include ink, toner, plastic, polymer, powder metal, alloy and the like. In one example, the printer cartridge 100 may be an ink cartridge that contains liquid ink for use with an inkjet printer. In another example, the printer cartridge 100 may be a toner cartridge that contains dry toner powder for use with a laser printer.

[0010] The printer cartridge 100 is shown to include a memory device 110. The memory device 110 may be any electronic, magnetic, optical, or other physical storage device. For example, the memory device 110 may be a Random Access Memory (RAM), an Electrically Erasable Programmable Read-Only Memory (EEPROM), a Read-only memory (ROM), flash memory, a storage drive or the like.

[0011] The memory device 110 is shown to store a transform wrapper 120, where the transform wrapper 120 includes metadata 130. The transform wrapper 120 may refer to any type of container or wrapper format, such as a metafile format that describes how different data elements and metadata coexist in a file. The term metafile may refer to a file format that can store multiple types of data. The term metadata 130 may include structural metadata and/or descriptive metadata. Structural metadata may refer to the design and specification of data structures, such as a container of data. Descriptive metadata may refer to individual instances of application data, such as the data content.

[0012] The transform wrapper 120 may dynamically build a transform map 140 for a printer (not shown), such as laser or inkjet printer, based on the metadata 130 stored at the memory device 110. The metadata 130 may indicate a type of the depositing material, transform map,

print media and printer. The metadata 130 will be explained in greater detail below with respect to FIG. 2.

[0013] The transform map 140 may be a type of color table and/or map. As explained above, a color table may be used to convert between different color models. For example, before an input image can be printed as a physical output, the input additive color model, such as RGB, may be converted to an output subtractive color model, such as CMYK. This may be done using a color table that transforms or converts RGB color data into CMYK color data.

Examples of RGB color models may include sRGB, Adobe® RGB, scan RGB, and the like.

However, examples are not limited to the RGB and CYMK color models, and may include any type of input and/or output color models, such as the Specifications for Web Offset Publications (SWOP) CMYK model and the International Commission on Illumination (CIE) L*a*b* color model.

[0014] In one example, the transform map 140 may correspond to a particular media type. For example, particular paper types, or particular paper colors may have corresponding transform maps 140. For example, one transform map 140 may correspond to plain paper and another transform map 140 may correspond to thicker paper, such as company letterhead, or bond paper. In another example, different degrees of output quality may have different transform maps 140. For example, a "draft" quality may have one transform map 140, and a "best" quality may have a different transform map 140. In yet another example, different input devices may have different corresponding transform maps 140. For example, different models of printers may have different corresponding transform maps 140.

[0015] While FIG. 1 show a single transform map 140, examples of the printer cartridge 100 may include a plurality of transform maps 140, such as for different types and/or versions of printers, media, depositing materials, users and the like. Moreover, while FIG. 1 shows a single printer cartridge 100, a plurality of the print cartridges 100 may be interfacing with a single printer. Each of these printer cartridges 100 may correspond to a different color.

[0016] For example, one of the printer cartridges 100 may include black ink and another of the printer cartridges may include cyan, magenta and yellow ink. In another example, one of the printer cartridges 100 may include black ink, another of the printer cartridges 100 may include cyan ink, yet another of the printer cartridges 100 may include magenta ink, and yet another of

the printer cartridges 100 may include yellow ink. Further, each of these printer cartridges 100 may contain the transform map 140. Also, the transform map 140 of one of the printer cartridges 100 may be influenced by another of the printer cartridges 100, such as if different versions of the printer cartridges 100 are used together for a single printer.

5

[0017] FIG. 2 is example block diagram of a memory device 210 of FIG. 1. The memory device 210 of FIG. 2 may respectively include at least the functionality and/or hardware of the memory device 110 of FIG. 1. For instance, the memory device 210 is shown to include a transform wrapper 220, which further includes metadata 230. Here, the metadata 230 is further shown to include a property 232, tag 234, condition 236 and recipe 238. Further, the memory device 210 is shown to store primitive data 250. While FIG. 2 shows a single property 232, tag 234, condition 236 and recipe 238, examples may include a plurality of the properties 232, tags 234, conditions 236 and/or recipes 238. For instance, there may be separate tags 224 for the type of media, color space, supply family and the like.

15

[0018] The property 232 may describe primitive data 250 stored and/or generated by the printer cartridge 100. The primitive data 250 may include basic color information about the contents of the printer cartridge 100, such as a version, depositing material channel, and/or dimension of the printer cartridge 110. The dimension may include a channel and/or count of nodes of a color table. The channel may relate to a type of color. The node may indicate output colorant amount.

20

[0019] The tag 234 may provide an identification of the printer cartridge 100. For example, the tag 234 may include a color space, media type, print quality, printer platform, supply family, and the like. The condition 236 may restrict when the transform map 140 is available for use. For example, the condition 236 may specify which of a plurality of types of transform maps to use based on the tag 234. In one example, the condition 236 may include a Boolean expression of properties 232 and tags 234. For example, the condition 236 may be used to specify exception color tables that handle cases such as multiple printer platforms, or multiple ink color revisions.

30

[0020] The recipe 238 may include instructions for how to build the transform map 140 from at least one of an existing map and the primitive data 250. In one example, the instructions of the recipe 238 may utilize a stack model with reverse Polish notation (RPN) operators. The recipe

238 may use tags 234, to identify components, such as the existing map 238 and/or primitive data 250. Without tags 234, the recipe 238 would only be able to identify other components using their properties 232. This may be problematic as the same set of properties 232 may describe multiple components. For example, there may be multiple channel map components that have the same channel color (e.g. Cyan) and node count (e.g. 17-cubed) properties 232.

[0021] The transform map 140 may be a channel map and/or a color map. The color map may include a mapping for a plurality of colors while the channel map may include a mapping for only one of the plurality of colors. The color map may, for example, convert between the CYMK and RGB color models. The color map may include a plurality of the channel maps and the channel map may include the primitive data.

[0022] In one example, the recipe 238 may include instructions to select a plurality of the channel maps by matching at least one of the property 232 and the tag 234 of the primitive data and to combine the plurality of channel maps to build the color map. Moreover, the primitive data may not be selected if there is a mismatch with the tag 234 and/or property 232. For example, the tag 234 may match the media type, such as plain paper, but there may be a mismatch with the property 232, such as different colors. In this case, the primitive data may not be used because of the mismatch with the property 232, despite the matching tag 234.

[0023] Each of the channel maps may correspond to one of a plurality of depositing material colors of the printer. For instance, the recipe may 238 may define the operation for building a CMYK color map for color matching an RGB source color to a specific printer's plain paper, normal quality mode. Here, the condition 236 may be set to default, such that this color table will normally be used when referenced by a set (or subset) of matching tags 234. The recipe 238 may specify that color data tables for the individual inks, e.g. channel maps, are to be determined by referencing the properties 2232, tags 234 and conditions 236, pushed onto the stack, and then combined to build the CYMK color map.

[0024] In another example, the recipe 238 may include instructions to build the channel map based on a neutral axis, a set of seed nodes and a delta table included in the primitive data 250. The neutral axis may relate to a line extending from an origin of a three-dimensional color table to a node of the color table farthest from the origin. The set of seed nodes may correspond to nodes of a compressed color table. The delta table may indicate a difference between an

interpolated color table node and a corresponding actual color table. For example, the recipe 238 may define the operation for building the cyan channel map by pushing elements onto a stack, such as the neutral axis, set of seed nodes, and the delta table.

5 **[0025]** The transform map 140 may be a base and/or modifier map. The base map may be used without any modification by the printer. The modifier map may be used to modify at least one of the base map and the primitive data. In one example, the recipe 238 may include instructions to build a new map based on the modifier map and the base map. The modifier map may be used to specify scale, specify offset and/or select replacement of data of the base map. For
10 example, a draft-mode color table may be specified as a normal-mode color table modified with a small set of scale factors. For instance, the modifier map could be referenced by the base map's recipe 238 to change the node values in the base map.

[0026] Here, the conditions 236 may specify a printer platform and specific color ink versions.
15 These conditions 236 may then be tested. If true, this color table may be used instead of the default. The recipe 238 may use inheritance to allow re-use of existing color data. For example, the channel map for a prior printer platform may be pushed onto the stack. Next, a scalar modifier table may be pushed onto the stack. Finally, an operator may apply the scalar table to the inherited channel map.

20 **[0027]** The above examples for specifying the creation and application of transform maps 140 as well as other color management data elements may exist on the supplies (e.g. printer cartridges), may be updated in the supplies, and may be resolved run-time when a customer changes inks or toners. The metadata 230 including tags 234, properties 232, and conditions
25 236 may allow for versioning and special casing for the permutation of potential changes in printers, inks, and color tables. The tags 234 may also provide references to allow inheritance, where a color data element may be defined as a derivation of a different element. The recipe 238 may specify the construction of color transform data, and also provide a means of specifying the construction of color data that is compactly derived from other data. In one
30 example, the metadata 230 may be compiled into a compact binary symbolic representation prior to storage in the memory device 210.

[0028] FIG. 3 is an example block diagram 300 of a computing device including instructions for generating a transform map at a printer cartridge. In the example of FIG. 3, the device 300

includes a processor 310 and a machine-readable storage medium 320. The machine-readable storage medium 320 further includes instructions 322, 324 and 326 for generating a transform map at a printer cartridge.

5 **[0029]** The computing device 300 may be, for example, a printer cartridge, a printer, a mobile device, a fax machine, multimedia device, a secure microprocessor, a notebook computer, a desktop computer, an all-in-one system, a server, a network device, a controller, a wireless device, or any other type of device capable of executing the instructions 322, 324 and 326. In certain examples, the computing device 300 may include or be connected to additional
10 components such as memories, controllers, etc.

[0030] The processor 310 may be, at least one central processing unit (CPU), at least one semiconductor-based microprocessor, at least one graphics processing unit (GPU), a microcontroller, special purpose logic hardware controlled by microcode or other hardware
15 devices suitable for retrieval and execution of instructions stored in the machine-readable storage medium 320, or combinations thereof. The processor 310 may fetch, decode, and execute instructions 322, 324 and 326 to implement generating the transform map at the printer cartridge. As an alternative or in addition to retrieving and executing instructions, the processor 310 may include at least one integrated circuit (IC), other control logic, other electronic
20 circuits, or combinations thereof that include a number of electronic components for performing the instructions 322, 324 and 326.

[0031] The machine-readable storage medium 320 may be any electronic, magnetic, optical, or other physical storage device that contains or stores executable instructions. Thus, the machine-
25 readable storage medium 320 may be, for example, Random Access Memory (RAM), an Electrically Erasable Programmable Read-Only Memory (EEPROM), a storage drive, a Compact Disc Read Only Memory (CD-ROM), and the like. As such, the machine-readable storage medium 320 can be non-transitory. As described in detail below, machine-readable storage medium 320 may be encoded with a series of executable instructions for generating the
30 transform map at the printer cartridge.

[0032] Moreover, the instructions 322, 324 and 326 when executed by a processor (e.g., via one processing element or multiple processing elements of the processor) can cause the processor to perform processes, such as, the process of FIG. 4. For example, the generate

instructions 322 may be executed by the processor 310 to generate a transform map based on a property and a tag included at the printer cartridge (not shown). The test instructions 324 may be executed by the processor 310 to test a condition associated with the transform map and included at the printer cartridge.

5

[0033] The allow instructions 326 may be executed by the processor 310 to allow the transform map to be used by a printer (not shown) if the tested condition is satisfied. The property may describe primitive data stored and/or generated by the printer cartridge. The tag may provide an identification of the printer cartridge. The transform map may be stored at the printer cartridge.

10 A change in the metadata may be communicated from the print cartridge to the printer during run-time, if at least one a type of a depositing material, transform map, print media and printer changes.

[0034] FIG. 4 is an example flowchart of a method 400 for generating a transform map at a printer cartridge. Although execution of the method 400 is described below with reference to the printer cartridge 100, other suitable components for execution of the method 400 can be utilized, such as the printer cartridge 200. Additionally, the components for executing the method 400 may be spread among multiple devices. In certain scenarios, multiple devices acting in coordination can be considered a single device to perform the method 400. The method 400 may be implemented in the form of executable instructions stored on a machine-readable storage medium, such as storage medium 320, and/or in the form of electronic circuitry.

[0035] At block 410, the printer cartridge 100 executes a transform wrapper 120 to dynamically generate a transform map 140 for a printer based on metadata 130 stored at the printer cartridge 100. At block 420, the transform map 140 is selected to be used by the printer based on testing a condition included in the metadata 130. The metadata 130 may indicate a type of depositing material, transform map, print media and/or printer. At least one of a plurality of different types of the transform map 140 is generated and used based on a property and tag included in the metadata 130.

30

Patentkrav**1. Hukommelsesindretning (110, 210) til en printerpatron (100), hvilken**

hukommelsesindretning (110, 210) omfatter:

en transformations-wrapper (120, 220), der er lagret på hukommelsesindretningen (110, 210), idet transformations-wrapperen (120, 220) dynamisk skal opbygge et

transformationskort (140) til en printer på basis af metadata (130, 230), der er lagret på hukommelsesindretningen (110, 210), hvor

metadataene (130, 230) skal angive en type afsætningsmateriale, transformationskort (140), printmedier og printer, hvor

metadataene (130, 230) indbefatter:

en egenskab (232) til beskrivelse af primitive data (250), som lagres og/eller genereres ved hjælp af printerpatronen (100); og

et tag (234) til tilvejebringelse af en identifikation af printerpatronen (100).

2. Hukommelsesindretning (110, 210) ifølge krav 1, hvor

metadataene (130, 230) indbefatter mindst én af en betingelse (236) og en opskrift (238),

betingelsen (236) skal indskrænke, når transformationskortet (140) er tilgængeligt til anvendelse, og

opskriften (238) skal indbefatte instruktioner i, hvordan transformationskortet (140) opbygges ud fra mindst én af et eksisterende kort og de primitive data (250).

3. Hukommelsesindretning (110, 210) ifølge krav 1 eller krav 2, hvor

egenskaben (232) indbefatter mindst én af en version, en afsætningsmaterialekanal og printerpatronens (100) dimension,

dimensionen indbefatter mindst én af en kanal og et antal af knuder, kanalen vedrører en type farve, og

en knude skal angive mængden af genereret farvestof.

4. Hukommelsesindretning (110, 210) ifølge krav 2, hvor

metadataene (130, 230) indbefatter betingelsen (236),

tagget (234) indbefatter mindst én af et farverum, en medietype, en printkvalitet, en printerplatform og en tilførselsfamilie, og

betingelsen (236) skal specificere, hvilken af en flerhed af typer af transformationskort (140), der på basis af tagget (234) skal anvendes.

5. Hukommelsesindretning (110, 210) ifølge krav 2, hvor

5 metadataene (130, 230) indbefatter opskriften (238),
betingelsen (236) indbefatter mindst et boolsk udtryk for egenskaber og tags (234), og
der i instruktionerne i opskriften (238) anvendes en stakmodel med omvendt polsk
notations-(RPN)-operatorer.

10 **6. Hukommelsesindretning (110, 210) ifølge krav 1 eller krav 2, hvor**

transformationskortet (140) er mindst én af et kanalkort og et farvekort,
farvekortet indbefatter en mapning for en flerhed af farver, og
kanalkortet indbefatter en mapning for én af flerheden af farver.

15 **7. Hukommelsesindretning (110, 210) ifølge krav 6, som det afhænger af krav 2, hvor**

metadataene (130, 230) indbefatter opskriften (238),
opskriften (238) indbefatter instruktioner i at
vælge en flerhed af kanalkortene ved at matche mindst én af egenskaben (232) og
tagget (234) med de primitive data (250) og
20 kombinere flerheden af kanalkort til opbygning af farvekortet, og
hvert af kanalkortene skal svare til én af en flerhed af afsætningsmaterialefarver i
printereren.

8. Hukommelsesindretning (110, 210) ifølge krav 6, som det afhænger af krav 2, hvor

25 opskriften (238) indbefatter instruktioner i at opbygge et kanalkort på basis af mindst én
af en neutral akse, et sæt startknuder og en delta-tabel, der er indbefattet i de primitive
data (250),
den neutrale akse vedrører en linje, der strækker sig fra en oprindelse i en
tredimensional farvetabel til en knude i farvetabellen, der er længst væk fra oprindelsen,
30 sættet af startknuder svarer til knuder i en komprimeret farvetabel, og
delta-tabellen skal angive en forskel mellem en interpoleret farvetabelknude og en
tilsvarende faktisk farvetabel.

9. Hukommelsesindretning (110, 210) ifølge krav 6, hvor

farvekortet skal konvertere mellem CYMK- og RGB-farvemodeller,
farvekortet indbefatter en flerhed af kanalkortene, og
kanalkortet indbefatter de primitive data (250).

- 5 **10.** Hukommelsesindretning (110, 210) ifølge krav 1 eller 2, hvor
transformationskortet (140) er mindst én af et basiskort og et modifikatorkort,
basiskortet skal anvendes uden nogen som helst modifikation via printerens, og
modifikatorkortet skal anvendes til at modificere mindst én af basiskortet og de
primitive data (250).
- 10
11. Hukommelsesindretning (110, 210) ifølge krav 10, som det afhænger af krav 2, hvor
opskriften (238) indbefatter instruktioner i at opbygge et nyt kort på basis af
modifikatorkortet og basiskortet, og
modifikatorkortet skal anvendes til mindst én af: specificere målestok, specificere
15 forskydning og vælge udskiftning af data til basiskortet.
12. Hukommelsesindretning (110, 210) ifølge krav 1, der omfatter:
instruktioner i at
afvikle transformations-wrapperen (120, 220) og
20 vælge transformationskortet (140) på basis af testning af en betingelse (236), der er
indbefattet i metadataene (130, 230).
13. Hukommelsesindretning (110, 210) ifølge krav 13, hvor mindst én af en flerhed af
forskellige typer af transformationskortet (140) genereres og anvendes på basis af en egenskab
25 (232) og et tag (234), der er indbefattet i metadataene (130, 230).
14. Hukommelsesindretning (110, 210) ifølge krav 1, der omfatter:
et ikke-flygtigt computerlæsbart lagermedie, der lagrer instruktioner, som ved afvikling med en
processor tilhørende en indretning får processoren til at
30 generere (322) transformationskortet (140) på basis af egenskaben (232) og tagget
(234), der er indbefattet i printerpatronen (100),
teste (324) en betingelse (236), der er associeret med transformationskortet (140) og
indbefattet i metadataene, og

muliggøre (326), at transformationskortet (140) kan anvendes af en printer, hvis den testede betingelse (236) er opfyldt.

15. Hukommelsesindretning (110, 210) ifølge krav 14, hvor

- 5 transformationskortet (140) lagres i printerpatronen (100), og
en ændring i metadataene (130, 230) skal kommunikeres fra printerpatronen til
printerens under kørselstiden, hvis mindst én type af et afsætningsmateriale, et
transformationskort (140), printmedier og printer ændrer sig.

10 **16.** Printerpatron (100), der omfatter:

en hukommelsesindretning (110, 210) ifølge et af kravene 1 til 15.

FIG. 1




FIG. 2




FIG. 3




FIG. 4

