

(19) World Intellectual Property Organization

(43) International Publication Date
4 October 2012 (04.10.2012)




(10) International Publication Number
WO 2012/131626 A3



- | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|--|----------------------------|----|------------|----------------------------|----|------------|-------------------------|----|------------|---------------------------|----|------------|-----------------------------|----|----------|--------------------------------|----|------------|--------------------------------|----|-----------|--------------------------------|----|-----------|-------------------------------|----|------------|-------------------------------|----|------------|-------------------------------|----|------------|-------------------------------|----|------------|----------------------------|----|------------|----------------------------|----|---|
| <p>(51) International Patent Classification:
 <i>A61M 16/04</i> (2006.01) <i>A61M 1/00</i> (2006.01)
 <i>A61M 25/00</i> (2006.01)</p> | <p>(71) Applicant (<i>for all designated States except US</i>): AIRWAY MEDIX SPOŁKA Z O.O. [PL/PL]; Rydygiera Ludwika 8 lok, BUD., 3A, województwo mazowieckie, PL-01-793 Warszawa (PL).</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>(21) International Application Number:
 PCT/IB2012/051532</p> | <p>(72) Inventors; and</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>(22) International Filing Date:
 29 March 2012 (29.03.2012)</p> | <p>(75) Inventors/Applicants (<i>for US only</i>): EINAV, Elad [IL/IL]; Haparsa 53, 61100 Tel Aviv (IL). ZACHAR, Oron [IL/IL]; 23 Mahne Yosef Street, 65153 Tel Aviv (IL).</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>(25) Filing Language:
 English</p> | <p>(74) Agent: VAN DYKE, Marc; Nachal Dolev 53/8, 99621 Beit Shemesh (IL).</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>(26) Publication Language:
 English</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>(30) Priority Data:</p> <table border="0"> <tr><td>61/468,990</td><td>29 March 2011 (29.03.2011)</td><td>US</td></tr> <tr><td>61/473,790</td><td>10 April 2011 (10.04.2011)</td><td>US</td></tr> <tr><td>61/483,699</td><td>8 May 2011 (08.05.2011)</td><td>US</td></tr> <tr><td>61/496,019</td><td>12 June 2011 (12.06.2011)</td><td>US</td></tr> <tr><td>61/527,658</td><td>26 August 2011 (26.08.2011)</td><td>US</td></tr> <tr><td>PL396436</td><td>26 September 2011 (26.09.2011)</td><td>PL</td></tr> <tr><td>61/539,998</td><td>28 September 2011 (28.09.2011)</td><td>US</td></tr> <tr><td>1116735.0</td><td>28 September 2011 (28.09.2011)</td><td>GB</td></tr> <tr><td>1119794.4</td><td>16 November 2011 (16.11.2011)</td><td>GB</td></tr> <tr><td>61/560,385</td><td>16 November 2011 (16.11.2011)</td><td>US</td></tr> <tr><td>61/603,340</td><td>26 February 2012 (26.02.2012)</td><td>US</td></tr> <tr><td>61/603,344</td><td>26 February 2012 (26.02.2012)</td><td>US</td></tr> <tr><td>61/609,763</td><td>12 March 2012 (12.03.2012)</td><td>US</td></tr> <tr><td>61/613,408</td><td>20 March 2012 (20.03.2012)</td><td>US</td></tr> </table> | 61/468,990 | 29 March 2011 (29.03.2011) | US | 61/473,790 | 10 April 2011 (10.04.2011) | US | 61/483,699 | 8 May 2011 (08.05.2011) | US | 61/496,019 | 12 June 2011 (12.06.2011) | US | 61/527,658 | 26 August 2011 (26.08.2011) | US | PL396436 | 26 September 2011 (26.09.2011) | PL | 61/539,998 | 28 September 2011 (28.09.2011) | US | 1116735.0 | 28 September 2011 (28.09.2011) | GB | 1119794.4 | 16 November 2011 (16.11.2011) | GB | 61/560,385 | 16 November 2011 (16.11.2011) | US | 61/603,340 | 26 February 2012 (26.02.2012) | US | 61/603,344 | 26 February 2012 (26.02.2012) | US | 61/609,763 | 12 March 2012 (12.03.2012) | US | 61/613,408 | 20 March 2012 (20.03.2012) | US | <p>(81) Designated States (<i>unless otherwise indicated, for every kind of national protection available</i>): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CI, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.</p> <p>(84) Designated States (<i>unless otherwise indicated, for every kind of regional protection available</i>): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW). Eurasian (AM, AZ, BY, KG, KZ, MD, RU,</p> |
| 61/468,990 | 29 March 2011 (29.03.2011) | US | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 61/473,790 | 10 April 2011 (10.04.2011) | US | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 61/483,699 | 8 May 2011 (08.05.2011) | US | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 61/496,019 | 12 June 2011 (12.06.2011) | US | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 61/527,658 | 26 August 2011 (26.08.2011) | US | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| PL396436 | 26 September 2011 (26.09.2011) | PL | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 61/539,998 | 28 September 2011 (28.09.2011) | US | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1116735.0 | 28 September 2011 (28.09.2011) | GB | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1119794.4 | 16 November 2011 (16.11.2011) | GB | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 61/560,385 | 16 November 2011 (16.11.2011) | US | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 61/603,340 | 26 February 2012 (26.02.2012) | US | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 61/603,344 | 26 February 2012 (26.02.2012) | US | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 61/609,763 | 12 March 2012 (12.03.2012) | US | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 61/613,408 | 20 March 2012 (20.03.2012) | US | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

[Continued on next page]

(54) Title: BALLOONED VENTILATION TUBE CLEANING DEVICE



(57) Abstract: A cleaning device, system and method for use with an ETT or tracheostomy ventilation tube (60), a ventilator machine (900), a source(s) (602) of fluid (for example, pressurized or unpressurized) and a source(s) of suctioning (603) is disclosed. In some embodiments, the cleaning device is useful for cleaning an inner surface of the ventilation tube (60) and/or for preventing or hindering the accumulation of biofilm thereon. In some embodiments, it is possible to clean biofilm or any other material on the inner surface (201) by delivering fluid into an interior of the ventilation tube, wiping the tube interior with a width- expanded wiping element (e.g. an inflated balloon) by longitudinal motion of the wiping element, and suctioning material out of the ventilation tube ventilation tube.

WO 2012/131626 A3



TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*

(88) Date of publication of the international search report:

29 November 2012

Published:

— *with international search report (Art. 21(3))*

BALLOONED VENTILATION TUBE CLEANING DEVICE

INVENTORS: Elad Einav, Oron Zachar

FIELD

Embodiments of present invention relates to devices, systems and methods of cleaning an interior of a ventilation tube and/or hindering the build-up of biofilm therein.

BACKGROUND AND RELATED ART

References Cited

- US patent publication no. 2007/0038226 ;
- US patent publication no. 2010/0137899 ;
- US patent publication no. 2010/0186748 titled "Endotracheal Tube Cleaning Apparatus" ;
- US patent publication no. 2010/023885;
- US patent 6,082,361;
- US patent 6,318,368;
- US patent 5,709,691;
- WO 2011/094517;
- US 2011/180072;
- WO 2010/091309;
- US 2006/099434;
- US 2007/089748;
- US 2007/024288;
- US 5,067,497;
- PCT patent publication WO 89/07466 ;
- PCT patent publication WO 2007/146613 ;
- US patent 5125893 titled "Suction catheter with wall lumen for irrigation" ;
- US patent 6923184 titled "Suction system with high efficiency suction control valve"
- US patent 7051737 titled "Mucus Shaving Apparatus for Endotracheal Tubes" ;
- US patent 7669600 titled "Endotracheal Tube Cleaning Apparatus" ;

US patent 4762125 titles “Balloon-tipped suction catheter” ;
US patent 4351328 ;
US patent 5738091 ;
US patent 6602219 ;
US patent 6612304 ;
US patent 6805125 ;
US patent 6935339 ;
US patent 7273473 ;
US patent application 20090178681

Suction catheters are commonly used to aspirate trachea-bronchial fluids in patients ventilated with endo-tracheal tube (ETT) devices. A problematic aspect of the use of suction catheters is the presence of bacterial biofilm within the ETT lumen through which the suction catheter passes. Consequently, as the suction catheter is inserted, there is high risk of it carrying bacterial biofilm from the ETT lumen deeper into the bronchial tree where the suction catheter reaches, and thereby increasing the risk of lung infection. Moreover, buildup of substantial biofilm thickness reduces the effective free lumen of the ETT for air passage. Therefore, there is a need for maintaining cleaner ETT lumen between suction operations, and preventing buildup of significant biofilm thickness.

Another application is the use of cleaning catheters to clean the lumen of other catheters. An example of such cleaning catheter device is illustrated in Fig. 1c adapted from PCT patent publication WO 89/07466. These devices are mostly intended for the removal of substantial local clogging of the tube lumen. Yet such devices would be inefficient for cleaning of thin biofilm buildup on the lumen surface of medical device catheters such as endo tracheal tubes.

Prior art of ETT lumen cleaning devices include US patent 7051737 titled “Mucus Shaving Apparatus for Endotracheal Tubes”, and US patent 7669600 titled “Endotracheal Tube Cleaning Apparatus”, US patent publication no. 2010/0186748 titled “Endotracheal Tube Cleaning Apparatus”, and references therein. Examples of prior art devices are provided in Figs. 2a-2d.

The art of suction catheters is exemplified in US patent 5125893 titled “Suction catheter with wall lumen for irrigation”, US patent 6923184 titled “Suction system with high efficiency suction control valve”, and US patent 4762125 titled “Balloon-tipped suction catheter”.

The type of “closed suction systems” are where the suction catheter can be used repeatedly without being detached from the tube system including the ventilation air supply. Such types of systems are known in the art of suction catheters, as exemplified in the discussion of US patent 6923184 and PCT patent publication WO 2007/146613, as well as US patents 5738091, 6602219, 6612304, 6805125, 6935339, 7273473, US patent application 20090178681, and references therein (together “closed system art”). Representative prior art devices are illustrated in Fig. 1a and Fig. 1b. Such systems employ a tubing connector with at least two ports – one for air delivery and one for catheter delivery. Patent 6923184 further discloses the option for cleaning the external surface of the catheter flexible shaft in a chamber located in front of the isolator seal of the multi-port tubing connector. The discussion of the closed system art patents is in the context of suction catheters.

Several problems plague present art devices: (a) The suction flexible shaft is coming up from the ETT with significant amount of bacterial rich slime drawn up bronchi; (b) the closed suction system needs to be replaced every about 48h due to risk of bacterial proliferation on the flexible shaft exterior surface wall; (c) the ETT lumen cleaning operation is performed by a distinct catheter which requires disconnection of ventilation process and/or tube connection; (d) the ETT lumen cleaning sweeps up biofilm which itself require removal from the cleaning catheter, and this removal is done in a manual open way and not within a closed system.

SUMMARY OF EMBODIMENTS

Some embodiments of the present invention relate to a wiping device for cleaning an inner surface of a ventilation tube in a closed ventilation system where air is mechanically forced into the ventilation tube by an external ventilator. The wiping device includes an elongate flexible main body, an width-expandable wiping element (e.g. an inflatable balloon), one or more suction orifice(s) and one or more fluid delivery orifice(s).

In order to clean an inside surface of a ventilation tube, it is possible to carry out (e.g. simultaneously or in any order) a wiping operation, a fluid delivery operation and a suction operation. In some embodiments, during the wiping operation the width-expanded wiping element (e.g. the inflated balloon) moves longitudinally within the ventilation tube when in contact with an inner surface thereof - e.g. to wipe material located on the ventilation tube inner surface (e.g. biofilm). In some embodiments, during the fluid delivery operation, stream(s) of fluid (e.g. liquid stream(s) and/or gas stream(s) and/or stream(s) of a gas/liquid mixture for example a mist stream or a stream(s) of liquid including bubbles within) are sent, via the fluid delivery orifice(s), into the ventilation tube (e.g. incident upon an inner surface of the ventilation tube). In some embodiments, during the suction operation, material in the 'interstitial region' outside of the main body and within the ventilation tube is suctioned out of the ventilation tube.

Examples of suctioned material that may be suctioned out of the interstitial region include (i) derivatives of biofilm that has been wiped away from an inner surface, (ii) derivatives of fluid delivered into the interstitial region, and (iii) mixtures thereof.

Examples of ventilation tubes which may be cleaned include an endo-tracheal tubes (ETT) and tracheostomy ventilation tubes.

In some embodiments, a distal end of the flexible main body (i.e. of the 'closed system device') may be inserted into the ventilation tube via the ventilation tube proximal end at a time that a patient is being ventilated. In some embodiments, the flexible main body distal snugly and slidably traverses an interior region of a ventilation tube assembly, which is mechanically coupled to a proximal end of the ventilation tube to form a substantially air-tight connection.

After insertion of a distal end of the elongate flexible main body into the ventilation tube (i.e. at a time that the main body traverses the interior of the ventilation tube assembly), an expandable wiping element (e.g. inflatable balloon) mounted to the elongate flexible main body (e.g. at or near a distal end thereof) is then caused to width-expand (e.g. by inflation with a liquid or gas or any combination thereof). In some embodiments, the width-expandable wiping element is expanded (e.g. by inflation) so as that a surface of the wiping element (e.g. balloon wall) is brought into contact with the ventilation tube inner surface.

As noted above, when the wiping element is in contact with the inner surface of the ventilation tube, it is possible to wipe away material located on the inner surface.

In some embodiments, width expansion of the width-expandable wiping element may be useful for creating a 'slidable boundary' which at least partially obstructs fluid communication between (i) a 'more proximal portion of the interstitial region' outside of the main body within the ventilation tube from (ii) more distal locations within the ventilation tube – i.e. a more distal portion of the interstitial region and/or locations in the ventilation tube that are distal of the balloon position. As will be discussed below, by at least partially obstructing fluid communication between the proximal and distal portions of the interstitial region (e.g. by balloon inflation) so as to 'significantly hinder' (but not necessarily completely prevent) this fluid communication, it is possible to introduce negative pressure (i.e. via suction orifice(s)) predominantly into the proximal portion of the interstitial region.

In this sense, even if the wiping element (e.g. balloon) does not completely prevent fluid communication between the more proximal and more distal portions of the tube interior, the expanded wiping element (e.g. inflated balloon) may hinder and/or at least partially obstruct such communications. Thus, in some embodiments, the width-expanded wiping element (e.g. inflated balloon) is 'boundary-forming' so as to form a boundary between the two regions (i.e. more proximal and more distal to the wiping element) of the interstitial region outside of the main body and within the ventilation tube. The 'boundary-forming' wiping element (e.g. balloon) which may or may not form a complete seal between the two regions..

Mechanical motion in a longitudinal direction (e.g. in a proximal direction) of the ventilation-tube-inner-surface-contacting width-expanded wiping element (e.g. inflated balloon) may wipe biofilm from the ventilation tube inner surface. The fluid delivery and the suction orifice(s) may respectively stream fluid into and suction material out of the more proximal portion of the interstitial region.

Outside of the ventilation tube and proximal to the ventilation tube connector assembly, a pliable and/or impermeable sleeve around at least a portion of the main body in location proximal to the tube connector assembly inhibits contamination (e.g. inhibits the transport of microbes from within the ventilation tube to an ambient environment or in the opposite direction). In some embodiments, the sleeve may be deployed around at least 5 cm or least 10 cm of the elongate flexible main body in locations proximal to the tube connector assembly. In some embodiments, the sleeve may be around at least a majority or at least a substantial majority that is at least 75%, or substantially an entirety of that is at least 90%, or an entirety of) the portion of the flexible main body that is proximal to the tube connector assembly and distal to a suction port in fluid communication with a suction orifice(s) (e.g. via a suction lumen(s)).

In some embodiments, the fluid delivery operation includes streaming fluid (e.g. including some sort of cleaning fluid such as water or saline solution or disinfectant solutions or mists thereof. The term 'fluid' broadly includes any combination of liquid and/or gas – in some embodiments, the fluid preferably includes at least some liquid for wetting) into the 'more proximal portion' of the interstitial region (e.g. so that fluid is incident upon the inner surface of the ventilation tube – for example, to wet the interior surface of the ventilation tube) via the fluid delivery port(s) – for example, located near the distal end of the main body and proximal to the inflatable balloon inflated in contact with the inner surface of the ventilation tube. A 'strength' or intensity or velocity of delivered fluid may depend on the degree to which the fluid is pressurized before delivery and/or on the size of the aperture through which the fluid is delivered and/or on other factors. In some embodiments, a jet of fluid (e.g. liquid and/or a liquid-gas mixture such as a mist or liquid containing bubbles) is incident upon an inner surface of the ventilation tube.

The delivered or streamed fluid may have sufficient linear momentum to be incident upon an inner surface of the ventilation tube. Material proximal to the balloon within the ventilation tube (e.g. including materials that was formerly biofilm and/or dirt and/or the delivered fluid) may, after being suctioned through the suction orifice, be proximally transported out of the ventilation tube within suction lumen(s) using negative pressure from the suction source.

A number of additional features are described herein.

According to a first example, the ballooned catheter device includes at least two balloons mounted and/or attached to the flexible main body (e.g. at or near the distal end of flexible main body): (i) the aforementioned inflatable 'wiping' and/or 'boundary forming' balloon which is inflated into contact with an inner surface of the ventilation tube (i.e. inflated by a liquid or gas) and/or is inflated to 'concentrate' suction into the proximal portion of the interstitial region; and (ii) a second balloon (referred to as the 'more proximal balloon') which may or may not be inflatable, is located proximal to the inflatable 'boundary-forming' or 'wiping' balloon, and which includes one or more of the fluid delivery ports.

In some embodiments, the inflatable 'boundary-forming' balloon is completely fluid-tight and substantially does not leak.

Alternatively, in a second example, the inflatable 'boundary-forming' balloon is not completely fluid-tight. According to this 'second' example, the balloon is inflated into contact with an inner surface **201** of ventilation tube **60** by liquid so to maintain balloon shape to contact the ventilation tube (i.e. for wiping) and/or so as to at least partially obstruct fluid communication within the tube. However, for the example where the 'boundary-forming balloon' is not fluid tight, some of the liquid within the balloon leaks into the 'more proximal portion' of the interstitial liquid via one or more relatively small holes in the surface of the inflatable 'boundary-forming' balloon. Although these hole(s) are small enough so as to allow the 'boundary-forming' balloon to maintain its shape and slidable contact with the ventilation tube inner surface (i.e. when receiving a relatively steady supply of pressurized liquid via the lumen(s)), the holes are large enough to allow liquid within the 'boundary-forming' inflatable balloon to stream into

the more proximal section of the interstitial region – for example, so that a stream of fluid is incident upon the ventilation tube inner surface.

In this second example, the hole(s) function as the aforementioned ‘fluid delivery ports’ discussed herein. As will be discussed below, this embodiment may provide a number of safety features discussed below.

In some embodiments, the one or more ‘fluid delivery ports’ include a plurality of fluid delivery ports, and a ‘multiple direction’ feature is provided whereby fluid (e.g. liquid and/or gas and/or a liquid-gas mixture such as a mist or a bubble-containing-liquid) is simultaneously streamed into the ‘more proximal’ portion of the interstitial region in multiple directions. Towards this end, the catheter device may include (i) a first fluid delivery port disposed at a first location on a first side of the flexible main body; and (ii) a second fluid delivery port disposed at a second location substantially (e.g. within a tolerance of 75 degrees or more) on a second side of the flexible main body. Not wishing to be bound by any theory, it is noted that the streaming of fluid in substantially opposite directions may facilitate the cleaning of the ventilation tube inner surface.

A number of implementations of this ‘multi-direction’ feature are described herein. In a first implementation, the ‘more proximal balloon’ may include fluid delivery ports that face in different directions relative to an elongate or ‘central’ axis of the flexible main body. In a second implementation, the liquid-filled boundary-forming balloon that includes multiple ‘small’ holes. For example, it is possible to provide first and second holes that both face in a proximal direction but which face in substantially the opposite direction relative to the flexible main body central axis.

In a third implementation, the device includes a plurality of fluid delivery ports located substantially on a surface of the flexible main body. In some embodiments, a first of the fluid delivery ports faces in a first direction while a second of fluid delivery ports faces substantially in the opposite directions.

Some embodiments of the present invention relate to a multi-mode technique for operating the aforementioned ballooned catheter device in a closed system. In both modes of operation, the flexible main body is inserted into the ventilation tube via the proximal end of the ventilation tube and via an inner channel of a ventilation tube connector assembly that is sealingly connected to a proximal end of the ventilator tube.

In the first operating mode, a balloon-inner wall contact within the interstitial region is maintained by the inflatable balloon (e.g. so as to obstruct – i.e. significantly hinder – longitudinal flow between locations proximal and distal to the balloon), and the suction and fluid delivery orifice(s) are operated as described above. The suction and fluid delivery orifice(s) are operated as described in one or more of the previous paragraphs so as to deliver fluid (e.g. a stream of liquid or a stream of a mist) into the ‘more proximal portion’ of the interstitial region while the slidable ‘boundary’ is maintained. A wiping operation caused by sliding the inflated balloon (i.e. inflated into contact with the ventilation tube inner surface) may be carried out simultaneous with or not simultaneous with the suction and fluid delivery operations.

In the second operating mode, the ‘boundary-forming’ balloon is deflated and/or not sufficiently inflated to contact the ventilation tube inner surface and/or not sufficiently inflated to at least partially obstruct (i.e. and ‘significantly inhibit’) fluid communication interstitial region into ‘more proximal’ and ‘more distal’ regions.

In the second mode of operation, suction provided by the suctioning port(s) may be used primarily to remove material from locations distal of the balloon (e.g. in the ‘more distal’ portion of the interstitial region or even from locations that are distal to the distal end of the ETT) and to transport this ‘distally-located’ material in a proximal direction out of the ETT. One example of such ‘distally-located’ material is tracheo-bronchial fluid or mucus located in the subject’s trachea.

Some embodiments relate to a method of cleaning a main lumen of an ETT or tracheostomy ventilation tube **60** comprising: at a time when: (i) a ventilation tube connector assembly **158** mediates a substantially air-tight connection between a ventilator machine and an interior of a main lumen of the ventilation tube **60** (e.g. such that air is forced from the ventilator machine through the ventilation tube connector assembly **158** into the main lumen of the ventilation tube **60**); and/or (ii) an elongate, narrow, flexible, main body **210** (e.g. of a length that is at least 15 cm) slidably and internally traverses the ventilation tube connector assembly **158** without substantially breaking the substantially air-tight breathing circuit such that: A. a proximal end **204** of the main body **210** is located outside of the ventilation tube **60** proximal to the ventilation tube connector assembly **158**; and B. a boundary-forming balloon **588** mounted to the

elongate, flexible main body **210** is located within the ventilation tube **60**, and/or (iii) at least a portion of the main body is a connection-assembly-proximal-portion **598** that is located proximal to the ventilation tube connector assembly **158**; and/or (iv) at least 5 cm of the connection-assembly-proximal-portion **598** is covered and/or enveloped by a substantially impermeable pliable sleeve; carrying out the following steps: A. effecting a balloon-inflation operation by forcing a fluid from outside of the ventilation tube **60** into the boundary-forming balloon **588** so that inflation of the boundary-forming balloon **588** obstructs (i.e. significantly hinders) fluid flow to forms a slidable boundary **770** between: I. a more proximal portion **774** of an interstitial region outside of the flexible main body and within the ventilation tube; and II. locations **778** within the ventilation tube **60** that are distal to slidable boundary **770**, the slidable boundary **770** being located in a distal half of the ventilation tube **60**; A. concurrent with a maintaining of the slidable boundary **770**, effecting a fluid delivery operation by forcing a pressurized fluid from outside of the ventilation tube **60** into the more proximal portion **774** of the interstitial region through one or more fluid delivery orifice(s) **525** that is: I. mechanically coupled to the flexible main body **210**; II. located proximal of the slidable boundary **770** and longitudinally closer to the slidable boundary **770** location than to a proximal opening of the ventilation tube; C. concurrent with the maintaining of the slidable boundary **770**, proximally suctioning, out of the ventilation tube **60**, material located: I. within the more proximal portion **774** of the ventilation tube **60**; II. in the distal half of the ventilation tube, via one or more suction orifice(s) **440** that is: I. mechanically coupled to the flexible main body **210**; and II. located proximal of the slidable boundary and longitudinally closer to the slidable boundary **770** location than to a proximal opening of the ventilation tube.

In some embodiments, the one or more suction orifice(s) is(are) longitudinally displaced from the slidable boundary **770** and/or to a midpoint of the boundary-forming balloon **588** by at most a suction-orifice-displacement-value that is at most 3 cm.

In some embodiments, i. the pressurized fluid (e.g. pressurized liquid or a pressurized mist or a pressurized bubble-containing liquid) is simultaneously forced through first **525A** and second **525B** fluid delivery orifices to respectively produce first **556A** and second **556B** fluid streams that are respectively and simultaneously incident

upon an inner surface **201** of the ventilation tube **60** at first **552A** and second **552B** locations; and ii. the first **552A** and second **552B** locations are substantially on opposite sides of the ventilation tube **60** inner surface **201** within a tolerance that is at most 75 degrees.

In some embodiments, each fluid-delivery-orifice is proximally displaced from the slidable boundary **770** and/or from a midpoint of the boundary-forming balloon **588** by at most a fluid-orifice-displacement-value that is at most 3 cm, or at most 2 cm.

In some embodiments, the fluid-orifice-displacement-value that is at most 2 cm.

In some embodiments, the tolerance is at most 45 degrees or at most 25 degrees.

In some embodiments, the first **525A** and second **525B** fluid delivery orifices are respectively supplied via first **520A** and second **520B** fluid-delivery lumens.

In some embodiments, the first **520A** and second **520B** second fluid delivery lumens are simultaneously supplied by a common pressurized fluid chamber (e.g. containing pressurized liquid or another pressurized fluid such as a pressurized mist or bubbled liquid).

In some embodiments, immediately before exiting each fluid delivery orifice, the delivered fluid is pressurized to at least 1.5 atmospheres or at least 2 atmospheres or at least 3 atmospheres.

In some embodiments, each fluid delivery orifice **525** has a width of at most 3 mm or at most 2 mm or at most 1 mm, or at most 0.5mm, at most 0.3mm, at most 0.2mm.

In some embodiments, each fluid delivery orifice **525** has width that is at most 50% of an average width of the **440** suction orifice(s).

In some embodiments, each fluid delivery orifice **525** has width that is at most 25% of an average width of the **440** suction orifice(s).

In some embodiments, each fluid delivery orifice **525** has width that is at most 10%, or at most 5%, of an average width of the **440** suction orifice(s).

In some embodiments, at a time that the slidable boundary is maintained, substantially no suction or suction at a significantly lower proximal air flow rate than the suction of step C is applied to locations distal of the slidable boundary.

In some embodiments, the suction-orifice-displacement-value is at most 2 cm or at most 1 cm or at most 0.5 cm.

In some embodiments, the ventilation tube **60** is an ETT. In some embodiments, the ventilation tube **60** is a tracheostomy tube.

In some embodiments, the fluid delivery operation and the suctioning are carried out simultaneously.

In some embodiments, the fluid delivery operation and the suctioning are carried out sequentially.

In some embodiments, the method further comprises: concurrent to the maintaining of the slidable boundary, longitudinally moving the boundary-forming balloon **588** so as to mechanically dislodge and/or loosen biofilm material located on the inner surface **201** of the ventilation tube **60**.

In some embodiments, the longitudinal moving is carried out simultaneously with the fluid delivery operation and/or the suctioning.

In some embodiments, at least one of the fluid delivery orifice(s) **525** are deployed to and/or voids within a second balloon **586** deployed distal to the boundary-forming balloon **588**.

In some embodiments, the second balloon **586** is inflatable.

In some embodiments, the second balloon **586** is not inflatable.

In some embodiments, at least one of the at least one of the fluid delivery orifice(s) **525** is an inner-surface-facing void in the main body **210** facing towards the inner surface **201** of the ventilation tube **60** or a inner-surface-facing-void in a fluid-delivery lumen **520** that at least spans a longitudinal range between the fluid delivery orifice(s) **525** and a location on or within the main body **210** that is proximal to the ventilation tube connector assembly **158**.

In some embodiments,

- i. at least one of the at least one of the fluid delivery orifice(s) **525** is a void in the boundary-forming balloon **588** so that the boundary-forming balloon **588** is leaky;
- ii. forcing of pressurized liquid into the boundary-forming balloon **588** is operative to carry out at least some of both of the balloon-inflation operation and the fluid-delivery of the fluid-delivery operation.

In some embodiments, a surface of the boundary-forming balloon **588** is at least 90% or at least 95% and/or at most 99% by surface area, substantially impermeable.

In some embodiments, the boundary-forming **588** balloon is substantially sealed and is not leaky.

In some embodiments, the method further comprises carrying out the additional step of: D. concurrent with the maintaining of the ventilation circuit, and at a time that the boundary-forming balloon **588** mounted to the elongate, flexible main body **210** is located within the ventilation tube **60** and in a non-obstructing or so that the slidable boundary (i.e. for significantly hindering fluid flow within the ventilation tube **60**) with the inner surface **201** of the ventilation tube **60** is not maintained and/or non-contact mode so that balloon **588** is not inflated into contact with the inner surface **201** of ventilation tube **60**, proximally suctioning into the suction orifice(s) **440** material that is located: I. within the ventilation tube **60** and distal to the boundary-forming balloon **588**; and/or II. distal to the ventilation tube distal end **60** so that the material located distal to the ventilation tube distal end **60** enters an interior region of ventilation tube **60** *en route* to the suction orifice(s), wherein the suctioning step when the boundary-forming balloon **588** is in non-obstructing and/or non-contact mode is carried out to proximally transport material suctioned in step D proximally out of ventilation tube **60** via a proximal opening of the ventilation tube **60**.

Some embodiments relate to a -system ballooned cleaning system comprising: a. an ETT or tracheostomy ventilation tube **60**; b. a ventilator machine; c. ventilation tube connector assembly **158** directly or indirectly connected to both the ventilation tube **60** and the a ventilator machine so as to mediate a substantially air-tight connection between the ventilator machine and an interior of the ventilation tube; d. an elongate, narrow, flexible, main body **210** of a length that is at least 15 cm (or at least 20 cm or at least 25 cm or at least 30 cm); e. a boundary-forming balloon **588** mounted to the elongate, flexible main body **210**, the main body configured to slidably and internally traverse the ventilation tube connector assembly **158** without substantially breaking the air-tight connection between the ventilator machine and an interior of the ventilation tube such that: I. a proximal end **204** of the main body **210** is located outside of the ventilation tube

60 proximal to the ventilation tube connector assembly **158**; and II. the mounted boundary-forming balloon **588** is located in the ventilation tube **60**; the boundary-forming balloon **588** being configured so that, when the mounted boundary-forming balloon **588** is located in the ventilation tube **60**, inflation of the boundary-forming balloon **588** forms a slidable boundary between: I. a more proximal portion **774** of an interstitial region outside of the flexible main body and within the ventilation tube; and II, locations **778** within the ventilation tube **60** that are distal to slidable boundary, f. a plurality of fluid-communication lumens located within and/or along the elongate, flexible main body **210** including one or more suction lumen(s) **530** and one or more fluid delivery lumen(s) **520**; g. one or more fluid delivery orifice(s) **525** that: I. is(are) mechanically coupled to flexible main body **210** so that

longitudinal motion of the flexible main body **210** induces longitudinal motion of the fluid delivery orifice(s) (e.g. so the orifice(s) move closer towards a ; II. is located proximal to the slidable boundary when the boundary-forming balloon **558** is inflated into contact with an inner surface of tube **60** to form a slidable 'boundary'; h. one or more suction orifice(s) **440** that: I. is(are) mechanically coupled to flexible main body **210** so that longitudinal motion of the flexible main body **210** induces longitudinal motion of the fluid delivery orifice(s);

II. is located proximal to the slidable boundary when the boundary forming balloon **558** is inflated to form the slidable boundary; i. a source of pressurized fluid (e.g. located outside of the ventilation tube **60**) and operative, at least some of the time and concurrent with the maintaining of the slidable boundary, to deliver pressurized fluid into more proximal portion **774** of the interstitial region such that the pressurized fluid travels to the fluid delivery orifice(s) **525** via the fluid delivery lumen(s) **520** and enters into the more proximal portion **774** of the interstitial region via the fluid delivery orifice(s) **525**; and j. a suction source **603** located outside of the ventilation tube **60**, and operative, at least some of the time and concurrent with the maintaining of the slidable boundary, to proximally transport material located within the more proximal portion **774** of the interstitial region out of the ventilation tube **60** such that the transported material exits the more proximal portion **774** of the interstitial region via the suction orifice(s) **440**, enters

into suction lumen(s) **530** and proximally exits the ventilation tube within suction lumen(s) **530**.

In some embodiments, boundary-forming balloon **588** is mounted to the main body **210** at a location in a distal half (or third or quarter or fifth or tenth) of the main body **210**.

In some embodiments, the fluid source (e.g. **602** and/or other examples) and the suction source **603** are respectively operative, in combination with the lumens and the orifices, to effect the fluid delivery and the suctioning when the boundary-forming balloon **588** is located in a distal half of the ventilation tube **60**.

Some embodiments closed-system ballooned cleaning system for use with an ETT or tracheostomy ventilation tube **60**, a ventilator machine, a source of pressurized fluid and a source of suctioning **603**, the cleaning system comprising: a. a ventilation tube connector assembly **158** operative, when directly or indirectly connected to both the ventilation tube **60** and the ventilator machine, to mediate a substantially air-tight mediating connection between the ventilator machine and an interior of the ventilation tube via an interior of the ventilation tube connector assembly **158**; b. an elongate, narrow, flexible, main body **210** of a length that is at least 15 cm (or at least 20 cm or at least 25 cm or at least 30 cm);; c. a boundary-forming balloon **588** mounted to the elongate, flexible main body **210**, the flexible main body operative to slidably and internally traverse the ventilation tube connector assembly **158** without substantially breaking the air-tight connection between the ventilator machine and an interior of the ventilation tube such that: I. a proximal end **204** of the main body **210** is located outside of the ventilation tube **60** proximal to the ventilation tube connector assembly **158**; and II. the mounted boundary-forming balloon **588** is located in the ventilation tube **60**; the boundary-forming balloon **588** being configured so that, when the mounted boundary-forming balloon **588** is located in the ventilation tube **60**, inflation of the boundary-forming balloon **588** forms a slidable boundary between: I. a more proximal portion **774** of an interstitial region outside of the flexible main body and within the ventilation tube; and II. locations **778** within the ventilation tube **60** that are distal to slidable boundary, f. a plurality of fluid-communication lumens located within and/or along the elongate,

flexible main body **210** including one or more suction lumen(s) **530** and one or more fluid delivery lumen(s) **520**; g. one or more distal fluid delivery orifice(s) **525** that: I. is(are) mechanically coupled to flexible main body **210** so that longitudinal motion of the flexible main body **210** induces longitudinal motion of the fluid delivery orifice(s); II. is located proximal to the slidable boundary when the boundary-forming balloon **558** is inflated to form the slidable boundary; h. one or more distal suction orifice(s) **440** that: I. is(are) mechanically coupled to flexible main body **210** so that longitudinal motion of the flexible main body **210** induces longitudinal motion of the fluid delivery orifice(s); II. is located proximal to the slidable boundary when the boundary forming balloon **558** is inflated to form the slidable boundary;

i. a rigid or resilient proximal fluid delivery port **827** in fluid communication with proximal interior location **829** within fluid delivery lumen(s) **520** that is proximal to the connector assembly **158**, the proximal fluid delivery port **827** being configured, when directly or indirectly connected to the source of pressurized fluid (e.g. **602** or other example(s)), to mediate a substantially fluid-tight (e.g. liquid-tight) coupling between the source of pressurized fluid and the fluid delivery lumen proximal interior location **829** via an interior of the proximal fluid delivery port **827**, the proximal fluid delivery port **827**, the fluid delivery lumen(s) **520** and the fluid delivery orifice(s) **525** being operative so that pressurized fluid distally delivered from the source of pressurized fluid into the fluid delivery lumen(s) **520** via the proximal fluid delivery port **827** distally flows through the fluid delivery lumen(s) **520** to fluid delivery orifice(s) **525** and enters into the more proximal portion **774** of the interstitial region via the fluid delivery orifice(s) **525**; and j. a proximal rigid or resilient suction port **830** in fluid (e.g. liquid) communication with proximal interior location **531** within suction lumen(s) **530** that is proximal to the connector assembly **158**, the proximal suction port **830** being configured, when directly or indirectly connected to the suction source **603**, to mediate a substantially air-tight coupling between the suction source **603** and the suction lumen proximal interior location **531** via an interior of the proximal suction port **830**, the proximal suction port **830**, the suction lumen(s) **530** and the suction orifice(s) **440** being operative so that negative pressure applied via the proximal suction port **830** causes material to exit the more

proximal portion **774** of the interstitial region via the suction orifice(s) **440** and travel proximally to the suction lumen proximal interior location **531**.

Some embodiments relate to a ballooned cleaning apparatus comprising : a. an elongate, narrow, flexible, main body **210** having length of at least 15 cm (or at least 20 cm or at least 25 cm or at least 30 cm); and a width of between 1 mm and 1 cm (for example, at least 3 mm and/or at most 6 mm – for example, between 3 and 6 mm); b. a boundary-forming balloon **588** mounted to the main body **210** in a distal half of the main body **210**, the boundary-forming balloon **588** being inflatable so that when the balloon **588** is inserted into an enclosing tube having a diameter between 4 and 11 mm so that the balloon **588**, inflation of the balloon **588** causes the balloon outer surface to contact an inner surface of the enclosing tube forms a slidable boundary between: I. a more proximal portion **774** of an interstitial region outside of the flexible main body and within the enclosing tube; and locations **778** within the ventilation tube **60** that are distal to the enclosing tube; c. a plurality of lumens located within and/or along the main body **210** including one or more suction lumen(s) **530** and one or more fluid delivery lumen(s) **520**, each lumen of the plurality of lumens substantially spanning a length of the main body **210** between the proximal end **204** of main body **210** and boundary-forming balloon **588**, each fluid delivery lumen(s) having an inner width of at most 3 mm (for example, at most 2 mm or at most 1 mm and/or at least 0.1 mm or at least 0.2 mm or at least 0.5 mm) each suction lumen(s) having an inner width of between 1 and 5 mm (for example, at least 2mm and/or at least 5 mm) (for example, a ratio between an inner width of the suction lumen and an inner width of the fluid delivery lumen).at least one of the plurality of lumens in fluid communication with the inner surface of the balloon; d. one or more distal suction orifice(s) **440** that: i. have an inner width of between 1 and 5 mm; ii. is(are) mechanically coupled to flexible main body **210** so that longitudinal motion of the flexible main body **210** induces longitudinal motion of the fluid delivery orifice(s) ; iii. is located proximal to the slidable boundary when the boundary-forming balloon **558** is inflated to form the slidable boundary longitudinally displaced from the slidable boundary by at most 2 cm; e. one or more distal fluid delivery orifice(s) **525** that: i. have an inner width of at most 3 mm and at most 30% of the inner width of the distal suction orifice(s) **440**; ii. is(are) mechanically coupled to flexible main body **210**

so that longitudinal motion of the flexible main body **210** induces longitudinal motion of the fluid delivery orifice(s) **525**; iii. is located proximal to the slidable boundary when the boundary-forming balloon **558** is inflated to form the slidable boundary and is longitudinally displaced from the slidable boundary by at most 2 cm.

In some embodiments, the flexible main body **210** includes a connection-assembly-proximal portion **598**, at least 5 cm of which is covered and/or enveloped by a substantially impermeable pliable sleeve **610**.

In some embodiments, a distal end of sleeve **610** is directly or indirectly attached to ventilation tube connector assembly **158** – for example, so that the main body **210** may slide through the sleeve. In contrast, in some embodiments, a proximal end of sleeve **610** is configured to have a substantially fixed longitudinal position relative to a proximal end of elongate flexible main body **210**.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGS. 1-3 describe prior-art devices.

FIGS. 4-25 illustrate systems, apparatus and portions thereof for cleaning an inner surface of a ventilation tube and/or hindering accumulation of biofilm thereon according to some embodiments.

FIGS. 26-29 are flowcharts of methods for cleaning an inner surface of a ventilation tube according to some embodiments.

BRIEF DESCRIPTION OF EMBODIMENTS

The invention is herein described, by way of example only, with reference to the accompanying drawings. With specific reference now to the drawings in detail, it is stressed that the particulars shown are by way of example and for purposes of illustrative discussion of the preferred embodiments of the exemplary system only and are presented in the cause of providing what is believed to be a useful and readily understood description of the principles and conceptual aspects of the invention. In this regard, no attempt is made to show structural details of the invention in more detail than is

necessary for a fundamental understanding of the invention, the description taken with the drawings making apparent to those skilled in the art how several forms of the invention may be embodied in practice and how to make and use the embodiments.

For brevity, some explicit combinations of various features are not explicitly illustrated in the figures and/or described. It is now disclosed that any combination of the method or device features disclosed herein can be combined in any manner – including any combination of features – any combination of features can be included in any embodiment and/or omitted from any embodiments.

Definitions

For convenience, in the context of the description herein, various terms are presented here. To the extent that definitions are provided, explicitly or implicitly, here or elsewhere in this application, such definitions are understood to be consistent with the usage of the defined terms by those of skill in the pertinent art(s). Furthermore, such definitions are to be construed in the broadest possible sense consistent with such usage.

Some embodiments relate to a 'width' of an objection – for example, a 'width' of an elongate flexible main body **210** or a width of an orifice(s) or a width of a lumen. A 'width' is defined as the square root of the cross section.

A 'fluid' (e.g. a cleaning fluid) may refer to flowable liquid or liquid-gas mixture such as: (i) a liquid; (ii) a mist (e.g. droplets of liquid suspended within a gas such as air) or (iii) any other mixture of liquid and gas (for example, having a significant liquid content - e.g. a mist or bubbled liquid including gas bubbles). Some embodiments refer to delivering of a 'cleaning liquid' or a 'source of pressurized liquid' – this is only one example. Any reference to a liquid (e.g. pressurized liquid, a liquid stream, a liquid lumen, a fluid delivery orifice, or other reference or combination thereof) may either refer to an actual liquid or to a gas-liquid mixture (e.g. a mist or any other gas-liquid mixture). 'Fluid communication' or 'liquid communication' refers to the ability of a liquid or a gas-liquid mixture to flow between two locations, and are used interchangeably. Throughout the present disclosure, a 'source of liquid' (e.g. pressurized liquid) and a 'source of fluid' (e.g. liquid or a liquid-gas mixture such as a mist) may be used interchangeably.

'Negative pressure' is suction -- 'negative pressure' and 'suction' are used interchangeably in the present disclosure.

A 'wiping element' is a 'wiper' and is used to wipe away material located on an inner surface **201** of ventilation tube **60**. Examples of wiping elements include but are not limited to inflatable balloons, stents, and any other width-expandable object configured to wipe away material on the inner surface **201** of ventilation tube **60**.

Some embodiments of the present invention relate to a wiping device for cleaning an inner surface of a ventilation tube in a closed ventilation system where an oxygen-including gas (e.g. air) is mechanically forced into the ventilation tube by an external ventilator. The wiping device includes an elongate flexible main body, a width-expandable wiping element (e.g. an inflatable balloon), one or more suction orifice(s) and one or more fluid delivery orifice(s).

In order to clean an inside surface of a ventilation tube, it is possible to carry out (e.g. simultaneously or in any order) a wiping operation, a fluid delivery operation and a suction operation. In some embodiments, during the wiping operation the width-expanded wiping element (e.g. the inflated balloon) moves longitudinally within the ventilation tube when in contact with an inner surface thereof - e.g. to wipe material located on the ventilation tube inner surface (e.g. biofilm). In some embodiments, during the fluid delivery operation, stream(s) of fluid (e.g. liquid stream(s) and/or gas stream(s) and/or stream(s) of a gas/liquid mixture for example a mist stream or a stream(s) of liquid including bubbles within) are sent, via the fluid delivery orifice(s), into the ventilation tube (e.g. incident upon an inner surface of the ventilation tube). In some embodiments, during the suction operation, material in the 'interstitial region' outside of the main body and within the ventilation tube is suctioned out of the ventilation tube.

FIGS. 4-6 and 8-22 relate to 'balloon embodiments' where the wiping element is an inflatable balloon **588**. FIG. 23A-23B illustrate a non-balloon embodiment where the width-expanding wiping element is other than a balloon. Unless specified otherwise, it is possible to substitute an inflatable balloon with any other width-expandable wiping element.

Fig. 4A illustrates a closed system cleaning system comprising: (i) an ETT or tracheostomy ventilation tube **60**; (ii) a ventilator machine **900**; (iii) a ventilation tube connector assembly **158** including a ventilator port **664**, a ventilation tube port **660**, and

a main body inlet **640**; and (iv) a flexible, elongate main body **210** having proximal **204** and distal **208** ends.

In some embodiments, the cleaning system is operative to clean an interior **201** of the ventilation tube **60** at a time when ventilation tube connector assembly **158** is directly or indirectly connected to both the ventilation tube **60** and the ventilator machine **900** so as to mediate a substantially air-tight connection (e.g. via an interior chamber(s) and/or conduit(s) of ventilation tube connector assembly **158**) between the ventilator machine and an interior of the ventilation tube. In one non-limiting example, an interior region and/or outer shape of ventilation tube port **660** matches a proximal end **62** of the ventilation tube **60** to create a substantial air-tight seal. In one non-limiting example, a tube or other conduit of a tube assembly (NOT SHOWN) may be connected to ventilator port **664** so that an interior of ventilator port **664** receives air from the ventilator machine and is in fluid communication with the ventilator machine **900** in a substantially air-tight manner.

In some embodiments, flexible, elongate main body **210** slidably and snugly passes through an interior of ventilation tube connector assembly **158** so that a proximal-distal direction of the main body **210** is aligned with a proximal-distal direction of the ventilation tube connector assembly **158** – i.e. distal end **208** of flexible main body **208** is on a distal side **908** of ventilation tube connector assembly **158** and proximal end **208** of flexible main body **208** is on a proximal side **908** of ventilation tube connector assembly **158**.

It is appreciated that when elongate main body **210** “snugly” passes through an interior of ventilation tube connector assembly **158** that there is no requirement for the fit between an outer surface of main body **210** and an interior of connector assembly **158** to be ‘snug’ in every location within connector assembly **158**. In some embodiments, a ‘snug fit’ in one or more locations is sufficient to provide the ‘snugly passing through’ feature.

In some embodiments, flexible, elongate main body **210** slidably and snugly passes through the interior of ventilation tube connector assembly **158** in a manner that does not substantially break the substantially air-tight connection between the ventilator machine **900** and the interior of the ventilation tube **60**.

The systems **600A-C** of FIGS. 4-16 all include an inflatable ‘boundary-forming balloon’ **588**, mounted to the flexible main body **200**. When inflated, the boundary forming balloon, in some embodiments, may provide two types of functionality: (i) an ‘flow obstruction functionality’ to significantly hinder fluid flow between locations on opposite longitudinal sides of the boundary-forming balloon (as discussed below, this may be useful for ‘concentrating’ suction so that the suction is predominantly in a proximal portion **774**); and (ii) a wiping functionality useful for cleaning the inner surface **201** of ventilator tube **60**, .

One salient feature of the ballooned cleaning apparatus provided by some embodiments is that the cleaning apparatus operates in a ‘closed system’ environment. During operation, it is possible to clean the inner surface **201** of ventilator tube **60** when the ventilation tube connector assembly **158**-mediated substantially air-tight seal between (i) ventilator machine **900** and/or an interior of ventilator port **664** and (ii) an interior of ventilation tube **60** and/or an interior of ventilation tube port **660** is maintained – this substantially air-tight seal is referred to as the ‘ventilation machine-ventilator tube’ seal.

As will be discussed below, concurrent with a maintaining of this ‘ventilation machine-ventilator tube’ seal, it is possible to position the mounted balloon **588** within the ventilation tube **60** (e.g. in a distal half of ventilation tube **60**) for example, by moving a distal end **208** of the main body **210** in a distal direction towards a distal end **64** of ventilation tube **60**. For example, it is possible to distally move the mounted balloon **588** at a time when the mounted balloon **588** is in a ‘non-contact state’ (i.e. not in contact with an inner surface **201** of ventilation tube **60**) . After the boundary-forming balloon **588** is thus positioned, inflation of the balloon induces contact between an outer surface of the balloon **588** and an inner surface **201** of ventilation tube **60** and/or ‘obstructs’ (i.e. significant hinders) longitudinal flow between proximal **774** and distal **778** portions of the interior of ventilation tube **60**. As will be discussed below, this slidable ‘boundary; between proximal **774** and distal **778** portions is useful for facilitating the cleaning of the inner surface **201** – for example, for substantially confining locations of negative pressure and/or fluid (e.g. pressurized fluid such as pressurized liquid or pressurized fluid) introduced into an interstitial region outside of main body **210** and within ventilation tube

60 so that the suction or pressurized fluid is introduced ‘predominantly’ in a proximal portion **774**.

In some embodiments, as illustrated in various figures (e.g. FIGS. 4A, 8, 14), inflatable “boundary forming” or ‘inflated-into-contact-with-an-inner-surface-of-ventilation-tube’ balloon **588** is mounted to flexible main body **210** at a location that is or near a distal end **208** or flexible main body **210**.

In different embodiments, a location ‘near a distal end’ **208** of main body **210** may refer to: (i) in a distal half of flexible main body **210**; or (ii) in a distal third of flexible main body **210**, or (iii) in a distal fifth of flexible main body **210**, or in (iv) a distal tenth of flexible main body **210**.

Also shown in FIG. 4A is a second balloon **550** (which may or may not be inflatable) which is mounted to flexible main body **210** at a ‘second balloon mounting location’ that is proximal to a ‘boundary-forming balloon mounting location’ of the main body **210** to which “boundary forming” and/or ‘inner surface-contacting’ balloon **588** is mounted. In some embodiments, the ‘second balloon mounting location’ is ‘near a distal end’ **208** of main body **210** – for example, in a distal half or third or fifth or tenth of flexible main body.

In the non-limiting example of FIG. 4A, second balloon **550** includes one or more fluid delivery orifice(s) **525** located on the surface of the second balloon **550**. In other embodiments, the fluid delivery orifice(s) **525** may be located in other locations.(e.g. see FIGS. 8 or 14). In various embodiments, fluid (e.g. liquid or mist or any gas/liquid mixture) delivered from source of pressurized liquid **602** into an interior of the ventilation tube **60** via fluid delivery orifice(s) **525** may be used to clean an inner surface **201** of ventilation tube **60**. In the non-limiting example of FIG. 4A, fluid delivery orifice(s) **525** located on the surface of the second balloon **550** – for example, as voids or holes in the surface of the second balloon **550**. This is not a limitation, and in the examples of FIGS. 8 and 16 alternative configurations are illustrated.

Also illustrated in FIG. 4A are suction orifice(s) **440**, which, in some embodiments, are supplied with negative pressure by suction source **601** and facilitate cleaning of the inner surface **201** of ventilation tube **60**. In some embodiments, material within the interior of ventilation tube **60** may be suctioned into suction orifice(s) **440** and

proximally transported out of ventilation tube **60** – e.g. to a location that is proximal of ventilation tube connector assembly **158**.

As will be discussed below, fluid communication between the suction source **601** and/or pressurized fluid source **602** and the suction **440** or fluid delivery **525** orifice(s) may be provided by one or more connecting lumen(s) within or along the main body **210**.

As illustrated in FIGS. 4A-4B, at least a portion **598** of elongate main body **210** is located proximal to ventilation tube connector assembly **158**. The magnitude of this ‘portion’ may depend on an extent to which distal end **208** and/or balloon **588** is deployed within ventilation tube **60** and/or an extent to which distal end **208** and/or balloon **588** is longitudinally displaced from ventilation tube connector assembly **158** – for example, an extent to which the main body **210** slides through ventilation tube connector assembly **158** in a distal direction.

Because The system or method of FIGS. 4A-4B is a ‘closed system,’ in some embodiments, the system may include a substantially impermeable and/or pliable sleeve **610** for protecting an outer surface of main body **210**. In some embodiments, sleeve **610** envelops and/or protects at least some (e.g. at least a majority or at least a substantial majority of at least 75% or substantially all of (i.e. at least 90%)) of an outer surface of the ventilation-tube-connector-assembly-proximal portion **598** of elongate main body **210**. In some embodiments, sleeve **610** may provide this enveloping and/or protection functionality when a length of the ventilation-tube-connector-assembly-proximal portion **598** of main body **210** is at least 3 cm or at least 5 cm or at least 7 cm or at least 10 cm. As noted above, in some embodiments, a length of this proximal portion **598** may be modified by sliding, in a proximal or distal end, main body **210** through ventilation tube connector assembly **158**.

In some embodiments, a distal end **908** of sleeve **610** is (i) directly or indirectly attached to and/or (ii) has a location that is fixed and/or longitudinally fixed relative to ventilation tube connector assembly **158**. In some embodiments, a longitudinal position of a location of a distal end **908** of sleeve **610** corresponds to a location on ventilation tube connector assembly **158** (e.g. at or near main body inlet **640**) and/or is longitudinally displaced from a proximal end (e.g. corresponding to main body inlet **640**) of ventilation tube connector assembly **158** by at most 5 cm or at most 3 cm or at most 2 cm or at most

1 cm and/or at most 50% or at most 30% or at most 20% or at most 10% of a length of ventilation-tube-connector-assembly-proximal portion **598** of main body **210**.

In some embodiments, a location of distal end **908** of sleeve **610** is not fixed relative to main body **210**. For example, main body **210** may be longitudinally slidable within the sleeve **610** at or near a location of the distal end **908**.

In some embodiments, a location of proximal end **904** of sleeve **610** is fixed and/or longitudinally fixed relative to a proximal end **204** of main body **210**.

In some embodiments, sleeve **610** forms a substantially air-tight seal between the external environment and an outer surface of ventilation-tube-connector-assembly-proximal portion **598** of main body **210** and/or between the external environment and region of space outside of an outer surface of ventilation-tube-connector-assembly-proximal portion **598** of main body **210** and within sleeve **610**.

In the non-limiting example of FIGS. 4A, an input module assembly **156** includes respective ports for interfacing: (i) with suction source **601** (i.e. suction port **820** – for example, shaped as in element **34** of FIG. 1A or any other shape appropriate to function as a suction port), (ii) a source of pressurized fluid such as liquid or mist or any gas-liquid mixture under pressure (i.e. a port for receiving pressurized fluid from **602**), and (iii) inflation source **603** (i.e. a port for receiving a gas flow or liquid flow from **603** – for balloon inflation). Suction source **601** provides negative pressure for suctioning material out of an interior of ventilation tube **60** (e.g. material formerly attached to an interior surface **201** of ventilation tube **60** – e.g. as biofilm) – e.g. via suction orifice(s) **440**.

In some embodiments, pressurized fluid from source **602** forced, via a fluid delivery lumen **520** (not shown in FIGS. 4A-4B) may enter, via fluid delivery orifice(s) **525**, into an interstitial region inside of the ventilation tube **60** and outside of the main body **210**. In some embodiments, a stream of the delivered fluid passes through an interstitial region *en route* to the inner surface **201** of ventilation tube **60**, and is incident upon the ventilation tube inner surface **201**. Delivery of the fluid (e.g. liquid or mist or any liquid-gas mixture) into the interstitial region and/or to the inner surface **201** may be useful for cleaning the ventilation tube inner surface **201**.

In some embodiments, pressurized liquid or gas delivered from inflation source **603** is delivered to boundary-forming inflatable balloon **588** inflate boundary-forming balloon **588** (e.g. to form a slidable boundary as will be discussed below).

In the non-limiting example of FIGS. 4A-4B, the fluids source **602** (e.g. source of pressurized liquid or mist or any gas/liquid mixture) and the inflation source **603** are illustrated as two separate elements. This is not a limitation. In other embodiments (see, for example, FIG.14) the source of pressurized liquid **602** may be used to both inflate boundary-forming balloon **588** and to delivery fluid via fluid delivery orifice(s) **525**.

FIGS. 4A-4B refer to the example where a source of fluids (e.g. liquid or any other liquid-gas mixture) is 'external' and may either be a source of liquids or a source of other fluids such as gas-liquid mixtures (e.g. mist). In the example of FIG. 4C, a gas/liquid mixture source (e.g. a pressurized gas/liquid mixture) **698** is explicitly illustrated and may be external to device **600**.

In the example of FIGS. 4A-4B the source of liquid **602** and/or source of a gas/liquid mixture (i.e. **602** or **698**) are 'external' to the device – the cleaning device receives either liquid or a mixture of liquid and gas (e.g. via one or more ports). In some embodiments, the received fluid (e.g. liquid and/or gas) is pressurized.

In the example of FIG. 4D, the cleaning device **600** receives: (i) gas (or gas-liquid mixture) (e.g. pressurized) from a first source **692** and (ii) liquid (or gas-liquid mixture) (e.g. pressurized) from a second source **602**. These may be mixed –for example, within an 'inlets module' of device **600** or in any other location – for example, within a chamber or mixing apparatus **696** that is directly or indirectly connected/attached (e.g. permanently attached) to main body **610**. This is illustrated schematically in FIG. 4E.

In some examples, this may obviate the need to provide a source of pressurized liquid. For example, it is possible to provide (i) a source of pressurized gas (or pressurized gas/liquid mixture) **692** and (ii) a source of liquids (i.e. pressurized or unpressurized) or liquid-gas mixture.

Liquids and gases may be mixed together within a mixing apparatus – for example, the apparatus **696** illustrated in FIG. 4F which operates for example according to the Venturi principle. The skilled artisan, after reading the present disclosure, will realize that there are a number of ways of mixing fluid and gases – for example, to

produces a pressurized gas-liquid mixture including but not limited to techniques from the art of nebulizers (e.g. atomizers or jet nebulizers). Exemplary techniques include but are not limited to atomizing techniques or ultrasonic techniques or bubbling techniques any other technique for mixing gas and liquid - e.g. to produce a liquid-gas mixture for example pressurized.

FIG. 5 is a close-up view of locations near distal end **208** of main body **210** in some embodiments and in some configurations. Inflatable balloon **588**, suction orifice(s) **440** and fluid delivery orifice(s) are all visible close to the distal end **208** of main body **210**.

FIG. 6 illustrates the distal end of main body **210** after insertion into ventilation tube **60** having an inner surface **201**. In the example of FIG. 6A, inflatable balloon **588** divides the region of space within the ventilation tube **60** but outside of main body **210** into two regions:

- (i) A first sub-region **774** that is proximal to slidable 'boundary' whose longitudinal location is identified in FIG. 6 by a dividing line **780** (it is appreciated that the dividing line **780** is only a mathematical construct). This first sub-region **774** is referred to as the 'more proximal portion of the interstitial region outside of the main body **210** and inside of ventilation tube **60**;
- (ii) A second sub-region **778** that is distal to dividing line **780**.

In the example of FIGS. 6A, 6E (also see FIG. 10A, 11A; 16A-16C) the balloon in contact with the inner surface **201** of ventilation tube **60** actually provides a seal between the first (i.e. proximal **774**) and second (i.e. distal **778**) regions. However, this is not a limitation, and in other embodiments (see, for example, FIGS. 6F-6I; 10C, 11C; 16D) it is possible for the inflated balloon to obstruct (i.e. significantly hinder) longitudinal flow between the first (i.e. proximal **774**) and second (i.e. distal **778**) regions without forming such a seal.

The first sub-region **774** may be referred to as 'the more proximal portion of the region within the ventilation tube and outside of main body' while the second sub-region **778** may be referred to as the 'the more distal portion of the region within the ventilation tube and outside of main body.'

This second sub-region **778** may include: (i) locations in the interstitial region that are distal to the slidable boundary **770**; and (ii) locations in the interior of the ventilation tube that are distal to the slidable boundary **770**.

In the examples of FIGS. 6A, 6B, 10A, 14A, 14B, 14C, contact balloon **588** (i.e. inflatable into contact) is deployed near the distal end **208** of main body **210** (but not at the distal end **208**), and sub-region **778A** is visible. In the examples of FIGS. 6E and 11A, inflatable balloon **588** is deployed at distal end **208** of main body **210** and sub-region **778A** is absent. In both sets of examples, sub-region **778B** is visible.

In the example of FIGS. 6, a plurality of balloons located within ventilation tube **60** (i.e., each mounted to the main body **210** – e.g. at or near a distal **208** end) include: (i) inflatable ‘first’ balloon **588** and (ii) second balloon **586** deployed to main body **210** (e.g. mounted to main body) which may or may not be inflatable and which functions as a ‘liquid supply balloon.’ The second balloon **586** includes one or more holes or voids which are fluid delivery orifice(s) **525** (in the example of FIG. 6A, four holes **525A-525D** are illustrated). A pressurized liquid **525** may enter, via the fluid delivery orifice(s) **525** into “the more proximal portion of the region within the ventilation tube and outside of main body’ **774** of the interstitial region proximal to inflatable balloon **588** (for example, when balloon **588** is inflated into contact and/or so as to obstruct).

In some embodiments, the delivered fluid takes the form of a stream **556** – for example, strong enough so that upon exit from the fluid delivery port **525** the flowing liquid has enough momentum to reach an interior surface **201** of ventilation tube **60**. In some embodiments, the delivered fluid is pressurized immediately before exiting fluid delivery port **525** by at least 1.5 atmospheres or at least 2 atmospheres or at least 3 atmospheres.

In some embodiments, the delivered fluid is pressurized enough so that upon exiting fluid delivery port **525** a ‘jet of fluid’ or a ‘strong jet’ of fluid is obtained. In some embodiments, pressurized under a pressure of at least 1.5 atmospheres or at least 2 atmospheres or at least 3 atmospheres exits a fluid delivery orifice having an internal width that is at most 1.5 mm or at most 1 mm or at most 0.75 mm or at most 0.5 mm.

In some embodiments, the includes only a single fluid delivery orifice. Alternatively, in other embodiments, it is advantageous to employ a plurality of delivery

ports. FIG. 7A illustrates four streams of liquid **556A-556D** respectively exit from four different fluid delivery orifices **525A-525B**.

In some embodiments, pressurized liquid (e.g. from a source outside of the ventilation tube and/or proximal to connector **158** – e.g. from pressurized liquid source **602**) is forced (e.g. simultaneously forced) through first **525A** and second **525B** fluid delivery orifices to respectively produce first **556A** and second **556B** fluid streams that are respectively incident (e.g. simultaneously incident) upon an inner surface **201** of the ventilation tube **60** at first **552A** and second **552B** locations. In some embodiments, the first **552A** and second **552B** locations are substantially on opposite sides of the ventilation tube **60** inner surface **201** within a tolerance that is at most 75 degrees (i.e. angle theta is between 105 and 180 degrees) or within a tolerance of at most 45 degrees (i.e. angle theta is between 135 and 180 degrees) or within a tolerance of at most 25 degrees (i.e. angle theta is between 155 and 180 degrees). Note that there is no requirement for first **552A** and second **552B** locations to have the same longitudinal position – i.e. it is possible to calculate theta by projecting the first and second positions into a plane that is perpendicular to a central axis of ventilation tube (e.g. having a longitudinal position that is the average of the longitudinal positions of the for first **552A** and second **552B** locations).

Although not a limitation, in some embodiments, one or more of the streams **556** may have enough momentum to reach an enclosing tube (e.g. ventilation tube **60**). For example, any combination of the extent to which the delivered fluid pressurized and/or the size of the orifice (i.e. smaller sizes facilitated greater fluid momentum in stream **556**) may be such that, for any position of main body **210** within tube **60**, when the local central axis **202** (i.e. in the region of locations **552A** and **552B**) of main body **210** is perpendicular to the gravity vector, and when the local central axis (i.e. in the region of locations **552A** and **552B**) of an enclosing tube (e.g. ventilation tube **60**) is parallel to gravity (e.g. both local axes are substantially straight), momentum of the delivered fluid upon exit via orifices **525A** and **525B** is sufficient such that respective streams **556A** and **556B** are incident upon locations in the inner wall

For example, this may be true any position of main body **210** relative to an enclosing tube – e.g. a “reference” cylindrical tube having an inner diameter that is at

least 4 mm or at least 6 mm and/or at most 12 mm or at most 10 mm or at most 8 mm. In some embodiments, under these conditions (e.g. both central axes parallel to the gravity vector so that the enclosing tube and main body **210** are at least locally 'upright', size features of the enclosing tube – e.g. ventilation tube **60**) streams **556A** and **556B** may have enough momentum so as to be incident upon inner surface **201** of the enclosing tube at locations **552A**, **552B** that are substantially on opposite sides of the inner surface **201** of the enclosing tube **60**.

Any features described with relation to FIGS. 7A-7B are not limited to embodiments of FIG. 6, and may relate to the any other embodiment.

Not wishing to be bound by any particular theory, in some embodiments, delivering a stream of fluid with sufficient momentum to be incident upon inner surface **201** of ventilation tube **60** may be useful for mechanically dislodging biofilm temporarily attached to the ventilation tube inner surface **201** and/or chemically interacting with the biofilm in order to reduce any forces causing the biofilm to adhere to inner surface **201**.

Not wishing to be bound by any particular theory, in some embodiments, ensuring that a plurality of streams are incident upon different 'sides' of ventilation tube inner surface **201** may be useful for achieving this effect throughout ventilation tube inner surface **201** (e.g. for longitudinal locations being cleaned – for example, located in a distal half of ventilation tube **60**).

Reference is made once again to FIG. 6A. In FIG. 6A, suction orifice(s) **440** is also illustrated.

As illustrated in FIG. 6A, fluid delivery orifice(s) **525** is supplied with pressurized liquid (e.g. from liquid source **602**) via fluid delivery lumen(s) **520**. In some non-limiting embodiments, pressurized liquid received via fluid delivery lumen(s) **520** also functions to inflate second balloon **586**. In some embodiments, second balloon **586** is inflatable. Alternatively, second balloon **586** is not required to be inflatable.

Suction orifice(s) **440** is supplied with negative pressure from suction source **601** via suction lumen(s) **530**.

Inflatable balloon **588** is inflated with liquid or gas received from inflation source **603** via balloon inflation lumen **585**.

In some embodiments, when inflatable balloon **588** is inserted into ventilation tube **60**, balloon **588** is not sufficiently inflated to contact an inner surface **201** of tube **60** and thus free longitudinal motion of inflatable sealing balloon **588** is possible. After inflation, a slidable obstructing 'boundary' is created so that inflatable balloon **588** may longitudinally move in ventilation tube **60** while in contact with the tube and/or inflated so as to 'obstruct' (i.e. significantly hinder) longitudinal flow. In some embodiments, inflation of balloon **588** is sufficient (e.g. for at least one location of main body **588** within main tube **210**) to cause contact with an enclosing ventilation tube **60** and/or to 'obstruct flow' with the aforementioned 'reference' enclosing tube having an inner diameter of at least 4 mm or at least 6 mm and/or at most 12 mm or at most 11 mm or at most 10 mm or at most 8 mm.

FIG. 6C illustrates a cross section of main body **210** according to some embodiments. In some non-limiting example, lumen(s) may be embedded within main body **210** and provided as elongate voids within main body **210**. In FIG. 6C, cross sections of three lumens are illustrated: (i) of suction lumen **530**; and (ii) fluid delivery lumen **520** and (iii) of balloon lumen **580** via which pressurized gas or liquid is delivered from inflation source **603** into boundary-forming inflatable balloon **588**. As noted earlier, there is no requirement for separate sources **602**, **603** for fluid delivery into proximal region **744** and for balloon inflation. Similarly, there is no requirement separate lumen **520**, **580**.

FIGS. 8-11 illustrates an embodiment that lacks the second balloon **586**. In the example of FIGS. 8-11, suction **440** orifice(s) and fluid delivery **525** orifice(s) are located on the surface of elongate main body **588**. As was the case in the embodiments of FIGS. 4-6, (i) boundary-forming balloon **588** is inflated to form the slidable boundary between proximal **774** and distal **778** regions of the interior of tube **60**, (ii) pressurized fluid (e.g. liquid or liquid-gas mixture such as a mist) enters proximal region **774** via fluid delivery **525** orifice(s), and (iii) material is suctioned into suction **440** orifice(s) for proximal transport out of ventilation tube **60**. As noted elsewhere, fluid delivery and suctioning operations may be carried out sequentially or simultaneously. As noted elsewhere, in some embodiments, longitudinal motion of inflated boundary-forming

balloon **588** (e.g. in a proximal direction) may be useful for wiping biofilm or other material attached to ventilation tube inner surface **201**.

In the example of FIGS. 10A-10B, balloon **588** is not mounted at the distal end of main body **210**. In the example of FIGS. 11A-11B, balloon **588** is mounted at the distal end of main body **210**. In different embodiments, balloon **588** may be mounted to main body **210** at different locations, including locations not illustrated in the figures.

In the example of FIG. 12, boundary-forming balloon is not inflated and/or not sufficiently inflated to form a boundary that obstructs (i.e. significantly hinders) longitudinal flow between locations proximal and distal to balloon **588**. This NON-CONTACT configuration may be useful for: (i) insertion of balloon **588** into tube **60** and/or distal motion of balloon **588** within tube **60** to a desired or target cleaning location; (ii) operation so that material located distal to balloon **588** (e.g. within the interior of tube **60** or distal to tube **60**) may be suctioned into suction orifice(s) **440** and subsequently proximally transported out of tube **60** (e.g. within suction lumen(s) **530**).

Thus, in some examples, it is possible to operate the cleaning device in multiple modes. In the first mode (see, e.g. FIGS. 6A-6B, 6E, 10A, 11A, 16A, 16B), (i) boundary-forming balloon **588** is in CONTACT mode so that 'obstructing' boundary (i.e. to significantly hinder longitudinal flow) is maintained; and (ii) material suctioned via proximally-located suction orifice(s) **440** (i.e. located proximal to boundary and/or balloon **588**) is restricted, by the presence of boundary, to material within the proximal portion **774** of the interstitial region. This mode may be used, in some embodiments, primarily to clean biofilm adhering to and/or temporarily attached to inner surface **201** of ventilation tube **60**.

In the second mode (see FIG. 12), boundary forming balloon **588** is not sufficiently inflated to main boundary – however, proximally-located suction orifice(s) **440** are used to suction material distal of balloon **588** (for example, tracheo-bronchial fluids in the patient's trachea).

FIG. 13 illustrated proximal ends of various lumens. For example, it is possible to deliver pressurized fluid (e.g. from a source **602** of pressurized liquid or liquid-gas mixtures) through a proximal fluid port **827** into pressurized fluid reservoir **820**.

Pressurized liquid enters fluid delivery lumens **520** via respective openings in fluid delivery lumen located near the proximal end of the fluid delivery lumen **520**.

In some embodiments, reservoir **820** may function as a mixing apparatus to mix gas and liquids – e.g. to provide pressurized liquid-gas mixtures).

As noted above, there is no requirement for multiple fluid delivery orifices **525**, and some embodiments relate to the case where only a single fluid delivery orifice **525** is present. For embodiments where pressurized fluid (e.g. liquid or liquid-gas mixture) is distally sent to multiple fluid delivery orifices **525**, it is possible to supply a multiple orifices by a single fluid delivery lumen **520** and/or to include multiple delivery lumen(s) **520**. In FIG. 13, where the device includes five fluid delivery orifice **525**, both features are illustrated. Multiple (e.g. two) fluid delivery lumen(s) are employed, and two of these lumens supply pressurized fluid (e.g. liquid or liquid-gas mixture) to multiple fluid delivery orifices **525**.

FIGS. 14-16 illustrate an embodiment of the invention where the fluid delivery orifices are actually located on surface **589** of boundary-forming balloon. In the non-limiting example of FIG. 4A, fluid delivery orifice(s) **525** located on the surface of the second balloon **550** – for example, as voids or holes in the surface **589** of the balloon **588**. In some embodiments, fluid delivered via these orifice(s) **525** is restricted to ‘proximal’ locations **774** within the interstitial region but proximal to boundary. As such, it may be useful to locate orifice(s) **525** on a proximal part of balloon and/or to orient orifice(s) **525** to deliver fluid in a proximal direction. In some embodiments (see FIG. 7) streams of fluid are incident upon substantially different sides of the inner surface **201** of tube **60** - this feature is also provided in FIGS. 16A-16C.

In the example of FIG. 16A, a single balloon is provided **588**. Because this balloon includes one or more voids/holes on its surface **589** (i.e. these function as fluid-delivery orifices), pressurized fluid (i.e. liquid or liquid-gas mixtures – for example, a liquid-gas mixture that is predominantly liquid such as a bubbled liquid) needs to be supplied (e.g. from a source outside of tube **60** such as fluids source **602**) at a sufficient rate (e.g. via lumen(s) **620**) to maintain sufficient inflation of balloon **588** to maintain boundary. In some embodiments, the rate of pressurized fluid delivery to balloon **588** should, in the steady state, exceed that rate at which fluid is delivered from orifice(s) **525** in balloon

surface **589** to maintain the contact between balloon **588** and inner surface **201** of tube **60**.

In some embodiments, a ratio between an area of all orifice(s) **525** or voids in a surface **589** of boundary-forming balloon **588** to the total area of the surface **589** of boundary-forming balloon is at most 0.2 or at most 0.1 or at most 0.05 or at most 0.03 or at most 0.01 and/or at least 0.005 or at least 0.01 or at least 0.03 or at least 0.05.

Not wishing to be bound by theory, it is noted that in some clinical situations, a practitioner (e.g. nurse or doctor) needs to deflate and/or remove the balloon rather 'quickly' – e.g. within 60 seconds or 30 seconds or 15 seconds from a time that boundary is formed. This may be useful for reducing a risk of suffocation to the patient. Not wishing to be bound by theory, the provisioning of a single mechanism for both pressurized fluid delivery as well as maintenance of boundary can be useful for reducing the risk that, at the end of the procedure whereby an inner surface **201** of tube **60** is cleaned, the practitioner remembers to 'shut off' the fluid delivery but neglects to deflate boundary-forming balloon **588**.

In some embodiments (see FIG. 14), it is no longer necessary to include separate pressurized fluid **602** and inflation **603** sources – it is sufficient to provide a single source for fluid delivery and for inflation.

In one variation (see FIG. 16B), it is possible to include a balloon within a balloon. For example, the inner balloon may be supplied with liquid or with a gas or a mixture thereof, and may have a separate fluids supply (and/or lumen(s)) than that of the outer balloon. In another variation (see FIG. 16C), a single balloon may include multiple compartments which are supplied by a common fluid supply and/or lumen or by separate supplies and/or lumens.

For the example of FIG. 16C, the proximal compartment includes fluid delivery orifice(s) **525**, while the distal compartment lacks such orifices. The device may be operated in multiple modes. In one mode, distal compartment is sufficiently inflated (e.g. with gas or fluid) to form boundary. In this mode, delivery of fluid via fluid orifice(s) **525** in the proximal compartment is not needed to maintain the contact.

In a second mode, the distal compartment is not inflated or not sufficiently inflated to form boundary. In this mode, the device may provide features similar to those observed in the embodiment of FIG. 16A.

FIG. 17A illustrates yet another embodiment. In the example of FIG. 17A, a common fluids source **602** supplies fluid (e.g. liquid-containing fluid) to both balloon **588** and fluids delivery orifice **525**. In some embodiments, common fluids source **602** is pressurized.

FIG. 17B illustrates an embodiment wherein a single fluids lumen **520** supplies both fluids delivery lumen **520** and an interior of balloon **588** with fluid (e.g. liquid and/or gas - for example, a pressurized fluid such as a pressurized liquid). The fluid travels within lumen **520** - at location **516**, a first portion of the fluid that has travelled within lumen **520** continues in a distal direction into balloon **588** to inflate balloon **518**; a second portion of the fluid that has travelled within lumen **520** exits into proximal portion **774** of the interstitial region via fluid delivery orifice **525**.

Although not a limitation, the balloon as illustrated in FIGS. 17A-17B is sealed and is not leaky - this is in contrast to the balloon of FIG. 16A which is leaky and has voids/holes therein.

In some embodiments related to FIG. 17A and/or 17B, one or more of (i.e. any combination) the following features may be provided: (i) a single lumen **520** or a single fluids source **602** supplies fluid to fluid delivery orifice **525** and to inflatable balloon **588**; and/or (ii) a single lumen **520** or a single fluids source **602** supplies fluid to fluid delivery orifice **525** and to an inflatable non-leaky or sealed balloon **588**; and/or (iii) a single lumen **520** or a single fluids source **602** supplies fluid to inflatable balloon **588** and to a fluid delivery orifice **525** not located on balloon **588** (e.g. proximal to balloon **588** - e.g. by at least 3 mm or at least 5 mm or at least 1 cm).

In the example of FIG. 17A, parallel lumens **580** and **520** respectively leading to an interior of balloon **588** and to fluid delivery orifice **525** are supplied with fluid (e.g. pressurized fluid - e.g. pressurized liquid or mist) by a common fluid source.

In the example of FIG. 17B, a single lumen supplies fluid (e.g. pressurized fluid) to both balloon **588** and to fluid delivery orifice **525**.

FIGS. 18-22 relate to an embodiment whereby cleaning device includes a 'mist-formation assembly.' In the examples of FIGS. 18-22, a mist is formed by combining (i) a gas or gas-rich fluid (e.g. from fluid source **602A**) and (ii) a liquid or liquid-rich fluid (e.g. from fluids source **602B**). In some embodiments, the gas or gas-rich fluid is received into a first fluid-delivery lumen **520A** (e.g. via port **822**) and the liquid or liquid-rich fluid is received into a second fluid-delivery lumen **520B** (e.g. via port **824**). Upon mixing (i.e. at a mixing location - see for example mixing location **522** of FIG. 19A) between the two fluids, the liquid or liquid-rich fluid forms droplets which are suspended within the gas or the gas-rich fluid, thereby forming the mist.

In some embodiments, the gas or gas-rich fluid is pressurized and/or flowing in a distal direction at some sort of 'significant flow velocity' upon exiting second fluid delivery lumen **520B** via fluid delivery orifice **224** to mixing location **522**. In some embodiments, there is no need for the fluids (e.g. the liquid or liquid-rich fluids) within the first fluid delivery lumen **520A** or fluids of liquids-rich fluids source **602B** to be pressurized. For example, the flow velocity of gas or gas-rich fluids at mixing location **522** (e.g. which is also 'close to' a fluid delivery orifice **244** via which fluids exit first fluid delivery lumen **520A**) may be sufficient to induce distal motion of liquid or a liquids-rich fluid within the first fluid delivery lumen **520A** to the mixing location **522** where the droplets are formed from liquid and suspended in the gas (or gas-rich fluid) flow to form the mist.

In the examples of FIG. 19A-19B, the mist may be formed at or below a surface of main body **210** or 'within main body **210**' (e.g. at a location within ventilation tube **210**). In the example of FIG. 20, the mist may be formed within the proximal portion **774** of interstitial region.

For both cases or for any other embodiment where mist is generated 'in situ' (i) at a location within main body **210** (e.g. within main body **210** at a location within ventilation tube); and/or (ii) at a location within proximal portion **774** of interstitial region, it may be useful to arrange fluid delivery lumens **224** and **244** to be 'close to each other' - i.e. so that a distance between 'closest locations' of fluid delivery lumens **224** and **244** (not a 'center-center distance') is at most 5 mm or at most 4 mm or at most 3 mm or at most 2 mm or at most 1 mm.

FIGS. 21A-21C are cross-sections of a main body **210** of a device including a mist-formation assembly according to some embodiments. In some embodiments, within a cross section of main body **210** the fluid delivery lumens **520A**, **520B** are 'close to each other' so that closest locations thereof are separated by at most 5 mm or at most 4 mm or at most 3 mm or at most 2 mm or at most 1 mm.

FIG. 22 is a more schematic illustration of a cleaning device including a mist formation assembly. In some embodiments, the mist formation assembly is operative, when the main body **210** is inserted through the tube-connector assembly **158** into the ventilation tube **60**, to form a mist from a liquid or a liquid-rich fluid and a gas or a gas-rich fluid (e.g. supplied by respective sources **602B** and **602A**) so that the formed mist flows within a proximal portion **774** of the interstitial region that is proximal of to balloon **588**.

As noted earlier, inflatable balloon **588** is just one example of a width-expandable wiping element.

Another example of a width-expandable wiping element is illustrated in FIGS. 23A-23B. The 'width-expandable' wiping element is expandable in a width direction defined by the elongated body **210** - i.e. expandable in cross-section plane or a plane perpendicular to an elongate or central axis **202** of elongated body **210**.

Inflatable balloon **588** is one example of the width-expandable wiping element - when inflated, balloon **588** may make contact with an inner surface **201** of ventilation tube **60**.

Another example of a width-expandable wiping element **588** is illustrated respectively in compressed and expanded configuration respectively in FIGS. 23A-23B. For example, in FIGS. 23A-23B or in other embodiments, the wiping element **380** may be outwardly biased - when within a lumen of main body (see FIG. 23A - the lumen functions as a 'sheath') the outwardly-biased element may be constrained within the lumen so that the width (i.e. in a direction perpendicular to a central axis or elongate axis of main body **210**) is relatively 'small.' This compressed configuration is illustrated in FIG. 23A.

In some embodiments, the wiping element **380** or **588** (e.g. outwardly-biased wiping element) may include a so-called shape-memory material. For example, the

wiping element may be pre-shaped into a spiral shape as shown in FIGS. 23A-23B. In FIG. 23A, the wiping element is 'compressed' within main body **210** - in FIG. 23B, the wiping element is moved distally relative to the 'sheath' or 'lumen' of main body. In this case, the wiping element expands to or towards its 'equilibrium shape' - in this case, a spiral shape. The spiral-shaped wiping element **380** may be contact with an interior wall **201** of ventilation tube **60**, and just like was seen for the balloon-related examples, longitudinal motion of wiping element **380** may wipe material on the interior wall **201** of ventilation tube **60** - for example, biofilm. The wiping element may also define a 'boundary' between proximal **774** and distal **778** portions of the interior of ventilation tube **60**.

Since, in some embodiments, an inflatable balloon **588** is a special case of a width-expandable wiping element, any element which may be 'proximal' to a balloon **588** may, in some embodiments, be proximal to any width-expandable wiping element, including balloons **588** or width-expandable wiping elements other than balloons (e.g. see FIGS. 23A-23B or any other width-expandable wiping element).

Unless indicated to the contrary, in any embodiment illustrated herein in the contact of an inflatable balloon **588** (e.g. a 'boundary-forming' balloon **588**), it is possible to substitute any width-expandable wiping element including those other than balloons instead.

In some embodiments it is possible to manually regulate the suctioning and fluid delivery operations that are carried out within ventilation tube **60** using suction **440** and fluid delivery **525** orifices. In the example of FIG. 24A, a switching assembly is provided - for example, to regulate behavior of a valve. Fluids switch **6022** regulates fluid delivery and suction switch **6011** regulates suction. In some embodiments, it is possible to easily and simultaneously control both switches. For example, a single switch may regulate both fluid delivery and suctioning - see for example, FIG. 24B. In some embodiments, any one of these switches, or both of these switches are biased to an 'off' position where there, substantially, is no suction and/or no fluid delivery.

In some embodiments, source **602** of pressurized fluid may include a syringe assembly - when the syringe is depressed, this distally forces fluid (e.g. liquid or a mist) into ventilation tube via the fluid delivery lumen.

Alternatively or additionally, a continuous (i.e. constant or non-constant) source of suction **601** or pressurized fluid **602** may be provided.

The example of FIG. 25 relates to the case where a balloon **588** (e.g. configured as a 'boundary-forming' balloon and/or as a width-expandable wiping element) is operatively linked to and/or in fluid communication with a balloon inflation indicator or meter **663** which indicates a degree to which boundary-forming balloon **588** (i.e. configured as a width-expandable wiping element). In FIG. 25, this is illustrated for the case of an inflation source **603** separate from fluids source **602** - however, this is not a limitation and it is possible also to meter or measure a degree of balloon inflation when the same fluids source **602** supplies fluids both to fluid delivery orifice **525** and boundary-forming balloon **588**.

In one non-limiting embodiment, the balloon inflation indicator or meter **663** is itself a balloon in fluid communication with boundary-forming balloon **588** (i.e. configured as a width-expandable wiping element).

In various examples described above, suctioning was restricted by slidable boundary to locations, within the interior of the tube. In some embodiments, concurrent with the maintaining of the slidable boundary, there is no suctioning carried out distal to the slidable boundary and/or only a "small" amount of suction relative to the suctioning of material from proximal locations **774** via suctioning orifice(s) **440**. For example, a ratio between the 'suctioning flow' rate of material from the distal locations **778** to the 'suctioning flow' rate of material from the proximal **774** locations may be at most 0.25 or at most 0.2 or at most 0.1 or at most 0.05.

One feature provided by some embodiments is that when boundary-forming balloon **588** is inflated so that boundary is maintained, there is little or no suction/negative pressure applied to locations **778** distal of the boundary. Not wishing to be bound by any theory, the inventors presently believe that application so such 'distal' suction while boundary is maintained may reduce an amount of air available to the patient and/or located in the patient's trachea precisely during the short period of time when the balloon **588**/boundary block air from the ventilator from reaching the patient's lungs.

FIGS. 26A-26C describes a manufacturing technique which, in some non-limiting embodiments, is useful to facilitating this feature. During an earlier stage of

manufacturing (FIG. 26A), suction lumen **520** and/or suction orifice(s) **440** is in fluid communication with a distal opening **519** which is located distal of the balloon mounting location **587** to which balloon **588** is mounted (for example, mounted at a later time). During a later stage of manufacturing, it is possible to completely (see FIG. 26B) or at least partially (see FIG. 26C) block this opening **519**. There is no limitation on how this may be accomplished –appropriate techniques include melting the lumen (e.g. near opening **519**) so as to close opening **519** or introduction of glue or any other foreign materials into **520** (e.g. near **519**). Blocking of **519** creates some sort of ‘blocking element’ or ‘blocking structure’ which partially or completely blocks opening **519**.

In some embodiments, after balloon **588** is inflated to create boundary, an interior of suction lumen **520** (e.g. at a ‘half-way’ location halfway between proximal **204** and distal **208** ends of main body **210** and/or at a location that is 3 cm or 5 cm or 10 cm proximal to balloon mounting location **587** or balloon **588**) and/or one or more or all of suction lumen(s) **440** (e.g. located proximal to balloon mounting location **587**) is not in substantially fluid communication with any location **778** outside of main body **210** and distal to boundary and/or is only in fluid communications with one or more opening(s) **519** whose total aggregate size is relatively ‘small’ relative to an aggregate size of suction port(s) **440** open to proximal locations **774** and/or located proximal to mounting location **587** or balloon **588**.

This, in exemplary embodiments, the device is configured, when sleeve **770** is maintained, to substantially restrict suction/negative pressure to proximal locations **774** – for example, at most 30% or at most 20% or at most 10% of a total negative pressure applied within an interior of tube **60** and/or applied via suction lumen **520** and/or via all suction lumen(s) **520** within or along main body **210** is applied to distal locations **778** – i.e. a significant majority or an entirety of the negative pressure is restricted (i.e. by the presence of inflatable balloon **588** which maintains the ‘obstructing boundary’) to proximal location(s) **774**.

In some embodiments, one or more of the suction orifice(s) **440** (e.g. proximal to mounting location **587** or balloon **588** or boundary and/or open to proximal locations **774**) (e.g. which is supplied or primarily supplied with negative pressure via suction

lumen(s) **520**) is in fluid communication, through suction lumen **520**, with a 'blocking element' or 'blocking structure' which partially or completely blocks opening **519**.

Some additional features (e.g. related to numerical parameters) are discussed in the present section. As with all features, they are intended as exemplary and not as limiting.

There is no limitations on the material from which any element (e.g. main body, lumen(s), orifice(s), balloon, etc) may be constructed. In non limiting embodiments, material used may include, but are not limited to biocompatible materials, polymer-based materials, plastics, silicone, polyurethane and latex. As the skilled artisan will appreciated after reading the present disclosure, other materials may be used.

In various embodiments (not limited to the embodiments of FIG. 4A or in any other figure), there is no particular limitation on the size of the fluid delivery orifice(s) **525** and/or suction **440** orifice(s).

In some embodiments, an average suction lumen(s) **520** width (e.g. averaged over a longitudinal direction) is between 2 and 5 mm. In some embodiments, an average fluid delivery lumen(s) **530** width (e.g. averaged over a longitudinal direction) is at most 0.75 or at most 0.5 or at most 0.25 or at most 0.2 or at most 0.15 or at most 0.1 times an average suction lumen(s) **520** width.

In some embodiments, an inner width of one or more of the fluid delivery orifice(s) **525**, or an average orifice inner width for any number (i.e. 2 or 3 or 4 or any other number) of fluid delivery orifice(s) **525** is at most 3 mm or at most 2 mm or at most 1 mm or at most 0.75 mm or at most 0.5 mm and/or at least 0.25 mm or at least 0.5 mm or at least 1 mm.

In some embodiments, an inner width of one or more of the suction orifice(s) **440**, or an average orifice inner width for any number (i.e. 2 or 3 or 4 or any other number) of suction orifice(s) **440** is at most 7 mm or at most 3 mm or at most 2 mm and/or at least 0.5 mm or at least 1 mm or at least 2 mm or at least 3 mm or at least 4 mm.

In some embodiments, an inner width of one or two or three or any number of fluid delivery orifice(s) **525** is at most 50% or at most 30% or at most 20% or at most 15% of an inner width of one or two or three or any number of suction orifice(s) **440**.

In some embodiments, one or more of the suction **440** and/or fluid delivery **525** orifice(s) is deployed at most 5 cm or at most 3 cm or at most 2 cm or at most 1 cm

proximal to a balloon mounting location **770** and/or an average or proximal location of boundary-forming balloon **588** and/or a location of boundary.

In some embodiments, an cross section of the suction lumen **530** exceeds a cross section of fluid delivery lumen **530** by a factor of at least 1.5 or a factor of at least 2 or a factor of at least 4 or a factor of at least 5 or a factor of between 6 and 15 or a factor of between 8 and 12.

It is now disclosed a ballooned cleaning device for use with an ETT or tracheostomy ventilation tube **60**, a ventilator machine **900**, a source(s) **602** of pressurized liquid and a source(s) of suctioning **603**, the cleaning device comprising:

- a. a tube-connector assembly **158** for connecting the ventilation tube **60** to the ventilator machine **900**, in a substantially air-tight manner;
- b. an elongate, flexible, main body **210** that is insertable through the tube-connector assembly **158** into the ventilation tube **60** to form an interstitial region outside of the main body **210** within ventilation tube **60**;
- c. a balloon **588** mounted to the main body **210** at a location in the distal half of the main body and inflatable into contact with an inner surface **201** of the ventilation tube **60**;
- d. one or more liquid-delivery lumen(s) **520** arranged within or along the elongated main body, and operative to transport pressurized liquid received from pressurized liquid source(s) outside of the ventilation tube **60**, into a proximal portion **774** of the interstitial region that is proximal of the balloon **588** so that the transported liquid enters the proximal portion **774** via liquid delivery orifice(s) **525** located on or mechanically coupled to the main body **210**;
- e. suction lumen(s) **530** arranged within or along the main body **210**, and operative to convey negative pressure from suction source(s) **603** predominantly into the proximal portion **774** of interstitial region via suction orifice(s) **440** when balloon **588** is inflated into contact, suction orifice(s) **440** being open to the proximal portion **774** and mechanically coupled to the main body **210**;
- f. a suction port **830** connectable to the suction source(s) **603** for mediating a connection between the suction source and the suction lumen(s); and

g. a pliable sleeve **610** around at least a portion of the main body **210** in locations proximal to the tube-connector assembly **158** and distal to the suction port **830** to inhibit contamination.

In some embodiments, at least one of the fluid delivery orifice(s) **525** is a void in the balloon **588** so that the balloon **588** is leaky.

In some embodiments, the inflatable balloon is operative to be inflated by pressurized fluid source via fluid delivery lumen(s) **520**.

In some embodiments,

- i. inflatable balloon **588** is a leaky balloon having one or more surface-located leak holes; and
- ii. one or more of the fluid delivery orifice(s) **525** are leak holes that face in a direction having a proximal component; and
- iii. inflatable balloon is operative to be inflated by pressurized fluid source via fluid delivery lumen(s) **520**.

In some embodiments,

- i. balloon **588** is a boundary-forming balloon which divides an interior of the ventilation tube into more proximate **774** and more distal **778** portions;
- ii. at least one of the at least one of the fluid delivery orifice(s) **525** is a void in the boundary-forming balloon **588** so that the boundary-forming balloon **588** is leaky;
- iii. forcing of pressurized liquid into the boundary-forming balloon **588** is operative both:

- A. to inflate boundary-forming balloon **588**;
- B. to cause the pressurized liquid to enter the proximal portion **774** via liquid delivery orifice(s) **525** located on or mechanically coupled to the main body **210**.

In some embodiments, the boundary-forming balloon **588** forms a seal between the proximate **774** and distal **778** portions of the interstitial region.

In some embodiments, the boundary-forming balloon **588** does not form a seal between the into proximate **774** and distal **778** portions of the interstitial region.

In some embodiments, the balloon **588** hinders and/or at least partially obstructs fluid communications between the more proximal and more distal portions.

It is now disclosed a cleaning device for use with an ETT or tracheostomy ventilation tube **60**, a ventilator machine **900**, a source(s) of fluid and a source(s) of suctioning **603**, the cleaning device comprising:

- a. a tube-connector assembly **158** for connecting the ventilation tube **60** to the ventilator machine **900**, in a substantially air-tight manner;
- b. an elongate, flexible, main body **210** that is insertable through the tube-connector assembly **158** into the ventilation tube **60** to form an interstitial region outside of the main body **210** within ventilation tube **60**;
- c. a balloon **588** mounted to the main body **210** at and inflatable into contact with an inner surface **201** of the ventilation tube **60**;
- d. one or more fluid delivery lumen(s) **520** arranged within or along the elongated main body, and operative to transport pressurized fluid received from pressurized fluid source(s) outside of the ventilation tube **60**, into a proximal portion **774** of the interstitial region that is proximal of the balloon **588** so that the transported fluid enters the proximal portion **774** via fluid delivery orifice(s) **525** located on or mechanically coupled to the main body **210**;
- e. suction lumen(s) **530** arranged within or along the main body, and operative to convey negative pressure from suction source(s) **603** predominantly into the proximal portion **774** of interstitial region via suction orifice(s) **440** when balloon **588** is inflated into contact, suction orifice(s) **440** being open to the proximal portion **774** and mechanically coupled to the main body **210**.
- f. a suction port **830** connectable to the suction source(s) **603** for mediating a connection between the suction source and the suction lumen(s); and
- g. a pliable sleeve **610** around at least a portion of the main body **210** in locations proximal to the tube-connector assembly **158** and distal to the suction port **830** to inhibit contamination.

It is now disclosed a ballooned cleaning device for use with an ETT or tracheostomy ventilation tube **60**, a ventilator machine **900**, a source(s) of fluid and a source(s) of suctioning **603**, the cleaning device comprising:

- a. a tube-connector assembly **158** for connecting the ventilation tube **60** to the

- ventilator machine **900**, in a substantially air-tight manner;
- b. an elongate, flexible, main body **210** that is insertable through the tube-connector assembly **158** into the ventilation tube **60** to form an interstitial region outside of the main body **210** within ventilation tube **60**;
 - c. a balloon **588** mounted to the main body **210** at and inflatable into contact with an inner surface **201** of the ventilation tube **60**;
 - d. one or more fluid delivery lumen(s) **520** arranged within or along the elongated main body, and operative to transport fluid received from fluid source(s) outside of the ventilation tube **60**, into a proximal portion **774** of the interstitial region that is proximal of the balloon **588** so that the transported fluid enters the proximal portion **774** via fluid delivery orifice(s) **525** located on or mechanically coupled to the main body **210**;
 - e. suction lumen(s) **530** arranged within or along the main body, and operative to convey negative pressure from suction source(s) **603** predominantly into the proximal portion **774** of interstitial region via suction orifice(s) **440** when balloon **588** is inflated into contact, suction orifice(s) **440** being open to the proximal portion **774** and mechanically coupled to the main body **210**.
 - f. a suction port **830** connectable to the suction source(s) **603** for mediating a connection between the suction source and the suction lumen(s); and
 - g. a pliable sleeve **610** around at least a portion of the main body **210** in locations proximal to the tube-connector assembly **158** and distal to the suction port **830** to inhibit contamination.

It is now disclosed a ballooned cleaning device for use with an ETT or tracheostomy ventilation tube **60**, a ventilator machine **900**, a source(s) of fluid and a source(s) of suctioning **603**, the cleaning device comprising:

- a. a tube-connector assembly **158** for connecting the ventilation tube **60** to the ventilator machine **900**, in a substantially air-tight manner;
- b. an elongate, flexible, main body **210** that is insertable through the tube-connector assembly **158** into the ventilation tube **60** to form an interstitial region outside of the main body **210** within ventilation tube **60**;

- c. a balloon **588** mounted to the main body **210** at a location inflatable into contact with an inner surface **201** of the ventilation tube **60**;
- d. suction lumen(s) **530** arranged within or along the main body, and operative to convey negative pressure from suction source(s) **603** predominantly into the proximal portion **774** of interstitial region via suction orifice(s) **440** when balloon **588** is inflated into contact, suction orifice(s) **440** being open to the proximal portion **774** and mechanically coupled to the main body **210**;
- e. a fluid delivery orifice(s) in fluid communication with a proximal portion **774** of the interstitial region that is proximal of the balloon **588** so that the fluid from the fluid source passing through the fluid delivery orifice enters the proximal portion **774**;
- f. a suction port **830** connectable to the suction source(s) **603** for mediating a connection between the suction source and the suction lumen(s); and
- g. a pliable sleeve **610** around at least a portion of the main body **210** in locations proximal to the tube-connector assembly **158** and distal to the suction port **830** to inhibit contamination.

It is now disclosed a ballooned cleaning device for use with an ETT or tracheostomy ventilation tube **60**, a ventilator machine **900**, and a source(s) of suctioning **603**, the cleaning device comprising:

- a. a tube-connector assembly **158** for connecting the ventilation tube **60** to the ventilator machine **900**, in a substantially air-tight manner;
- b. an elongate, flexible, main body **210** that is insertable through the tube-connector assembly **158** into the ventilation tube **60** to form an interstitial region outside of the main body **210** within ventilation tube **60**;
- c. a balloon **588** mounted to the main body **210** at a location inflatable into contact with an inner surface **201** of the ventilation tube **60**;
- d. suction lumen(s) **530** arranged within or along the main body, and operative to convey negative pressure from suction source(s) **603** predominantly into the proximal portion **774** of interstitial region via suction orifice(s) **440** when balloon

588 is inflated into contact, suction orifice(s) **440** being open to the proximal portion **774** and mechanically coupled to the main body **210**;

e. a suction port **830** connectable to the suction source(s) **603** for mediating a connection between the suction source and the suction lumen(s); and

f. a pliable sleeve **610** around at least a portion of the main body **210** in locations proximal to the tube-connector assembly **158** and distal to the suction port **830** to inhibit contamination.

It is now disclosed a ballooned cleaning device for use with an ETT or tracheostomy ventilation tube **60**, a ventilator machine **900**, a source(s) of fluid and a source(s) of suctioning **603**, the cleaning device comprising:

a. an elongate, flexible, main body **210** that into the ventilation tube **60** to form an interstitial region outside of the main body **210** within ventilation tube **60**;

b. an inflatable balloon **588** mounted to the main body **210** and inflatable when within the ventilation tube **60**;

c. one or more fluid delivery lumen(s) **520** arranged within or along the elongated main body, and operative to transport fluid received from fluid source(s) outside of the ventilation tube **60**, into a proximal portion **774** of the interstitial region that is proximal of the balloon **588** so that the transported fluid enters the proximal portion **774** via fluid delivery orifice(s) **525** located on or mechanically coupled to the main body **210**;

d. suction lumen(s) **530** arranged within or along the main body, and operative to convey negative pressure from suction source(s) **603** via suction orifice(s) **440** when balloon **588** is inflated into contact, suction orifice(s) **440** being open to the proximal portion **774** and mechanically coupled to the main body **210**.

It is now disclosed a ballooned cleaning device for use with an ETT or tracheostomy ventilation tube **60**, a ventilator machine **900**, a source(s) of fluid and a source(s) of suctioning **603**, the cleaning device comprising:

a. an elongate, flexible, main body **210** that into the ventilation tube **60** to form an interstitial region outside of the main body **210** within ventilation tube **60**;

b. an inflatable balloon **588** mounted to the main body **210** and inflatable towards an inner surface **201** the ventilation tube **60**;

c. a fluid delivery orifice(s) **525** in fluid communication with a proximal portion **774** of the interstitial region that is proximal of the balloon **588** so that the fluid from the fluid source passing through the fluid delivery orifice enters the proximal portion **774**;

d. suction lumen(s) **530** arranged within or along the main body, and operative to convey negative pressure from suction source(s) **603** via suction orifice(s) **440** when balloon **588** is inflated into contact, suction orifice(s) **440** being open to the proximal portion **774** and mechanically coupled to the main body **210**.

In some embodiments, the balloon **588** is inflatable into contact with an inner surface **201** of the ventilation tube **60**

In some embodiments, further comprising at least one of:

- i. a tube-connector assembly **158** for connecting the ventilation tube **60** to the ventilator machine **900**, in a substantially air-tight manner; and/or
- ii. a suction port **830** connectable to the suction source(s) **603** for mediating a connection between the suction source and the suction lumen(s).

In some embodiments, the main body is insertable through the tube-connector assembly **158** into the ventilation tube **60** and/or the fluid delivery orifice is located on or mechanically coupled to the main body **210**.

In some embodiments, further comprising a pliable sleeve **610** around at least a portion of the main body **210** in locations proximal to the tube-connector assembly **158** and distal to the suction port **830** to inhibit contamination.

In some embodiments, the balloon is fluid-inflatable, and the device is configured so that for a given fluid delivery lumen **520**, a first portion of fluid flowing through the given fluid delivery lumen enters into the proximal portion **774** after passing through fluid delivery orifice(s) **525**, and a second portion of fluid flowing through the given fluid delivery lumen inflates balloon **588**.

In some embodiments, balloon **588** is leaky and fluid delivery orifice(s) that is supplied by fluid via the given fluid delivery lumen **520** is located on a surface **589** of balloon **588**.

In some embodiments, the balloon **588** is sealed and fluid delivery orifice(s) that is supplied by fluid via the given fluid delivery lumen **520** is not located on a surface **589** of balloon **588**.

In some embodiments, fluid delivery orifice(s) that is supplied by fluid via the given fluid delivery lumen **520** is located proximal to balloon **588**.

It is now disclosed a cleaning device for use with an ETT or tracheostomy ventilation tube **60**, a ventilator machine **900**, a source(s) of fluid and a source(s) of suctioning **603**, the cleaning device comprising:

- a. a tube-connector assembly **158** for connecting the ventilation tube **60** to the ventilator machine **900**, in a substantially air-tight manner;
- b. an elongate, flexible, main body **210** that is insertable through the tube-connector assembly **158** into the ventilation tube **60** to form an interstitial region outside of the main body **210** within ventilation tube **60**;
- c. a width-expandable wiping element **588** mounted to the main body **210** and width-expandable in a direction perpendicular to an elongate axis of the main body **210** into contact with an inner surface **201** of the ventilation tube **60**;
- d. one or more fluid delivery lumen(s) **520** arranged within or along the elongated main body, and operative to transport fluid received from fluid source(s) outside of the ventilation tube **60**, into a proximal portion **774** of the interstitial region that is proximal of the wiping element **588** so that the transported fluid enters the proximal portion **774** via fluid delivery orifice(s) **525** located on or mechanically coupled to the main body **210**;
- e. suction lumen(s) **530** arranged within or along the main body, and operative to convey negative pressure from suction source(s) **603** predominantly into the proximal portion **774** of interstitial region via suction orifice(s) **440** when wiping element **588** is expanded into contact, suction orifice(s) **440** being open to the proximal portion **774** and mechanically coupled to the main body **210**;
- f. a suction port **830** connectable to the suction source(s) **603** for mediating a connection between the suction source and the suction lumen(s); and
- g. a pliable sleeve **610** around at least a portion of the main body **210** in locations proximal to the tube-connector assembly **158** and distal to the suction port **830** to inhibit contamination.

It is now disclosed a cleaning device for use with an ETT or tracheostomy ventilation tube **60**, a ventilator machine **900**, a source(s) of fluid and a source(s) of suctioning **603**, the cleaning device comprising:

- a. a tube-connector assembly **158** for connecting the ventilation tube **60** to the ventilator machine **900**, in a substantially air-tight manner;
- b. an elongate, flexible, main body **210** that is insertable through the tube-connector assembly **158** into the ventilation tube **60** to form an interstitial region outside of the main body **210** within ventilation tube **60**;
- c. a width-expandable wiping element **588** mounted to the main body **210** and width-expandable in a direction perpendicular to an elongate axis of the main body **210** into contact with an inner surface **201** of the ventilation tube **60**;
- d. suction lumen(s) **530** arranged within or along the main body, and operative to convey negative pressure from suction source(s) **603** predominantly into the proximal portion **774** of interstitial region via suction orifice(s) **440** when the width-expandable wiping element **588** is expanded into contact, suction orifice(s) **440** being open to the proximal portion **774** and mechanically coupled to the main body **210**;
- e. a fluid delivery orifice(s) in fluid communication with a proximal portion **774** of the interstitial region that is proximal of the wiping element **588** so that the fluid from the fluid source passing through the fluid delivery orifice enters the proximal portion **774**;
- f. a suction port **830** connectable to the suction source(s) **603** for mediating a connection between the suction source and the suction lumen(s); and
- g. a pliable sleeve **610** around at least a portion of the main body **210** in locations proximal to the tube-connector assembly **158** and distal to the suction port **830** to inhibit contamination.

It is now disclosed a cleaning device for use with an ETT or tracheostomy ventilation tube **60**, a ventilator machine **900**, a source(s) of fluid and a source(s) of suctioning **603**, the cleaning device comprising:

- a. a tube-connector assembly **158** for connecting the ventilation tube **60** to the ventilator machine **900**, in a substantially air-tight manner;

- b. an elongate, flexible, main body **210** that is insertable through the tube-connector assembly **158** into the ventilation tube **60** to form an interstitial region outside of the main body **210** within ventilation tube **60**;
- c. a width-expandable wiping element **588** mounted to the main body **210** and width-expandable in a direction perpendicular to an elongate axis of the main body **210** into contact with an inner surface **201** of the ventilation tube **60**;
- d. first **220** and second **240** fluid delivery lumen(s) arranged within or along the elongated main body, and operative to transport fluid, received respectively from first and second fluid source(s) outside of the ventilation tube **60**, into a proximal portion **774** of the interstitial region that is proximal of the wiping element **588** so that the:
 - (i) transported fluid from both fluid delivery lumen(s) enters the proximal portion **774** via a common fluid delivery orifice(s) **225** located on or mechanically coupled to the main body **210**; or
 - (ii) fluid respectively transported through the first **220A** and second **220B** fluid delivery lumen(s) respectively enters the proximal portion **774** via first **224** and second **244** orifices that are separated from each other by at most 5 mm and that are each located on or mechanically coupled to the main body **210**;
- e. suction lumen(s) **530** arranged within or along the main body, and operative to convey negative pressure from suction source(s) **603** predominantly into the proximal portion **774** of interstitial region via suction orifice(s) **440** when wiping element **588** is expanded into contact, suction orifice(s) **440** being open to the proximal portion **774** and mechanically coupled to the main body **210**;
- f. a suction port **830** connectable to the suction source(s) **603** for mediating a connection between the suction source and the suction lumen(s); and
- g. a pliable sleeve **610** around at least a portion of the main body **210** in locations proximal to the tube-connector assembly **158** and distal to the suction port **830** to inhibit contamination.

It is now disclosed a cleaning device for use with an ETT or tracheostomy ventilation tube **60**, a ventilator machine **900**, an array of fluid sources and a source(s) of suctioning **603**, the cleaning device comprising:

- a. a tube-connector assembly **158** for connecting the ventilation tube **60** to the ventilator machine **900**, in a substantially air-tight manner;
- b. an elongate, flexible, main body **210** that is insertable through the tube-connector assembly **158** into the ventilation tube **60** to form an interstitial region outside of the main body **210** within ventilation tube **60**;
- c. a width-expandable wiping element **588** mounted to the main body **210** and width-expandable in a direction perpendicular to an elongate axis of the main body **210** into contact with an inner surface **201** of the ventilation tube **60**;
- d. a mist formation assembly operative, when the main body **210** is inserted through the tube-connector assembly **158** into the ventilation tube **60**, to form a mist from a liquid-containing fluid and a gas-containing fluid so that the formed mist flows within a proximal portion **774** of the interstitial region that is proximal of the wiping element **588**
- e. suction lumen(s) **530** arranged within or along the main body, and operative to convey negative pressure from suction source(s) **603** predominantly into the proximal portion **774** of interstitial region via suction orifice(s) **440** when wiping element **588** is expanded into contact, suction orifice(s) **440** being open to the proximal portion **774** and mechanically coupled to the main body **210**;
- f. a suction port **830** connectable to the suction source(s) **603** for mediating a connection between the suction source and the suction lumen(s); and
- g. a pliable sleeve **610** around at least a portion of the main body **210** in locations proximal to the tube-connector assembly **158** and distal to the suction port **830** to inhibit contamination.

In some embodiments, the mist is formed within the proximal portion **774** of the interstitial region.

In some embodiments, the mist is formed within the main body **210**.

In some embodiments, when the main body is inserted through the tube-connector assembly **158** into the ventilation tube **60** to form the interstitial region, the mist is formed within the main body in location(s) within ventilation tube **60**.

In some embodiments, the device is configured so that the mist enters the proximal portion **774** of the interstitial region via a fluid delivery orifice(s) open thereto, the fluid delivery orifice(s) being mechanically coupled to main body **210**.

In some embodiments, the mist formation assembly includes first and second fluid-delivery lumen(s) arranged within or along the elongated main body and respectively operative to receive and transport the liquid-containing and gas-containing fluids.

In some embodiments, the mist formation assembly includes a common orifice via which material transported within the first and second fluid-delivery lumen(s) enters into the proximal portion **774** of the interstitial region.

In some embodiments, the first and second fluid-delivery lumen(s) merge within main body **210** at a merge or mixing location **522**.

In some embodiments, wherein the mist is formed as fluid(s) flow from the merge location to or through a fluid delivery orifice, mechanically coupled to main body **210** and open to the proximal portion **774** of the interstitial region.

In some embodiments, the first **224** and second **244** orifices are separated from each other by at most 4 mm or at most 3 mm or at most 2 mm or at most 1 mm.

It is now disclosed a cleaning device for use with an ETT or tracheostomy ventilation tube **60**, a ventilator machine **900**, a source(s) of fluid and a source(s) of suctioning **603**, the cleaning device comprising:

- a. an elongate, flexible, main body **210** that into the ventilation tube **60** to form an interstitial region outside of the main body **210** within ventilation tube **60**;
- b. a width-expandable wiping element **588** mounted to the main body **210** and width-expandable in a direction perpendicular to an elongate axis of the main body **210**;
- c. one or more fluid delivery lumen(s) **520** arranged within or along the elongated main body, and operative to transport fluid received from fluid source(s) outside of the ventilation tube **60**, into a proximal portion **774** of the interstitial region that

is proximal of the wiping element **588** so that the transported fluid enters the proximal portion **774** via fluid delivery orifice(s) **525**;

d. suction lumen(s) **530** arranged within or along the main body, and operative to convey negative pressure from suction source(s) **603** via suction orifice(s) **440** when wiping element **588** is expanded into contact, suction orifice(s) **440** being open to the proximal portion **774** and mechanically coupled to the main body **210**.

It is now disclosed a cleaning device for use with an ETT or tracheostomy ventilation tube **60**, a ventilator machine **900**, a source(s) of fluid and a source(s) of suctioning **603**, the cleaning device comprising:

- a. an elongate, flexible, main body **210** that into the ventilation tube **60** to form an interstitial region outside of the main body **210** within ventilation tube **60**;
- b. a width-expandable wiping element **588** mounted to the main body **210** and width-expandable in a direction perpendicular to an elongate axis of the main body **210**;
- c. a fluid delivery orifice(s) **525** in fluid communication with a proximal portion **774** of the interstitial region that is proximal of the wiping element **588** so that the fluid from the fluid source passing through the fluid delivery orifice enters the proximal portion **774**;
- d. suction lumen(s) **530** arranged within or along the main body, and operative to convey negative pressure from suction source(s) **603** via suction orifice(s) **440** when wiping element **588** is expanded into contact, suction orifice(s) **440** being open to the proximal portion **774** and mechanically coupled to the main body **210**.

In some embodiments, the width-expandable wiping element **588** is expandable into contact with an inner surface **201** of the ventilation tube **60**

In some embodiments, further comprising at least one of:

- i. a tube-connector assembly **158** for connecting the ventilation tube **60** to the ventilator machine **900**, in a substantially air-tight manner; and/or
- ii. a suction port **830** connectable to the suction source(s) **603** for mediating a connection between the suction source and the suction lumen(s).

In some embodiments, the main body is insertable through the tube-connector assembly **158** into the ventilation tube **60** and/or the fluid delivery orifice is located on or mechanically coupled to the main body **210**.

In some embodiments, further comprising a pliable sleeve **610** around at least a portion of the main body **210** in locations proximal to the tube-connector assembly **158** and distal to the suction port **830** to inhibit contamination.

In some embodiments, the width-expandable wiping element is an inflatable object that width-expands upon inflation.

In some embodiments, the width-expandable wiping element is a balloon that width-expands upon inflation.

In some embodiments, the balloon **588** is inflatable via a balloon lumen **580** along or within main body **210**.

In some embodiments, the balloon **588** is inflatable via one of the fluid delivery lumen(s) **520** along or within main body **210**.

In some embodiments, the width-expandable wiping element is expands by a mechanism other than inflation.

In some embodiments, the width-expandable wiping element includes an outwardly biased element.

In some embodiments, the width-expandable wiping element includes an outwardly-biased shape memory device.

In some embodiments, when in an expanded configuration, the outwardly-biased shape memory is shaped as a spiral.

In some embodiments, when in the expanded configuration, the outwardly-biased shape memory is pre-shaped as a spiral having a central axis that is substantially parallel to an elongate axis of the main body **210**.

In some embodiments, the outwardly biased element is a stent.

In some embodiments, the width-expandable wiping element is not outwardly biased.

In some embodiments, the width-expandable wiping element includes a rigid skeleton having a multiple configuration.

In some embodiments, a width ratio between:

- i. an expanded-configuration width of the width-expandable wiping element;
 - and
 - ii. a contracted-configuration width of the width-expandable wiping element
- is at least 1.5.

In some embodiments, a contracted-configuration width of the width-expandable wiping element is at most one-half of an inner diameter of the ventilation tube **60**.

In some embodiments, a contracted-configuration width of the width-expandable wiping element is at most one-third of an inner diameter of the ventilation tube **60**.

In some embodiments inflatable balloon **588** and fluid delivery orifice **525** are supplied by a common fluid supply.

In some embodiments, inflatable balloon **588** and fluid delivery orifice **525** are supplied by a common fluid supply via a common fluid delivery lumen **520**.

In some embodiments, inflatable balloon **588** and fluid delivery orifice **525** are supplied by a common fluid supply respectively via first **520A** and second **520B** fluid delivery lumen.

In some embodiments, balloon **588** or swiping element **588** are mounted to the main body **210** in a distal half thereof.

It is now disclosed a system comprising:

- any device described herein; and
- source(s) of pressurized liquid **602**, the device and liquid source configured, when the main body **210** is inserted within the ventilation tube **60**, such that the pressurized liquid received from the fluid(s) source or a derivative thereof enters proximal portion **774** after passing through fluid delivery orifice(s).

It is now disclosed a system comprising:

- any device described herein; and

source(s) of liquid **602**, the device and liquid source configured, when the main body **210** is inserted within the ventilation tube **60**, such that the liquid received from the fluid(s) source or a derivative thereof enters proximal portion **774** after passing through fluid delivery orifice(s).

It is now disclosed a system comprising:

any device described herein; and

source(s) of pressurized fluid **602**, the device and fluid source configured, when the main body **210** is inserted within the ventilation tube **60**, such that the pressurized fluid received from the fluid(s) source or a derivative thereof enters proximal portion **774** after passing through fluid delivery orifice(s).

It is now disclosed a system comprising:

any device described herein; and

source(s) of fluid **602**, the device and liquid source configured, when the main body **210** is inserted within the ventilation tube **60**, such that the fluid received from the fluid(s) source or a derivative thereof enters proximal portion **774** after passing through fluid delivery orifice(s).

In some embodiments, the fluid(s) source includes a source of unpressurized fluid.

In some embodiments, a mist is formed from a liquid-containing source and a gas containing source within main body **210** and is delivered into proximal portion **774**.

In some embodiments, a mist is formed from a liquid-containing source and a gas containing source upon entry into proximal portion **774**.

It is now disclosed a method comprising employing any device or system disclosed herein to clean biofilm from the inner surface **201** of the ventilation tube.

It is now disclosed a method comprising employing any device or system disclosed herein to prevent accumulation or hinder accumulation of biofilm from the inner surface **201** of the ventilation tube.

It is now disclosed a method of cleaning a main lumen of an ETT or tracheostomy ventilation tube **60** and/or hindering accumulation of biofilm on an inner surface of ventilation tube **60**, the method comprising:

at a time when:

- i. a ventilation machine **900** is connected to the ventilation tube **60** via a tube connector assembly **158** in a substantially air-tight manner;
- ii. an elongate, flexible, main body **210** traverses an interior of the tube connector assembly **158** so that a distal end of the main body **210** is located within the ventilation tube **60** to form an interstitial region outside of the main body **210** and within the ventilator tube;
- iii. an inflatable balloon **588** mounted to the main body **210** is located within the ventilation tube **60**;
- iv. sources of fluid **602** and suction **603** are respectively in fluid communication with fluid delivery orifice(s) **525** and suction orifice(s) **440**, the suction **440** orifice(s) being located proximal to balloon **588** within ventilation tube **60** and on main body **210** or mechanically coupled to main body **210**,

carrying out the following:

inflating the balloon **588** outwardly towards an inner surface **201** of the ventilation tube **60** and/or into contact with the inner surface **201** of the ventilation tube **60** so that both suction **440** and fluid delivery **525** orifice(s) are in fluid communication to a proximal portion **774** of the interstitial region that is proximal to inflatable balloon **588**;

concurrent with a maintaining the balloon in an inflated state, conveying negative pressure from the suction source(s) **603**, via the suction lumen(s) **530** and orifice(s) **440**, predominantly into the proximal portion **774** of the interstitial region; and

concurrent with a maintaining of the balloon in the inflated state, sending fluid from the fluid source(s) **602** through the fluid delivery orifice(s) **525** into the interstitial region proximal portion **774**.

It is now disclosed a method of cleaning a main lumen of an ETT or tracheostomy ventilation tube **60** and/or hindering accumulation of biofilm on an inner surface of ventilation tube **60**, the method comprising:

at a time when:

- i. a ventilation machine **900** is connected to the ventilation tube **60** via a tube connector assembly **158** in a substantially air-tight manner;
- ii. an elongate, flexible, main body **210** traverses an interior of the tube connector assembly **158** so that a distal end of the main body **210** is located within the ventilation tube **60** to form an interstitial region outside of the main body **210** and within the ventilator tube;
- iii. an inflatable balloon **588** mounted to the main body **210** is located within the ventilation tube **60**;
- iv. sources of fluid **602** and suction **603** are respectively in fluid communication with fluid delivery orifice(s) **525** and suction orifice(s) **440**, the suction **440** orifice(s) being located proximal to balloon **588** within ventilation tube **60** and on main body **210** or mechanically coupled to main body **210**,

carrying out the following:

inflating the balloon **588** into contact with the inner surface **201** of the ventilation tube **60** so that both suction **440** and fluid delivery **525** orifice(s) are in fluid communication to a proximal portion **774** of the interstitial region that is proximal to inflatable balloon **588**;

concurrent with a maintaining the balloon inflated into contact, conveying negative pressure from the suction source(s) **603**, via the suction lumen(s) **530** and orifice(s) **440**, predominantly into the proximal portion **774** of the interstitial region; and

concurrent with a maintaining of the balloon inflated into contact, sending fluid from the fluid source(s) **602** through the fluid delivery orifice(s) **525** into the interstitial region proximal portion **774**.

It is now disclosed a method of cleaning a main lumen of an ETT or tracheostomy ventilation tube **60** and/or hindering accumulation of biofilm on an inner surface of ventilation tube **60**, the method comprising:

at a time when:

- i. a ventilation machine **900** is connected to the ventilation tube **60** via a tube connector assembly **158** in a substantially air-tight manner;
- ii. an elongate, flexible, main body **210** traverses an interior of the tube connector assembly **158** so that a distal end of the main body **210** is located within the ventilation tube **60** to form an interstitial region outside of the main body **210** and within the ventilator tube;
- iii. a width-expandable wiping element **588** mounted to the main body **210** is located within the ventilation tube **60**;
- iv. sources of fluid **602** and suction **603** are and are respectively in fluid communication with fluid delivery orifice(s) **525** and suction orifice(s) **440**, the suction **440** orifice(s) being located proximal to wiping element **588** within ventilation tube **60** and on main body **210** or mechanically coupled to main body **210**,

carrying out the following:

expanding the mounted width-expandable wiping element **588** towards an inner surface **201** of the ventilation tube **60** so that both suction **440** and fluid delivery **525** orifice(s) are in fluid communication to a proximal portion **774** of the interstitial region that is proximal to width-expanded wiping element **588**;

concurrent with a maintaining of the width-expanded wiping element **588** in the width-expanded state, conveying negative pressure from the suction source(s) **603**, via the suction lumen(s) **530** and orifice(s) **440**, predominantly into the proximal portion **774** of the interstitial region; and

concurrent with a maintaining of the width-expanded wiping element **588** in the width-expanded state, sending fluid from the fluid source(s) **602** through the fluid delivery orifice(s) **525** into the interstitial region proximal portion **774**.

It is now disclosed a method of cleaning a main lumen of an ETT or tracheostomy ventilation tube **60** and/or hindering accumulation of biofilm on an inner surface of ventilation tube **60**, the method comprising:

at a time when:

- i. a ventilation machine **900** is connected to the ventilation tube **60** via a tube connector assembly **158** in a substantially air-tight manner;
- ii. an elongate, flexible, main body **210** traverses an interior of the tube connector assembly **158** so that a distal end of the main body **210** is located within the ventilation tube **60** to form an interstitial region outside of the main body **210** and within the ventilator tube;
- iii. a width-expandable wiping element **588** mounted to the main body **210** is located within the ventilation tube **60**;
- iv. sources of fluid **602** and suction **603** are and are respectively in fluid communication with fluid delivery orifice(s) **525** and suction orifice(s) **440**, the suction **440** orifice(s) being located proximal to wiping element **588** within ventilation tube **60** and on main body **210** or mechanically coupled to main body **210**,

carrying out the following:

- a. expanding the mounted width-expandable wiping element **588** into contact with an inner surface **201** of the ventilation tube **60** so that both suction **440** and fluid delivery **525** orifice(s) are in fluid
- b. communication to a proximal portion **774** of the interstitial region that is proximal to width-expanded wiping element **588**;

concurrent with a maintaining of the contact by the width-expanded wiping element **588**, conveying negative pressure from the suction source(s) **603**, via the suction lumen(s) **530** and orifice(s) **440**, predominantly into the proximal portion **774** of the interstitial region; and

c. concurrent with a maintaining of the contact by the width-expanded wiping element **588**, sending fluid from the fluid source(s) **602** through the fluid delivery orifice(s) **525** into the interstitial region proximal portion **774**.

In some embodiments, the suction source and/or the source of fluid(s) are located outside of ventilation tube **60**.

In some embodiments, further comprising moving the expanded wiping element or inflated balloon in a longitudinal direction so as to wipe material from the inner surface of ventilation tube **60** and/or to hinder accumulation of biofilm thereon.

In some embodiments, the fluid which enters the proximal portion **774** includes a liquid.

In some embodiments, the fluid which enters the proximal portion **774** includes a mist.

In some embodiments, the fluid is sent into the interstitial region proximal portion **774** so that a liquid-containing stream of fluid flows therein, the fluid stream being sustained so that a liquid fraction thereof flows at a flow rate of at least x cc/second for at least y seconds, a value of x being at least 0.25 cc/second and a value of y being at least y seconds.

In some embodiments, x is at least 0.5 cc/second or at least 1 cc/second and/or at most 10 cc/second or at most 5 cc/second.

In some embodiments, carried out to deliver a mist into proximal region **774**.

In some embodiments, carried out to form a mist within ventilation tube **60** which is formed within and/or delivered to proximal region **774**.

In some embodiments, fluid cannot be delivered into proximal portion **774** when the balloon is not in contact with the inner surface **201** of ventilation tube **60** and/or is in an uninflated state.

In some embodiments, fluid cannot be delivered into proximal portion **774** when the width-expandable wiping element is not in contact with the inner surface **201** of ventilation tube **60** and/or is in an unexpanded state.

In some embodiments, an inner surface of the ventilation tube is cleaned within 15 second.

It is now disclosed a method of cleaning a main lumen of an ETT or tracheostomy ventilation tube **60** comprising:

at a time when:

- i. a ventilation machine **900** is connected to the ventilation tube **60** via a tube connector assembly **158** in a substantially air-tight manner;
- ii. an elongate, flexible, main body **210** traverses an interior of the tube connector assembly **158** so that a distal end of the main body **210** is located within the ventilation tube **60** to form an interstitial region outside of the main body **210** and within the ventilator tube;
- iii. a balloon **588** mounted to the main body **210** is located within the ventilation tube **60**;
- iv. sources of pressurized fluid and/or suction **603** are:
 - A. any of which or both of which located in a tube-connector-assembly-proximal location outside of the ventilation tube **60** and proximal to tube connector assembly **158**; and
 - B. are respectively in fluid communication with fluid delivery orifice(s) **525** and suction orifice(s) **440** via fluid delivery lumen(s) **520** and suction lumen(s) **530**,

each of the suction **440** and fluid delivery **525** orifice(s) being:

- A. located proximal to balloon **588** within ventilation tube **60**, and
- B. on main body **210** or mechanically coupled to main body **210**,

carrying out the following steps:

- a. inflating the balloon **588** mounted to the main body **210** into contact with an inner surface **201** of the ventilation tube **60** so that both suction **440** and fluid delivery **525** orifice(s) are open to a proximal portion **774** of the interstitial region that is proximal to balloon **588**;
- b. concurrent with a maintaining of the contact by the balloon **588**, forcing pressurized fluid from the pressurized fluid source(s) **602** through the fluid delivery lumen(s) **520** and orifice(s) **525**, into the interstitial region proximal portion **774**;

- c. concurrent with a maintaining of the contact by the balloon **588**, conveying negative pressure from the suction source(s) **603**, via the suction lumen(s) **530** and orifice(s) **440**, predominantly into the proximal portion **774** of the interstitial region.

It is now disclosed a ballooned cleaning device for use with an ETT or tracheostomy ventilation tube **60**, a ventilator machine **900**, a source(s) of fluid (e.g. pressurized) and a source(s) of suctioning **603**, the cleaning device comprising:

- a. a tube-connector assembly **158** for connecting the ventilation tube **60** to the ventilator machine **900**, in a substantially air-tight manner;
- b. an elongate, flexible, main body **210** that is insertable through the tube-connector assembly **158** into the ventilation tube **60** to form an interstitial region outside of the main body **210** within ventilation tube **60**;
- c. a balloon **588** mounted to the main body **210** at a location (for example in the distal half of the main body) and inflatable into contact with an inner surface **201** of the ventilation tube **60**;
- d. one or more fluid delivery lumen(s) **520** arranged within or along the elongated main body, and operative to transport pressurized fluid received from pressurized fluid source(s) outside of the ventilation tube **60**, into a proximal portion **774** of the interstitial region that is proximal of the balloon **588** so that the transported fluid enters the proximal portion **774** via fluid delivery orifice(s) **525** located on or mechanically coupled to the main body **210**;
- e. suction lumen(s) **520** arranged within or along the main body, and operative to convey negative pressure from suction source(s) **603** predominantly into the proximal portion **774** of interstitial region via suction orifice(s) **440** when balloon **588** is inflated into contact, suction orifice(s) **440** being open to the proximal portion **774** and mechanically coupled to the main body **210**.
- f. a suction port **820** connectable to the suction source(s) **603** for mediating a connection between the suction source and the suction lumen(s); and
- g. a pliable sleeve **610** around at least a portion of the main body **210** in locations proximal to the tube-connector assembly **158** and distal to the suction port **820** to inhibit contamination.

In some embodiments, the balloon **588** is inflated by liquid or gas supplied by balloon fluid source that is located in the tube-assembly-proximal location.

In some embodiments, balloon **588** is supplied via a balloon lumen(s) **580** that is different from fluid delivery lumen(s) **520**.

In some embodiments, balloon **588** is inflated by gas or by a liquid.

In some embodiments, the fluid delivered via orifice(s) **525** and/or sent through fluid delivery lumen(s) **520** is a liquid and/or a liquid-gas mixture (e.g. a mist or bubbled fluid).

In some embodiments, balloon **588** is inflated by fluid (e.g. liquid and/or liquid-gas mixture) delivered via fluid delivery lumen(s) **520**.

In some embodiments, a length of the pliable sleeve **610** is at least 5 cm.

In some embodiments, the method is carried out when the suction orifice(s) and/or the fluid delivery are located closer to balloon **588** than to a proximal end **62** of ventilation tube **60**.

In some embodiments, the method is carried out at a time when a pliable sleeve **610** is arranged around at least a portion of the main body **210** in locations **598** proximal to the tube-connector assembly **158**.

In some embodiments, the method is carried out at a time when a pliable sleeve **610** is arranged around at least a portion of the main body **210** in locations **598** proximal to the tube-connector assembly and distal to a suction port **820** which mediates a connection between suction source(s) **603** and suction lumen(s) **520**.

In some embodiments, the one or more suction orifice(s) is(are) longitudinally displaced from the balloon **588** by at most a suction-orifice-displacement-value that is at most 3 cm or at most 2 cm or at most 1 cm.

In some embodiments,

- i. the pressurized fluid is simultaneously forced through first **525A** and second **525B** fluid delivery orifices to respectively produce first **556A** and second **556B** fluid streams that are respectively and simultaneously incident upon an inner surface **201** of the ventilation tube **60** at first **552A** and second **552B** locations; and
- ii. the first **552A** and second **552B** locations are substantially on opposite sides of the ventilation tube **60** inner surface **201** within a tolerance that is at most 75 degrees or at most 45 degrees or at most 25 degrees.

In some embodiments, at least one fluid-delivery-orifice **525** is proximally displaced from the slidable boundary by at most a fluid-orifice-displacement-value that is at most 3 cm, or at most 2 cm or at most 1 cm.

In some embodiments, the first **525A** and second **525B** fluid delivery orifices are respectively supplied via first **520A** and second **520B** fluid-delivery lumens.

In some embodiments, the first **520A** and second **520B** second fluid delivery lumens are simultaneously supplied by a common pressurized fluid chamber (e.g. a chamber mixing apparatus **696** of any other chamber).

In some embodiments, immediately before exiting each fluid delivery port **525**, the delivered fluid is pressurized to at least 1.5 atmospheres, or at least 2 atmospheres or at least 3 atmospheres.

In some embodiments, each fluid delivery orifice **525** has a width of at most 5 mm, at most 3 mm, or at most 2 mm, or at most 0.5mm, at most 0.3mm, at most 0.2mm.

In some embodiments, each fluid delivery orifice **525** has width that is at most 50%, or at most 25% or at most 10%, or at most 5%, of an average width of the **440** suction orifice(s).

In some embodiments, the suction-orifice-displacement-value is at most 2 cm, or at most 1 cm or at most 0.5 cm.

In some embodiments, the ventilation tube **60** is an ETT.

In some embodiments, the ventilation tube **60** is a tracheostomy tube.

In some embodiments, the fluid delivery operation and the suctioning are carried out simultaneously.

In some embodiments, the fluid delivery operation and the suctioning are carried out sequentially.

In some embodiments, concurrent to the maintaining of the slidable boundary, longitudinally moving

the boundary-forming balloon **588** so as to mechanically dislodge and/or loosen biofilm material located on the inner surface **201** of the ventilation tube **60**.

In some embodiments, the longitudinal moving is carried out simultaneously with the fluid delivery operation and/or the suctioning.

In some embodiments, at least one of the fluid delivery orifice(s) **525** are deployed to and/or voids within a second balloon **586** deployed distal to the boundary-forming balloon **588**.

In some embodiments, the second balloon **586** is inflatable.

In some embodiments, the second balloon **586** is not inflatable.

In some embodiments, at least one of the at least one of the fluid delivery orifice(s) **525** is an inner-surface-facing void in the main body **210** facing towards the inner surface **201** of the ventilation tube **60** or a inner-surface-facing-void in a fluid-delivery lumen **520** that at least spans a longitudinal range between the fluid delivery orifice(s) **525** and a location on or within the main body **210** that is proximal to the ventilation tube connector assembly **158**.

- In some embodiments, i. at least one of the at least one of the fluid delivery orifice(s) **525** is a void in the boundary-forming balloon **588** so that the boundary-forming balloon **588** is leaky;
- ii. forcing of pressurized fluid into the boundary-forming balloon **588** is operative to carry out at least some of both of the balloon-inflation operation and the fluid-delivery of the fluid-delivery operation.

In some embodiments, a surface of the boundary-forming balloon **588** is at least 90% or at least , by surface area, substantially impermeable.

In some embodiments, a surface of the boundary-forming balloon **588** is at most 99%, by surface area, substantially impermeable.

In some embodiments, boundary-forming **588** balloon is substantially sealed and is not leaky.

In some embodiments, further comprising carrying out the additional step of:

- D. concurrent with the maintaining of the ventilation circuit, and at a time that the boundary-forming balloon **588** mounted to the elongate, flexible main body **210** is located within the ventilation tube **60** and in a non-obstructing mode so that the slidable boundary with the inner surface **201** of the ventilation tube **60**

is not maintained and/or in non-contact mode so that balloon **588** is not inflated into contact with the inner surface **201** of ventilation tube **60**, proximally suctioning into the suction orifice(s) **440** material that is located:

- I. within the ventilation tube **60** and distal to the boundary-forming balloon **588**; and/or
- II. distal to the ventilation tube distal end **60** so that the material located distal to the ventilation tube distal end **60** enters an interior region of ventilation tube **60** *en route* to the suction orifice(s),

wherein the suctioning step when the boundary-forming balloon **588** is in non-obstructing and/or non-contact mode is carried out to proximally transport material suctioned in step D proximally out of ventilation tube **60** via a proximal opening of the ventilation tube **60**.

In some embodiments, the balloon is mounted to the main body **210** at a location in a distal half, or distal third, or distal quarter, or distal fifth or distal tenth of the main body **210**.

In some embodiments, an inner diameter of ventilation tube **60** is at least 4 mm and/or at most 11 mm.

In some embodiments, the pressurized fluid source **602** and the suction source **603** are respectively operative, in combination with the lumens and the orifices, to effect the fluid delivery and the suctioning when the boundary-forming balloon **588** is located in a distal half of the ventilation tube **60** and/or the system lacks suction orifice(s) more distal than the balloon **588**.

In some embodiments, the system lacks suction orifice(s) more distal than the balloon **588** and/or distal to boundary and in fluid communication with suction source **603**.

In some embodiments, the combined total aperture area of any and all suction orifices more distal than the balloon **588** and/or open to distal locations **778** is at most 50%, or at

most 40%, or at most 30%, or at most 20%, or at most 10% of the combined total aperture area of any and all suction orifices **440** proximal to the balloon **558** and/or open to proximal location(s) **774**.

In some embodiments, the combined total aperture area of any and all suction orifices in fluid communication with suction source **603** and more distal than the balloon **588** and/or open to distal locations **778** is at most 50%, or at most 40%, or at most 30%, or at most 20%, or at most 10% of the combined total aperture area of any and all suction orifices **440** in fluid communication with suction source **603** and proximal to the balloon **558** and/or open to proximal location(s) **774**.

In some embodiments, further comprising: a sleeve **610** operative to envelop and/or cover at least 5 cm of the elongate flexible main body **210**.

In some embodiments, wherein a distal end of the sleeve **610** is directly or indirectly attached to ventilation tube connector assembly **158** so that the main body **210** may slide through the sleeve.

In some embodiments, a proximal end of sleeve **610** is configured to have a substantially fixed longitudinal position relative to a proximal end of elongate flexible main body **210**.

In some embodiments, the system lacks suction orifice(s) more distal than the balloon **558** and/or distal to boundary.

In some embodiments, the system lacks suction orifice(s) more distal than the balloon **558** and/or distal to boundary and in fluid communication with suction source **603**.

In some embodiments, wherein the combined total aperture area of any and all suction orifices more distal than the balloon **588** and/or open to distal locations **778** is at most 50%, or at most 40%, or at most 30%, or at most 20%, or at most 10% of the combined total aperture area of any and all suction orifices **440** proximal to the balloon **558** and/or open to proximal location(s) **774**.

In some embodiments, the combined total aperture area of any and all suction orifices in fluid communication with suction source **603** and more distal than the balloon **588** and/or open to distal locations **778** is at most 50%, or at most 40%, or at most 30%, or at most 20%, or at most 10% of the combined total aperture area of any and all suction orifices

440 in fluid communication with suction source **603** and proximal to the balloon **558** and/or open to proximal location(s) **774**.

In some embodiments, wherein at least one of the suction orifice(s) **440** is in fluid communication, via suction lumen **520**, with a blocking construct or blocking element that is distal of at least one suction orifice **440** and that is configured to mostly or completely block fluid communication with a distal opening **519**. 132. The device, system or method of any of preceding claim wherein the blocking construct or blocking element comprises a blocking glue or other material introduced onto or into suction lumen **520** and/or comprises a melt construct of a melted inner wall(s) of suction lumen(s) **520**.

In some embodiments, the system is operative such that:

- i. the pressurized fluid is simultaneously forced through first **525A** and second **525B** fluid delivery orifices to respectively produce first **556A** and second **556B** fluid streams that are respectively and simultaneously incident upon an inner surface **201** of the ventilation tube **60** at first **552A** and second **552B** locations; and
- ii. the first **552A** and second **552B** locations are substantially on opposite sides of the ventilation tube **60** inner surface **201** within a tolerance that is at most 75 degrees.

In some embodiments, the system or apparatus comprises a plurality of fluid delivery orifices **525** including:

- i. a first fluid delivery orifice **525A** deployed to a first side of the elongate main body **210**; and
- ii. a second fluid delivery orifice **525B** deployed substantially to a second side of the elongate main body **210** that is on opposite side of main body central axis **202** within a tolerance that is at most 75 degrees or at most 45 degrees or at most 25 degrees.

In some embodiments, the system or apparatus comprises first **525A** and second **525B** fluid delivery orifice(s) which are operative such that:

- i. when an inner diameter of ventilation tube **60** is between 4 and 11 mm and exceeds an outer diameter of main body **210**,

- ii. when the main body **210** traverses the ventilation tube connector **158** so as to enter the ventilation tube;
- iii. when the boundary-forming balloon **588** is inflated so as to maintain the boundary; and
- iv. when the pressurized fluid is simultaneously forced, via fluid delivery lumen(s) **530** through first **525A** and second **525B** fluid delivery orifice,

to respectively produce first **556A** and second **556B** fluid streams that are respectively and simultaneously incident upon an inner surface **201** of the ventilation tube **60** at first **552A** and second **552B** locations such that the first **552A** and second **552B** locations are substantially on opposite sides of the ventilation tube **60** inner surface **201** within a tolerance that is at most 75 degrees or at most 45 degrees or at most 25 degrees.

In some embodiments, at least one fluid-delivery-orifice **525** is proximally displaced from the slidable boundary by at most a fluid-orifice-displacement-value that is at most 3 cm, or at most 2 cm.

In some embodiments, the first **520A** and second **520B** fluid second fluid delivery lumens are simultaneously supplied by a common pressurized fluid chamber.

In some embodiments, immediately before exiting each fluid delivery port **525**, the delivered fluid is pressurized to at least 1.5 atmospheres, or at least 2 atmospheres or at least 3 atmospheres.

In some embodiments, one or more fluid delivery orifice **525**, or a majority of the fluid delivery orifice(s) **525**, has a width of at most 3 mm, or at most 2 mm or at most 1 mm, or at most 0.5mm, at most 0.3mm, at most 0.2mm and/or that is at most 50% or at most 25% or at most 10% or at most 5% of an average width of the **440** suction orifice(s).

In some embodiments, the suction-orifice-displacement-value is at most 2 cm, or at most 1 cm or at most 0.5 cm.

In some embodiments, the main body **210** is operative to slidably, snugly and/or internally traverse the connector assembly **158**.

In some embodiments, i. negative pressure from suction source(s) **603** induces air flow within the

interstitial region; and

ii. the cleaning device provides a mode whereby a maximum rate of the

induced air flow within a distal portion **778** of the interstitial region distal to the inflatable balloon **588** is at most 20% of a maximum rate of the induced air flow in the proximal portion **774**.

In some embodiments, all suction lumen(s) are collectively not in fluid communication with any suction orifice located distal to balloon **588**.

In some embodiments,

- i. collectively all suction lumen(s) of the cleaning device are in fluid communication with one or more proximal suction orifice(s) located proximal to balloon **588** and one or more distal orifice(s) located distal to balloon **588**; and
- ii. a ratio between an aggregate surface area of all proximal suction orifice(s) **440** to an aggregate surface area of all distal suction orifice(s) is at least *SURF_AREA_RAT*;
- iii. a value of *SURF_AREA_RAT* is at least 1.5.

Although various embodiments were describe with respect to assembled systems, it is appreciate that kits including one or more parts which, when assembled, form any presently disclosed apparatus or device or portion thereof are also in the scope of the invention. In different non-limiting examples, connector assembly **158** and/or input module assembly **156** and/or any port disclosed herein may be provided as parts which may be assembled on-site (e.g. in the intensive care ward). In some examples, sleeve **610** may be part of a kit and deployed on site. Other configurations are within the scope of embodiments of the invention.

In the description and claims of the present application, each of the verbs, "comprise" "include" and "have", and conjugates thereof, are used to indicate that the object or objects of the verb are not necessarily a complete listing of members, components, elements or parts of the subject or subjects of the verb.

All references cited herein are incorporated by reference in their entirety. Citation of a reference does not constitute an admission that the reference is prior art.

The articles "a" and "an" are used herein to refer to one or to more than one (i.e., to at least one) of the grammatical object of the article. By way of example, "an element" means one element or more than one element.

The term "including" is used herein to mean, and is used interchangeably with, the phrase "including but not limited" to. The term "or" is used herein to mean, and is used interchangeably with, the term "and/or," unless context clearly indicates otherwise. The term "such as" is used herein to mean, and is used interchangeably, with the phrase "such as but not limited to".

The present invention has been described using detailed descriptions of embodiments thereof that are provided by way of example and are not intended to limit the scope of the invention. The described embodiments comprise different features, not all of which are required in all embodiments of the invention. Some embodiments of the present invention utilize only some of the features or possible combinations of the features. Variations of embodiments of the present invention that are described and embodiments of the present invention comprising different combinations of features noted in the described embodiments will occur to persons of the art.

WHAT IS CLAIMED IS:

1. A ballooned cleaning device for use with an ETT or tracheostomy ventilation tube **60**, a ventilator machine **900**, a source(s) **602** of pressurized liquid and a source(s) of suctioning **603**, the cleaning device comprising:
 - a. a tube-connector assembly **158** for connecting the ventilation tube **60** to the ventilator machine **900**, in a substantially air-tight manner;
 - b. an elongate, flexible, main body **210** that is insertable through the tube-connector assembly **158** into the ventilation tube **60** to form an interstitial region outside of the main body **210** within ventilation tube **60**;
 - c. a balloon **588** mounted to the main body **210** at a location in the distal half of the main body and inflatable into contact with an inner surface **201** of the ventilation tube **60**;
 - d. one or more liquid-delivery lumen(s) **520** arranged within or along the elongated main body, and operative to transport pressurized liquid received from pressurized liquid source(s) outside of the ventilation tube **60**, into a proximal portion **774** of the interstitial region that is proximal of the balloon **588** so that the transported liquid enters the proximal portion **774** via liquid delivery orifice(s) **525** located on or mechanically coupled to the main body **210**;
 - e. suction lumen(s) **530** arranged within or along the main body **210**, and operative to convey negative pressure from suction source(s) **603** predominantly into the proximal portion **774** of interstitial region via suction orifice(s) **440** when balloon **588** is inflated into contact, suction orifice(s) **440** being open to the proximal portion **774** and mechanically coupled to the main body **210**;
 - f. a suction port **830** connectable to the suction source(s) **603** for mediating a connection between the suction source and the suction lumen(s); and
 - g. a pliable sleeve **610** around at least a portion of the main body **210** in locations proximal to the tube-connector assembly **158** and distal to the suction port **830** to inhibit contamination.
2. The device of claim 1 wherein at least one of the fluid delivery orifice(s) **525** is a void in the balloon **588** so that the balloon **588** is leaky.

3. The device of claim 2 wherein inflatable balloon is operative to be inflated by pressurized fluid source via fluid delivery lumen(s) **520**.
4. The system of any of claims 2-3 wherein:
 - i. inflatable balloon **588** is a leaky balloon having one or more surface-located leak holes; and
 - ii. one or more of the fluid delivery orifice(s) **525** are leak holes that face in a direction having a proximal component; and
 - iii. inflatable balloon is operative to be inflated by pressurized fluid source via fluid delivery lumen(s) **520**.
5. The device of claim 1 wherein:
 - i. balloon **588** is a boundary-forming balloon which divides an interior of the ventilation tube into more proximate **774** and more distal **778** portions;
 - ii. at least one of the at least one of the fluid delivery orifice(s) **525** is a void in the boundary-forming balloon **588** so that the boundary-forming balloon **588** is leaky;
 - iii. forcing of pressurized liquid into the boundary-forming balloon **588** is operative both:
 - C. to inflate boundary-forming balloon **588**;
 - D. to cause the pressurized liquid to enter the proximal portion **774** via liquid delivery orifice(s) **525** located on or mechanically coupled to the main body **210**.
6. The device of claim 5 wherein the boundary-forming balloon **588** forms a seal between the proximate **774** and distal **778** portions of the interstitial region.
7. The device of claim 5 wherein the boundary-forming balloon **588** does not form a seal between the into proximate **774** and distal **778** portions of the interstitial region.
8. The device of any of claims 5-7 wherein the balloon **588** hinders and/or at least partially obstructs fluid communications between the more proximal and more distal portions.
9. A ballooned cleaning device for use with an ETT or tracheostomy ventilation tube **60**, a ventilator machine **900**, a source(s) of fluid and a source(s) of suctioning **603**, the cleaning device comprising:
 - a. a tube-connector assembly **158** for connecting the ventilation tube **60** to the

- ventilator machine **900**, in a substantially air-tight manner;
- b. an elongate, flexible, main body **210** that is insertable through the tube-connector assembly **158** into the ventilation tube **60** to form an interstitial region outside of the main body **210** within ventilation tube **60**;
 - c. a balloon **588** mounted to the main body **210** at and inflatable into contact with an inner surface **201** of the ventilation tube **60**;
 - d. one or more fluid delivery lumen(s) **520** arranged within or along the elongated main body, and operative to transport pressurized fluid received from pressurized fluid source(s) outside of the ventilation tube **60**, into a proximal portion **774** of the interstitial region that is proximal of the balloon **588** so that the transported fluid enters the proximal portion **774** via fluid delivery orifice(s) **525** located on or mechanically coupled to the main body **210**;
 - e. suction lumen(s) **530** arranged within or along the main body, and operative to convey negative pressure from suction source(s) **603** predominantly into the proximal portion **774** of interstitial region via suction orifice(s) **440** when balloon **588** is inflated into contact, suction orifice(s) **440** being open to the proximal portion **774** and mechanically coupled to the main body **210**.
 - f. a suction port **830** connectable to the suction source(s) **603** for mediating a connection between the suction source and the suction lumen(s); and
 - g. a pliable sleeve **610** around at least a portion of the main body **210** in locations proximal to the tube-connector assembly **158** and distal to the suction port **830** to inhibit contamination.

10. A ballooned cleaning device for use with an ETT or tracheostomy ventilation tube **60**, a ventilator machine **900**, a source(s) of fluid and a source(s) of suctioning **603**, the cleaning device comprising:

- a. a tube-connector assembly **158** for connecting the ventilation tube **60** to the ventilator machine **900**, in a substantially air-tight manner;
- b. an elongate, flexible, main body **210** that is insertable through the tube-connector assembly **158** into the ventilation tube **60** to form an interstitial region outside of the main body **210** within ventilation tube **60**;

- c. a balloon **588** mounted to the main body **210** at and inflatable into contact with an inner surface **201** of the ventilation tube **60**;
 - d. one or more fluid delivery lumen(s) **520** arranged within or along the elongated main body, and operative to transport fluid received from fluid source(s) outside of the ventilation tube **60**, into a proximal portion **774** of the interstitial region that is proximal of the balloon **588** so that the transported fluid enters the proximal portion **774** via fluid delivery orifice(s) **525** located on or mechanically coupled to the main body **210**;
 - e. suction lumen(s) **530** arranged within or along the main body, and operative to convey negative pressure from suction source(s) **603** predominantly into the proximal portion **774** of interstitial region via suction orifice(s) **440** when balloon **588** is inflated into contact, suction orifice(s) **440** being open to the proximal portion **774** and mechanically coupled to the main body **210**.
 - f. a suction port **830** connectable to the suction source(s) **603** for mediating a connection between the suction source and the suction lumen(s); and
 - g. a pliable sleeve **610** around at least a portion of the main body **210** in locations proximal to the tube-connector assembly **158** and distal to the suction port **830** to inhibit contamination.
11. A ballooned cleaning device for use with an ETT or tracheostomy ventilation tube **60**, a ventilator machine **900**, a source(s) of fluid and a source(s) of suctioning **603**, the cleaning device comprising:
- a. a tube-connector assembly **158** for connecting the ventilation tube **60** to the ventilator machine **900**, in a substantially air-tight manner;
 - b. an elongate, flexible, main body **210** that is insertable through the tube-connector assembly **158** into the ventilation tube **60** to form an interstitial region outside of the main body **210** within ventilation tube **60**;
 - c. a balloon **588** mounted to the main body **210** at a location inflatable into contact with an inner surface **201** of the ventilation tube **60**;
 - d. suction lumen(s) **530** arranged within or along the main body, and operative to convey negative pressure from suction source(s) **603** predominantly into the proximal portion **774** of interstitial region via suction orifice(s) **440** when balloon

588 is inflated into contact, suction orifice(s) **440** being open to the proximal portion **774** and mechanically coupled to the main body **210**;

e. a fluid delivery orifice(s) in fluid communication with a proximal portion **774** of the interstitial region that is proximal of the balloon **588** so that the fluid from the fluid source passing through the fluid delivery orifice enters the proximal portion **774**;

f. a suction port **830** connectable to the suction source(s) **603** for mediating a connection between the suction source and the suction lumen(s); and

g. a pliable sleeve **610** around at least a portion of the main body **210** in locations proximal to the tube-connector assembly **158** and distal to the suction port **830** to inhibit contamination.

12. A ballooned cleaning device for use with an ETT or tracheostomy ventilation tube **60**, a ventilator machine **900**, and a source(s) of suctioning **603**, the cleaning device comprising:

a. a tube-connector assembly **158** for connecting the ventilation tube **60** to the ventilator machine **900**, in a substantially air-tight manner;

b. an elongate, flexible, main body **210** that is insertable through the tube-connector assembly **158** into the ventilation tube **60** to form an interstitial region outside of the main body **210** within ventilation tube **60**;

c. a balloon **588** mounted to the main body **210** at a location inflatable into contact with an inner surface **201** of the ventilation tube **60**;

d. suction lumen(s) **530** arranged within or along the main body, and operative to convey negative pressure from suction source(s) **603** predominantly into the proximal portion **774** of interstitial region via suction orifice(s) **440** when balloon **588** is inflated into contact, suction orifice(s) **440** being open to the proximal portion **774** and mechanically coupled to the main body **210**;

e. a suction port **830** connectable to the suction source(s) **603** for mediating a connection between the suction source and the suction lumen(s); and

f. a pliable sleeve **610** around at least a portion of the main body **210** in locations proximal to the tube-connector assembly **158** and distal to the suction port **830** to inhibit contamination.

13. A ballooned cleaning device for use with an ETT or tracheostomy ventilation tube **60**, a ventilator machine **900**, a source(s) of fluid and a source(s) of suctioning **603**, the cleaning device comprising:

- a. an elongate, flexible, main body **210** that into the ventilation tube **60** to form an interstitial region outside of the main body **210** within ventilation tube **60**;
- b. an inflatable balloon **588** mounted to the main body **210** and inflatable when within the ventilation tube **60**;
- c. one or more fluid delivery lumen(s) **520** arranged within or along the elongated main body, and operative to transport fluid received from fluid source(s) outside of the ventilation tube **60**, into a proximal portion **774** of the interstitial region that is proximal of the balloon **588** so that the transported fluid enters the proximal portion **774** via fluid delivery orifice(s) **525** located on or mechanically coupled to the main body **210**;
- d. suction lumen(s) **530** arranged within or along the main body, and operative to convey negative pressure from suction source(s) **603** via suction orifice(s) **440** when balloon **588** is inflated into contact, suction orifice(s) **440** being open to the proximal portion **774** and mechanically coupled to the main body **210**.

14. A ballooned cleaning device for use with an ETT or tracheostomy ventilation tube **60**, a ventilator machine **900**, a source(s) of fluid and a source(s) of suctioning **603**, the cleaning device comprising:

- a. an elongate, flexible, main body **210** that into the ventilation tube **60** to form an interstitial region outside of the main body **210** within ventilation tube **60**;
- b. an inflatable balloon **588** mounted to the main body **210** and inflatable towards an inner surface **201** the ventilation tube **60**;
- c. a fluid delivery orifice(s) **525** in fluid communication with a proximal portion **774** of the interstitial region that is proximal of the balloon **588** so that the fluid from the fluid source passing through the fluid delivery orifice enters the proximal portion **774**;

- d. suction lumen(s) **530** arranged within or along the main body, and operative to convey negative pressure from suction source(s) **603** via suction orifice(s) **440** when balloon **588** is inflated into contact, suction orifice(s) **440** being open to the proximal portion **774** and mechanically coupled to the main body **210**.
15. The device of any of claims 13-14 wherein the balloon **588** is inflatable into contact with an inner surface **201** of the ventilation tube **60**
16. The device of any of claims 13-14 further comprising at least one of:
- i. a tube-connector assembly **158** for connecting the ventilation tube **60** to the ventilator machine **900**, in a substantially air-tight manner; and/or
 - ii. a suction port **830** connectable to the suction source(s) **603** for mediating a connection between the suction source and the suction lumen(s).
17. The device of any of claims 13-16 wherein the main body is insertable through the tube-connector assembly **158** into the ventilation tube **60** and/or the fluid delivery orifice is located on or mechanically coupled to the main body **210**.
18. The device of any of claims 13-17 further comprising a pliable sleeve **610** around at least a portion of the main body **210** in locations proximal to the tube-connector assembly **158** and distal to the suction port **830** to inhibit contamination.
19. The device of any preceding claim wherein the balloon is fluid-inflatable, and the device is configured so that for a given fluid delivery lumen **520**, a first portion of fluid flowing through the given fluid delivery lumen enters into the proximal portion **774** after passing through fluid delivery orifice(s) **525**, and a second portion of fluid flowing through the given fluid delivery lumen inflates balloon **588**.
20. The device of claims 19 wherein balloon **588** is leaky and fluid delivery orifice(s) that is supplied by fluid via the given fluid delivery lumen **520** is located on a surface **589** of balloon **588**.
21. The device of claim 19 wherein the balloon **588** is sealed and fluid delivery orifice(s) that is supplied by fluid via the given fluid delivery lumen **520** is not located on a surface **589** of balloon **588**.
22. The device of any of claims 19 or 21 wherein fluid delivery orifice(s) that is supplied by fluid via the given fluid delivery lumen **520** is located proximal to balloon **588**.

23. A cleaning device for use with an ETT or tracheostomy ventilation tube **60**, a ventilator machine **900**, a source(s) of fluid and a source(s) of suctioning **603**, the cleaning device comprising:

- a. a tube-connector assembly **158** for connecting the ventilation tube **60** to the ventilator machine **900**, in a substantially air-tight manner;
- b. an elongate, flexible, main body **210** that is insertable through the tube-connector assembly **158** into the ventilation tube **60** to form an interstitial region outside of the main body **210** within ventilation tube **60**;
- c. a width-expandable wiping element **588** mounted to the main body **210** and width-expandable in a direction perpendicular to an elongate axis of the main body **210** into contact with an inner surface **201** of the ventilation tube **60**;
- d. one or more fluid delivery lumen(s) **520** arranged within or along the elongated main body, and operative to transport fluid received from fluid source(s) outside of the ventilation tube **60**, into a proximal portion **774** of the interstitial region that is proximal of the wiping element **588** so that the transported fluid enters the proximal portion **774** via fluid delivery orifice(s) **525** located on or mechanically coupled to the main body **210**;
- e. suction lumen(s) **530** arranged within or along the main body, and operative to convey negative pressure from suction source(s) **603** predominantly into the proximal portion **774** of interstitial region via suction orifice(s) **440** when wiping element **588** is expanded into contact, suction orifice(s) **440** being open to the proximal portion **774** and mechanically coupled to the main body **210**;
- f. a suction port **830** connectable to the suction source(s) **603** for mediating a connection between the suction source and the suction lumen(s); and
- g. a pliable sleeve **610** around at least a portion of the main body **210** in locations proximal to the tube-connector assembly **158** and distal to the suction port **830** to inhibit contamination.

24. A cleaning device for use with an ETT or tracheostomy ventilation tube **60**, a ventilator machine **900**, a source(s) of fluid and a source(s) of suctioning **603**, the cleaning device comprising:

- a. a tube-connector assembly **158** for connecting the ventilation tube **60** to the

ventilator machine **900**, in a substantially air-tight manner;

b. an elongate, flexible, main body **210** that is insertable through the tube-connector assembly **158** into the ventilation tube **60** to form an interstitial region outside of the main body **210** within ventilation tube **60**;

c. a width-expandable wiping element **588** mounted to the main body **210** and width-expandable in a direction perpendicular to an elongate axis of the main body **210** into contact with an inner surface **201** of the ventilation tube **60**;

d. suction lumen(s) **530** arranged within or along the main body, and operative to convey negative pressure from suction source(s) **603** predominantly into the proximal portion **774** of interstitial region via suction orifice(s) **440** when the width-expandable wiping element **588** is expanded into contact, suction orifice(s) **440** being open to the proximal portion **774** and mechanically coupled to the main body **210**;

e. a fluid delivery orifice(s) in fluid communication with a proximal portion **774** of the interstitial region that is proximal of the wiping element **588** so that the fluid from the fluid source passing through the fluid delivery orifice enters the proximal portion **774**;

f. a suction port **830** connectable to the suction source(s) **603** for mediating a connection between the suction source and the suction lumen(s); and

g. a pliable sleeve **610** around at least a portion of the main body **210** in locations proximal to the tube-connector assembly **158** and distal to the suction port **830** to inhibit contamination.

25. A cleaning device for use with an ETT or tracheostomy ventilation tube **60**, a ventilator machine **900**, a source(s) of fluid and a source(s) of suctioning **603**, the cleaning device comprising:

a. a tube-connector assembly **158** for connecting the ventilation tube **60** to the ventilator machine **900**, in a substantially air-tight manner;

b. an elongate, flexible, main body **210** that is insertable through the tube-connector assembly **158** into the ventilation tube **60** to form an interstitial region outside of the main body **210** within ventilation tube **60**;

c. a width-expandable wiping element **588** mounted to the main body **210** and width-expandable in a direction perpendicular to an elongate axis of the main body **210** into contact with an inner surface **201** of the ventilation tube **60**;

d. first **220** and second **240** fluid delivery lumen(s) arranged within or along the elongated main body, and operative to transport fluid, received respectively from first and second fluid source(s) outside of the ventilation tube **60**, into a proximal portion **774** of the interstitial region that is proximal of the wiping element **588** so that the:

(i) transported fluid from both fluid delivery lumen(s) enters the proximal portion **774** via a common fluid delivery orifice(s) **225**

located on or mechanically coupled to the main body **210**; or

(ii) fluid respectively transported through the first **220A** and second **220B** fluid delivery lumen(s) respectively enters the proximal portion **774** via first **224** and second **244** orifices that are separated from each other by at most 5 mm and that are each located on or mechanically coupled to the main body **210**;

e. suction lumen(s) **530** arranged within or along the main body, and operative to convey negative pressure from suction source(s) **603** predominantly into the proximal portion **774** of interstitial region via suction orifice(s) **440** when wiping element **588** is expanded into contact, suction orifice(s) **440** being open to the proximal portion **774** and mechanically coupled to the main body **210**;

f. a suction port **830** connectable to the suction source(s) **603** for mediating a connection between the suction source and the suction lumen(s); and

g. a pliable sleeve **610** around at least a portion of the main body **210** in locations proximal to the tube-connector assembly **158** and distal to the suction port **830** to inhibit contamination.

26. A cleaning device for use with an ETT or tracheostomy ventilation tube **60**, a ventilator machine **900**, an array of fluid sources and a source(s) of suctioning **603**, the cleaning device comprising:

a. a tube-connector assembly **158** for connecting the ventilation tube **60** to the ventilator machine **900**, in a substantially air-tight manner;

- b. an elongate, flexible, main body **210** that is insertable through the tube-connector assembly **158** into the ventilation tube **60** to form an interstitial region outside of the main body **210** within ventilation tube **60**;
- c. a width-expandable wiping element **588** mounted to the main body **210** and width-expandable in a direction perpendicular to an elongate axis of the main body **210** into contact with an inner surface **201** of the ventilation tube **60**;
- d. a mist formation assembly operative, when the main body **210** is inserted through the tube-connector assembly **158** into the ventilation tube **60**, to form a mist from a liquid-containing fluid and a gas-containing fluid so that the formed mist flows within a proximal portion **774** of the interstitial region that is proximal of the wiping element **588**
- e. suction lumen(s) **530** arranged within or along the main body, and operative to convey negative pressure from suction source(s) **603** predominantly into the proximal portion **774** of interstitial region via suction orifice(s) **440** when wiping element **588** is expanded into contact, suction orifice(s) **440** being open to the proximal portion **774** and mechanically coupled to the main body **210**;
- f. a suction port **830** connectable to the suction source(s) **603** for mediating a connection between the suction source and the suction lumen(s); and
- g. a pliable sleeve **610** around at least a portion of the main body **210** in locations proximal to the tube-connector assembly **158** and distal to the suction port **830** to inhibit contamination.

27. The device of any of claims 25-26 wherein the mist is formed within the proximal portion **774** of the interstitial region.

28. The device of any of claims 25-26 wherein the mist is formed within the main body **210**.

29. The device of any of claims 25-26, wherein when the main body is inserted through the tube-connector assembly **158** into the ventilation tube **60** to form the interstitial region, the mist is formed within the main body in location(s) within ventilation tube **60**.

30. The device of any of claims 25-29 wherein the device is configured so that the mist enters the proximal portion **774** of the interstitial region via a fluid delivery orifice(s) open thereto, the fluid delivery orifice(s) being mechanically coupled to main body **210**.

31. The device of any of claims 25-30 wherein the mist formation assembly includes first and second fluid-delivery lumen(s) arranged within or along the elongated main body and respectively operative to receive and transport the liquid-containing and gas-containing fluids.

32. The device of claim 31 wherein the mist formation assembly includes a common orifice via which material transported within the first and second fluid-delivery lumen(s) enters into the proximal portion **774** of the interstitial region.

33. The device of claim 32 wherein the first and second fluid-delivery lumen(s) merge within main body **210** at a merge or mixing location **522**.

34. The device of claim 33 wherein the mist is formed as fluid(s) flow from the merge location to or through a fluid delivery orifice, mechanically coupled to main body **210** and open to the proximal portion **774** of the interstitial region.

35. The device of any of claims 25-34 wherein the first **224** and second **244** orifices are separated from each other by at most 4 mm or at most 3 mm or at most 2 mm or at most 1 mm.

36. A cleaning device for use with an ETT or tracheostomy ventilation tube **60**, a ventilator machine **900**, a source(s) of fluid and a source(s) of suctioning **603**, the cleaning device comprising:

- a. an elongate, flexible, main body **210** that into the ventilation tube **60** to form an interstitial region outside of the main body **210** within ventilation tube **60**;
- b. a width-expandable wiping element **588** mounted to the main body **210** and width-expandable in a direction perpendicular to an elongate axis of the main body **210**;
- c. one or more fluid delivery lumen(s) **520** arranged within or along the elongated main body, and operative to transport fluid received from fluid source(s) outside of the ventilation tube **60**, into a proximal portion **774** of the interstitial region that is proximal of the wiping element **588** so that the transported fluid enters the proximal portion **774** via fluid delivery orifice(s) **525**;
- d. suction lumen(s) **530** arranged within or along the main body, and operative to convey negative pressure from suction source(s) **603** via suction orifice(s) **440**

- when wiping element **588** is expanded into contact, suction orifice(s) **440** being open to the proximal portion **774** and mechanically coupled to the main body **210**.
37. A cleaning device for use with an ETT or tracheostomy ventilation tube **60**, a ventilator machine **900**, a source(s) of fluid and a source(s) of suctioning **603**, the cleaning device comprising:
- a. an elongate, flexible, main body **210** that into the ventilation tube **60** to form an interstitial region outside of the main body **210** within ventilation tube **60**;
 - b. a width-expandable wiping element **588** mounted to the main body **210** and width-expandable in a direction perpendicular to an elongate axis of the main body **210**;
 - c. a fluid delivery orifice(s) **525** in fluid communication with a proximal portion **774** of the interstitial region that is proximal of the wiping element **588** so that the fluid from the fluid source passing through the fluid delivery orifice enters the proximal portion **774**;
 - d. suction lumen(s) **530** arranged within or along the main body, and operative to convey negative pressure from suction source(s) **603** via suction orifice(s) **440** when wiping element **588** is expanded into contact, suction orifice(s) **440** being open to the proximal portion **774** and mechanically coupled to the main body **210**.
38. The device of any of claims 36-37 wherein the width-expandable wiping element **588** is expandable into contact with an inner surface **201** of the ventilation tube **60**
39. The device of any of claims 36-37 further comprising at least one of:
- i. a tube-connector assembly **158** for connecting the ventilation tube **60** to the ventilator machine **900**, in a substantially air-tight manner; and/or
 - ii. a suction port **830** connectable to the suction source(s) **603** for mediating a connection between the suction source and the suction lumen(s).
40. The device of any of claims 36-39 wherein the main body is insertable through the tube-connector assembly **158** into the ventilation tube **60** and/or the fluid delivery orifice is located on or mechanically coupled to the main body **210**.
41. The device of any of claims 36-40 further comprising a pliable sleeve **610** around at least a portion of the main body **210** in locations proximal to the tube-connector assembly **158** and distal to the suction port **830** to inhibit contamination.

42. The device of any of claims 23-41 wherein the width-expandable wiping element is an inflatable object that width-expands upon inflation.
43. The device of any of claims 23-41 wherein the width-expandable wiping element is a balloon that width-expands upon inflation.
44. The device of claim 43 wherein the balloon **588** is inflatable via a balloon lumen **580** along or within main body **210**.
45. The device of any of claims 43-44 wherein the balloon **588** is inflatable via one of the fluid delivery lumen(s) **520** along or within main body **210**.
46. The device of any of claims 23-45 wherein the width-expandable wiping element is expands by a mechanism other than inflation.
47. The device of any of claims 23-46 wherein the width-expandable wiping element includes an outwardly biased element.
48. The device of any of claims 23-48 wherein the width-expandable wiping element includes an outwardly-biased shape memory device.
49. The device of any of claims 47-48 wherein when in an expanded configuration, the outwardly-biased shape memory is shaped as a spiral.
50. The device of any of claims 47-49 wherein when in the expanded configuration, the outwardly-biased shape memory is pre-shaped as a spiral having a central axis that is substantially parallel to an elongate axis of the main body **210**.
51. The device of claim 47 wherein the outwardly biased element is a stent.
52. The device of any of claims 23-54 wherein the width-expandable wiping element is not outwardly biased.
53. The device of claim 52 wherein the width-expandable wiping element includes a rigid skeleton having a multiple configuration.
54. The device of any of claims 23-54 wherein a width ratio between:
- i. an expanded-configuration width of the width-expandable wiping element;
 - and
 - i.. a contracted-configuration width of the width-expandable wiping element
- is at least 1.5.

55. The device of any of claims 23-54 wherein a contracted-configuration width of the width-expandable wiping element is at most one-half of an inner diameter of the ventilation tube **60**.

55. The device of any of claims 12-54 wherein a contracted-configuration width of the width-expandable wiping element is at most one-third of an inner diameter of the ventilation tube **60**.

56. The device of any preceding claim wherein inflatable balloon **588** and fluid delivery orifice **525** are supplied by a common fluid supply.

56. The device of any preceding claim wherein inflatable balloon **588** and fluid delivery orifice **525** are supplied by a common fluid supply via a common fluid delivery lumen **520**.

57. The device of any preceding claim wherein inflatable balloon **588** and fluid delivery orifice **525** are supplied by a common fluid supply respectively via first **520A** and second **520B** fluid delivery lumen.

58. The device of any preceding claim wherein balloon **588** or wiping element **588** are mounted to the main body **210** in a distal half thereof.

59. A system comprising:

the device of any of claims 1-58;

source(s) of pressurized liquid **602**, the device and liquid source configured, when the main body **210** is inserted within the ventilation tube **60**, such that the pressurized liquid received from the fluid(s) source or a derivative thereof enters proximal portion **774** after passing through fluid delivery orifice(s).

60. A system comprising:

the device of any of claims 1-58;

source(s) of liquid **602**, the device and liquid source configured, when the main body **210** is inserted within the ventilation tube **60**, such that the liquid received from the fluid(s) source or a derivative thereof enters proximal portion **774** after passing through fluid delivery orifice(s).

61. A system comprising:

the device of any of claims 1-58;

source(s) of pressurized fluid **602**, the device and fluid source configured, when the main body **210** is inserted within the ventilation tube **60**, such that the pressurized fluid received from the fluid(s) source or a derivative thereof enters proximal portion **774** after passing through fluid delivery orifice(s).

62. A system comprising:

the device of any of claims 1-58;

source(s) of fluid **602**, the device and liquid source configured, when the main body **210** is inserted within the ventilation tube **60**, such that the fluid received from the fluid(s) source or a derivative thereof enters proximal portion **774** after passing through fluid delivery orifice(s).

63. The system of claim 62 wherein the fluid(s) source includes a source of unpressurized fluid.

64. The system of any of claims 59-63 wherein a mist is formed from a liquid-containing source and a gas containing source within main body **210** and is delivered into enters proximal portion **774**.

65. The system of any of claims 59-65 wherein a mist is formed from a liquid-containing source and a gas containing source upon entry into proximal portion **774**.

66. A method comprising employing any device or system of any preceding claim to clean biofilm from the inner surface **201** of the ventilation tube.

67. A method comprising employing any device or system of any preceding claim to prevent accumulation or hinder accumulation of biofilm from the inner surface **201** of the ventilation tube.

68. A method of cleaning a main lumen of an ETT or tracheostomy ventilation tube **60** and/or hindering accumulation of biofilm on an inner surface of ventilation tube **60**, the method comprising:

at a time when:

- i. a ventilation machine **900** is connected to the ventilation tube **60** via a tube connector assembly **158** in a substantially air-tight manner;
- ii. an elongate, flexible, main body **210** traverses an interior of the tube connector assembly **158** so that a distal end of the main body **210** is located within the ventilation tube **60** to form an interstitial region

outside of the main body **210** and within the ventilator tube;

iii. an inflatable balloon **588** mounted to the main body **210** is located within the ventilation tube **60**;

iv. sources of fluid **602** and suction **603** are respectively in fluid communication with fluid delivery orifice(s) **525** and suction orifice(s) **440**, the suction **440** orifice(s) being located proximal to balloon **588** within ventilation tube **60** and on main body **210** or mechanically coupled to main body

210,

carrying out the following:

inflating the balloon **588** outwardly towards an inner surface **201** of the ventilation tube **60** and/or into contact with the inner surface **201** of the ventilation tube **60** so that both suction **440** and fluid delivery **525** orifice(s) are in fluid communication to a proximal portion **774** of the interstitial region that is proximal to inflatable balloon **588**;

concurrent with a maintaining the balloon in an inflated state, conveying negative pressure from the suction source(s) **603**, via the suction lumen(s) **530** and orifice(s) **440**, predominantly into the proximal portion **774** of the interstitial region; and

concurrent with a maintaining of the balloon in the inflated state, sending fluid from the fluid source(s) **602** through the fluid delivery orifice(s) **525** into the interstitial region proximal portion **774**.

69. A method of cleaning a main lumen of an ETT or tracheostomy ventilation tube **60** and/or hindering accumulation of biofilm on an inner surface of ventilation tube **60**, the method comprising:

at a time when:

- i. a ventilation machine **900** is connected to the ventilation tube **60** via a tube connector assembly **158** in a substantially air-tight manner;
- ii. an elongate, flexible, main body **210** traverses an interior of the tube connector assembly **158** so that a distal end of the main body **210** is located within the ventilation tube **60** to form an interstitial region

outside of the main body **210** and within the ventilator tube;

iii. an inflatable balloon **588** mounted to the main body **210** is located within the ventilation tube **60**;

iv. sources of fluid **602** and suction **603** are respectively in fluid communication with fluid delivery orifice(s) **525** and suction orifice(s) **440**, the suction **440** orifice(s) being located proximal to balloon **588** within ventilation tube **60** and on main body **210** or mechanically coupled to main body

210,

carrying out the following:

inflating the balloon **588** into contact with the inner surface **201** of the ventilation tube **60** so that both suction **440** and fluid delivery **525** orifice(s) are in fluid communication to a proximal portion **774** of the interstitial region that is proximal to inflatable balloon **588**;

concurrent with a maintaining the balloon inflated into contact, conveying negative pressure from the suction source(s) **603**, via the suction lumen(s) **530** and orifice(s) **440**, predominantly into the proximal portion **774** of the interstitial region; and

concurrent with a maintaining of the balloon inflated into contact, sending fluid from the fluid source(s) **602** through the fluid delivery orifice(s) **525** into the interstitial region proximal portion **774**.

70. A method of cleaning a main lumen of an ETT or tracheostomy ventilation tube **60** and/or hindering accumulation of biofilm on an inner surface of ventilation tube **60**, the method comprising:

at a time when:

- i. a ventilation machine **900** is connected to the ventilation tube **60** via a tube connector assembly **158** in a substantially air-tight manner;
- ii. an elongate, flexible, main body **210** traverses an interior of the tube connector assembly **158** so that a distal end of the main body **210** is located within the ventilation tube **60** to form an interstitial region outside of the main body **210** and within the ventilator tube;

- iii. a width-expandable wiping element **588** mounted to the main body **210** is located within the ventilation tube **60**;
- iv. sources of fluid **602** and suction **603** are and are respectively in fluid communication with fluid delivery orifice(s) **525** and suction orifice(s) **440**, the suction **440** orifice(s) being located proximal to wiping element **588** within ventilation tube **60** and on main body **210** or mechanically coupled to main body **210**,

carrying out the following:

expanding the mounted width-expandable wiping element **588** towards an inner surface **201** of the ventilation tube **60** so that both suction **440** and fluid delivery **525** orifice(s) are in fluid communication to a proximal portion **774** of the interstitial region that is proximal to width-expanded wiping element **588**;

concurrent with a maintaining of the width-expanded wiping element **588** in the width-expanded state, conveying negative pressure from the suction source(s) **603**, via the suction lumen(s) **530** and orifice(s) **440**, predominantly into the proximal portion **774** of the interstitial region; and concurrent with a maintaining of the width-expanded wiping element **588** in the width-expanded state, sending fluid from the fluid source(s) **602** through the fluid delivery orifice(s) **525** into the interstitial region proximal portion **774**.

71. A method of cleaning a main lumen of an ETT or tracheostomy ventilation tube **60** and/or hindering accumulation of biofilm on an inner surface of ventilation tube **60**, the method comprising:

at a time when:

- i. a ventilation machine **900** is connected to the ventilation tube **60** via a tube connector assembly **158** in a substantially air-tight manner;
- ii. an elongate, flexible, main body **210** traverses an interior of the tube connector assembly **158** so that a distal end of the main body **210** is located within the ventilation tube **60** to form an interstitial region outside of the main body **210** and within the ventilator tube;

- iii. a width-expandable wiping element **588** mounted to the main body **210** is located within the ventilation tube **60**;
- iv. sources of fluid **602** and suction **603** are and are respectively in fluid communication with fluid delivery orifice(s) **525** and suction orifice(s) **440**, the suction **440** orifice(s) being located proximal to wiping element **588** within ventilation tube **60** and on main body **210** or mechanically coupled to main body **210**, carrying out the following:
 - a. expanding the mounted width-expandable wiping element **588** into contact with an inner surface **201** of the ventilation tube **60** so that both suction **440** and fluid delivery **525** orifice(s) are in fluid
 - b. communication to a proximal portion **774** of the interstitial region that is proximal to width-expanded wiping element **588**;
 - concurrent with a maintaining of the contact by the width-expanded wiping element **588**, conveying negative pressure from the suction source(s) **603**, via the suction lumen(s) **530** and orifice(s) **440**, predominantly into the proximal portion **774** of the interstitial region; and
 - c. concurrent with a maintaining of the contact by the width-expanded wiping element **588**, sending fluid from the fluid source(s) **602** through the fluid delivery orifice(s) **525** into the interstitial region proximal portion **774**.

72. The method of any of claims 67-71 wherein the suction source and/or the source of fluid(s) are located outside of ventilation tube **60**.

73. The method of any of claims 67-72 further comprising moving the expanded wiping element or inflated balloon in a longitudinal direction so as to wipe material from the inner surface of ventilation tube **60** and/or to hinder accumulation of biofilm thereon.

74. The method of any of claims 67-72 wherein the fluid which enters the proximal portion **774** includes a liquid and/or includes a mist.

75. The method of any of claims 67-74 wherein the fluid is sent into the interstitial region proximal portion **774** so that a liquid-containing stream of fluid flows therein, the fluid stream being sustained so that a liquid fraction thereof flows at a flow rate of at least x

cc/second for at least y seconds, a value of x being at least 0.25 cc/second and a value of y being at least y seconds.

76. The method of claim 75 wherein x is at least 0.5 cc/second or at least 1 cc/second and/or at most 10 cc/second or at most 5 cc/second.

77. The method of any of claims 67-76 carried out to deliver a mist into proximal region **774**.

77. The method of any of claims 67-76 carried out to form a mist within ventilation tube **60** which is formed within and/or delivered to proximal region **774**.

78. The method, system or device of any previous claim wherein fluid cannot be delivered into proximal portion **774** when the balloon is not in contact with the inner surface **201** of ventilation tube **60** and/or is in an uninflated state.

79. The method, system or device of any previous claim wherein fluid cannot be delivered into proximal portion **774** when the width-expandable wiping element is not in contact with the inner surface **201** of ventilation tube **60** and/or is in an unexpanded state.

80. The method of any previous method claim wherein an inner surface of the ventilation tube is cleaned within 15 second.

81. A method of cleaning a main lumen of an ETT or tracheostomy ventilation tube **60** comprising:

at a time when:

- i. a ventilation machine **900** is connected to the ventilation tube **60** via a tube connector assembly **158** in a substantially air-tight manner;
- ii. an elongate, flexible, main body **210** traverses an interior of the tube connector assembly **158** so that a distal end of the main body **210** is located within the ventilation tube **60** to form an interstitial region outside of the main body **210** and within the ventilator tube;
- iii. a balloon **588** mounted to the main body **210** is located within the ventilation tube **60**;
- iv. sources of pressurized fluid and/or suction **603** are:

A. any of which or both of which located in a tube-connector-assembly-proximal location outside of the ventilation tube **60** and proximal to tube connector assembly **158**; and

B. are respectively in fluid communication with fluid delivery orifice(s) **525** and suction orifice(s) **440** via fluid delivery lumen(s) **520** and suction lumen(s) **530**,

each of the suction **440** and fluid delivery **525** orifice(s) being:

A. located proximal to balloon **588** within ventilation tube **60**, and

B. on main body **210** or mechanically coupled to main body **210**,

carrying out the following steps:

- d. inflating the balloon **588** mounted to the main body **210** into contact with an inner surface **201** of the ventilation tube **60** so that both suction **440** and fluid delivery **525** orifice(s) are open to a proximal portion **774** of the interstitial region that is proximal to balloon **588**;
- e. concurrent with a maintaining of the contact by the balloon **588**, forcing pressurized fluid from the pressurized fluid source(s) **602** through the fluid delivery lumen(s) **520** and orifice(s) **525**, into the interstitial region proximal portion **774**;
- f. concurrent with a maintaining of the contact by the balloon **588**, conveying negative pressure from the suction source(s) **603**, via the suction lumen(s) **530** and orifice(s) **440**, predominantly into the proximal portion **774** of the interstitial region.

82. A ballooned cleaning device for use with an ETT or tracheostomy ventilation tube **60**, a ventilator machine **900**, a source(s) of fluid (e.g. pressurized) and a source(s) of suctioning **603**, the cleaning device comprising:

- a. a tube-connector assembly **158** for connecting the ventilation tube **60** to the ventilator machine **900**, in a substantially air-tight manner;
- b. an elongate, flexible, main body **210** that is insertable through the tube-connector assembly **158** into the ventilation tube **60** to form an interstitial region outside of the main body **210** within ventilation tube **60**;

- c. a balloon **588** mounted to the main body **210** at a location (for example in the distal half of the main body) and inflatable into contact with an inner surface **201** of the ventilation tube **60**;
- d. one or more fluid delivery lumen(s) **520** arranged within or along the elongated main body, and operative to transport pressurized fluid received from pressurized fluid source(s) outside of the ventilation tube **60**, into a proximal portion **774** of the interstitial region that is proximal of the balloon **588** so that the transported fluid enters the proximal portion **774** via fluid delivery orifice(s) **525** located on or mechanically coupled to the main body **210**;
- e. suction lumen(s) **520** arranged within or along the main body, and operative to convey negative pressure from suction source(s) **603** predominantly into the proximal portion **774** of interstitial region via suction orifice(s) **440** when balloon **588** is inflated into contact, suction orifice(s) **440** being open to the proximal portion **774** and mechanically coupled to the main body **210**.
- f. a suction port **820** connectable to the suction source(s) **603** for mediating a connection between the suction source and the suction lumen(s); and
- g. a pliable sleeve **610** around at least a portion of the main body **210** in locations proximal to the tube-connector assembly **158** and distal to the suction port **820** to inhibit contamination.

83. The device, system or method of any of claims 81-82 wherein the balloon **588** is inflated by liquid or gas supplied by balloon fluid source that is located in the tube-assembly-proximal location.

84. The device, system or method of any of claims 81-82 wherein balloon **588** is supplied via a balloon lumen(s) **580** that is different from fluid delivery lumen(s) **520**.

85. The device, system or method of any of claims 81-84 wherein balloon **588** is inflated by gas or by a liquid.

86. The device, system or method of any preceding claim wherein the fluid delivered via orifice(s) **525** and/or sent through fluid delivery lumen(s) **520** is a liquid and/or a liquid-gas mixture (e.g. a mist or bubbled fluid).

87. The device, system or method of claim 86 wherein balloon **588** is inflated by fluid (e.g. liquid and/or liquid-gas mixture) delivered via fluid delivery lumen(s) **520**.

88. The device, system or method of any preceding claim wherein a length of the pliable sleeve **610** is at least 5 cm.

89. The device, system or method of any preceding claim wherein the method is carried out when the suction orifice(s) and/or the fluid delivery are located closer to balloon **588** than to a proximal end **62** of ventilation tube **60**.

90. The device, system or method of any preceding claim wherein the method is carried out at a time when a pliable sleeve **610** is arranged around at least a portion of the main body **210** in locations **598** proximal to the tube-connector assembly **158**.

91. The device, system or method of any preceding claim wherein the method is carried out at a time when a pliable sleeve **610** is arranged around at least a portion of the main body **210** in locations **598** proximal to the tube-connector assembly and distal to a suction port **820** which mediates a connection between suction source(s) **603** and suction lumen(s) **520**.

92. The device, system or method of any preceding claim wherein the one or more suction orifice(s) is(are) longitudinally displaced from the balloon **588** by at most a suction-orifice-displacement-value that is at most 3 cm or at most 2 cm or at most 1 cm.

93. The device, system or method of any preceding claim wherein:

- i. the pressurized fluid is simultaneously forced through first **525A** and second **525B** fluid delivery orifices to respectively produce first **556A** and second **556B**

fluid streams that are respectively and simultaneously incident upon an inner surface **201** of the ventilation tube **60** at first **552A** and second **552B** locations; and

ii. the first **552A** and second **552B** locations are substantially on opposite sides of the ventilation tube **60** inner surface **201** within a tolerance that is at most 75 degrees or at most 45 degrees or at most 25 degrees.

94. The device, system or method of any preceding claim wherein at least one fluid-delivery-orifice **525** is proximally displaced from the slidable boundary by at most a fluid-orifice-displacement-value that is at most 3 cm, or at most 2 cm or at most 1 cm.

95. The device, system or method of any of preceding claim wherein the first **525A** and second **525B** fluid delivery orifices are respectively supplied via first **520A** and second **520B** fluid-delivery lumens.

96. The device, system or method of claim 95 wherein the first **520A** and second **520B** second fluid delivery lumens are simultaneously supplied by a common pressurized fluid chamber (c.g. a chamber mixing apparatus **696** of any other chamber).

97. The device, system or method of any preceding claim wherein immediately before exiting each fluid delivery port **525**, the delivered fluid is pressurized to at least 1.5 atmospheres, or at least 2 atmospheres or at least 3 atmospheres.

98. The device, system or method of any preceding claim wherein each fluid delivery orifice **525** has a width of at most 5 mm, at most 3 mm, or at most 2 mm, or at most 0.5mm, at most 0.3mm, at most 0.2mm.

99. The device, system or method of any preceding claim wherein each fluid delivery orifice **525** has width that is at most 50%, or at most 25% or at most 10%, or at most 5%, of an average width of the **440** suction orifice(s).

100. The device, system or method of any preceding claim wherein the suction-orifice-displacement-value is at most 2 cm, or at most 1 cm or at most 0.5 cm.

101. The device, system or method of any preceding claim wherein the ventilation tube **60** is an ETT.

102. The device, system or method of any preceding claim wherein the ventilation tube **60** is a tracheostomy tube.

103. The device, system or method of any previous claim wherein the fluid delivery operation and the suctioning are carried out simultaneously.

104. The device, system or method of any previous claim wherein the fluid delivery operation and the suctioning are carried out sequentially.

105. The device, system or method of any previous claim further comprising:
concurrent to the maintaining of the slidable boundary, longitudinally moving
the boundary-forming balloon **588** so as to mechanically dislodge and/or loosen
biofilm material located on the inner surface **201** of the ventilation tube **60**.

106. The device, system or method of claim 105 wherein the longitudinal moving is carried out simultaneously with the fluid delivery operation and/or the suctioning.

107. The device, system or method of any of previous claim wherein at least one of the fluid delivery orifice(s) **525** are deployed to and/or voids within a second balloon **586** deployed distal to the boundary-forming balloon **588**.

108. The device, system or method of claim 107 wherein the second balloon **586** is inflatable.

109. The device, system or method of claim 107 wherein the second balloon **586** is not inflatable.

110. The device, system or method of any previous claim at least one of the at least one of the fluid delivery orifice(s) **525** is an inner-surface-facing void in the main body **210** facing towards the inner surface **201** of the ventilation tube **60** or a inner-surface-facing-void in a fluid-delivery lumen **520** that at least spans a longitudinal range between the fluid delivery orifice(s) **525** and a location on or within the main body **210** that is proximal to the ventilation tube connector assembly **158**.

111. The device, system or method of any previous claim wherein

- i. at least one of the at least one of the fluid delivery orifice(s) **525** is a void in the boundary-forming balloon **588** so that the boundary-forming balloon **588** is leaky;
- ii. forcing of pressurized fluid into the boundary-forming balloon **588** is operative to carry out at least some of both of the balloon-inflation operation and the fluid-delivery of the fluid-delivery operation.

112. The device, system or method of claim 110 wherein a surface of the boundary-forming balloon **588** is at least 90% or at least , by surface area, substantially impermeable.

113. The device, system or method of any of claims 110-112 wherein a surface of the boundary-forming balloon **588** is at most 99%, by surface area, substantially impermeable.

114. The device, system or method of any previous claim wherein the boundary-forming **588** balloon is substantially sealed and is not leaky.

115. The device, system or method of any of previous claim further comprising carrying out the additional step of:

- D. concurrent with the maintaining of the ventilation circuit, and at a time that

the boundary-forming balloon **588** mounted to the elongate, flexible main body **210** is located within the ventilation tube **60** and in a non-obstructing mode so that the slidable boundary with the inner surface **201** of the ventilation tube **60** is not maintained and/or in non-contact mode so that balloon **588** is not inflated into contact with the inner surface **201** of ventilation tube **60**, proximally suctioning into the suction orifice(s) **440** material that is located:

III. within the ventilation tube **60** and distal to the boundary-forming balloon **588**; and/or

IV. distal to the ventilation tube distal end **60** so that the material located distal to the ventilation tube distal end **60** enters an interior region of ventilation tube **60** *en route* to the suction orifice(s),

wherein the suctioning step when the boundary-forming balloon **588** is in non-obstructing and/or non-contact mode is carried out to proximally transport material suctioned in step D proximally out of ventilation tube **60** via a proximal opening of the ventilation tube **60**.

116. The device, system or method of any preceding claim wherein the balloon is mounted to the main body **210** at a location in a distal half, or distal third, or distal quarter, or distal fifth or distal tenth of the main body **210**.

117. The device, system or method of any preceding claim wherein an inner diameter of ventilation tube **60** is at least 4 mm and/or at most 11 mm.

118. The device, system or method of any preceding claim wherein the pressurized fluid source **602** and the suction source **603** are respectively operative, in combination with the lumens and the orifices, to effect the fluid delivery and the suctioning when the boundary-forming balloon **588** is located in a distal half of the ventilation tube **60** and/or the system lacks suction orifice(s) more distal than the balloon **588**.

119. The device, system or method of preceding claim wherein the system lacks suction orifice(s) more distal than the balloon 558 and/or distal to boundary and in fluid communication with suction source **603**.

120. The device, system or method of preceding claim wherein the combined total aperture area of any and all suction orifices more distal than the balloon **588** and/or open to distal locations **778** is at most 50%, or at most 40%, or at most 30%, or at most 20%, or at most 10% of the combined total aperture area of any and all suction orifices **440** proximal to the balloon **558** and/or open to proximal location(s) **774**.

121. The device, system or method of preceding claim wherein the combined total aperture area of any and all suction orifices in fluid communication with suction source **603** and more distal than the balloon **588** and/or open to distal locations **778** is at most 50%, or at most 40%, or at most 30%, or at most 20%, or at most 10% of the combined total aperture area of any and all suction orifices **440** in fluid communication with suction source **603** and proximal to the balloon **558** and/or open to proximal location(s) **774**.

122. The device, system or method of any preceding claims further comprising: a sleeve **610** operative to envelop and/or cover at least 5 cm of the elongate flexible main body **210**.

123. The device, system or method of any previous claim wherein a distal end of the sleeve **610** is directly or indirectly attached to ventilation tube connector assembly **158** so that the main body **210** may slide through the sleeve.

124. The device, system or method of any preceding claim wherein a proximal end of sleeve **610** is configured to have a substantially fixed longitudinal position relative to a proximal end of elongate flexible main body **210**.

126. The device, system or method of any of preceding claim wherein the system lacks suction orifice(s) more distal than the balloon 558 and/or distal to boundary.

128. The device, system or method of any of preceding claim wherein the system lacks suction orifice(s) more distal than the balloon 558 and/or distal to boundary and in fluid communication with suction source **603**.

129. The device, system or method of any of preceding claim wherein the combined total aperture area of any and all suction orifices more distal than the balloon **588** and/or open to distal locations **778** is at most 50%, or at most 40%, or at most 30%, or at most 20%, or at most 10% of the combined total aperture area of any and all suction orifices **440** proximal to the balloon **558** and/or open to proximal location(s) **774**.

130. The device, system or method of any of preceding claim wherein the combined total aperture area of any and all suction orifices in fluid communication with suction source **603** and more distal than the balloon **588** and/or open to distal locations **778** is at most 50%, or at most 40%, or at most 30%, or at most 20%, or at most 10% of the combined total aperture area of any and all suction orifices **440** in fluid communication with suction source **603** and proximal to the balloon **558** and/or open to proximal location(s) **774**.

131. The device, system or method of any of preceding claim wherein at least one of the suction orifice(s) **440** is in fluid communication, via suction lumen **520**, with a blocking construct or blocking element that is distal of at least one suction orifice **440** and that is configured to mostly or completely block fluid communication with a distal opening **519**.

132. The device, system or method of any of preceding claim wherein the blocking construct or blocking element comprises a blocking glue or other material introduced onto or into suction lumen **520** and/or comprises a melt construct of a melted inner wall(s) of suction lumen(s) **520**.

133. The device, system or method of any preceding claim wherein, the system is operative such that:

- i. the pressurized fluid is simultaneously forced through first **525A** and second **525B** fluid delivery orifices to respectively produce first **556A** and second **556B** fluid streams that are respectively and simultaneously incident upon an inner surface **201** of the ventilation tube **60** at first **552A** and second **552B** locations; and
- ii. the first **552A** and second **552B** locations are substantially on opposite sides of the ventilation tube **60** inner surface **201** within a tolerance that is at most 75 degrees.

134. The device, system or method of any preceding claim wherein the system or apparatus comprises a plurality of fluid delivery orifices **525** including:

- i. a first fluid delivery orifice **525A** deployed to a first side of the elongate main body **210**; and
- ii. a second fluid delivery orifice **525B** deployed substantially to a second side of the elongate main body **210** that is on opposite side of main body central axis **202** within a tolerance that is at most 75 degrees or at most 45 degrees or at most 25 degrees.

135. The device, system or method of any of preceding claim wherein the system or apparatus comprises first **525A** and second **525B** fluid delivery orifice(s) which are operative such that:

- i. when an inner diameter of ventilation tube **60** is between 4 and 11 mm and exceeds an outer diameter of main body **210**,
- ii. when the main body **210** traverses the ventilation tube connector **158** so as to enter the ventilation tube;
- iii. when the boundary-forming balloon **588** is inflated so as to maintain the boundary; and
- iv. when the pressurized fluid is simultaneously forced, via fluid delivery lumen(s) **530** through first **525A** and second **525B** fluid delivery orifice,

to respectively produce first **556A** and second **556B** fluid streams that are respectively and simultaneously incident upon an inner surface **201** of the ventilation tube **60** at first **552A** and second **552B** locations such that the first **552A** and second **552B** locations are substantially on opposite sides of the ventilation tube **60** inner surface **201** within a tolerance that is at most 75 degrees or at most 45 degrees or at most 25 degrees.

136. The device, system or method of any of claims 36-39 wherein at least one fluid-delivery-orifice **525** is proximally displaced from the slidable boundary by at most a fluid-orifice-displacement-value that is at most 3 cm, or at most 2 cm.

137. The device, system or method of any preceding claim wherein the first **520A** and second **520B** fluid second fluid delivery lumens are simultaneously supplied by a common pressurized fluid chamber.

138. The device, system or method of any of preceding claim wherein immediately before exiting each fluid delivery port **525**, the delivered fluid is pressurized to at least 1.5 atmospheres, or at least 2 atmospheres or at least 3 atmospheres.

139. The device, system or method of any preceding claim wherein one or more fluid delivery orifice **525**, or a majority of the fluid delivery orifice(s) **525**, has a width of at most 3 mm, or at most 2 mm or at most 1 mm, or at most 0.5mm, at most 0.3mm, at most 0.2mm and/or that is at most 50% or at most 25% or at most 10% or at most 5% of an average width of the **440** suction orifice(s).

140. The device, system or method of any preceding claim wherein the suction-orifice-displacement-value is at most 2 cm, or at most 1 cm or at most 0.5 cm.

141. The device, system or method of any preceding claim wherein the main body **210** is operative to slidably, snugly and/or internally traverse the connector assembly **158**.

142. The device, system or method of any preceding claim wherein:

- i. negative pressure from suction source(s) **603** induces air flow within the interstitial region; and
- ii. the cleaning device provides a mode whereby a maximum rate of the induced air flow within a distal portion **778** of the interstitial region distal to the inflatable balloon **588** is at most 20% of a maximum rate of the induced air flow in the proximal portion **774**.

143. The device, system or method of any preceding claim wherein all suction lumen(s) are collectively not in fluid communication with any suction orifice located distal to balloon **588**.

144. The device, system or method of any preceding claim wherein:

- i. collectively all suction lumen(s) of the cleaning device are in fluid communication with one or more proximal suction orifice(s) located proximal to balloon **588** and one or more distal orifice(s) located distal to balloon **588**; and
- ii. a ratio between an aggregate surface area of all proximal suction orifice(s) **440** to an aggregate surface area of all distal suction orifice(s) is at least *SURF_AREA_RAT*;
- iii. a value of *SURF_AREA_RAT* is at least 1.5.

145. The device, system or method of claim 144 wherein the value of *SURF_AREA_RAT* is at least 2 or at least 5.

146. The device, system or method of any preceding claim whereby at least one fluid delivery orifice(s) **440** is oriented substantially perpendicularly to a central axis **202** of the main body **210** within an orientation tolerance that is at most 60 degrees, or at most 40 degrees or at most 20 degrees.

147. The device, system or method of any preceding claim whereby at least one fluid delivery orifice(s) **440** is located proximal to balloon **588**.

148. The device, system or method of any preceding claim whereby at least one fluid delivery orifice(s) **440** is located proximal to a distal end **208** of main body **210** by at least 1 cm and/or at least 10% of a length of main body **210**.

149. The device, system or method of any preceding claim whereby at least one fluid delivery orifice(s) **440** is located proximal to a distal end **208** of main body **210** by at least 3 cm and/or at least 20% of a length of main body **210**.

150. The device, system or method of any preceding claim wherein the inflatable balloon **588** is inflatable so as that at least 25% angular positions of the ventilation tube inner surface **201** are contacted by inflatable balloon.

151. The device, system or method of any preceding claim wherein the inflatable balloon **588** is inflatable so as that at least 50% angular positions of the ventilation tube inner surface **201** are contacted by inflatable balloon.

152. The device, system or method of any preceding claim wherein the inflatable balloon **588** is inflatable so as that at least 75% angular positions of the ventilation tube inner surface **201** are contacted by inflatable balloon.

153. The device, system or method of any preceding claim wherein the inflatable balloon **588** is inflatable so as to seal proximal portion **774** of the interstitial region from locations distal **778** to balloon **588**.

154. The device, system or method of any preceding claim wherein balloon **588** is mounted to a distal quarter of main body **210**.

155. The device, system or method of any preceding claim wherein balloon **588** is mounted to a distal tenth of main body **210**.

156. The device, system or method of any preceding claim further comprising a second **586** balloon mounted on main body **210** at a location proximal to inflatable balloon **588**, wherein at least one of the fluid delivery orifice(s) **525** is disposed on a surface of the second balloon **586**.

157. The device, system or method of any of preceding claim wherein:

- i. inflatable balloon **588** is a leaky balloon having one or more surface-located leak holes; and
- ii. one or more of the fluid delivery orifice(s) **525** are leak holes that facing in a direction having a proximal component;
- iii. inflatable balloon is operative to be inflated by pressurized fluid source via fluid delivery lumen(s) ,

158. The device, system or method of claim 157 wherein an average width of all holes in the leaky balloon surface is less than 1 mm.

159. The device, system or method of any of claims 157-158 wherein an aggregate surface area of all holes in the leaky balloon surface is at most 10%, or at most 5%, or at most 2.5%, or at most 1% of a total surface area of inflatable balloon **588**.

160. The device, system or method of any preceding claim wherein the main body is insertable into ventilation tube **60** so that a location of suction orifice(s) and/or fluid delivery orifice(s) is longitudinally displaced from a proximal end **62** of ventilation tube **60** by at least one quarter of a length of the ventilation tube **60**.

161. The device, system or method of any preceding claim wherein the main body is insertable into ventilation tube **60** so that a location of suction orifice(s) and/or fluid delivery orifice(s) is in the distal half of the ventilation tube.

162. The device, system or method of any preceding claim further comprising: a flexible, substantially impermeable sleeve **610** operative to envelop and/or cover at least 5 cm of the elongated flexible main body **210** in locations proximal to the ventilation tube connector assembly **158**,

163. The device, system or method of claim 86 wherein a distal end of the sleeve **610** is directly or indirectly attached to ventilation tube connector assembly **158** so that the main body **210** may slide through the sleeve.

164. The device, system or method of any of claims 162-163 wherein a proximal end of sleeve **610** is configured to have a substantially fixed longitudinal position relative to a proximal end of elongated flexible main body **210**.

165. The device, system or method of any preceding claim wherein the device has a plurality of fluid delivery orifice(s) including first **525A** and second **525B** fluid delivery orifices.

166. The device, system or method of claim 165 wherein both first **525A** and second **525B** fluid delivery orifices are supplied by a common fluid delivery lumen **520**.

167. The device, system or method of claim 165 wherein first **525A** fluid delivery orifice is supplied by a first fluid delivery lumen **520A** and second **525B** fluid delivery orifice is supplied by a second fluid delivery lumen **520B**.

168. The device, system or method of any of claims 166-167 wherein fluid delivery orifice(s) **525** are operative to receive pressurized fluid from pressurized fluid source(s) **602** when a distal end **208** of main body **210** is inserted into ventilation tube **60** so that:

- i. the pressurized fluid is simultaneously forced through first **525A** and second **525B** fluid delivery orifices to respectively produce first **556A** and second **556B** fluid streams that are respectively and simultaneously incident upon an inner surface **201** of the ventilation tube **60** at first **552A** and second **552B** locations; and
- ii. the first **552A** and second **552B** locations are substantially on opposite sides of the ventilation tube **60** inner surface **201** within a stream-location tolerance that is at most 75 degrees.

169. The device, system or method of claim 168 wherein the stream-location tolerance that is at most 45 degrees.

170. The device, system or method of claim 169 wherein the stream-location tolerance that is at most 25 degrees.

171. The device, system or method of any of claims 165-169 wherein:

- i. first fluid delivery orifice **525A** is deployed to a first side of the elongated main body **210**; and
- ii. a second fluid delivery orifice **525B** deployed substantially to a second side of the elongated main body **210** that is on opposite side of main body central axis **202** within a tolerance that is at most 75 degrees or at most 45 degrees or at most 25 degrees.

172. The device, system or method of any preceding claim wherein at least one fluid-delivery-orifice **525** is proximally displaced from inflatable balloon **588** by at most a fluid-orifice-displacement-value that is at most 3 cm, or at most 2 cm.

173. The device, system or method of any of preceding claim further comprising the source(s) of pressurized fluid **602**, wherein immediately before exiting each fluid delivery port **525**, the delivered fluid is pressurized to at least 1.5 atmospheres, or at least 2 atmospheres or at least 3 atmospheres.

174. The device, system or method of preceding claim wherein one or more fluid delivery orifice **525**, or a majority of the fluid delivery orifice(s) **525**, has a width of at most 3 mm, or at most 2 mm or at most 1 mm, or at most 0.5mm, at most 0.3mm, at most 0.2mm and/or that is at most 50% or at most 25% or at most 10% or at most 5% of an average width of the **440** suction orifice(s).

175. The device, system or method of any preceding claim wherein the suction-orifice-displacement-value is at most 2 cm, or at most 1 cm or at most 0.5 cm.

176. The device, system or method of any preceding claim wherein the device lacks suction orifice(s) distal to balloon **588**.

177. The device, system or method of any preceding claim wherein the system lacks suction orifice(s) more distal than the balloon **588** and in fluid communication with suction source **603**.

178. The device, system or method of any preceding claim wherein the combined total aperture area of any and all suction orifices more distal than the balloon **588** and/or open to distal locations **778** is at most 50%, or at most 40%, or at most 30%, or at most 20%, or at most 10% of the combined total aperture area of any and all suction orifices **440** proximal to the balloon **558** and/or open to proximal location(s) **774**.

179. The device, system or method of any preceding claim wherein the combined total aperture area of any and all suction orifices in fluid communication with suction source **603** and more distal than the balloon **588** and/or open to distal locations **778** is at most 50%, or at most 40%, or at most 30%, or at most 20%, or at most 10% of the combined total aperture area of any and all suction orifices **440** in fluid communication with suction source **603** and proximal to the balloon **558** and/or open to proximal location(s) **774**.

180. The device, system or method of any preceding claim wherein at least one of the suction orifice(s) **440** is in fluid communication, via suction lumen **520**, with a blocking construct or blocking element that is distal of at least one suction orifice **440** and that is configured to mostly or completely block fluid communication with a distal opening **519**.

181. The device, system or method of any preceding claim wherein the blocking construct or blocking element comprises a blocking glue or other material introduced onto or into suction lumen **520** and/or comprises a melt construct of a melted inner wall(s) of suction lumen(s) **520**.

182. A method of cleaning a main lumen of an ETT or tracheostomy ventilation tube **60** comprising:

at a time when:

- i. a ventilation machine **900** is connected to the ventilation tube **60** via a tube connector assembly **158** in a substantially air-tight manner;
- ii. an elongate, flexible, main body **210** traverses an interior of the tube connector assembly **158** so that a distal end of the main body **210** is located within the ventilation tube **60** to form an interstitial region outside of the main body **210** and within the ventilator tube;
- iii. a balloon **588** mounted to the main body **210** is located within the ventilation tube **60**;
- iv. sources of pressurized fluid **602** and/or suction **603** are:

A. any one of or both located in a tube-connector-assembly-proximal location outside of the ventilation tube **60** and proximal to tube connector assembly **158**; and

B. are respectively in fluid communication with fluid delivery orifice(s) **525** and suction orifice(s) **440** via fluid delivery lumen(s) **520** and suction lumen(s) **530**,

each of the suction **440** and fluid delivery **525** orifice(s) being:

A. located proximal to balloon **588** within ventilation tube **60**, and

B. on main body **210** or mechanically coupled to main body **210**,

carrying out the following steps:

- g. inflating the balloon **588** mounted to the main body **210** into contact with an inner surface **201** of the ventilation tube **60** so that both the suction **440** and fluid delivery **525** orifice(s) are open to a proximal portion **774** of the interstitial region that is proximal to balloon **588**;
- h. concurrent with a maintaining of the contact by the balloon **588**, forcing pressurized fluid from the pressurized fluid source(s) **602** through the fluid delivery lumen(s) **520** and orifice(s) **525**, into the interstitial region proximal portion **774**;
- i. conveying negative pressure from the suction source(s) **603**, via the suction lumen(s) **530** and orifice(s) **440**, into the proximal portion **774** of the interstitial region.

183. A ballooned cleaning device for use with an ETT or tracheostomy ventilation tube **60**, a ventilator machine **900**, a source(s) **602** of pressurized fluid and a source(s) of suctioning **603**, the cleaning device comprising:

- a. a tube-connector assembly **158** for connecting the ventilation tube **60** to the ventilator machine **900**, in a substantially air-tight manner


- b. an elongate, flexible, main body **210** that is insertable through the tube-connector assembly **158** into the ventilation tube **60** to form an interstitial region outside of the main body **210** within ventilation tube **60**;
- c. a balloon **588** mounted to the main body **210** at a location in the distal half of the main body and inflatable into contact with an inner surface **201** of the ventilation tube **60**;
- d. one or more fluid delivery lumen(s) **520** arranged within or along the elongated main body and operative to transport pressurized fluid, received from pressurized fluid source(s) outside of the ventilation tube **60**, into a proximal portion **774** of the interstitial region that is proximal of the balloon **588** so that the transported fluid enters the proximal portion **774** via fluid delivery orifice(s) **525** located on or mechanically coupled to the main body **210**;
- e. suction lumen(s) **520** arranged within or along the main body and operative to convey negative pressure from suction source(s) **603** into the proximal portion **774** of interstitial region via suction orifice(s) **440** when balloon **588** is inflated into contact, suction orifice(s) **440** being open to the proximal portion **774** and mechanically coupled to the main body **210**.
- f. a suction port **820** connectable to the suction source(s) **603** for mediating a connection between the suction source and the suction lumen(s); and
- g. a pliable sleeve **610** around at least a portion of the main body **210** in locations proximal to the tube-connector assembly **158** and distal to the suction port **820** to inhibit contamination

184. The method of system of any preceding claim wherein the steps of the balloon inflating, forcing of the pressurized fluid and the conveying of the negative pressure are initiated/commenced in any order.

185. The method or system of any preceding claim wherein a mist is delivered via fluid delivery orifice(s) **525** and/or into proximal portion **774** of the interstitial region.


186. The method or system of any preceding claim wherein a liquid is delivered via fluid delivery orifice(s) **525** and/or into proximal portion **774** of the interstitial region.

187. The method or system of any claim 111 wherein the liquid includes gas bubbles within.



Prior Art - Cleaning Chamber
US patent 662219

Fig. 1b (prior art)



Prior Art - US 7273474

Fig. 1a (prior art)




Fig. 1c (Prior Art)







FIG. 1d(prior art)



(a) US 2007/0038226



(c) WO 89/07466



(d) US 2010/0186748

(b) US 2010/0137899

Fig. 2 (prior art)

BACKGROUND ART









FIG. 3A











Examples of Pressurized Fluid Source




Fig. 4E At least one of which supplies pressurized fluid




Fig. 4F




Fig. 5A





FIG. 5B






Fig. 6B




Fig. 6C





Fig. 6D






Fig. 6F




Fig. 6G




Fig. 6H




Fig. 19




FIG. 7A






FIG. 7B








Fig. 10A




Fig. 10B




Fig. 10C





Fig. 11A



Balloon 588 AT
Distal end of the main body

Fig. 11B




Fig. 11C






Fig. 13








Fig. 16A




Fig. 16B




Fig. 16C




Fig. 16D




Fig. 17A





Fig. 17B







Fig. 19A







Fig. 20






Fig. 22




Fig. 23A




Fig. 23B




Fig. 24A




Fig. 24B




Fig. 25




Fig. 26A

**AFTER PARTIAL TOTAL SEALING
OF THE LUMEN DISTAL OPENING**




Fig. 26B




Fig. 26C




Fig. 27

Cause PRESSURIZED FLUID (e.g. liquid and/or gas and/or liquid-gas mixture) (e.g. from a ventilation tube-external source (e.g. a continuous source) that is located outside of the ventilation tube)) to:

Enter **S171**, at a location outside of ventilation tube **(60)**, into a substantially-spanning fluid-delivery lumen **(520)** that substantially spans a length of the elongated main body **(210)**

Travel **S175** through the fluid-delivery lumen(s) **(520)** towards a distally-located orifice(s) **(525)** that is located near the distal end **(208)** of the elongated main body **(210)** but proximal to the inflatable balloon **(588)**

Exit **S179** the fluid-delivery lumen **(525)** via distally-located orifice(s) **(525)** so as to deliver pressurized fluid (e.g. pressurized liquid and/or gas and/or liquid-gas mixture into the more proximal portion **(774)** of the interstitial region (e.g. so as to create a fluid stream **556** (e.g. liquid stream Or gas stream or stream of a liquid-gas mixture) within the more proximal portion **(774))** – for example, to deliver a stream **556** of fluid incident upon an inner wall **(201)** of the ventilation tube **(60)** in the more proximal portion **(774)** near inflatable Balloon **588** and proximal to the sliding obstructing boundary

Fig. 28




Fig. 29