

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
26 August 2004 (26.08.2004)

PCT

(10) International Publication Number
WO 2004/071352 A1

- (51) International Patent Classification⁷: **A61F 2/06**
- (21) International Application Number:
PCT/IE2004/000023
- (22) International Filing Date: 16 February 2004 (16.02.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/447,314 14 February 2003 (14.02.2003) US
- (71) Applicant (for all designated States except US):
SALVIAC LIMITED [IE/IE]; 39-40 Upper Mount
Street, Dublin 2 (IE).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **HORAN, Steven**
[IE/IE]; Carrick, The Pidgeons, Athlone, County West-
meath (IE). **VALE, David** [IE/IE]; 26 The Stiles Road,
Clontarf, Dublin 3 (IE). **MOLLOY, Shane** [IE/IE]; Kilroe,
Corrandulla, County Galway (IE). **BRADY, Earmon**
[IE/IE]; 12 Karol Avenue, Elphin, County Roscommon
(IE). **KEEGAN, Martin** [IE/IE]; 114 Seacrest, Shangort
Road, Knocknacarra, Galway (IE).
- (74) Agents: **O'BRIEN, John, A.** et al.; c/o John A. O'Brien
& Associates, Third Floor, Duncairn House, 14 Carysfort
Avenue, Blackrock, County Dublin (IE).
- (81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.
- (84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,
GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).
- Published:**
— with international search report
— before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: STENT DELIVERY AND DEPLOYMENT SYSTEM



(57) Abstract: A delivery system for delivery and deployment of a self expanding stent (1) especially in an arterial vessel with a tortuous passageway leading thereto comprises a catheter shaft (9) with a distal sheath (6). An inner core (5) is fixed to a larger diameter outer core (10), the difference in diameter providing an abutment. To deploy the stent (1), the sheath (6) is drawn proximally relative to the inner core (5), the proximal end of the stent (1) is engaged by the abutment and the stent (1) expands as it is uncovered by the sheath (6). The system includes a stabiliser tube (25) to which the inner core (5) is fixed, at least during the deployment of the stent (1).

WO 2004/071352 A1

"STENT DELIVERY AND DEPLOYMENT SYSTEM"Introduction

5 The invention relates to a delivery system for delivery and deployment of a stent to a desired vascular location.

Vascular intervention is today undertaken to treat a large number of diseases that had heretofore been treated by surgery. Stents are used widely in a number of applications
10 to provide structural support to vessels that are being treated.

Stents are commonly used in the repair of aneurysms, as liners for vessels, or to provide mechanical support to prevent the collapse of stenosed or occluded vessels. Stents are typically delivered in a compressed state to a specific location inside the
15 lumen of a vessel or other tubular structure, and then deployed at that location in the lumen to an expanded state. A stent has a diameter in its expanded state which is several times larger than the diameter of the stent in its compressed state. Stents are also frequently deployed in the treatment of atherosclerotic stenosis in blood vessels, especially after percutaneous transluminal coronary angioplasty (PTCA) procedures,
20 to improve the results of the procedure and to reduce the likelihood of restenosis.

Stent designs are broadly divided into two categories, balloon expandable stents and self-expanding stents. The invention relates particularly to the delivery and positioning of self-expanding stents. The term self-expanding refers to the inherent
25 material properties of the stent which cause the expansion of the stent once an external constraint has been removed. The effect is most commonly achieved by using a shape memory metallic alloy such as nitinol.

Generally, stents are delivered to the desired location by means of a catheter,
30 specifically referred to as a delivery catheter. Delivery catheters are threaded through

– 2 –

a guiding catheter to the site of the disease and once the correct position has been established by means of fluoroscopic or other imaging method, the stent is deployed.

5 Delivery systems for self expanding stents generally comprise an inner component or core about which the stent is positioned in a retracted or reduced diameter and an outer sheath surrounding the stent. The stent is deployed by retracting the outer sheath relative to the inner component. This has the effect of removing the constraint on the stent which, on release, expands into an increased diameter deployed configuration. The procedure is controlled by a clinician by manipulating various components
10 outside of the vasculature.

Conventional self expanding stent delivery systems suffer from the considerable disadvantage that they are difficult to use, even for a very skilled clinician. The clinician must hold some components steady whilst at the same time manipulating
15 others. Even small irregular movements by the clinician may result in inaccurate deployment at the target site. Inaccurate deployment of a stent may diminish the effectiveness of supporting the vascular wall at the site of deployment.

There is therefore a need for an improved self expanding stent delivery system which
20 will address these problems.

There are particular difficulties in navigating complex stent delivery systems through tortuous arterial passageways, especially a carotid artery, a superficial femoral artery or a renal artery.
25

One objective of the invention is to provide a stent delivery system that is capable of navigating significant tortuosity en route to a target location which can be a significant distance from the catheter entry location.
30

Statements of Invention

According to the invention there is provided a delivery system for delivery and deployment of a self expanding stent to a desired vascular location of a patient, the system comprising;

a catheter shaft having a proximal end and a distal end, the distal end of the shaft defining a reception space for receiving a self expanding stent, the stent having a reduced diameter delivery configuration;

an inner core engagable with the proximal end of the stent;

an operator handle for movement of the catheter shaft relative to the inner core to deploy the self expanding stent;

a stabiliser component;

the inner core being fixed to the stabiliser component, at least during deployment of the self expanding stent.

In one embodiment the inner core has an abutment which is engagable with the proximal end of the stent to deploy the stent. The inner core may have a reduced diameter distal portion extending distally of the abutment at least partially through the stent in the reduced diameter delivery configuration of the stent. The inner core may form a tubular member in the region of abutment. The inner core may have a high compressive stiffness. The inner core may be of a composite, or a metallic construction.

In one embodiment the catheter shaft comprises a distal sheath and a stent is frictionally coupled to the distal sheath in the delivery configuration. The inner core may have an abutment which is engagable with the proximal end of the stent to decouple the stent and distal sheath to deploy the stent.

- 4 -

In another embodiment the catheter shaft comprises a distal sheath portion and a proximal shaft portion, the diameter of the proximal shaft portion being smaller than the diameter of the distal sheath portion. The stabiliser component may be disposed
5 over the smaller diameter proximal shaft. The stabiliser may comprise a tube and the diameter of the stabiliser tube is not greater than the diameter of the distal sheath of the catheter shaft.

The catheter shaft may have a guidewire exit port which is located proximally of the
10 distal end of the catheter shaft. The guidewire exit port may be located proximally of the stent and/or proximally of the delivery sheath.

In one case the guidewire exit port is located at a transition between the distal sheath and the reduced diameter proximal shaft portion. The guidewire exit port may be
15 located distally of the stabiliser component.

In one embodiment the guidewire exit port is configured to exit along an axis that is substantially parallel to a longitudinal axis of the distal sheath.

In another embodiment the system comprises a guidewire and the sum of the diameter
20 of the guidewire and the diameter of the proximal shaft is less than the diameter of the distal sheath.

In one case the sum of the diameter of the guidewire and the diameter of the stabiliser
25 component is less than the diameter of the distal sheath.

In one embodiment the inner core comprises a large diameter distal segment , a reduced diameter proximal segment , and a transition segment between the distal and proximal segments. The transition segment may be proximal of the abutment region.
30 The transition segment may be distal of the exit port.

– 5 –

In one embodiment the stent directly engages the distal sheath and is slidable relative to the sheath. The distal sheath may be a composite with a low friction inner surface. In one case the distal sheath is reinforced to withstand the radial stresses of the stent in its constrained reduced diameter configuration.

5

In one embodiment the inner core is fixed to a component of the delivery system.

The component of the system to which the inner core is fixed may comprise the handle.

10

In one case the stabiliser component is fixed to a procedural catheter. In this case a haemostasis gasket may be provided between the stabiliser component and the procedural catheter.

15

Alternatively the catheter is an introducer sheath. The introducer sheath may have an integral haemostasis gasket.

Alternatively the procedural catheter is a guide catheter which may have a haemostasis gasket attachment. The gasket may be adjustable by the operator. The gasket attachment may be a Touhy Borst.

20

In one embodiment the system comprises a procedural guidewire and the guidewire is fixed or fixable to the stabiliser component.

25

In another embodiment the stabiliser component is length adjustable. The stabiliser component may comprise at least two parts which are movable relative to one another.

The stabiliser component position may be adjustable. For example, the stabiliser component may be adjusted by rotation of a threaded element which provides a position control device.

30

- 6 -

In one embodiment an intermediate component is provided between the stabiliser component and the inner core. The intermediate component may comprise the handle. The intermediate component may comprise at least one bridging piece. The bridging piece may extend through the wall of the proximal shaft. The bridging piece may project laterally of the inner core and/or the stabiliser component. In one case the bridging piece projects radially between the inner core and the stabiliser component.

In another embodiment the stabiliser component and the inner core are directly mounted to one another. The stabiliser component may be melded to the inner core, for example, by a welding, gluing, joining, laminating, or bonding process.

In another embodiment the stabiliser component and the inner core are directly mounted to one another proximal of the distal outer sheath. The stabiliser component and the inner core may be directly mounted to one another proximal of the outer shaft.

In a further embodiment the system includes a guidewire and the guidewire extends at least the length of the catheter shaft. In one case, the inner core defines a guidewire lumen along the length thereof.

The system may include a lock for the guidewire. The lock may be located proximal of the handle.

In another embodiment the stabiliser component comprises a tubular element and the tubular element has a tapered distal end.

In a further embodiment the system includes a guidewire and the guidewire is located within the profile of the stabiliser component

The stabiliser component may have a proximal opening to allow backflow of blood.

- 7 -

In another embodiment the stabiliser component extends substantially the length of the catheter shaft.

5 In another aspect the system provides a delivery system for delivery and deployment of a self expanding stent to a desired vascular location of a patient, the system comprising:

10 a catheter shaft having a proximal end and a distal end, the distal end of the shaft defining a reception space for receiving a self expanding stent, the stent having a reduced diameter delivery configuration;

an inner core engagable with the proximal end of the stent;

15 an external mounting for the inner core; and

an operator actuating element for the catheter shaft;

20 the operator actuating element being movable proximally of the external mounting for movement of the catheter shaft relative to the inner core to deploy the self expanding stent.

25 In one embodiment the operator handle is a pull handle for pulling the catheter shaft proximally relative to the inner core to deploy the self expanding stent. The catheter shaft and the operating handle may be interconnected by a connector. The connector may extend proximally of the external mounting. The connector may extend through the external mounting. The connector may comprise an elongate member such as a pull wire.

30 In one embodiment the inner core is fixed internal of the external mounting. A guidewire exit port may be provided at the proximal end of the external mounting.

- 8 -

In another aspect the invention provides a method for delivery and deployment of a self expanding stent comprising the steps of:

5 providing a delivery system comprising a catheter shaft having a proximal end and a distal end, the distal end of the shaft defining an outer sheath having a reception space for receiving a self expanding stent, the stent having a reduced diameter delivery configuration;

10 an inner core engaging the proximal end of the stent;

an operator handle for movement of the catheter shaft relative to the inner core to deploy the self expanding stent;

15 introducing the delivery system into a vasculature of a patient;

delivering the stent delivery catheter to a region of interest;

fixing the inner core relative to the stabiliser component; and

20 deploying the self expanding stent by engaging the inner core with the proximal end of the stent.

25 In one embodiment the stent is deployed by sliding the outer sheath and stent proximally to engage the inner core with the proximal end of the stent, the inner core engagement frictionally decoupling the stent and the sheath to deploy the stent.

In one case the stent is frictionally coupled to the outer sheath in the delivery configuration.

30 The method may comprise:

– 9 –

introducing a procedural guidewire into the vasculature;

advancing the guidewire to a region of interest; and

5 advancing the delivery system over the procedural guidewire.

In one embodiment the method is of the rapid exchange type.

In one case the method comprises the steps of:

10

 providing an embolic protection filter; and

 deploying the filter distal of the region of interest, in advance of introduction
of the delivery system.

15

The filter may be mounted on the guidewire or mountable to the guidewire.

In one embodiment the region of interest is a region of stenosis in an arterial vessel
having a tortuous passageway leading thereto. The arterial vessel may typically be a
20 carotid artery, a superficial femoral artery, or a renal artery.

In one embodiment the inner core is fixed relative to a component of the system. The
component may be a guide catheter. The component may be a Touhy Borst.

25

In one embodiment the system comprises a stabiliser fixed at a proximal end to the
handle and the method comprises fixing the stabiliser to a component of the system.
In this case, the method may comprise fixing the distal end of the stabiliser to a guide
catheter. The method may comprise fixing the distal end of the stabiliser to a Touhy
Borst.

30

– 10 –

In a further aspect the invention provides a method for delivery and deployment of a self expanding stent comprising the steps of:

providing a delivery system providing:

5

a catheter shaft having a proximal end and a distal end, the distal end of the shaft defining a reception space for receiving a self expanding stent, the stent having a reduced diameter delivery configuration;

10

an inner core engagable with the proximal end of the stent;

an external mounting for the inner core; and

an operator actuating element for the catheter shaft; and

15

moving the operating actuating element proximally of the external mounting to move the catheter shaft relative to the inner core to deploy the stent.

In one embodiment the operator handle is a pull handle and the catheter shaft is pulled proximally of the inner core to deploy the stent.

20

Brief Description of the Drawings

The invention will be more clearly understood from the following description thereof given by way of example only in which:-

25

Fig.1 is a side view of a stent delivery system of the invention;

30

Fig. 2 is an enlarged view of one region of Fig. 1;

- 11 -

Fig. 3 is an enlarged view of another region of Fig. 1;

Fig. 4 is a diagrammatic view of the delivery system of the invention in position in a tortuous anatomy of a patient;

5

Fig. 5 is an enlarged cross sectional view of one region of Fig. 4;

Fig. 6 is an enlarged cross sectional view of another region of Fig. 4;

10

Figs. 7(a) to 7(e) are diagrammatic side, partially cross sectional views illustrating various steps in using the stent delivery system of the invention;

Figs. 8(a) to 8(g) are diagrammatic side, partially cross sectional view illustrating various steps in a method of the invention;

15

Figs. 9(a) is a side view of the delivery system with a stent at a desired location constrained in a sheath;

Fig. 9(b) is a side view similar to Fig. 9(a) with the stent deployed;

20

Fig. 10 is a diagrammatic view of the delivery system in position in a patient;

Fig. 11 is an enlarged view of an indicated distal end region of the delivery system of Fig. 10;

25

Fig. 12 is an enlarged view of an indicated proximal end region of the delivery system of Fig. 10;

30

Figs. 13(a) to 13(c) are side cross sectional views of a proximal end of the delivery system in different positions of use;

- 12 -

Fig. 14 is a side view of an over the wire stent delivery system of the invention;

5 Fig. 15 is a side view of another over the wire stent delivery system of the invention;

Fig. 16 is a side cross sectional view of a proximal end of the delivery system of Fig. 15;

10 Fig. 17 is a view similar to Fig. 16 of a rapid exchange version of the delivery system;

Fig. 18 is a side, partially cross sectional view of an alternative delivery system in which a stabiliser comprises telescoping parts;

15 Fig. 19 is a side, partially cross sectional view of another delivery system in which a stabiliser is provided with a port;

Fig. 20 is a perspective view of a delivery system in which an outer sheath is accessed through a slot in the stabiliser;

20 Fig. 21 is a side, partially cross sectional view of a delivery system in which an outer sheath is accessed through a port at a proximal end of the system;

25 Fig. 22 is a side, partially cross sectional view of a delivery system in which a stabilising tube has a relatively small diameter;

Fig. 23 is a transverse cross sectional view at a proximal end of a delivery system in which the guidewire is not clamped on tightening of a Touhy Borst fitting;

30

- 13 -

Fig. 24 is a side partially cross sectional view of another delivery system with a stabiliser tube having a tapered distal end;

Fig. 25 is a perspective view of another delivery system of the invention;

5

Fig. 26 is a side, partially cross sectional view of a distal end of the delivery system of Fig. 25, in use;

10

Figs. 27 and 28 are side views of an alternative delivery system including a position control device; and

Fig. 29 is a cross sectional view of portion of another delivery system of the invention.

15

Detailed Description

20

Referring to the drawings and initially to Figs. 1 to 13 thereof there illustrated a delivery and deployment system for a self expanding stent 1. The system is in this case configured for use with a guidewire 2 of the rapid exchange type with a distal tip 3.

25

The system comprises an inner core 5 about which the stent 1 is located and a catheter shaft 9 having a distal sheath 6 which retains the stent 1 in a compressed configuration during delivery through the vasculature of a patient to a deployment site as illustrated for example in Fig. 9(a). To deploy the stent 1 the sheath 6 is drawn proximally relative to the inner core 5 and the stent expands into a deployed configuration as illustrated, for example in Fig. 9(b). The sheath 6 has a rapid exchange guidewire exit port 7.

– 14 –

The delivery system has a distal tip 8 with a guidewire lumen 8a. Marker bands 1a, 1b are provided for visualisation of the inner core 5 at the proximal and distal ends of the stent 1.

5 The inner core 5 is fixed to a larger diameter outer core 10, the difference in diameter providing a step or abutment 5a for engagement with the stent 1 for deployment. The inner and outer core 5, 10 are fixed to a handle 12 at the proximal end. The outer distal sheath 6 is connected to a catheter shaft 9 at the distal end and the catheter shaft 9 is connected at the proximal end to a deployment/actuating mechanism which in this case is operated by an actuator in this case in the form of a thumbscrew 11, rotation of
10 the screw 11 being converted into linear movement of the sheath 6.

The stent 1 is frictionally coupled to the inside wall of the distal sheath 6 in the delivery configuration. In use, the inner core 5 abutment is engagable with the proximal end of the stent to decouple the stent 1 and the sheath 6 to enable the stent to
15 be deployed. This, on sliding of the outer sheath 6 and stent 1 proximally the abutment of the inner core 5 is engaged with the stent 1 to frictionally decouple the stent 1 and sheath 6 to deploy the stent 1.

20 The catheter shaft 9 and the guidewire 2 in this case extend through a standard Touhy Borst fitting 20.

In the invention, the inner core 5 is locked relative to any suitable fixed location of the delivery system. In this case the delivery system comprises a stabiliser in the form of a stabiliser tube 25. The stabiliser 25 is clamped with an O-ring / seal 26 to the Touhy
25 Borst 20 which in turn is fixed to the handle 12. The stabiliser tube 25 is thereby fixed relative to the inner core 5 which controls the position of the stent 1 as it is deployed.

The stabilising tube 25 has sufficient hoop stiffness in the region at which it is clamped down by the Touhy Borst 20 so that it does not interfere with the outer sheath
30 6 or catheter shaft 9 as the stent 1 is deployed. In addition, the stabilising tube 25 has

- 15 -

a bending stiffness so that it is flexible enough so that the handle 12 may be used at an angle to the Touhy Borst 20 but stiff enough so that the stent may be deployed even if the tube is in a bent configuration. The internal surface of the stabiliser tubing 25 has a low frictional surface to allow the outer sheath 6 to move relative to the stabilising tube 25 without affecting the deployment force of the stent 1. The external surface of the stabiliser tubing 25 may have sufficiently low friction so that the stent 1 may be repositioned without opening the Touhy Borst 20. However the tubing would not have so low a friction that the repositioning could happen unintentionally. The stabiliser tube 25 is of a low wall thickness, typically less than 0.008 inches, preferably less than 0.006 inches, and especially less than 0.003 inches. It may be manufactured from any suitable high performance material such as PEEK (Polyether ketane); polyamide, Nylons such as Nylon 6, Nylon 66, Nylon 610, polyimide, PEK (Polyether ketane); reinforced polymeric system such as braided systems, covered spring. In rapid exchange systems the stabiliser may be of PEEK or the like. In over the wire systems the stabiliser may be of polyamide or the like.

The invention provides a delivery system which is stabilised to facilitate accurate deployment of a self expanding stent 1 at a desired location. The stabilisation is in this case achieved by fixing the inner core 5 to the Touhy Borst 20. The Touhy Borst 20 is connected to a guide catheter 30 which in turn is fixed to the patient's body. In the arrangement of Figs. 1 to 6 the stabiliser 25 comprises a tube that is connected to the inner core 5 at the proximal end and extends over the outer sheath 9. This allows the tube 25 to be fixed relative to the guide catheter 30 by tightening the Touhy Borst 20. As the outer sheath 9 is retracted the inner core 5 remains fixed relative to the patient. The inner core 5 holds the stent 1 in the same position throughout the deployment and thus an accurate deployment is achieved.

In use, an artery is accessed using a standard Seldenger technique. A short introducer sheath 29 is inserted at the access point to protect the artery at the proximal end. A dilator is then used to open the entry and a guidewire is introduced. A guide catheter 30 is then introduced over the guidewire and a Touhy Borst 20 is attached to the

- 16 -

proximal end of the guide catheter 30. A procedural guidewire which is typically a 14 thou wire is introduced in a rapid exchange mode with a typical length of 190cm or, in on over the wire mode with a length of 320cm. An embolic protection filter may be introduced over the procedural guidewire and deployed distal of a site of interest. In
5 the case of a lesion, the site may be pre-dilated using a balloon technique. The stent delivery catheter of the invention is then introduced and tracked over the guidewire to the location of interest. The sheathed stent is positioned relative to the target site. The Touhy Borst 20 is then locked to the stabiliser tube 25. With the stent 1 locked to the guide catheter 30 stent deployment is initiated, for example by moving the sheath 6
10 proximally relative to the inner core 5. The stent 1 is accurately deployed and the delivery system is then removed leaving the stent 1 in place.

The delivery system may be used with an embolic protection filter 35 of the type described in our WO 99/23976, the entire contents of which are hereby incorporated
15 by reference. The method involved is illustrated in Figs. 8(a) to 8(g). In this case a filter 35 is deployed distal of the site of interest (such a region of stenosis). The filter 35 may be mounted on a guidewire or may be delivered over a pre-advanced guidewire. The filter 35 is delivered in a collapsed form using a delivery catheter. The filter 35, on exiting the delivery catheter 36 self-expands or is expandable into the
20 expanded deployed configuration located distal of the site of interest. Any embolic material which is dislodged during subsequent procedures such as a balloon angioplasty or a stent deployment is captured in the filter 35. On completion of the procedure the filter (with any captured emboli) is retracted into an at least partially retracted configuration and withdrawn from the vasculature, for example using a
25 retrieval catheter.

In the embodiments of the invention illustrated in Figs. 1 to 13 a rapid exchange configuration is used. In this case the guidewire may be clamped between the stabiliser 26 and a Touhy Borst 20. The position of the guidewire is therefore fixed
30 relative to the Touhy Borst 20 and the guide catheter 30.

- 17 -

Referring to Figs. 14 to 16 the stabiliser 25 may also be used in association with an over the wire stent delivery system. In this case a locking mechanism 40 may be provided, for example at the proximal end of the handle 12 to lock the guidewire 41 position. The locking mechanism 40 may, for example, include a collet type arrangement.

The invention provides a stent delivery system that is of very low profile, excellent deliverability, and which can be used for very accurate placement of a self expanding stent in a tortuous arterial anatomy. It is suitable for deployment of a stent in a diseased vessel that may have a very significant reduction in lumen diameter. This reduction in lumen diameter may be as a result of atherosclerotic material on the vessel wall or it may be a hyperplasia response to injury. The stent may be deployed in vessels which have tortuous passageways leading thereto. Such vessels include a carotid artery, a superficial femoral artery or a renal artery.

Another rapid exchange system is shown in Fig. 17.

Referring now to Fig. 18 the stabiliser component 25 may comprise two or more telescoping parts 50, 51. This feature minimises the length of the stabiliser that needs to be inserted into the Touhy Borst 20 and prevents the stabiliser 25 from being inserted into the guide catheter 30.

Referring to Fig. 19 the stabiliser 25 in this case has a side port 55 distal of the handle 12. The side port 55 allows any backflow of blood from the guide catheter/Touhy Borst 20 to be vented prior to the handle 12. The side port 55 may have a standard female Luer adapter to provide additional means of injecting contrast media or other fluids into the guide catheter 30.

Fig. 20 shows a schematic of another embodiment of the invention. This figure shows the tubular housing 25 acting as both a stabilising tube and a user handle. The proximal section of tubular housing 25 remains outside the guide catheter or sheath

- 18 -

while the distal end enters the sheath. The portion of tubular housing 25 proximal to the gasket 21 may be gripped by the user. A deployment pin 66 moves in slot 65 to deploy the stent. The gasket 21, of either the sheath or Touhy Borst (not shown), grips the outer surface of housing 25 and fixes the position of the stent during deployment.

5 It will be appreciated that tubular housing 25 may extend much more distally of valve 21 than is shown in this schematic.

Deployment pin 66 is connected to catheter shaft 6. When the deployment pin 66 is moved proximally in the slot 65, the catheter shaft 6 slides proximally relative to the inner core 5. The inner core 5 engages the proximal end of the stent 1 and the stent 1 is restrained axially as the sheath is deployed.

10

In Fig. 21 there is illustrated an arrangement in which the stabiliser tube 25 has a proximal end port 68 through which a connector 69 extends. The connector 69 is connected to the outer sheath 6 at one end and has a proximal end operator actuating element 70. In use, the stabiliser tube 25 and/or the associated external mounting for the inner core 5 is held stationary while the operator actuating element is pulled back proximally from the mounting. The connector 69, which in this case extends through the proximal wall of the mounting and is in the form of a pull wire, connects the pull handle 75 to the outer sheath 6 of the catheter shaft and pulling on the handle 75 results in a corresponding retraction of the sheath 6 to expose the stent 1, on deployment. The action of the user corresponds to the action of the sheath and is therefore easy and intuitive for a clinician. The external mounting is stationary whilst the pull handle 75 is pulled proximally. This system may or may not include a suitable stabiliser component as described in any of the embodiments or drawings herein.

15

20

25

Referring to Fig. 22 a stabiliser 25 has an outside diameter d_2 that is less than the diameter d_1 of the distal end of the delivery system. Thus, the addition of the stabiliser 25 does not affect the profile of the system. This is an important feature in ensuring a low profile system and may be applied to all embodiments of the invention.

30

- 19 -

In Fig. 22 the abutment or step which is engaged against the proximal end of the stent 1 is illustrated as a simple lateral projection 5a on the inner core 5. Many other possibilities exist including those referred to in the various embodiments of the invention described and illustrated therein.

Fig. 23 illustrates an embodiment in which a stabiliser 80 has an elongate opening 82 to receive a guidewire 81. This arrangement is particularly suitable for rapid exchange. The wall thickness of the stabiliser 80 may be larger than the diameter of the guidewire 81 and the slot or gap 82 in the wall ensures that the guidewire is not clamped when the Touhy Borst 20 is tightened.

Referring to Fig. 24, a stabilising tube 90 may have a tapered distal end 91 to provide a smooth transition as the stabiliser 90 is inserted into a Touhy Borst 20.

In Figs. 25 and 26 there is illustrated another stent delivery system according to the invention for a stent 100. The delivery system comprises an inner core 101, a retractable middle sheath 102, a stent delivery outer 103 and a guide catheter 104. Conventional 2-layer systems do not make it easy for the user to hold the stent and inner core in a fixed position while retracting the outer layer to deploy the stent. Friction between the outer layer and the guide catheter and its fittings also hinder smooth deployment. In this embodiment of the invention a 3-layer delivery system is provided and the outer layer of the device which the user sees and holds remains in a fixed position relative to the guide catheter. The stent is deployed by operating a simple actuator (push/pull/trigger/rotate) 105 which retracts the middle sheath 102 relative to the outer layer 103 and inner core 101. In this case the stabiliser extends up to the sheath. This avoids the necessity for a lock at the proximal end. The stabiliser itself may have a distal region for a pod.

It will be noted that in this case the stabiliser component extends substantially the length of the catheter shaft. The stabiliser component can terminate a short distance

- 20 -

(twice the length of the stent) from the distal end of the catheter shaft. The stabiliser is sufficiently long that it generates a lot of friction with the inner (such as a guide catheter and/or catheter shaft). Thus, the stabiliser component will stay substantially stationary, in use, during stent deployment.

5

Referring to Figs. 27 and 28 there is illustrated another stent deployment system which is similar to that of Fig. 9 and like parts are assigned the same reference numerals. In this case the system has a position control device 120. The delivery catheter is advanced to the deployment site, causing the stabiliser 25 to enter the Touhy Borst 20 which is tightened to the stabiliser 25. The guidewire 2 is clamped between the stabiliser 25 and the Touhy Borst 20 thereby fixing the position of the tip 3 and the guidewire 2 relative to the Touhy Borst 20 and guide catheter. The position control device 120 allows readjustment of the catheter tip 3 before deployment without the necessity of opening the Tuohy Borst. The control device 120 may be used to move the handle (and hence the inner core assembly and stent position) proximally or distally relative to the guide catheter. The control device 120 may be implemented, for example, as a thumbscrew located on the same axis as that of the stabiliser 25. It may also be implemented as a push/pull mechanism. A user may use one hand on the handle with the free hand operating the position control device 120. The user may also open the Tuohy Borst and then readjust the position of the catheter, without necessarily using the position control device. The advantage of the position control device 120 is that it can be used to increase deployment accuracy as small adjustments may be made to the position of the inner core/outer core (and hence the position of the stent) prior to deployment and/or during deployment up to the stage at which the stent contacts a vessel wall without the necessity of opening the introducer valve.

25

Fig. 29 is a cross sectional view of a stent deployment system with an inner member 150 such as a tube or a wire and a catheter shaft 151. The shaft 151 has through slots 152 through which a connector 153 extends between the inner member 150 and a stabiliser tube 157. The stabiliser tube 157 is engaged with a gasket 158. The connector 153 fixes the inner member 150 to the stabiliser tube 157 even though there

30

- 21 -

is not necessarily any connection between the stabiliser tube and the handle (not shown). The slots 152 facilitate relative movement between the inner member 150 and the shaft 151 for stent deployment.

5 The stabiliser component used in the invention has an added advantage of creating an anti-backbleed feature. With the current set-up the Touhy Borst is required to be open so that the sheath can be retracted, this leads to the loss of blood through the Touhy Borst. This is prevented with the stabiliser as the Touhy Borst is tightened preventing the loss of blood. The blood is prevented from flowing down through the gap between
10 the stabiliser and the catheter shaft because the gap between the tubes is very small and because the length of the stabiliser is long enough so that it resists the blood flow down the gap between the tubes.

The invention is not limited to the embodiments hereinbefore described which may by
15 varied in detail.

20

25

30

Claims

1. A delivery system for delivery and deployment of a self expanding stent to a
5 desired vascular location of a patient, the system comprising;
- a catheter shaft having a proximal end and a distal end, the distal end of
the shaft defining a reception space for receiving a self expanding stent,
the stent having a reduced diameter delivery configuration;
- 10 an inner core engagable with the proximal end of the stent;
- an operator handle for movement of the catheter shaft relative to the
inner core to deploy the self expanding stent;
- 15 a stabiliser component;
- the inner core being fixed to the stabiliser component, at least during
deployment of the self expanding stent.
- 20
2. A delivery system as claimed in claim 1 wherein the inner core has an
abutment which is engagable with the proximal end of the stent to deploy the
stent.
- 25
3. A delivery system as claimed in claim 2 wherein the inner core has a reduced
diameter distal portion extending distally of the abutment at least partially
through the stent in the reduced diameter delivery configuration of the stent.
- 30
4. A delivery system as claimed in claim 3 wherein the inner core forms a tubular
member in the region of abutment.

- 23 -

5. A delivery system as claimed in claim 4 wherein the inner core has high compressive stiffness.
6. A delivery system as claimed in claim 5 wherein the inner core is of a composite, or a metallic construction.
7. A delivery system as claimed in claim 1 wherein the catheter shaft comprises a distal sheath and a stent is frictionally coupled to the distal sheath in the delivery configuration.
8. A delivery system as claimed in claim 7 wherein the inner core has an abutment which is engagable with the proximal end of the stent to decouple the stent and distal sheath to deploy the stent.
9. A delivery system as claimed in any of claims 1 to 8 wherein the catheter shaft comprises a distal sheath portion and a proximal shaft portion, the diameter of the proximal shaft portion being smaller than the diameter of the distal sheath portion.
10. A delivery system as claimed in claim 9 wherein the stabiliser component is disposed over the smaller diameter proximal shaft.
11. A delivery system as claimed in claim 10 wherein the stabiliser comprises a tube and the diameter of the stabiliser tube is not greater than the diameter of the distal sheath of the catheter shaft.
12. A delivery system as claimed in any of claims 9 to 11 wherein the catheter shaft has a guidewire exit port which is located proximally of the distal end of the catheter shaft.

- 24 -

13. A delivery system as claimed in claim 12 wherein the guidewire exit port is located proximally of the stent.
- 5 14. A delivery system as claimed in claim 12 or 13 wherein the guidewire exit port is located proximally of the delivery sheath.
- 10 15. A delivery system as claimed in any of claims 12 to 14 wherein the guidewire exit port is located at a transition between the distal sheath and the reduced diameter proximal shaft portion.
16. A delivery system as claimed in any of claims 12 to 15 wherein the guidewire exit port is located distally of the stabiliser component.
- 15 17. A delivery system as claimed in any of claims 12 to 16 wherein the guidewire exit port is configured to exit along an axis that is substantially parallel to a longitudinal axis of the distal sheath.
- 20 18. A delivery system as claimed in claim 1 wherein the system comprises a guidewire and the sum of the diameter of the guidewire and the diameter of the proximal shaft is less than the diameter of the distal sheath.
- 25 19. A delivery system as claimed in claim 1 wherein the sum of the diameter of the guidewire and the diameter of the stabiliser component is less than the diameter of the distal sheath.
- 30 20. A delivery system as claimed in claim 1 wherein the inner core comprises a large diameter distal segment , a reduced diameter proximal segment , and a transition segment between the distal and proximal segments.

- 25 -

21. A delivery system as claimed in claim 20 wherein the transition segment is proximal of the abutment region.
22. A delivery system as claimed in claim 20 wherein the transition segment is distal of the exit port.
23. A delivery system as claimed in claim 1 wherein the stent directly engages the distal sheath and is slidable relative to the sheath.
24. A delivery system as claimed in claim 23 wherein the distal sheath is a composite with a low friction inner surface
25. A delivery system as claimed in claim 24 wherein the distal sheath is reinforced to withstand the radial stresses of the stent in its constrained reduced diameter configuration.
26. A system as claimed in any of claims 1 to 25 wherein the inner core is fixed to a component of the delivery system.
27. A system as claimed in any of claims 1 to 26 wherein the component of the system to which the inner core is fixed comprises the handle.
28. A system as claimed in any of claims 1 to 27 wherein the stabiliser component is fixed to a procedural catheter.
29. A system as claimed in claim 28 wherein a haemostasis gasket is provided between the stabiliser component and the procedural catheter.
30. A system as claimed in claim 28 wherein the catheter is an introducer sheath.

- 26 -

31. A system as claimed in claim 30 wherein the introducer sheath has an integral haemostasis gasket.
- 5 32. A system as claimed in claim 28 wherein the procedural catheter is a guide catheter.
33. A system as claimed in claim 32 wherein the guide catheter has a haemostasis gasket attachment.
- 10 34. A system as claimed in claim 33 wherein the gasket is adjustable by the operator.
35. A system as claimed in claim 34 wherein the gasket attachment is a Touhy Borst.
- 15 36. A system as claimed in any of claims 1 to 35 wherein the system comprises a procedural guidewire and the guidewire is fixed or fixable to the stabiliser component.
- 20 37. A system as claimed in any of claims 1 to 36 wherein the stabiliser component is length adjustable.
38. A system as claimed in any of claims 1 to 37 wherein the stabiliser component comprises at least two parts which are movable relative to one another.
- 25 39. A system as claimed in claim 1 wherein the stabiliser component position is adjustable.
40. A system as claimed in claim 39 wherein the stabiliser component is adjusted by rotation of a threaded element which provides a position control device.
- 30

- 27 -

41. A system as claimed in any of claims 1 to 40 wherein an intermediate component is provided between the stabiliser component and the inner core.
- 5 42. A system as claimed in claim 41 wherein the intermediate component comprises the handle.
43. A system as claimed in claim 41 wherein the intermediate component comprises at least one bridging piece.
- 10 44. A system as claimed in claim 43 wherein the bridging piece extends through the wall of the proximal shaft.
45. A system as claimed in claim 44 wherein the bridging piece projects laterally of the inner core and/or the stabiliser component.
- 15 46. A system as claimed in claim 45 wherein the bridging piece projects radially between the inner core and the stabiliser component.
47. A system as claimed in claim 1 wherein the stabiliser component and the inner core are directly mounted to one another.
- 20 48. A system as claimed in claim 47 wherein the stabiliser component is melded to the inner core.
- 25 49. A system as claimed in claim 48 wherein the stabiliser component is melded by a welding, gluing, joining, laminating, or bonding process.
- 30 50. A system as claimed in claim 47 to 49 wherein the stabiliser component and the inner core are directly mounted to one another proximal of the distal outer sheath .

- 28 -

51. A system as claimed in claim 50 wherein the stabiliser component and the inner core are directly mounted to one another proximal of the outer shaft.
52. A system as claimed in claim 1 wherein the system includes a guidewire and the guidewire extends at least the length of the catheter shaft.
53. A system as claimed in claim 52 wherein the inner core defines a guidewire lumen along the length thereof.
54. A system as claimed in claim 52 or 53 wherein the system includes a lock for the guidewire.
55. A system as claimed in claim 54 wherein the lock is located proximal of the handle.
56. A system as claimed in claim 1 wherein the stabiliser component comprises a tubular element and the tubular element has a tapered distal end.
57. A system as claimed in claim 1 wherein the system includes a guidewire and the guidewire is located within the profile of the stabiliser component.
58. A system as claimed in claim 1 wherein the stabiliser component has a proximal opening to allow backflow of blood.
59. A system as claimed in claim 1 wherein the stabiliser component extends substantially the length of the catheter shaft.
60. A delivery system for delivery and deployment of a self expanding stent to a desired vascular location of a patient, the system comprising:

– 29 –

a catheter shaft having a proximal end and a distal end, the distal end of the shaft defining a reception space for receiving a self expanding stent, the stent having a reduced diameter delivery configuration;

5 an inner core engagable with the proximal end of the stent;

an external mounting for the inner core; and

an operator actuating element for the catheter shaft;

10

the operator actuating element being movable proximally of the external mounting for movement of the catheter shaft relative to the inner core to deploy the self expanding stent.

15 61 A delivery system as claimed in claim 60 wherein the operator handle is a pull handle for pulling the catheter shaft proximally relative to the inner core to deploy the self expanding stent.

20 62 A delivery system as claimed in claim 60 or 61 wherein the catheter shaft and the operating handle or interconnected by a connector.

63 A delivery system as claimed in claim 62 wherein the connector extends proximally of the external mounting.

25 64 A delivery system as claimed in claim 63 wherein the connector extends through the external mounting.

65 A delivery system as claimed in any of claims 62 to 64 wherein the connector comprises an elongate member.

30

– 30 –

- 66 A delivery system as claimed in claim 65 wherein the elongate member comprises a pull wire.
- 5 67 A delivery system as claimed in any of claims 60 to 66 wherein the inner core is fixed internal of the external mounting.
- 68 A delivery system as claimed in any of claims 60 to 66 wherein a guidewire exit port is provided at the proximal end of the external mounting.
- 10 69 A method for delivery and deployment of a self expanding stent comprising the steps of:
- 15 providing a delivery system comprising a catheter shaft having a proximal end and a distal end, the distal end of the shaft defining an outer sheath having a reception space for receiving a self expanding stent, the stent having a reduced diameter delivery configuration;
- an inner core engaging the proximal end of the stent;
- 20 an operator handle for movement of the catheter shaft relative to the inner core to deploy the self expanding stent;
- introducing the delivery system into a vasculature of a patient;
- 25 delivering the stent delivery catheter to a region of interest;
- fixing the inner core relative to the stabiliser component; and
- 30 deploying the self expanding stent by engaging the inner core with the proximal end of the stent.

– 31 –

- 70 A method as claimed in claim 69 wherein the stent is deployed by sliding the outer sheath and stent proximally to engage the inner core with the proximal end of the stent, the inner core engagement frictionally decoupling the stent and the sheath to deploy the stent.
- 5
- 71 A method as claimed in claim 69 or 70 wherein the stent is frictionally coupled to the outer sheath in the delivery configuration.
- 72 A method as claimed in any of claims 69 to 70 comprising:
- 10
- introducing a procedural guidewire into the vasculature;
- advancing the guidewire to a region of interest; and
- 15
- advancing the delivery system over the procedural guidewire.
- 73 A method as claimed in claim 72 wherein the method is of the rapid exchange type.
- 20
- 74 A method as claimed in any of claims 69 to 73 comprising the steps of:
- providing an embolic protection filter; and
- deploying the filter distal of the region of interest, in advance of
- 25
- introduction of the delivery system.
- 75 A method as claimed in claim 74 wherein the filter is mounted on the guidewire.
- 30
- 76 A method as claimed in claim 74 wherein the filter is mountable to the guidewire.

- 77 A method as claimed in any of claims 69 to 76 wherein the region of interest is a region of stenosis in an arterial vessel having a tortuous passageway leading thereto.
- 5
- 78 A method as claimed in claim 77 wherein the arterial vessel is a carotid artery.
- 79 A method as claimed in claim 77 wherein the arterial vessel is a superficial femoral artery.
- 10
- 80 A method as claimed in claim 77 wherein the arterial vessel is a renal artery.
- 81 A method as claimed in any of claims 69 to 74 wherein the inner core is fixed relative to a component of the system.
- 15
- 82 A method as claimed in claim 75 wherein the component is a guide catheter.
- 83 A method as claimed in claim 75 or 76 wherein the component is a Touhy Borst.
- 20
- 84 A method as claimed in any of claims 69 to 77 wherein the system comprises a stabiliser fixed at a proximal end to the handle and the method comprises fixing the stabiliser to a component of the system.
- 25
- 85 A method as claimed in claim 78 wherein the method comprises fixing the distal end of the stabiliser to a guide catheter.
- 86 A method as claimed in claim 78 or 79 wherein the method comprises fixing the distal end of the stabiliser to a Touhy Borst.
- 30

- 33 -

87 A method for delivery and deployment of a self expanding stent comprising the steps of:

providing a delivery system providing:

5

a catheter shaft having a proximal end and a distal end, the distal end of the shaft defining a reception space for receiving a self expanding stent, the stent having a reduced diameter delivery configuration;

10

an inner core engagable with the proximal end of the stent;

an external mounting for the inner core; and

15

an operator actuating element for the catheter shaft; and

moving the operating actuating element proximally of the external mounting to move the catheter shaft relative to the inner core to deploy the stent.

20

88 A method as claimed in claim 87 wherein the operator handle is a pull handle and the catheter shaft is pulled proximally of the inner core to deploy the stent.

25

30

1/22




Fig. 3




Fig. 2






Fig. 1



11
12






Fig. 7(a)




Fig. 7(b)




Fig. 7(c)




Fig. 7(a)

4/22





Fig. 7(e)

5/22



6/22




Fig. 8(f)




Fig. 8(g)

7/22




Fig. 9(a)






Fig. 9(b)



8/22




Fig. 10

9/22




Fig. 11

10/22




Fig. 12

11/22




Fig. 13(a)




Fig. 13(b)




Fig. 13(c)

12/22




Fig. 14

13/22




Fig. 15




Fig. 16

14/22




Fig. 17

15/22




Fig. 18




Fig. 19

16/22




Fig. 20




Fig. 21




Fig. 22

18/22




Fig. 23

13/22




Fig. 24

20/22




Fig. 25




Fig. 26

21/22




Fig. 27





Fig. 28

22/22



DISTAL

PROXIMAL

Fig. 29

INTERNATIONAL SEARCH REPORT

International Application No
P... IE2004/000023

<p>A. CLASSIFICATION OF SUBJECT MATTER IPC 7 A61F2/06</p>		
<p>According to International Patent Classification (IPC) or to both national classification and IPC</p>		
<p>B. FIELDS SEARCHED</p>		
<p>Minimum documentation searched (classification system followed by classification symbols) IPC 7 A61F</p>		
<p>Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched</p>		
<p>Electronic data base consulted during the international search (name of data base and, where practical, search terms used) EPO-Internal</p>		
<p>C. DOCUMENTS CONSIDERED TO BE RELEVANT</p>		
Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 1 095 634 A (CORDIS CORP) 2 May 2001 (2001-05-02)	1,4-8, 10, 12-14, 17,18, 25, 27-34, 36,39, 40,52, 53,59
Y	the whole document	15,20-22
<p><input checked="" type="checkbox"/> Further documents are listed in the continuation of box C. <input checked="" type="checkbox"/> Patent family members are listed in annex.</p>		
<p>° Special categories of cited documents :</p> <p>*A* document defining the general state of the art which is not considered to be of particular relevance</p> <p>*E* earlier document but published on or after the international filing date</p> <p>*L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>*O* document referring to an oral disclosure, use, exhibition or other means</p> <p>*P* document published prior to the international filing date but later than the priority date claimed</p> <p>*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>*&* document member of the same patent family</p>		
<p>Date of the actual completion of the international search 16 July 2004</p>		<p>Date of mailing of the international search report 02.08.2004</p>
<p>Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016</p>		<p>Authorized officer Newman, B</p>

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IE2004/000023

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 733 267 A (DEL TORO CONNIE) 31 March 1998 (1998-03-31) the whole document	1,12-14, 16,17, 26-28, 30,32, 42,43, 45,50, 51,53, 59-63, 67,68
X	US 6 464 721 B1 (MARCADE JEAN PAUL ET AL) 15 October 2002 (2002-10-15) column 14, line 35 -column 15, line 57; figures 9,10	1-14,17, 23,24, 26-28, 30-35, 39,41, 47-49, 52,53, 57-59
X	WO 01/12256 A (JUNG JIN WOOK ;PARK JAE HYUNG (KR); SHIN KYONG MIN (KR)) 22 February 2001 (2001-02-22) page 5, line 19 -page 6, line 20; figure 3	1-4,7, 11-14, 17,23, 26-33, 41,43, 45,53,58
Y	WO 03/002020 A (CASEY BRENDAN ;KEEGAN MARTIN (IE); SALVIAC LTD (IE); COLL SIORA (I) 9 January 2003 (2003-01-09) the whole document	15,20-22
A		1-9, 12-15, 17,18, 20-23, 25-28, 30,32, 52,53
X	WO 03/002019 A (BRADY EAMON ;NEILAN JOHN (IE); SALVIAC LTD (IE); VALE DAVID (IE)) 9 January 2003 (2003-01-09) figures 18,19	60-68
X	US 5 944 727 A (FORTIER RICHARD C ET AL) 31 August 1999 (1999-08-31) column 3, line 37 -column 5, line 30; figures 1,4,6,7	60-62,67

INTERNATIONAL SEARCH REPORT

national application No.
PCT/IE2004/000023

Box II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. Claims Nos.: 69 - 88
because they relate to subject matter not required to be searched by this Authority, namely:
Rule 39.1(iv) PCT - Method for treatment of the human or animal body by surgery
2. Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- The additional search fees were accompanied by the applicant's protest.
- No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claims: 1 - 59

A delivery sytem for a self expanding stent, with the following features:
A catheter shaft defining a reception space for a stent,
an inner core,
an operator handle for movement of chaft relative to inner core,
a stabiliser component,
the inner core being fixed to stabiliser component.

2. Claims: 60 - 68

A delivery system for a self-expanding stent, with the following features:
a catheter shaft,
an inner core,
an external mounting for the inner core,
an operator actuating element for the catheter shaft,
the operator actuating element being movable proximally of the external mounting for movement of the catheter shaft relative to the inner core.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No
PCT/IE2004/000023

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 1095634	A	02-05-2001	US 6613075 B1 CA 2324577 A1 EP 1095634 A2	02-09-2003 27-04-2001 02-05-2001
US 5733267	A	31-03-1998	US 5571168 A AT 202464 T CA 2216952 A1 DE 69613572 D1 DE 69613572 T2 EP 0821574 A1 JP 11503054 T WO 9631174 A1	05-11-1996 15-07-2001 10-10-1996 02-08-2001 25-04-2002 04-02-1998 23-03-1999 10-10-1996
US 6464721	B1	15-10-2002	US 6416542 B1 US 5993481 A US 5683449 A US 6660033 B1 US 6592615 B1 US 5676696 A	09-07-2002 30-11-1999 04-11-1997 09-12-2003 15-07-2003 14-10-1997
WO 0112256	A	22-02-2001	KR 2001018324 A AU 1187700 A CN 1371295 T EP 1263494 A1 JP 2004509651 T WO 0112256 A1 US 6645239 B1	05-03-2001 13-03-2001 25-09-2002 11-12-2002 02-04-2004 22-02-2001 11-11-2003
WO 03002020	A	09-01-2003	CA 2449961 A1 CA 2449981 A1 EP 1399084 A1 EP 1408873 A1 EP 1399085 A1 EP 1399095 A1 WO 03002018 A2 WO 03002019 A2 WO 03002020 A2 WO 03002033 A1 IE 20020529 A1 IE 20020530 A1 IE 20020532 A1 IE 20020533 A1 IE 20020535 A1 US 2003097095 A1 US 2003093110 A1 US 2003125751 A1 US 2003109886 A1 US 2003093106 A1	09-01-2003 09-01-2003 24-03-2004 21-04-2004 24-03-2004 24-03-2004 09-01-2003 09-01-2003 09-01-2003 09-01-2003 30-12-2002 05-03-2003 05-03-2003 28-05-2003 28-05-2003 22-05-2003 15-05-2003 03-07-2003 12-06-2003 15-05-2003
WO 03002019	A	09-01-2003	CA 2449961 A1 CA 2449981 A1 EP 1399084 A1 EP 1408873 A1 EP 1399085 A1 EP 1399095 A1 WO 03002018 A2 WO 03002019 A2 WO 03002020 A2	09-01-2003 09-01-2003 24-03-2004 21-04-2004 24-03-2004 24-03-2004 09-01-2003 09-01-2003 09-01-2003

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

P IE2004/000023

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 03002019	A	WO 03002033 A1	09-01-2003
		IE 20020529 A1	30-12-2002
		IE 20020530 A1	05-03-2003
		IE 20020532 A1	05-03-2003
		IE 20020533 A1	28-05-2003
		IE 20020535 A1	28-05-2003
		US 2003097095 A1	22-05-2003
		US 2003093110 A1	15-05-2003
		US 2003125751 A1	03-07-2003
		US 2003109886 A1	12-06-2003
		US 2003093106 A1	15-05-2003
<hr/>			
US 5944727	A	31-08-1999	NONE
<hr/>			