

[54] CALCULATOR WITH ALGEBRAIC OPERATING SYSTEM

3,995,148 11/1976 Ozawa et al. 364/751
4,156,903 5/1979 Barton et al. 364/200

[75] Inventor: Herman W. Harrison, Dallas, Tex.

Primary Examiner—Jerry Smith
Attorney, Agent, or Firm—Robert D. Marshall, Jr.; Leo N. Heiting; Melvin Sharp

[73] Assignee: Texas Instruments Incorporated, Dallas, Tex.

[*] Notice: The portion of the term of this patent subsequent to Jun. 17, 1997, has been disclaimed.

[57] ABSTRACT

[21] Appl. No.: 95,838

Disclosed is an electronic calculator having a data entry unit for inputting numeric data, expressions such as parentheses and hierarchal mathematical commands, an arithmetic unit for performing arithmetic operations on the numeric data, a memory for storing the numeric data and associated hierarchal mathematical commands inputted via the data entry unit and logic circuitry for enabling the arithmetic unit to perform arithmetic operations on numeric data inputted via the data entry unit within a pair of parentheses, the logic circuitry enabling the arithmetic unit to perform a higher order hierarchal mathematical command before a lower order hierarchal command eventhough the higher order command is received after the lower order hierarchal mathematical command.

[22] Filed: Nov. 19, 1979

Related U.S. Application Data

[62] Division of Ser. No. 708,958, Jul. 26, 1976, Pat. No. 4,208,720.

[51] Int. Cl.³ G06F 7/38; G06F 15/02

[52] U.S. Cl. 364/709; 364/736

[58] Field of Search 364/709, 710, 736, 751

References Cited

U.S. PATENT DOCUMENTS

3,720,820 3/1973 Cochran 364/736
3,971,924 7/1976 Ozawa et al. 364/710

8 Claims, 2 Drawing Figures





Fig. 2



CALCULATOR WITH ALGEBRAIC OPERATING SYSTEM

This is a division of application Ser. No. 708,958, filed July 26, 1976 now U.S. Pat. No. 4,208,720.

BACKGROUND OF THE INVENTION

The present invention relates to data entry system for an electronic calculator and more particularly to an algebraic operating system capable of responding to parentheses in an algebraic expression. When referring to a hierarchal mathematical command, I intend to refer to an inputted mathematic function which requires two operators, such as the functions: add, subtract, multiply, divide, Y^x , $\sqrt[x]{Y}$ and the like. Non-hierarchal mathematical commands then refer to an inputted mathematic function which requires only one operator, such as: $\log x$, $\ln x$, $X!$, sine X , cosine X , tangent X and the like.

The data entry systems which have been used on electronic calculators known in the prior art may be separated into three classes. The first class corresponds to hierarchal data entry systems which are discussed hereafter. The second and third classes correspond to non-hierarchal data entry systems; the second class being algebraic, non-hierarchal calculators and the third class being non-algebraic, non-hierarchal calculators. The difference between these classes of calculators is best pointed out by example. Calculators of the third class utilize, for instance, data entry systems known as "reverse polish notation" in which both operators in an hierarchal expression must be entered before the hierarchal mathematical command is inputted into the electronic calculator. Thus, to multiply 3×6 , first the three is keyed in, then the six is keyed in and finally the multiply command (X) is keyed in. Since the order in which the data and hierarchal mathematical commands are keyed in differs from the corresponding algebraic expression $\dots 3 \times 6 \dots$ this third class is referred to as non-hierarchal, non-algebraic data entry systems. Data entry systems of the second class are algebraic in nature but are similarly non-hierarchal. That is, the mathematic commands are performed in the order received, thus if $2 + 3 \times 6$ were keyed into an electronic calculator of the second class then the two would first be added to the three and the sum (five) would be multiplied by the six to obtain thirty. However, since the normal hierarchy associated with mathematic expressions requires the multiplication to be performed prior to the addition, the expression $2 + 3 \times 6$ should equal twenty and not thirty.

Electronic calculators of the first class are those calculators which generally follow the rules of algebraic hierarchy. Thus, in the aforementioned example, such an electronic calculator would not perform the $2 + 3$ addition when the three is followed by a multiplication command, but would carry out the indicated multiplication before the addition.

Electronic calculators having a hierarchal algebraic data entry system are known in the prior art; however, these hierarchal algebraic data entry systems exhibit only minimal hierarchy. Exemplary of the electronic calculators exhibiting minimal algebraic hierarchy is the electronic calculator disclosed in U.S. Pat. No. 3,720,820 dated Mar. 13, 1973. This electronic calculator has three levels of hierarchy and therefore, can perform the expression $2 + 3 \times 5^3$ in correct algebraic hierarchy, in as much as the 5 would be cubed before it is multiplied times three and the cubing operations and

multiplying operations would be accomplished before the indicated addition operation. However, the electronic calculator disclosed in U.S. Pat. No. 3,720,820 is incapable of receiving an algebraic expression such as $2 + 3 \times 5(2 + 1)$, there being no provision for parentheses keys with the calculator disclosed in U.S. Pat. No. 3,720,820. It should be evident to a person acquainted with writing of algebraic expressions that the use of parentheses in algebraic expressions greatly expands the ability of one to write or express complicated algebraic formula.

It is therefore one object of this invention to equip an electronic calculator with an algebraic operating system capable of responding to parentheses in an algebraic expression according to the rules of algebraic hierarchy.

It is another object of this invention to increase the levels of complexity of algebraic expressions which a hand held or desk model calculator can accommodate.

The foregoing objects are achieved according to the present invention as now described. In a preferred embodiment of the invention, an algebraic operating system memory is interconnected with a modern electronic calculator system. The algebraic operating system memory is preferably implemented as a stack memory, and has provision for storing data words, pending arithmetic operator codes and a parentheses level count associated with each data word. The algebraic operating system memory is arranged to store the most recently received hierarchal mathematical command as a pending arithmetic operator and to execute any previously stored pending arithmetic operator having the same or higher hierarchy than the just received hierarchal mathematical command, so long as both pending arithmetic operators are at the same parentheses level count. If the previously stored pending arithmetic operator is of a lower hierarchy level than the just received pending arithmetic operator, or if the parentheses level count increments the previously stored pending arithmetic operator is not executed but is rather bumped in the memory stack when the most recently received arithmetic operator and associated data are inserted into the algebraic operating system memory stack. A left handed parentheses increments the parentheses level count while a right handed parentheses decrements the parentheses level count. A right handed parentheses also causes all pending arithmetic operators at that parentheses level count to be executed in the order that they are read out of the algebraic operating system memory stack. An equals sign causes all pending arithmetic operators to be executed in the order that they are read out of the algebraic operating system memory stack regardless of parentheses count level.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 depicts a hand-held calculator of the type which may employ the present invention, and

FIG. 2 is a block diagram of an electronic calculator system embodying the present invention.

DETAILED DESCRIPTION OF SPECIFIC EMBODIMENT

Referring to FIG. 1 an electronic portable calculator of the type which may employ features of this invention is shown in pictorial form. The calculator 1 comprises a keyboard 2 and a display 3. The display 3, in one embodiment, consists of twelve digits or characters, each provided by an array of light emitting diodes, a liquid crystal display, gas discharge tube or other display

means. The display is preferably implemented having 8 mantissa digits, 2 exponent digits, 2 sign places (one for the mantissa and one for the exponent), thereby permitting outputting of the data in scientific notation, for instance. Ordinarily, the display would be of the seven segment or eight segment variety, with provision for indicating a decimal point for each digit. The display 2 includes a number of keys (0-9), a decimal point key, and the conventional plus (+), minus (-), multiply (\times), divide (\div), and equal (=) keys. Further the keyboard 2 includes keys for higher order hierarchal mathematical commands, such as exponentiation (Y^X and $\sqrt[X]{Y}$), left hand parentheses (. . . and right hand parentheses . . .) . . . The calculator may further be provided with non-hierarchal mathematical command keys such as, for example, X^2 , $X!$, the reciprocal of X , $\ln X$, $\log X$, and so forth. These mathematical functions are referred to as being non-hierarchal inasmuch as only one operator must be entered into the calculator in order to perform the indicated operation, whereas for hierarchal expressions, two numbers must be entered into the calculator in order to accomplish the indicated mathematical function. Further, the calculator may be provided with keys for storing and recalling data from memory, for clearing the calculator (C) and for clearing the last entry (CE). When referring to parentheses, I also means to refer to brackets or other similar algebraic expressions which accomplish the function of the parentheses in an algebraic equation.

Referring now to FIG. 2 there is shown in block diagram form of an electronic calculator embodying the present invention. It is to be understood that the block diagram of FIG. 2 is not intended to represent the block diagram of a detailed representation of an electronic calculator but rather is intended to merely indicate how the algebraic operating system of this invention is implemented in a very typical electronic calculator. Thus, the calculator of FIG. 2 is shown with a clock 10 which provides the clocking signals for transferring data throughout the electronic calculator and provides scanning signals for scanning the display 3 and keyboard 2 or other data entry means. The inputs from the keyboard are provided to keyboard logic 11 which provides an address in response to the depression of a particular key to branch logic and program counter 12.

It should be evident to one skilled in the art that keyboard logic 11, as well as other logic circuitry, may be separately implemented on the calculator as here indicated or it may be implemented as a part of read-only-memory 13 and instruction word decoder logic 14. The address received from keyboard logic 11 is inserted into the counter in branch logic and program counter 12 which address is utilized in addressing read-only-memory (ROM) 13. ROM 13 provides a set of instruction words in response to the depression of a key at keyboard 3, typically a different set of instruction words being associated with each key on keyboard 3. The instruction words read out of ROM 13 are decoded by instruction word decoder logic 14 to provide instruction commands to branch logic and program counter 12, arithmetic unit 15 and data control 16. The instruction commands provided to branch logic in program counter 12 enable branches to be executed by inserting a new address into the program counter in response to a branch instruction command. The instruction commands provided to data control 16 and arithmetic unit 15 control the manipulation of the numeric data in the calculator

Data control 16 is interconnected with the algebraic operating system memory 17, with display register 19 and operational registers 18 and with arithmetic unit 15. The display register 19 holds the number then being displayed by the display 2 and has associated therewith a plurality of operational registers 18 which are used in conjunction with arithmetic unit 15 perform arithmetic operations in response to particular instruction commands. Data control 16 comprises a series of selector gates for interconnecting the appropriate operational registers 18, display register 19 and algebraic operating system memory 17 with the arithmetic unit 15 or with portions instruction words, if need be, in response to different instruction commands.

Numeric data is inputted into display register 19 from keyboard 2 either by a data path from keyboard logic 11 via data control 16 under control of appropriate instruction commands or by inputting selected portions of appropriate instruction words in response to selected instruction commands. The electronic calculator system hereinbefore described, with the exception of the algebraic operating system memory 17, basically corresponds to the type of electronic calculators known in the prior art. Exemplary of prior art calculator systems, is the calculator system disclosed in U.S. Pat. No. 3,922,538 issued to Cochran et al on Nov. 25, 1975 and assigned to the assignee of this invention.

Register 18 and display register 19 typically store data words of numeric data having at least as many digits as display 2 has character positions. The operating system memory 17 preferably stores a plurality of data words, each word preferably being of the same length as the data word stored in registers 18 and 19, and, in addition, algebraic operating system memory 17 preferably stores a pending arithmetic operator code associated with each stored data word and further a parentheses level count associated with each stored data word. The parentheses level count preferably starts at zero and advances one for each left handed parentheses encountered and decrements one for each right handed parentheses encountered. The pending arithmetic operator code is typically a 3 or 4 bit code representative of a hierarchal mathematical command. The algebraic operating system memory 17 is preferably a push-pop stack, that is, it operates in a first-in-last-out mode. The memory location from which data is retrieved or to which data is entered is hereinafter referred to the accessible memory location in algebraic operating system memory 17. It should be evident, moreover, that algebraic operating system memory 17 need not be a hard-wired push-pop stack, but may also be implemented as a series of shift registers, as is sequentially addressed memory (S.A.M.), as a random access memory (RAM) or other means which is manipulated by the electronic calculator to function in much the same manner as a push-pop stack. In the practice of this invention, only the accessible memory location (for a data word, its pending arithmetic operator code and its parentheses level count) is preferably accessible at any given time. If the memory means is not a push-pop stack, then preferably there would also be an accessible stack pointer register. The stack pointer in that case indicates where in the memory means is the location designated as the accessible memory location in the algebraic operating system memory.

When the calculator embodying the present invention receives data via keyboard 2, the data is loaded, according to instruction commands, into display regis-

ter 19, thus providing a visual display of data entering the electronic calculator. The data is stored in the display register 19 as a data word. Upon receiving a first hierarchal mathematical command (as decoded by instruction word decoder logic 14), the data word then being stored in the display register 19 is loaded into the accessible memory location in algebraic operating system memory 17 along with the then parentheses level count and the pending arithmetic operator code indicative of the hierarchal mathematical command decoded. The entry of additional data following the entry of the hierarchal mathematical command causes the newly received additional data to be stored in the display register 19 as a new data word.

Upon receipt of the next hierarchal mathematical command (without an intervening parentheses) its hierarchy level (as denoted by Table I) is compared with the hierarchy level of the previous hierarchal mathematical command which is stored as a pending arithmetic operator code in the accessible memory location in algebraic operating system memory 17. If the hierarchy level of the most recently received hierarchal mathematical command is of the same or lower hierarchy level than that of the pending arithmetic operator code, then that code and its associated data word are read out of the algebraic operating system memory 17, causing the indicated pending arithmetic operation to be executed by arithmetic unit 15 using the data word read out of the algebraic operating system memory 17 and the data word stored in the display register 19 as operators. The result of the arithmetic operation is stored in display register 19. The comparison is then repeated for the next pending arithmetic operator code unless algebraic operating system memory 17 has been emptied or unless the stored parentheses level count would decrement.

If the hierarchy level of the most recently received hierarchal mathematical command is of a higher hierarchy level than that of the pending arithmetic operator, then the most recently received hierarchal mathematical command, along with the current parentheses level count and the data word in the display register, are stored in the accessible memory location in the algebraic operating system memory 17. The most recently received hierarchal mathematical command is stored as a pending arithmetic operator code at that time.

If an intervening left hand parentheses is received between the hierarchal mathematical commands, then the most recently received hierarchal mathematical command and associated data word along with the incremented parentheses level count are stored in the accessible memory location in algebraic operating system memory 17 much like the receipt of a first hierarchal mathematical command.

Upon the receipt of a right handed parentheses, the pending arithmetic operator code and associated data word are read out of the accessible memory location in algebraic operating system memory 17, causing the arithmetic unit to perform the indicated arithmetic operation using the data word read out of memory 17 and the data word in the display register 19 as operators. The result is stored in the display register 19. The next pending arithmetic operator code and associated data word are similarly read out and executed, the process repeating until the stored parentheses level count decrements by one. At that time, the data word and pending arithmetic operator code associated with the stored decremented parentheses level count are not executed.

Upon the receipt of an equals sign, the algebraic operating system performs the same steps as is done upon the receipt of a right handed parenthesis, except that the pending arithmetic operators and associated data words in the algebraic operating system memory are read out in sequence without regard to the parentheses level count. By ignoring the parentheses level count, the equal sign effectively supplies any missing right handed parenthesis, this being an important feature of my invention reducing the number of keystrokes to solve certain algebraic expressions.

The aforementioned storage of pending arithmetic operators along with the associated data words or the execution of the indicated hierarchal mathematical command depending upon the relative hierarchy levels of the commands and codes involved continues as long as data is being entered into the calculator system. It should be evident that without the entry of any parentheses, three data words and associated pending arithmetic operator codes at most need be loaded into algebraic operating system memory 17, if the number of levels of hierarchy instructions is limited to that showed in Table I. That is, a data word and associated code would be stored upon the entry of a plus or minus, a second data word and its code which should be stored upon the entry of a divide or multiply and then a third data word and its code would be stored upon the entry of an exponentiation command; there being no command having a higher hierarchy level in the hierarchy system of Table I, no more than three data words and associated codes would be stored in the algebraic operating system memory 17. However, when a left handed parenthesis is encountered, the algebraic operating system then permits the entry of a lower order hierarchal mathematical command following a higher order hierarchal mathematical command in the algebraic operating system memory 17 without the normal hierarchy level comparison being made. Thus, the aforementioned normal hierarchy rules are applied to the data entered within a pair of parentheses. It should be evident, therefore, that with the entry of parentheses, the number of data words (and associated pending operators and parentheses level counts) to be stored in the algebraic operating system memory is a function of how complicated an algebraic expression the calculator is to be able to accommodate. While the precise number of data words to be stored in the algebraic operating system memory is, of course, a design choice, I have found that utilizing an algebraic operating system memory capable of storing 7 to 10 data words permits the solution of moderately complex to very complex algebraic expressions.

The operation of the algebraic operating system described is more clearly understood with reference to Table II wherein the solution of the algebraic expression $3 \times 6 + 2 \times 3^{(2 \times (5+1))} \times 6 = 6,377,310$ using my algebraic operating system is demonstrated.

Referring now to Table II, there is shown the algebraic problem $3 \times 6 + 2 \times 3^{(2 \times (5+1))} \times 6 = 6,377,310$ being solved in an electronic calculator equipped with an algebraic operating system according to the present invention. In Table II there is shown in the columns reading from left to right (1) the function or data keyed in, (2) the contents of the display register and (3) the contents of the algebraic operating system memory. As aforementioned, the contents of the algebraic operating system memory preferably includes a data word, here shown as an 8 digit word, a pending arithmetic operator

code and the parentheses level count. It being understood of course, that the length of the data word in the algebraic operating system memory or in the display register is a design choice and that the pending arithmetic operator code would typically be a three of four bit binary code, but is here shown as a conventional mathematical function symbol for sake of clarity. Further, the contents of the display register would typically have leading zeroes similar to the data word in the algebraic operating system memory, but is here shown without the leading zeroes because when the contents of the display register are displayed, the leading zeroes are preferably blanked. Since the algebraic operating system memory 17 functions as a stack memory, a plurality of data words may be shown stored therein. The lowest data word is in the accessible location, and the highest data word is in the memory located farthest from the accessible location.

Considering now the solution of the aforementioned algebraic expression, when the number three is keyed into the electronic calculator, a three is loaded into the display register. Upon subsequent entry of the hierarchal multiply command (X for multiply), the contents of the display register is loaded into the accessible data word location in the algebraic operating system memory along with the parentheses level count (here zero because no parentheses have been encountered) and the hierarchal mathematical command (here multiply) as the pending arithmetic operator. Upon entry of the additional data, e.g., the six, the data is loaded into the display register. Now upon the entry of the next hierarchal mathematical command (here add), the algebraic operating system compares the relative hierarchy level of the just received hierarchal mathematical command with the previously stored pending arithmetic operator. As aforementioned, if the just received hierarchal mathematical command is of the same or lower hierarchy level than that of the pending arithmetic operator code, the arithmetic operation indicated by the pending arithmetic operator code is executed before the just received hierarchal mathematical command and its associated data word are stored in the algebraic operating system memory 17. If, on the other hand, the just received hierarchal mathematical command is of a higher hierarchy level than that of the pending arithmetic operator code, the just received hierarchal mathematical command and its associated data word are similarly stored in the accessible location of algebraic operating system memory 17, the data previously located at the accessible location in algebraic operating system memory 17 being bumped in the algebraic operating system memory 17 stack. Since the hierarchal mathematical command now being inputted is an add command having a hierarchy level of 3 (see Table I) while the pending multiply operator code, has a hierarchy level of 4, the algebraic operating system executes the pending arithmetic operator. Therefore, the number three stored in the data word in the algebraic operating system memory becomes the multiplicand and the number six stored in the display register 19 becomes the multiplier. The result, e.g., the number 18, is stored in display register 19. The result is also stored in the accessible data word location in algebraic operating system memory 17 along with the just received hierarchal mathematical command (add) since there are no additional pending arithmetic operators to be executed.

Next the number two is keyed into the calculator in the solution of the algebraic equation, the number two

being stored in the display register. The following hierarchal multiply command has a higher hierarchy level and the pending arithmetic operator code (add), therefore the contents of the display register along with the just received hierarchal mathematical command are loaded into the accessible location in the algebraic operating system memory 17. The data previously at the accessible location is simultaneously bumped up one location if algebraic operating system memory is a stack memory. Of course, as is known in the art, instead of using a stack memory a more conventional memory may be used along with a pointer to keep track of the accessible memory location.

The next data to be keyed in is the number three which is duly loaded into the display register. Keying in the exponentiation command (Y^X) causes the algebraic operating system to compare the hierarchy level of the just received hierarchal mathematical command (Y^X) with that of the pending arithmetic operator (multiply) and since the exponentiation command has the higher hierarchy level (according to Table I), the hierarchal exponentiation command along with the number three is loaded into the accessible location of the algebraic operating system memory, the previously received data again being bumped in that memory. The receipt of a left hand parenthesis by the calculator causes one to be added to the then current parentheses level count, thus the stack is bumped and a one is loaded into the parentheses level digit of the accessible location in the algebraic operating system memory 17.

Keying in of additional data (the number two) and an additional hierarchal mathematical command (multiply) causes the data and its code to be loaded under the accessible location of the algebraic operating system memory. The normal comparison between the hierarchy level of the just received hierarchal mathematical command (multiply) and the pending arithmetic operator (exponentiation) is not carried out since they are not at the same parentheses level count. The keying in of another left handed parenthesis again causes the stack to be bumped and the parentheses level count to be incremented by one. Keying in of the number 5 and the addition command again causes the data and the most recently received hierarchal mathematical command to be loaded into the algebraic operating system memory without the comparison being made, the parentheses level count having been incremented to 2. The entry of the number one loads a one into display register 19.

The keying in of the first right handed parenthesis, which has the hierarchy level 2 (see Table I) causes all previously keyed in hierarchal mathematical commands at the two parentheses count level to be executed in sequence. That is, all stored pending arithmetic operators at the two parentheses count level are read out in the opposite order in which they are read in (the algebraic operating system memory functioning as a memory stack). Thus, the data word (the number 5) and the pending arithmetic operator (add) are executed using the contents of the display register (the number one) as an operator, the result (the number 6) being stored in the display register. Since the data word and pending operator code at the accessible location in the algebraic operating system memory has been read out, the stack then "pops"—that is, the data word and associated code and parentheses level count previously stored in the location adjacent to the accessible location moves into the accessible location, the other data words and associ-

ated codes and parentheses level counts similarly moving closer to the accessible location.

Upon receipt of second right handed parenthesis, all pending operators at the one parentheses level count are executed, the number two in the data word position becoming the multiplier according to the multiply code and the six in the display register becoming the multiplicand. The execution of the multiply command then stores the number twelve in the display register, the algebraic operating system memory stack again popping as shown in Table II.

Upon keying in the last multiply command in the exemplary algebraic expression, the hierarchy level the multiply command is compared with the pending arithmetic operator and, as aforementioned, the pending arithmetic operator is executed if it has the same or higher hierarchy level. Since exponentiation has a higher hierarchy level than multiplication, the exponentiation command is executed, i.e., the number in the data word (three) is taken to the power indicated by the number in the display register (twelve).

Similarly, since the next pending arithmetic operator (here multiply) has the same hierarchy level as the just received hierarchal mathematical command, the pending arithmetic operation is also executed, the two becoming the multiplier and the results of 3^{12} becoming the multiplicand, thereby storing the result (1,062,882) in the display register. The next pending arithmetic operator (add) is not executed, it having a lower hierarchy level than the just received multiply command. Thus, the contents of the display register along with the just received hierarchal command (multiply) are loaded into the accessible location AOS memory, the memory being bumped accordingly.

The keying in of additional data (the number 6) loads the data into the display register. Finally, the keying in of the equals sign, which has a hierarchy level of one, causes all pending arithmetic operations to be performed regardless of parentheses level count. Thus, the equals sign effectively supplies any missing right handed parenthesis (none is missing in the exemplary problem). Thus, in the exemplary problem, the number in the display register becomes the multiplier while the number 1,062,882 in the accessible data word location becomes the multiplicand for the execution of the pending arithmetic operation (multiply). The execution of the pending arithmetic operates code "pops" the stack and the result of the multiplication is added to the number 18 stored in the next pending arithmetic operation according to the add code stored therewith. The results of these operations (6,377,310) is stored in the display register for display purposes, the stack now being empty.

It should be evident from the foregoing discussion that additional levels of hierarchy may be used, if other algebraic expressions are used. For example, the expression $D\%$, which calculates percent change in two numbers, can be given a higher hierarchy level than exponentiation, if desired. Thus, $64 D\% 32 = 8^2 D\% 32 = -50$. Additionally, it should be evident that the algebraic operating system memory may comprise separate memories for the data words, pending arithmetic operations and parentheses level count rather than a single memory for all three elements.

Referring now to Table III, there is a list of read-only-memory (ROM) microcode instruction words which may be used to implement the algebraic operating system of this invention in an electronic calculator

of the type disclosed in U.S. Pat. No. 3,922,538 issued to Cochran et al on Nov. 25, 1975 and assigned to the assignee of this invention. In Table III, considering the columns from left to right, the left most column is the address (in hexadecimal) of the instruction word located in the ROM, the next column list the 13 bit instruction word (in binary) located at the address indicated, the third column indicates the line number of the entry in Table III (for information only), and the remaining columns are various mnemonic and narrative terms relating to the instruction words located in the second column. The list of instruction words in Table III when implemented in an electronic calculator of the type disclosed in U.S. Pat. No. 3,922,538 issued Nov. 25, 1975, the Cochran et al and assigned to the assignee of this invention provides data electronic calculator with an algebraic operating system according to the present invention. U.S. Pat. No. 3,922,538, which is hereby incorporated herein by reference, describes the format of the instruction words in Table III.

Having described the invention in connection with the specific embodiment thereof, it is to be understood that further modification may suggest itself those skilled in the art. The scope of the present invention is not to be limited to the embodiment disclosed except as set forth in the appended claims.

TABLE I

Hierarchy Level	Hierarchal Mathematical Command And Pending Arithmetic Operators
5	EXPONENTATION ... Y^x ... OR ... $\sqrt[x]{Y}$
4	MULTIPLY ... \times ... OR DIVIDE ... \div ...
3	ADD ... $+$... OR SUBTRACT ... $-$...
2	RIGHT HANDED PARENTHESIS ...) ...
1	EQUALS SIGN ... = ...

TABLE II

FUNCTION OR DATA KEYPED IN	DISPLAY REGISTER	A.O.S. MEMORY		
		DATA WORD	PEND. OPCODE	PAREN. LEVEL CT.
3	3	—	—	—
\times	3	00000003	\times	0
6	6	00000003	\times	0
+	18	00000018	+	0
2	2	00000018	+	0
\times	2	00000018	+	0
		00000002	\times	0
3	3	00000018	+	0
		00000002	\times	0
y^x	3	00000018	+	0
		00000002	\times	0
		00000003	y^x	0
(3	00000018	+	0
		00000002	\times	0
		00000003	y^x	0
				1
2	2	00000018	+	0
		00000002	\times	0
		00000003	y^x	0
				1
\times	2	00000018	+	0
		00000002	\times	0
		00000003	y^x	0
		00000002	\times	1
(2	00000018	+	0
		00000002	\times	0
		00000003	y^x	0
		00000002	\times	1
				2
5	5	00000018	+	0
		00000002	\times	0
		00000003	y^x	0
		00000002	\times	1

TABLE II-continued

TABLE II-continued

FUNCTION OR DATA KEYED IN	DISPLAY REG-ISTER	A.O.S. MEMORY		
		DATA WORD	PEND. OPCODE	PAREN. LEVEL CT.
				2
+	5	00000018	+	0
		00000002	x	0
		00000003	y ^x	0
		00000002	x	1
		00000005	+	2
1	1	00000018	+	0
		00000002	x	0
		00000003	y ^x	0
		00000002	x	1
		00000005	+	2
)	6	00000018	+	0

5

10

15

FUNCTION OR DATA KEYED IN	DISPLAY REG-ISTER	A.O.S. MEMORY		
		DATA WORD	PEND. OPCODE	PAREN. LEVEL CT.
		00000002	x	0
		00000003	y ^x	0
)	12	00000002	x	1
		00000018	+	0
		00000002	x	0
		00000003	y ^x	0
x	1062882	00000018	+	0
		01062882	x	0
6		00000018	+	0
		01062882	x	0
=	6377310		-	

TABLE III

Ad-dress	Instruction Word	Line Number	Informational Mnemonics		
		0631	*-----NESTING ROUTINE FOR MATH HIERARCHY A,B,C,D REG=DEST		
011F	0 1010 0000 0 111	0632	EQU	NUMBER 0	
0120	1 1 00000000 10 0	0633	0122	BO	ALWAYS BRANCH
0121	0 1010 0001 0 111	0634	RPAR	NUMBER 1	
0122	0 0010 1111 0 110	0635	NES	R5D	DPT
0123	0 1010 0011 1 111	0636		RCLG	
0124	0 1100 1101 0 110	0637		LOADD	MAEX
0125	0 0000 0110 0 000	0638		TF	AMUL
0126	1 0 00000100 1 0	0639	013F	BZ	NEST2
0127	0 0110 0011 1 001	0640		CDK	EXP
0128	1 1 00000101 1 0	0641	013F	BO	NEST2
0129	0 0000 1001 1 001	0642		SF	BASSUME
012A	0 1001 0111 1 110	0643		SRLD	MANT
012B	0 0001 1101 0 101	0644		EXCD	ALL
012C	0 0111 0010 1 100	0645		SCKC	EXPI
012D	0 0001 1101 0 101	0646		EXCD	ALL
012E	1 1 00000100 1 0	0647	013F	BO	NEST2
012F	0 1010 0100 0 111	0648	NEAS	NUMBER 4	ALWAYS BRANCH
0130	1 1 00000010 0 0	0649	0134	BO	NEST
0131	0 1010 1000 0 111	0650	NFMD	NUMBER 8	ALWAYS BRANCH
0132	1 1 00000000 10 0	0651	0134	BO	NEST
0133	0 1010 1100 0 111	0652	NEER	NUMBER 12	ALWAYS BRANCH
0134	0 0010 1111 0 110	0653	NEST	R5D	DPT
0135	0 0000 0110 0 000	0654		TF	AMUL
					TEST ILLEGAL MULTIPLE-OPR PUSHES
0136	1 0 00000000 11 0	0655	0139	BZ	NESTA
0137	0 0000 0110 1 010	0656		ZF	BMUL
0138	1 1 00011000 0 0	0657	0198	BO	NEST6
0139	0 1010 0011 1 111	0658	NESTA	RCLG	
013A	0 1100 1101 0 110	0659		LOADD	MAEX
013B	1 1 00000000 10 0	0660	013F	BO	NEST2
013C	0 1010 0011 1 111	0661	NEST1	RCLG	
013D	0 0001 1101 0 110	0662		LOADD	ALL
013E	0 0000 0001 0 100	0663		XF	ASUDI
013F	0 0001 0011 0 100	0664	NEST2	ADKC	ALL
0140	0 0111 0010 1 001	0665		CCK	EXPI
0141	1 0 00001001 10 0	0666	0167	BZ	NEST4
0142	0 1001 0110 1 100	0667		SRLC	MANT
0143	0 1100 0110 1 100	0668		SRLC	MAEX
0144	0 0001 0111 1 110	0669		SRLD	ALL
0145	0 0110 1010 1 001	0670		CCD	EXP
0146	0 0001 0111 0 110	0671		SLLD	ALL
0147	0 0010 1101 0 101	0672		EXCD	DPT
0148	1 0 00000111 11 0	0673	0167	BZ	NEST4
0149	0 0001 0011 0 100	0674		ADKC	ALL
014A	0 0111 0010 1 100	0675		SCKC	EXPI
014B	0 1100 0110 0 100	0676		SLLC	MAEX
104C	0 1001 1101 1 100	0677		CLC	MANT
014D	0 0010 1101 1 100	0678		CLC	DPT
014E	0 1010 1111 1 000	0679		MEMO	
014F	0 0001 0010 0 001	0680		CIO	ALL
0150	0 0001 1101 0 011	0681		LOADB	ALL
0151	0 0010 0001 0 100	0682		ABKC	DPT
0152	0 0010 1010 1 001	0683		CCD	DPT
0153	1 0 00000100 0 0	0684	016B	BZ	NEST5
0154	0 1100 0110 1 100	0685		SRLC	MAEX
0155	0 0110 0010 0 110	0686		ACKD	EXP
0156	0 1001 0111 1 110	0687		SRLD	MANT
					DELETE PAREN-LEVEL CT FOR RECALLED NUM
0157	0 1010 0010 1 111	0688		STOG	
0158	0 0001 0011 0 001	0689		DIO	ALL

TABLE III-continued

Ad- dress	Instruction Word	Line Number	Informational Mnemonics		
0159	0 1010 0000 1 100	0690	NEST3	EXTKR	SET KR FOR SUBROUTINE JUMP
015A	0 1010 0000 1 101	0691		XKRSR	
015B	0 1010 0000 1 100	0692		FXTKR	
015C	0 0000 1011 0 101	0693		SKRD8	
015D	0 0000 1010 0 101	0694		SKRD7	
015E	0 0010 0001 0 011	0695		ABKB	DPT
015F	0 1010 0001 1 000	0696		R5KR	
0160	0 0001 0101 1 011	0697		SRLB	ALL
0161	0 0010 0001 0 011	0698		ABKB	DPT
0162	0 0000 0000 1 111	0699		R5FLB	
0163	0 0100 1101 0 011	0700		CONSTB	DPT12
0164	0 1001 0101 0 011	0701		SLLB	MANT
0165	0 0000 001 0 100	0702		XF	ASUDI
0166	1 1 0011011101 0	0703	0243	BO	NEST3A
0167	0 1010 0010 0 111	0704	NEST4	NUMBER	2
0168	0 0010 1111 0 100	0705		R5C	DPT
0169	0 0010 1010 1 001	0706		CCD	DPT
016A	1 1 0000100000 0	0707	018A	BO	NEST7
016B	0 0001 0011 0 100	0708	NEST5	ADKC	ALL
016C	0 0111 0010 0 110	0709		ACKD	ESP 1
016D	0 0001 0110 1 100	0710		SRLC	ALL
016E	0 1001 1101 1 100	0711		CLC	MANT
016F	0 0001 0110 0 100	0712		SLLC	ALL
		0713	*	TF	BMUL
		0714	*	BZ	NEST11
		0715	*	ACKC	LLSD1
		0716	*	BZ	LPAR3
0170	0 0001 0000 0 000	0717		AAKA	ALL
0171	0 0001 0000 0 000	0718		AAKA	ALL
0172	0 0001 0000 0 000	0719		AAKA	ALL
0173	0 0001 0000 0 000	0720		AAKA	ALL
0174	0 0001 0110 0 100	0721	NEST11	SLLC	ALL
0175	0 0101 0010 1 001	0722		CCK	LLSD1
0176	1 1 0000100010 0	0723	0198	BO	NEST6
0177	0 1001 0110 1 100	0724		SRLC	MANT
0178	0 1001 0111 0 110	0725		SLLD	MANT
0179	0 1001 1010 0 110	0726		ACDD	MANT
017A	0 1010 0010 1 111	0727		STOG	
017B	0 0001 0011 0 001	0728		DIO	ALL
017C	0 0000 0110 1 010	0729		ZF	BMUL
017D	0 0001 0000 0 011	0730		AAKB	ALL
017E	0 1010 0000 0 110	0731		FLAR5	
017F	0 0010 1111 0 011	0732		R5B	DPT
0180	0 1001 0101 1 011	0733		SRLB	MANT
0181	0 0001 0101 0 011	0734		SLLB	ALL
0182	0 0010 0011 0 011	0735		ADKB	DPT
0183	0 1001 1101 1 100	0736		CLC	MANT
0184	0 0011 1101 0 100	0737		CONSTC	DPT1
0185	0 1010 1111 1 000	0738		MEMO	
0186	0 0001 0010 0 001	0739		CIO	ALL
0187	0 0001 0001 0 001	0740		BIO	ALL
0188	0 0000 0000 0 001	0741	NEST9L	SF	ALBL
0189	1 1 000010000 0	0742	0199	BO	NEST9
018A	0 0001 0011 0 100	0743	NEST7	ADKC	ALL
018B	0 0101 0010 1 100	0744		SCKC	LLSD1
018C	1 0 000000100 0	0745	0190	BZ	NEST8
018D	0 1001 0010 0 110	0746		ACKD	MANT
018E	0 1010 0010 1 111	0747	NEST10	STOG	
018F	0 0001 0011 0 001	0748		DIO	ALL
0190	0 0010 0011 1 001	0749	NEST8	CDK	DPT
0191	1 0 000001001 1	0750	0188	BZ	NEST9L
0192	0 0110 0011 1 001	0751		CDK	EXP
0193	1 0 0001010100 1	0752	013F	BZ	NEST2
0194	0 0001 1101 1 110	0753		CLD	ALL
0195	0 1010 0010 1 111	0754		STOG	
0196	0 0001 0011 0 001	0755		DIO	ALL
0197	1 1 0000000010 0	0756	0199	BO	NEST9
0198	0 0000 1001 1 001	0757	NEST6	SF	BASSUME
0199	0 0000 0101 0 001	0758	NEST9	SF	AEND
019A	0 0000 0101 1 010	0759		ZF	BERASE
019B	0 0000 1100 1 000	0760	IPREINC	TF	BREGPUSH
019C	1 0 0000101110 0	0761	01CA	BZ	PRE
019D	0 1010 0000 1 101	0762		XKRSR	
019E	0 1010 0000 0 100	0763		INCKR	
019F	0 1010 0000 1 101	0764		XKRSR	
01A0	0 0000 0100 0 000	0765		TF	AZELF
01A1	1 1 0000100011 0	0766	01C4	BO	PR10
01A2	0 0000 0100 0 010	0767		ZF	AZELF

TABLE III-continued

Ad- dress	Instruction Word	Line Number	Informational Mnemonics				
01A3	1 1 0001000110 0	0768	01E9	BO	IERR3	ALWAYS BRANCH	
01A4	0 0000 1011 0 001	0769		TAN	SF	ATAN	
01A5	1 1 0111010010 0	0770	0377	BO	SINE	ALWAYS	
01A6	0 1100 1101 0 010	0771		PRODS	EXAB	MAEX	
01A7	0 0010 0001 0 011	0772			ABKB	DPT	
01A8	0 0000 0000 0 111	0773			R5FLA		
01A9	0 0000 1000 1 000	0774			TF	BINV	
01AA	1 1 0000000010 0	0775	01AC	BO	M/DS		
01AB	0 0000 0001 0 001	0776		SF	ASUDI		
01AC	0 1010 0000 1 100	0777		M/DS	ESTKR	MUST BE AFTER PRODS	
01AD	0 1010 0001 0 111	0778			NUMBER 1	***POUT TO LOC. D11***	
01AE	0 0000 1000 0 101	0779		SETD10	SKRD5		
01AF	0 0000 1100 0 101	0780		SETD00	SKRD9		
01B0	0 0000 1111 0 101	0781		SETC00	SKRD12		
01B1	0 0000 1110 0 101	0782			SKRD11		
01B2	0 1010 0001 1 000	0783		R5POUT	R5KR		
01B3	0 0000 0001 0 101	0784		AUSE	SKRPOUT		
01B4	0 0001 0000 0 000	0785		AAKA	ALL	DUMMY	

What is claimed:

1. An electronic calculator comprising:

- (a) data entry means including a keyboard having a plurality of keys arranged for inputting algebraic expressions, including numeric data, hierarchical mathematical commands, left and right-hand algebraic parentheses and a sign which indicates the completion of an algebraic expression;
- (b) memory means for storing numeric data, mathematical commands and an indication of parentheses entered into said calculator;
- (c) arithmetic means for performing arithmetic operations on the entered numeric data in accordance with the entered mathematical commands associated therewith;
- (d) logic means for controlling said arithmetic means to perform arithmetic operations on numeric data within each pair of parentheses according to fixed hierarchy so that said arithmetic means performs higher order mathematical commands before lower order mathematical commands within the same respective pair of parentheses, said logic means being responsive to entry of said sign which indicates the completion of an algebraic expression for controlling said arithmetic means to perform arithmetic operations on all previously stored numeric data according to the stored mathematical commands associated therewith, said logic means being further responsive to the entry of said sign for supplying any missing right-hand parentheses; and
- (e) display means for displaying numeric data entered into said calculator via said keyboard entry means and for displaying the results of said arithmetic operations performed on said numeric data.

2. The calculator according to claim 1 wherein said sign which indicates the completion of an algebraic expression is an equals sign and said logic means adds any missing right-hand parentheses in sequence at the end of the algebraic expression and before the equals sign to balance the number of left-hand and right-hand parentheses in the algebraic expression in response to the entry of said equals sign.

3. An electronic data processing system comprising:

- (a) data entry means for entering into said data processing system numeric data, hierarchical mathematical commands, left- and right-hand algebraic

parentheses and a sign which indicates the completion of an algebraic expression;

- (b) memory means for storing numeric data, mathematical commands and left-hand algebraic parentheses entered into said data processing system, said memory means having a first-in-last-out organization;
- (c) mathematical means for performing mathematical operations on said numeric data stored in said memory means in accordance with said mathematical commands stored in said memory means;
- (d) logic means for controlling said memory means and said mathematical means, for storing in said memory means numeric data entered via said data entry means, for storing in said memory means left-hand algebraic parentheses entered via said data entry means, for comparing the hierarchical rank of a mathematical command entered via said data entry means with the hierarchical rank of the mathematical command last stored in said memory means and (i) if there is no mathematical command stored in said memory means after the last stored left-hand algebraic parenthesis, then storing said entered mathematical command in said memory means, (ii) if the hierarchical rank of said entered mathematical command is greater than the hierarchical rank of said last stored mathematical command, then storing said entered mathematical command in said memory means and (iii) if the hierarchical rank of said entered mathematical command is less than or equal to the hierarchical rank of said last stored mathematical command, then recalling said last stored mathematical command and the numeric data stored in said memory means immediately prior to and immediately after said last stored mathematical command for causing said mathematical means to perform a mathematical operation in accordance with said last stored mathematical command on said numeric data and to store the result in said memory means, the recalling of said last stored mathematical command thereby defining a new last stored mathematical command for hierarchical rank comparison with said entered mathematical command, for recalling numeric data and mathematical commands and the last stored left-hand parenthesis and causing said mathematical means to perform mathematical operations in accordance with said recalled mathematical com-

- mands in the order recalled and to store the result in said memory means upon entry of a right-hand algebraic parenthesis via said data entry means and for recalling numeric data and mathematical commands from said memory means and causing said mathematical means to perform mathematical operations in accordance with said recalled mathematical commands in the order recalled irrespective of any stored left-hand algebraic parentheses upon entry of said sign which indicates the completion of an algebraic expression via said data entry means; and
- (e) display means for displaying numeric data entered into said data processing system via said data entry means and for displaying the results of said mathematical operations performed on said numeric data.
4. An electronic data processing system comprising:
- (a) data entry means for entering into said data processing system numeric data, hierarchical mathematical commands, left- and right-hand algebraic parentheses and a sign which indicates the completion of an algebraic expression;
- (b) memory means for storing numeric data, mathematical commands and left-hand algebraic parentheses entered into said data processing system, said memory having a first-in-last-out organization;
- (c) mathematical means for performing mathematical operations on said numeric data stored in said memory means in accordance with said mathematical commands stored in said memory means;
- (d) logic means for controlling said memory means and said mathematical means, for recalling numeric data, mathematical commands and the last stored left-hand parenthesis from said memory and causing said mathematical means to perform mathematical operations on said recalled data in accordance with the respective hierarchical ranks of said recalled mathematical commands and to store the result as numeric data in said memory means upon entry of a right-hand algebraic parenthesis via said data entry means and for completing said algebraic expression by successively recalling numeric data, mathematical commands and the last stored left-hand parenthesis, causing said mathematical means to perform mathematical operations on said recalled data in accordance with the respective hierarchical ranks of said recalled mathematical commands and storing the result as numeric data in said memory means for each stored left-hand parenthesis until the first stored left-hand parenthesis is recalled and thereupon recalling any remaining numeric data and mathematical commands and causing said mathematical means to perform mathematical operations on said recalled numeric data in accordance with the respective hierarchical ranks of said recalled mathematical commands thereby obtaining the result of said algebraic expression upon entry of said sign which indicates the completion of an algebraic expression via said data entry means; and
- (e) display means for displaying numeric data entered into said data processing system via said data entry means and for displaying the results of said mathematical operations on said numeric data.
5. An electronic data processing system comprising:
- (a) data entry means for entering into said data processing system data, operational commands operable on by said data processing system according to

- a fixed hierarchy, first and second hierarchy modifier commands for selecting a hierarchy of operation by said data processing means different from said fixed hierarchy and a sign which indicates the completion of an operational expression;
- (b) memory means for storing received data and associated operational commands entered via said data entry means, and for storing an indication of first and second hierarchy modifier commands entered via said data entry means;
- (c) means for performing operations on said data stored in said memory means in accordance with a hierarchy of operations determined by said fixed hierarchy of said operational commands stored in said memory means as modified by said different hierarchy selected by said indication of first and second hierarchy modifier commands stored in said memory, said means being responsive to entry of said sign which indicates the completion of an operational expression for completing the operational expression by performing all stored operational commands according to said modified hierarchy; and
- (d) display means for displaying data entered into said data processing system via said data entry means and for displaying the results of said operational commands performed on said data.
6. An electronic data processing system as claimed in claim 5, wherein:
- said means for performing operations further comprises means responsive to entry of said sign which indicates the completion of an operational expression for performing all stored operational commands according to said modified hierarchy by supplying any missing second hierarchy modifier commands.
7. An electronic data processing system comprising:
- (a) data entry means for entering into said data processing system numeric data, mathematical commands operable on by said data processing system according to a fixed hierarchy, left- and right-hand algebraic parentheses commands for selecting a hierarchy of operation by said data processing system different from said fixed hierarchy and a sign which indicates the completion of an algebraic expression;
- (b) memory means for storing received numeric data and associated mathematical commands entered via said data entry means, and for storing an indication of left- and right-hand algebraic parentheses of an algebraic expression entered via said data entry means;
- (c) means for performing mathematical operations on said numeric data stored in said memory means in accordance with a hierarchy of operations determined by the fixed hierarchy of said mathematical commands stored in said memory means as modified by said different hierarchy selected by said indication of left and right-hand algebraic parentheses stored in said memory means, said means being responsive to entry of said sign which indicates the completion of an algebraic expression for completing the algebraic expression by performing all stored mathematical commands according to said modified hierarchy; and
- (d) display means for displaying numeric data entered into said data processing system via said data entry

19

means and for displaying the results of said mathematical operations performed on said numeric data.

8. An electronic data processing system as claimed in claim 7, wherein:

said means for performing mathematical operations 5
further comprises means responsive to entry of said

20

sign which indicates the completion of a mathematical expression for performing all stored mathematical commands according to said modified hierarchy by supplying any missing right-hand parentheses.

* * * * *

10

15

20

25

30

35

40

45