

# UK Patent Application GB 2 148 359 A

(12) (19) (11) (43) Application published 30 May 1985

(21) Application No 8327641

(22) Date of filing 14 Oct 1983

(71) Applicant  
Glasdon Limited (United Kingdom),  
117-123 Talbot Road, Blackpool, Lancashire FY1 3QY

(72) Inventor  
John Lloyd

(74) Agent and/or Address for Service  
Marks & Clerk,  
Scottish Life House, Bridge Street, Manchester M3 3DP

(51) INT CL<sup>4</sup>  
E01F 9/01


(52) Domestic classification  
E1G 701 702 791 LJ

(56) Documents cited  
GB A 2108182 GB 1531725  
GB A 2090625 US 4466376  
GB A 2090313 US 4050401  
GB A 2063969

(58) Field of search  
E1G

## (54) Base for road cone or post


(57) A base to maintain a cone or post in an upstanding state, the base comprising a container formed of moulded plastics material and having mounted thereon or being arranged to be engaged by a cone or post to be maintained upstanding above the base. The container has a lower part to stand on a floor or ground surface, and an upper covering wall forming at least one upwardly open recess or tray. The base has a shape enabling it to stand stably and to increase the stability or resistance to upset the base so as to maintain said element upstanding when the base is in use, the base can be ballasted by liquid, slurry, particulate or lumpy material material introduced into the interior of the container through an access opening leading thereinto and/or by ballast loaded into the tray.



The drawing(s) originally filed was (were) informal and the print here reproduced is taken from a later filed formal copy.

The claims were filed later than the filing date within the period prescribed by Rule 25(1) of the Patents Rules 1982. This print takes account of replacement documents submitted after the date of filing to enable the application to comply with the formal requirements of the Patents Rules 1982.

4401140 CCC






FIG. 3




FIG. 4

## SPECIFICATION

## A base to maintain an upstanding element

5 This invention concerns a base to maintain an upstanding element.

According to the invention there is provided a base to maintain an element in an upstanding state, said base comprising a container formed of moulded plastics material, said container having mounted thereon or being arranged to be engaged by an element to be maintained upstanding above the base, said container having a lower part to stand on a floor or ground surface, and an upper covering 15 wall of the container forming at least one upwardly open recess or tray means, said base having a shape enabling it to stand stably and wherein, to increase the stability or resistance to upset of the base so as to maintain said element upstanding when the base 20 is in use, said base can be ballasted by liquid, slurry, particulate or lumpy material introduced into the interior of the container through an access opening leading thereinto and/or by ballast mass loaded into the tray means.

25 The element to be maintained upstanding may be a post or upright or upstanding cone, for example a road traffic cone. The post or upright may support a light, and/or a sign and/or support members, for example horizontal rails, forming in conjunction with 30 other posts and members a barrier or de-lineator which may be used to indicate closure of a road or street or provide a warning fence alongside road works. The light or sign may be used for road traffic warning or information purposes.

35 The base which may be of any desired shape may have relatively low height compared with its side or diameter dimensions so it can stand substantially stable on the ground over an adequate or not inconsiderable area. It can be in the form of a closed 40 container of moulded plastics with an access hole leading into its interior. That hole is closable preferably by a removable plug or cap. The top wall of the container may be recessed to define a well or tray arrangement surrounded by a rim which may extend 45 about the periphery of the base.

The element to be maintained upright may ascend from the tray arrangement. For example the container may be formed with an opening, which may be central of the tray arrangement, in which opening a 50 lower end of the element may be permanently or removably fitted. The lower end of the element may be a snap-fit in the opening. If desired the element may be snap-fitted in the opening whilst the base is still warm from moulding so that when the plastics 55 cools or sets in its shape, the base permanently engages the element. An upstanding collar which may be of similar height to the rim, may surround the hole.

To ballast the base, the container may be filled 60 with ballast capable of passing through the access hole, for example liquid or slurry, or material in the form of particles of small lumps and/or the tray may be loaded with external ballast, for example soil or stones or excavated spoil, for example from road 65 works, or other weighty solid matter which may be

bagged for example bags of sand.

As it is optional whether the base is ballasted internally or externally, it may be pre-ballasted internally before use when it is to be used at a 70 location where ballast is not readily available, or ballasted externally at the site of use where suitable solid ballast is available.

The invention will now be further described, by way of example, with reference to the accompanying 75 drawings in which:-

*Figure 1* is a perspective view of a base formed according to the invention mounted on a lower end of an upright element formed by a post;

*Figure 2* is a fragment of *Figure 1* and partly in 80 section,

*Figure 3* is a plan view, on enlarged scale, of the underneath of the base in *Figure 1*, and

*Figure 4* is section on line IV - IV in *Figure 3*.

In *Figures 1* and *2* an upright hollow post P of 85 plastics is to be maintained upright by a base 2. The post may be used to hold barrier rails R1 and R2 attached to it by headed tethers T engaging keyhole slots K with which the post is provided.

The low base 2 of moulded plastics and square 90 shape in plan defines a hollow container 4 having top bottom and side walls 6, 8, 10, 12. The top wall 6 is dished to form a tray 14 surrounded by an outer peripheral rim 6a. Centrally of the tray is a through circular opening 16 bounded by the inner side wall

95 12 which has a conical shaped upper lead-in 12a terminating in annular shoulder 12b extending into a wider annular part 12c. Access to the interior of the container 4 is through a hole closed by a removable plug 18. At intervals the base of the tray 14 is

100 supported by hollow cone formations 8' in the bottom 8.

The tray 14 is of annular channel form having an inner peripheral wall formed by a collar constituted by wall parts 6b, 12a surrounding the opening 16.

105 The post P is a snap-fit in opening 16. For this purpose the lower end of the post has conical part C with an annular stepped lip L to engage the shoulder 12b. The post also has a collar or excrecence E which sits on the collar 6b, 12a of the base.

## 110 CLAIMS

1. A base to maintain an element in an upstanding state, said base comprising a container formed 115 of moulded plastics material, said container having mounted thereon or being arranged to be engaged by an element to be maintained upstanding above the base, said container having a lower part to stand on a floor or ground surface, and an upper covering 120 wall of the container forming at least one upwardly open recess or tray means, said base having a shape enabling it to stand stably and wherein, to increase the stability or resistance to upset the base so as to maintain said element upstanding when the base is 125 in use, said base can be ballasted by liquid, slurry, particulate or lumpy material introduced into the interior of the container through an access opening leading thereinto and/or by ballast mass loaded into the tray means.

130 2. A base according to claim 1, wherein the base

---

has a relatively low height compared with its horizontal diameter dimensions which it stands substantially stably on the ground.

3. A base according to claim 2, wherein the base is in the form of a closed container of moulded plastics with an access hole leading into its interior.
4. A base according to claim 3, wherein the container has a recessed top wall which defines a tray surrounded by a rim extending about the periphery of the base.
5. A base according to any preceding claim, wherein the container is formed with an opening located centrally of the tray in which opening a lower end of the element is snap-fitted.
- 15 6. A base according to claim 5, wherein the element is snap-fitted in the opening whilst the base is still warm from moulding so that when the plastics sets the base permanently engages the element.
- 20 7. A base to maintain an element in an upstanding state substantially as hereinbefore described with reference to the accompanying drawings.