




US 20110130722A1

(19) **United States**(12) **Patent Application Publication**
Fangrow, JR.(10) **Pub. No.: US 2011/0130722 A1**(43) **Pub. Date: Jun. 2, 2011**(54) **INFUSION SET****Publication Classification**(75) Inventor: **Thomas F. Fangrow, JR.**, Mission Viejo, CA (US)(51) **Int. Cl.**
A61M 5/00 (2006.01)(52) **U.S. Cl.** **604/174**(73) Assignee: **ICU MEDICAL, INC.**, San Clemente, CA (US)(57) **ABSTRACT**(21) Appl. No.: **12/825,199**(22) Filed: **Jun. 28, 2010**

An infusion set comprises a base member (60), an introducer cap (64), and an infusion cap (54). The base member (60) preferably comprises a soft cannula (52) extending from a lower side (118) of the base member (60), and a port (62) on an upper side (92) thereof. The port (62) is configured to be in fluid communication with the cannula (52). The port (62) also comprises a septum (130) adapted to seal the port (62) against unwanted fluid flow. The introducer cap (64) is adapted to be mounted to the base member (60) and has a needle (66) adapted to extend through the septum (130) and said soft cannula (52) in an assembled position. The infusion cap (54) comprises a lumen (160) adapted to receive an elongate flexible tube (162). The infusion cap (54) also comprises a hard cannula (170) adapted to be inserted through the septum (130) and to place said soft cannula (52) in fluid communication with said lumen (160).

Related U.S. Application Data

(63) Continuation of application No. 12/177,821, filed on Jul. 22, 2008, now Pat. No. 7,744,570, which is a continuation of application No. 11/418,494, filed on May 3, 2006, now Pat. No. 7,407,491, which is a continuation of application No. 10/715,985, filed on Nov. 18, 2003, now Pat. No. 7,309,326.






FIG. 1




FIG. 2

FIG. 3




FIG. 4

FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14

INFUSION SET

RELATED APPLICATIONS

[0001] This application is a continuation of U.S. patent application Ser. No. 12/177,821, filed Jul. 22, 2008, which is a continuation of U.S. patent application Ser. No. 11/418,494, filed May 3, 2006, now U.S. Pat. No. 7,407,491, which is a continuation of U.S. patent application Ser. No. 10/715,985, filed Nov. 18, 2003, now U.S. Pat. No. 7,309,326, all of which are hereby incorporated in their entireties by reference herein.

BACKGROUND OF THE INVENTION

[0002] 1. Field of the Invention

[0003] The invention relates in general to the field of infusion sets and more particularly to infusion sets with removable injection needles.

[0004] 2. Description of the Related Art

[0005] Subcutaneous injection is a standard method for the delivery of medication into a patient's body. To facilitate frequent or continuous subcutaneous injection of medication, subcutaneous injection ports are often used. Such injection ports extend through the skin and may remain in place for several days. Currently, a major application of such injection ports is to provide continuous delivery of medication, such as insulin, from portable pumps carried with the patient. When used with a portable pump, the injection port is typically connected to the pump via a fluid line. Another application of subcutaneous injection ports is to permit multiple injections of medication into a patient without the need to repuncture the patient's skin. In this application, medication is injected from a standard medical implement, such as a syringe, through a soft elastomer septum in the injection port which delivers the medication subcutaneously.

[0006] Subcutaneous injection ports generally require a sharp, rigid needle to pierce the patient's skin when initially attached to the patient. However, if the needle were left in place through the skin to provide medication delivery, after one or two days the needle would become uncomfortable to the patient. To solve this problem, infusion sets with removable needles and soft plastic cannula to be placed inside the body of a patient have been developed. However, these sets have many disadvantages. There remains a need for an improved infusion set that is less bulky, less susceptible to contamination, more comfortable to a user, and easier to use.

SUMMARY

[0007] One embodiment of the present invention provides an infusion set comprising a base member, an introducer cap, and an infusion cap. The base member preferably comprises a port on a first side thereof, and a soft cannula extending from a second side of the base member. The port is configured to be in fluid communication with the cannula. The port also comprises a septum adapted to seal the port against unwanted fluid flow. The introducer cap is adapted to be mounted to the base member and has a needle adapted to extend through the septum and said soft cannula in an assembled position. The infusion cap comprises a lumen adapted to receive an elongate flexible tube. The infusion cap also comprises a hard cannula adapted to be inserted through the septum and to place said soft cannula in fluid communication with said lumen.

[0008] The base member is preferably circular, and the port preferably comprises a cylindrical portion extending from a

first side of the base member. The introducer cap preferably comprises a hollow cylindrical portion extending from the second side of the introducer cap and located coaxially with the introducer needle. The infusion cap preferably comprises a hollow cylindrical portion extending from the second side of the infusion cap and located coaxially with the hard cannula. The first side of the infusion cap preferably is dome-shaped, and the infusion cap is preferably adapted to be rotatable relative to the base member when the infusion cap and the base member are assembled.

[0009] The base is preferably surrounded by a rim adapted to engage and retain an external component. A cannula extends downward from a first side of said base; and an adhesive layer is secured to the first side of the base. The adhesive layer includes a second side with an adhesive. A substantially cylindrical port extends upward from a second side of said base. The port comprises a septum configured to have a fluid pathway therethrough. The fluid pathway is preferably formed by a slit extending through the septum, but alternatively the fluid pathway can be created by puncturing the septum with a needle or other object. In a method of using an embodiment of the infusion set described herein, the base member is prepared for adhesion to a patient's skin, and the needle and the cannula are inserted through the patient's skin. The introducer cap is disconnected and the needle is withdrawn from the base member. The infusion cap is then assembled on the base member such that the cannula of the infusion cap is in fluid communication with the base cannula, and the infusion cap is rotatable relative to the base member.

BRIEF DESCRIPTION OF DRAWINGS

[0010] Having thus summarized the general nature of the invention, certain preferred embodiments and modifications thereof will become apparent to those skilled in the art from the detailed description herein having reference to the figures that follow, of which:

[0011] FIG. 1 is a perspective exploded view of an infusion set introducer assembly and base assembly having desired features and advantages.

[0012] FIG. 2 is a top view of the introducer cap of FIG. 1.

[0013] FIG. 3 is a cross-sectional view of the introducer cap of FIG. 1, taken through line 3-3.

[0014] FIG. 4 is a cross-sectional view of the introducer cap of FIG. 1, taken through line 4-4.

[0015] FIG. 5 is a perspective view of the base member of FIG. 1.

[0016] FIG. 6 is a cross-sectional view of the base member of FIG. 4.

[0017] FIG. 7 is a perspective view of an assembled introducer and base member.

[0018] FIG. 8 is a cross-sectional view of the assembly of FIG. 7 taken through line 8-8.

[0019] FIG. 9 is a cross-sectional view of the assembly of FIG. 7 taken through line 9-9.

[0020] FIG. 10 is a top view of an infusion cap having desired features and advantages.

[0021] FIG. 11 is a cross-sectional view of the infusion cap of FIG. 10 taken through line 11-11.

[0022] FIG. 12 is a perspective view of an assembly of an infusion cap and a base member.

[0023] FIG. 13 is a cross-sectional view of the assembly of FIG. 12 taken through line 13-13.

[0024] FIG. 14 is a cross-sectional view of the assembly of FIG. 12 taken through line 14-14.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

[0025] An infusion set having desirable features and advantages will now be described with reference to the attached figures. Although the following description is provided in the context of an infusion set for use with an insulin pump, the skilled artisan will recognize that the features of the present infusion set can provide advantages in other applications as well.

[0026] The infusion set illustrated in FIGS. 1-14 and described herein generally comprises a base assembly 20 adapted to removably receive an introducer assembly 30 and an infusion assembly 40 (See FIG. 13).

[0027] FIG. 1 illustrates an exploded view of components of the base assembly 20 and the introducer assembly 30. The base assembly 20 is generally configured to be secured to a patient's skin by an adhesive layer 50 to maintain a soft cannula 52 within a patient and to allow an infusion cap 54 (see FIGS. 10-14) to be mounted to the base assembly 20 for delivering a fluid through the cannula 52 and into a patient's body. The base assembly 20 preferably comprises a base member 60 with a soft cannula 52 extending from a first side of the base member 60, a port 62 extending from a second side of the base member 60, and an adhesive layer 50 securable to the second side of the base member 60.

[0028] The introducer assembly 30 is generally configured to be removably engageable with the base assembly 20 to facilitate introduction of the soft cannula 52 through a patient's skin to a desired depth in the patient's sub-dermal fatty tissue.

[0029] FIGS. 1-4 illustrate embodiments of an introducer assembly 30 comprising an introducer cap 64 and an introducer needle 66 extending downward from the cap 64. In the illustrated embodiment, the introducer cap 64 is generally dome-shaped, and has a handle portion 72, a port-engaging portion 74, a base-engaging portion 76, and release grips 100.

[0030] As illustrated, the handle portion 72 generally includes a flange with a needle-holding section 82 extending through a central portion of the flange 72. In one embodiment, the introducer cap 64 is formed with a needle-holding section 82 comprising a lumen into which an introducer needle 66 can be subsequently inserted and secured. Alternatively, the introducer needle 66 can be molded into the material of the introducer cap 64 by any of a variety of over-molding processes available to the skilled artisan. According to one embodiment, the needle-receiving section 82 extends partially into the cavity 84 of the port-engaging portion 74 to provide additional length along which the needle 66 will be supported. The supported length of the needle (i.e. the length of the needle held within the needle-holding lumen 82) can vary as needed for needles of various lengths. For example, in the case of a needle with an overall length of about 1", a needle-receiving section preferably has a length of between about $\frac{3}{16}$ " and about $\frac{5}{16}$ ".

[0031] Introducer needles can be provided in a variety of sizes as needed for a particular cannula or application. For example, needles can be provided with lengths from about 0.5" to about 2" or more. In further alternative embodiments, needles outside of these ranges can also be used as needed. Additionally, an introducer needle can be solid, or may have a hollow inner lumen as desired.

[0032] The handle section 72 of the introducer cap 64 is illustrated as comprising a substantially planar section extending upward from the dome-shaped cap 64. The handle section 72 preferably has a substantially large surface area such that a patient or caregiver can easily grasp the introducer cap 64 for assembly with the base member 60 and for insertion of the needle 66 into the patient. For example, as shown, the handle section can extend across a substantial portion of the diameter of the introducer cap. The handle section 72 can also extend upwards from the dome of the cap by about 0.2" to about 1". In one preferred embodiment, the handle section 72 extends about $\frac{1}{2}$ " above the top of the introducer cap 64. The skilled artisan will recognize that the handle portion 72 can be otherwise shaped and sized as desired. Alternatively, the introducer cap 30 can be held by the release grips 100 or any other convenient portion during insertion of the needle as will be further described below.

[0033] As illustrated in FIG. 2, the port-engaging portion 74 preferably comprises a cylindrical section configured to closely surround the port 62 of the base portion 60 in an assembled position. The tubular wall 86 of the port-engaging portion 74 is generally configured to contact the top surface 92 of the base member 60 as will be further described below. A close fit between the port 62 and the tubular wall 86 of the port-engaging portion 74 of the introducer cap 64 advantageously provides a minimum of movement of the base member 60 relative to the introducer cap 64 during introduction of the needle 66 and catheter 52 into a patient.

[0034] In the illustrated embodiment, the base-engaging portion 76 of the introducer cap 64 generally comprises a pair of wings 98 extending downward from the cap. The wings 98 preferably include barbed feet 94 adapted to engage a rim 96 of the base member 60 (FIG. 6). The barbed feet 94 are generally configured to secure the introducer cap to the base member disc 60. The height 'h' between the top of the barbed feet 94 and the bottom of the tubular wall 86 of the port-engaging portion 74 is generally selected to correspond to dimensions of the base member 60 in order to provide a secure fit between the assemblies 20 and 30 as will be further described below. In an alternative embodiment, the barbed feet 94 can be omitted, and the introducer cap can be held in an operative position relative to the base assembly 20 by other means. For example, the port 62 and the port-engaging portion 74 can alternatively be threaded such that the introducer cap can screw onto the base member.

[0035] In the illustrated embodiment, the introducer cap 64 is generally circular as viewed from above (see FIG. 2). As shown in FIG. 2, a pair of release grips 100 are provided on opposite sides of the circular cap 64 in the area of the barbed feet 94 so as to allow the introducer cap 64 to be released from engagement with the base member by the application of a force at the arrows 102, preferably by pinching the release grips 100 between the thumb and middle finger. In the embodiments illustrated in FIGS. 2-4 and 8, the release grips 100 comprise vertically extending portions which can be integrally formed with the dome-shaped portion of the introducer cap 64. Alternatively, the vertically extending portions can be separate sections which can be made separately from the introducer cap and secured thereto by any appropriate method. In operation, application of a force at the arrows 102 will create a bending moment at the intersection of the vertically extending portion and the dome-shaped cap. This bending moment will cause the wing sections 98 of the introducer

cap 64 to bend radially outwards, thereby releasing the barbed feet 94 from engagement with the base member 60.

[0036] In alternative embodiments, the release grips 100 can include convex protrusions, concave recesses, or other shapes to allow the shape of the introducer cap to be deformed in order to facilitate removal of the introducer cap 64 from the base member 60. The illustrated release grips 100 advantageously allow the user to grasp the introducer cap 30 with his or her fingers without simultaneously grasping the rim 96 of the base member 60, making it easier to release the introducer cap 64 from the base member 60. Alternatively, a separate tool can also be used to grip an introducer cap 64 and/or an infusion cap 54 during assembly or disassembly of a cap with the base member 60.

[0037] The introducer cap 64 is preferably injection molded from a plastic material suitable for use in medical applications. In one embodiment, the introducer cap 64 is made of a biocompatible ABS, and has a wall thickness 't' of about 0.030"±0.005". In alternative embodiments, the introducer cap 64 can be made of other biocompatible materials such as polycarbonate in any appropriate size as desired.

[0038] As shown in FIG. 3, the introducer cap 64 can also include ribs 104 extending radially from the tubular wall 86 of the port-engaging portion 74. Ribs 104 can be provided in any size and number as desired in order to provide additional rigidity to the joint between the tubular wall and the body of the introducer cap.

[0039] Embodiments of the base assembly 20 will now be described with reference to FIGS. 1, 5 and 6. In the illustrated embodiments, the base assembly 20 comprises a base member 60 with a port 62 extending upward therefrom and a soft cannula 52 extending downward from the disc 60. In the illustrated embodiments, the base member 60 is shown as being a substantially circular disc; however, in alternative embodiments, the disc can have other shapes such as an ellipse, polygon, etc. A circular base member 60 as shown provides the advantage of allowing an introducer cap 64 and/or an infusion cap 54 attached thereto to be rotatable about the central axis of the base member 60.

[0040] The illustrated base member 60 comprises a rim 96 surrounding the disc-shaped base member 60. The rim 96 is generally configured to receive the barbed feet of an introducer cap 64 and/or an infusion cap 54 to retain the cap member (64 or 54) on the base member 60. As seen in FIG. 6, the rim 96 of the base member 60 can include a notched portion 110 to provide clearance for the barbed feet 94. The rim 96 can also be provided with a sloped edge 112 for facilitating assembly of the cap members 54 and 64 with the base member 60 as the cap is pressed axially downward onto the base member 60 as will be further described below.

[0041] With particular reference to FIG. 6, one embodiment of the base member 60 is adapted to have a substantially low profile. For example, in some embodiment, the overall height, 'q' can be between about 0.15" and about 0.25". In one preferred embodiment, the overall height 'q' of the base member 60 is about 0.20".

[0042] According to one embodiment, the distance 'd' between the bottom surface of the rim 96 and the top surface 92 of the base member 60 is selected to correspond to the height 'h' between the top edge of the barbed feet 94 and the bottom edge of the tubular wall 86 of the port-engaging portion of the introducer cap 64 (as discussed above with reference to FIG. 3) and the infusion cap 54 (as further discussed below with reference to FIG. 11). In one embodiment,

the dimensions 'd' and 'h' are substantially the same, thereby providing a substantially rigid connection between a cap (64 or 54) and the base member 60. Alternatively, the dimension 'h' can be made larger than the dimension 'd' in order to provide a looser connection between a cap (64 or 54) and the base member 60.

[0043] Certain advantages arise from loose or tight connections between the base member 60 and a cap member (64 or 54). For example, a tight connection between the base member 60 and the introducer cap 64 will assist in control of the needle 66 during insertion of the needle 66 and the soft cannula 52 through the patient's skin. On the other hand, a loose but secure connection between the base member and the infusion cap 54 will allow the infusion cap 54 to rotate and move about the base member without transmitting substantial torsional stress to the base member 60 and the patient.

[0044] As illustrated in FIG. 6, the base member 60 comprises a fluid pathway extending from the top 114 of the port 62 through the soft cannula 52 extending from the bottom surface 118 of the base member 60. The central portion of the fluid pathway preferably comprises a substantially funnel-shaped section 120 with a tubular lower section 122. According to one embodiment, a funnel-shaped insert 124 can be provided to line the interior surface of the funnel-shaped section 120. The insert 124 is preferably made of a rigid material, such as a metal, to protect the wall of the funnel-shaped section 120 during insertion of the introducer needle 66 (FIGS. 1 and 3). The insert 124 prevents the wall of the funnel-shaped section 120 from scoring and/or causing fragments of the wall to break away and enter the infusion stream.

[0045] The soft cannula 52 extending from the base member 60 can comprise any material recognized as being suitable for use in fluid-carrying lumens implantable within a patient's body. Infusion sets can be offered with soft cannulas having a variety of lengths to accommodate differences in the desired depth to which the cannula extends within a patient. As will be understood by the skilled artisan, in many embodiments the soft cannula 52 preferably extends into a subcutaneous fat layer of a patient. Thus, cannulas of various lengths are helpful in allowing a variety of different patients with more or less subcutaneous fat to use the present infusion set. For example, soft cannulas can be produced in lengths from about 1/4" to about 2". Depending upon the intended use, soft cannulas with lengths outside of this range may also be employed.

[0046] FIGS. 1, 5 and 6 illustrate embodiments in which the cannula 52 extends from the bottom surface 118 of the base member 60 at a substantially right angle. In alternative embodiments, the cannula 52 can be configured to extend from the base member at an angle substantially less than 90°.

[0047] In alternative embodiments, the soft cannula 52 could be replaced by a substantially hard cannula or hypodermic needle as may be desired. Such a hard cannula or needle could also be provided at any angle relative to the bottom surface 118 of the base member 60 as desired.

[0048] In one embodiment, the soft cannula 52 can be secured to the funnel-shaped insert 124, and the cannula-funnel assembly can be inserted into the funnel-shaped section 120 of the base member 60. In an alternative embodiment, the soft cannula 52 can be secured directly to the base member to extend from the bottom surface 118 of the base member 60 at an inner or outer surface of the tubular lower section 122 of the funnel-shaped portion as desired.

[0049] As shown in FIGS. 1, 5 and 6, the port 62 extending from the base member 60 preferably comprises a self-sealing

septum **130** positioned in the cavity **132** above the funnel-shaped section **120** of the port **62**. The septum **130** is preferably positioned at or near the top of the port **62** so as to present a readily accessible surface for swabbing with antiseptic to maintain the septum **130** free of bacteria and other debris. The positioning of the septum above the funnel-shaped section **120** helps maintain the funnel-shaped section **120** sterile. In the illustrated embodiment, the septum **130** preferably comprises a slit **134** forming a fluid pathway through the septum **130**. Although the illustrated slit **134** is in the shape of a straight line, in alternative embodiments, the slit **134** can be circular, cross-shaped, or otherwise shaped to provide a sealable fluid pathway through the septum **130**. In further alternative embodiments, a pre-formed slit **134** can be omitted, and the septum **130** can be punctured with a needle or other sharp object to create a fluid pathway through the septum **130**.

[0050] In order to create a self-sealing fluid pathway, the septum **130** is generally made of a substantially resilient material biased toward a sealed position. In one embodiment, the septum **130** is made of a molded disc of silicon, polyurethane or other appropriate material which can be secured to the port **62**. The securing of the septum **130** to the port **62** can be accomplished by any suitable adhesive, bonding or other securement process such as heat sealing, sonic welding, etc. In alternative embodiments a suitably resilient material such as silicone, polyurethane, or other suitable elastomeric material can be molded into the cavity **132** at the top of the port **62** (see FIG. 6). In still further embodiments, the septum **130** can be replaced by any of a variety of mechanical check-valves or other seals configured to provide a re-sealable fluid pathway. In another embodiment, the septum **130** and the body of the base member **60** can both be integrally formed from the same substantially resilient material.

[0051] According to one embodiment, as illustrated for example in FIG. 8, the septum **130** is a molded disc of a substantially resilient material that is retained in the port **62** by heat staking. As shown, a portion of a port wall **136** is provided that extends above the septum **130** and surrounds the cavity **132** in which the septum **130** is located. The port wall **136** is heat staked by slightly heating the material of the wall **136** to a temperature below its melting temperature, but sufficiently high to soften the material of the wall. Once the port wall **136** material has been softened, it can be deformed radially inward slightly so as to trap the septum **130** in the cavity **132** of the port **62**. The heat staking procedure can be performed uniformly around the circumference of the port, or at intervals around the wall **136**. The skilled artisan will recognize that alternative methods can also be used for securing the septum within the cavity **132**, such as bonding, welding, etc as described above.

[0052] As shown in FIG. 6, the tubular lower portion **122** of the funnel-shaped section **120** is surrounded by an annular space **138** configured to allow a needle guard **140** to be affixed to the funnel-shaped section **120** (see FIGS. 8 and 9). In the embodiments illustrated in FIGS. 7 and 8, the needle guard **140** comprises a section of tubing of sufficient length and rigidity that the guard **140** will not expose the sharpened needle tip. The needle guard **140** can comprise any suitable material and/or design as desired. For example, in one embodiment, the needle guard **140** comprises a section of vinyl tubing which extends **144** about $\frac{1}{8}$ " to about $\frac{1}{2}$ " beyond the needle tip in the assembled position shown in FIG. 8. In alternative embodiments, the annular space **138** can be omitted and the needle guard **140** can be retained over the needle

66 by some other means, such as by a tighter friction-fit around the needle **66** or by providing a needle guard as part of the packaging for the infusion assembly. In some embodiments, as illustrated in FIGS. 3 and 4, the needle guard **140** can be configured to be attached directly to the introducer cap **64** in order to extend at least a distance **146** of between about $\frac{1}{16}$ " and about $\frac{1}{8}$ " or more beyond the needle tip. In an alternative embodiment, a needle guard can be provided to attach to the barbed feet **94** of the introducer cap **64** after the introducer cap **64** has been removed from the base member **60**.

[0053] If desired, the annular space **138** of the base member **60** can be provided with annular rings **142** to aid in release of the base member from a mold half during an injection molding process. As will be clear to the skilled artisan, it is often desirable that an injection molded part remain temporarily retained in one of the halves of an injection mold until the mold half is moved to a location over a drop bucket, at which time the part can be ejected from the mold by ejector pins. In the absence of the annular rings **142**, an injection molded base member **60** may prematurely fall out of the mold. It should be noted that the base member **60** need not be made by injection molding, and could be made by any number of other suitable processes in which case, the annular rings **142** might be excluded.

[0054] According to one embodiment, an adhesive layer **50** such as that illustrated in FIG. 1 can be secured to the bottom surface of the base member **60**. The adhesive layer **50** is generally configured to allow the base member **60** to adhere to a patient's skin as will be further described below. The adhesive layer **50** is typically provided with a backing layer **150** to protect the adhesive side **152** of the adhesive layer **50** from dirt, dust and other contaminants that may reduce the ability of the adhesive side **152** to securely adhere to a patient's skin and may increase the risk of infection at the injection site. The adhesive layer **50** can be secured to the bottom surface **118** of the base member **60** by any suitable bonding substance or process. For example, the adhesive layer can be adhered to the base member with a glue or other bonding agent. Alternatively the adhesive layer **50** can be bonded to the base member **60** by heat sealing, sonic welding, or any other suitable process. Alternatively, the function of adhering the base member **60** to a patient's skin may be accomplished by other means known to those of skill in the art.

[0055] FIGS. 7-9 illustrate one embodiment of an introducer assembly **30** attached to a base assembly **20**. As shown, the introducer cap **64** is preferably attached to the base member **60** by the engagement of the barbed feet **94** with the rim **96** of the base member **60**. By removably engaging the introducer cap to the base member **60**, the needle **66** is temporarily secured within the cannula **52** to provide a rigid puncturing surface during the process of inserting the cannula **52** into the patient's body. If the introducer cap **64** or needle **66** were not engaged with the base member **60**, then the introducer cap **64** and base member **60** could separate or become misaligned during insertion into the patient, possibly entailing repeated puncturing, and causing unnecessary pain and discomfort to the patient. In the illustrated embodiment, the engagement of the introducer cap **64** and the base member **60** allow these components to be pressed together against the patient, preferably with a single, rapid motion. The cylindrical wall **86** of the port-engaging portion **74** also preferably engages the upper surface **92** of the base member **60**.

[0056] The port-engaging portion 74 of the introducer cap 64 is preferably adapted to surround the port 62 of the base member 60. This provides for a close fit between the introducer cap 64 and the base member. This close fit can aid in preventing the base member from rocking or performing other unwanted movement relative to the introducer cap 64. These same advantages can also be beneficial in the context of the infusion cap 54 as will be further described below. In one embodiment, the inner diameter of the port-engaging portion 74 is about 0.025" to about 0.1" larger than the port 62 of the base member 60. Depending upon the desired application, in alternative embodiments, the inner diameter may be outside of this range.

[0057] With reference to FIGS. 10-14, embodiments of infusion assemblies 40 adapted to be mounted to the base member 60 will now be described. As illustrated, an infusion cap 54 can be configured to attach to a base member 60 in a similar manner to that of the introducer caps 64 discussed above.

[0058] With reference to FIG. 11, one embodiment of the infusion cap 54 is adapted to have a substantially low profile. For example, in some embodiment, the overall height, 's' can be between about 0.300" and about 0.400". In one preferred embodiment, the overall height 's' of the infusion cap 54 is about 0.335".

[0059] In one embodiment, an infusion cap 54 comprises a tube-receiving lumen 160. The tube-receiving lumen 160 is generally configured to accept a section of flexible tubing 162 with an internal lumen 164 as shown in FIG. 11. The tube-receiving lumen 160 can comprise any appropriate transverse cross-section (e.g. as viewed in the axial direction) as desired, but will typically have an axial cross-section corresponding to an axial cross-section of the selected tube 162.

[0060] The tube 162 typically comprises a circular cross-section with a diameter of between about 0.030" and about 0.10". The tube can be any material suitable for use in transmitting fluids in medical applications. Typically the tube will be made of polyethylene or medical grade polyvinyl chloride, although other materials can alternatively be used. The end of the tube 162 that is opposite from the infusion cap can be provided with a connector for joining the tube in fluid communication with the output of a pump or other fluid source. For example, in one embodiment, the opposite end of the tube 162 comprises a Luer lock connector. Other connectors can alternatively be used as will be understood by the skilled artisan in view of the present disclosure.

[0061] The tube 162 can be secured to the infusion cap 54 by any suitable process or mechanism as desired. For example, in the illustrated embodiment, the tube-receiving lumen 160 tapers in diameter from the outer end 166 to the inner end 168. This taper provides for a tight press-fit, allowing the tube to be retained by friction between the inner wall of the tube-receiving lumen 160 and the outer wall of the tube 162. If desired, the tube 162 can be further secured in the tube-receiving lumen by adhesives, sonic welding, heat sealing, or any other suitable process.

[0062] As can be seen in FIGS. 11, 13 and 14, the infusion cap 54 can further comprise a hard cannula 170 with a lumen 172 configured to be in fluid communication with the tube 162. The hard cannula 170 can be integrally molded as part of the infusion cap 54, or it can be subsequently attached by any suitable process. The inner diameter of the hard cannula lumen 172 will typically be selected to allow a sufficient fluid flow rate therethrough. For example, in some embodiments,

the lumen 172 has an internal diameter of between about 0.01" and about 0.03", and in one embodiment, the lumen 172 has an internal diameter of about 0.02". Other diameters outside of these ranges can alternatively be used as desired.

[0063] In the embodiment of FIG. 9, the hard cannula 170 is surrounded by a cylindrical wall 86 to protect the cannula 170 from contact with a user's fingers, or other objects that might contaminate the sterility of the lumen. The hard cannula 170 can be positioned within the cylindrical wall 86 such that the cannula is substantially co-axial with the cylinder wall 86, thereby providing for automatic alignment of the cannula with the exact center of the septum 130 as the cylinder wall 86 engages the port 62. As described with reference to the introducer cap 64 above, the cylindrical wall 86 of the infusion cap 54 is preferably sized and configured to provide a substantially close fit with the port 62 of the base member 60. Providing a close fit advantageously assists in alignment of the hard cannula 170 with the port. The close fit also advantageously causes any forces applied to the infusion cap 54, such as the cap being bumped or the tube 162 being pulled, will be applied at the intersection of the port and the port-engaging portion 74 rather than at the barbed feet (which could cause the infusion cap to become disconnected from the base member 60).

[0064] The hard cannula 170 is generally configured to extend through at least a portion of the septum 130 when the infusion cap 54 and base member 60 are assembled. Thus, the hard cannula 170 is typically dimensioned such that it extends into the port-engaging portion 74 a sufficient distance that when the wall of the port-engaging portion contacts the top surface 92 of the base member 60, the hard cannula 170 will extend through at least a portion of the septum 130. Thus, the dimension 'e' between the outlet 174 of the hard cannula 170 and the bottom edge 182 of the port-engaging portion 74 is preferably less than the dimension 'j' between the top surface 92 of the base member and the bottom of the cavity 132 in the port 62 (see FIG. 5). In alternative embodiments, the dimension 'e' can be equal to or greater than the dimension 'j' if it is desirable that the hard cannula 170 extend only partially through the septum 130, for example. In one preferred embodiment, as illustrated in FIG. 11, the hard cannula 170 extends completely through the septum 130.

[0065] The hard cannula 170 also preferably has sufficient column strength to be inserted through the septum 130 (or other sealing member). Thus, the hard cannula 170 is typically made of a rigid material such as PVC, PET, nylon, stainless steel, or other material suitable for use in medical applications and having sufficient rigidity.

[0066] Similarly to the introducer cap 64, the infusion cap 54 also preferably comprises release grips 100 which can be compressed to release the cap from engagement with the base member 60. In the embodiment illustrated in FIG. 10, the release grips 100 are shown as scalloped convex segments located at about 90° to the wings 98 and barbed feet 94. The release grips 100 can be engaged by a user's fingers to release the cap 54 or 64 from engagement with the base member 60. By pinching the release grips 100, the circular shape of the cap 64 is deformed into an elliptical shape with the barbed feet 94 along the major axis of the ellipse. Thus, pinching the cap 64 at the release grips 100 causes the barbed feet to move radially outwards and away from the edges of the base member 60, thereby releasing the cap 64 from the base member 60. In alternative embodiments, the release grips 100 of the introducer cap 64 and/or the release grips 100 of the infusion cap

54 can comprise smooth convex sections, concave sections, or any of a variety of other shapes.

[0067] Methods of using the infusion set embodiments described above will now be described with continued reference to FIGS. 1-11. In preparation for introduction of the infusion set into a patient, the base assembly **20** and the introducer assembly **30** will typically be assembled as shown in FIGS. 6 and 7. In some embodiments, the base assembly **20** and the introducer assembly **30** can be provided to an end user in a pre-assembled condition. Alternatively, in other embodiments, the parts can be provided separately for assembly by an end user.

[0068] According to one embodiment, a patient will follow these steps in order to introduce the soft cannula **52** and connect the infusion set. The patient can remove the needle guard **140** from the position shown in FIG. 7 by gripping the needle guard **140** and pulling it axially away from the introducer cap **64**, thereby exposing the introducer needle **66** and the soft cannula **52** extending from the underside **118** of the base member **60**.

[0069] The backing layer **150** can then be removed from the adhesive layer **50**, thereby exposing the “sticky” side of the adhesive layer to be adhered to the patient’s skin. While gripping the introducer cap **64** in any desirable manner, or using any suitable tool, the introducer needle **66** and soft cannula **52** are rapidly pressed against and inserted through the patient’s skin and into the patient’s sub-dermal tissue until the adhesive layer **50** contacts the patient’s skin and adheres thereto. The adhesive layer **50** is preferably substantially free from folds or ‘bubbles,’ thereby forming a close, secure attachment.

[0070] Once the needle **66** and soft cannula **52** have been inserted to the desired depth, the introducer cap **64** can be removed from the base member **60** and from the patient. In order to remove the introducer cap **64** from the base member **60**, the release grips **100** can be engaged by a user’s fingers and compressed, thereby deforming the circular cap and causing the barbed feet **94** to be released from engagement with the rim **96** of the base member **60**. In alternative embodiments, the release grips **100** can be compressed by a supplemental tool. In further alternative embodiments, the introducer cap **64** can be configured such that release grips are otherwise manipulated (e.g. twisted, spread apart, etc) in order to remove the introducer cap **64** from the base member. In still further embodiments, the barbed feet **94** may be omitted, as discussed above, or replaced with a suitable alternative structure, thereby allowing a user to merely pull outward on the introducer cap **64** to remove the needle **66**.

[0071] Once the introducer cap **64** is disengaged from the base member **60**, the cap is pulled outward and away from the patient, and the needle **66** is withdrawn from the soft cannula **52**. The soft cannula remains within the patient, extending to a desired depth within the patient’s sub-dermal tissue and held in place by the base member **60** and the adhesive layer **50**. As described above, the septum **130** is generally configured to seal the fluid pathway upon removal of the needle **66**, thereby preventing unwanted flow of fluids or contaminants through the cannula **52**.

[0072] Once the base member **60** and cannula **52** are in place, the infusion cap **54** can be joined to the base member **60**, thereby placing the tube lumen **164** of the infusion tube **162** in fluid communication with the soft cannula **52**. As the user assembles the infusion cap **54** with the base member **60**, the port-engaging portion **74** will surround the port **62**,

thereby aligning the hard cannula **170** of the infusion cap **54** with the slit **134** in the septum **130**. As mentioned previously, the slit can be pre-formed, or a hole can be formed by the needle **66** extending through the septum **130**. The automatic alignment of the hard cannula with the septum slit **134** allows for simple assembly and diminished risk of misalignment. This is particularly advantageous to diabetic patients who often have deteriorating eyesight.

[0073] The infusion cap **54** can be pressed against the base member until the barbed feet **94** “snap” into engagement with the rim **96** of the base member. In one embodiment, the infusion cap **54** can be configured to create an audible “snap” sound when it is pressed onto the base member **60** to enable a user to audibly and/or tactilely verify the complete engagement of the infusion cap **54** on the base member **60**.

[0074] There are many circumstances, such as when the patient bathes, sleeps, plays sports, etc, when it is desirable to disconnect the infusion set without removing the cannula from the patient’s body. When the infusion set is disconnected, the base member is exposed to potential contamination by dust, dirt, bacteria and other contaminants. In addition, the possibility of the base member becoming snagged or pulled by clothing or other objects poses potential problems. As will be clear to the skilled artisan in view of the present disclosure, these issues and others are addressed by the advantageous features of the infusion set embodiments shown and described herein.

[0075] The illustrated infusion set provides for repeated disconnection and reconnection of the infusion cap **54** to and from the base member **60**. The infusion cap **54** can be removed from the base member **60** by engaging and applying a force to the release grips **100** in order to cause the barbed feet **94** to disengage from the rim **96** of the base member **60**. Similarly to the introducer cap **64**, the infusion cap **54** can be engaged by a user’s fingers or any other appropriate tool or device to facilitate removal of the cap from the base member **60**.

[0076] The infusion set embodiments described herein provide a single fluid pathway through the base member by allowing the hard cannula **170** of the infusion cap **54** to extend through the same path through the base member as the needle **66** of the introducer cap **64**. This arrangement advantageously reduces the number of possible points of contamination within the infusion system. When the infusion cap **54** is removed, the septum **130** will seal the fluid pathway to prevent the unwanted egress of blood, and to prevent particles and unwanted fluids from entering the patient through the cannula **52**.

[0077] As mentioned above, the base member **60** and cannula **52** can be left in place within a patient for a few days or longer, and in some circumstances, the base member may be left disconnected from the infusion cap for a period of a few hours or more. The illustrated base member **60** has an advantageously low profile, thereby reducing the likelihood of the base member **60** becoming “snagged” on clothing, towels, or other objects when the patient bathes, dresses, etc. The dome-shaped infusion cap of the above embodiments also advantageously covers the entire base member, thereby protecting the base member from contamination by dirt, dust, germs, or other contaminants. The low profile of the base member **60** and the substantially flat top surface of the septum **130** are also advantageously substantially free from cavities or crevices which might hold contaminants. In addition, the low-profile design diminishes the likelihood that a patient will

inadvertently bump or jostle the infusion set during use, causing discomfort and/or requiring repositioning or replacement of the infusion set.

[0078] Additionally, the position of the septum **130** at a distal surface of the base member relative to the patient's body advantageously provides for simplified cleaning of the septum. As shown and described above, the septum **130** is preferably positioned such that it is flush with the top edge of the port **62**. This provides for easy cleaning of the septum **130** and the port **62**, such as with a cotton swab and alcohol, or any other cleaning products suitable for use in medical applications.

[0079] In other circumstances, it is desirable for the infusion set to have substantial freedom of movement while installed and assembled. For example, once assembled, the embodiment of an infusion set illustrated in FIG. 12 has the advantage that the infusion cap **54** can rotate relative to the base member about an axis perpendicular to the plane of the bottom surface **118** of the base member and extending through the center of the port **62**. Such rotatability advantageously allows a patient to move the tube **162** to the front or the back of the patient's body without inducing a twisting moment on the base member **60**. Thus, an infusion set having an infusion cap that is capable of rotation about a central axis of a base member while maintaining fluid communication between a pump and a patient's body has the distinct advantage of providing the patient with substantial freedom to position the infusion tube **162** at any radial position relative to the base member.

[0080] The end of the tube **162** that is opposite the infusion cap can be connected to a suitable pump or other fluid source either before or after assembly of the infusion cap **54** and base member **60**. In alternative embodiments, an infusion system may comprise additional tubes, connectors, or other components between the soft cannula and a fluid source.

[0081] In alternative embodiments, the base member **60** shown and described herein can be employed to deliver medicants or other therapeutic fluids to a patient without the use of the other members of the infusion set described herein. For

example, a base member such as those described above could be used in combination with a standard hypodermic syringe to deliver a therapeutic fluid to a patient by extending a cannula of the syringe through the septum and injecting the fluid through the soft cannula of the base member and into the patient.

[0082] Although certain embodiments and examples have been described herein, it will be understood by those skilled in the art that many aspects of the methods and devices shown and described in the present disclosure may be differently combined and/or modified to form still further embodiments. For example, any one component of the infusion sets shown and described above can be used alone or with other components without departing from the spirit of the present invention. Additionally, it will be recognized that the methods described herein may be practiced in different sequences, and/or with additional devices as desired. Such alternative embodiments and/or uses of the methods and devices described above and obvious modifications and equivalents thereof are intended to be included within the scope of the present invention. Thus, it is intended that the scope of the present invention should not be limited by the particular embodiments described above, but should be determined only by a fair reading of the claims that follow.

What is claimed is:

1. A base for an infusion set, the base comprising:
 - upper and lower sides;
 - a base cannula extending downwardly from the lower side;
 - a port extending upwardly from the upper side, the port being in fluid communication with the base cannula, the port comprising a septum adapted to seal said port from fluid communication therethrough;
 - a funnel-shaped section disposed within the port and in fluid communication with the base cannula, a funnel-shaped insert disposed within the funnel-shaped section and adapted to protect the surface of the funnel-shaped section from scoring.

* * * * *